

REPLACED SHEETS		SG
☒ Description	: paged 1 to paged 17	
☒ Claim(s)	: paged 18 to paged 19	
☒ Drawing(s)	: paged 1/5 to paged 5/5	
☒ Abstract	: paged - to paged 20	

960111 3-5

1905 copy

3

-1-

DESCRIPTION

The present invention relates to a wear and erosion resistant coating for a substrate having a titanium-containing surface.

Resistance against erosion wear is normally related to the hardness of the wear part. Some articles are subject to solid particle erosion in which particles of various sizes and hardness are propelled at various angles against the surface of the articles. For example, a vehicle or the like (for example a vehicle itself or a large container associated with a road vehicle or part of a railroad train) travelling in the desert during a wind storm will encounter various size solid particles of sand travelling at various velocities hitting the vehicle or the like. If the size of the particles is large and the velocity of the particles is high, the coating on the vehicle or the like could be chipped or pitted. In turbomachines which operate in a dust environment, this solid particle erosion is a severe problem. Recently, physical and chemical vapour deposited coatings, such as titanium nitride coatings and zirconium nitride coatings, have been used to provide a protective layer having good hardness characteristics. These coatings have been found to have good erosion resistance to Al_2O_3 and SiO_2 particles at both high and low impact angles. Although these coatings have high hardness characteristics, they exhibit inherently brittle

This Sheet Has Been Replaced



behaviour and their erosion resistance at normal impact decreases markedly with increasing hardness and particle size of the erodent. It has been observed that dynamic impact of solid particle
5 erodents onto a coated surface of an article can form lateral and/or median cracks around the impact site. Median cracks are responsible for the strength degradation of the material while lateral cracks, which grow from the centre of impact
10 parallel to the substrate surface and then propagate through the coating surface, account for most of the material loss during solid particle impact erosion. The solid particle impact erosion of these coatings at a 90° impact angle is due primarily to brittle
15 fracture. Thin coatings are more susceptible to spalling and exposure of the substrate which may lead to premature failure of the article. When coatings applied by conventional techniques are exposed to particle impact, pinholes and/or lateral
20 spalling pits generally result in the coating. Once the coating material is cracked, additional impact by even relatively small particles will cause furrowing or grooves in the coating material. In a turbomachine, this furrowing can greatly affect the
25 overall performance of the turbomachine.

Based on the elastic-plastic theory, toughness and hardness are the dominant properties controlling the erosion behaviour. Higher hardness is believed to increase erosion resistance at both
30 low and high impingement angles while higher toughness reduces the vulnerability to brittle fracture and markedly increases 90° erosion

This Sheet Has Been Replaced



resistance. An erosion resistant coating needs to be simultaneously hard and tough. However, hardness and toughness are generally in opposition in hard materials. Higher hardness is usually associated with greater brittleness. Multilayer hard compound materials have been found to have simultaneously high hardness and high toughness. The high hardness is an inherent property of hard compounds and the high toughness is attributed to the formation of a coherent or partly coherent interface boundary between two different hard compound layers. For example, it has been found that a TiC/TiB₂ multilayer coating has a better wear resistance than either the TiC or TiB₂ single layer. In cutting tool applications, the multilayer coated tool bits, having a TiC/Al₂O₃/TiN three layer coating, or a two layer coating in which one layer is a nitride, carbide, boride, or silicide of a metal of Group VI of the Periodic Table and the other layer is a nitride or carbide of a metal of Group VI of the Periodic Table, have shown good performance in wear resistance.

In copending application U.S. Serial No. 405,131, a multilayer coating is disclosed which has good wear and erosion resistant characteristics, such multilayer coating comprising alternate lamellas layers of a nitride-containing compound in which at least one layer contains at least 2 atomic percent of nitrogen different than the nitrogen contained in an adjacent layer.

It has now been found possible to provide a substrate having a titanium-containing

This Sheet Has Been Replaced



surface with a top layer of a non-stoichiometric titanium nitride coating that has good wear resistance and/or erosion characteristics to solid particle impact.

5 It has also been found possible to provide a titanium coated substrate with a non-stoichiometric titanium nitride coating in which the atomic percent of nitrogen in the titanium nitride is from 32.5% to 47%.

10 The above and further objects and advantages of this invention will become apparent upon consideration of the following description.

15 According to the present invention there is provided a non-stoichiometric titanium nitride coating for substrates having a non-nitrogen titanium-containing outer surface, in which the atomic percent of nitrogen in the titanium nitride coating is from 32.5% to
20 47%. Preferably, the atomic percent of nitrogen in the non-stoichiometric titanium nitride coating could be from 36% to 44% and most preferably about 40%. A coating containing a layer of titanium nitride in which the nitrogen is less than 32.5 atomic percent
25 has been observed to be extremely difficult to strip by conventional means, while a nitrogen content of greater than 47 atomic percent has been observed to be susceptible to spalling by radial and lateral cracks due to direct impact of particles and has been
30 found to have high residual compressive stress. The coating of the present invention has good wear and corrosion characteristics and should have a crystallize size, measured in the direction perpendicular to (111)

This Sheet Has Been Replaced



diffraction plane, of less than 55 nm, preferably less than 50 nm.

The titanium nitride coating preferably has a microhardness from 2061 to 2695 kilograms force per square millimetre. The titanium nitride coating preferably has a residual compressive stress of 1207 to 2406×10^6 Pa (175 to 349 kilopounds per square inch).

According to the present invention there is also provided a coated article having a coating of the present invention secured to a substrate having a titanium-containing outer surface.

According to a particular embodiment of the present invention there is provided a method for producing a non-stoichiometric titanium nitride coating on a substrate having a titanium-containing surface could comprise the steps:

(a) placing a substrate having a titanium-containing outer surface in a chamber containing a titanium-based target and a nitrogen-containing gas mixture;

(b) evaporating the titanium from the titanium-based target to produce a titanium vapour to react with the nitrogen in the nitrogen-containing gas mixture and adjust the ratio of nitrogen to titanium to form a titanium nitride layer on the substrate that has a nitrogen content from 32.5 atomic percent to 47 atomic percent.

One preferred embodiment for producing a titanium nitride coating on a titanium coated substrate would comprise the steps:

(a) placing a titanium coated substrate having a titanium-containing outer surface in a vapour

This Sheet Has Been Replaced



deposition chamber having an anode and containing a titanium-based cathode along with a nitrogen-containing gas mixture;

(b) applying a voltage across the cathode and anode to establish a current to effect evaporation of the titanium from the titanium-based cathode to produce a titanium vapour to react with the nitrogen in the nitrogen-containing gas mixture and;

(c) adjusting the ratio of nitrogen to titanium to form a titanium nitride layer on the substrate that has a nitrogen content from 32.5 atomic percent to 47 atomic percent.

It is believed that the simultaneous coating of a substrate with a TiN_x based composition and bombardment of the titanium-containing outer surface of the substrate with inert gas ions, such as, for example, argon ions, will produce a low stress and small crystallite for the TiN_x coating of the present invention.

Preferably, the nitrogen-containing gas mixture could be argon-nitrogen; krypton-nitrogen; helium-nitrogen; xenon-nitrogen; neon-nitrogen or the like. the titanium nitride coating of the present invention can be deposited by using conventional physical vapour deposition techniques such as arc processes, dc and rf magnetron sputtering, reactive ion plating and the like.

As used herein, a substrate having a titanium-containing outer surface is a titanium substrate or a substrate coated with titanium or with a non-nitrogen titanium alloy. If the substrate is other than titanium, the titanium-containing outer layer should



preferably be from 0.1 to 6.0 microns thick, and more preferably from 0.2 to 4.0 microns thick.

The thickness of the titanium nitride coating of this invention can vary greatly as for example from 1 to 40 microns thick while for wear applications the preferred thickness of the coating could be from 1 to 15 microns and for erosion applications the coating could be from 8 to 40 microns.

The titanium nitride coating of this invention is ideally suited for coating substrates such as, for example, titanium, titanium coated iron, titanium coated aluminium, titanium coated nickel, titanium coated cobalt, alloys of the base substrate material thereof and the like. In applications using other than a titanium substrate, the substrate should be coated with a non-nitrogen titanium-containing layer prior to depositing the coating of this invention since titanium will effectively provide a better adherence for the coating.

The present invention will now be further described with reference to the following Examples.

Example 1

Titanium nitride coatings were deposited on Ti-6Al-4V substrates using a physical vapour deposition arc evaporation process. Before deposition, the vapour deposition chamber was evacuated to a pressure below 7×10^{-4} Pa and then backfilled with argon to 0.7 Pa. The substrate to be



coated was sputtered to remove surface contaminants. Subsequently, a 250 ampere d.c. arc was activated across a titanium cathode and a chamber which acts as an anode to evaporate Ti from the Ti cathode in an argon environment at an overall pressure about 4 Pa so as to deposit about 1 micron of titanium on the substrate and then the argon was changed to an argon-nitrogen reactive gas mixture. The ionized Ti vapour reacted with N_2 ions and then formed a titanium nitride coating on the substrate. Each coating was formed by adjusting the nitrogen N_2 gas flow rates during the deposition. Specifically the nitrogen gas flow was varied from approximately 80 to 100 standard cubic centimetres per minute (sccm) and the total argon gas flow was maintained at about 250 sccm. The deposition temperature, determined using an optical pyrometer, was between 420°C and 530°C.

The nitrogen content of each sample coating was measured by sputtered mass neutral spectrometry. The neutral atoms of the coating were sputtered from its surface into plasma by ions which were generated from a low pressure r.f. plasma. The neutral atoms were then ionized by energetic electron impact. These ions were subsequently analyzed and detected in a quadrupole mass spectrometer. The measured area was in an 8 mm diameter circle and the total sputtered depth was approximately 5 microns.

The nitrogen content of each sample coating is shown in the Table.

This Sheet Has Been Replaced




TABLE

COMPARISON OF MATERIAL AND STRUCTURAL PROPERTIES BETWEEN
NON-STOICHIOMETRIC AND STOICHIOMETRIC TITANIUM NITRIDE COATINGS

15

Coating	N Content (at.%)	Crystallite Size (nm)		Microhardness (Kgf mm ⁻²)	Residual Compressive Stress (Ksi)	Relative Erosion Resistance		
		D ₁₁₁	D ₂₀₀			90°	20°	
20	I	32.5	18.2	10.9	2286 ± 17	233 ± 17	5.3	0.92
	II	38.6	27.8	16.0	2636 ± 53	195 ± 8	6.5	1.5
	III	39.9	33.8	18.8	2611 ± 84	183 ± 8	7.3	1.6
	IV	46.8	45.4	22.3	2168 ± 46	221 ± 17	4.0	0.91
	V	47.0	50.3	33.0	2122 ± 45	278 ± 22	3.2	1.1
25	VI	48.0	45.4	27.4	2120 ± 51	302 ± 23	2.4	0.91
	VII	49.3	73.8	33.0	2081 ± 60	323 ± 26	1.5	1.1
	VIII	50.0	75.0	41.5	1800 ± 90	450 ± 15	1.0	1.0

This Sheet Has Been Replaced



The crystallite size of each of the sample coatings was determined by the Scherrer formula as follows:

$$D_{hkl} = \frac{K\lambda}{\beta \cos\theta}$$

Where D_{hkl} is the dimension of crystallite in the direction perpendicular to the reflecting plan (hkl), K is the crystallite shape factor which is assumed to be 1 in this case, λ is the wavelength of the X-rays, θ is the glancing angle of incidence, and β is the half-maximum breadth. Typically, the experimentally observed breadth (β) is comprised of β due to the particle size effect and b resulting from the instrumental broadening, $\beta = \beta + b$. The instrumental broadening, b , was determined using TiN powder with particle size greater than several microns. The crystallite size D_{111} and D_{200} were determined and the results are shown in the Table. This data shows that the crystallite size D_{111} and D_{200} increased with increasing nitrogen content. A large increase in crystallite size of both D_{111} and D_{200} occurred at approximately 47 atomic percent of nitrogen. Although not bound by theory, it is believed that the small crystallite size in the coatings with nitrogen content less than 47 atomic percent was probably caused by a continuous formation of nucleation sites resulting from argon ion bombardment during deposition in which the reactants such as Ti and N ions were sufficient to rapidly renucleate new grains at newly formed nucleation sites.



Residual stresses of the sample TiN_x coatings were determined using the standard $\sin^2\psi$ method based on the change in lattice spacings (strain).

The stresses of TiN_x sample coatings were then measured with the assumption of Young's modulus of $279.9 \times 10^6 \text{ kPa}$ ($40.6 \times 10^6 \text{ psi}$) and a poisson ratio of 0.25.

Residual compressive stress was found in all the TiN_x sample coatings and the data are shown in the Table. The magnitude of compressive stress decreased with decreasing N content and reached a minimum at about 39 atomic percent of nitrogen.

The as-coated surface of each of the TiN_x sample coatings was metallographically polished before being subjected to microhardness measurements, using a Vickers hardness tester with a load of 0.1 Kg for 15 seconds. The data obtained is presented in the Table and shows that the microhardness of TiN_x increased with increasing nitrogen content from 2290 kilogram force per square millimetre (Kg/mm^2) at 32.5 atomic percent N to a maximum of 2640 Kg/mm^2 at 38.6 atomic percent N, and then decreased to 1800 Kg/mm^2 at 50 atomic percent N. Based on the data in the Table, the TiN_x coatings with a maximum microhardness exhibited a minimum residual compressive stress. This discovery is in contrast to what has been observed in the art in which the hardness of a coating increases with increasing residual compressive stress. In general, the microhardness of the coating increases with decreasing crystallite size and it is also believed that small crystallite size contributed to high



microhardness of the coating. However, relatively high Ti content in the coating with 32.5 atomic percent of nitrogen, showed an adverse effect on microhardness in spite of small crystallites.

The TiN_x sample coatings were exposed to 50 microns alumina erosion at both 20° and 90° impingement angles at room temperature. Compressed air with a pressure of 290 kPa (42 psig) was used to deliver alumina particles through a 5 mm diameter alumina nozzle. The nozzle-to-specimen distance was maintained at 10 cm. The amount of alumina particles used for 20° and 90° erosion was 1600 g and 400 g, respectively. The relative erosion resistance was calculated by comparing the total weight loss of the non-stoichiometric TiN_x coatings with that of a stoichiometric TiN coating, in which the erosion resistance was assumed to be 1 at both 20° and 90° impact angles. The data obtained is presented in the Table and shows that a maximum erosion resistance at 20° and 90° occurred at about 38 to 40 atomic percent N, which corresponds very well to the region of maximum microhardness.

The present invention will now be further described with reference to, and as illustrated in the accompanying drawings, in which:-

Figure 1 is a plot of residual compressive stress vs. microhardness for the coating of the present invention;

Figure 2 is a plot of erosion resistance vs. the nitrogen content in TiN_x coatings and a plot of residual compressive stress vs. the nitrogen content in TiN_x coatings;



Figure 3 is a plot of erosion resistance vs. the nitrogen content in TiN_x coatings and a plot of crystallite size vs. the nitrogen content in TiN_x coatings;

Figure 4 is a plot of the texture coefficient vs. the nitrogen content in TiN_x coatings; and

Figure 5 is a plot of relative life vs. coating thickness for various TiN_x coatings.

Based on the elastic-plastic theory, toughness and hardness are the dominant properties controlling erosion behavior. Higher hardness is believed to increase erosion resistance at both low and high impact angles; high toughness reduces the vulnerability to brittle fracture and markedly increases high angle erosion resistance. An erosion resistant coating needs to be simultaneously hard and tough. Previous study showed that the erosion resistance of TiN coating to 50 microns alumina

This Sheet Has Been Replaced



particles increases with decreasing residual compressive stress. Higher residual compressive stress, which generally leads to radial and lateral cracks in the coating during particle impacts, suggests lower toughness. In ZrN coatings, it was found that residual compressive stress of the coating increased linearly with increasing microhardness. A plot of residual compressive stress versus microhardness was plotted in Figure 1 for the sample coating from the Tables and the data demonstrates that the residual compressive stress of non-stoichiometric TiN_x coatings decreased linearly with increasing microhardness. This implies that non-stoichiometric TiN_x coatings are simultaneously hard and tough.

Figure 2 shows a combined plot of erosion resistance vs. N content and compressive stress vs. N content. A trend of increase in 90° erosion resistance with decreasing residual compressive stress was clearly indicated. A marked decrease in residual compressive stress of the coating occurred at about 48 atomic percent N. In Figure 3 a combined plot of erosion resistance vs. N content and crystallite size vs. N content shows that the erosion resistance of the coating increased with decreasing crystallite size except the coating containing 32.5 atomic percent N. The coatings which contain 32.5 atomic percent N or less are relatively reactive due to high Ti content and susceptible to burning during solid particle impact. Therefore, in spite of small crystallite size in the coating with 32.5 atomic percent N, the



higher compressive stress compared with that containing 38 to 40 atomic percent N and the burning of the coating during erosion was probably responsible for a significant reduction in erosion resistance.

Figure 4 shows that the texture coefficient is a function of N concentration in the coating. The coating exhibited a $\langle 311 \rangle$ preferred orientation at N content between 35.5 and 41.5 atomic percent, while a $\langle 111 \rangle$ preferred orientation appeared at N content greater than 45 atomic percent. A combination of $\langle 111 \rangle$ and $\langle 311 \rangle$ preferred orientation was obtained at N content between 41.5 and 45 atomic percent; the $\langle 311 \rangle$ and $\langle 200 \rangle$ preferred orientations occurred between 33.5 and 35.5 atomic percent; and the $\langle 200 \rangle$ and $\langle 220 \rangle$ preferred orientations occurred at less than 33.5 atomic percent, respectively.

In summary the data from Example 1 shows:

- a) The crystallite size decreases with decreasing N content. A transition from large to small crystallite occurs at approximately 47 atomic percent nitrogen.
- b) The microhardness of TiN_x coatings increases with decreasing nitrogen content, from 2081 Kg/mm^2 at 49.3 atomic percent nitrogen to 2611 Kg/mm^2 at 39.9 atomic percent nitrogen, and then decreases to 2286 Kg/mm^2 at 32.5 atomic percent nitrogen.
- c) The residual compressive stress of the TiN_x coatings decreases with decreasing nitrogen content, from 323 Ksi at 49.3 atomic percent nitrogen to a minimum of 183 Ksi at 39.9

This Sheet Has Been Replaced



atomic percent nitrogen and then increases to 233 Ksi at 32.5 atomic percent nitrogen.

d) The residual compressive stress of TiN_x coatings decreases linearly with increasing microhardness and the coating containing approximately 40 atomic percent nitrogen exhibits maximum microhardness and minimum residual compressive stress.

e) Erosion resistance of non-stoichiometric TiN_x coatings of this invention to 50 micron alumina particles at both 20° and 90° impact angles is superior to a stoichiometric TiN coating.

f) The non-stoichiometric TiN_x coating of this invention containing approximately 40 atomic percent nitrogen has optimum erosion resistance at both 20° and 90° impact angles.

Example 2

TiN_x coatings on titanium coated samples as in Example 1 containing approximately 40 atomic percent nitrogen, with coating thicknesses varying from 3.5 to 17.5 microns, were subjected to 50 microns alumina particles at 90° impact angle to establish the coating life/thickness relationship. The amount of alumina erodent which is needed to penetrate the coating was determined as a function of coating thickness. A 5 to 15 gram increment of alumina erodent was used for each test. Typically, the erosion scar covers a 2.5 cm diameter area. The area of substrate exposure, approximately 1 cm in diameter, was used as a cursory measure for coating penetration. From the data a plot of relative life



(arbitrary number) vs. thickness was prepared and is shown in Fig. 5.

Under this test condition, a marked increase in coating life (relative) was observed at coating thicknesses greater than 9 μm . The relative coating life to 50 μm Al_2O_3 erodent appeared to have a linear relationship with the coating thickness in the thickness range from 9 microns to 17.5 microns.

=====

This Sheet Has Been Replaced





CLAIMS

1. A non-stoichiometric titanium nitride coating for substrates having good wear and corrosion resistance, in which the substrate has a non-nitrogen, titanium-containing outer surface and on which a titanium nitride coating containing from 32.5 to 47 atomic percent nitrogen is disposed over the titanium-containing outer surface.

2. A coating according to claim 1, wherein the titanium nitride contains from 36 to 44 atomic percent nitrogen.

3. A coating according to claim 2, wherein the titanium nitride contains about 40 atomic percent nitrogen.

4. A coating according to any of claims 1 to 3, wherein the titanium nitride coating has a microhardness from 2061 to 2695 kilograms force per square millimetre.

5. A coating according to any of claims 1 to 4, wherein the titanium nitride coating has a residual compressive stress of 1207 to 2406×10^6 Pa (175 to 349 kilopounds per square inch).

6. A coating according to any of claims 1 to 5, which is from 1 to 40 microns thick.

7. A coating according to claim 6, which is from 1 to 15 microns thick.

8. A coating according to claim 6, which is from 8 to 40 microns.

9. A coated article having a coating as defined in any of claims 1 to 8, secured to a substrate having a titanium-containing outer surface.

10. A coated article according to claim 9, wherein the substrate is selected from titanium,





-19-

titanium alloy, titanium coated iron or iron alloys, titanium coated aluminium or aluminium alloys, titanium coated nickel or nickel alloys and titanium coated cobalt or cobalt alloys.

11. A coated article according to claim 10, wherein the nitrogen content in the titanium nitride coating is from 36 to 44 atomic percent and the substrate is titanium.

12. A coated article according to claim 11, wherein the thickness of the titanium nitride coating is from 1 to 40 microns thick.

This Sheet Has Been Replaced

