

- 1 -

SPECIFICATION

TITLE OF THE INVENTION

PROCESS FOR REFINING METHACRYLIC ACID

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a process for producing highly refined methacrylic acid containing
10 little dibasic acids such as maleic acid and citraconic acid efficiently on an industrial scale from an aqueous methacrylic acid solution obtained by cooling a methacrylic acid-containing reaction gas formed by oxidizing methacrolein, isobutyl aldehyde, t-butanol or isobutyl-
15 ene catalytically in a vapor phase.

2. Description of the Related Art

Methacrylic acid is generally refined by extracting it from an aqueous methacrylic acid solution, which is obtained by cooling and condensing a methacrylic
20 acid-containing gas formed by oxidizing a 4 C compound such as methacrolein, isobutyl aldehyde, t-butanol or isobutylene catalytically in a vapor phase, with an organic solvent, which does not mix with water and hence forms separated phases with the condensed aqueous
25 solution, followed by distillation of the extract. The

organic solvent used for this purpose may include, for example, aliphatic hydrocarbons having 5 to 9 carbon atoms, aromatic hydrocarbons such as benzene and toluene and esters such as methyl methacrylate.

5 The process for producing methacrylic acid by the catalytic oxidation of the above-described 4 C compounds in one or two reaction stages or more is now actually practiced on an industrial scale. However, a variety of side reactions occur simultaneously in the
10 catalytic oxidation reaction and therefore the reaction product gas contains a variety of by-produced impurities in addition to the desired methacrylic acid. The miscellaneous by-produced impurities get mixed partially in the aqueous methacrylic acid solution obtained by
15 cooling and condensing the reaction product gas and in the extract from the aforesaid aqueous solution with the organic solvent. The principal by-produced impurities include acetaldehyde, acetone, acetic acid, acrolein, methacrolein, acrylic acid, maleic acid, citra-
20 conic acid, aromatic aldehydes, aromatic carboxylic acids, heterocyclic compounds and the like.

 Among these by-produced impurities, acetaldehyde, acetone, acetic acid, acrolein and methacrolein, which are lower boiling point components than methacrylic
25 acid, can be separated by distillation, and aromatic

compounds, higher boiling point components, can also be separated by distillation. However, it is difficult to separate by distillation dibasic acids such as maleic acid and citraconic acid transferred to the extract
5 phase along with methacrylic acid during the extraction.

With a view to removing these hardly separable impurities from methacrylic acid, the present inventors have examined a process in which the impurities-containing methacrylic acid extract prior to the distillation is brought into contact with a basic ion-exchange resin, followed by refining of the resultant extract by distillation. Thus, inventions of United State Patent No. 4,879,412 and Japanese Patent Laid-Open No.
10 193740/1989 have been proposed. The present inventors have also studied a process in which the impurities-containing methacrylic acid extract prior to the distillation is brought into contact with a basic amine, followed by refining of the resultant extract by distillation. As a result, an invention of Unitet State
15 Patent No. 5,196,578 has been proposed.

According to the processes proposed by the inventors, it has been proved that impurities including dibasic acids such as maleic acid contained in methacrylic acid are adsorbed or made high boiling point
25

components by bringing the methacrylic acid extract into contact with a basic ion-exchange resin or a basic amine, and the extract thus treated is subjected to the subsequent distillation step to produce methacrylic acid of a high quality.

To solve the aforementioned problems, in processes other than those proposed by the present inventors, for example, in the specification of Japanese Patent Laid-Open No. 152438/1985, there is proposed a process comprising the steps of subjecting an aqueous methacrylic acid solution obtained by cooling and condensing the reaction product gas to an evaporation step such as distillation to remove low boiling point components, extracting methacrylic acid from the resulting solution with an organic solvent that forms an azeotropic composition with water, such as an aromatic hydrocarbon, bringing the extract into contact with an aqueous hydrogensulfite solution to separate the mixture thus obtained into two phases, and subjecting only the oily phase to a distillation and refining step. Further, for example, in the specification of Japanese Patent Laid-Open No. 178842/1985, there is proposed a process comprising the steps of cooling and condensing the reaction product gas to an aqueous methacrylic acid solution, extracting methacrylic acid from the aqueous

solution with an aromatic or aliphatic hydrocarbon solvent, and adding an alkali or an aqueous hydrazine solution to the extract to separate maleic acid and the like as a salt by precipitation.

5 In these conventional processes, however, substances, which do not originally exist in their process solutions, are incorporated so that waste water and wastes, which are unrecoverable to and unreusable in the processes, are evolved therein to render the processes' defective. Therefore, expenses are necessary to
10 treat the waste water and wastes that are unrecoverable to and unreusable in the processes. Consequently, the processes involve an essential problem of deteriorated economical efficiency.

15 Further, a reaction of polymerizing methacrylic acid takes place due to the substances incorporated, giving rise to the problem of equipment being contaminated.

20 SUMMARY OF THE INVENTION

 It is an object of the present invention to provide a process for refining methacrylic acid for the purpose of producing highly refined methacrylic acid at low cost by reducing the amount of impurities including
25 dibasic acids such as maleic acid and citraconic acid.

The present inventors have intensively investigated a process which removes the above-described dibasic acids such as maleic acid and citraconic acid efficiently, does not evolve waste water and wastes
5 which are unrecoverable to the process, and is excellent in economical efficiency. As a result, it has been found that the contents of dibasic acids such as maleic acid and citraconic acid can be decreased to significantly low concentrations by adding a small
10 amount of water, and the added water can be recovered and reused in the process by separating it from the methacrylic acid extract. The present invention has been completed on the basis of this finding.

Thus, the present invention provides a process
15 for refining methacrylic acid comprising the steps of:
oxidizing methacrolein, isobutyl aldehyde, t-butanol or isobutylene catalytically in a vapor phase to form a methacrylic acid-containing reaction gas;
cooling and condensing the reaction gas to an
20 aqueous methacrylic acid solution;
adding to the aqueous solution an organic solvent that forms two liquid phases with water to carry out an extraction operation and thereby to obtain an extract of the methacrylic acid in the organic solvent;
25 bringing the extract into contact with water;

separating the resultant mixture into an organic phase and a water phase; and

distilling the organic phase for refining.

According to the present invention, it is possible to remove dibasic acids such as maleic acid and citraconic acid to a considerably low level prior to the distillation and refining, and thereby provide highly refined methacrylic acid containing little dibasic acids, economically and without increasing the amount of wastes from the process.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will be described in detail hereunder.

When methacrolein, isobutyl aldehyde, t-butanol or isobutylene is oxidized in a vapor phase in one or more stages of reaction using a catalyst for catalytic oxidation composed primarily of molybdenum oxide or a composite oxide thereof, a reaction product gas containing methacrylic acid as a main component can be obtained. The product gas is cooled and condensed to an aqueous methacrylic acid solution and the condensed aqueous solution is extracted with a given organic solvent to obtain a methacrylic acid extract. The organic solvent useful in the practice of the present

invention is a conventionally known organic solvent which does not mix with water to cause phase separation, i.e., forming two liquid phases with water. The exemplary suitable organic solvents include specifically
5 ly aliphatic hydrocarbons having 5 to 9 carbon atoms, aromatic hydrocarbons such as benzene and toluene, and esters such as methyl methacrylate. They may be used alone or as a mixture.

In the present invention, water is added to the
10 methacrylic acid extract, and they are fully mixed and brought into contact with each other to subject the mixture to extraction again. Thus, dibasic acids such as maleic acid and citraconic acid in the extract are transferred to the water phase and thereby separated
15 and removed from the organic phase. The organic phase is sent to a distillation step where methacrylic acid is obtained as the product. The water phase may be preferably reused as a process water by recycling and mixing it to the aqueous methacrylic acid solution
20 obtained by cooling and condensing thus obtained methacrylic acid-containing reaction gas, but it may also be subjected to distillation together with the organic phase or discharged as waste water.

As the water specified by the present invention,
25 it is common to use distilled water or ion-exchanged

water not containing metal salts and the like, but is also possible to use potable water or water with methacrylic acid dissolved.

The amount of the water added is suitably in the
5 range of from 0.01 to 10% by weight, preferably from 0.1 to 5% by weight, relative to the extract.

To add and mix the water with the extract, generally, both liquids are fully brought into contact with each other by mixing in a continuous or batch stirring
10 vessel or in a line mixer and sent to a filter-type or settling-type two-phase separation vessel. Also, it is possible to use a packing-type or spray-type extraction column or an orifice column-type extraction column. Here, the organic phase is preferably fed to the dis-
15 tillation step in the state under which the water phase and the organic phase are completely separated into two phases. The organic phase with water droplets mixed may also be fed to the distillation step.

The time for mixing and contacting the extract
20 with water is suitably from 10 seconds to 1 hour, preferably from 30 seconds to 10 minutes. The contact temperature is not particularly restricted and is commonly in the range of from 0 to 100°C.

After mixing and contact with the water, the
25 extract is allowed to stand to separate the mixture

into two phases. The time required for this operation is suitably from 30 seconds to 2 hours.

In all the operations after obtaining the condensed solution, no particular restrictions are placed on the operation pressures, which are usually atmospheric.

The present invention will be illustrated specifically by the following examples. However, the present invention shall not be limited to or by these examples.

10 Example 1:

Using a molybdenum-base composite oxide catalyst as a former-stage oxidation catalyst and a molybdenum-base heteropoly-acid catalyst as a latter-stage catalyst, isobutylene was oxidized to form a reaction product gas, which was cooled and condensed to an aqueous methacrylic acid solution. Then, low boiling point components such as acetone and methacrolein were removed from the aqueous solution, and methacrylic acid was extracted from the resulting aqueous solution with n-heptane as an extraction solvent to obtain an extract. The extract comprised 18.8% by weight of methacrylic acid, 0.16% by weight of water, 35 ppm by weight of maleic acid, 60 ppm by weight of citraconic acid, a small amount of other impurities, and n-heptane as the rest.

Seventy five grams of the extract was mixed with 1.5 g of distilled water, and the mixture was stirred at 25°C for two minutes and allowed to stand for one minute to clarify the liquid mixture. Then, the supernatant liquid was separated.

The composition of the liquid thus separated was 18.7% by weight of methacrylic acid, 0.17% by weight of water, 2.1 ppm by weight of maleic acid, 16 ppm by weight of citraconic acid and a trace amount of other impurities, the rest being n-heptane. Here, the rate of removal of maleic acid was 94%, while that of citraconic acid was 73.3%.

Phenothiazine (100 ppm by weight) was added as a polymerization inhibitor to the supernatant liquid obtained above, and the mixture was distilled to obtain refined methacrylic acid.

Five grams of the refined liquid was taken in a 10-cc test tube, to which 100 ppm by weight of phenothiazine was added as a polymerization inhibitor. The test tube was tightly sealed with air enclosed and heated to 120°C to carry out a polymer deposition test. As a result, the time for depositing a polymer was found to be 6 hours.

Comparative Example 1:

Refined methacrylic acid was prepared by distill-

ing the extract obtained in Example 1 in the same manner as in Example 1, except that distilled water was not added to and mixed with the extract. Then, a polymer deposition test was carried out for the refined liquid in the same manner as in Example 1. The time for depositing a polymer was found to be 4 hours and 20 minutes.

Example 2:

Three grams of distilled water was added to and mixed with 75 g of the same extract as prepared in Example 1, and the mixture was stirred at 25°C for two minutes and allowed to stand for one minute. Then, the supernatant liquid was separated.

The liquid thus separated was composed of 18.8% by weight of methacrylic acid, 0.18% by weight of water, 1 ppm by weight of maleic acid, 13 ppm by weight of citraconic acid, a trace amount of other impurities, and n-heptane as the rest. Here, the rate of removal of maleic acid was 97%, while that of citraconic acid was 78.3%.

The supernatant liquid obtained above was distilled in the same manner as in Example 1 to obtain a refined liquid, and a polymer deposition test was carried out for the refined liquid in the same manner as in Example 1. It took 7 hours and 40 minutes to

deposit a polymer.

Example 3:

A supernatant liquid was obtained in the same manner as in Example 1, except that the standing time
5 after the addition and mixing of distilled water was changed to 30 seconds.

The liquid so obtained was composed of 18.7% by weight of methacrylic acid, 0.17% by weight of water, 16 ppm by weight of maleic acid, 28 ppm by weight of
10 citraconic acid, a trace amount of other impurities, and n-heptane as the rest. Here, the rate of removal of maleic acid was 51.5%, while that of citraconic acid was 53.5%.

The supernatant liquid obtained above was dis-
15 tilled in the same manner as in Example 1 to obtain a refined liquid, and a polymer deposition test was carried out for the refined liquid in the same manner as in Example 1. It took 5 hours and half to deposit a polymer.

20 Example 4:

Distilled water was added at a rate of 2 kg/hr to an extract fed at a rate of 100 kg/hr, which comprised 19.4% by weight of methacrylic acid, 0.17% by weight of water, 14 ppm by weight of maleic acid, 22 ppm by
25 weight of citraconic acid, a small amount of other

impurities, and n-heptane as the rest. Both liquids were mixed in a static mixer and fed to a continuous extraction vessel operated at 10 kg/cm² gauge, where the organic phase was discharged at the top at a rate of 100 kg/hr and the water phase at the bottom at a rate of 2 kg/hr.

The static mixer employed had an inner diameter of 4 inches and comprised six elements. The extraction vessel was of a filter-type and had a shell diameter of 250 mm and a shell height of 450 mm.

The organic phase obtained was composed of 19.3% by weight of methacrylic acid, 0.15% by weight of water, 0.9 ppm by weight of maleic acid, 3 ppm by weight of citraconic acid, a small amount of other impurities, and n-heptane as the rest. Here, the rate of removal of maleic acid was 93.6%, while that of citraconic acid was 86.4%.

The organic phase obtained above was distilled to obtain a refined liquid, and a polymer deposition test was carried out for the refined liquid in the same manner as in Example 1. The time for depositing a polymer was 8 hours.



THIS SHEET HAS BEEN
REPLACED

What is claimed is:

1 1. A process for refining methacrylic acid
2 comprising the steps of:
3 oxidizing methacrolein, isobutyl aldehyde, t-
4 butanol or isobutylene catalytically in a vapor phase
5 to form a methacrylic acid-containing reaction gas;
6 cooling and condensing the reaction gas to an
7 aqueous methacrylic acid solution;
8 adding to the aqueous solution an organic solvent
9 which forms two liquid phases with water to carry out
10 an extraction operation and thereby to obtain an ex-
11 tract of the methacrylic acid in the organic solvent;
12 bringing the extract into contact with water;
13 separating the resultant mixture into an organic
14 phase and a water phase; and
15 distilling the organic phase for refining.

1 2. The process according to Claim 1, wherein
2 the amount of the water brought into contact with the
3 extract is from 0.01 to 10% by weight relative to the
4 extract.

1 3. The process according to Claim 1, wherein
2 the organic solvent is an aliphatic hydrocarbon having
3 from 5 to 9 carbon atoms, an aromatic hydrocarbon, an

This Sheet Has Been Replaced





- 16 -

THIS SHEET HAS BEEN
REPLACED

4 ester or a mixture thereof.

1 4. The process according to Claim 1, wherein
2 the organic solvent is n-heptane, benzene or toluene.

1 5. The process according to Claim 1, wherein
2 the water phase after being brought into contact with
3 the extract is reused as a process water.

1 6. The process according to Claim 1, wherein
2 the water phase after being brought into contact with
3 the extract is recycled and mixed to the aqueous metha-
4 crylic acid solution obtained by cooling and condensing
5 the obtained methacrylic acid-containing reaction gas.

This Sheet Has Been Replaced

