INFORMATION INTERACTION METHOD, APPARATUS, AND SYSTEM

Technical Field

The present application relates to the field of network information interaction technologies, and in particular, to an information interaction method, apparatus, and system.

Background Art

With the constant development of network science and technology, safe and convenient network payment modes have been continuously popularized. People can already process, by using a terminal device in a network connected state, data information online in real time through a network data processing technology, thereby achieving payment.

However, a terminal device that cannot be connected to a network, for example, a wearable device (such as a smart watch), cannot perform communication interaction with a payment server terminal, and a user is unable to perform information interaction through the terminal device to achieve payment. Alternatively, when in an offline state, a terminal device that can be connected to a network (such as a mobile phone) cannot communicate with the payment server terminal online, and a user is also unable to perform information interaction through such an offline terminal device to achieve payment. To sum up, in either of the above situations, the user is unable to perform information interaction through such an offline terminal device to achieve payment.

Summary of the Invention

An objective of the present application is to provide an information interaction method, apparatus, and system, so that safe and convenient payment can still be achieved when a terminal device is in an offline state.

The present application provides an information interaction method, which includes:

receiving, by a terminal, an authentication factor issued by a first server terminal, the authentication factor carrying an authentication key and account information of a user, and a dynamic time factor, the first server terminal being a server terminal that completes a first service operation after authenticating the terminal when the terminal requests the first service operation;

generating bound authentication information by using the authentication factor and device

information of the terminal, and returning the bound authentication information to the first server terminal, such that the first server terminal performs authorization through the first service operation according to the bound authentication information; and

generating a graphical identifier for completing the first service operation offline according to the authentication factor, the graphical identifier carrying authentication information of the first service operation, the authentication information of the first service operation including the authentication key of the user, device account information, and a dynamic password, the dynamic password being generated according to the dynamic time factor, and the device account information being generated according to the account information of the user and the device information of the terminal.

In another aspect, the present application further provides an information interaction method, which includes:

acquiring, by a second server terminal, authentication information of a first service operation carried in a graphical identifier displayed on a terminal, the authentication information of the first service operation including an authentication key of a user, device account information, and a dynamic password;

generating a first service operation request by using the authentication information of the first service operation and service data, and sending the first service operation request to the first server terminal, such that the first server terminal performs authentication according to the authentication information of the first service operation carried in the first service operation request, and completes the first service operation after the authentication is successful; and

receiving a result of the first service operation returned by the first server terminal.

In further another aspect, the present application further provides an information interaction method, which includes:

receiving, by a first server terminal, a first service operation request sent by a second server terminal, the first service operation request being a request generated by the second server terminal by acquiring authentication information of the first service operation that is carried in a graphical identifier displayed on a terminal and service data, the first service operation request carrying the authentication information of the first service operation and the service data, and the authentication information of the first service operation including an authentication key of a user,

device account information, and a dynamic password; and

performing authentication according to the authentication information carried in the first service operation request, and completing, by the first server terminal, the first service operation when the authentication is successful.

In further another aspect, the present application further provides a terminal, which includes:

a receiving unit configured to receive an authentication factor issued by a first server terminal, the authentication factor carrying an authentication key and account information of a user, and a dynamic time factor, the first server terminal being a server terminal that completes a first service operation after authenticating the terminal when the terminal requests the first service operation;

a binding unit configured to generate bound authentication information by using the authentication factor received by the receiving unit and device information of the terminal;

a sending unit configured to return the bound authentication information generated by the binding unit to the first server terminal, such that the first server terminal performs authorization through the first service operation according to the bound authentication information; and

a processing unit configured to generate a graphical identifier for completing the first service operation offline according to the authentication factor received by the receiving unit, the graphical identifier carrying authentication information of the first service operation, the authentication information of the first service operation including the authentication key of the user, device account information, and a dynamic password, the dynamic password being generated according to the dynamic time factor, and the device account information being generated according to the account information of the user and the device information of the terminal.

In further another aspect, the present application further provides a server terminal, which includes:

an acquisition unit configured to acquire authentication information of a first service operation carried in a graphical identifier displayed on a terminal, the authentication information of the first service operation including an authentication key of a user, device account information, and a dynamic password;

a processing unit configured to generate a first service operation request by using the authentication information of the first service operation acquired by the acquisition unit and service data;

a sending unit configured to send the first service operation request generated by the processing unit to the first server terminal, such that the first server terminal performs authentication according to the authentication information of the first service operation carried in the first service operation request, and completes the first service operation after the authentication is successful; and

a receiving unit configured to receive a result of the first service operation returned by the first server terminal.

In further another aspect, the present application further provides a server terminal, which includes:

a receiving unit configured to receive a first service operation request sent by a second server terminal, the first service operation request being a request generated by the second server terminal by acquiring authentication information of the first service operation that is carried in a graphical identifier displayed on a terminal and service data, the first service operation request carrying the authentication information of the first service operation and the service data, and the authentication information of the first service operation including an authentication key of a user, device account information, and a dynamic password; and

a processing unit configured to perform authentication according to the authentication information of the first service operation carried in the first service operation request received by the receiving unit, wherein the first server terminal completes the first service operation when the authentication is successful.

In further another aspect, the present application further provides an electronic device, which includes:

a display;

a processor; and

a memory configured to store an authentication factor issued by a first server terminal and a

program of generating a graphical identifier for completing a first service operation offline according to the authentication factor, wherein when the program is executed by the processor, the graphical identifier for completing the first service operation offline is displayed in a display area of the display, the graphical identifier carrying authentication information of the first service operation, the authentication information of the first service operation including an authentication key of a user, device account information, and a dynamic password, the dynamic password being generated according to the dynamic time factor, and the device account information being generated according to account information of the user and device information of the terminal.

In further another aspect, the present application further provides an information interaction system, which includes: a terminal, a first server terminal, and a second server terminal;

the terminal displays, in an offline state, a graphical identifier for completing a first service operation, the graphical identifier carrying authentication information of the first service operation, and the authentication information of the first service operation including an authentication key of a user, device account information, and a dynamic password;

the second server terminal acquires the authentication information of the first service operation carried in the graphical identifier;

the second server terminal generates a first service operation request by using the authentication information of the first service operation and service data, and sends the first service operation request to the first server terminal; and

the first server terminal performs authentication according to the authentication information of the first service operation carried in the first service operation request, and the first server terminal completes the first service operation when the authentication is successful.

In the information interaction method, apparatus, and system provided in the embodiments of the present application, a dynamic graphical identifier for an offline service operation is generated through bound authentication information and a dynamic time factor, a terminal in an offline state may perform information interaction by using the graphical identifier, to achieve safe payment, or a terminal device that cannot be connected to a network can also perform information interaction by using the graphical identifier to achieve safe payment. The present application can achieve safe and convenient payment when the terminal device is in an offline state.

Brief Description of the Drawings

To describe the technical solutions in the embodiments of the present invention more clearly, the following briefly introduces the accompanying drawings required for describing the embodiments. Apparently, the accompanying drawings in the following description show merely some embodiments of the present application, and a person of ordinary skill in the art can still derive other drawings from these accompanying drawings without creative efforts.

FIG. 1 is a schematic structural diagram of an information interaction system according to an embodiment of the present application;

FIG. 2 is a schematic structural diagram of another information interaction system according to an embodiment of the present application;

FIG. 3a is a flowchart of an information interaction method on a terminal side according to an embodiment of the present application;

FIG. 3b is a method flowchart of the terminal side during offline payment according to an embodiment of the present application;

FIG. 4 is a flowchart of an information interaction method on a second server terminal side according to an embodiment of the present application;

FIG. 5a is a flowchart of an information interaction method on a first server terminal side according to an embodiment of the present application;

FIG. 5b is a method flowchart of the first server terminal side during offline payment authorization according to an embodiment of the present application;

FIG. 5c is a method flowchart of another first server terminal side during offline payment authorization according to an embodiment of the present application;

FIG. 6 is an interaction diagram of an information interaction method according to an embodiment of the present application;

FIG. 7 is an interaction diagram during a (mobile phone) offline payment authorization according to an embodiment of the present application;

FIG. 8 is an interaction diagram during another (smart watch) offline payment authorization according to an embodiment of the present application;

FIG. 9 is a schematic structural diagram of a terminal according to an embodiment of the present application;

FIG. 10 is a schematic structural diagram of a second server terminal according to an embodiment of the present application;

FIG. 11 is a schematic structural diagram of a first server terminal according to an embodiment of the present application; and

FIG. 12 is a schematic structural diagram of composition of an electronic device according to an embodiment of the present application.

Detailed Description

To make the objectives, features, and advantages of the present application more apparent and comprehensible, the technical solutions in the embodiments of the present application will be described below with reference to the drawings in the embodiments of the present application. Apparently, the described embodiments are merely some of rather than all of the embodiments of the present application. Based on the embodiments in the present application, all other embodiments obtained by those of ordinary skill in the art without creative efforts fall within the protection scope of the present application.

The information interaction method and apparatus provided in the embodiments of the present application are applicable to all types of intelligent mobile terminal devices, for example, a smart mobile phone, a tablet computer, and other terminal devices, particularly applicable to smart wearable devices that do not have a network connection function, for example, a smart watch, a smart bracelet, and other devices.

FIG. 1 is a schematic structural diagram of an information interaction system according to an embodiment of the present application. In FIG. 1, a terminal 1, a merchant server terminal 2 (a second server terminal), and a payment server terminal 3 (a first server terminal) are shown. The terminal 1 in the figure is a terminal having a network connection function, for example, a smart mobile phone, a tablet computer or the like, and the terminal 1 may have a network connection with the payment server terminal 3. The dashed line in the figure indicates that, in the scenario of

actual use, the terminal 1 fails to establish a network connection to the payment server terminal 3. When in an online state, the terminal 1 may establish a network connection to the payment server terminal 3, and the terminal 1 requests the payment server terminal 3 to perform offline payment authorization. After authorization verification, the payment server terminal 3 issues an authentication factor to the terminal 1. In the scenario of actual use, the terminal 1 is in an offline state, and displays, on the screen, a graphical identifier which carries payment authentication information and is generated according to the authentication factor issued by the payment server terminal 3. The merchant server terminal 2 acquires payment authentication information by scanning the graphical identifier, and generates a payment request from the payment authentication information and order information and sends the payment request to the payment server terminal 3. The payment server terminal 3 verifies the payment authentication information, and when the verification is successful, the payment server terminal 3 performs payment.

Wherein, the merchant server terminal 2 includes a foreground code-scanning end 21 and a back-end server terminal 22. The foreground code-scanning end 21 is mainly installed with a code scanning gun, which scans the graphical identifier displayed on the terminal 1, and transmits the graphical identifier to the back-end server terminal 22. The back-end server terminal 22 mainly checks parameters of the foreground code-scanning end 21, and extracts to obtain the payment authentication information in the graphical identifier. After preprocessing order parameters of a merchant, the back-end server terminal 22 submits an order creation and payment request to the payment server terminal 3.

FIG. 2 is a schematic structural diagram of another information interaction system according to an embodiment of the present application. Difference with FIG. 1 lies in that, the terminal 1 in FIG. 2 is a terminal having no network connection function, for example, a smart watch, a smart bracelet, and other wearable devices; the terminal 1 cannot establish a network connection to the payment server terminal 3, but the terminal 1 can establish a connection to a second terminal 4 having the network connection function through other communication modules (such as Bluetooth), and acquire, through the second terminal 4, the authentication factor issued by the payment server terminal 3. The dashed line in the figure indicates that after the offline payment authorization, in the scenario of actual use, the second terminal 4 having the network connection function may not be necessary. Hereinafter, a specific information interaction process is introduced.

FIG. 3a is a flowchart of an information interaction method on a terminal side according to

an embodiment of the present application. As shown in FIG. 3a, the information interaction method of the embodiment of the present application includes:

S101. A terminal receives an authentication factor issued by a first server terminal.

The authentication factor carries an authentication key and account information of a user, and a dynamic time factor.

Wherein, a first service operation includes network exchange operations for virtual resources, such as payment amount and voucher write-off.

The first server terminal is a server terminal that completes the first service operation after authenticating the terminal when the terminal requests the first service operation.

For illustration purposes, the present application takes payment as an example of the first service operation, offline payment as an example of the offline first service operation, a payment request as an example of the first service operation request, a payment server terminal as an example of the first server terminal, and a merchant server terminal as an example of the second server terminal for illustration, and network exchange operations for other virtual resources are similar to the above.

When in an online state, the terminal establishes a network connection to the first server terminal, and requests offline payment authentication from the first server terminal. The first server terminal issues the authentication factor to the terminal after the authentication verification is successful.

The following steps may be specifically included: sending, by the terminal, an account identity verification request to the first server terminal; receiving a verification result sent by the first server terminal after identity verification is successful; sending a verification request for offline payment authorization to the first server terminal; and receiving the authentication factor issued by the first server terminal after authorization verification is successful.

S102. Bound authentication information is generated by using the authentication factor and device information of the terminal, and the bound authentication information is returned to the first server terminal, such that the first server terminal performs authorization through the first service operation according to the bound authentication information.

In order to achieve safe and convenient payment in an offline state, the terminal, when in an online state, needs to request the first server terminal to perform authentication verification on binding of the device information and the authentication factor issued by the first server terminal, to be authorized during offline payment.

S103. A graphical identifier for completing the first service operation offline is generated according to the authentication factor, the graphical identifier carrying authentication information of the first service operation.

The authentication information of the first service operation, i.e., payment authentication information, includes the authentication key of the user, device account information, and a dynamic password, the dynamic password is generated according to the dynamic time factor, and the device account information is generated according to the account information of the user and the device information of the terminal. The graphical identifier is a QR code or a bar code.

Wherein, the dynamic password remains unchanged in a same time window, and in a next time window, the dynamic password is regenerated according to the dynamic time factor, to change dynamically. This can ensure the safety of the payment authentication information, thereby achieving the purpose of anti-counterfeiting.

The dynamic password is specifically obtained through calculation by using the authentication key of the user, the dynamic time factor, the device account information, and a preset password length according to a one-time password calculating method.

If the displaying mode of the graphical identification is a QR code, it may carry a large amount of information, thereby increasing the preset password length of the one-time password, and enhancing the safety.

A terminal in an offline state, when needing to perform payment, generates a graphical identifier for offline payment, which is scanned by a merchant end to acquire payment authentication information carried in the graphical identifier, to complete offline payment through the second server terminal.

Specifically, as shown in FIG. 3b, S103 may include the following steps:

S1031. A display instruction for displaying the graphical identifier for offline payment is received.

S1032. The graphical identifier for offline payment is generated according to the authentication factor.

S1033. The terminal displays the graphical identifier, so as to perform payment in an offline state by using the graphical identifier.

The displaying mode of the graphical identifier includes one or a combination of: a bar code and a QR code.

Optionally, after the terminal displays the graphical identifier, the method further includes: S1034, in which the displaying mode of the graphical identifier is switched when a switch instruction for the displaying mode of the graphical identifier is received.

When the switch instruction for the displaying mode of the graphical identifier is received, if the current displaying mode of the graphical identifier is a QR code, the displaying mode is switched to a bar code; on the contrary, if the current displaying mode of the graphical identifier is a bar code, the displaying mode is switched to a QR code.

A terminal (such as a smart watch) that cannot directly establish a network connection to the first server terminal may receive, through a second terminal (such as a smart mobile phone) that can establish a network connection to the first server terminal, the authentication factor issued by the first server terminal; and return the bound authentication information to the first server terminal through the second terminal.

The following steps are specifically included: sending, by a second terminal in an online state, an account identity verification request to the first server terminal; receiving, by the second terminal, a verification result sent by the first server terminal after identity verification is successful; sending, by the second terminal in an online state, a verification request for offline payment authorization to the first server terminal; and receiving, by the second terminal, an authentication factor issued by the first server terminal after authorization verification is successful.

After acquiring the authentication factor, the second terminal sends the authentication factor to the terminal. Likewise, after acquiring the authentication factor, the terminal binds it with the device information of the terminal, and sends bound authentication information through the second terminal, such that the first server terminal performs authorization through the payment of the terminal according to the bound authentication information, thereby achieving the offline

payment of the terminal.

Specifically, a management program of the terminal is installed on the second terminal. For example, a management application (management APP) of a smart watch is installed on a smart mobile phone, the APP in the mobile phone integrates login, payment authentication, and other functions of the mobile phone, such as payment account login check, and through the APP, the mobile phone can achieve functions such as Bluetooth communication with the watch, sending authentication parameters (the authentication factor) to the watch, and processing safe communication with the first server terminal and the watch. The watch completes safe communication with the mobile phone, stores and updates a generation parameter of payment authentication information, further generates payment authentication information according to the generation parameter of the payment authentication information, and displays the payment authentication information in the form of a QR code or a bar code.

FIG. 4 is a flowchart of an information interaction method on a second server terminal side according to an embodiment of the present application. As shown in FIG. 4, the information interaction method of the embodiment of the present application includes:

S201. A second server terminal acquires payment authentication information carried in a graphical identifier displayed on a terminal.

The payment authentication information includes an authentication key, device account information, and a dynamic password.

The second server terminal includes a foreground code-scanning end and a back-end server terminal. The foreground code-scanning end is mainly installed with a code scanning gun, which scans the graphical identifier displayed in the form of a QR code or a bar code on the terminal, and transmits the graphical identifier to the back-end server terminal. The back-end server terminal mainly checks parameters of the foreground code-scanning end, and extracts to obtain payment authentication information in the graphical identifier.

S202. A payment request is generated by using the payment authentication information and service data, and sent to the first server terminal, such that the first server terminal performs payment authentication according to the payment authentication information carried in the payment request, and performs payment when the payment authentication is successful.

The back-end server terminal of the second server terminal preprocesses the service data

(order parameters of a merchant), generates an order and a payment request from the payment authentication information and the service data, and sends the order and the payment request to the first server terminal.

S203. A payment result returned by the first server terminal is received.

After the first server terminal completes payment authentication verification and performs payment, the second server terminal receives a payment result returned by the first server terminal.

FIG. 5a is a flowchart of an information interaction method on a first server terminal side according to an embodiment of the present application. As shown in FIG. 5a, the information interaction method of the embodiment of the present application includes:

S301. A first server terminal receives a payment request sent by a second server terminal, the payment request carrying payment authentication information and service data.

The payment authentication information includes an authentication key, device account information, and a dynamic password.

When a terminal is in an offline state, the first server terminal receives the payment request sent by the second server terminal, the request carrying payment authentication information of the terminal.

S302. Payment authentication is performed according to the payment authentication information carried in the payment request, and the first server terminal performs payment when the payment authentication is successful.

Specifically, the step of performing payment authentication according to the payment authentication information carried in the payment request specifically includes: checking whether a binding relationship between the device account information and the authentication key that are carried in the payment authentication information is correct, and checking whether the dynamic password is valid according to the dynamic time factor in the authentication factor; and if yes, the payment authentication is successful.

Before S301 of receiving a payment request sent by a second server terminal, the method further includes:

performing, by the first server terminal, online account binding on the terminal.

When in an online state, the terminal first needs to perform online account binding with the first server terminal.

As shown in FIG. 5b, the step of performing, by the first server terminal, online account binding on the terminal specifically includes:

S401. The first server terminal receives an account identity verification request sent by the terminal.

The account identity verification request carries account information of a user.

S402. It is judged whether the account identity verification request passes verification, and a result of successful verification is sent to the terminal if the verification is successful.

S403. A verification request for offline payment authorization verification sent by the terminal is received.

S404. It is judged whether verification on the verification request is successful, if the verification is successful, an authentication key of the user is generated, and a dynamic time factor of the first server terminal is calculated.

S405. An authentication factor is generated by using the authentication key, the dynamic time factor, and the account information of the user.

S406. The authentication factor is issued to the terminal.

S407. Bound authentication information submitted by the terminal is received, the bound authentication information being generated by binding the authentication factor and the device account information.

S408. Authorization verification is performed on the bound authentication information, and the offline payment authorization verification is completed when authorization is successful.

Optionally, after S404 of generating an authentication key of the user, the method further includes: generating a compressed string from the authentication key and the account information of the user, the compressed string having a one-to-one mapping relationship with the

authentication key and the account information of the user. In this way, storage space can be saved, thus avoiding the problem that excessively long identification information of the device account cannot be displayed in a limited password length. When the payment authentication information is received, the one-to-one corresponding authentication key and account information of the user can also be found through the compressed string.

In S405, the authentication factor is generated by using the authentication key, the compressed string, and the dynamic time factor. Specifically, if SN represents the authentication factor, key represents the authentication key of the user, Seq represents the compressed string of the device account information, UserId represents the account identification information, Did represents device identification information, timestamp represents the dynamic time factor, N represents a preset password length, Zip represents the one-to-one mapping relationship, OTP represents the dynamic password, and Tag represents an authentication information tag, the authentication factor may be obtained by using the following equations:

Seq = Zip (UserId, Did)

OTP = HOTP (Key, Tag + Seq + timestamp, N)

SN = Tag + Seq + OTP

It can be seen that, through Seq = Zip(UserId, Did), the device identification information and the account identification information are first compressed into the compressed string Seq of the device account information, the dynamic password OTP is then obtained through calculation according to a Hash Message Authentication Code (HMAC) based One-Time Password (HOTP) algorithm, and the authentication factor SN is obtained through a combination of the authentication information tag Tag, the compressed string Seq, and the dynamic password OTP.

A terminal that cannot directly establish a network connection to the first server terminal performs online account binding through a second terminal that can establish a network connection to the first server terminal. As shown in FIG. 5c, the step of performing, by the first server terminal, online account binding on the terminal, which is similar to FIG. 5b, specifically includes:

S501. The first server terminal receives an account identity verification request sent by the second terminal.

The account identity verification request carries account information of a user.

S502. It is judged whether the account identity verification request passes verification, and a result of successful verification is sent to the second terminal if the verification is successful.

S503. A verification request for offline payment authorization verification sent by the second terminal is received.

S504. It is judged whether verification on the verification request is successful, if the verification is successful, an authentication key of the user is generated, and a dynamic time factor of the first server terminal is calculated.

S505. An authentication factor is generated by using the authentication key, the dynamic time factor, and the account information of the user.

S506. The authentication factor is issued to the second terminal.

S507. Bound authentication information that is returned by the terminal and submitted by the second terminal is received, the bound authentication information being generated by binding the authentication factor and device account information.

S508. Authorization verification is performed on the bound authentication information, and the offline payment authorization verification is completed when authorization is successful.

After receiving a result of successful authorization of the first server terminal, the second terminal sends the result to the terminal.

FIG. 6 is an interaction diagram of an information interaction method according to an embodiment of the present application; as shown in FIG. 6, the method includes:

S601. A terminal receives a display instruction for displaying a graphical identifier, and switches to a presentation interface of the graphical identifier.

After a user determines the content and amount of an order with a merchant, the user operates the terminal to display the graphical identifier for offline payment. The terminal receives the display instruction of the user, and switches to the presentation interface of the graphical identifier.

S602. The terminal generates payment authentication information according to an authentication factor.

The payment authentication information may be payment authentication information presented in the form of a QR code, and may also be payment authentication information presented in the form of a bar code.

S603. The terminal presents the graphical identifier according to the interface and a type of a code scanning gun, for the use of code scanning.

The terminal, under an operation instruction of the user, presents the graphical identifier according to a required presentation mode.

S604. A foreground code-scanning end of a second server terminal acquires the payment authentication information.

S605. The foreground code-scanning end performs local data processing on order information.

S606. The foreground code-scanning end generates a payment request of the foreground code-scanning end from the order information and the payment authentication information and sends the payment request to a back-end server terminal of the second server terminal, such that the back-end server terminal checks the payment request of the foreground code-scanning end.

S607. The back-end server terminal extracts the payment authentication information and order service information, generates a payment request, and sends the payment request to the first server terminal.

S608. The first server terminal extracts, from the payment request, the payment authentication information and merchant information in the order service information.

S609. The first server terminal authenticates the payment authentication information.

S610. The first server terminal performs payment when the authentication is successful.

S611. The first server terminal returns a payment result to the second server terminal.

S612. Merchant staff confirms the payment result.

In this way, the user completes the payment, and the merchant delivers a commodity.

The terminal in FIG. 6 is a terminal on which online account binding has been performed. Hereinafter, an interaction process during online account binding is introduced through FIG. 7 and FIG. 8. Wherein, the terminal in FIG. 7 is a terminal that can directly establish a connection to the first server terminal, and the terminal in FIG. 8 is a terminal that cannot directly establish a connection to the first server terminal. In order to give a more detailed illustration on the solution, the terminal in FIG. 7 is a mobile phone, the terminal in FIG. 8 is a watch, and the second terminal is a mobile phone.

FIG. 7 is an interaction diagram during a (mobile phone) offline payment authorization according to an embodiment of the present application; as shown in FIG. 7, the following steps are included:

S701. A terminal, when in an online state, sends an account identity verification request to a first server terminal.

The account identity verification request carries account information of a user.

S702. The first server terminal judges whether the account identity verification request passes verification, and a result of successful verification is sent to the terminal if the verification is successful; otherwise, the process ends with failure.

S703. The terminal sends a verification request for offline payment authorization to the first server terminal.

S704. The first server terminal judges whether verification on the verification request is successful, and the process proceeds to S705 if the verification is successful; otherwise, the process ends with failure.

S705. The first server terminal generates an authentication key of the user.

S706. The first server terminal generates a compressed string from the authentication key and the account information.

S707. The first server terminal calculates a dynamic time factor of the first server terminal.

S708. The first server terminal generates an authentication factor by using the authentication

key, the dynamic time factor, and the account information of the user.

S709. The first server terminal performs communication encryption processing on the authentication factor.

S710. The first server terminal returns the authentication factor to the terminal.

S711. The terminal generates bound authentication information by using the authentication factor and device information of the terminal after receiving the authentication factor that is sent by the first server terminal after the authorization verification is successful, and submits the bound authentication information to the first server terminal.

S712. The first server terminal parses the bound authentication information, and checks whether the authorization is successful according to the account, the authentication key, and the dynamic time factor, and if yes, the process proceeds to S713; otherwise, the process ends with failure.

S713. The first server terminal performs payment when the payment authorization is successful.

FIG. 8 is an interaction diagram during another (smart watch) offline payment authorization according to an embodiment of the present application; as shown in FIG. 8, the following steps are included:

S801. A second terminal, when in an online state, sends an account identity verification request to a first server terminal.

The account identity verification request carries account information of a user.

S802. The first server terminal judges whether the account identity verification request passes verification, and a result of successful verification is sent to the second terminal if the verification is successful; otherwise, the process ends with failure.

S803. The second terminal sends a verification request for offline payment authorization to the first server terminal.

S804. The first server terminal judges whether verification on the verification request is successful, and the process proceeds to S805 if the verification is successful; otherwise, the

process ends with failure.

S805. The first server terminal generates an authentication key of the user.

S806. The first server terminal calculates a dynamic time factor of the first server terminal.

S807. The first server terminal generates an authentication factor by using the authentication key, the dynamic time factor, and the account information of the user.

S808. The first server terminal performs communication encryption processing on the authentication factor.

S809. The first server terminal returns the authentication factor to the second terminal, and the second terminal parses to obtain the authentication factor.

S810. The second terminal writes the authentication factor into a terminal (watch), and the terminal receives the authentication factor.

S811. The terminal stores the authentication factor in an encrypted manner.

S812. The terminal generates bound authentication information by using the authentication factor and device information of the terminal.

S813. The terminal sends the bound authentication information to the second terminal.

S814. The second terminal submits the bound authentication information of a payment account to the first server terminal.

S815. The first server terminal parses the bound authentication information, and checks whether the authorization is successful according to the account, the authentication key, and the dynamic time factor, and if yes, the process proceeds to S816; otherwise, the process ends with failure.

S816. The first server terminal performs payment when the payment authorization is successful.

In the information interaction method provided in the embodiments of the present application, a dynamic graphical identifier for offline payment is generated through bound payment authentication information and dynamic time factor, such that a terminal device in an

offline state can also perform safe payment by using the graphical identifier, thereby achieving safe and convenient payment. In the present application, since the graphical identifier (a bar code/a QR code) carries information about an account, a device, a dynamic time factor timestamp, and an authentication key, a first server terminal may check the validity of a One-Time Password according to a binding relationship among the account, the device, and the authentication key, as well as a HOTP signature result, to determine whether to complete the payment check, thereby achieving safe and convenient offline payment.

Hereinabove is a detailed description on the information interaction method provided in the embodiments of the present application, the information interaction apparatus provided by the present application will be described in detail below.

FIG. 9 is a schematic structural diagram of a terminal according to an embodiment of the present application; as shown in FIG. 9, the terminal in the present application includes: a receiving unit 901, a binding unit 902, a sending unit 903, and a processing unit 904.

The receiving unit 901 is configured to receive an authentication factor issued by a first server terminal.

The authentication factor carries an authentication key and account information of a user, and a dynamic time factor.

The binding unit 902 is configured to generate bound authentication information by using the authentication factor received by the receiving unit 901 and device information of the terminal.

The sending unit 903 is configured to return the bound authentication information generated by the binding unit 902 to the first server terminal, such that the first server terminal performs authorization through payment according to the bound authentication information.

The processing unit 904 is configured to generate a graphical identifier for offline payment according to the authentication factor received by the receiving unit 901, the graphical identifier carrying payment authentication information.

The payment authentication information includes the authentication key of the user, device account information, and a dynamic password, the dynamic password being generated according to the dynamic time factor, and the device account information being generated according to the

account information of the user and the device information of the terminal.

Optionally, before the processing unit 904 generates the graphical identifier, the receiving unit 901 is further configured to receive a display instruction for displaying the graphical identifier. The processing unit 904, after the receiving unit 901 receives the display instruction, is configured to generate the graphical identifier for offline payment according to the authentication factor.

The terminal further includes: a displaying unit (not shown) configured to display the graphical identifier generated by the processing unit 904, such that the terminal performs payment in an offline state by using the graphical identifier.

The displaying mode of the graphical identifier displayed by the displaying unit includes one or a combination of: a bar code and a QR code.

The receiving unit 901 is further configured to receive a switch instruction for the displaying mode of the graphical identifier, and the processing unit 904 is configured to switch the displaying mode of the graphical identifier displayed by the displaying unit when the receiving unit 901 receives the switch instruction.

Optionally, the receiving unit 901 is configured to receive, through a second terminal, the authentication factor issued by the first server terminal; and the sending unit 903 is configured to return the bound authentication information to the first server terminal through the second terminal.

Optionally, the sending unit 903 is further configured to send an account identity verification request to the first server terminal; the receiving unit 901 is configured to receive payment authorization sent by the first server terminal after identity verification is successful; the sending unit 903 is configured to send a verification request for offline payment authorization to the first server terminal; and the receiving unit 901 is configured to receive the authentication factor issued by the first server terminal after authorization verification is successful.

The functions of the above units may be corresponding to the processing steps of the above information interaction method described in FIGs. 3a-3b in detail. Details are not described herein again.

FIG. 10 is a schematic structural diagram of a server terminal according to an embodiment

of the present application; as shown in FIG. 10, the server terminal includes: an acquisition unit 1001, a processing unit 1002, a sending unit 1003, and a receiving unit 1004.

The acquisition unit 1001 is configured to acquire payment authentication information carried in a graphical identifier displayed on a terminal.

The payment authentication information includes an authentication key, device account information, and a dynamic password.

The processing unit 1002 is configured to generate a payment request by using the payment authentication information acquired by the acquisition unit 1001 and service data.

The sending unit 1003 is configured to send the payment request generated by the processing unit 1002 to the first server terminal, such that the first server terminal performs payment authentication according to the payment authentication information carried in the payment request, and performs payment when the payment authentication is successful.

The receiving unit 1004 is configured to receive a payment result returned by the first server terminal 3.

FIG. 11 is a schematic structural diagram of a server terminal according to an embodiment of the present application; as shown in FIG. 11, the server terminal includes: a receiving unit 1101, a processing unit 1102, and a sending unit 1103.

The receiving unit 1101 is configured to receive a payment request sent by a second server terminal, the payment request carrying payment authentication information and service data.

The payment authentication information includes an authentication key, device account information, and a dynamic password.

The processing unit 1102 is configured to perform payment authentication according to the payment authentication information carried in the payment request received by the receiving unit 1101, and the server terminal performs payment when the payment authentication is successful.

Optionally, the processing unit 1102 is further configured to perform account binding on the terminal.

First situation:

The receiving unit 1101 is configured to receive an account identity verification request sent by the terminal, the account identity verification request carrying account information of the user.

The processing unit 1102 is configured to judge whether the account identity verification request passes verification, and use the sending unit 1103 to send a result of successful verification to the terminal if the verification is successful.

The receiving unit 1101 is configured to receive a verification request for offline payment authorization verification sent by the terminal.

The processing unit 1102 is configured to judge whether verification on the verification request is successful, if the verification is successful, generate an authentication key of the user, and calculate a dynamic time factor of the server terminal; and generate an authentication factor by using the authentication key, the dynamic time factor, and the account information of the user.

The sending unit 1103 is configured to issue the authentication factor generated by the processing unit 1102 to the terminal.

The receiving unit 1101 is configured to receive bound authentication information submitted by the terminal, the bound authentication information being generated by binding the authentication factor and the device account information.

The processing unit 1102 is configured to perform authorization verification on the bound authentication information, and complete the offline payment authorization verification when authorization is successful.

Second situation:

The receiving unit 1101 is configured to receive an account identity verification request sent by the second terminal, the account identity verification request carrying account information of the user.

The processing unit 1102 is configured to judge whether the account identity verification request passes verification, and use the sending unit 1103 to send a result of successful verification to the second terminal if the verification is successful.

The receiving unit 1101 is configured to receive a verification request for offline payment authorization verification sent by the second terminal.

The processing unit 1102 is configured to judge whether verification on the verification request is successful, if the verification is successful, generate an authentication key of the user, and calculate a dynamic time factor of the server terminal; and generate an authentication factor by using the authentication key, the dynamic time factor, and the account information of the user.

The sending unit 1103 is configured to issue the authentication factor to the second terminal, such that the second terminal sends the authentication factor to the terminal.

The receiving unit 1101 is configured to receive bound authentication information that is returned by the terminal and submitted by the second terminal, the bound authentication information being generated by the terminal through binding the authentication factor and device account information.

The processing unit 1102 is configured to perform authorization verification on the bound authentication information, and complete the offline payment authorization verification when authorization is successful.

Optionally, after generating the authentication key of the user, the processing unit 1102 is further configured to generate a compressed string from the authentication key and the account information of the user, the compressed string having a one-to-one mapping relationship with the authentication key and the account information of the user.

The processing unit 1102 is configured to generate the authentication factor by using the authentication key, the dynamic time factor, and the account information of the user, which specifically includes: generating the authentication factor by using the authentication key, the compressed string, and the dynamic time factor.

Optionally, the processing unit 1102 is specifically configured to check whether a binding relationship between the device account information and the authentication key that are carried in the payment authentication information is correct, and check whether the dynamic password is valid according to the dynamic time factor in the authentication factor; and if yes, the payment authentication is successful.

The functions of the above units may be corresponding to the processing steps of the above information interaction method described in FIGs. 5a-5c in detail. Details are not described herein again.

FIG. 12 is a schematic structural diagram of composition of an electronic device according to an embodiment of the present application; as shown in FIG. 12, the electronic device includes: a display 1201, a processor 1202, a memory 1203, and a communication module 1204.

The memory 1203 is configured to store an authentication factor issued by a first server terminal and a program of generating a graphical identifier for offline payment according to the authentication factor, and when the program is executed by the processor, the graphical identifier for offline payment is displayed in a display area of the display. The graphical identifier carries payment authentication information, the payment authentication information including an authentication key of the user, device account information, and a dynamic password, the dynamic password is generated according to the dynamic time factor, and the device account information is generated according to account information of the user and device information of the terminal.

The communication module 1204, in communication with a second electronic device, is configured to receive the authentication factor that is issued by the first server terminal and sent by the second electronic device; and during binding authentication, send bound authentication information to the second electronic device, such that the bound authentication information is forwarded to the first server terminal.

The communication module 1204 is a Bluetooth module or a WiFi module.

Optionally, the dynamic password remains unchanged in a same time window, and in a next time window, the dynamic password is regenerated according to the dynamic time factor, to change dynamically.

Optionally, the dynamic password is specifically obtained through calculation by using the authentication key of the user, the dynamic time factor, the device account information, and a preset password length according to a one-time password calculating method.

Optionally, the device account information is a compressed string obtained by compressing the account information of the user and the device information of the terminal displaying the graphical identifier.

Optionally, the graphical identifier is a QR code or a bar code.

The present application further provides an information interaction system, which includes: a terminal, a first server terminal, and a second server terminal;

the terminal displays, in an offline state, a graphical identifier for completing a first service operation, the graphical identifier carrying authentication information of the first service operation, and the authentication information of the first service operation including an authentication key of a user, device account information, and a dynamic password;

the second server terminal acquires the authentication information of the first service operation carried in the graphical identifier;

the second server terminal generates a first service operation request by using the authentication information of the first service operation and service data, and sends the first service operation request to the first server terminal; and

the first server terminal performs authentication according to the authentication information of the first service operation carried in the first service operation request, and the first server terminal completes the first service operation when the authentication is successful.

Optionally, before the terminal displays the graphical identifier for completing the first service operation offline,

the terminal receives a display instruction for displaying the graphical identifier; and

the terminal generates the graphical identifier carrying the authentication information of the first service operation according to the authentication factor issued by the first server terminal.

Optionally, before the terminal generates the graphical identifier carrying the authentication information of the first service operation according to the authentication factor issued by the first server terminal,

the terminal, when in an online state, sends an authorization verification request for completing the first service operation offline to the first server terminal;

the first server terminal verifies the authorization verification request, and the first server terminal sends the authentication factor to the terminal after the verification is successful, the authentication factor including an authentication key of a user, account information, and a server terminal time;

the terminal generates a bound authentication code by binding the authentication factor and the device account information, and sends the bound authentication code to the first server

terminal; and

the first server terminal performs authorization verification on the bound authentication code, and completes the authorization verification when authorization is successful.

Optionally, before the terminal generates the graphical identifier carrying the authentication information of the first service operation according to the authentication factor issued by the first server terminal,

the second terminal in an online state sends an authorization verification request for completing the first service operation offline to the first server terminal;

the first server terminal verifies the authorization verification request, and the first server terminal sends the authentication factor to the second terminal after the verification is successful, the authentication factor including an authentication key of a user, account information, and a server terminal time;

the second terminal sends the authentication factor to the terminal;

the terminal generates a bound authentication code by binding the authentication factor and the device account information, and sends the bound authentication code to the second terminal;

the second terminal submits the bound authentication code to the first server terminal;

the first server terminal performs authorization verification on the bound authentication code, and completes the authorization verification when authorization is successful.

Optionally, before the second terminal sends the authorization verification request for completing the first service operation offline to the first server terminal,

the second terminal sends an account identity verification request to the first server terminal, the account identity verification request carrying the account information of the user;

the first server terminal verifies the account identity verification request, and sends a result of successful verification to the second terminal when the verification is successful.

Optionally, before the first server terminal sends the authentication factor after the verification is successful,

the first server terminal generates an authentication key of the user after the verification is successful and calculates a dynamic time factor;

the first server terminal generates the authentication factor by using the authentication key, the dynamic time factor, and the account information of the user.

Optionally, that the first server terminal performs authorization verification on the bound authentication code specifically includes:

parsing the bound authentication code to obtain the authentication key, the device account information, and the server terminal time; and

checking whether the authorization verification is successful according to the authentication key, the device account information, and the server terminal time obtained through parsing.

Optionally, after the first server terminal completes the first service operation,

the first server terminal returns a result of the first service operation to the second server terminal, such that the second server terminal confirms the result of the first service operation.

In the information interaction method, apparatus, and system provided in the embodiments of the present application, a dynamic graphical identifier for offline payment is generated through bound payment authentication information and dynamic time factor, such that a terminal device in an offline state can also perform safe payment by using the graphical identifier, thereby achieving safe and convenient payment.

Professionals should also be aware that units and algorithm steps in examples described with reference to the embodiments disclosed herein can be implemented by electronic hardware, computer software, or a combination thereof. To clearly illustrate the interchangeability between hardware and software, the composition and steps of each example have been described in general according to functions in the foregoing description. Whether these functions are executed by using hardware or software depends on a specific application and design constraint conditions of the technical solution. For each specific application, professionals may use a different method to implement the described functions. However, such implementation should not be considered as exceeding the scope of the present application.

Steps of the method or algorithm described with reference to the embodiments disclosed

herein may be implemented by hardware, a software module executed by a processor, or a combination thereof. The software module may be disposed in a random access memory (RAM), a memory, a read-only memory (ROM), an electrically programmable ROM, an electrically erasable programmable ROM, a register, a hard drive, a removable disk, a CD-ROM, or any other form of storage medium commonly known in the technical field.

The foregoing specific implementations provide further detailed descriptions of the objectives, technical solutions, and beneficial effects of the present application. It should be understood that, described above are merely specific implementations of the present application, which are not intended to limit the protection scope of the present application. Any modification, equivalent replacement, improvement, and the like made within the spirit and principle of the present application shall be included in the protection scope of the present application.

Claims

1. An information interaction method, comprising:

receiving, by a terminal, an authentication factor issued by a first server terminal, the authentication factor carrying an authentication key and account information of a user, and a dynamic time factor, the first server terminal being a server terminal that completes a first service operation after authenticating the terminal when the terminal requests the first service operation (S101);

generating, by the terminal, bound authentication information by using the authentication factor and device information of the terminal, and returning, by the terminal, the bound authentication information to the first server terminal, such that the first server terminal performs authorization through the first service operation according to the bound authentication information (S102); and

generating, by the terminal, a graphical identifier for completing the first service operation offline according to the authentication factor, the graphical identifier carrying authentication information of the first service operation, the authentication information of the first service operation comprising the authentication key of the user, device account information, and a dynamic password, the dynamic password being generated according to the dynamic time factor, and the device account information being generated according to the account information of the user and the device information of the terminal (S103).

2. The method of claim 1, before the step of generating a graphical identifier for completing the first service operation offline according to the authentication factor, further comprising:

receiving a display instruction for displaying the graphical identifier for completing the first service operation offline (S1031); and

generating the graphical identifier for completing the first service operation offline according to the authentication factor after the display instruction is received (S1032);

wherein after the step of generating a graphical identifier for completing the first service operation offline according to the authentication factor, the method further comprises:

displaying, by the terminal, the graphical identifier, to complete the first service operation in an offline state by using the graphical identifier (S1033).

3. The method of claim 2, wherein a displaying mode of the graphical identifier comprises one or a combination of: a bar code and a QR code; and

after the step of displaying, by the terminal, the graphical identifier, the method further

comprises:

switching the displaying mode of the graphical identifier when receiving a switch instruction for the displaying mode of the graphical identifier (S1034).

4. The method of claim 1, wherein the terminal receives, through a second terminal, the authentication factor issued by the first server terminal; and returns the bound authentication information to the first server terminal through the second terminal.

5. The method of claim 1, before the step of receiving an authentication factor issued by a first server terminal, further comprising:

sending, by the terminal, an account identity verification request to the first server terminal;

receiving a verification result sent by the first server terminal after identity verification is successful;

sending an authorization verification request for the offline first service operation to the first server terminal; and

receiving the authentication factor issued by the first server terminal after authorization verification is successful.

6. The method of claim 1, wherein the dynamic password remains unchanged in a same time window, and in a next time window, the dynamic password is regenerated according to the dynamic time factor, to change dynamically.

7. The method of claim 1, wherein the dynamic password is specifically obtained through calculation by using the authentication key of the user, the dynamic time factor, the device account information, and a preset password length according to a one-time password calculating method.

8. The method of claim 2, further comprising:

acquiring, by a second server terminal, the authentication information of the first service operation carried in the graphical identifier displayed on the terminal (S201);

generating a first service operation request by using the authentication information of the first service operation and service data, and sending the first service operation request to the first server terminal, such that the first server terminal performs authentication according to the authentication information of the first service operation carried in the first service operation

request, and completes the first service operation after the authentication is successful (S202); and

receiving a result of the first service operation returned by the first server terminal (S203).

9. The method of claim 8, further comprising:

receiving, by the first server terminal, the first service operation request sent by the second server terminal (S301); and

performing authentication according to the authentication information carried in the first service operation request (S302), and completing, by the first server terminal, the first service operation when the authentication is successful. (S303)

10. The method of claim 9, before the step of receiving a first service operation request sent by a second server terminal, further comprising:

performing, by the first server terminal, online account binding on the terminal.

11. The method of claim 10, wherein the step of performing, by the first server terminal, online account binding on the terminal specifically comprises:

receiving an account identity verification request sent by the terminal, the account identity verification request carrying account information of the user (S401);

determining whether the account identity verification request passes verification, and sending a verification result of successful verification to the terminal if the verification is successful (S402);

receiving an authorization verification request, sent by the terminal, for completing the first service operation offline (S403);

determining whether verification on the authorization verification request is successful, if the verification is successful, generating the authentication key of the user, and calculating a dynamic time factor of the first server terminal (S404);

generating an authentication factor by using the authentication key of the user, the dynamic time factor, and the account information of the user (S405);

issuing the authentication factor to the terminal (S406);

receiving bound authentication information submitted by the terminal, the bound authentication information being generated by binding the authentication factor and the device account information (S407); and

performing authorization verification on the bound authentication information, and

completing the authorization verification after authorization is successful (S408).

12. The method of claim 10, wherein the step of performing, by the first server terminal, online account binding on the terminal specifically comprises:

receiving an account identity verification request sent by the second terminal, the account identity verification request carrying the account information of the user (S501);

determining whether the account identity verification request passes verification, and sending a verification result of successful verification to the second terminal if the verification is successful (S502);

receiving an authorization verification request, sent by the second terminal, for completing the first service operation offline (S503);

determining whether verification on the authorization verification request is successful, if the verification is successful, generating the authentication key of the user, and calculating a dynamic time factor of the first server terminal (S504);

generating an authentication factor by using the authentication key of the user, the dynamic time factor, and the account information of the user (S505);

issuing the authentication factor to the second terminal, such that the second terminal sends the authentication factor to the terminal (S506);

receiving bound authentication information that is returned by the terminal and submitted by the second terminal, the bound authentication information being generated by the terminal through binding the authentication factor and the device account information of the terminal (S507); and

performing authorization verification on the bound authentication information, and completing the authorization verification after authorization is successful (S508).

13. The method of claim 11 or 12, after the step of generating the authentication key of the user, further comprising:

generating a compressed string from the authentication key of the user and the account information of the user, the compressed string having a one-to-one mapping relationship with the authentication key and the account information of the user; and

generating the authentication factor by using the authentication key of the user, the dynamic time factor, and the account information of the user, which specifically comprises: generating the authentication factor by using the authentication key of the user, the compressed string, and the dynamic time factor.

14. The method of claim 9, wherein the step of performing authentication according to the authentication information of the first service operation carried in the first service operation request specifically comprises:

checking whether a binding relationship between the device account information and the authentication key that are carried in the authentication information of the first service operation is correct, and checking whether the dynamic password is valid according to the dynamic time factor in the authentication factor; wherein if yes, the authentication is successful.

15. An apparatus comprising:

a terminal;

a first server terminal; and

a second server terminal;

wherein the apparatus is configured to perform the method of any one of claims 1 to 14.