WHAT IS CLAIMED IS:

1. A cable laying method using a cable laying apparatus capable of changing a direction of a cable, the cable laying method comprising:

~~(A)~~ installing a frame ~~unit~~assembly;

~~(B)~~ arranging a trailer bogie loaded with a cable drum inside the frame ~~unit without additional loading work~~assembly;

~~(C)~~ rotating the cable drum, which is loaded in the trailer bogie, by an under-roller ~~part~~frame;

~~(D)~~ changing a withdrawal direction of ~~a~~ the cable unwound from the cable drum by a traverse ~~part~~ panel of the frame ~~unit~~assembly;

~~(E)~~ supplying the cable, the withdrawal direction of which is changed by the traverse ~~part~~panel, to a cable unwinding ~~part~~ roller assembly located at ~~the~~ a rear side of the traverse ~~part~~panel; and

~~(F)~~ supplying the cable passing through the cable unwinding ~~part~~ roller assembly to a required place through a curvature guide ~~part~~ located at ~~the~~ a rear side of the cable unwinding ~~part~~roller assembly,

wherein the traverse ~~part~~ panel is configured to change ~~a~~ the direction of the cable withdrawn in a radial direction of the cable drum to an axial direction of the cable drum,

wherein the installing of the frame assembly comprises:

moving the frame assembly loaded on a cargo box of a truck to a site at which the cable is to be laid; and

extending lengths of a first unloading pillar and a second unloading pillar of the frame assembly to support and fix the first unloading pillar on a road surface and

bring the second unloading pillar into contact with the road surface.

~~2. The cable laying method of claim 1, wherein (A) comprises:~~

~~(A1) moving the frame unit loaded on a cargo box of a truck to a site at which the cable is to be laid; and~~

~~(A2) extending lengths of a first unloading pillar part and a second unloading pillar part of the frame unit to support and fix the first unloading pillar part on a road surface and bring the second unloading pillar part into contact with the road surface.~~

~~3~~2. The cable laying method of claim ~~2~~1, wherein ~~after (A2), (A)~~the installing of the frame assembly further comprises ~~(A3)~~ increasing a width of the frame ~~unit~~ assembly to a predetermined width by a movement of the second unloading pillar ~~part~~.

~~4~~3. The cable laying method of claim ~~3~~2, wherein ~~after (A3), (A)~~the installing of the frame assembly further comprises:

~~(A4)~~ moving the truck while the width of the frame ~~unit~~ assembly is increased; and

~~(A5)~~ extending a first lifting frame included in a first pillar ~~part~~ of the frame ~~unit~~ assembly and a second lifting frame included in a second pillar ~~part~~ of the frame ~~unit~~ assembly downward and adjusting a height of the frame ~~unit~~ assembly to a predetermined height.

~~5~~4. The cable laying method of claim ~~4~~3, wherein ~~after (A5), (A)~~the

installing of the frame assembly further comprises ~~(A6)~~ adjusting the lengths of the first unloading pillar ~~part~~ and the second unloading pillar ~~part~~ to return to ~~an~~ original ~~position~~ lengths thereof while the first lifting frame and the second lifting frame are fixed on the road surface.

~~6~~5. The cable laying method of claim ~~3~~2, wherein ~~(A3)~~the increasing of the width of the frame assembly comprises adjusting the width of the frame ~~unit~~ assembly to arrange the trailer bogie loaded with the cable drum in the frame ~~unit~~assembly.

~~7~~6. The cable laying method of claim 1, wherein, during ~~(D)~~the changing of the withdrawal direction of the cable, the traverse ~~part~~ panel is slidingly moved in a lengthwise direction of the frame ~~unit~~ assembly and configured to change ~~a~~ the withdrawal direction of the cable.

7. The cable laying method of claim 1, wherein the cable unwinding roller assembly and the curvature guide are installed in a moving vehicle.

8. ~~The~~ A cable laying method ~~of claim 7~~using a cable laying apparatus capable of changing a direction of a cable, the cable laying method comprising:

installing a frame assembly;

arranging a trailer bogie loaded with a cable drum inside the frame assembly;

rotating the cable drum, which is loaded in the trailer bogie, by an under-roller frame;

changing a withdrawal direction of the cable unwound from the cable drum by a traverse panel of the frame assembly;

supplying the cable, the withdrawal direction of which is changed by the traverse panel, to a cable unwinding dev roller assembly ice located at a rear side of the traverse panel; and

supplying the cable passing through the cable unwinding roller assembly to a required place through a curvature guide located at a rear side of the cable unwinding roller assembly,

wherein the traverse panel is configured to change the direction of the cable withdrawn in a radial direction of the cable drum to an axial direction of the cable drum, and

~~,~~ wherein a cable sagging preventer provided at ~~the~~ a rear side of the frame ~~unit~~ assembly is unfolded about a rotation axis to support the cable in a state in which the traverse ~~part~~ panel is moved forward along the frame ~~unit~~assembly, and is folded about the rotation axis to prevent interference with the traverse ~~part~~ panel in a state in which the traverse ~~part~~ panel is moved backward along the frame ~~unit~~assembly.

9. ~~The~~ A cable laying method ~~of claim 1~~using a cable laying apparatus capable of changing a direction of a cable, the cable laying method comprising:

installing a frame assembly;

arranging a trailer bogie loaded with a cable drum inside the frame assembly;

rotating the cable drum, which is loaded in the trailer bogie, by an under-roller frame;

changing a withdrawal direction of the cable unwound from the cable drum by a traverse panel of the frame assembly;

supplying the cable, the withdrawal direction of which is changed by the traverse panel, to a cable unwinding roller assembly located at a rear side of the traverse panel; and

supplying the cable passing through the cable unwinding roller assembly to a required place through a curvature guide located at a rear side of the cable unwinding roller assembly,

wherein the traverse panel is configured to change the direction of the cable withdrawn in a radial direction of the cable drum to an axial direction of the cable drum, and

wherein a rear end of the traverse ~~part~~ panel is located at a position higher than that of the cable unwinding ~~part~~roller assembly.

~~10. The cable laying method of claim 1, wherein the cable unwinding part and a curvature guide part are installed in a moving vehicle.~~