

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
2 October 2003 (02.10.2003)

PCT

(10) International Publication Number
WO 03/080501 A1

(51) International Patent Classification⁷: B67D 5/42,
G01F 11/00, B65D 83/00, 83/06, 83/14, 83/60, 83/68,
83/70, 83/72, 83/76, 47/10

(21) International Application Number: PCT/US02/08876

(22) International Filing Date: 21 March 2002 (21.03.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: TSAUR, Garry [US/US]; 19222 Tranbarger
Street, Rowland Heights, CA 91748 (US).

(74) Agent: NIEH, Joe; Suite 475, 17800 Castleton Street, City
of Industry, CA 91748 (US).

(81) Designated States (national): AU, BR, CA, CH, CN, CZ,
DE, DZ, ES, GB, ID, IL, IN, JP, KE, KR, NZ, PL, PT, RO,
RU, SG, TR, TZ, UA, US, VN, ZA.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to the identity of the inventor (Rule 4.17(i)) for all des-ignations
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.



162162

(54) Title: PRESSURIZED PISTON PUSHER

WO 03/080501 A1



(57) Abstract: A pressurized piston pusher (7) is disclosed that will extract viscous fluids (2) from a container. The pressurized piston pusher (7) operates with the seal (1) to allow the rate of flow of the viscous fluid (2) from the container to be predetermined and controlled economically and accurately. The pressurized piston pusher (7) will also allow the forced ejection of the viscous fluid (2) from the container.