

PROGRAMMABLE CYLINDER LOCK AND KEYS FOR THE OPERATION THEREOF

The subject of this invention is a programmable cylinder lock, namely
5 a lock comprising devices intended to allow the initial codification of the lock
or, through a change operation, to modify the former lock codification in order
to adjust the lock for being operated by a key different from the key to which
the lock was formerly adapted.

More particularly, the invention concerns improvements in a kind of
10 programmable cylinder lock which is known from the European Patents Nos.
0.226.252 and 0.900.310.

The programmable locks of the kind to which applies the present in-
vention and which are described in the cited documents comprise, within a
rotor rotatably mounted inside the stator, a number of key followers movable
15 along their longitudinal and transversal directions, intended to cooperate with
the codification conformations of a key inserted into the rotor keyhole, and
locking pins having movability along their own longitudinal directions, which
are the blocking members of the lock. The key followers and the locking pins
form pairs each comprising a locking pin and a key follower, and they are pro-
20 vided with toothings intended to mutually cooperate, in different relative posi-
tions, for determining the lock codification. A transversally displaceable stop
bar, cooperating with a longitudinal stator groove, is susceptible of cooperat-
ing with recesses of the locking pins in order to immobilize the locking pins
when the rotor is rotated within the stator and, as a consequence, the stop bar
25 comes out of said groove and engages the locking pins. A transversally dis-
placeable change bar is slidably engaged with the key followers and normally
retains the key followers engaged with the locking pins, but this change bar,
when it enters said stator groove, transversally displaces the key followers by
disengaging the same from the locking pins, thus allowing the modification of
30 the lock codification by replacing the former key by a new different key.

A requirement laid down for the known locks of this kind is to ensure
that the codification change may be effected only by using a special change
key. This gives the security that the lock codification cannot be modified or

altered by mistake. Another requirement, common to all kinds of locks, is to allow an increase in the number of different keys that can be provided. Still another requirement common to all kinds of locks is to hinder the non-authorized manufacture of key copies. Several solutions have been proposed
5 for all these problems, but in general they involve complications or constructive difficulties, thus increasing the lock size and cost.

The main object of this invention is to improve a lock of the considered kind in order to supply a simple and sure solution to the above stated problems without increasing in a noticeable manner the size, the complication and
10 the cost of the lock.

This object is attained, according to the invention, in a lock of the stated kind, in that the stop bar has at least one protrusion facing the keyhole of the rotor intended to receive the key, and that the use key has in the side surface thereof at least one recess situated in such a way that it faces said
15 protrusion of the stop bar when the key is correctly inserted in the lock, whereas the corresponding change key has in the side surface thereof a longitudinal groove extending in a position corresponding to said at least one recess of the use key.

In this way, when the rotor is made to rotate by means of a use key, and the stop bar comes out of the stator groove, in the presence of the correct
20 key said projection of the stop bar enters the corresponding recess of the key and then retains the key, whereby it is not possible to take the key away from the lock and provide a change condition. On the contrary, when the rotor is made to rotate by a change key, said projection of the stop bar enters the longitudinal groove of the change key, but this groove does not hinder the key
25 extraction for a change operation.

Moreover, if in the lock is inserted a use key whose teeth are correctly codified, but that does not have in its side surface a recess corresponding to the projection of the stop bar, this latter cannot displace in radial direction for
30 coming out of the stator groove and thus blocks the rotor, which therefore cannot be made to rotate by that key. It follows that the presence and position of said recess of the use key are additional elements to the lock and key codification, and therefore allow to increase the number of different keys which may be provided.

Besides, because usually the non-authorized key copies are obtained by means of copying cutters that provide a correct outline of the key teeth but are not able to provide in the side surface of the key a recess so located that it places itself in front of a projection of the stop bar, it follows that the key copies suitable for operating the lock according to the invention cannot be provided by the usual equipments, and this fact seriously hinders their manufacture.

In order to increase the effectiveness of the provision according to the invention, it is of advantage that the stop bar is provided with two or more projections, and that in a corresponding manner the use keys have in their side surface two or more recesses intended to place themselves in front of said projections of the stop bar. By suitably choosing the number and position of the projections of the stop bar it is possible to increase at wish the number of different keys which may be provided.

These and other features, objects and advantages of the subject of the present invention will more clearly appear from the following description of a preferred embodiment, being a not limiting example, with reference to the accompanying drawings, wherein:

Figure 1 represents, for the purpose of reference, a cross section of a programmable cylinder lock carried down according to the teachings of the European Patent No. 0.900.310, having inserted a key suitable for operating the lock, in the condition of insertion of the key.

Figure 2 shows a cross section corresponding to that of Figure 1, but in the condition in which by means of the key the rotor has been made to rotate of a certain angle.

Figure 3 shows a cross section of a lock rotor according to the invention, in the condition in which the inserted key has a recess or groove corresponding to a projection of the stop bar, and therefore it allows the radial displacement of the stop bar.

Figure 4 shows a cross section corresponding to that of Figure 3, but refers to the case in which the inserted key does not have a recess or groove corresponding to a projection of the stop bar, and therefore it does not allow the radial displacement of the stop bar.

Figure 5 shows a side view of a use key shaped according to the present invention.

Figure 6 shows, in a manner similar to Figure 5, a change key suitable for the lock according to the present invention.

Figure 7 shows, in a manner similar to Figure 5, a key copy as can be manufactured by means of the usual copying cutter for keys.

5 At first, reference to Figure 1 will be made in order to recall the general structure and the operation of a lock of the considered kind, for whose particulars reference is made to the cited documents.

10 Number 1 designates a stator inside which there is rotatably mounted a cylindrical rotor 2 susceptible of receiving in its keyhole a key 3. In the following, it will be considered as longitudinal the direction parallel to the geometrical axis of the corresponding cylindrical rotor, and will be considered as transversal the direction perpendicular to the plane of the key and the corresponding keyhole.

15 In rotor 2 there are mounted key followers 4, which lies in a plane perpendicular to the axis of the cylindrical rotor 2 and are movable along the longitudinal and transversal directions. The key followers 4 are provided for cooperating with the codification conformations of key 3. Moreover, in rotor 2 there are mounted locking pins 6, and each of them is coplanar with a key follower 4 and is movable along its own longitudinal direction. The locking pins 6
20 form the blocking member of the lock. The lock can possibly counterpins 8 mounted in stator 1.

25 The key followers 4 and the locking pins 6 have toothings intended to mutually cooperate, and this may take place in different relative positions in order to define the lock codification. in the position of key insertion (Figure 1), the locking pins are free to displace along their own longitudinal direction, but
30 a stop bar 9, displaceable in the transverse direction within rotor 2 and susceptible of cooperating with a groove 10 of stator 1, serves for immobilizing the locking pins 6 when rotor 2 is made to rotate within stator 1 and, as a consequence, the stop bar 9 comes out of said groove 10 and engages the locking pins 6.

 A change bar 11 which is transversally displaceable in rotor 2 is slidably coupled with the key followers 4, and normally the change bar 11 keeps the key followers 4 engaged with the locking pins 6 but, when said change bar 11, due to a rotation of rotor 2, comes to correspond to said groove 10 of sta-

tor 1 and enters therein, it transversally displaces the key followers 4 and disengages the same from the locking pins 6. Then, by means of the replacement of the former key 3 by a different key, it is possible to modify the lock codification.

5 Figure 2 shows that, when rotor 2 is rotated by key 3, the stop bar 9 leaves the groove 10 of stator 1 and displaces radially inwards by engaging the locking pins 6 in order to immobilize the same. Of course, this inwards displacement of the stop bar is needed for allowing the rotation of rotor 2, which would be positively prevented by the stop bar if the same would be prevented from displacing radially inwards by disengaging from the groove 10.

10 In Figures 3 and 4, which refer to the lock according to the invention, there are represented only the rotor 2, the stop bar 9 and the key, now designated 13, 15 or 17, because the other component parts are not interested in the operation according to the invention, and they could conform to any known embodiment.

15 The stop bar 9 has at least a projection 12 facing the keyhole of rotor 2 intended to receive the key 13. The extension of projection 12 is such that it does not hinder the insertion of key 13 when the stop bar 9 is inserted in the groove 10 of stator 1 and is displaced outwards.

20 The use key 13 according to the invention (Figure 5) differs from the known keys only in that it is provided in its side surface with one or more recesses 14, which are so located that, when key 13 is inserted in the lock rotor 2, they place themselves in front of the corresponding projections 12 of the stop bar 9.

25 Therefore, when the key 13 causes rotor 2 to rotate, the stop bar 9 displaces radially inwards, and this displacement is not hindered because a recess 14 of key 13 faces the projection 12. Therefore the lock can be operated in the usual manner. The engagement of projection 12 of the stop bar 9 in the recess 14 of key 13 lasts in any position of rotor 2, except the position of key insertion; in this position the stop bar enters the groove 10, displaces
30 radially outwards and the projection 12 disengages from the recess 14.

 Until projection 12 remains engaged in recess 14, key 13 cannot be withdrawn from the lock. Therefore, the key cannot be extracted in the change position, and the lock codification cannot be modified by mistake.

The change key 15 (Figure 6) differs from the use key 13 in that, in the position corresponding to the recesses 14 of key 13, it is provided with an uninterrupted longitudinal groove 16. Therefore, when the change key 15 is inserted in the lock, the projection 12 of the stop bar 9 meets the facing
5 groove 16 wherein it can enter, and the stop bar 9 is not hindered to radially displace inwards for coming out of the groove 10 of stator 1. Rotor 2 can freely be made to rotate by the change key 15. However, because the groove 16 is uninterrupted, the change key 15 is not retained by projection 12, and in the change position of the lock the change key can be extracted and replaced
10 by a different change key in order to modify the lock codification.

If of key 13 or 15 is made a copy by using the usual copying equipments, the resulting key is like key 17 represented in Figure 7. It is identical to the original key 13 or 15, except in that its side surface is not provided with the recesses 14 nor with the groove 16.

15 If this key copy is inserted in the lock rotor 2, the condition represented in Figure 4 takes place. The projection 12 of the stop bar 9 does not find in front a recess nor a groove, but the side surface 18 of key 17. Therefore the stop bar 9 is kept unmovable in the position in which it projects from rotor 2 and is engaged in groove 10 of stator 1. So the rotor 2 cannot be ro-
20 tated by the key copy 17.

As already said, by suitably choosing the number and disposition of the projections of the stop bar it is possible to attain the desired increase in the number of different keys which can be manufactured. Besides, by provid-
25 ing a number of projections 12 and recesses 14, the arrangement according to the invention may also be used for providing master use keys suitable for operating a number of locks whose normal use keys are suitable only for operating the corresponding lock.

In this case, a master use key is provided with recesses whose positions correspond to the positions of projections of a number of locks which are
30 operable by normal use keys provided with recesses whose number and positions correspond to the number and positions of the projections of the stop bar of the corresponding lock.

Thanks to the application of this invention there is obtained, by simple and sure means and without in any way increasing the size, the complexity
35 and the cost of the lock, the safety in the preservation of the lock codification

against maneuver mistakes, an increase in the number of different keys which can be provided, an obstacle to the non-authorized copy of the keys and also, if required, the possibility of producing master keys.

5 It is to be understood that this invention is not limited to the embodiments described and shown as examples. Several possible modifications have been pointed out in the course of the description, and others are within the ability of those skilled in the art. These modification and others, and any replacement by technically equivalent means, can be made to what has been described and shown, without departing from the spirit of the invention and the
10 scope of this Patent as defined by the appended Claims.

CLAIMS

1 . A system comprising a programmable cylinder lock, a use key and a change key, wherein the programmable cylinder lock is of the type comprising a stator (1) and a cylindrical rotor (2), mounted inside the stator (1) for rotation around its own axis and having a keyhole extending in the axis direction for insertion of a key, and comprising inside rotor (1) a number of key followers (4) movable along the longitudinal and transversal directions, intended to cooperate with the codification conformations of a key inserted into the keyhole of rotor (2), and a number of locking pins (6) movable along the longitudinal direction, which form the lock blocking members, said key followers (4) and locking pins (6) forming together a number of pairs each including a locking pin (6) and a key follower (4) and having toothings intended to mutually cooperate, in different relative positions, in order to define the lock codification, the rotor (2) including a transversally displaceable stop bar (9) cooperating with a longitudinal groove (10) of stator (1) and cooperating with the locking pins (6) in order to immobilize said locking pins (6) when rotor (2) is made to rotate within stator (1) and the stop bar (9) comes out of said groove (10) and engages the locking pins (6), and comprising a change bar (11) which is transversally displaceable and is slidably coupled with the key followers (4) in order to normally keeping the key followers (4) engaged with the locking pins (6) and to disengage the key followers (4) from the locking pins (6) when said change bar (11) comes into said groove (10) of stator (1) and provides a lock programming position, characterized in that said stop bar (9) has at least one protrusion (12) facing the keyhole of rotor (2) intended to receive the key (13,15), and that the use key (13) has at least one recess (14) situated in such a way that it faces said protrusion (12) of the stop bar (9) when the key (13) is correctly inserted in the lock, whereas the corresponding change key (15) has a longitudinal groove (16) extending in a position corresponding to said at least one recess (14) of the use key (13).

2 . A system as set forth in Claim 1, characterized in that said stop bar (9) has two or more protrusions (12), and that the use key (13) has recesses (14) corresponding in number and positions to said protrusions (12) of the stop bar.

3 . A system as set forth in Claim 1, characterized in that a master use key has recesses whose positions correspond to the positions of the protrusions (12) of a number of locks operated by different normal use keys (13) having recesses (14) corresponding in number and positions to said protrusions (12) of the stop bar (9) of the corresponding lock.

5