CLAIMS:

1. A heterogeneous three-dimensional circuit stack comprising:

a first processor;

a second processor communicatively coupled with the first processor through one or more through silicon vias, wherein at least one of the first processor or the second processor is a graphics processor; and

interconnect logic to communicatively couple the first processor and the second processor to a shared resource, the interconnect logic to couple with the first processor and the second processor via corresponding on-chip interconnects;

wherein the interconnect logic includes bandwidth sharing logic to adjust bandwidth to the shared resource; and

wherein the shared resource includes a shared memory resource.

2. The heterogeneous three-dimensional circuit stack as in claim 1, wherein the shared memory resource includes dynamic random access memory.

3. The heterogeneous three-dimensional circuit stack as in claim 1, wherein the shared memory resource includes non-transitory machine readable storage medium.

4. The heterogeneous three-dimensional circuit stack as in claim 1, wherein the interconnect logic is to operate at a higher frequency than one of the first processor or the second processor.

5. The heterogeneous three-dimensional circuit stack as in claim 1, wherein at least one of the first processor or the second processor is an accelerator.

6. The heterogeneous three-dimensional circuit stack as in claim 1, additionally comprising a third processor, wherein the third processor includes an accelerator or a graphics processor.

7. The heterogeneous three-dimensional circuit stack as in claim 6, wherein the third processor includes an accelerator and a graphics processor.

8. The heterogeneous three-dimensional circuit stack as in claim 7, wherein the interconnect logic enables coherent access to the shared resource for execution threads of the graphics processor.

9. The heterogeneous three-dimensional circuit stack as in claim 8, wherein the interconnect logic enables coherent access via programmatically assigned traffic classifications.

10. A system comprising:

a heterogeneous three-dimensional circuit stack including a first processor communicatively coupled with a second processor through one or more through silicon vias, wherein at least one of the first processor or the second processor is a graphics processor;

a first memory communicatively coupled with the first processor;

interconnect logic to communicatively couple the first processor and the second processor to a shared resource, the interconnect logic to couple with the first processor and the second processor via corresponding on-chip interconnects; and

wherein the interconnect logic includes bandwidth sharing logic to adjust bandwidth to the shared resource; and

the shared resource includes a second memory.

11. The system as in claim 101, wherein the second processor includes an accelerator or a graphics processor.

12. The system as in claim 11, wherein the second processor includes an accelerator and a graphics processor.

13. The system as in claim 10, wherein the shared resource is a shared memory resource including dynamic random access memory.

14. The system as in claim 10, wherein the first memory includes dynamic random access memory.

15. The system as in claim 10, wherein the interconnect logic is to operate at a higher frequency than one of the first processor or the second processor.

16. A method of interconnecting a heterogeneous three-dimensional circuit stack, the method comprising:

communicatively coupling a first processor to a second processor through one or more through silicon vias, wherein at least one of the first processor or the second processor is a graphics processor, the first processor and the second processor communicatively coupled to a shared resource via interconnect logic via corresponding on-chip interconnects; and

configuring bandwidth sharing logic to adjust bandwidth to the shared resource.

17. The method as in claim 16, additionally comprising communicatively coupling a third processor to the interconnect logic, the third processor including an accelerator or a graphics processor.

18. An apparatus comprising:

means for communicatively coupling a first processor to a second processor through one or more through silicon vias, wherein at least one of the first processor or the second processor is a graphics processor, the first processor and the second processor communicatively coupled to a shared resource via interconnect logic via corresponding on-chip interconnects;

means for configuring bandwidth sharing logic to adjust bandwidth to the shared resource.

19. The apparatus as in claim 18, additionally comprising means for communicatively coupling a third processor to the interconnect logic, the third processor including an accelerator or a graphics processor.