

Description

One of the most effective methods of preventing erosion of the river or sea bed around underwater structures is by anchoring an array or mat of synthetic buoyant fronds close to the structure. The fronds exert a viscous drag which reduces the velocity of the fines (soil particles) in underwater currents to a point where the particles are deposited, and the deposited particles then accumulate to form a permanent consolidated sandbank.

The array of fronds generally consists of lines of fronds arranged in a predetermined pattern and interconnected by flexible ties, or the fronds may be secured individually or in bunches to a matting.

In either case, the difficulties of manufacturing the array in a simple but cost-effective manner, combined with the difficulties of deploying the array on the river or sea bed, have prevented the potential of the method being fully exploited.

There is therefore the need for a soil retention and reinforcement structure which can be easily deployed on the sea bed, and which is simple to produce on a commercial scale. Ideally, the method of deploying the structure should lend itself to automation.

It would also be an advantage if the density and/or height of the structure could be easily varied over a wide range without affecting the manufacturing process.

IN GB-A-2,127,469 there is disclosed an underwater soil retention and reinforcement structure comprising a sequence of synthetic buoyant fronds arranged side-by-side to form a frond line. Several such lines can be placed end-to-end, or in spaced apart parallel rows, to form an array.

In US-A-4,534,675 individual sheets of buoyant material are slit to form respective lines of fronds, the sheets being roped together end-to-end and deployed in various patterns on the sea bed. In this arrangement, the roped together sheets are each anchored to the sea bed at both ends.

According to one aspect of the present invention, there is provided an underwater soil retention and reinforcement structure comprising a sequence of synthetic buoyant fronds arranged side-by-side to form a frond line, the line being folded back and forth to form an array of fronds, and the successive folded sections of the frond line having aligned openings threaded by at least one anchor line for anchoring the array to the soil bed. In this manner, a curtain of fronds is presented to the soil particles in almost every direction, and the pitch or spacing between the successive folded sections is infinitely variable from a virtual solid to whatever pitch or spacing is required.

In a preferred embodiment, the structure comprises a fan-folded continuous sheet with vertical

slits forming the individual fronds. The folded sheet is initially packed in a box-like dispenser with the folded sections in a tightly bunched, compact state. As the anchor line is withdrawn from the dispenser, the sections are spread apart.

In this manner, the density of fronds in the structure can be regulated simply by controlling the pitch of the folded sections. Moreover, since the frond line is a continuous folded structure, manufacture of a complete array of fronds is greatly simplified. A change in frond height is obtained merely by changing the width of the sheet.

The base of the sheet is preferably reinforced, and the anchor lines pass through aligned holes in the reinforced base section of the sheet.

One particular example of the invention will now be described with reference to the accompanying drawings in which:

Fig. 1 is a diagrammatic perspective view showing a scour control structure partially withdrawn from a dispenser and anchored to the sea bed;

Fig. 2 is a diagrammatic Underside plan view of the structure shown in Fig. 1; and

Fig. 3 is a detail of a part of the structure shown in Fig. 2 when viewed from one side and showing the attachment of a side anchor.

Referring to these drawings, the illustrated scour control structure consists of a continuous sheet 10 of buoyant synthetic material, such as polypropylene, slit into 25mm vertical strips 11 to provide a sequence of individual fronds each having a height of up to 2 metres above the soil bed 12 when the structure is anchored to the bed 12.

The slits 15 terminate some distance above the bottom edge 16 of the sheet, and the bottom of the sheet is folded upwards to provide a reinforced base 18. A reinforcing strap 17 is encased within the base 18.

The sheet 10 is folded back and forth in a fan-folded configuration, and is dispensed from a box 13. As best shown in Fig. 2, the successive fan-folded sections 14 of the folded base strip 18 are stored at the bottom of the box 13 in a bunched compact state, and the frond strips 11 are then laid flat and folded over in the space above. As the sections 14 are progressively withdrawn from the box, the structure expands into an open extended state and the frond strips 11 are released into an upright buoyant position (Fig. 1).

The structure is threaded by anchor lines 19a, 19b, 19c passing through aligned holes 20 in the reinforced base 18. The lines 19 each carry adjustable sheet stops in the form of grommets 21 which are slidable along the respective lines and can be used to adjust the spacing between the fan-folded sections 14 of the sheet. This in turn controls the density of the fronds in the overall structure. Alternatively, a short foldable inter-sheet link 41 (Fig. 2)

is provided between each of the successive sections 14 which limits the pitch of the fan-folded structure. The link may be of the same material as the sheet and effectively forms a V-shaped hinge between each of the successive sections 14 at the outboard edges of the structure as shown in Fig. 2.

The use of links 41 formed of sheet material permits a greater packing density in the dispenser 13 compared to the use of grommets 21, and controls the pitch of the fan-folded structure.

At the leading end of each line 19 is a ground anchor plate 22 which may be of the type more fully described in UK patent application 8904169.3. The anchor plates 22a, 22b, 22c are driven downwardly into the sea bed 12 to anchor the leading end of the structure 10 firmly to the sea bed.

These three leading anchors 22a, 22b and 22c are initially stored on top of the dispenser box 13. Once these three anchors have been anchored, the dispenser box 13 is advanced rearwardly in the direction of arrow 23. The leading section 14a of the fan-folded structure is attached to the anchor lines 19 so that this rearward movement progressively withdraws the successive sections 14 of the sheet 10 through a throat at the bottom of the front wall of the dispenser and opens out the fan-folded structure. During this process, the anchor lines 19a, 19b, 19c run through the openings 20 in the base of the fan-folded sheet, the three lines being drawn from respective supplies folded concertina fashion at the back of the dispenser as shown in Fig. 2. At predetermined intervals, denoted for example by colour coding on the anchor lines 19 and/or on the sheet 10, a side anchor 25 is secured to the respective outside anchor lines 19a and 19c by respective anchoring straps 24 and using a carabiner clip fastening 28 which clips around the anchor line and passes through an aperture 26 formed in the sheet 10 along one of the fold lines 27. Finally, three trailing anchors 40 secured by straps (omitted for the sake of clarity) to the opposite ends of the respective lines 19a, 19b, 19c are driven into the sea bed to complete the anchoring process.

With the structure 10 anchored to the sea bed in the path of an underwater current, the velocity of the current will be reduced below the critical transport velocity so as to ensure particle deposition. Accordingly, substantially all the fines carried by the current will be deposited within the structure and a permanent consolidated sandbank will be created having a particularly uniform distribution of reinforcement.

In particular, it can be seen that the fronds present an almost solid wall in every direction, and once the fines enter the V-shaped pockets formed by the successive sections of the folded sheet they are virtually trapped since there are no clear cur-

rent flow paths through the structure.

The base pitch between successive sections might be of the order of 20mm giving 50 frond lines per linear metre. This density can be easily varied by adjusting the spacing between the grommets 21. As illustrated, the grommets 21 are arranged so that the interleaved V-shaped pockets formed between the successive sections 14 extend from one side of the structure to the other in alternating directions. However, the grommets 21 can be adjusted to provide any required pattern of pockets. In particular, the grommets on the centre anchor line 19b could be adjusted to provide a different pattern in which the pockets terminate at the centre line.

In the alternative arrangement of Fig. 2, the base pitch is fixed by the length of the foldable inter-sheet links 41.

The front anchor plate 22 and the side anchor plate 25 with their respective anchoring straps 24 are stored on top of the box 13 one behind the other so that they are easily accessible when deploying the structure on the sea bed.

Claims

1. An underwater soil retention and reinforcement structure comprising a sequence of synthetic buoyant fronds (11) arranged side-by-side to form a frond line, characterised in that the line is folded back and forth to form an array of fronds, and the successive folded sections (14) of the frond line have aligned openings (20) threaded by at least one anchor line (19) for anchoring the array to the soil bed (12).
2. A structure according to claim 1 further comprising means (21, 41) for controlling the pitch or spacing between the successive folded sections (14) of the frond line.
3. A structure according to claim 2 in which the control means comprises spacing elements (21) slidable along the respective anchor lines (19).
4. A structure according to claim 2 in which the control means comprises foldable links (41) between the successive folded sections (14).
5. A structure according to any one of the claims 1-4 in which a ground anchor (22) is secured at one or both ends of each anchor line (19), the structure being anchored by driving the ground anchors into the soil bed (12).
6. A structure according to claim 5 further comprising means for releasably attaching at least



is provided between each of the successive sections 14 which limits the pitch of the fan-folded structure. The link may be of the same material as the sheet and effectively forms a V-shaped hinge between each of the successive sections 14 at the outboard edges of the structure as shown in Fig. 2.

The use of links 41 formed of sheet material permits a greater packing density in the dispenser 13 compared to the use of grommets 21, and controls the pitch of the fan-folded structure.

At the leading end of each line 19 is a ground anchor plate 22 which may be of the type more fully described in UK patent application 8904169.3. The anchor plates 22a, 22b, 22c are driven downwards into the sea bed 12 to anchor the leading end of the structure 10 firmly to the sea bed.

These three leading anchors 22a, 22b and 22c are initially stored on top of the dispenser box 13. Once these three anchors have been anchored, the dispenser box 13 is advanced rearwardly in the direction of arrow 23. The leading section 14a of the fan-folded structure is attached to the anchor lines 19 so that this rearward movement progressively withdraws the successive sections 14 of the sheet 10 through a throat at the bottom of the front wall of the dispenser and opens out the fan-folded structure. During this process, the anchor lines 19a, 19b, 19c run through the openings 20 in the base of the fan-folded sheet, the three lines being drawn from respective supplies folded concertina fashion at the back of the dispenser as shown in Fig. 2. At predetermined intervals, denoted for example by colour coding on the anchor lines 19 and/or on the sheet 10, a side anchor 25 is secured to the respective outside anchor lines 19a and 19c by respective anchoring straps 24 and using a carabiner clip fastening 28 which clips around the anchor line and passes through an aperture 26 formed in the sheet 10 along one of the fold lines 27. Finally, three trailing anchors 40 secured by straps (omitted for the sake of clarity) to the opposite ends of the respective lines 19a, 19b, 19c are driven into the sea bed to complete the anchoring process.

With the structure 10 anchored to the sea bed in the path of an underwater current, the velocity of the current will be reduced below the critical transport velocity so as to ensure particle deposition. Accordingly, substantially all the fines carried by the current will be deposited within the structure and a permanent consolidated sandbank will be created having a particularly uniform distribution of reinforcement.

In particular, it can be seen that the fronds present an almost solid wall in every direction, and once the fines enter the V-shaped pockets formed by the successive sections of the folded sheet they are virtually trapped since there are no clear cur-

rent flow paths through the structure.

The base pitch between successive sections might be of the order of 20mm giving 50 frond lines per linear metre. This density can be easily varied by adjusting the spacing between the grommets 21. As illustrated, the grommets 21 are arranged so that the interleaved V-shaped pockets formed between the successive sections 14 extend from one side of the structure to the other in alternating directions. However, the grommets 21 can be adjusted to provide any required pattern of pockets. In particular, the grommets on the centre anchor line 19b could be adjusted to provide a different pattern in which the pockets terminate at the centre line.

In the alternative arrangement of Fig. 2, the base pitch is fixed by the length of the foldable inter-sheet links 41.

The front anchor plate 22 and the side anchor plate 25 with their respective anchoring straps 24 are stored on top of the box 13 one behind the other so that they are easily accessible when deploying the structure on the sea bed.

Claims

1. An underwater soil retention and reinforcement structure comprising a sequence of synthetic buoyant fronds (11) arranged side-by-side to form a frond line, characterised in that the line is folded back and forth to form an array of fronds, and the successive folded sections (14) of the frond line have aligned openings (20) threaded by at least one anchor line (19) for anchoring the array to the soil bed (12).
2. A structure according to claim 1 further comprising means (21, 41) for controlling the pitch or spacing between the successive folded sections (14) of the frond line.
3. A structure according to claim 2 in which the control means comprises spacing elements (21) slidable along the respective anchor lines (19).
4. A structure according to claim 2 in which the control means comprises foldable links (41) between the successive folded sections (14).
5. A structure according to any one of the claims 1-4 in which a ground anchor (22) is secured at one or both ends of each anchor line (19), the structure being anchored by driving the ground anchors into the soil bed (12).
6. A structure according to claim 5 further comprising means for releasably attaching at least



one additional ground anchor (25) to at least one of the anchor lines (19) at a point intermediate the ends of the anchor line.

7. A structure according to any one of the preceding claims wherein the frond line comprises a continuous sheet (10) of synthetic buoyant material.
8. A structure according to claim 7 wherein the anchor line (19) is threaded through a reinforced base portion (18) of the sheet (10).
9. A structure according to claim 8 in which the reinforced portion (18) of the sheet (10) comprises an upturned bottom edge.
10. A structure according to claim 9 in which a flexible reinforcing member (17) is encased within the upturned bottom edge portion of the sheet (10).
11. A method of deploying an underwater soil retention and reinforcement structure, the structure comprising a line of buoyant fronds folded back and forth and threaded by at least one anchor line (19), and characterised in that the method comprises retaining each anchor line in a box-like dispenser (13) with the folded sections (14) of the frond line in a bunched, compact state, and the fronds lying flat, lowering the dispenser (13) to the soil bed (12), anchoring one end of each anchor line (19) to the soil bed (12), and thereafter advancing the dispenser (13) over the soil bed (12) such that the anchor line (19) is progressively withdrawn from the dispenser and the fronds (11) are released into an upright buoyant state.
12. A method according to claim 11 further comprising increasing the pitch or spacing between the successive folded sections (14) of the frond line along the anchor line (19) as the anchor line is withdrawn from the dispenser (13).

Patentansprüche

1. Unterwasserstruktur zum Festhalten und Verstärken des Bodens, die eine Folge von zur Bildung einer Wedelreihe nebeneinander angeordneten synthetischen schwimmenden Wedeln (11) umfaßt, dadurch gekennzeichnet, daß die Reihe zur Bildung einer Wedelanordnung ziehharmonikaartig gefaltet ist, und die aufeinanderfolgenden gefalteten Abschnitte (14) der Wedelreihe fluchtende Öffnungen (20) aufweisen, durch die zur Verankerung der Anordnung

mit dem Bodenbett (12) mindestens eine Ankerleine (19) gezogen ist.

2. Struktur nach Anspruch 1, die weiterhin Mittel (21, 41) zur Steuerung des Zwischenraums oder Abstands zwischen den aufeinanderfolgenden gefalteten Abschnitten (14) der Wedelreihe umfaßt.
3. Struktur nach Anspruch 2, bei der das Steuermittel Abstandselemente (21) umfaßt, die entlang den jeweiligen Ankerleinen (19) gleiten können.
4. Struktur nach Anspruch 2, bei der das Steuermittel zwischen den aufeinanderfolgenden gefalteten Abschnitten (14) faltbare Verbindungsglieder (41) umfaßt.
5. Struktur nach einem der Ansprüche 1-4, bei der ein Erdanker (22) an einem oder beiden Enden jeder Ankerleine (19) befestigt ist, wobei die Struktur durch Eintreiben der Erdanker in das Bodenbett (12) verankert wird.
6. Struktur nach Anspruch 5, die weiterhin Mittel zum lösbaren Anbringen mindestens eines zusätzlichen Erdankers (25) an mindestens einer der Ankerleinen (19) an einem zwischen den Enden der Ankerleine liegenden Punkt umfaßt.
7. Struktur nach einem der vorhergehenden Ansprüche, bei der die Wedelreihe eine durchgehende Tafel (10) aus synthetischem schwimmenden Material umfaßt.
8. Struktur nach Anspruch 7, bei der die Ankerleine (19) durch einen verstärkten Basisteil (18) der Tafel (10) gezogen wird.
9. Struktur nach Anspruch 8, bei der der verstärkte Teil (18) der Tafel (10) eine umgebogene Unterkante umfaßt.
10. Struktur nach Anspruch 9, bei der ein flexibles Verstärkungsglied (17) in dem umgebogenen Unterkantenteil der Tafel (10) untergebracht ist.
11. Verfahren zum Anbringen einer Unterwasserstruktur zum Festhalten und Verstärken des Bodens, wobei die Struktur eine Reihe von ziehharmonikaartig gefalteten schwimmenden Wedeln umfaßt, die von mindestens einer Ankerleine (19) durchzogen sind, dadurch gekennzeichnet, daß es das Halten jeder Ankerleine in einer kastenartigen Ausgabevorrichtung (13) umfaßt, wobei sich die gefalteten Abschnitte (14) der Wedelreihe in einem ge-



bündelten, kompakten Zustand befinden und die Wedel flach liegen, das Absenken der Ausgabevorrichtung (13) zum Bodenbett (12), das Verankern eines Endes jeder Ankerleine (19) mit dem Bodenbett (12) und danach das Vorwärtsbewegen der Ausgabevorrichtung (13) über dem Bodenbett (12), so daß die Ankerleine (19) nach und nach aus der Ausgabevorrichtung gezogen wird und die Wedel (11) in einen aufrecht schwimmenden Zustand freigesetzt werden.

12. Verfahren nach Anspruch 11, das weiterhin beim Herausziehen der Ankerleine aus der Ausgabevorrichtung (13) das Vergrößern des Zwischenraums oder Abstands zwischen den aufeinanderfolgenden gefalteten Abschnitten (14) der Wedelreihe entlang der Ankerleine (19) umfaßt.

Revendications

1. Structure immergée de rétention et de renforcement du sol comprenant une série de frondes flottantes synthétiques (11) arrangées côte à côte pour former une ligne de frondes, caractérisée en ce que la ligne est pliée en accordéon pour former un arrangement de frondes, et les portions pliées successives (14) de la ligne de frondes ont des ouvertures alignées (20) dans lesquelles est enfilé au moins un câble d'ancrage (19) pour ancrer l'arrangement au lit du sol (12).
2. Structure selon la revendication 1, comprenant en outre un moyen (21, 41) pour contrôler l'écartement ou l'espacement entre les portions pliées successives (14) de la ligne de frondes.
3. Structure selon la revendication 2, dans laquelle le moyen de contrôle comprend des éléments d'espacement (21) pouvant coulisser le long des câbles d'ancrage respectifs (19).
4. Structure selon la revendication 2, dans laquelle le moyen de contrôle comprend des liens pliables (41) entre les portions pliées successives (14).
5. Structure selon l'une quelconque des revendications 1 à 4, dans laquelle un tirant d'ancrage (22) est fixé à une ou aux deux extrémités de chaque câble d'ancrage (19), la structure étant ancrée en enfonçant les tirants d'ancrage dans le lit du sol (12).

6. Structure selon la revendication 5, comprenant en outre un moyen pour attacher de manière détachable au moins un tirant d'ancrage supplémentaire (25) à au moins un des câbles d'ancrage (19) en un point entre les extrémités du câble d'ancrage.

7. Structure selon l'une quelconque des revendications précédentes, dans laquelle la ligne de frondes comprend une feuille continue (10) de matériau flottant synthétique.

8. Structure selon la revendication 7, dans laquelle le câble d'ancrage (19) est enfilé dans une portion de base renforcée (18) de la feuille (10).

9. Structure selon la revendication 8, dans laquelle la portion renforcée (18) de la feuille (10) comprend un bord inférieur replié vers le haut.

10. Structure selon la revendication 9, dans laquelle un organe de renforcement flexible (17) est encastré dans la portion de bord inférieur replié vers le haut de la feuille (10).

11. Procédé de déploiement d'une structure immergée de rétention et de renforcement du sol, la structure comprenant une ligne de frondes flottantes pliée en accordéon et dans laquelle est enfilé au moins un câble d'ancrage (19), et caractérisé en ce que le procédé comprend la rétention de chaque câble d'ancrage dans un distributeur de type boîte (13), les portions pliées (14) de la ligne de frondes étant à l'état compact en paquet, et les frondes étant à plat, l'abaissement du distributeur (13) jusqu'au lit du sol (12), l'ancrage d'une extrémité de chaque câble d'ancrage (19) au lit du sol (12), puis l'avance du distributeur (13) le long de la surface du lit du sol (12) de telle sorte que le câble d'ancrage (19) soit extrait progressivement du distributeur et que les frondes (11) soient dégagées pour flotter verticalement.

12. Procédé selon la revendication 11, comprenant en outre l'augmentation de l'écartement ou de l'espacement entre les portions pliées successives (14) de la ligne de frondes le long du câble d'ancrage (19) au fur et à mesure que le câble d'ancrage est extrait du distributeur (13).