

DESCRIPTION

METHOD FOR DYEING OR BLEACHING THE HAIR

TECHNICAL FIELD

5 [0001]

The present invention relates to a hair dyeing or bleaching method using a two-part hair dye or bleach composition.

BACKGROUND ART

10 [0002]

Two-part hair dye compositions or two-part hair bleach compositions which include a first agent containing an alkaline agent and a second agent containing hydrogen peroxide are widely used. Generally, such a two-part hair dye or bleach composition is an agent in the form of a gel or cream which has a post-mixing viscosity of about several thousand to several tens of thousand mPa·s so that after applying on the hair the agent does not trickle down while being left.

20 [0003]

To carry out hair dyeing or bleaching without any unevenness using a gel- or cream-formed two-part hair dye or bleach composition, first the first and second agents have to be vigorously shaken or mixed in a mixing container in order to carefully mix them. Furthermore, to carry out hair dyeing or bleaching without any unevenness

using a gel- or cream-formed two-part hair dye or bleach composition, since the mixed solution has a high viscosity as mentioned above, not only skill is required, but the hair must be "pre-blocked" (in other words, the hair must be braided into sections at the front, sides, and rear of the head). Thus, required are a lot of time and effort to carry out such dyeing or bleaching.

[0004]

On the other hand, two-part dye or bleach compositions are known which contain a surfactant in at least one of the first or second agents as a foaming agent so that the mixed solution of the first and second agents is discharged in a foam from a foamer container (Patent Documents 1 and 2). According to this two-part dye or bleach composition, by discharging the mixed solution of the first and second agents in a foam, the mixed solution can be simply applied on the hair without any unevenness. This allows a finish without any unevenness to be more easily obtained compared with when coating a gel- or cream-formed two-part hair dye or bleach composition.

[0005]

Patent Document 1: JP-A-2004-339216

Patent Document 2: JP-A-2006-124279

25 DISCLOSURE OF THE INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

[0006]

In the case of using a squeeze container to discharge the mixed solution of the first and second agents of a two-part hair dye or bleach composition in a foam which is applied on the hair, the foam of the mixed solution has to be able to be easily spread over all of the hair. In addition, the foam quality also has to be formed with a fine texture to prevent drips from being formed after applying the foam of the mixed solution on the hair during the approximately 30 minutes that is usually required for them to be left. Furthermore, it is necessary to stably discharge the mixed solution in a foam from start to finish of its use.

[0007]

In contrast, it is an object of the present invention to obtain a finish with dramatically less color unevenness when using a squeeze container to discharge a mixed solution of the first and second agents of a two-part hair dye or bleach composition in a foam by enabling fine foam to be stably discharged from start to finish.

MEANS FOR SOLVING THE PROBLEMS

[0008]

The present inventors discovered that when mixing the first and second agents of a two-part hair dye or bleach composition and discharging the resultant mixture in a foam from a squeeze container, by using a squeeze

container equipped with a specific squeeze foamer, using first and second agents which produce a mixed solution with a viscosity in a specific range, and mixing the first and second agents so as not to produce a foam, the mixed solution which is subsequently discharged in a foam has greatly improved foam qualities, and can be stably discharged until the finish, thus enabling a finish with dramatically less color unevenness to be obtained. As a result of this discovery, the present inventors completed the present invention.

[0009]

Specifically, the present invention provides a method for hair dyeing or bleaching using a two-part hair dye or bleach composition which is applied on hair containing

discharging in a foam from a squeeze container a mixed solution of a first agent containing an alkaline agent and a second agent containing hydrogen peroxide, wherein

the squeeze container is used which includes a container body and a squeeze foamer, the squeeze foamer having a gas-liquid mixing chamber for causing the mixed solution to foam by mixing air in the container body with the mixed solution, foam homogenizing means for homogenizing foam of the mixed solution which has been made to foam in the gas-liquid mixing chamber, and a discharge outlet for discharging

the homogenized foam,

at least one of the first or second agents contains
a foaming agent, the mixed solution of the first and
second agents has a viscosity (25°C) of from 1 mPa·s
5 to 100 mPa·s,

mixing the first and second agents in the container body
of the squeeze container so as not to produce a foam, and
carrying out squeezing with the squeeze container stood
upright so that the mixed solution does not reach an air
10 induct path of the squeeze foamer.

EFFECT OF THE INVENTION

[0010]

In the present invention, a specific squeeze
container is used for the foamer container. In this
15 squeeze container, fine foam cannot be discharged if the
air induct path of the squeeze foamer is blocked by the
mixed solution or the foam of the mixed solution during
squeezing. However, if the mixed solution does not
produce a foam in the container body, and, if the air
20 induct path is not blocked by the mixed solution or foam
of the mixed solution, fine foam can be discharged.

[0011]

Furthermore, in the present invention, the mixed
solution of the first and second agents of the two-part
25 hair dye or bleach composition has a viscosity within a
specific range. The first and second agents both have a

viscosity which is considerably lower than the conventional gel or cream. Thus, the first and second agents can be homogenously mixed without having to vigorously shake the container in which they are filled, just by slowly switching the up/down positions of the container so that their mixed solution does not produce a foam.

[0012]

Therefore, according to the present invention, by mixing the first and second agents so as not to produce a foam, and using the squeeze container while it is standing upright so that the mixed solution or the foam of the mixed solution do not reach the upper aperture of the container body so that the air induct path of the squeeze foamer is not covered by the mixed solution, fine foam can be stably discharged.

[0013]

Thus, according to the method for hair dyeing or bleaching using a two-part hair dye or bleach composition of the present invention, a foamy mixed solution can be easily spread over all of the hair, enabling a finish without any color unevenness to be obtained. Furthermore, the problem of drips being formed while the foamy mixed solution is left after being applied on the hair can be resolved.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014]

Fig. 1A is a schematic view of the two-part hair dye or bleach composition used in the present invention prior to the mixing of the first and second agents;

Fig. 1B is a schematic view of the two-part hair dye or bleach composition used in the present invention after the first and second agents have been mixed;

Fig. 2 is a cross-sectional view of a squeeze container;

Fig. 3 is an explanatory diagram of the upright direction of the squeeze container;

Fig. 4 is a cross-sectional view of the squeeze container when being squeezed; and

Fig. 5 is a schematic view of the squeeze container after the first and second agents have been mixed.

DESCRIPTION OF THE REFERENCE NUMERALS

[0015]

- 1 two-part hair cosmetic for hair dyeing or bleaching
- 20 2 first container
- 3 second container
- 4 container body of second container or container body of squeeze container
- 5 squeeze foamer
- 25 6, 6B squeeze container
- 7 cap member

- 8 head member
- 10 mixing device
- 11 gas-liquid mixing chamber
- 12 air induct path
- 5 13 dip tube
- 14 foam homogenizing means
- 15 liquid path
- 16 liquid path
- 17 discharge outlet
- 10 18 foam homogenizing means
- 19 gap
- 20 check valve
- A1 first agent
- A2 second agent
- 15 A3 mixed solution

MODE FOR CARRYING OUT THE INVENTION

[0016]

The present invention will now be described in more
20 detail while referring to the drawings. It is noted that
in the drawings, the same reference numerals represent the
same or similar structural elements.

[0017]

Fig. 1A is a schematic view of one embodiment of a
25 two-part hair cosmetic 1 for hair dyeing or bleaching
including the two-part hair dye or bleach composition used

in the present invention and a squeeze container. Fig. 1A illustrates a pre-mixed state of the first and second agents. Fig. 1B illustrates a post-mixed state of the first and second agents of this two-part hair dye or
5 bleach composition.

[0018]

As illustrated in Fig. 1A, this two-part hair cosmetic 1 for hair dyeing or bleaching includes a first agent A1 filled in a first container 2, a second agent A2
10 filled in a second container 3, and a squeeze foamer 5. The container body 4 of the second container 3 also serves as the container body of the squeeze container. As illustrated in Fig. 1B, a squeeze container 6 is constituted of the container body 4 and the squeeze foamer
15 5. Here, the squeeze container is preferably such a container as causes a mixed solution to foam by mixing the mixed solution with air in the same container body. Examples of such a squeeze container include a container like the squeeze container 6 illustrated in Fig. 1B, which
20 discharges its contents while in an upright manner (for example, "S1 Squeeze Foamer", manufactured by Daiwa Can Company). Further examples include a container such as the squeeze container 6B illustrated in Fig. 5, which is provided with a check valve (not shown) in the discharge
25 path of the liquid so that it can discharge its contents either in an upright or inverted manner, since when the

container is standing upright the portion which is the air induct path becomes the liquid induct path when inverted, while the dip tube which is the liquid induct path when the container is standing upright becomes the air induct path when inverted (for example, "Squeeze Foamer RF-270" manufactured by Toyo Seikan Kaisha, Ltd.). From the perspective of the discharge performance of the foam, a squeeze container which can discharge its contents in an upright manner as illustrated in Fig. 1B is preferred.

10 [0019]

The concept of the "two-part hair dye or bleach composition" in the present invention includes hair dye or bleach compositions which contain a first agent and a second agent and which are used by mixing these agents at the time of use. In the case of a hair dye composition, the first agent A1 contains an alkaline agent and a dye, and the second agent A2 contains hydrogen peroxide. Furthermore, in the case of a hair bleach composition, the first agent A1 contains an alkaline agent but not a dye, and the second agent A2 contains hydrogen peroxide. In addition, this concept also includes embodiments wherein a third agent containing a persulfate is used. In such a case, the first, second, and third agents are used by mixing together.

25 [0020]

Here, as the alkaline agent contained in the first

agent A1, ammonia, an alkanolamine such as monoethanolamine, sodium hydroxide, and potassium hydroxide can be used. Furthermore, a buffer may be appropriately added, for example, an ammonium salt such as ammonium hydrogencarbonate and ammonium chloride, and a carbonate such as potassium carbonate and sodium hydrogencarbonate.

[0021]

The concentration of the alkaline agent can be appropriately set so that the pH in the mixed solution A3 of the first agent A1 and the second agent A2 is from 8 to 12, and preferably from 9 to 11.

[0022]

On the other hand, the concentration of the hydrogen peroxide in the second agent A2 is preferably in the range of from 1 mass% to 9 mass%, and more preferably in the range of from 3 mass% to 6 mass%. The hydrogen peroxide concentration in the mixed solution of the first agent A1 and the second agent A2 is preferably in the range of from 1 mass% to 6 mass%, and more preferably in the range of from 2 mass% to 5 mass%. Furthermore, to suppress decomposition of the hydrogen peroxide, the pH of the second agent A2 is preferably in the range of from 2 to 6, and more preferably in the range of from 2.5 to 4.

[0023]

Both the first agent A1 and the second agent A2

preferably have water as their main solvent.

[0024]

At least one of the first agent A1 or the second agent A2 used in the present invention contains a foaming agent. This enables the mixed solution A3 of the first agent A1 and the second agent A2 to easily foam by discharging the mixed solution A3 from the squeeze container 6. Furthermore, the produced foam has a longer life. Although the foaming agent may be anything so long as it has foaming properties, a surfactant is preferable. Examples of the surfactant include nonionic surfactants, anionic surfactants, cationic surfactants, ampholytic surfactants, semipolar surfactants, and the like. Among these, the use of an anionic surfactant is preferred, and using together with an ampholytic surfactant as well is more preferred. Examples of the anionic surfactant include an alkylsulfate, polyoxyethylenealkylethersulfate and the like. Examples of the ampholytic surfactant which can be used include fatty acid amidopropyl betaine, alkyldimethylamine oxide, alkylcarboxymethyl hydroxyethyl imidazolinium betaine, alkyldimethylaminoacetic acid betaine and sulfobetaine.

[0025]

Furthermore, generally, considering that the first agent A1 in many cases contains ammonia or a carbonate and has a high ionic strength, to solubilize the dye or to

improve the sense of feel, the first agent A1 preferably contains a nonionic surfactant, such as a polyoxyethylenealkylether, an alkylpolyglucoside, and an alkylalkanolamide. Among these, an alkylpolyglucoside or
5 polyoxyethylenealkylether are preferred. More specifically, preferred examples of the alkylpolyglucoside have 8 to 14 carbon atoms on the alkyl group and an average degree of condensation of the glucoside of 1 to 2. Furthermore, preferred examples of the
10 polyoxyethylenealkylether have 10 to 18 carbon atoms on the alkyl group and an average degree of polymerization of the polyoxyethylene of 5 to 40.

[0026]

Furthermore, the second agent A2 may also contain a
15 nonionic surfactant, such as a polyoxyethylenealkylether, an alkylpolyglucoside, and an alkylalkanolamide, and a cationic surfactant, such as alkyltrimethylammonium chloride and dialkyldimethylammonium chloride in order to improve the sense of feel.

20 [0027]

When the two-part hair dye or bleach composition is for hair dyeing, the dye contained in the first agent A1 may be an oxidation dye or a direct dye. Examples of the oxidation dye include: dye precursors, such as para-
25 phenylenediamine, para-aminophenol, toluene-2,5-diamine, N,N-bis(2-hydroxyethyl)para-phenylenediamine, 2-(2-

hydroxyethyl)para-phenylenediamine, 4-amino-3-methylphenol, 6-amino-3-methylphenol, ortho-aminophenol and 1-hydroxyethyl-4,5-diaminopyrazole; couplers, such as resorcin, 2-methylresorcin, meta-aminophenol, para-amino-5 ortho-cresol, 5-(2-hydroxyethylamino)-2-methylphenol, meta-phenylenediamine, 2,4-diaminophenoxyethanol, and 1-naphthol; and the like. Examples of the direct dye include para-nitro-ortho-phenylenediamine, para-nitro-meta-phenylenediamine, basic yellow 87, basic orange 31, 10 basic red 12, basic red 51, basic blue 99, acid orange 7, and the like.

[0028]

It is preferred that at least one of the first agent A1 or the second agent A2 contains a higher alcohol, since 15 this improves the life of the foam of the mixed solution discharged from the squeeze container 6, and suppresses drips from forming when the foam collapses after being applied on the hair. The higher alcohol preferably has 14 to 24 carbon atoms. Examples thereof include myristyl 20 alcohol, cetyl alcohol, stearyl alcohol, behenyl alcohol, isostearyl alcohol, oleyl alcohol, and the like. These can be used as a combination of two kinds or more. Furthermore, these can be contained, based on the whole composition for hair dyeing after the first and second 25 agents have been mixed, in an amount of 0.01 mass% to 3 mass%, preferably 0.1 mass% to 2 mass%, more preferably

0.2 mass% to 1 mass% and even more preferably 0.3 mass% to 0.8 mass%.

[0029]

In addition, the first agent A1 and the second agent
5 A2 may contain various additives as required. For example,
to prevent the scalp from being irritated by an irritant
component, such as hydrogen peroxide, which becomes more
concentrated due to moisture evaporation after the mixed
solution A3 of the first agent A1 and the second agent A2
10 is applied on the hair, addition of a nonvolatile,
hydrophilic solvent, such as a polyol or lower alkyl ether
thereof thereto are preferred. Furthermore, to give a
conditioning effect to the hair, an ampholytic or cationic
polymer, or a silicone and the like are also preferably
15 added. Also they may appropriately contain a perfume
material, an ultraviolet ray absorbent, a metal
sequestering agent such as edetic acid, an antiseptic, a
germicide such as methyl paraoxybenzoate, a stabilizing
agent such as dibutylhydroxytoluene, 1-hydroxyethane-1,1-
20 diphosphonic acid and sulfuric acid oxyquinoline, an
organic solvent such as ethanol, benzyl alcohol and
benzyloxy ethanol, a water-soluble polymer compound such
as and hydroxyethylcellulose, a moisturizer, and the like.
[0030]

25 Furthermore, the viscosity (25°C) of the first agent
A1 is preferably in the range of from 1 mPa·s to 50 mPa·s,

more preferably in the range of from 3 mPa·s to 40 mPa·s, and even more preferably in the range of from 5 mPa·s to 30 mPa·s. The viscosity (25°C) of the second agent A2 is preferably in the range of from 1 mPa·s to 300 mPa·s, more
5 preferably in the range of from 3 mPa·s to 200 mPa·s, and even more preferably in the range of from 5 mPa·s to 100 mPa·s. The viscosity (25°C) of the mixed solution A3 of the first agent A1 and the second agent A2 is in the range of from 1 mPa·s to 100 mPa·s, preferably in the range of
10 from 3 mPa·s to 50 mPa·s, and more preferably in the range of from 5 mPa·s to 30 mPa·s. It is noted that these viscosity values are found using a B-type rotary viscometer (Model TV-10) with the No. 1 rotor manufactured by Tokimec Inc., after rotating the rotor for 1 minute.
15 Measurement is carried out at a rotation speed of 60 rpm when the measuring target has a viscosity of 100 mPa·s or less, 30 rpm when the measuring target has a viscosity of from 100 mPa·s to 200 mPa·s, and 12 rpm when the measuring target has a viscosity of 200 mPa·s to 500 mPa·s. The
20 viscosities of the first agent, second agent and mixed solution are taken as the values measured in a 25°C thermostat bath. Furthermore, in the case of the mixed solution, the value measured immediately after mixing is used, and any temperature change due to heat of reaction
25 is ignored. By setting the viscosity of the mixed solution in the above range, the mixed solution can be

homogenously mixed without producing a foam. Furthermore, homogenous foam can be obtained which are easily applied on the hair, react well with the hair, and which do not easily form drips after being applied on the hair.

5 [0031]

Adjustment of the viscosities of the first agent A1, second agent A2 and their mixed solution A3 to within the above ranges can be carried out by adding a water-soluble solvent such as ethanol to the first agent A1 and the
10 second agent A2, or by appropriately adjusting the kind or added amount of the above-described surfactant, polyol or higher alcohol.

[0032]

Further, the squeeze container 6 for causing the
15 two-part hair dye or bleach composition to foam has the same basic structure as a known squeeze container disclosed in, for example, JP-A-1995-215352. As illustrated in Fig. 2, the squeeze container 6 is composed of a flexible container body 4 and a squeeze foamer 5.
20 The squeeze foamer 5 is composed of a cap member 7 attached to an aperture of the container body 4, and a head member 8 which sits over the cap member 7.

[0033]

A mixing device 10 is fitted to the cap member 7 so
25 as to hang down from the cap member 7. In the interior of the mixing device 10 are provided a gas-liquid mixing

chamber 11, and an air induct path 12 through which the interior space in the container body 4 and the gas-liquid mixing chamber 11 are in communication with each other. Furthermore, in the mixing device 10, a dip tube 13 is
5 fitted which extends into the container body 4. A net is attached to the ceiling of the gas-liquid mixing chamber 11 as foam homogenizing means 14, and the head member 8 side of the foam homogenizing means 14 serves as a liquid path 15.

10 [0034]

On the other hand, on the head member 8 are provided a liquid path 16 connecting to the liquid path 15 of the cap member 7, and a discharge outlet 17 connecting to the liquid path 16. Furthermore, a net is provided in the
15 liquid path 16 in the vicinity of the discharge outlet 17 as foam homogenizing means 18.

[0035]

In the present invention, the foam homogenizing means 14 and 18 of the gas-liquid mixing chamber and the
20 discharge outlet are not limited to a net. A porous material such as a sponge or a sintered body may also be used.

[0036]

One method for using such a two-part hair dye or
25 bleach composition is to, during use, first transfer the whole amount of the first agent A1 filled in the first

container 2 to the container body 4 of the second container 3 filled with the second agent A2 to prepare the mixed solution A3. However, in the present invention this mixing is carried out so that the mixing of the first agent A1 and the second agent A2 produces as little foam as possible, or so that no foam are produced. Here, "not producing foam" or "no foam is produced" are a concept which excludes the intentional production of foam, but includes cases where a small amount of foam is unintentionally produced when the mixing is carried out like in the specific examples illustrated below. As long as a foam is not produced during the mixing, there are no restrictions on the mixing method. Examples of such methods include mixing carried out by shaking a test tube, or by moving the container body 4 from a roughly upright state to an inverted through sideways state, and then once again returning to a roughly upright state. More specifically, the lid of the second container 3 is put on the container body 4 containing the first agent A1 and the second agent A2, and the cycle of moving the container body 4 from a roughly upright state to an inverted through sideways state, and then once again returning to a roughly upright state, may be carried out 1 to 30 times, preferably 1.5 to 20 times, and more preferably 2 to 10 times, in 10 seconds. The operation of moving from a roughly upright state to an inverted though sideways state,

and then once again returning to a roughly upright state is carried out 1 to 15 times, preferably 2 to 10 times, and more preferably 3 to 7 times. A uniform mixed solution A3 can be easily obtained without a foam being produced even if the container body 4 is slowly shaken in this manner, since the first agent A1 and the second agent A2 used in the present invention have a much lower viscosity than a gel or cream type agent.

[0037]

10 As illustrated in Fig. 1B, after the first agent A1 and the second agent A2 have been mixed, the squeeze foamer 5 is attached to the container body 4. It is noted that the mixing of the first agent A1 and the second agent A2 may also be carried out by transferring the whole
15 amount of the first agent A1 to the container body 4 of the second container filled with the second agent A2, then attaching the squeeze foamer 5 to the container body 4 in place of the lid of the second container 3, and slowly shaking the container body 4 by a mixing method like that
20 of shaking a test tube.

Then, the container body 4 is held in one hand and squeezed.

[0038]

During this squeezing, the container body 4 is
25 squeezed while stood upright so that the mixed solution A3 or the foam of the mixed solution does not reach the upper

aperture of the container body 4, specifically, so that the air induct path 12 is not blocked by the mixed solution A3 or the foam of the mixed solution. Although the upright direction of the container body 4 at this stage depends on the proportion of mixed solution A3 in the container body 4, as illustrated in Fig. 3, the direction may be set so that the angle θ formed with the vertical direction is in the range of from 0° to 60° , preferably in the range of from 5° to 50° and more preferably in the range of from 10° to 40° . As a result, as illustrated in Fig. 4, the mixed solution A3 in the container body 4 is pushed up in the direction of the arrow into the gas-liquid mixing chamber 11 via the tube 10. Since this also results in the air in the container body 4 being pushed into the gas-liquid mixing chamber 11 via the air induct path 12, in the gas-liquid mixing chamber 11, the mixed solution A3 foams, and the mixed solution A3 is discharged in a foam from the discharge outlet 17 via the two-stage foam homogenizing means 14 and 18.

[0039]

Furthermore, it is preferred to squeeze this container body 4 slowly, so that the time required for one squeeze from the start of pushing the container body 4 until a fully pushed state is in the range of from 0.5 seconds to 5 seconds, preferably in the range of from 1

seconds to 4 seconds, and more preferably in the range of from 2 seconds to 3 seconds. As a result, the foam quality of the mixed solution A3 is stable.

[0040]

5 Concerning the level of shape change of the container body 4 during squeezing, to increase the discharge amount of the mixed solution A3 from one squeeze, it is preferred to squeeze so that both opposing sides of the container body 4 touch each other. On the other hand,
10 to squeeze with a suitably modified force in the vicinity of the middle in the height direction of the container body 4 with one's dominant hand, it is preferred to squeeze so to about 1/3 to 2/3 of the thickness in the minor axis direction.

15 [0041]

 Once the squeezing of the container body 4 is released, external air flows into the head member 8 from a gap 19 between the cap member 7 and the head member 8. Since this air enters the container body 4 via a check
20 valve 20, the container body 4 is restored to its shape prior to squeezing, thereby allowing repeated squeezing. Thus, by repeating the squeezing 1 to 3 times, a lemon-sized amount of foam of the mixed solution A3 easy to handle in one hand can be discharged.

25 [0042]

 The discharged foam of the mixed solution A3 is

collected in the palm of a gloved hand and are, for example, rubbed into the hair as upon using shampoo. It is also preferred to apply the foam to the hair so that the foam is further foamed. When applying the foam to all
5 the hair, it is preferable to cover all the hair with the foam. From the perspective of preventing un-dyed portions, it is preferable to apply a larger amount of the foam of the mixed solution A3 on the hairline or parted areas than other areas. Furthermore, from the perspective of
10 preventing drips and un-dyed portions, it is preferable to rub the hairline or parted areas in a circular motion.
[0043]

In this case, the blocking operation which is conventionally, normally carried out by coating a hair dye
15 composition is unnecessary. By rubbing the foam of the mixed solution A3 by hand, the foam can be spread from the roots to the tips of the hair in a short period of time. Therefore, color unevenness due to differences in time from after applying the foam of the mixed solution A3 on
20 the hair until washing off is less likely to occur. In addition, since the foam of the mixed solution A3 is applied so as to foam further, drip formation caused by the applied foam collapsing can be suppressed.
[0044]

25 Furthermore, since the foam can be spread on the hair in a short period of time, the foam of the mixed

solution A3 can be applied from any part of the hair.

This means that, as being different from in the case of using conventional liquid or cream two-part hair dye or bleach compositions, it is no longer necessary to apply

5 such compositions from the neckline. The foam of the mixed solution A3 can be applied from a desired area.

Usually, it is preferable to apply it from the hairline or parted areas.

[0045]

10 After applying the foam of the mixed solution A3 on the hair in this manner, the hair can be subjected to hair dyeing or bleaching by leaving for a certain time, preferably 3 minutes to 60 minutes, and more preferably 5 minutes to 45 minutes, and then washed off.

15

EXAMPLES

[0046]

The following examples were all carried out at room temperature (25°C).

20 [0047]

Example 1

The first and second agents of the two-part hair dyeing compositions having the blended compositions shown in Tables 1 and 2 were prepared. The viscosity and pH of
25 each of the first and second agents were measured. Also measured were the viscosity and pH of mixed solutions in a

4:6 mass ratio of the first and second agents. Viscosity was measured using a B-type rotary viscometer with the No. 1 rotor by rotating at 30 rpm for 1 minute. The pH was measured using a pH meter (F-52, electrode 9611-10D, manufactured by Horiba, Ltd.). These results are shown in Tables 1 to 3.

[0048]

On the other hand, the squeeze container 6 of Fig. 1B was constituted of a flexible container body 4 and a squeeze foamer ("S1 Squeeze Foamer" manufactured by Daiwa Can Company). This flexible container body 4 was made from polypropylene (PP), and had a resin weight of 17 g and an inner volume of 210 mL. The $2/3$ power coefficient α calculated from this resin weight and inner volume ($\alpha = w/V^{2/3}$) was 0.46. The cross-sectional profile at a height 55 mm from the bottom, which corresponds to the middle in the height direction of the container body 4, was an ellipse (60 mm major axis, 44 mm minor axis, 21 cm² area). The ratio L_a/L_b of minor axis L_a to major axis L_b was 0.72.

[0049]

The container body of this squeeze container was charged with 40 g of the first agent and 60 g of the second agent. Shaking was then carried out by moving the container body from a roughly upright state to an inverted state, and then once again returning to a roughly upright state at a rate of 3 times in 10 seconds. This shaking

was carried out 5 times. As a result of this shaking, the mixed solution of the first and second agents was mixed without producing a foam. A squeeze foamer was then attached.

5 [0050]

Next, the squeeze container was stood upright, and then squeezed for about 3 seconds per squeeze in the vicinity of the middle in the height direction of the container body 4 with a person's dominant hand to about
10 1/2 of the thickness in the minor axis direction to discharge foamy mixed solution. The foam quality was evaluated in the following manner for (a) gas/liquid mixed ratio, (b) foam life, and (c) drips.

[0051]

15 Furthermore, foam discharged in the same manner was applied by rubbing on the hair of a wig (775s (model number) manufactured by Beaulax Co., Ltd. cut to a short hair style (3 cm below the chin)). This squeezing and application were repeated until the foam had been spread
20 over all of the hair. The wig was then left for 30 minutes. At this stage, the coating time of from application start until the start of leaving the foam on the wig was measured (application method 1). Furthermore, separately to this, foam discharged in the same manner was
25 applied by rubbing on the hair of the same type of wig, and foam was further foamed on the hair. This cycle of

applying the foam and further foaming the foam applied was repeated so that the foam was spread over all of the hair. The wig was then left for 30 minutes. At this stage, the coating time of from application start until the start of

5 leaving the foam on the wig was measured (application method 2). After being left for the time required, the foam was washed off, and then the wig was shampooed, rinsed and dried, in this order. The dried hair was evaluated for color unevenness in the following manner.

10 It is noted that the applied amount for both application methods was 75 g.

[0052]

These results are shown in Table 4.

[0053]

15 (1) Foam Quality Evaluation Method

(a) Gas-liquid Mixing Ratio

To remove the top of the mixed solution in the squeeze container, 0.5 g was discharged. Then, 5 g was discharged into a 250 mL graduated cylinder. The gas-

20 liquid mixing ratio (mL/g) was found by dividing the total volume (mL) of the foam and the liquid 1 minute after the initial discharge by 5 g. Using this value, the evaluation was carried out according to the following criteria.

25 "AA": 20 mL/g or more to less than 30 mL/g

"A": 15 mL/g or more to less than 20 mL/g, or 30 mL/g or

more to less than 40 mL/g

"B": 10 mL/g or more to less than 15 mL/g, or 40 mL/g or more to less than 50 mL/g

"C": less than 10 mL/g, or 50 mL/g or more

5 The evaluation criteria were determined from the perspectives of the amount placed on the hand, and the liquor ratio when coated on the hair.

[0054]

(b) Foam Life

10 To remove the top of the mixed solution in the squeeze container, 0.5 g was discharged. Then, 5 g was discharged into a 250 mL graduated cylinder. The portion that had turned back into a liquid 5 minutes after the initial discharge was transferred to a graduated cylinder.

15 This volume was measured and the foam life was evaluated according to the following criteria.

"AA": 0 mL or more to less than 0.6 mL

"A": 0.6 mL or more to less than 1.2 mL

"B": 1.2 mL or more to less than 1.8 mL

20 "C": 1.8 mL or more

[0055]

(c) Drips

 Foam was applied on the hair according to the application method 1 or application method 2. Then, 30
25 minutes after the leaving was started, the state of drips was visually observed, and evaluated on a 3-point scale

according to the following criteria.

"A": No drips formed

"B": A few drips formed (as a guide, the number of drips rolling down from the neckline to the skin)

5 "C": Drips formed (as a guide, liquid was trickling down from the hair tips)

[0056]

(2) Color Unevenness Evaluation Method

Hair which had been subjected to a hair dyeing
10 treatment was evaluated on a 5-point scale according to the following criteria from visual evaluations made by 5 specialist panelists. The average value was used as the evaluation result.

1: Color unevenness clear over a broad range of the hair
15 surface

2: Color unevenness clear on part of the hair surface

3: Dyeing of the hair roots insufficient over all of the hair

4: Dyeing of the hair roots insufficient in part of the
20 hair

5: Hardly any color unevenness over all of the hair

[0057]

[Table 1]

First agent blend component	Blend amount (mass%)
Meta-aminophenol	0.03
Toluene-2,5-diamine	0.18
Resorcin	0.07
5-Amino-ortho-cresol	0.04
2,4-Diaminophenoxyethanol hydrochloride	0.06
Strong ammonia water	6.0
Ammonium hydrogencarbonate	10.5
Decylpoly(1.4)glucoside	6.16
Polyoxyethylene(2) lauryl ether sodium sulfate	2.7
Polyoxyethylene(9) tridecyl ether	0.5
Polyoxyethylene(23) lauryl ether	2.0
Myristyl alcohol	0.2
Propylene glycol	4.0
Ethanol	10.0
Dimethyldiallylammonium chloride/acrylic acid copolymer	0.4
Dimethyldiallylammonium chloride/acrylamide copolymer	0.5
Royal jelly extract	0.01
L-arginine	0.01
Ascorbic acid	0.4
Sodium sulfite anhydride	0.5
Tetrasodium edetate dihydrate	0.1
Perfume	0.95
Purified water	Balance
Viscosity (mPa·s)	14
PH	9.1

[0058]

[Table 2]

Second agent blend component	Blend amount (mass%)
Hydrogen peroxide water (35%)	16.3
Polyoxyethylene(2) lauryl ether sodium sulfate	0.6
Cetanol	0.48
Myristyl alcohol	0.28
Hydroxyquinoline sulfate	0.04
Hydroxyethane diphosphonic acid	0.08
Sodium hydroxide solution	(*1)
Purified water	Balance
Viscosity (mPa·s)	15

(*1): the amount required for adjusting pH to 3.5

5 [0059]

[Table 3]

Mixed solution viscosity (mPa·s)	7
Mixed solution pH	9.0

[0060]

Example 2

10 Evaluation was carried out using a two-part hair dye composition in the same manner as in Example 1, except that the squeeze velocity per squeeze was 1.5 seconds. The results are shown in Table 4.

[0061]

15 Example 3

Evaluation was carried out using a two-part hair dye composition in the same manner as in Example 1, except that the squeezing was performed by tilting so that the

angle formed between the upright direction of the squeeze container and the vertical direction was a slope ($\theta = 60^\circ$). The results are shown in Table 4. It is noted that even though the squeezing was performed by tilting to $\theta = 60^\circ$,
5 the mixed solution did not reach the air induct path of the squeeze foamer.

[0062]

Comparative Example 1

Evaluation was carried out using a two-part hair dye
10 composition in the same manner as in Example 1, except that a squeeze container (lacking a foamer and a dip tube) equipped with a tubular injection nozzle having a diameter which became narrower towards the tip was used instead of a squeeze container including a squeeze foamer, and that
15 the mixed solution was directly discharged on the hair from the squeeze container. The results are shown in Table 4.

[0063]

Comparative Example 2

20 Evaluation was carried out using a two-part hair dye composition in the same manner as in Example 1, except that when mixing the first and second agents, the mixed solution was made to produce a foam in the squeeze container by carrying out a shaking operation of moving
25 the container body from a roughly upright state to an inverted through sideways state, and then once again

returning to a roughly upright state, thirty times at a speed of 4 times per second. The results are shown in Table 4.

[0064]

5 Comparative Example 3

Evaluation was carried out using a two-part hair dye composition in the same manner as in Example 1, except that squeezing was performed by tilting the squeeze container ($\theta = 75^\circ$) so that the mixed solution reached the upper aperture of the container body. The results are shown in Table 4.

[0065]

[Table 4]

	Example 1	Example 2	Example 3	Comparative Example 1	Comparative Example 2	Comparative Example 3
Foam state during mixing of the first and second agents (in the container)	A few foams could be seen on the surface of the mixed solution	A few foams could be seen on the surface of the mixed solution	A few foams could be seen on the surface of the mixed solution	A few foams could be seen on the surface of the mixed solution	A foam was produced as far as the upper aperture of the container body	A foam was produced as far as the upper aperture of the container body
Squeeze speed per squeeze (sec)	3	1.5	3	3	3	3
Standing state of the container during squeezing	Upright ($\theta = 0^\circ$)	Upright ($\theta = 0^\circ$)	$\theta = 60^\circ$	Inverted ($\theta = 180^\circ$)	Upright ($\theta = 0^\circ$)	$\theta = 75^\circ$
Foam quality evaluation (a and b are the average value of three times)						
(a) Gas-liquid mixing ratio (mL/g)	AA 23	A 15	AA 22	C 1	C 3	C 8
(b) Foam life (mL)	AA 0	AA 0.1	AA 0	C 5.0	C 3.8	B 1.3
(c) Drips (application method 1)	A	B	A	C	C	C
(c) Drips (application method 2)	A	A	A	C	B	B
Coating time (min) (application method 1)	8	8	8	15	8	8
Coating time (min) (application method 2)	10	10	10	20	10	10
Hair color unevenness evaluation (application method 1)	4.2	4.0	4.2	3.0	3.2	3.4
Hair color unevenness evaluation (application method 2)	4.8	4.8	4.8	3.6	4.0	4.0

[0066]

From the results of Table 4, it can be seen that if, like in Examples 1 to 3, the first and second agents are mixed without producing a foam, and the mixed solution is applied on the hair by discharging in a foam, the gas-liquid mixing ratio is high, foam life is good, and drips are not formed. However, like in Comparative Example 1, if the foam is applied on the hair just in a liquid state without forming into a foam, drips are formed when a foam is produced on the hair.

[0067]

Furthermore, like in Comparative Example 2, if a foam is produced when mixing the first and second agents, the foam quality of the mixed solution deteriorates, the gas-liquid mixing ratio is low, foam life is poor, and drips tend to form.

[0068]

In addition, like in Comparative Example 3, if the squeeze container is tilted during squeezing so that the mixed solution reaches the upper aperture of the container body, the foam quality of the mixed solution deteriorates, the gas-liquid mixing ratio is low, foam life is poor, and drips tend to form.

[0069]

Moreover, it can be seen that drips are less likely to form and color unevenness less likely to occur by

further producing a foam on the hair so that the foam is spread over all of the hair.

INDUSTRIAL APPLICABILITY

5 [0070]

The method for hair dyeing or bleaching using the two-part hair dye or bleach composition of the present invention enables more pleasant hair dyeing or bleaching.

CLAIMS

1. A method for hair dyeing or bleaching using a two-part hair dye or bleach composition which is applied
5 on hair comprising discharging in a foam from a squeeze container a mixed solution of a first agent containing an alkaline agent and a second agent containing hydrogen peroxide, wherein

the squeeze container is used which includes a
10 container body and a squeeze foamer, the squeeze foamer having a gas-liquid mixing chamber for causing the mixed solution to foam by mixing air in the container body with the mixed solution, foam homogenizing means for homogenizing foam of the mixed
15 solution which has been made to foam in the gas-liquid mixing chamber, and a discharge outlet for discharging the homogenized foam, at least one of the first or second agents contains a foaming agent, the mixed solution of the first and
20 second agents has a viscosity (25°C) of from 1 mPa·s to 100 mPa·s,

mixing the first and second agents in the container body of the squeeze container so as not to foam, and carrying out squeezing with the squeeze container stood
25 upright so that the mixed solution does not reach an air induct path of the squeeze foamer.

2. The method for hair dyeing or bleaching according to claim 1, wherein the cycle of moving the container body containing the first agent and the second agent from a roughly upright state to an inverted through sideways state, and then once again returning to a roughly upright state, is carried out by mixing the first agent and the second agent 1 to 15 times at a speed of 1 to 30 times per 10 seconds.

10

3. The method for hair dyeing or bleaching according to claim 1, wherein the time required for one squeeze is in a range of from 0.5 seconds to 5 seconds.

15

4. The method for hair dyeing or bleaching according to claim 1, wherein the squeeze container can discharge its contents in an upright manner.

5. The method for hair dyeing or bleaching according to claim 4, wherein squeezing is carried out while an angle formed between an upright direction of the squeeze container and a vertical direction is in a range of from 0° to 60°.

25

6. The method for hair dyeing or bleaching according to claim 1, wherein the mixed solution discharged in a

foam is applied from a hairline or a parted area of hair.

7. The method for hair dyeing or bleaching according to claim 1, wherein the mixed solution discharged in a
5 foam is applied on a hairline or a parted area of hair with a larger amount than other areas.

8. The method for hair dyeing or bleaching according to claim 1, wherein the mixed solution discharged in a
10 foam is rubbed into hair.