

METHODS AND ASSOCIATED APPARATUS FOR DOWNHOLE DATA RETRIEVAL, MONITORING AND TOOL ACTUATION

TECHNICAL FIELD

5 The present invention relates generally to operations performed in conjunction with a subterranean well and, in an embodiment described herein, more particularly provides a method and apparatus for downhole retrieval of data, monitoring and tool actuation.

BACKGROUND

10 It is usually the case that a tubular string is installed in a subterranean well with one or more items of equipment interconnected in the tubular string. Thereafter, a tool conveyed into the tubular string may be positioned relative to the item of
15 equipment, engaged with the item of equipment and/or utilized to actuate the item of equipment, etc.

- 2 -

In the past, various mechanisms and methods have been utilized for positioning a tool relative to an item of equipment in a tubular string, for engaging the tool with the item of equipment and for utilizing the tool to actuate the item of equipment. For example, where the item of equipment is a sliding sleeve-type valve, a shifting tool is typically conveyed on wireline, slickline or coiled tubing into the valve and engaged with the sliding sleeve. An operator is aware that the shifting tool is properly positioned relative to the valve due to the engagement therebetween, as confirmed by the application of force to the shifting tool. The shifting tool may be configured so that it operatively engages only the desired sliding sleeve, out of multiple items of equipment installed in the tubular string, by equipping the shifting tool with a particular set of keys or lugs designed to engage only a particular profile formed in the desired sliding sleeve.

Unfortunately, it is often the case that the operator is not able to positively determine whether the shifting tool is properly engaged with the desired sliding sleeve, such as when the well is highly deviated. Additionally, the operator may not accurately know information which would aid in performance of the task of shifting the sleeve. For example, the operator might not know that an excessive pressure differential exists across the sleeve, or the operator might attempt to shift the sleeve to its fully open position

not knowing that this should not be done with an excessive pressure differential across the sleeve. Thus, it may be clearly seen that improved methods of positioning, engaging and actuating tools are needed.

5 Many operations in wells would be enhanced if communication were permitted between an item of equipment installed in a tubular string and a tool conveyed into the string. For example, if a valve was able to communicate its identity to a shifting tool, an accurate determination could be made as to whether the tool should be
10 engaged with the valve. If a valve was able to communicate to the tool data indicative of pressure applied to a closure member of the valve, such as a sliding sleeve, a determination could be made as to whether the tool should displace the closure member, or to what position the closure member should be displaced.

15 Improved communication methods would also permit monitoring of items of equipment in a well. In one application, a tool conveyed into a tubular string could collect data relating to the status of various items of equipment installed in the tubular string. It would be desirable, for example, to be able to monitor the status
20 of a packer seal element in order to determine its remaining useful service life, or to be able to monitor the strain, pressure, etc. applied to a portion of the tubular string, etc.

Therefore, from the foregoing, it may be seen that it would be highly advantageous to provide improved methods and apparatus for downhole data retrieval, monitoring and tool actuation.

SUMMARY

5 In carrying out the principles of the present invention, in accordance with an embodiment thereof, a system for facilitating downhole communication between an item of equipment installed in a tubular string and a tool conveyed into the tubular string is provided. Associated methods of facilitating such downhole
10 communication are also provided, as well as applications in which the downhole communication is utilized for data retrieval, monitoring and tool actuation.

 In one aspect of the present invention, the downhole communication system includes a first communication device
15 associated with the item of equipment and a second communication device included in the tool. Communication may be established between the devices when the device in the tool is brought into sufficiently close proximity to the device associated with the item of equipment.

20 In another aspect of the present invention, the tool supplies power to the first device. Such provision of power by the tool may enable the first device to communicate with the second device. In

this manner, the first device does not need to be continuously powered. The first device may, however, be maintained in a dormant state and then activated to an active state by the tool.

In yet another aspect of the present invention, the
5 communication between the first and second devices may be by any of a variety of means. For example, electromagnetic waves, inductive coupling, pressure pulses, direct electrical contact, etc. may be used. The communication means may also be the means by which power is supplied to the first device.

10 In still another aspect of the present invention, communication between the devices may be used to control operation of the tool. For example, where the item of equipment is a valve and the tool is a shifting tool for displacing a closure member of the valve, communication between the first and second devices
15 may be used to determine whether an excessive pressure differential exists across the closure member. This determination may then be utilized to control the displacement of the closure member by the tool. As another example, the tool may not be permitted to engage the item of equipment until the
20 communication between the devices indicates that the tool is appropriately positioned relative to the item of equipment.

In yet another aspect of the present invention, communication between the devices may be used to monitor a status of the item of

equipment. For example, the first device may be connected to a sensor, such as a pressure sensor, a strain gauge, a hardness sensor, a position sensor, etc., and may transmit data regarding the status to the second device.

5 These and other features, advantages, benefits and objects of the present invention will become apparent to one of ordinary skill in the art upon careful consideration of the detailed description of representative embodiments of the invention hereinbelow and the accompanying drawings.

10 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic partially cross-sectional view of a first apparatus and method embodying principles of the present invention;

FIG. 2 is a schematic partially cross-sectional view of a second
15 apparatus and method embodying principles of the present invention;

FIG. 3 is a schematic partially cross-sectional view of a third apparatus and method embodying principles of the present invention;

20 FIG. 4 is a schematic partially cross-sectional view of a fourth apparatus and method embodying principles of the present invention;

FIGS. 5A&B are schematic partially cross-sectional views of a fifth apparatus and method embodying principles of the present invention;

FIG. 6 is a schematic partially cross-sectional view of a sixth
5 apparatus and method embodying principles of the present invention;

FIG. 7 is an enlarged scale schematic partially cross-sectional view of a portion of the sixth apparatus of FIG. 6; and

FIG. 8 is a schematic partially cross-sectional view of a seventh
10 apparatus and method embodying principles of the present invention.

DETAILED DESCRIPTION

Representatively and schematically illustrated in FIG. 1 is a method 10 which embodies principles of the present invention. In
15 the following description of the method 10 and other apparatus and methods described herein, directional terms, such as "above", "below", "upper", "lower", etc., are used for convenience in referring to the accompanying drawings. Additionally, it is to be understood that the various embodiments of the present invention described
20 herein may be utilized in various orientations, such as inclined, inverted, horizontal, vertical, etc., without departing from the principles of the present invention.

In the method 10, a service tool 12 is conveyed into a tubular string 14 and engaged with an item of equipment or valve 16 interconnected in the string. As representatively illustrated in FIG. 1, the valve 16 is a sliding sleeve-type valve and the tool 12 is utilized to
5 displace a closure member or sleeve 18 of the valve relative to a housing 20 of the valve to thereby permit or prevent fluid flow through one or more openings 22 formed through a sidewall of the housing. However, it is to be clearly understood that a method incorporating principles of the present invention may be performed
10 with other items of equipment and other types of valves, and with other types of service tools.

The sleeve 18 of the representatively illustrated valve 16 has three positions relative to the housing 20. In the closed position of the sleeve 18 as depicted in FIG. 1, the sleeve completely prevents
15 fluid flow through the opening 22. If the sleeve 18 is displaced upwardly until a relatively small diameter opening 24 formed through a sidewall of the sleeve is aligned with the opening 22 in the housing 20, the sleeve is in an equalizing position in which limited fluid flow is permitted through the opening 22. The equalizing
20 position of the sleeve 18 is typically utilized in this type of valve when there is an excessive pressure differential across the sleeve and it is desired to reduce this pressure differential without eroding or damaging seals resisting the pressure differential. If the sleeve 18 is

displaced further upwardly until another opening 26 formed through the sleeve sidewall is aligned with the opening 22 in the housing 20, the sleeve is in an open position in which relatively unrestricted fluid flow is permitted through the opening 22. Of course, it is not necessary in keeping with the principles of the present invention for a valve or other item of equipment to have the positions representatively described above and depicted in FIG. 1.

The tool 12 is utilized to displace the sleeve 18 between the closed, equalizing and open positions as needed to control fluid flow through the opening 22. In order to secure the tool 12 relative to the housing 20, the tool is provided with one or more engagement members, lugs, dogs or keys 28 configured for cooperative engagement with a profile 30 internally formed in the housing. Other means of securing the tool 12 relative to the valve 16, other types of engagement members and other types of profiles may be utilized in the method 10, without departing from the principles of the present invention.

The tool 12 also includes engagement members or dogs 32 for engaging the sleeve 18. The dogs 32 permit application of an upwardly or downwardly directed force from the tool 12 to the sleeve 18 for displacement of the sleeve upwardly or downwardly relative to the housing 20. Of course, if in an alternate embodiment

- 10 -

a closure member of a valve is displaced radially, rotationally, laterally or otherwise, corresponding changes to the tool 12 may be made in keeping with the principles of the present invention. Additionally, differently configured, numbered, arranged, etc.,
5 engagement members may be used to provide engagement between the tool 12 and the sleeve 18 and/or housing 20.

The dogs 32 extend outwardly from a housing 34 which is attached to an actuator 36 of the tool 12. As representatively described herein, the actuator 36 is a linear actuator, since the sleeve
10 18 is linearly displaced between its positions relative to the housing 20, however, it is to be clearly understood that other types of actuators may be utilized, without departing from the principles of the present invention. An acceptable actuator which may be used for the actuator 36 is the DPU (Downhole Power Unit) available from
15 Halliburton Energy Services, Inc.

The DPU is especially adapted for conveyance by slickline or coiled tubing, since it is battery-powered. A slickline 46 is depicted in FIG. 1 as the means used to convey the tool 12 in the string 14. It should be noted, however, that otherwise powered actuators and
20 other means of conveying a tool within a string may be utilized, without departing from the principles of the present invention.

The valve 16 includes communication devices 38, 40 which permit communication between the valve and respective

communication devices 42, 44 of the tool 12. The communication devices 38, 40, 42, 44 may serve many purposes in the interaction of the tool 12 with the valve 16, and many of these are described below. However, the descriptions of specific purposes for the communication devices 38, 40, 42, 44 in the representatively illustrated method 10 are not to be taken as limiting the variety of uses for communication devices in a method incorporating principles of the present invention.

The device 38 may be supplied with power by a battery or other power source 39. The power source 39 may be included in the valve 16, or it may be remote therefrom. It is to be clearly understood that any means of supplying power to the device 38 may be utilized, without departing from the principles of the present invention. The power source 39 may also supply power to sensors, etc. associated with the device 38.

The device 38 may communicate to the device 42 the identity of the valve 16 (e.g., a digital address of the valve), so that a determination may be made as to whether the tool 12 is positioned relative to the proper item of equipment in the string 14. The string 14 may include multiple items of equipment, and this communication between the devices 38, 42 may be used to select the valve 16 from among the multiple items of equipment for operation of the tool 12 therewith. For example, the device 38 may

- 12 -

continuously transmit a signal indicative of the identity of the valve 16 so that, as the tool 12 is conveyed through the string 14, the device 42 will receive the signal when the devices 38, 42 are in sufficiently close proximity to each other.

5 As another example, the device 38 may not transmit a signal until the device 42 polls the device 38 by transmitting a signal as the tool 12 is conveyed through the string 14. The tool 12 may be programmed to transmit a signal to which only the device 38, out of multiple such devices of respective other items of equipment
10 installed in the string 14, will respond. Such programming may be accomplished, for example, by utilizing an electronic circuit 48 connected to the device 42 in the tool 12 or, if the tool 12 is in communication with a remote location, for example, via wireline or other data transmission means, the programming may be
15 accomplished remote from the tool. The above-described methods of identifying an item of equipment to a service tool, and of selecting from among multiple items of equipment installed in a tubular string for operation of a tool therewith, may be utilized with any of the methods described herein.

20 Transmission of a signal from the device 42 to the device 38 may activate the device 38 from a dormant state, in which the device 38 consumes very little power, to an active state, in which more power is consumed by the device 38 as it communicates with

the device 42. Such activation of the device 38 may permit the device 38 to communicate with the device 42.

As another alternative, the tool 12 may supply power to operate the device 38. Thus, the device 38 may not communicate
5 with the device 42 until the tool 12 is in sufficiently close proximity to the valve 16, or is in an operative position relative to the valve. Methods of supplying power from the tool 12 to operate the device 38 are described below. However, it is to be clearly understood that other methods may be utilized, without departing from the
10 principles of the present invention.

Another purpose which may be served by the communication between the devices 42, 38 is to provide an indication that the tool 12 is operatively positioned, or at least within a predetermined distance of an operative position, relative to the valve 16. For
15 example, communication between the devices 38, 42 may indicate that the engagement member 28 is aligned with the profile 30. The tool 12 may be prevented from extending the engagement member 28 outwardly into engagement with the profile 30 until the communication between the devices 38, 42 indicates such
20 alignment. This indication may be transmitted by the tool 12 to a remote location, for example, so that an operator may confirm that the tool 12 has operatively engaged the valve 16.

- 14 -

Yet another purpose which may be served by the communication between the devices 38, 42 is to indicate the position of the sleeve 18 relative to the housing 20. As representatively illustrated in FIG. 1, one or more position sensors 50, 5 such as hall effect devices or a displacement transducer, etc., may be connected to the device 38, so that the device may transmit data indicative of the sleeve 18 position to the device 42. This indication may then be transmitted by the tool 12 to a remote location, for example, so that an operator may confirm the sleeve 18 position.

10 Note that one or more of the sensors 50 may be any type of sensor. For example, one of the sensors 50 may be a pressure or temperature sensor. Use of one of the sensors 50 as a pressure indicator may be useful in determining pressure applied to, or a pressure differential across, the sleeve 18.

15 Another sensor 51 is positioned proximate at least one of the openings 22, and may be in contact with fluid flowing through the opening. The sensor 51 is connected to the device 38 for transmission of data from the sensor to the device. The sensor 51 may be a resistivity, capacitance, inductance and/or particle sensor 20 for detecting these properties of fluid flowing through the opening 22. For example, the sensor 51 may be utilized to determine a percentage of water in the fluid flowing through the opening 22, to

determine the number and/or size of particles flowing through the opening 22, etc.

The devices 40, 44 communicate by direct electrical contact therebetween. As depicted in FIG. 1, the device 40 is connected to a
5 pressure sensor 52 exposed to fluid pressure on the exterior of the housing 20. In conjunction with another pressure sensor, such as one of the sensors 50 or another pressure sensor 54, exposed to fluid pressure in the interior of the housing 20, the pressure differential across the sleeve 18 may be readily determined. Such determination
10 may be made by an electronic circuit 56 of the tool 12, transmitted from the tool to a remote location and/or the determination may be made at the remote location from a transmission of the interior and exterior pressure indications.

As with the devices 38, 42 described above, communication
15 between the devices 40, 44 may be used for many purposes, in addition to that of sensor data communication. For example, communication between the devices 40, 44 may be used to indicate that the tool 12 is operatively positioned relative to the valve 16. Since the representatively illustrated devices 40, 44 communicate by
20 direct electrical contact, such communication between the devices indicates at least that the devices are aligned with each other. This indication may be transmitted by the tool 12 to a remote location. This indication may also be used to control extension of the dogs 32

- 16 -

outwardly from the housing 34 into engagement with the sleeve 18 by the tool 12 in a manner similar to that described above for control of extension of the keys 28. An indication that the keys 28 and/or dogs 32 have operatively engaged the respective housing 20
5 and/or sleeve 18 may also be transmitted by the tool 12 to a remote location.

As another example, the circuit 56, or another circuit at a remote location, may be programmed to control operation of the tool 12 based at least in part on data communicated between the
10 devices 40, 44. The circuit 56 may be connected to the actuator 36 and may be programmed to prevent the actuator from displacing the sleeve 18 to the open position if the sensors 52, 54 indicate that the pressure differential across the sleeve is outside an acceptable range, e.g., if the pressure differential is excessive. The circuit 56
15 may further be programmed to permit the actuator 36 to displace the sleeve 18 to the equalizing position, but not to the open position, if the pressure differential across the sleeve is excessive.

Thus, it will be readily appreciated that the method 10 provides for convenient operation of the tool 12 in conjunction with
20 the valve 16, with reduced possibility of human error involved therewith. An operator may convey the tool 12 into the string 14, the tool and the valve 16 may communicate via the devices 38, 42 and/or 40, 44 to indicate the identity of the valve and/or to select the

valve from among multiple items of equipment installed in the string, and such communication may be used to indicate that the tool is operatively positioned relative to the valve, to control engagement of the tool with the valve, to indicate useful status
5 information regarding the valve, such as the position of the sleeve 18, pressure applied to the valve, pressure differential across the sleeve, etc., and to control operation of the tool. Due to the advances in the art provided by the method 10, when the tool 12 is utilized additionally to transmit information to a remote location,
10 the operator is able to positively determine whether the valve 16 is the appropriate item of equipment intended to be engaged by the tool, whether the tool is operatively positioned relative to the valve, whether the tool has operatively engaged the valve, the position of the sleeve 18 both before and after it is displaced, if at all, by the
15 tool, and the pressures and/or differential pressures, temperatures, etc. of concern.

Referring additionally now to FIG. 2, alternate communication devices 58, 60 are representatively and schematically illustrated which may be used for the devices 38, 42 described above. As
20 depicted in FIG. 2, the devices 58, 60 are shown installed in the actuator 36 and housing 20 of the method 10, but it is to be clearly understood that the devices 58, 60 may be used in other apparatus, other methods, and in substitution for other communication devices

described herein, without departing from the principles of the present invention.

The devices 58, 60 communicate by inductive coupling therebetween. Power may also be supplied from the device 58 to
5 the device 60 by such inductive coupling.

The device 58 includes an annular-shaped coil 62, which is connected to an electronic circuit 64. The circuit 64 causes electrical current to be flowed through the coil 62, and manipulates that current to cause the device 58 to transmit a signal to the device 60.
10 Note that such signaling is via a magnetic field, and manipulations of the magnetic field, propagated by the coil 62 in response to the current flowed therethrough. The device 58 may also respond to a magnetic field, for example, propagated by the device 60, in which case the magnetic field would cause a current to flow through the
15 coil 62 and be received by the circuit 64. Thus, the device 58 may serve as a transmitter or receiver.

The device 60 also includes a coil 66 and a circuit 68 connected to the coil. The device 60 may operate in a manner similar to that described above for the device 58, or it may operate differently. For
20 example, the device 60 may only transmit signals, without being configured for receiving signals.

Referring additionally now to FIG. 3, further alternate communication devices 70, 72 are representatively and schematically

illustrated which may be used for the devices 38, 42 described above. As depicted in FIG. 3, the devices 70, 72 are shown installed in the actuator 36 and housing 20 of the method 10, but it is to be clearly understood that the devices 70, 72 may be used in other
5 apparatus, other methods, and in substitution for other communication devices described herein, without departing from the principles of the present invention.

The devices 70, 72 communicate by transmission of electromagnetic waves therebetween, preferably using radio
10 frequency (RF) transmission. Power may also be supplied from the device 70 to the device 72 by such electromagnetic wave transmission.

The device 70 includes an antenna 74, which is connected to an electronic circuit 76. The circuit 76 causes electrical current to be
15 flowed through the antenna 74, and manipulates that current to cause the device 70 to transmit a signal to the device 72. The device 70 may also respond to electromagnetic wave transmission from the device 72, in which case the device 70 may also serve as a receiver.

The device 72 also includes an antenna 78 and a circuit 80
20 connected to the antenna. The device 72 may operate in a manner similar to that described above for the device 70, or it may operate differently. For example, the device 72 may only transmit signals, without being configured for receiving signals.

Referring additionally now to FIG. 4., still further alternate communication devices 82, 84 are representatively and schematically illustrated which may be used for the devices 38, 42 described above. As depicted in FIG. 4, the devices 82, 84 are shown installed in the actuator 36 and housing 20 of the method 10, but it is to be clearly understood that the devices 82, 84 may be used in other apparatus, other methods, and in substitution for other communication devices described herein, without departing from the principles of the present invention.

10 The devices 82, 84 communicate by transmission of pressure pulses therebetween, preferably using acoustic wave transmission. Power may also be supplied from the device 82 to the device 84 by such pressure pulses.

The device 82 includes at least one piezoelectric crystal 86, which is connected to an electronic circuit 88. The circuit 88 causes electrical current to be flowed through the crystal 86, and manipulates that current to cause the device 82 to transmit a signal to the device 84. The device 82 may also respond to pressure pulses transmitted from the device 84, in which case the device 82 may also serve as a receiver.

The device 84 also includes a piezoelectric crystal 90 and a circuit 92 connected to the crystal. The device 84 may operate in a manner similar to that described above for the device 82, or it may

operate differently. For example, the device 84 may only transmit signals, without being configured for receiving signals.

Of course, it is well known that a piezoelectric crystal distorts when an electric current is applied thereto, and that distortion of a piezoelectric crystal may be used to generate an electric current therefrom. Thus, when the circuit 88 applies a current, or manipulates a current applied to, the crystal 86, the crystal distorts and causes a pressure pulse or pulses in fluid disposed between the actuator 36 and the housing 20. This pressure pulse or pulses, in turn, causes the crystal 90 to distort and thereby causes a current, or a manipulation of a current, to be flowed to the circuit 92. In a similar manner, the device 84 may transmit a signal to the device 82. Multiple ones of either or both of the crystals 86, 90 may be used, if desired, to increase the amplitude of the pressure pulses generated thereby, or to increase the amplitude of the signal generated when the pressure pulses are received.

Thus have been described several alternate means by which devices may communicate between an item of equipment interconnected in a tubular string and a tool conveyed into the string. It is to be clearly understood, however, that any type of communication device may be used for the communication devices described herein, and that the principles of the present invention are not to be considered as limited to the specifically described

communication devices. Many other communication devices, and other types of communication devices, may be used in methods and apparatus incorporating principles of the present invention. For example, the crystal 90 could be a radioactivity producing device
5 and the crystal 86 could be a radioactivity sensing device, the crystal 90 could be a magnet and the crystal 86 could be a hall effect device or a reed switch which closes in the presence of a magnetic field, etc. Furthermore, each of the communication devices described herein may have a power source incorporated therein, for example,
10 a battery may be included in the each of the circuits 64, 68, 76, 80, 88, 92 described above.

Referring additionally now to FIGS. 5A&B, a method 100 which embodies principles of the present invention is representatively and schematically illustrated. The method 100 is similar in many respects
15 to the method 10 described above, in that a tool 102 is engaged with an item of equipment 104 installed in a tubular string and communication is established between a communication device 106 of the tool and a communication device 108 of the item of equipment. As depicted in FIGS. 5A&B, the item of equipment 104 is
20 a plug system and the tool 102 is a retrieving tool, but it is to be understood that principles of the present invention may be incorporated in other tools and items of equipment.

The plug system 104 includes a closure member, pressure equalizing member or prong 110, which is sealingly received within a plug assembly 112. The plug assembly 112, in turn, is sealingly engaged within a nipple 114. The nipple 114 is of the type well known to those skilled in the art and which may be interconnected in a tubular string, but is shown apart from the tubular string for illustrative clarity.

The plug assembly 112 includes a lock mandrel 134, which releasably secures the plug assembly relative to the nipple 114, and a plug 136, which sealingly engages the nipple to block fluid flow therethrough. The plug system 104 may be considered to include the nipple 114, although the plug assembly 112 and prong 110 may be used to block fluid flow through other nipples or other tubular members and, thus, the plug assembly and prong may also be considered to comprise a plugging device apart from the nipple.

The device 108 may be supplied with power by a battery or other power source 109. The power source 109 may be included in the plug system 104, or it may be remote therefrom. It is to be clearly understood that any means of supplying power to the device 108 may be utilized, without departing from the principles of the present invention. The power source 109 may also supply power to sensors, etc. associated with the device 108.

- 24 -

When the prong 110 is sealingly received within the plug assembly 112 as shown in FIG. 5B, fluid flow axially through the nipple 114 (and through the plug 136) is prevented. When the prong 110 is displaced upwardly relative to the plug assembly 112 and nipple 114, fluid flow is permitted through one or more relatively small openings 116 formed through a sidewall of the plug 136. Such fluid flow through the opening 116 may be used to equalize pressure across the plug assembly 112 before retrieving the plug assembly from the nipple. Note that, when the plug assembly 112 is removed from the nipple 114, relatively unrestricted fluid flow is permitted axially through the nipple.

A pressure sensor 118 is included in the prong 110 and is exposed to pressure in the nipple 114 below the plug assembly 112. Another pressure sensor 120 is included in the tool 102 and is exposed to pressure in the nipple 114 above the plug assembly 112. The pressure sensor 118 is connected to the device 108, which permits communication of pressure data from the sensor to the device 106. Pressure data from the sensor 118 (via the devices 106, 108) and pressure data from the sensor 120 may be input to an electronic circuit 122 of the tool 102 and/or transmitted to a remote location. Such pressure data may be used to determine pressures applied to the prong 110, plug assembly 112 and/or nipple 114, and may be used to determine the pressure differential across the plug

assembly. The circuit 122 (or another circuit, e.g., at a remote location) may be programmed to prevent operation of the tool 102 to displace the prong 110 if the pressure differential is excessive, or to permit only limited displacement of the prong if the pressure differential is excessive. Another pressure sensor 132 may optionally
5 be included in the prong 110 for measurement of pressure in the nipple 114 above the plug assembly 112.

The tool 102 includes one or more engagement members 124 configured for operatively engaging an external profile 126 formed
10 on the prong 110. Such engagement permits the tool 102 to apply an upwardly directed force to the prong 110. Another portion (not shown) of the tool 102 may be engaged with another profile for releasably securing the tool relative to the nipple 114 or plug assembly 112, similar to the manner in which the tool 12 is releasably
15 secured relative to the valve 16 using the keys 28 and profile 30 described above. For example, the tool 102 could have a portion which engages an internal profile 128 formed on the mandrel 134. In that case, the tool 102 would be releasably secured to the mandrel 134, and could be used to retrieve the mandrel by applying an
20 upwardly directed force to the profile 128 if desired.

The engagement member 124 is displaced into engagement with the profile 126 by an actuator 130, which is connected to the circuit 122 (or to another circuit, e.g., at a remote location). The

- 26 -

circuit 122 may be programmed or configured to permit the actuator 130 to displace the engagement member 124 into engagement with the profile 126 only when communication between the devices 106, 108 indicates that the tool 102 is
5 operatively positioned relative to the prong 110, nipple 114 or plug assembly 112. The representatively illustrated devices 106, 108 communicate by direct electrical contact, so establishment of communication therebetween may be the indication that the tool 102 is operatively positioned.

10 Alternatively, the circuit 122 may be programmed to permit engagement between the engagement member 124 and the profile 126 only when the pressure differential across the prong 110 and plug assembly 112 is within an acceptable range, or at least not excessive, although, since displacement of the prong is utilized to
15 cause reduction of the pressure differential as described above, this alternative is not preferred. As another alternative, the tool 102 may be prevented from engaging the profile 128, or may be prevented from displacing the plug assembly 112 relative to the nipple 114, if the pressure differential across the prong 110 and plug assembly is
20 excessive.

The method 100 demonstrates that principles of the present invention may be incorporated into a variety of different apparatus and methods. Thus, the principles of the present invention are not

to be considered limited to the specific apparatus and method embodiments described herein.

Referring additionally now to FIG. 6, another method 140 embodying principles of the present invention is representatively and schematically illustrated. In the method 140, multiple items of equipment 142, 144 are placed in communication with a service tool 146 conveyed into a tubular string 148. The item of equipment 142 is a portion of the tubular string 148, and the item of equipment 144 is a packer.

10 The tool 146 includes a communication device 150, and another communication device 152 is included in the string portion 142. As depicted in FIG. 6, the devices 150, 152 communicate via inductive coupling, in a manner similar to communication between the devices 58, 60 described above.

15 The device 152 is connected to various sensors of the string portion 142 and packer 144. For example, a sensor 154 may be positioned externally relative to the string portion 142, and a sensor 156 may be positioned internally relative to the packer 144. Additionally, other sensors 158, 160 may be positioned in the string
20 148 and connected to the device 152.

The sensor 154 may be a strain gauge, in which case indications of strain in the string 148 may be communicated from the device 152 to the device 150 for storage in a memory device of the tool 146

for later retrieval, e.g., at the earth's surface, or the tool 146 may transmit the indications to a remote location. Such a strain gauge sensor 154 may be utilized, for example, to identify problematic displacement of the string portion 142, which could prevent
5 insertion of a tool string therethrough, or to monitor fatigue in the tubing string 148.

The sensor 154 may alternatively, or additionally, be a pressure sensor, temperature sensor, or any other type of sensor. For example, the sensor 154 may be utilized to indicate pressure applied
10 to the string portion 142 or a pressure differential across the string portion. To indicate a pressure differential across the string portion 142, another of the sensors 154 may be positioned internal to the string portion.

The sensors 158, 160 may be pressure sensors, in which case
15 indications of pressure above and below the packer 144 may be communicated via the devices 150, 152 to the tool 146 and stored therein or transmitted to a remote location. The sensors 158, 160 may be included in the packer 144, and may indicate a pressure differential across a seal member or element 168 of the packer.

20 Note that the device 152 is remotely located relative to the sensors 156, 158, 160 and packer 144. Thus, it will be readily appreciated that a communication device is not necessarily included in a particular item of equipment or in the same item of equipment

as a source of data communicated by the device, in keeping with the principles of the present invention.

Referring additionally now to FIG. 7, the packer 144 is shown in an enlarged quarter-sectional view. In this view, the sensor 156 is depicted as actually including multiple individual sensors 162, 164, 166. The packer 144 includes the seal member or element 168, which is radially outwardly extended into sealing engagement with a wellbore 170 of the well.

FIG. 7 also depicts a seal assembly 180 sealingly received in the packer 144. Confirmation that the seal assembly 180 is properly positioned relative to the packer 144 is provided by a position sensor 178 of the packer. The position sensor 178 is connected to the device 152, so that an indication that the seal assembly 180 is properly positioned relative to the packer 144 may be transmitted to an operator. The position sensor 178 may be a proximity sensor, a hall effect device, fiber optic device, etc., or any other sensor capable of detecting the position of the seal assembly 180 relative to the packer 144.

The sensor 162 may be a compression or pressure sensor configured for measuring compression or pressure in the seal member 168. The sensor 166 may be a temperature sensor for measuring the temperature of the seal member 168. Alternatively, one or both of the sensors 162, 166 may be a resistivity sensor, strain

- 30 -

sensor or hardness sensor. Thus, it will be readily appreciated that any type of sensor may be included in the packer 144, without departing from the principles of the present invention.

The sensor 164 is a special type of sensor incorporating
5 principles of the present invention. The sensor 164 includes a portion 172 configured for inducing vibration in the seal member 168, and a portion 174 configured for measuring a resonant frequency of the seal member. In operation of the sensor 164, the vibrating portion 172 is activated to cause a projection 176
10 extending into the seal member 168 to vibrate. For example, the vibrating portion 172 may include a piezoelectric crystal to which is applied an alternating current. The crystal vibrates in response to the current, and thereby causes the projection 176, which is attached to the crystal, to vibrate also. This vibration of the
15 projection 176 in turn causes the seal member 168 to vibrate. Of course, the crystal could be directly contacting the seal member 168, in which case vibration of the crystal could directly cause vibration of the seal member 168, without use of the projection 176. Other methods of inducing vibration in the seal member may be utilized,
20 , without departing from the principles of the present invention.

When vibration has been induced in the seal member 168, it will be readily appreciated that the seal member will vibrate at its natural or resonant frequency. The frequency measuring portion

174 detects the resonant frequency vibration of the seal member 168, and data indicating this resonant frequency is communicated by the devices 150, 152 to the tool 146 for storage therein and/or transmission to a remote location. Note that it is not necessary for
5 the vibrating and frequency measuring portions 172, 174 to be separate portions of the sensor 164 since, for example, a piezoelectric crystal may be used both to induce vibration in the seal element 168 and to detect vibration of the seal element.

The resonant frequency of the seal member 168 may be used,
10 for example, to determine the hardness of the seal member and/or the projected useful life of the seal member. The strain in the tubular string 148 as detected by the sensor 154 may be used, for example, to determine a radius of curvature of the string and/or the projected useful life of the string. Thus, a wide variety of useful
15 information regarding items of equipment installed in the well may be acquired by the tool 146 in a convenient manner.

The device 152 may be supplied with power by a battery or other power source 153. The power source 153 may be included in the packer 144, or it may be remote therefrom. It is to be clearly
20 understood that any means of supplying power to the device 152 may be utilized, without departing from the principles of the present invention. The power source 153 may also supply power to the sensors 154, 156, 158, 160, 178 associated with the device 152.

Alternatively, one or more of the sensors 154, 156, 158, 160, 178 may have a power source, such as a battery, combined therewith or integral thereto, so that a remote power source is not needed to operate the sensor. Note that any of the other sensors 50, 51, 52, 54,
5 118, 120, 132 described above may also include a power source. In each of the methods 10, 100, 140 described above, a power source included in any sensor used in the method may supply power to operate its associated communication device.

A memory device 182, such as a random access memory device,
10 is shown in FIG. 7 included in the packer 144 and interconnected to the sensors 162, 164, 166. The memory device 182 is utilized to store data generated by the sensors 162, 164, 166, and then transmit the stored data to the tool 146 via the devices 150, 152. In this manner, the memory device may store, for example, indications of the
15 hardness of, or compression in, the seal element 168 over time, and these readings may then be retrieved by the tool 146 and stored therein, or be transmitted directly to a facility at the earth's surface, for evaluation.

Note that, although the memory device 182 is shown as being
20 included in the packer 144, it may actually be remotely positioned relative to the packer. For example, the memory device 182 could be packaged with the communication device 152. In addition, the memory device 182 may be connected to other sensors, such as the

- 33 -

sensor 154. Power to operate the memory device 182 may be supplied by the power source 153, or another power source.

Referring additionally now to FIG. 8, another method 190 embodying principles of the present invention is schematically and representatively illustrated. In the method 190, an item of equipment 192 is interconnected in a tubular string 194. The item of equipment 192 includes a nipple 200 or other tubular housing and a particle sensor 196 of the type capable of detecting particles, such as sand grains, passing through the nipple.

10 A memory device 198, such as a random access memory device, is connected to the sensor 196 and stores data generated by the sensor. The sensor 196 is also connected to a communication device 202. The communication device 202 is configured for communication with another communication device 204 included in
15 a service tool 206. The communication devices 202, 204 may be similar to any of the communication devices described above, other they may be other types of communication devices.

When the tool 206 is received in the nipple 200 and appropriately positioned relative thereto, the devices 202, 204
20 communicate, thereby permitting download of the data stored in the memory device 198. This data may be stored in another memory device of the tool 206 for later retrieval, or it may be communicated directly to a remote location.

Power to operate the sensor 196, the memory device 198 and/or the communication device 202 may be supplied by a power source 208, such as a battery, included with the sensor. Alternatively, the communication device 202 could be supplied with
5 power from the communication device 204, as described above. As another alternative, the power source may not be included with the sensor, but may be remotely positioned relative thereto.

Note that it is not necessary for the data generated by the sensor 196 to be stored in the memory device 198, since data may be
10 transmitted directly from the sensor to the tool 206 via the devices 202, 204 in real time.

It will now be fully appreciated that the method 190 permits evaluation of particle flow through the nipple 200 over time. The data for such evaluation may be conveniently obtained by conveying
15 the tool 206 into the nipple 200 and establishing communication between the devices 202, 204. This evaluation may assist in predicting future particle production, assessing the effectiveness of a sand control program, etc.

It is to be clearly understood that, although the method 190
20 has been described herein as being used to evaluate particle flow axially through the tubular member 200, principles of the present invention may also be incorporated in methods wherein other types of particle flows are experienced. For example, the sensor 51 of the

method 10 may be a particle sensor, in which case particle flow through a sidewall of the housing 20 may be evaluated.

The method 190 may also utilize functions performed by the communication devices as described above. For example, the communication device 202 may communicate to the communication device 204 an indication that the tool 206 is operatively positioned, or within a predetermined distance of an operative position, relative to the item of equipment 192. The communication device 204 may activate the communication device 202 from a dormant state to an active state, thereby permitting communication between the devices.

Of course, a person skilled in the art, upon a careful consideration of the above description of various embodiments of the present invention would readily appreciate that many modifications, additions, substitutions, deletions and other changes may be made to the apparatus and methods described herein, and these changes are contemplated by the principles of the present invention. For example, although certain types of sensors have been described above as being interconnected to communication devices, any type of sensor may be used in any of the above described apparatus and methods, and the communication devices described above may be used in conjunction with any type of sensor. As another example, items of equipment have been described above as

being interconnected in tubing strings, but principles of the present invention may be incorporated in methods and apparatus wherein items of equipment are interconnected or installed in other types of tubular strings, such as casing or coiled tubing. Accordingly, the
5 foregoing detailed description is to be clearly understood as being given by way of illustration and example only, the spirit and scope of the present invention being limited solely by the appended claims.

WHAT IS CLAIMED IS:



- 37 -

1 1. A system for facilitating downhole communication between
2 an item of equipment installed in a tubular string in a subterranean
3 well and a tool conveyed into the tubular string, the system
4 comprising:


5 a first communication device associated with the item of
6 equipment; and

7 a second communication device included in the tool,
8 communication between the first and second devices being
9 established when the second device is brought into sufficiently close
0 proximity to the first device.

1 2. The system according to Claim 1, wherein the second device
2 supplies power to the first device, thereby permitting the first
3 device to communicate with the second device.

1 3. The system according to Claim 2, wherein the power is
2 supplied by electromagnetic waves emanating from the second
3 device.

This Sheet Has Been Replaced





- 38 -

1 4. The system according to Claim 3, wherein the
2 electromagnetic waves are radio frequency waves.

1 5. The system according to Claim 2, wherein the power is
2 supplied by pressure pulses emanating from the second device.

1 6. The system according to Claim 5, wherein the pressure
2 pulses are acoustic waves.

1 7. The system according to Claim 2, wherein the power is
2 supplied by direct electrical contact between the first and second
3 devices.

1 8. The system according to Claim 2, wherein the power is
2 supplied by inductive coupling between the first and second
3 devices.

This Sheet Has Been Replaced





1 9. The system according to Claim 1, wherein the second device
2 activates the first device from a dormant state to an active state,
3 thereby permitting communication between the first and second
4 devices.

1 10. The system according to Claim 9, wherein the
2 communication between the first and second devices is via
3 electromagnetic waves.

1 11. The system according to Claim 10, wherein the
2 electromagnetic waves are radio frequency waves.

1 12. The system according to Claim 9, wherein the
2 communication between the first and second devices is via pressure
3 pulses.

1 13. The system according to Claim 12, wherein the pressure
2 pulses are acoustic waves.

This Sheet Has Been Replaced





- 40 -

1 14. The system according to Claim 9, wherein the
2 communication between the first and second devices is via direct
3 electrical contact between the first and second devices.

1 15. The system according to Claim 9, wherein the
2 communication between the first and second devices is via inductive
3 coupling between the first and second devices.

1 16. The system according to Claim 1, wherein the
2 communication between the first and second devices indicates
3 when the tool is within a predetermined distance of an operative
4 position of the tool relative to the item of equipment.

1 17. The system according to Claim 16, wherein the first device
2 communicates to the second device that the tool is operatively
3 positioned relative to the item of equipment.

This Sheet Has Been Replaced





- 41 -

1 18. The system according to Claim 16, wherein the item of
2 equipment has a profile, the tool has an engagement member
3 configured for engagement with the profile to secure the tool
4 relative to the item of equipment, and wherein the communication
5 between the first and second devices indicates when the
6 engagement member is aligned with the profile.

1 19. The system according to Claim 18, wherein the tool is
2 permitted to displace the engagement member into engagement
3 with the profile only when the communication between the first
4 and second devices indicates that the engagement member is
5 aligned with the profile.

1 20. The system according to Claim 1, wherein the first device
2 communicates a status of the item of equipment to the second
3 device.

This Sheet Has Been Replaced





1 21. The system according to Claim 20, wherein the item of
2 equipment is a valve, and wherein the status is a position of the
3 valve.

1 22. The system according to Claim 20, wherein the item of
2 equipment is a packer, and wherein the status of a seal member of
3 the packer is communicated to the second device.

1 23. The system according to Claim 22, wherein the status is a
2 hardness of the seal member.

1 24. The system according to Claim 22, wherein the status is
2 compressive stress in the seal member.

1 25. The system according to Claim 20, wherein the item of
2 equipment is a portion of the tubular string, and wherein the status
3 is a strain in the portion of the tubular string.

This Sheet Has Been Replaced





- 43 -

1 26. The system according to Claim 1, wherein communication
2 between the first and second devices at least partially controls
3 operation of the tool.

1 27. The system according to Claim 26, wherein an engagement
2 member of the tool is permitted to engage a profile of the item of
3 equipment when the first and second devices are in sufficiently
4 close proximity to each other.

1 28. The system according to Claim 27, wherein the profile is
2 internally formed.

1 29. The system according to Claim 27, wherein the profile is
2 externally formed.

This Sheet Has Been Replaced





- 44 -

1 30. The system according to Claim 26, wherein the tool is
2 permitted to displace a closure member of the item of equipment
3 when the communication between the first and second devices
4 indicates that a pressure differential across the closure member is
5 within a predetermined range.

1 31. The system according to Claim 30, wherein the tool is
2 permitted to displace the closure member to an equalizing position
3 configured for reducing the pressure differential, but the tool is
4 permitted to displace the closure member to an open position only
5 when the communication between the first and second devices
6 indicates that the pressure differential is within the predetermined
7 range.

1 32. The system according to Claim 30, wherein the closure
2 member is a pressure equalizing member, wherein the tool is
3 permitted to displace the pressure equalizing member to an
4 equalizing position configured for reducing the pressure
5 differential, but the tool is permitted to remove the pressure

This Sheet Has Been Replaced



- 45 -

6 equalizing member from the item of equipment only when the
7 communication between the first and second devices indicates that
8 the pressure differential is within the predetermined range.

1 33. The system according to Claim 26, wherein the item of
2 equipment is one of a plurality of structures interconnected in the
3 tubular string, and wherein the item of equipment is selected from
4 the plurality of structures for operation of the tool therewith in
5 response to the communication between the first and second
6 devices.

1 34. The system according to Claim 33, wherein the tool is
2 programmable for selection of multiple ones of the plurality of
3 structures for operation of the tool therein in response to
4 communication between the second device and a device of each of
5 the selected structures.

This Sheet Has Been Replaced





- 46 -

1 35. The system according to Claim 1, wherein the first device is
2 remotely positioned relative to the remainder of the item of
3 equipment.

1 36. The system according to Claim 1, wherein the first device
2 includes an electronic circuit, and wherein the second device is
3 responsive to a signal produced by the electronic circuit.

1 37. The system according to Claim 1, wherein the first device
2 includes a magnet, and wherein the second device is responsive to a
3 magnetic field produced by the magnet.

1 38. The system according to Claim 1, wherein the first device
2 includes a radioactive device, and wherein the second device is
3 responsive to radioactivity produced by the radioactive device.

1 39. The system according to Claim 1, wherein the first device
2 includes a reed switch, and wherein the second device is responsive
3 to actuation of the reed switch.

This Sheet Has Been Replaced





1 40. The system according to Claim 1, wherein the first device
2 includes a hall effect device, and wherein the second device causes
3 the hall effect device to generate an electrical current.

1 41. The system according to Claim 1, wherein the first device
2 identifies the item of equipment to the tool.

1 42. The system according to Claim 1, wherein the first device
2 responds to a magnet to activate the first device from a dormant
3 state to an active state.

1 43. The system according to Claim 1, wherein the first device
2 responds to radioactivity to activate the first device from a dormant
3 state to an active state.

1 44. The system according to Claim 1, wherein the first device
2 responds to a signal transmitted from the second device to activate
3 the first device from a dormant state to an active state.

This Sheet Has Been Replaced





- 48 -

1 45. The system according to Claim 1, wherein the first device is
2 connected to a sensor of the item of equipment and communication
3 between the first and second devices transmits data from the
4 sensor.

1 46. The system according to Claim 45, wherein the sensor
2 includes a power source.

1 47. The system according to Claim 46, wherein power to
2 operate the first device is provided by the sensor power source.

This Sheet Has Been Replaced





- 49 -

1 48. A downhole valve system, comprising:
2 a valve including a closure member selectively positionable in
3 open and closed positions, and a first communication device; and
4 a tool positionable relative to the first device and operable to
5 cause displacement of the closure member between the open and
6 closed positions, the tool including a second communication device,
7 with communication being established between the first and second
8 devices.

1 49. The valve system according to Claim 48, wherein the tool is
2 permitted to displace the closure member only when
3 predetermined acceptable data is transmitted from at least one
4 sensor via the first and second devices.

1 50. The valve system according to Claim 48, wherein the first
2 device communicates data indicative of pressure applied to the
3 closure member.

This Sheet Has Been Replaced





- 50 -

1 51. The valve system according to Claim 50, wherein the first
2 device is connected to a pressure sensor of the valve.

1 52. The valve system according to Claim 50, wherein the first
2 device communicates data indicative of a pressure differential across
3 the closure member.

1 53. The valve system according to Claim 50, wherein data is
2 communicated from the first to the second device, and wherein the
3 tool transmits the data to a remote location.

1 54. The valve system according to Claim 48, wherein the first
2 device communicates data indicative of the position of the closure
3 member to the second device.

1 55. The valve system according to Claim 54, wherein the first
2 device is connected to a position sensor.

This Sheet Has Been Replaced





- 51 -

1 56. The valve system according to Claim 54, wherein the first
2 device is connected to a pressure sensor.

1 57. The valve system according to Claim 54, wherein the tool
2 transmits the data to a remote location.

1 58. The valve system according to Claim 48, wherein the tool is
2 permitted to displace the closure member to the open position only
3 when a differential pressure across the closure member is within a
4 predetermined range.

1 59. The valve system according to Claim 48, wherein the tool is
2 permitted to displace the closure member to an equalizing position
3 configured for reducing a pressure differential across the closure
4 member, but the tool is permitted to displace the closure member
5 to the open position only when the pressure differential is within a
6 predetermined range.

This Sheet Has Been Replaced





- 52 -

60. The valve system according to Claim 48, wherein the tool includes a first pressure sensor sensing pressure on a first side of the closure member, and the valve includes a second pressure sensor sensing pressure on a second side of the closure member.

61. The valve system according to Claim 48, wherein the valve includes a first pressure sensor sensing pressure on a first side of the closure member, and a second pressure sensor sensing pressure on a second side of the closure member.

62. The valve system according to Claim 48, wherein the tool includes an engagement member which is permitted to engage the valve only when the second device is in sufficiently close proximity to the first device.

This Sheet Has Been Replaced





- 53 -

1 63. The valve system according to Claim 48, wherein the valve
2 is one of a plurality of structures interconnected in the tubular
3 string, and wherein the valve is selected from the plurality of
4 structures for operation of the tool therewith in response to the
5 communication between the first and second devices.

1 64. The valve system according to Claim 63, wherein each of
2 the structures has a communication device associated therewith,
3 and wherein the tool is programmed to activate only the first device
4 from a dormant state to an active state.

1 65. The valve system according to Claim 63, wherein each of
2 the structures has a communication device associated therewith,
3 and wherein the first device is activated from a dormant state to an
4 active state only in response to communication from the second
5 device.

1 66. The valve system according to Claim 48, wherein power for
2 operation of the first device is supplied by the tool.

This Sheet Has Been Replaced





1 67. The valve system according to Claim 48, wherein the first
2 device is connected to a sensor including a power source.

1 68. The valve system according to Claim 67, wherein power to
2 operate the first device is supplied by the sensor power source.

1 69. The valve system according to Claim 48, wherein power for
2 operation of the first device is supplied by a power source of the
3 valve.

1 70. The valve system according to Claim 69, wherein the power
2 source is remotely positioned relative to the valve.

1 71. The valve system according to Claim 48, wherein the first
2 device is remotely positioned relative to the valve.

This Sheet Has Been Replaced





- 55 -

1 72. The valve system according to Claim 48, wherein the valve
2 further includes an opening formed through a sidewall of the valve,
3 fluid flowing through the opening when the closure member is in
4 the open position, and a sensor interconnected to the first device
5 and sensing a property of a fluid flowing through the opening.

1 73. The valve system according to Claim 72, wherein the sensor
2 is a resistivity sensor.

1 74. The valve system according to Claim 72, wherein the sensor
2 is a capacitance sensor.

1 75. The valve system according to Claim 72, wherein the sensor
2 is an inductance sensor.

1 76. The valve system according to Claim 72, wherein the sensor
2 is a particle sensor.

This Sheet Has Been Replaced





- 56 -

1 77. A downhole plug system, comprising:
2 a plug assembly;
3 a first communication device;
4 a closure member selectively positionable in engaged and
5 released positions relative to the plug assembly, the closure member
6 blocking flow through the plug assembly in the engaged position,
7 and flow through the plug assembly being permitted in the released
8 position; and

9 a tool positionable relative to the first device and operable to
0 cause displacement of the closure member between the engaged
1 and released positions, the tool including a second communication
2 device, and communication being established between the first and
3 second devices.

1 78. The plug system according to Claim 77, wherein the first
2 device communicates data indicative of pressure applied to the
3 closure member.

This Sheet Has Been Replaced





- 57 -

1 79. The plug system according to Claim 78, wherein the first
2 device is connected to a pressure sensor of the closure member.

1 80. The plug system according to Claim 78, wherein the first
2 device communicates data indicative of a pressure differential across
3 the closure member.

1 81. The plug system according to Claim 78, wherein data is
2 communicated from the first to the second device, and wherein the
3 tool transmits the data to a remote location.

1 82. The plug system according to Claim 77, wherein the tool is
2 permitted to displace the closure member only when
3 predetermined acceptable data is transmitted from at least one
4 sensor via the first and second devices.

This Sheet Has Been Replaced





1 83. The plug system according to Claim 77, wherein the tool is
2 permitted to displace the closure member to the released position
3 only when a differential pressure across the closure member is
4 within a predetermined range.

1 84. The plug system according to Claim 77, wherein the
2 released position is an equalizing position configured for reducing a
3 pressure differential across the closure member.

1 85. The plug system according to Claim 77, wherein the tool
2 includes a first pressure sensor sensing pressure on a first side of the
3 closure member, and the closure member includes a second
4 pressure sensor sensing pressure on a second side of the closure
5 member.

1 86. The plug system according to Claim 77, further comprising
2 a first pressure sensor sensing pressure on a first side of the closure
3 member, and a second pressure sensor sensing pressure on a second
4 side of the closure member.

This Sheet Has Been Replaced






1 87. The plug system according to Claim 77, wherein the tool
2 includes an engagement member which is permitted to engage the
3 closure member only when the second device is in sufficiently close
4 proximity to the first device.

1 88. The plug system according to Claim 77, wherein the plug
2 assembly is one of a plurality of structures interconnected in the
3 tubular string, and wherein the plug assembly is selected from the
4 plurality of structures for operation of the tool therewith in
5 response to the communication between the first and second
6 devices.

1 89. The plug system according to Claim 88, wherein each of
2 the structures has a communication device associated therewith,
3 and wherein the tool is programmed to activate only the first device
4 from a dormant state to an active state.

This Sheet Has Been Replaced





- 60 -

1 90. The plug system according to Claim 88, wherein each of
2 the structures has a communication device associated therewith,
3 and wherein the first device is activated from a dormant state to an
4 active state only in response to communication from the second
5 device.

1 91. The plug system according to Claim 77, wherein power for
2 operation of the first device is supplied by the tool.

1 92. The plug system according to Claim 77, wherein power for
2 operation of the first device is supplied by a power source of the
3 closure member.

1 93. The plug system according to Claim 77, wherein the first
2 device is connected to a sensor including a power source.

1 94. The plug system according to Claim 93, wherein power for
2 operation of the first device is supplied by the sensor power source.

This Sheet Has Been Replaced





- 61 -

1 95. A downhole packer system, comprising:
2 a packer including a first communication device and an
3 outwardly extendable seal member; and
4 a tool positionable relative to the first device and including a
5 second communication device, communication being established
6 between the first and second devices.

1 96. The packer system according to Claim 95, wherein the first
2 device communicates data indicative of pressure applied to the seal
3 member.

1 97. The packer system according to Claim 96, wherein the first
2 device is connected to a pressure sensor of the packer.

1 98. The packer system according to Claim 96, wherein the first
2 device communicates data indicative of a pressure differential across
3 the seal member.

This Sheet Has Been Replaced





- 62 -

1 99. The packer system according to Claim 96, wherein data is
2 communicated from the first to the second device, and wherein the
3 tool transmits the data to a remote location.

1 100. The packer system according to Claim 95, wherein the
2 first device is remotely positioned relative to the remainder of the
3 packer.

1 101. The packer system according to Claim 95, wherein the
2 packer includes a first pressure sensor sensing pressure on a first side
3 of the seal member, and a second pressure sensor sensing pressure
4 on a second side of the seal member.

1 102. The packer system according to Claim 95, wherein the
2 packer is one of a plurality of structures interconnected in the
3 tubular string, and wherein the packer is selected from the plurality
4 of structures for operation of the tool therewith in response to the
5 communication between the first and second devices.

This Sheet Has Been Replaced





1 103. The packer system according to Claim 102, wherein each
2 of the structures has a communication device associated therewith,
3 and wherein the tool is programmed to activate only the first device
4 from a dormant state to an active state.

1 104. The packer system according to Claim 102, wherein each
2 of the structures has a communication device associated therewith,
3 and wherein the first device is activated from a dormant state to an
4 active state only in response to communication from the second
5 device.

1 105. The packer system according to Claim 95, wherein power
2 for operation of the first device is supplied by the tool.

1 106. The packer system according to Claim 95, wherein power
2 for operation of the first device is supplied by a power source of the
3 packer.

This Sheet Has Been Replaced





1 107. The packer system according to Claim 95, wherein the
2 first device is connected to a sensor including a power source.

1 108. The packer system according to Claim 107, wherein power
2 to operate the first device is supplied by the sensor power source.

1 109. The packer system according to Claim 95, wherein the
2 first device is connected to a seal member sensor.

1 110. The packer system according to Claim 109, wherein the
2 seal member sensor is a temperature sensor.

1 111. The packer system according to Claim 109, wherein the
2 seal member sensor is a compression sensor.

1 112. The packer system according to Claim 109, wherein the
2 seal member sensor is a resistivity sensor.

This Sheet Has Been Replaced





- 65 -

1 113. The packer system according to Claim 109, wherein the
2 seal member sensor is a strain sensor.

1 114. The packer system according to Claim 109, wherein the
2 seal member sensor is a hardness sensor.

1 115. The packer system according to Claim 109, wherein the
2 seal member sensor is a resonant frequency sensor.

1 116. The packer system according to Claim 115, wherein the
2 seal member sensor induces vibration in the seal member.

1 117. The packer system according to Claim 95, wherein the
2 packer includes a position sensor.

1 118. The packer system according to Claim 117, wherein the
2 position sensor indicates a position of a seal assembly relative to the
3 packer.

This Sheet Has Been Replaced





- 66 -

1 119. The packer system according to Claim 95, wherein the
2 first device communicates data indicative of a position of a seal
3 assembly relative to the packer.

1 120. A downhole tubular string monitoring system,
2 comprising:

3 a tubular string including a first sensor and a first
4 communication device communicating data acquired by the first
5 sensor; and

6 a tool positionable relative to the first device and including a
7 second communication device communicating with the first device.

1 121. The monitoring system according to Claim 120, wherein
2 the communicated data is indicative of pressure applied to the first
3 sensor.

1 122. The monitoring system according to Claim 120, wherein
2 the first device communicates data indicative of a pressure
3 differential across the tubular string.

This Sheet Has Been Replaced





1 123. The monitoring system according to Claim 120, wherein
2 the tool transmits the data to a remote location.

1 124. The monitoring system according to Claim 120, wherein
2 the first device is remotely positioned relative to the first sensor.

1 125. The monitoring system according to Claim 120, wherein
2 the tool includes a second sensor sensing pressure on the interior of
3 the tubular string, and wherein the first sensor senses pressure on
4 the exterior of the tubular string.

1 126. The monitoring system according to Claim 120, wherein
2 the first device is one of a plurality of communication devices
3 interconnected in the tubular string, and wherein the first device is
4 selected from the plurality of structures for operation of the tool
5 therewith in response to the communication between the first and
6 second devices.

This Sheet Has Been Replaced





1 127. The monitoring system according to Claim 120, wherein
2 the first device is activated from a dormant state to an active state
3 only in response to communication from the second device.

1 128. The monitoring system according to Claim 120, wherein
2 power for operation of the first device is supplied by the tool.

1 129. The monitoring system according to Claim 120, wherein
2 power for operation of the first device is supplied by a power source
3 interconnected in the tubular string.

1 130. The monitoring system according to Claim 120, wherein
2 the first device is connected to a sensor including a power source.

1 131. The monitoring system according to Claim 130, wherein
2 power to operate the first device is supplied by the sensor power
3 source.

This Sheet Has Been Replaced





- 69 -

1 132. The monitoring system according to Claim 120, wherein
2 the first sensor is a strain sensor.

1 133. The monitoring system according to Claim 120, wherein
2 the first sensor is a temperature sensor.

1 134. The monitoring system according to Claim 120, wherein
2 the first sensor is a pressure sensor.

1 135 The monitoring system according to Claim 120, wherein
2 the first sensor is associated with an item of equipment
3 interconnected in the tubular string, and wherein the tool is
4 permitted to displace a closure member of the item of equipment
5 to an open position only when predetermined acceptable data is
6 transmitted from the first sensor via the first and second devices.

1 136. The monitoring system according to Claim 135, wherein
2 the predetermined acceptable data indicates an acceptable pressure
3 differential across the closure member.

This Sheet Has Been Replaced





- 70 -

1 137. The monitoring system according to Claim 135, wherein
2 the tool is permitted to displace the closure member to an
3 equalizing position when the predetermined acceptable data is not
4 transmitted from the first sensor.

1 138. A downhole communication method, comprising the
2 steps of:

3 installing an item of equipment in a tubular string in a
4 subterranean well, the item of equipment including a first
5 communication device;

6 conveying a tool into the tubular string, the tool including a
7 second communication device; and

8 establishing communication between the first and second
9 devices.

1 139. The method according to Claim 138, wherein the step of
2 establishing communication is performed in response to positioning
3 the second device in sufficiently close proximity to the first device.

This Sheet Has Been Replaced





- 71 -

1 140. The method according to Claim 138, further comprising
2 the step of supplying power to the first device from the second
3 device.


1 141. The method according to Claim 140, wherein the
2 supplying power step is performed by transmitting waves from the
3 second device to the first device.

1 142. The method according to Claim 141, wherein the
2 transmitting step is performed by the second device generating
3 electromagnetic waves.

1 143. The method according to Claim 141, wherein the
2 transmitting step is performed by the second device generating
3 pressure waves.

1 144. The method according to Claim 143, wherein the
2 generating step is performed by exciting at least one piezoelectric
3 crystal included in the second device.

This Sheet Has Been Replaced





- 72 -

1 145. The method according to Claim 140, wherein the
2 supplying power step is performed by inductive coupling between
3 the first and second devices.

1 146. The method according to Claim 140, wherein the
2 supplying power step is performed by direct electrical contact
3 between the first and second devices.

1 147. The method according to Claim 138, wherein the
2 establishing communication step further includes activating the first
3 device from a dormant state to an active state.

1 148. The method according to Claim 147, wherein
2 performance of the activating step permits communication
3 between the first and second devices.

1 149. The method according to Claim 138, further comprising
2 the step of utilizing the communication between the first and

This Sheet Has Been Replaced.





- 73 -

3 second devices to determine when the tool is within a
4 predetermined distance of an operative position of the tool relative
5 to the item of equipment.

1 150. The method according to Claim 138, further comprising
2 the step of the first device communicating to the second device an
3 indication that the tool is operatively positioned relative to the item
4 of equipment.

1 151. The method according to Claim 138, further comprising
2 the step of utilizing the communication between the first and
3 second devices to indicate that an engagement member of the tool
4 is aligned with a profile of the item of equipment.

1 152. The method according to Claim 151, further comprising
2 the step of permitting the tool to displace the engagement member
3 into engagement with the profile in response to the indication that
4 the engagement member is aligned with the profile.

This Sheet Has Been Replaced





- 74 -

1 153. The method according to Claim 138, further comprising
2 the step of communicating data indicative of a status of the item of
3 equipment from the first device to the second device.

1 154. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a valve, and the
3 status is a position of a closure member of the valve.

1 155. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a valve, and the
3 status is a pressure applied to a closure member of the valve.

1 156. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a valve, and the
3 status is a pressure differential across a closure member of the valve.

1 157. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a portion of the

This Sheet Has Been Replaced





3 tubular string, and the status is a pressure applied to the tubular
4 string portion.

1 158. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a portion of the
3 tubular string, and the status is a strain in the tubular string portion.

1 159. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a portion of the
3 tubular string, and the status is a pressure differential across the
4 tubular string portion.

1 160. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a packer, and the
3 status is a pressure applied to the packer.

1 161. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a packer, and the
3 status is a pressure differential across the packer.

This Sheet Has Been Replaced





- 76 -

1 162. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a packer, and the
3 status is a position of a seal assembly relative to the packer.


1 163. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a packer, and the
3 status is a hardness of a seal member of the packer.

1 164. The method according to Claim 163, further comprising
2 the step of determining the seal member hardness by inducing
3 vibration of the seal member.

1 165. The method according to Claim 164, wherein the
2 determining step further comprises measuring a resonant frequency
3 of the seal member.

This Sheet Has Been Replaced





- 77 -

1 166. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a packer, and the
3 status is a compression in a seal member of the packer.

1 167. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a packer, and the
3 status is a temperature of a seal member of the packer.

1 168. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a packer, and the
3 status is a strain in a seal member of the packer.

1 169. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a packer, and the
3 status is a resistivity of a seal member of the packer.

1 170. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a plug system, and

This Sheet Has Been Replaced





- 78 -


3 the status is a pressure applied to a closure member of the plug
4 system.

1 171. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a plug system, and
3 the status is a pressure differential across a closure member of the
4 plug system.

1 172. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a plug system, and
3 the status is a pressure differential across a plug assembly of the
4 plug system.

1 173. The method according to Claim 153, wherein in the
2 communicating step, the item of equipment is a plug system, and
3 the status is a pressure differential across an equalizing member of
4 the plug system.

This Sheet Has Been Replaced





1 174. The method according to Claim 138, further comprising
2 the step of controlling operation of the tool at least in part in
3 response to data communication from the first device to the second
4 device.

1 175. The method according to Claim 174, wherein the item of
2 equipment is a valve having a closure member, and wherein the
3 controlling step further comprises restricting the tool from
4 displacing the closure member at least in part in response to data
5 communicated from the first device to the second device.

1 176. The method according to Claim 174, wherein the item of
2 equipment is a plug system having an equalizing member, and
3 wherein the controlling step further comprises restricting the tool
4 from displacing the equalizing member at least in part in response
5 to data communicated from the first device to the second device.

This Sheet Has Been Replaced





- 80 -

1 177. The method according to Claim 138, wherein the installing
2 step further comprises remotely positioning the first device relative
3 to the remainder of the item of equipment.

1 178. The method according to Claim 138, further comprising
2 the step of transmitting from the tool to a remote location data
3 communicated from the first device to the second device.

1 179. The method according to Claim 138, further comprising
2 the step of connecting the first device to a sensor including a power
3 source.

1 180. The method according to Claim 179, further comprising
2 the step of supplying power to operate the first device from the
3 sensor power source.

This Sheet Has Been Replaced





- 81 -

1 181. A particle detection system, comprising:
2 a tubular member interconnected in a tubular string;
3 a particle sensor configured for detecting flow of particles
4 through the tubular member;
5 a first communication device connected to the particle sensor;
6 and
7 a tool received in the tubular string, the tool including a
8 second communication device, and communication being
9 established between the first and second devices.

1 182. The system according to Claim 181, further comprising a
2 memory device interconnected to the sensor.

1 183. The system according to Claim 182, wherein the memory
2 device stores indications of particle flow through the tubular
3 member as detected by the sensor.

This Sheet Has Been Replaced





- 82 -

1 184. The system according to Claim 182, wherein the memory
2 device is connected to the first communication device.

1 185. The system according to Claim 184, wherein data is
2 transferred from the memory device to the tool when the first
3 communication device communicates with the second
4 communication device.

1 186. The system according to Claim 181, wherein indications of
2 particle flow through the tubular member are transferred directly
3 from the particle sensor to the tool 206 via the first and second
4 communication devices in real time.

1 187. The system according to Claim 181, wherein the first and
2 second communication devices communicate via direct electrical
3 contact.

This Sheet Has Been Replaced





1 188. The system according to Claim 181, wherein the second
2 communication device supplies power to the first communication
3 device, thereby permitting the first device to communicate with the
4 second device.

1 189. The system according to Claim 188, wherein the power is
2 supplied by electromagnetic waves emanating from the second
3 device.

1 190. The system according to Claim 189, wherein the
2 electromagnetic waves are radio frequency waves.

1 191. The system according to Claim 188, wherein the power is
2 supplied by pressure pulses emanating from the second device.

1 192. The system according to Claim 191, wherein the pressure
2 pulses are acoustic waves.

This Sheet Has Been Replaced





- 84 -

1 193. The system according to Claim 188, wherein the power is
2 supplied by direct electrical contact between the first and second
3 devices.

1 194. The system according to Claim 188, wherein the power is
2 supplied by inductive coupling between the first and second
3 devices.

1 195. The system according to Claim 181, wherein the second
2 device activates the first device from a dormant state to an active
3 state, thereby permitting communication between the first and
4 second devices.

1 196. The system according to Claim 195, wherein the
2 communication between the first and second devices is via
3 electromagnetic waves.

1 197. The system according to Claim 196, wherein the
2 electromagnetic waves are radio frequency waves.

This Sheet Has Been Replaced





1 198. The system according to Claim 195, wherein the
2 communication between the first and second devices is via pressure
3 pulses.

1 199. The system according to Claim 198, wherein the pressure
2 pulses are acoustic waves.

1 200. The system according to Claim 195, wherein the
2 communication between the first and second devices is via inductive
3 coupling between the first and second devices.

1 201. The system according to Claim 181, wherein the
2 communication between the first and second devices indicates
3 when the tool is within a predetermined distance of an operative
4 position of the tool relative to the item of equipment.

This Sheet Has Been Replaced





1 202. The system according to Claim 201, wherein the first
2 device communicates to the second device that the tool is
3 operatively positioned relative to the item of equipment.

1 203. The system according to Claim 181, wherein the particle
2 sensor detects particle flow axially through the tubular member.

1 204. The system according to Claim 181, wherein the particle
2 sensor detects particle flow through a sidewall of the tubular
3 member.

This Sheet Has Been Replaced



**AMENDED CLAIMS**

[received by the International Bureau on 24 April 2001(24.04.01);
original claims 1-204 replaced by amended claims 5-204 (36 pages)]

5. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

5 a first communication device associated with the item of equipment; and

a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close
10 proximity to the first device,

the second device supplying power to the first device, thereby permitting the first device to communicate with the second device,

the power being supplied by pressure pulses
15 emanating from the second device.

6. The system according to Claim 5, wherein the pressure pulses are acoustic waves.

20 8. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

a first communication device associated with the item of
25 equipment; and

a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close proximity to the first device,

the second device supplying power to the first device,
thereby permitting the first device to communicate with the second
device,

the power being supplied by inductive coupling between
5 the first and second devices.

12. A system for facilitating downhole communication between
an item of equipment installed in a tubular string in a subterranean
well and a tool conveyed into the tubular string, the system
10 comprising:

a first communication device associated with the item of
equipment; and

a second communication device included in the tool,
communication between the first and second devices being
15 established when the second device is brought into sufficiently close
proximity to the first device,

the second device activating the first device from a
dormant state to an active state, thereby permitting communication
between the first and second devices,

20 the communication between the first and second
device being via pressure pulses.

13. The system according to Claim 12, wherein the pressure
pulses are acoustic waves.

25

14. The system according to Claim 9, wherein the
communication between the first and second devices is via direct
electrical contact between the first and second devices.





15. The system according to Claim 9, wherein the communication between the first and second devices is via inductive coupling between the first and second devices.

5 16. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

a first communication device associated with the item of
10 equipment; and

a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close proximity to the first device,

15 the communication between the first and second devices indicating when the tool is within a predetermined distance of an operative position of the tool relative to the item of equipment.

20 17. The system according to Claim 16, wherein the first device communicates to the second device that the tool is operatively positioned relative to the item of equipment.

25 18. The system according to Claim 16, wherein the item of equipment has a profile, the tool has an engagement member configured for engagement with the profile to secure the tool relative to the item of equipment, and wherein the communication between the first and second devices indicates when the engagement member is aligned with the profile.

30

19. The system according to Claim 18, wherein the tool is permitted to displace the engagement member into engagement with the profile only when the communication between the first and second devices indicates that the engagement member is aligned
5 with the profile.

21. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system
10 comprising:

a first communication device associated with the item of equipment; and

a second communication device included in the tool, communication between the first and second devices being
15 established when the second device is brought into sufficiently close proximity to the first device,

the first device communicating a status of the item of equipment to the second device,

the item of equipment being a valve, and the status
20 being a position of the valve.

22. The system according to Claim 21, wherein the item of equipment is a packer, and wherein the status of a seal member of the packer is communicated to the second device.
25

23. The system according to Claim 22, wherein the status is a hardness of the seal member.

24. The system according to Claim 22, wherein the status is
30 compressive stress in the seal member.





25. The system according to Claim 21, wherein the item of equipment is a portion of the tubular string, and wherein the status is a strain in the portion of the tubular string.

5

26. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

10 a first communication device associated with the item of equipment; and

a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close
15 proximity to the first device

communication between the first and second devices at least partially controlling operation of the tool.

27. The system according to Claim 26, wherein an engagement
20 member of the tool is permitted to engage a profile of the item of equipment when the first and second devices are in sufficiently close proximity to each other.

28. The system according to Claim 27, wherein the profile is
25 internally formed.

29. The system according to Claim 27, wherein the profile is externally formed.

30. The system according to Claim 26, wherein the tool is permitted to displace a closure member of the item of equipment when the communication between the first and second devices indicates that a pressure differential across the closure member is
5 within a predetermined range.

31. The system according to Claim 30, wherein the tool is permitted to displace the closure member to an equalizing position configured for reducing the pressure differential, but the tool is
10 permitted to displace the closure member to an open position only when the communication between the first and second devices indicates that the pressure differential is within the predetermined range.

32. The system according to Claim 30, wherein the closure member is a pressure equalizing member, wherein the tool is permitted to displace the pressure equalizing member to an equalizing position configured for reducing the pressure differential, but the tool is permitted to remove the pressure equalizing member
15 from the item of equipment only when the communication between the first and second devices indicates that the pressure differential is within the predetermined range.

33. The system according to Claim 26, wherein the item of
25 equipment is one of a plurality of structures interconnected in the tubular string, and wherein the item of equipment is selected from the plurality of structures for operation of the tool therewith in response to the communication between the first and second devices.





34. The system according to Claim 33, wherein the tool is programmable for selection of multiple ones of the plurality of structures for operation of the tool therein in response to communication between the second device and a device of each of
5 the selected structures.

35. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system
10 comprising:

a first communication device associated with the item of equipment; and

a second communication device included in the tool, communication between the first and second devices being
15 established when the second device is brought into sufficiently close proximity to the first device,

the first device being remotely positioned relative to the remainder of the item of equipment.

20 37. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

a first communication device associated with the item of
25 equipment; and

a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close proximity to the first device

the first device including a magnet, and the second device being responsive to a magnetic field produced by the magnet.

5 38. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

 a first communication device associated with the item of
10 equipment; and

 a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close proximity to the first device,

15 the second device including a radioactive device, and the proximity between the first and second devices being indicated by the response of the second device to radioactivity.

 39. A system for facilitating downhole communication between
20 an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

 a first communication device associated with the item of equipment; and

25 a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close proximity to the first device,

 the first device including a reed switch, and the second
30 device being responsive to actuation of the reed switch.



40. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system
5 comprising:

a first communication device associated with the item of equipment; and

a second communication device included in the tool, communication between the first and second devices being
10 established when the second device is brought into sufficiently close proximity to the first device

the first device including a hall effect device, and the second device causing the hall effect device to generate an electrical current.

15

41. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

20 a first communication device associated with the item of equipment; and

a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close
25 proximity to the first device,

the first device identifying the item of equipment to the tool.



42. A system for facilitating downhole communication between an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

5 a first communication device associated with the item of equipment; and

a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close
10 proximity to the first device

the first device responding to a magnet to activate the first device from a dormant state to an active state.

43. A system for facilitating downhole communication between
15 an item of equipment installed in a tubular string in a subterranean well and a tool conveyed into the tubular string, the system comprising:

a first communication device associated with the item of equipment; and

20 a second communication device included in the tool, communication between the first and second devices being established when the second device is brought into sufficiently close proximity to the first device,

the first device responding to radioactivity to
25 activate the first device from a dormant state to an active state.



49. A downhole valve system, comprising:

a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to
5 cause displacement of the closure member between the open and closed positions, the tool including a second communication device, with communication being established between the first and second devices,

the tool being permitted to displace the closure member
10 only when predetermined acceptable data is transmitted from at least one sensor via the first and second devices.

52. A downhole valve system, comprising:

a valve including a closure member selectively positionable in
15 open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to cause displacement of the closure member between the open and closed positions, the tool including a second communication device, with communication being established between the first and second
20 devices

the first device communicating data indicative of a pressure differential across the closure member.



54. A downhole valve system, comprising:

a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to
5 cause displacement of the closure member between the open and closed positions, the tool including a second communication device, with communication being established between the first and second devices,

the first device communicating data indicative of the
10 position of the closure member to the second device.

55. The valve system according to Claim 54, wherein the first device is connected to a position sensor.

15 56. The valve system according to Claim 54, wherein the first device is connected to a pressure sensor.

57. The valve system according to Claim 54, wherein the tool transmits the data to a remote location.

20

58. A downhole valve system, comprising:

a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to
25 cause displacement of the closure member between the open and closed positions, the tool including a second communication device, with communication being established between the first and second devices,



the tool being permitted to displace the closure member to the open position only when a differential pressure across the closure member is within a predetermined range.

5 59. A downhole valve system, comprising:

a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to cause displacement of the closure member between the open and closed positions, the tool including a second communication device,
10 with communication being established between the first and second devices,

the tool being permitted to displace the closure member to an equalizing position configured for reducing a pressure differential across the closure member, but the tool being permitted
15 to displace the closure member to the open position only when the pressure differential is within a predetermined range.

60. A downhole valve system, comprising:

20 a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to cause displacement of the closure member between the open and closed positions, the tool including a second communication device,
25 with communication being established between the first and second devices,

the tool including a first pressure sensor sensing pressure on a first side of the closure member, and the valve including a second pressure sensor sensing pressure on the second side of the
30 closure member.



61. A downhole valve system, comprising:

a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

5 a tool positionable relative to the first device and operable to cause displacement of the closure member between the open and closed positions, the tool including a second communication device, with communication being established between the first and second devices,

10 the valve including a first pressure sensor sensing pressure on a first side of the closure member, and a second pressure sensor sensing pressure on a second side of the closure member.

15 62. A downhole valve system, comprising:

a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to cause displacement of the closure member between the open and closed positions, the tool including a second communication device; 20 with communication being established between the first and second devices,

the tool including an engagement member which is permitted to engage the valve only when the second device is in 25 sufficiently close proximity to the first device.



63. A downhole valve system, comprising:

a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to
5 cause displacement of the closure member between the open and closed positions, the tool including a second communication device, with communication being established between the first and second devices,

the valve being one of a plurality of structures
10 interconnected in the tubular string, and the valve being selected from the plurality of structures for operation of the tool therewith in response to the communication between the first and second devices.

15 64. The valve system according to Claim 63, wherein each of the structures has a communication device associated therewith, and wherein the tool is programmed to activate only the first device from a dormant state to an active state.

20 65. The valve system according to Claim 63, wherein each of the structures has a communication device associated therewith, and wherein the first device is activated from a dormant state to an active state only in response to communication from the second device.

25

66. A downhole valve system, comprising:

a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to
30 cause displacement of the closure member between the open and



closed positions, the tool including a second communication device,
with communication being established between the first and second
devices,

power for the operation of the first device being
5 supplied by the tool.

68. A downhole valve system, comprising:

a valve including a closure member selectively positionable in
open and closed positions, and a first communication device; and

10 a tool positionable relative to the first device and operable to
cause displacement of the closure member between the open and
closed positions, the tool including a second communication device,
with communication being established between the first and second
devices,

15 the first device being connected to a sensor including a
power source,

power to operate the first device being supplied by the
sensor power source.

20 70. A downhole valve system, comprising:

a valve including a closure member selectively positionable in
open and closed positions, and a first communication device; and

a tool positionable relative to the first device and operable to
cause displacement of the closure member between the open and
25 closed positions, the tool including a second communication device,
with communication being established between the first and second
devices,

power for the operation of the first device being
supplied by a power source of the valve,



the power source being remotely positioned relative to the valve.

71. A downhole valve system, comprising:

- 5 a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and
a tool positionable relative to the first device and operable to cause displacement of the closure member between the open and closed positions, the tool including a second communication device,
10 with communication being established between the first and second devices,

the first device being remotely positioned relative to the valve.

15 72. A downhole valve system, comprising:

- a valve including a closure member selectively positionable in open and closed positions, and a first communication device; and
a tool positionable relative to the first device and operable to cause displacement of the closure member between the open and closed positions, the tool including a second communication device,
20 with communication being established between the first and second devices,

the valve further including an opening formed through a sidewall of the valve, fluid flowing through the opening when the closure member is in the open position, and a sensor interconnected
25 to the first device and sensing a property of a fluid flowing through the opening.

73. The valve system according to Claim 72, wherein the sensor
30 is a resistivity sensor.



74. The valve system according to Claim 72, wherein the sensor is a capacitance sensor.

5 75. The valve system according to Claim 72, wherein the sensor is an inductance sensor.

76. The valve system according to Claim 72, wherein the sensor is a particle sensor.

10

77. A downhole plug system, comprising:

a plug assembly;

a first communication device;

a closure member selectively positionable in engaged and released positions relative to the plug assembly, the closure member blocking flow through the plug assembly in the engaged position, and flow through the plug assembly being permitted in the released position; and

a tool positionable relative to the first device and operable to cause displacement of the closure member between the engaged and released positions; the tool including a second communication device, and communication being established between the first and second devices.

25 78. The plug system according to Claim 77, wherein the first device communicates data indicative of pressure applied to the closure member.

79. The plug system according to Claim 78, wherein the first device is connected to a pressure sensor of the closure member.



80. The plug system according to Claim 78, wherein the first device communicates data indicative of a pressure differential across the closure member.

5

81. The plug system according to Claim 78, wherein data is communicated from the first to the second device, and wherein the tool transmits the data to a remote location.

10

82. The plug system according to Claim 77, wherein the tool is permitted to displace the closure member only when predetermined acceptable data is transmitted from at least one sensor via the first and second devices.

15

83. The plug system according to Claim 77, wherein the tool is permitted to displace the closure member to the released position only when a differential pressure across the closure member is within a predetermined range.

20

84. The plug system according to Claim 77, wherein the released position is an equalizing position configured for reducing a pressure differential across the closure member.

85. The plug system according to Claim 77, wherein the tool includes a first pressure sensor sensing pressure on a first side of the closure member, and the closure member includes a second pressure sensor sensing pressure on a second side of the closure member.



86. The plug system according to Claim 77, further comprising a first pressure sensor sensing pressure on a first side of the closure member, and a second pressure sensor sensing pressure on a second side of the closure member.

5

87. The plug system according to Claim 77, wherein the tool includes an engagement member which is permitted to engage the closure member only when the second device is in sufficiently close proximity to the first device.

10

88. The plug system according to Claim 77, wherein the plug assembly is one of a plurality of structures interconnected in the tubular string, and wherein the plug assembly is selected from the plurality of structures for operation of the tool therewith in response to the communication between the first and second devices.

89. The plug system according to Claim 88, wherein each of the structures has a communication device associated therewith, and wherein the tool is programmed to activate only the first device from a dormant state to an active state.

90. The plug system according to Claim 88, wherein each of the structures has a communication device associated therewith, and wherein the first device is activated from a dormant state to an active state only in response to communication from the second device.

91. The plug system according to Claim 77, wherein power for operation of the first device is supplied by the tool.



92. The plug system according to Claim 77, wherein power for operation of the first device is supplied by a power source of the closure member.

5

93. The plug system according to Claim 77, wherein the first device is connected to a sensor including a power source.

94. The plug system according to Claim 93, wherein power for
10 operation of the first device is supplied by the sensor power source.

95. A downhole packer system, comprising:

a packer including a first communication device and an outwardly extendable seal member; and

15 a tool positionable relative to the first device and including a second communication device, communication being established between the first and second devices.

96. The packer system according to Claim 95, wherein the first
20 device communicates data indicative of pressure applied to the seal member.

97. The packer system according to Claim 96, wherein the first device is connected to a pressure sensor of the packer.

25

98. The packer system according to Claim 96, wherein the first device communicates data indicative of a pressure differential across the seal member.



99. The packer system according to Claim 96, wherein data is communicated from the first to the second device, and wherein the tool transmits the data to a remote location.

5 100. The packer system according to Claim 95, wherein the first device is remotely positioned relative to the remainder of the packer.

10 101. The packer system according to Claim 95, wherein the packer includes a first pressure sensor sensing pressure on a first side of the seal member, and a second pressure sensor sensing pressure on a second side of the seal member.

15 102. The packer system according to Claim 95, wherein the packer is one of a plurality of structures interconnected in the tubular string, and wherein the packer is selected from the plurality of structures for operation of the tool therewith in response to the communication between the first and second devices.

20 103. The packer system according to Claim 102, wherein each of the structures has a communication device associated therewith, and wherein the tool is programmed to activate only the first device from a dormant state to an active state.

25 104. The packer system according to Claim 102, wherein each of the structures has a communication device associated therewith, and wherein the first device is activated from a dormant state to an active state only in response to communication from the second device.



105. The packer system according to Claim 95, wherein power for operation of the first device is supplied by the tool.

106. The packer system according to Claim 95, wherein power
5 for operation of the first device is supplied by a power source of the packer.

107. The packer system according to Claim 95, wherein the first
10 device is connected to a sensor including a power source.

108. The packer system according to Claim 107, wherein power to operate the first device is supplied by the sensor power source.

109. The packer system according to Claim 95, wherein the first
15 device is connected to a seal member sensor.

110. The packer system according to Claim 109, wherein the seal member sensor is a temperature sensor.

20 111. The packer system according to Claim 109, wherein the seal member sensor is a compression sensor.

112. The packer system according to Claim 109, wherein the seal member sensor is a resistivity sensor.

25 113. The packer system according to Claim 109, wherein the seal member sensor is a strain sensor.

114. The packer system according to Claim 109, wherein the
30 seal member sensor is a hardness sensor.



115. The packer system according to Claim 109, wherein the seal member sensor is a resonant frequency sensor.

5 116. The packer system according to Claim 115, wherein the seal member sensor induces vibration in the seal member.

117. The packer system according to Claim 95, wherein the packer includes a position sensor.

10

118. The packer system according to Claim 117, wherein the position sensor indicates a position of a seal assembly relative to the packer.

15 119. The packer system according to Claim 95, wherein the first device communicates data indicative of a position of a seal assembly relative to the packer.

120. A downhole tubular string monitoring system,
20 comprising:

a tubular string including a first sensor and a first communication device communicating data acquired by the first sensor; and

a tool positionable relative to the first device and including a
25 second communication device communicating with the first device.

121. The monitoring system according to Claim 120, wherein the communicated data is indicative of pressure applied to the first sensor.



122. The monitoring system according to Claim 120, wherein the first device communicates data indicative of a pressure differential across the tubular string.

5 123. The monitoring system according to Claim 120, wherein the tool transmits the data to a remote location.

124. The monitoring system according to Claim 120, wherein the first device is remotely positioned relative to the first sensor.

10

125. The monitoring system according to Claim 120, wherein the tool includes a second sensor sensing pressure on the interior of the tubular string, and wherein the first sensor senses pressure on the exterior of the tubular string.

15

126. The monitoring system according to Claim 120, wherein the first device is one of a plurality of communication devices interconnected in the tubular string, and wherein the first device is selected from the plurality of structures for operation of the tool
20 therewith in response to the communication between the first and second devices.

127. The monitoring system according to Claim 120, wherein the first device is activated from a dormant state to an active state
25 only in response to communication from the second device.

128. The monitoring system according to Claim 120, wherein power for operation of the first device is supplied by the tool.



129. The monitoring system according to Claim 120, wherein power for operation of the first device is supplied by a power source interconnected in the tubular string.

5 130. The monitoring system according to Claim 120, wherein the first device is connected to a sensor including a power source.

131. The monitoring system according to Claim 130, wherein power to operate the first device is supplied by the sensor power
10 source.

132. The monitoring system according to Claim 120, wherein the first sensor is a strain sensor.

15 133. The monitoring system according to Claim 120, wherein the first sensor is a temperature sensor.

134. The monitoring system according to Claim 120, wherein the first sensor is a pressure sensor.

20

135 The monitoring system according to Claim 120, wherein the first sensor is associated with an item of equipment interconnected in the tubular string, and wherein the tool is permitted to displace a closure member of the item of equipment to
25 an open position only when predetermined acceptable data is transmitted from the first sensor via the first and second devices.

136. The monitoring system according to Claim 135, wherein the predetermined acceptable data indicates an acceptable pressure
30 differential across the closure member.



137. The monitoring system according to Claim 135, wherein the tool is permitted to displace the closure member to an equalizing position when the predetermined acceptable data is not
5 transmitted from the first sensor.

139. A downhole communication method, comprising the steps of:

installing an item of equipment in a tubular string in a
10 subterranean well, the item of equipment including a first communication device;

conveying a tool into the tubular string, the tool including a second communication device; and

establishing communication between the first and second
15 devices,

the step of establishing communication being performed in response to positioning the second device in sufficiently close proximity to the first device.

20 143. A downhole communication method, comprising the steps of:

installing an item of equipment in a tubular string in a subterranean well, the item of equipment including a first communication device;

25 conveying a tool into the tubular string, the tool including a second communication device; and

establishing communication between the first and second devices,

the supplying power step being performed by
30 transmitting waves from the second device to the first device,



the transmitting step being performed by the second device generating pressure waves.

144. The method according to Claim 143, wherein the
5 generating step is performed by exciting at least one piezoelectric crystal included in the second device.

145. A downhole communication method, comprising the steps of:

10 installing an item of equipment in a tubular string in a subterranean well, the item of equipment including a first communication device;

conveying a tool into the tubular string, the tool including a second communication device;

15 establishing communication between the first and second devices; and

supplying power to the first device from the second device,
the supplying power step being performed by inductive coupling between the first and second devices.

20

149. A downhole communication method, comprising the steps of:

installing an item of equipment in a tubular string in a subterranean well, the item of equipment including a first
25 communication device;

conveying a tool into the tubular string, the tool including a second communication device;

establishing communication between the first and second devices; and



utilizing the communication between the first and second devices to determine when the tool is within a predetermined distance of an operative position of the tool relative to the item of equipment.

5

150. The method according to Claim 138, further comprising the step of the first device communicating to the second device an indication that the tool is operatively positioned relative to the item of equipment.

10

151. The method according to Claim 138, further comprising the step of utilizing the communication between the first and second devices to indicate that an engagement member of the tool is aligned with a profile of the item of equipment.

15

152. The method according to Claim 151, further comprising the step of permitting the tool to displace the engagement member into engagement with the profile in response to the indication that the engagement member is aligned with the profile.

20

156. The method according to Claim 153, wherein in the communicating step, the item of equipment is a valve, and the status is a pressure differential across a closure member of the valve.

25

157. The method according to Claim 153, wherein in the communicating step, the item of equipment is a portion of the tubular string, and the status is a pressure applied to the tubular string portion.



158. The method according to Claim 153, wherein in the communicating step, the item of equipment is a portion of the tubular string, and the status is a strain in the tubular string portion.

5 159. The method according to Claim 153, wherein in the communicating step, the item of equipment is a portion of the tubular string, and the status is a pressure differential across the tubular string portion.

10 160. The method according to Claim 153, wherein in the communicating step, the item of equipment is a packer, and the status is a pressure applied to the packer.

15 161. The method according to Claim 153, wherein in the communicating step, the item of equipment is a packer, and the status is a pressure differential across the packer.

20 162. The method according to Claim 153, wherein in the communicating step, the item of equipment is a packer, and the status is a position of a seal assembly relative to the packer.

25 163. The method according to Claim 153, wherein in the communicating step, the item of equipment is a packer, and the status is a hardness of a seal member of the packer.

164. The method according to Claim 163, further comprising the step of determining the seal member hardness by inducing vibration of the seal member.



165. The method according to Claim 164, wherein the determining step further comprises measuring a resonant frequency of the seal member.

5 166. The method according to Claim 153, wherein in the communicating step, the item of equipment is a packer, and the status is a compression in a seal member of the packer.

167. The method according to Claim 153, wherein in the
10 communicating step, the item of equipment is a packer, and the status is a temperature of a seal member of the packer.

168. The method according to Claim 153, wherein in the
15 communicating step, the item of equipment is a packer, and the status is a strain in a seal member of the packer.

169. The method according to Claim 153, wherein in the communicating step, the item of equipment is a packer, and the status is a resistivity of a seal member of the packer.

20

170. The method according to Claim 153, wherein in the communicating step, the item of equipment is a plug system, and the status is a pressure applied to a closure member of the plug system.

25

171. The method according to Claim 153, wherein in the communicating step, the item of equipment is a plug system, and the status is a pressure differential across a closure member of the plug system.



172. The method according to Claim 153, wherein in the communicating step, the item of equipment is a plug system, and the status is a pressure differential across a plug assembly of the plug system.

5

173. The method according to Claim 153, wherein in the communicating step, the item of equipment is a plug system, and the status is a pressure differential across an equalizing member of the plug system.

10

174. The method according to Claim 138, further comprising the step of controlling operation of the tool at least in part in response to data communication from the first device to the second device.

15

175. The method according to Claim 174, wherein the item of equipment is a valve having a closure member, and wherein the controlling step further comprises restricting the tool from displacing the closure member at least in part in response to data communicated from the first device to the second device.

20

176. The method according to Claim 174, wherein the item of equipment is a plug system having an equalizing member, and wherein the controlling step further comprises restricting the tool from displacing the equalizing member at least in part in response to data communicated from the first device to the second device.

25



177. A downhole communication method, comprising the steps of:

installing an item of equipment in a tubular string in a subterranean well, the item of equipment including a first communication device;

conveying a tool into the tubular string, the tool including a second communication device; and

establishing communication between the first and second devices,

the installing step further comprising remotely positioning the first device relative to the remainder of the item of equipment.

181. A particle detection system, comprising:

a tubular member interconnected in a tubular string;

a particle sensor configured for detecting flow of particles through the tubular member;

a first communication device connected to the particle sensor; and

a tool received in the tubular string, the tool including a second communication device, and communication being established between the first and second devices.

182. The system according to Claim 181, further comprising a memory device interconnected to the sensor.

183. The system according to Claim 182, wherein the memory device stores indications of particle flow through the tubular member as detected by the sensor.



184. The system according to Claim 182, wherein the memory device is connected to the first communication device.

185. The system according to Claim 184, wherein data is
5 transferred from the memory device to the tool when the first communication device communicates with the second communication device.

186. The system according to Claim 181, wherein indications of
10 particle flow through the tubular member are transferred directly from the particle sensor to the tool via the first and second communication devices in real time.

187. The system according to Claim 181, wherein the first and
15 second communication devices communicate via direct electrical contact.

188. The system according to Claim 181, wherein the second communication device supplies power to the first communication
20 device, thereby permitting the first device to communicate with the second device.

189. The system according to Claim 188, wherein the power is
25 supplied by electromagnetic waves emanating from the second device.

190. The system according to Claim 189, wherein the electromagnetic waves are radio frequency waves.



191. The system according to Claim 188, wherein the power is supplied by pressure pulses emanating from the second device.

192. The system according to Claim 191, wherein the pressure
5 pulses are acoustic waves.

193. The system according to Claim 188, wherein the power is supplied by direct electrical contact between the first and second devices.

10

194. The system according to Claim 188, wherein the power is supplied by inductive coupling between the first and second devices.

195. The system according to Claim 181, wherein the second
15 device activates the first device from a dormant state to an active state, thereby permitting communication between the first and second devices.

196. The system according to Claim 195, wherein the
20 communication between the first and second devices is via electromagnetic waves.

197. The system according to Claim 196, wherein the
electromagnetic waves are radio frequency waves.

25

198. The system according to Claim 195, wherein the communication between the first and second devices is via pressure pulses.



199. The system according to Claim 198, wherein the pressure pulses are acoustic waves.

200. The system according to Claim 195, wherein the
5 communication between the first and second devices is via inductive coupling between the first and second devices.

201. The system according to Claim 181, wherein the
10 communication between the first and second devices indicates when the tool is within a predetermined distance of an operative position of the tool relative to the item of equipment.

202. The system according to Claim 201, wherein the first
15 device communicates to the second device that the tool is operatively positioned relative to the item of equipment.

203. The system according to Claim 181, wherein the particle sensor detects particle flow axially through the tubular member.

204. The system according to Claim 181, wherein the particle
20 sensor detects particle flow through a sidewall of the tubular member.

