

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 May 2003 (08.05.2003)

PCT

(10) International Publication Number
WO 03/038159 A2

(51) International Patent Classification⁷: **C25D 17/28**,
21/12

(21) International Application Number: PCT/EP02/11764

(22) International Filing Date: 21 October 2002 (21.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
101 53 171.0 27 October 2001 (27.10.2001) DE

(71) Applicant (for all designated States except US):
ATOTECH DEUTSCHLAND GMBH [DE/DE];
Erasmusstrasse 20, 10553 Berlin (DE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HÜBEL, Egon**
[DE/DE]; Altdorfer Strasse 35, 90537 Feucht (DE).

(74) Agent: **EFFERT, BRESSEL UND KOLLEGEN**;
Radickestrasse 48, 12489 Berlin (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND CONVEYORIZED SYSTEM FOR ELECTROLYTICALLY PROCESSING WORK PIECES



(57) Abstract: In order to avoid an edge-effect (increased electrical field line density at the edges of electrolytically to be processed work pieces) during the electrolytic processing of work pieces 3.x in a conveyORIZED system, the electric currents originating from various counter electrodes 5.x in the plant are set to values in function of the electrolytically to be processed surface areas of the work pieces 3.x as far as they are located directly opposite the respective ones of the various counter electrodes 5.x. Moreover, the distance between the work pieces 3.x and the counter electrodes 5.x is chosen to be 50mm maximum. Means 19 for individually controlling and adjusting every single current supply unit 15.x of the counter electrodes 5.x are provided for this purpose. Said means 19 are configured in such a manner that the respective electric currents originating from the various counter electrodes 5.x are settable to values in function of the electrolytically to be processed surface areas of the work pieces 3.x, as far as they are located directly opposite the respective various counter electrodes 5.x.



WO 03/038159 A2