

AN ADDITIVE COMPOSITION HAVING LOW TEMPERATURE VISCOSITY, CORROSION AND DETERGENT PROPERTIES

5 The present invention relates to an additive composition for lubricating oils used in internal combustion engines. More particularly, the present invention relates to an additive composition containing an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation with an alkaline earth metal salt of a linear, saturated carboxylic acid. The additive composition of the present invention provides low temperature viscosity,
10 corrosion and detergent properties when used in lubricating oils for internal combustion engines.

BACKGROUND OF THE INVENTION

15 The preparation of hydrocarbyl phenates and hydrocarbyl salicylates is well known in the art.

U.S. Patent No. 3,036,971 discloses preparing detergent-dispersant additives based on sulfurized alkylphenates of high basicity alkaline earth metals. These
20 additives are prepared by sulfurization of an alkylphenol, neutralization of the sulfurized alkylphenol with an alkaline earth metal base, then super-alkalization by carbonation of the alkaline earth metal base dispersed in the sulfurized alkylphenate.

25 U.S. Patent No. 3,410,798 discloses basic metal salts of phenol or salicylic acid sulfides prepared by reacting a phenol or salicylic acid, or a salt thereof, with sulfur and an alkaline earth base at a temperature of about 150-200°C, in the presence of a carboxylic acid or salt thereof and a polyalkylene glycol or alkylene or polyalkylene glycol alkyl ether. The products are useful as detergent
30 additives for lubricants.

U.S. Patent No. 5,035,816 discloses a process for preparing alkylsalicylate superalkalinized detergent-dispersant lubricating oil additives: (a) by the acid

catalyzed neutralization of C₁₂-C₃₀ alkylphenol with alkaline earth base in the presence of an azeotropic solvent for the water of reaction; (b) by the carboxylation of the first product with CO₂ to partially convert the alkylphenate to alkylsalicylate; and (c) by sulfurization-superalkalinization of the product in the presence of sulfur, alkaline earth base, azeotropic solvent and added CO₂.
5 superalkalized detergent-dispersant additives based on alkylphenates and alkylsalicylates.

U.S. Patent No. 6,291,408 discloses dispersant detergent additives for lubricating oils prepared by neutralization, carboxylation, sulfurization-
10 overalkalinization, carbonation, distillation, filtering and degassing from alkyl phenols containing 35-85% by weight of linear alkyl substituents. The process does not require, during the neutralizing phase, the presence of a third solvent, which, by forming an azeotropic mixture with water promote the elimination of water arising from the neutralizing reaction. The additives of the invention have
15 improved stability to hydrolysis and improved dispersion properties, improved compatibility and improved foaming properties.

U.S. Patent Nos. 6,162,770 and 6,262,001 teach an unsulfurized, alkali metal-free, detergent-dispersant composition having from 40% to 60% alkylphenol, from 10% to 40% alkaline earth alkylphenate, and from 20% to 40% alkaline
20 earth single-aromatic-ring alkylsalicylate, and a process for preparing the same. This composition may have an alkaline earth double-aromatic-ring alkylsalicylate as long as the mole ratio of single-ring alkylsalicylate to double-aromatic-ring alkylsalicylate is at least 8:1. This composition may be produced by the three-step process involving neutralization of alkylphenols, carboxylation
25 of the resulting alkylphenate, and filtration of the product of the carboxylation step. The detergent-dispersant produced by the method can be used in an engine lubricating composition to improve antioxidant properties, high temperature deposit control, and black sludge control.

30 The addition of aliphatic carboxylic acids during the preparation of lubricating oil detergents is known. The resulting detergents can be referred to as carboxylic

acid modified detergents and a variety of such detergents are known. The incorporation of aliphatic carboxylic acids into such detergents is known to modify their physical and/or performance properties. The most common physical modification observed by the incorporation of fatty acids into
5 detergents, which is also the most common reason for performing this modification, is an increase in the TBN of the detergent without deleteriously increasing the viscosity of the product to an unacceptable level.

U.S. Patent No. 3,493,516 discloses that the alkalinity value in the preparation
10 of overbased phenates is enhanced by the addition of aliphatic carboxylic acids of from 1 to 6 carbon atoms to the reaction mixture during the preparation of the overbased alkyl phenate. Adding small amounts of low molecular weight carboxylic acids during the preparation of overbased alkylphenates, greater than 10 percent enhancements in the amount of calcium is obtained. The
15 enhanced amount of calcium provides greater neutralization capability and superior protection in the engine against sludge formation. Despite the great enhancement in calcium content, the viscosity remains sufficiently low to provide a tractable product.

20 European Patent Application No. 385,616 discloses the use of fatty acids in the production of overbased phenates from alkylphenols or phenates with increased TBN's and acceptable viscosity.

European Patent Application No. 351,052 discloses the use of long chain
25 carboxylic acids in the production of overbased salicylate detergents with TBN's greater than 300 and viscosity's less than 1000 cSt at 100°C.

European Patent Application No. 347,104 discloses the use of long chain carboxylic acids to produce overbased carboxylic modified low overbased
30 sulphonates and/or phenates and/or salicylate detergents with improved deposit forming properties.

European Patent Application No. 347,103 discloses a process for producing carboxylic acid modified overbased phenates with TBN's greater than 300 and viscosities less than 1000 cSt at 100°C starting from a phenate.

- 5 European Patent Application No. 351,053 discloses the production of carboxylic acid modified overbased sulphonates with TBN's greater than 350 and viscosities less than 1000 cSt at 100°C that have better filtration processing characteristics.
- 10 U.S. Patent No. 5,716,914 discloses a process for producing a carboxylic acid modified overbased phenates with TBN's greater than 300 and viscosities less than 1000 cSt at 100°C.
- 15 U.S. Patent No. 5,069,804 discloses improved stability of overbased phenates, particularly when formulated with overbased sulphonates, as well as improved foaming tendency and viscosity is obtained by treating the overbased phenate, either during or subsequent to the overbasing process, with from 0.1 to 10 wt %, preferably 2 to 6 wt %, of a carboxylic acid with a C₁₀ to C₂₄ unbranched segment, e.g. behenic acid.
- 20 U.S. Patent No. 5,714,443 discloses an additive concentrate suitable for incorporation into a into a finished lubricating oil composition, the additive concentrate comprising: (a) a lubricating oil; (b) a lubricating oil soluble sulphurised alkaline earth metal hydrocarbyl phenate modified by incorporation of from greater than 2 to 35% by weight based on the weight of the composition
- 25 of either (i) at least one carboxylic acid having formula (I), wherein R is C₁₀ to C₂₄ alkyl or alkenyl group and R¹ is either hydrogen, a C₁ to C₄ alkyl group or a --CH₂ --COOH group, or an anhydride, acid chloride or ester thereof or (ii) a di- or polycarboxylic acid containing from 36 to 100 carbon atoms or an anhydride, acid chloride or ester thereof, the composition having a TBN greater than 300.
- 30 U.S. Patent No. 5,433,871 discloses a process for the production of carboxylic acid modified overbased mixed detergents (phenate and/or salicylate and/or

napthenate and/or sulfonate) with TBN's greater than 300 while retaining an acceptable viscosity.

U.S. Patent No. 6,348,438 discloses an overbased alkaline earth metal single-aromatic ring hydrocarbyl salicylate-carboxylate is produced by overbasing a mixture of a single-aromatic ring hydrocarbyl salicylate, at least one solvent, a metal hydroxide, and an alkyl polyhydric alcohol alkaline earth metal hydroxide, by contacting that mixture with carbon dioxide under overbasing reaction conditions. The alkyl group of the alkyl polyhydric alcohol has from one to five carbon atoms. The overbased metal single-aromatic ring hydrocarbyl salicylate is treated, before, during, or subsequent to overbasing, with a long-chain carboxylic acid to form a single-aromatic ring hydrocarbyl salicylate-carboxylate.

SUMMARY OF THE INVENTION

Disclosed herein is an additive composition for lubricating oils used in internal combustion engines. More particularly, disclosed herein is an additive composition that provides low temperature viscosity, corrosion and detergent properties when used in lubricating oils for internal combustion engines.

In one aspect, there is provided an additive composition comprising an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

Preferably, the sediment value is less than 0.15 %, more preferably less than 0.1 % by volume.

Preferably, the unsulfurized carboxylate detergent-dispersant additive comprises:

- a) Less than about 30 wt % hydrocarbyl phenol,
- b) from about 10 wt % to 50 wt % alkaline earth metal hydrocarbyl phenate, and
- c) from about 15 wt % to 60 wt % alkaline earth metal single aromatic-ring hydrocarbyl salicylate.

The hydrocarbyl group on the hydrocarbyl phenol, hydrocarbyl phenate and hydrocarbyl salicylate is independently derived from a linear olefin, an isomerized olefin, a branched chain olefin or a mixture thereof. The hydrocarbyl group is typically an alkyl group having from about 12 to 40, preferably from about 18 to 30 carbon atoms. The alkyl group is derived from an isomerized olefin. The alkyl group may be a branched alkyl group having at least 9, preferably from about 9 to 24, and more preferably from about 10 to 18, carbon atoms.

The alkaline earth metal of the alkaline earth metal hydrocarbyl phenate and the alkaline earth metal single aromatic-ring hydrocarbyl salicylate is independently selected from the group consisting of calcium, magnesium, barium or strontium. Preferably, the alkaline earth metal of the alkaline earth metal hydrocarbyl phenate and the alkaline earth metal single aromatic-ring hydrocarbyl salicylate is calcium.

The alkaline earth metal of the alkaline earth metal salt of the linear, saturated carboxylic acid is calcium. Preferably, the linear, saturated carboxylic acid is stearic acid. The preferred alkaline earth metal salt of the linear, saturated carboxylic acid is calcium stearate.

Typically, the alkaline earth metal salt of the linear, saturated carboxylic acid is present at a concentration of from about 3.2 wt % to 7.5 wt %, preferably from about 3.5 wt % to 7.0 wt %, and more preferably from about 4.0 wt % to 6.0 wt %, based on the total additive composition.

In another aspect, there is provided a lubricating oil composition comprising:

- a) a major amount of base oil of lubricating viscosity; and
- b) a minor amount of an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

In yet another aspect, there is provided a method for producing an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

The method comprising:

- a) neutralizing one or more hydrocarbyl phenols using an alkaline earth metal base to form an intermediate product,
- b) carboxylating the intermediate product of a) using carbon dioxide so that at least about 5 wt % of the original hydrocarbyl phenol starting material has been converted to alkaline earth single aromatic-ring hydrocarbyl salicylate,
- c) separating at least about 10 wt % of the starting hydrocarbyl phenols from the product obtained in b), and
- d) adding an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms in the presence of a solvent selected from the group consisting

of aromatic hydrocarbons, aliphatic hydrocarbons and monoalcohols to produce the unsulfurized carboxylate detergent-dispersant additive.

- 5 In still another aspect, there is provided a product produced according to the method described above.

In yet another aspect, there is provided a method of improving low temperature viscosity while maintaining corrosion and detergent

- 10 properties of a lubricating oil composition in an internal combustion engine, said method comprising operating the internal combustion engine with a lubricating oil composition comprising:

- 15 a) a major amount of base oil of lubricating viscosity; and
b) a minor amount of an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms
20 and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

Preferably, the lubricating oil composition is a low emission diesel lubricant.

25

Among other aspects, the disclosed additive composition has been found to be effective in improving the low temperature viscosity of lubricating oils when employed in internal combustion engines. In particular, the additive composition is preferably desirable in low emission diesel lubricants (LEDL) in low emission diesel engines equipped with exhaust gas after-
30 treatment systems. Additional beneficial properties of the LEDL are the low levels of ash, sulfur, and phosphorus contents. Not only does the LEDL disclosed herein provide improved low temperature properties, it also provides

measurable improvement of corrosion and detergency properties when employed in low emission diesel engines.

DETAILED DESCRIPTION OF THE INVENTION

5

As mentioned previously, the present invention relates to an additive composition comprising an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a
10 linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

15 Prior to discussing the present invention in detail, the following terms have the following meanings unless expressly stated to the contrary.

Definitions

20 The term "hydrocarbyl" means an alkyl or alkenyl group.

The term "alkali metal" or "alkaline metal" means lithium, sodium or potassium.

The term "metal" means alkali metals, alkaline earth metals, or mixtures
25 thereof.

The term "alkaline earth metal" means calcium, barium, magnesium, strontium, or mixtures thereof.

30 The term "salicylate" means a metal salt of a salicylic acid.

The term "alkaline earth metal single-aromatic-ring hydrocarbyl salicylate" means an alkaline earth metal salt of a hydrocarbyl salicylic acid, wherein there

is only one hydrocarbyl salicylic anion per each alkaline earth metal base cation.

5 The term "alkaline earth metal single-aromatic-ring alkylsalicylate" means an alkaline earth metal single-aromatic-ring hydrocarbyl salicylate wherein the hydrocarbyl group is an alkyl group.

10 The term "alkaline earth metal double-aromatic-ring hydrocarbyl salicylate" means an alkaline earth metal salt of a hydrocarbyl salicylic acid, wherein there are two hydrocarbyl salicylic anions per each alkaline earth metal base cation.

15 The term "alkaline earth metal double-aromatic-ring alkylsalicylate" means an alkaline earth metal double-aromatic-ring hydrocarbyl salicylate wherein the hydrocarbyl groups are alkyl groups.

The term "hydrocarbyl phenol" means a phenol having one or more hydrocarbyl substituents; at least one of which has a sufficient number of carbon atoms to impart oil solubility to the phenol.

20 The term "alkylphenol" means a phenol having one or more alkyl substituents, wherein at least one of the alkyl substituents has a sufficient number of carbon atoms to impart oil solubility to the phenol.

The term "phenate" means a metal salt of a phenol.

25 The term "hydrocarbyl phenate" means a metal salt of a hydrocarbyl phenol.

The term "alkaline earth metal hydrocarbyl phenate" means an alkaline earth metal salt of a hydrocarbyl phenol.

30 The term "isomerized" means a linear olefin that has been isomerized prior to alkylation of a phenol.

The term "linear, saturated carboxylic acid" means a carboxylic acid having a linear, saturated alkyl chain, wherein the average carbon number of the carboxylic acid is from about 16 to about 20.


- 5 The term "stearic acid" means a linear, saturated carboxylic acid, wherein the carbon number of the acid is predominately 18.

The term "unsulfurized" means containing less than 0.1 wt % sulfur.


- 10 The term "Total Base Number" or "TBN" refers to the equivalent number of milligrams of KOH needed to neutralize 1 gram of a product. Therefore, a high TBN reflects strongly overbased products and, as a result, a higher base reserve for neutralizing acids. The TBN of a product can be determined by ASTM Standard No. D2896 or equivalent procedure.

15

The term "carboxylate" refers to an alkaline earth metal single aromatic ring hydrocarbyl salicylate.



single aromatic ring hydrocarbyl salicylate wherein M_1 is an alkaline earth metal selected from the group consisting of barium, calcium, magnesium, and strontium



double aromatic ring hydrocarbyl salicylate.


When the weight ratio of single aromatic ring hydrocarbyl salicylate divided by double aromatic ring hydrocarbyl salicylate is greater than 8:1, it is also called single aromatic ring hydrocarbyl salicylate.

5

Unless otherwise specified, all percentages are in weight percent (wt %).

Unsulfurized Carboxylate Detergent-Dispersant Additive

- 10 The additive composition of the present invention comprises an unsulfurized carboxylate detergent-dispersant additive as shown in Formula (I) below (also referred to herein as "carboxylate" or "carboxylated detergent").



15

Formula I

- wherein R_a is a linear hydrocarbyl group, branched hydrocarbyl group, or a mixture thereof. Preferably, R_a is an alkenyl or alkyl group. More preferably, R_a is an alkyl group. M_1 is an alkaline earth metal selected from the group consisting of barium, calcium, magnesium, and strontium. Calcium is preferred.
- 20

Level of Superalkalinization

- The level of superalkalinization is the molar ratio of mineral calcium salt to organic calcium. The level of superalkalinization is preferably low because high soap content is desired in order to obtain good detergency properties. The level of superalkalinization takes into account:
- 25

- Mineral calcium salt is mainly calcium carbonate coming from the reaction of lime with carbon dioxide (CO_2)
- Calcium soap is mainly the calcium linked to a long alkyl chain (stearic, alkylphenol or single aromatic ring alkylcyclic)
- 5 ▪ Calcium formiate, calcium acetate and calcium glycolate are in very low quantity, so they are not included in the determination of level of superalkalinization

Typically, the level of superalkalinization is less than about 1.4:1, preferably
10 less than about 1.2:1, more preferably less than about 1:1 and most preferably less than about 0.2:1.

The unsulfurized carboxylate detergent-dispersant additive may be prepared by the following process.

15

A. Neutralization Step

In the first step, alkylphenols are neutralized using an alkaline-earth metal base in the presence of at least one carboxylic acid that contains from about 1 to 4
20 carbon atoms, i.e., C_1 to C_4 as a promoter. This reaction is carried out in the absence of alkaline metal base, and in the absence of dialcohol or monoalcohol.

The hydrocarbyl group on the hydrocarbyl phenols may be derived from up to
25 about 98 wt % linear olefin groups, up to about 98 wt % isomerized olefin groups, up to about 100 wt % branched chain olefin groups, or a mixture thereof. Preferably, the linear hydrocarbyl group is an alkyl group having from about 12 to 40 carbon atoms, more preferably from about 18 to 30 carbon atoms. The alkyl group may be derived from an isomerized olefin. The
30 branched chain olefin group is an alkyl group having at least 9 carbon atoms, preferably from about 9 to 24 carbon atoms, more preferably from about 10 to 18 carbon atoms.

In one embodiment, the hydrocarbonyl group of the hydrocarbonyl phenols is derived from up to 85 wt % of linear olefin (preferably at least 35 wt % linear olefin) in mixture with at least 15 wt % of branched chain olefin.

- 5 The use of an alkylphenol containing up to at least 35 wt % of long chain linear alkylphenol, wherein the alkyl group has from about 18 to 30 carbon atoms, is particularly attractive because a long linear alkyl chain promotes the compatibility and solubility of the additives in lubricating oils. However, the presence of relatively long linear alkyl groups in the alkylphenols makes the
- 10 latter less reactive than branched alkylphenols, hence the need to use harsher reaction conditions to bring about their neutralization by an alkaline-earth metal base. For example, linear olefins are marketed by Chevron Phillips Company (CPC) under the names normal alpha olefin NAO C₂₆-C₂₈ or normal alpha olefin NAO C₂₀-C₂₄.

15

Branched alkylphenols can be obtained by reaction of phenol with a branched olefin, generally originating from propylene. They consist of a mixture of monosubstituted isomers, the great majority of the substituents being in the para position, very few being in the ortho position, and hardly any in the meta

20 position. That makes them relatively reactive towards an alkaline-earth metal base, since the phenol function is practically devoid of steric hindrance.

On the other hand, linear alkylphenols can be obtained by reaction of phenol with a linear olefin, generally originating from ethylene. They consist of a

25 mixture of monosubstituted isomers in which the proportion of linear alkyl substituents in the ortho, meta, and para positions is much more uniformly distributed. This makes them much less reactive towards an alkaline-earth metal base since the phenol function is much less accessible due to considerable steric hindrance, due to the presence of closer and generally

30 heavier alkyl substituents. Of course, linear alkylphenols may contain alkyl substituents with some branching, such as those marketed by the British Petroleum Company (BP) under the name BP Olefin C₂₀-C₂₆, which increases the amount of para substituents and, resultantly, increases the relative

reactivity towards alkaline earth metal bases. One difference between CPC NAO C₂₀-C₂₄ and BP olefin C₂₀-C₂₆ is the level of alpha olefin (double bond at the end of alkyl chain) which is around 90 % in CPC and in the range of 30 % to 65 % in BP which has some internal olefin. Another way to increase the reactivity of linear alpha olefin such as CPC C₂₀-C₂₄ and CPC C₂₀-C₂₈ is to isomerize them before the conversion into alkylphenols.

The alkaline earth metal bases that can be used for carrying out this step include the oxides or hydroxides of calcium, magnesium, barium, or strontium, and particularly of calcium oxide, calcium hydroxide, magnesium oxide, and mixtures thereof. In one embodiment, slaked lime (calcium hydroxide) is preferred.

The promoter used in this step can be any material that enhances neutralization. For example, the promoter may be a polyhydric alcohol, ethylene glycol or any carboxylic acid. Preferably, a carboxylic acid is used. More preferably, C₁ to C₄ carboxylic acids are used in this step include formic, acetic, propionic and butyric acid, and may be used alone or in mixture. Preferably, a mixture of acids is used, most preferably a formic acid/acetic acid mixture. The molar ratio of formic acid/acetic acid should be from about 0.2:1 to 100:1, preferably from about 0.5:1 to 4:1, and most preferably about 1:1. The carboxylic acids act as transfer agents, assisting the transfer of the alkaline-earth metal bases from a mineral reagent to an organic reagent.

The neutralization operation is carried out at a temperature of at least 200°C, preferably at least 215°C, and, more preferably, at least 240°C. The pressure is reduced gradually below atmospheric in order to distill off the water of reaction. Accordingly, the neutralization should be conducted in the absence of any solvent that may form an azeotrope with water. Preferably, the pressure is reduced to no more than 7,000 Pa (70 mbars).

The quantities of reagents used should correspond to the following molar ratios:

(1) alkaline-earth metal base/alkylphenol from about 0.2:1 to 0.7:1, preferably from about 0.3:1 to 0.5:1; and

(2) carboxylic acid/alkylphenol from about 0.01:1 to 0.5:1, preferably from about 0.03:1 to 0.15:1.

5

Preferably, at the end of this neutralization step the hydrocarbyl phenate obtained is kept for a period not exceeding fifteen hours at a temperature of at least 215°C and at an absolute pressure from about 5,000 to 10^5 Pa (between 0.05 and 1.0 bar). More preferably, at the end of this neutralization step the
10 alkylphenate obtained is kept for between two and six hours at an absolute pressure from about 10,000 to 20,000 Pa (between 0.1 and 0.2 bar).

By providing that operations are carried out at a sufficiently high temperature and that the pressure in the reactor is reduced gradually below atmospheric,
15 the neutralization reaction is carried out without the need to add a solvent that forms an azeotrope with the water formed during this reaction.

B. Carboxylation Step

20 The carboxylation step is conducted by simply bubbling carbon dioxide into the reaction medium originating from the preceding neutralization step and is continued until at least about 5 wt % of the starting alkylphenol has been converted to hydrocarbyl salicylate (measured as salicylic acid by potentiometric determination). It must take place under pressure in order to
25 avoid any decarboxylation of the hydrocarbyl salicylate that forms.

Preferably, at least 22 mole %, of the starting alkylphenols is converted to alkylsalicylate using carbon dioxide at a temperature between 180°C and 240°C, under a pressure within the range of from above atmospheric pressure
30 to 15×10^5 Pa (15 bars) for a period of one to eight hours.

According to one variant, at least 25 mole % of the starting alkylphenols is

converted to alkylsalicylate using carbon dioxide at a temperature equal to or greater than 200°C under a pressure of 3.5×10^5 Pa (3.5 bars).

C. Filtration Step

5

The product of the carboxylation step may advantageously be filtered. The purpose of the filtration step is to remove sediments, and particularly crystalline calcium carbonate, which might have been formed during the preceding steps, and which may cause plugging of filters installed in lubricating oil circuits.

10

D. Separation Step of Hydrocarbyl Phenol

At least about 10 wt % of the hydrocarbyl phenol is separated from the product of the carboxylation step. Preferably, the separation is accomplished using
15 distillation. More preferably, the distillation is carried out in a wiped film evaporator at a temperature of from about 150°C to 270°C and at a pressure of from about 0.1 to 4 mbar; more preferably from about 190°C to 260°C and at from about 0.5 to 3 mbar; most preferably from about 210°C to 250°C and at a pressure of from about 1 to 2 mbar. At least about 10 wt % of the hydrocarbyl
20 phenol is separated. More preferably, at least about 30 wt % of the hydrocarbyl phenol is separated. Most preferably, up to about 55 wt % of the hydrocarbyl phenol is separated. The separated hydrocarbyl phenol may then be recycled to be used as starting materials in the present process or in other processes.

25 The unsulfurized carboxylated detergent-dispersant additive formed by this process can be characterized by its unique composition, with much more alkaline-earth metal single aromatic-ring hydrocarbyl salicylate and less alkylphenol than produced by other routes.

30 The reaction product (at the filtration step before separation step) will typically have the following composition:

- a) Less than about 30 wt % hydrocarbyl phenol,

- b) from about 10 wt % to 50 wt % alkaline-earth metal hydrocarbyl phenate, and
- c) from about 15 wt % to 60 wt % alkaline-earth metal single aromatic-ring hydrocarbyl salicylate.

5

The preceding process is more fully described in U.S. Patent No. 6,162,770, which is incorporated by reference into this application.

10 Unlike alkaline-earth metal hydrocarbyl salicylates produced by other processes, this unsulfurized carboxylate detergent-dispersant additive composition can be characterized by having only minor amounts of an alkaline-earth metal double aromatic-ring hydrocarbyl salicylate. The mole ratio of single aromatic-ring hydrocarbyl salicylate to double aromatic-ring hydrocarbyl salicylate is at least 8:1.

15

Preferably, the TBN of the unsulfurized carboxylate detergent-dispersant additive is less than about 200, preferably less than about 160 and more preferably less than about 140.

20 Characterization of the Unsulfurized Carboxylate Detergent-Dispersant Additive by Infrared Spectrometry

25 Out-of-aromatic-ring-plane C-H bending vibrations were used to characterize the unsulfurized carboxylate detergent-dispersant additive of the present invention.

Infrared spectra of aromatic rings show strong out-of-plane C-H bending transmittance band in about the 675-870 cm^{-1} region, the exact frequency depending upon the number and location of substituents. For ortho-

30 disubstituted compounds, transmittance band occurs at about 735-770 cm^{-1} . For para-disubstituted compounds, transmittance band occurs at about 810-840 cm^{-1} .

Infrared spectra of reference chemical structures relevant to the present invention indicate that the out-of-plane C-H bending transmittance band occurs at about $750 \pm 3 \text{ cm}^{-1}$ for ortho-alkylphenols, at about $760 \pm 2 \text{ cm}^{-1}$ for salicylic acid, and at about $832 \pm 3 \text{ cm}^{-1}$ for para-alkylphenols.

Alkaline earth alkylphenates known in the art have infrared out-of-plane C-H bending transmittance bands at about $750 \pm 3 \text{ cm}^{-1}$ and at about $832 \pm 3 \text{ cm}^{-1}$. Alkaline earth alkylsalicylates known in the art have infrared out-of-plane C-H bending transmittance bands at about $763 \pm 3 \text{ cm}^{-1}$ and at about $832 \pm 3 \text{ cm}^{-1}$.

The unsulfurized carboxylate detergent-dispersant additive of the present invention shows essentially no out-of-plane C-H bending vibration at about $763 \pm 3 \text{ cm}^{-1}$, even though there is other evidence that alkylsalicylate is present. This particular characteristic has not been fully explained. However, it may be hypothesized that the particular structure of the single aromatic ring alkylsalicylate prevents in some way this out-of-plane C-H bending vibration. In this structure, the carboxylic acid function is engaged in a cyclic structure, and thus may generate increased steric hindrance in the vicinity of the aromatic ring, limiting the free motion of the neighbor hydrogen atom. This hypothesis is supported by the fact that the infrared spectrum of the acidified product (in which the carboxylic acid function is no longer engaged in a cyclic structure and thus can rotate) has an out-of-plane C-H transmittance band at about $763 \pm 3 \text{ cm}^{-1}$.

The unsulfurized carboxylate detergent-dispersant additive of the present invention can thus be characterized by having a ratio of infrared transmittance band of out-of-plane C-H bending at about $763 \pm 3 \text{ cm}^{-1}$ to out-of-plane C-H bending at about $832 \pm 3 \text{ cm}^{-1}$ of less than 0.1:1.

E. Treatment With Alkaline Earth Metal Salt of a Linear, Saturated Carboxylic Acid

5 The additive composition of the present invention containing the unsulfurized carboxylate detergent-dispersant additive is preferably modified by incorporation of from about 3.2 wt % to 7.5 wt %, more preferably from about 3.5 wt % to 7.0 wt %, and most preferably from about 4.0 wt % to 6.0 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon
10 atoms.

The alkaline earth metal of the alkaline earth metal salt of the linear, saturated carboxylic acid is selected from the group consisting of barium, calcium, magnesium and strontium. Calcium is the preferred alkaline earth metal.
15 Preferably, the linear, saturated carboxylic acid is stearic acid (stearate), i.e., a long-chain carboxylic acid, wherein the carbon number of the acid is predominately 18, as commercially available from any number of manufacturers, e.g., ATOFINA under the name of STAVINOR CA90C. The preferred alkaline earth metal salt of the linear, saturated carboxylic acid is
20 calcium stearate.

In one embodiment, dispersion of the alkaline earth metal stearate is done at a temperature between from about 80°C to 250°C, preferably from about 120°C to 200°C, and more preferably from about 150°C to 180°C. A small quantity of
25 solvent may be utilized to increase the rate of reaction. An unsulfurized carboxylate detergent-dispersant additive having been treated with an alkaline earth metal salt of stearic acid is obtained.

In a second embodiment, calcium stearate is generated "*in situ*". The first step,
30 a premix is formed by reaction with stearic acid, alkaline earth metal base, diluent oil, a small quantity of C₁ to C₄ carboxylic acid as a promoter in the presence of a solvent selected from the group consisting of aromatic hydrocarbons, aliphatic hydrocarbons and monoalcohols at a temperature from

about 100°C to 140°C, preferably from about 110°C to 130°C. Among the solvents that can be used are, for example, xylene, toluene, cyclohexane, 2-ethylhexanol, the oxo alcohols, decyl alcohol, tridecyl alcohol, 2-butoxyethanol, 2-butoxypropanol, methyl ether of propylene glycol. Monoalcohols with boiling points above 120°C are preferred. A preferred monoalcohol is 2-ethylhexanol. The reaction was maintained between about 1 to 3 hours, then a small vacuum is applied to facilitate the elimination of water. This first step generates the calcium stearate.

10 Then the unsulfurized carboxylate detergent-dispersant additive obtained at the end of the separate step (step d) is added and the temperature is increased up to from about 150°C to 200°C and preferably from about 160°C to 180°C to incorporate the calcium stearate.

15 Solvent is removed from the medium preferably by distillation under vacuum. The sediment (unreacted alkaline earth metal base and stearate salt) is removed by filtration using a Buckner filtration apparatus. An additive composition is obtained comprising an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

25

Lubricating Oil Composition

The present invention also relates to a lubricating oil composition containing the additive composition of the present invention. Such a lubricating oil composition will comprise a major amount of a base oil of lubricating viscosity and a minor amount of an additive composition comprising an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an

30

alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

5

Base oil as used herein is defined as a base stock or blend of base stocks which is a lubricant component that is produced by a single manufacturer to the same specifications (independent of feed source or manufacturer's location); that meets the same manufacturer's specification; and that is identified by a
10 unique formula, product identification number, or both. Base stocks may be manufactured using a variety of different processes including but not limited to distillation, solvent refining, hydrogen processing, oligomerization, esterification, and rerefining. Rerefined stock shall be substantially free from materials introduced through manufacturing, contamination, or previous use.

15 The base oil of this invention may be any natural or synthetic lubricating base oil fraction particularly those having a kinematic viscosity at 100° Centigrade (C) and about 4 centistokes (cSt) to about 20 cSt. Hydrocarbon synthetic oils may include, for example, oils prepared from the polymerization of ethylene, i.e., polyalphaolefin or PAO, or from hydrocarbon synthesis procedures using
20 carbon monoxide and hydrogen gases such as in a Fisher-Tropsch process. A preferred base oil is one that comprises little, if any, heavy fraction; e.g., little, if any, lube oil fraction of viscosity about 20 cSt or higher at about 100 C. Oils used as the base oil will be selected or blended depending on the desired end use and the additives in the finished oil to give the desired grade of engine oil,
25 e.g. a lubricating oil composition having an SAE Viscosity Grade of 0W, 0W-20, 0W-30, 0W-40, 0W-50, 0W-60, 5W, 5W-20, 5W-30, 5W-40, 5W-50, 5W-60, 10W, 10W-20, 10W-30, 10W-40, 10W-50, 15W, 15W-20, 15W-30, or 15W-40.

The base oil may be derived from natural lubricating oils, synthetic lubricating
30 oils or mixtures thereof. Suitable base oil includes base stocks obtained by isomerization of synthetic wax and slack wax, as well as hydrocrackate base stocks produced by hydrocracking (rather than solvent extracting) the aromatic and polar components of the crude. Suitable base oils include those in all API

categories I, II, III, IV and V as defined in API Publication 1509, 14th Edition, Addendum I, December 1998. Saturates levels and viscosity indices for Group I, II and III base oils are listed in Table I. Group IV base oils are polyalphaolefins (PAO). Group V base oils include all other base oils not
5 included in Group I, II, III, or IV. Group III base oils are preferred.

TABLE I

Saturates, Sulfur and Viscosity Index of Group I, II, III, IV and V Base Stocks

Group	Saturates (As determined by ASTM D2007) Sulfur (As determined by ASTM D2270)	Viscosity Index (As determined by ASTM D4294, ASTM D4297 or ASTM D3120)
I	Less than 90 % saturates and/or Greater than to 0.03 % sulfur	Greater than or equal to 80 and less than 120
II	Greater than or equal to 90 % saturates and less than or equal to 0.03 % sulfur	Greater than or equal to 80 and less than 120
III	Greater than or equal to 90 % saturates and less than or equal to 0.03% sulfur	Greater than or equal to 120
IV	All Polyalphaolefins (PAOs)	
V	All others not included in Groups I, II, III, or IV	

Natural lubricating oils may include animal oils, vegetable oils (e.g., rapeseed oils, castor oils and lard oil), petroleum oils, mineral oils, and oils derived from
10 coal or shale.

Synthetic oils may include hydrocarbon oils and halo-substituted hydrocarbon oils such as polymerized and inter-polymerized olefins, alkylbenzenes, polyphenyls, alkylated diphenyl ethers, alkylated diphenyl sulfides, as well as
15 their derivatives, analogues and homologues thereof, and the like. Synthetic lubricating oils also include alkylene oxide polymers, interpolymers, copolymers

and derivatives thereof wherein the terminal hydroxyl groups have been modified by esterification, etherification, etc. Another suitable class of synthetic lubricating oils comprises the esters of dicarboxylic acids with a variety of alcohols. Esters useful as synthetic oils also include those made from C₅ to C₁₂ monocarboxylic acids and polyols and polyol ethers. Tri-alkyl phosphate ester oils such as those exemplified by tri-n-butyl phosphate and tri-iso-butyl phosphate are also suitable for use as base oils.

Silicon-based oils (such as the polyakyl-, polyaryl-, polyalkoxy-, or polyaryloxy-siloxane oils and silicate oils) comprise another useful class of synthetic lubricating oils. Other synthetic lubricating oils include liquid esters of phosphorus-containing acids, polymeric tetrahydrofurans, polyalphaolefins, and the like.

The base oil may be derived from unrefined, refined, rerefined oils, or mixtures thereof. Unrefined oils are obtained directly from a natural source or synthetic source (e.g., coal, shale, or tar sand bitumen) without further purification or treatment. Examples of unrefined oils include a shale oil obtained directly from a retorting operation, a petroleum oil obtained directly from distillation, or an ester oil obtained directly from an esterification process, each of which may then be used without further treatment. Refined oils are similar to the unrefined oils except that refined oils have been treated in one or more purification steps to improve one or more properties. Suitable purification techniques include distillation, hydrocracking, hydrotreating, dewaxing, solvent extraction, acid or base extraction, filtration, and percolation, all of which are known to those skilled in the art. Rerefined oils are obtained by treating used oils in processes similar to those used to obtain the refined oils. These rerefined oils are also known as reclaimed or reprocessed oils and often are additionally processed by techniques for removal of spent additives and oil breakdown products.

Base oil derived from the hydroisomerization of wax may also be used, either alone or in combination with the aforesaid natural and/or synthetic base oil. Such wax isomerase oil is produced by the hydroisomerization of natural or synthetic waxes or mixtures thereof over a hydroisomerization catalyst.

5

It is preferred to use a major amount of base oil in the lubricating oil of the present invention. A major amount of base oil as defined herein comprises 40 wt % or more. Preferred amounts of base oil comprise about 40 wt % about 97 wt %, preferably greater than about 50 wt % to about 97 wt %, more preferably about 60 wt % to about 97 wt % and most preferably about 80 wt % to about 95 wt % of the lubricating oil composition. (When weight percent is used herein, it is referring to weight percent of the lubricating oil unless otherwise specified.)

10

The additive composition of the present invention in the lubricating oil composition will be in a minor amount compared to the base oil of lubricating viscosity. Generally, it will be in an amount from about 1 to 15 wt %, preferably from about 2 to 12 wt % and more preferably from about 3 to 8 wt % based on the total weight of the lubricating oil composition.

15

In one embodiment, the lubricating oil composition of the present invention will be a low emission diesel lubricant or LEDL having low levels of ash, sulfur and phosphorus. LEDL are particularly desirable for use in low emission diesel engines equipped with exhaust gas after-treatment systems that can be sensitive to lubricant constituents. The LEDL of the present invention will have from about 0 wt % to 1.2 wt % ash, from about 0.1 wt % to 0.5 wt % sulfur, and from about 0.002 wt % to 0.1 wt % phosphorus. Among other things, the LEDL of the present invention provides low temperature viscosity, corrosion and detergent properties while at the same time providing compatibility with exhaust gas after-treatment systems.

20

25

30

The LEDL of the present invention may have, for example, the following composition:

- a) a major amount of a base oil of lubricating viscosity;
from about 1 wt % to 15 wt % of an unsulfurized
carboxylate detergent-dispersant additive having been
modified by incorporation of from about 3.2 wt % to 7.5 wt
%, based on the total additive composition, of an alkaline
earth metal salt of a linear, saturated carboxylic acid
having from about 16 to about 20 carbon atoms and
wherein the additive composition has a superalkalinization
ratio of less than about 1.4:1, a TBN of less than about 200
and a sediment value of less than about 0.2 % by volume,
- b) from about 1 wt % to 12 wt % of at least one dispersant,
- c) from about 0.5 wt % to 1.1 wt % of at least one zinc
dithiophosphate,
- d) from about 0 wt % to 2.5 wt % of at least one oxidation
inhibitor,
- e) from about 0 wt % to 1 wt % of at least one foam inhibitor,
- f) from about 0 wt % to 10 wt % of at least one viscosity
index improver, and
- g) from about 0 wt % to 0.5 wt % of a corrosion inhibitor,

having from about 0.05 wt % to 0.5 wt % sulfur, from about 0.1 wt
% to 0.5 wt % ash and from about 0.02 wt % to 0.1 wt %
phosphorus.

The LEDL of the present invention is produced by the method of blending a
mixture of the above components. The LEDL produced by that method might
have a slightly different composition than the initial mixture, because the
components may interact. The components can be blended in any order and
can be blended as combinations of components.

Other Additive Components

The following additive components are examples of components that can be favorably employed in combination with the lubricating additive of the present invention. These examples of additives are provided to illustrate the present invention, but they are not intended to limit it.

(A) Ashless Dispersants: alkenyl succinimides, alkenyl succinimides modified with other organic compounds, and alkenyl succinimides modified with boric acid, alkenyl succinic ester.

(B) Oxidation Inhibitors:

- 1) Phenol type phenolic) oxidation inhibitors: 4,4'-methylenebis (2,6-di-tert-butylphenol), 4,4'-bis(2,6-di-tert-butylphenol), 4,4'-bis(2-methyl-6-tert-butylphenol), 2,2'-(methylenebis(4-methyl-6-tert-butyl-phenol), 4,4'-butylidenebis(3-methyl-6-tert-butylphenol), 4,4'-isopropylidenebis(2,6-di-tert-butylphenol), 2,2'-methylenebis(4-methyl-6-nonylphenol), 2,2'-isobutylidenebis(4,6-dimethylphenol), 2,2'-methylenebis(4-methyl-6-cyclohexylphenol), 2,6-di-tert-butyl-4-methylphenol, 2,6-di-tert-butyl-4-ethylphenol, 2,4-dimethyl-6-tert-butyl-phenol, 2,6-di-tert- α -dimethylamino-p-cresol, 2,6-di-tert-4(N.N'-dimethylaminomethylphenol), 4,4'-thiobis(2-methyl-6-tert-butylphenol), 2,2'-thiobis(4-methyl-6-tert-butylphenol), bis(3-methyl-4-hydroxy-5-tert-butylbenzyl)-sulfide, and bis (3,5-di-tert-butyl-4-hydroxybenzyl).
- 2) Diphenylamine type oxidation inhibitor: alkylated diphenylamine, phenyl- α -naphthylamine, and alkylated α -naphthylamine.
- 3) Other types: metal dithiocarbamate (e.g., zinc dithiocarbamate), and methylenebis (dibutyldithiocarbamate).

(C) Rust Inhibitors (Anti-rust agents):

- 1) Nonionic polyoxyethylene surface active agents: polyoxyethylene lauryl ether, polyoxyethylene higher alcohol ether, polyoxyethylene nonylphenyl

ether, polyoxyethylene octylphenyl ether, polyoxyethylene octyl stearyl ether, polyoxyethylene oleyl ether, polyoxyethylene sorbitol monostearate, polyoxyethylene sorbitol mono-oleate, and polyethylene glycol monooleate.

- 5 2) Other compounds: stearic acid and other fatty acids, dicarboxylic acids, metal soaps, fatty acid amine salts, metal salts of heavy sulfonic acid, partial carboxylic acid ester of polyhydric alcohol, and phosphoric ester.

- (D) Demulsifiers: addition product of alkylphenol and ethyleneoxide,
10 polyoxyethylene alkyl ether, and polyoxyethylene sorbitane ester.

- (E) Extreme Pressure Agents (EP agents): zinc dialkyldithiophosphate (Zn-DTP, primary alkyl type & secondary alkyl type), sulfurized oils, diphenyl sulfide, methyl trichlorostearate, chlorinated naphthalene, benzyl iodide,
15 fluoroalkylpolysiloxane, and lead naphthenate.

(F) Friction Modifiers: fatty alcohol, fatty acid, amine, borated ester, and other esters

- 20 (G) Multifunctional Additives: sulfurized oxymolybdenum dithiocarbamate, sulfurized oxymolybdenum organo phosphoro dithioate, oxymolybdenum monoglyceride, oxymolybdenum diethylate amide, amine-molybdenum complex compound, and sulfur-containing molybdenum complex compound

- 25 (H) Viscosity Index Improvers: polymethacrylate type polymers, ethylene-propylene copolymers, styrene-isoprene copolymers, hydrated styrene-isoprene copolymers, polyisobutylene, and dispersant type viscosity index improvers.

- 30 (I) Pour-point Depressants: polymethyl methacrylate.

(K) Foam Inhibitors: alkyl methacrylate polymers and dimethyl silicone polymers.

(L) Metal Detergents: sulfurized or unsulfurized alkyl or alkenyl phenates, alkyl or alkenyl aromatic sulfonates, calcium sulfonates, sulfurized or unsulfurized metal salts of multi-hydroxy alkyl or alkenyl aromatic compounds, alkyl or
5 alkenyl hydroxy aromatic sulfonates, sulfurized or unsulfurized alkyl or alkenyl naphthenates, metal salts of alkanolic acids, metal salts of an alkyl or alkenyl multi-acid, and chemical and physical mixtures thereof.

EXAMPLES

10

The invention will be further illustrated by the following examples, which set forth particularly advantageous method embodiments. While the Examples are provided to illustrate the present invention, they are not intended to limit it. This application is intended to cover those various changes and substitutions that
15 may be made by those skilled in the art without departing from the spirit and scope of the appended claims.

Unless otherwise specified, all percentages are in weight percent (wt %).

20

Example 1. Preparation of the Additive Composition

a) Neutralization

A charge of 875 grams (g) of branched dodecylphenol (DDP) having a
25 molecular weight of 270 (3.24 moles) and 875 g of linear alkylphenol having a molecular weight of 430 (2.03 moles) was loaded in a four-necked 4 liter glass reactor equipped with a heat insulated Vigreux fractionating column. The isomeric molar repartition of para versus ortho alkylphenol was:

30

- DDP = 89 % para and 5.5 % ortho

- Linear alkylphenol = 39 % para and 53 % ortho

The agitator was started and the reaction mixture was heated to 65°C before

162 grams of slaked lime: $\text{Ca}(\text{OH})_2$ (2.19 moles) and 19 g of a mixture of formic acid and acetic acid (50/50 by weight) were added.

5 The reaction medium was heated up to 165°C. Distillation of water started at this temperature. The temperature was increased up to 240°C and the pressure was reduced gradually below atmospheric until an absolute pressure of 5000 Pa (50 mbars) was obtained. The reaction mixture was kept under these conditions for five hours.

10 The reaction mixture was then allowed to cool to 180°C, when the vacuum was broken under a nitrogen atmosphere and a sample was taken for analyses. The total distillate obtained was about 120 cm³, demixing took place in the lower phase (66 cm³ being water).

15 b) Carboxylation

The product obtained in step a) was transferred to a 3.6 liter autoclave and heated to 180°C. At this temperature, scavenging of the reactor with carbon dioxide (CO_2) was started and continued for ten minutes. The amount of CO_2 used in this step was in the order of 20 g.

25 After the temperature had reached 200°C, the autoclave was closed, leaving a very small leak and the introduction of CO_2 was continued so as to maintain a pressure of 3.5×10^5 Pa (3.5 bars) for 5 hours at 200°C. The amount of CO_2 introduced was approximately 50 g. After the autoclave had been cooled to 165°C, the pressure was restored to atmospheric and the reactor was then purged with nitrogen. A total quantity of 1,917 g of product was recovered prior to filtration.

30 c) Filtration

The product from step b) was then filtered. Analytical results for this product were as follows:

- TBN = 120 mg KOH/g
- Calcium = 4.1 wt %
- Salicylic acid index (SAI) = 40 mg KOH/g

5

SAI is a measure of the quantity of alkyl carboxylate (salicylate) formed in the detergent-dispersant. It was determined by acidification of the product by a strong acid (hydrochloric acid) in the presence of diethyl ether, followed by a potentiometric titration on the organic fraction (tetra-n-butyl ammonium hydroxide was used as a titration agent). Results are expressed in equivalent
10 mg KOH per g of product (TBN, base number unit).

The above procedure was scaled up to a 36 m³ reactor and used to prepare the intermediate product. The intermediate product was then separated from
15 any hydrocarbyl phenol as outlined below.

d) Separation (Distillation) of Hydrocarbyl Phenol

The intermediate product from step b) was fed at a rate of 90 kg/h to a wiped
20 film evaporator (WFE) which had a surface of 0.39 m². The WFE has an external condenser. The hot oil of the jacket was about 270°C. The pressure inside the WFE was 1.3 mbars (130 Pa), the feed temperature to the WFE was 140°C. Final product exiting the WFE was 225°C.

The product which has a TBN of 209 was cooled down to less than 100°C before diluting with 100N base in order to obtain a TBN of 140. Approximately 47 % (by weight) of the feed from the WFE was collected as distillate. Analytical results for the distilled product were as follows:

5

- TBN = 140 mg KOH/g
- Calcium = 5.0 wt %
- Salicylic acid index (SAI) = 47 mg KOH/g

10 e) Addition of Calcium Stearate

The product (950 g) obtained after separation of hydrocarbyl phenol was loaded in a 5 liter glass reactor, heated up to 60°C then 15 g of 2-ethylhexanol and 50 g calcium stearate (5 wt %, based on the total additive composition) were added under agitation.

The reactor was heated up to 170°C and maintained for 4 hours until the complete integration of calcium stearate. During the last hour, the reactor was stripped with nitrogen at a flow rate of 20 L/h. After which, the reactor was cooled down to ambient temperature. The additive composition obtained was an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume. Analytical results for the distilled products were as follows:

5

- TBN = 146 mg KOH/g
- Calcium = 5.18 wt %
- Viscosity at 100°C = 111 mm²/s
- Sediments = 0.08 % volume

Example 2. Addition of Calcium Stearate Generated "In Situ"

10 In a 5 liter glass reactor was loaded the following premix: 250 g (1.92 moles) 2-ethylhexanol, 46 g (0.16 moles) stearic acid, 12 g water, 12.5 g (0.24 moles) formic acid/acetic acid (50/50 by weight) and 18 g (0.24 moles) slaked lime. The loaded reactor was placed under vacuum, heated up to 100°C over a period of 15 minutes and maintain for one hour at 100°C. Temperature was raised to 120°C and maintained a period of one hour while the pressure was gradually reduced below atmospheric until an absolute pressure of 10,000 Pa (100 mbars) was obtained.

20 The vacuum was gradually broken with nitrogen and 912 g of the product obtained in Example1 from the end of step d) was added. The mixture was heated to 172°C over a period of 10 minutes and maintained for one hour at 172°C. About 49 g of calcium stearate was generated in situ, or about 5.1 wt %, based on the total additive composition. The mixture was further heated to 195°C over a period of 60 minutes while the pressure was reduced gradually below atmospheric until an absolute pressure of 5,000 Pa (50 mbars) was obtained and maintained for 45 minutes at these conditions. The vacuum was broken with nitrogen and the mixture was cooled down to ambient temperature. 25 The analytical results of the unsulfurized carboxylate detergent-dispersant were as follows:

30

- TBN = 147 mg KOH/g
- Calcium = 5.23 wt %
- Viscosity at 100°C = 91 mm²/s
- Sediments = 0.06 % volume

Example 3

Example 3 was carried out according to Example 1 except a lower quantity of calcium stearate was added, i.e., 45 g instead of 50 g.

950 g of the product obtained after separation of hydrocarbyl phenol was loaded in a 5 liter glass reactor, heated up to 60°C then 15 g of 2-ethylhexanol and 45 g (versus 50 g as in Example 1) of calcium stearate were added under agitation. This corresponds to about 4.5 wt %, based on the total additive composition. The batch procedure was the same as Example 1.

Analytical results for the distilled product were as follows:

- TBN = 144 mg KOH/g
- Calcium = 5.14 wt %
- Viscosity at 100°C = 98 mm²/s
- Sediments = 0.06 % volume

Comparative Example A

This example follows the procedure of Example 1 except the addition of calcium stearate and 2-ethylhexanol was omitted. That is, there was no step e).

The analytical results were as follows:

- TBN = 140 mg KOH/g
- Calcium = 5.0 wt %
- Viscosity at 100°C = 70 mm²/s
- Sediments = 0.02 % volume

Comparative Example B

This example follows the procedure of Example 1 except the addition of calcium stearate in step e) was omitted. 985 g of product of Example 1 from the end of step d) and 15 g 2-ethylhexanol were added in step e). The analytical results are as follows:

- TBN = 138 mg KOH/g
- Calcium = 4.92 wt %
- Viscosity at 100°C = 50 mm²/s
- Sediments = 0.02 % volume

Comparative Example C

This example follows the procedure of Example 1 except the addition of 2-ethylhexanol in step e) was omitted. 984 g of product of Example 1 from the end of step d) and 46 g calcium stearate were added in step e). The analytical results are as follows:

- TBN = 141 mg KOH/g
- Calcium = 5.03 wt %
- Viscosity at 100°C = 190 mm²/s
- Sediments = 0.25 % volume

A higher sediment is observed due to a poor dispersion of calcium stearate.

Comparative Example D

This example follows the procedure of Example 1 except a lower quantity of calcium stearate (25 g instead of 46 g) was utilized. This corresponds to about 2.56%, based on the total additive composition. The analytical results are as follows:

- TBN = 139 mg KOH/g
- Calcium = 4.96 wt %
- Viscosity at 100°C = 105 mm²/s
- Sediments = 0.02 % volume

5

Comparative Example E

This example follows the procedure of Example 1 except the 50 g calcium stearate was substituted by 50 g calcium oleate. The analytical results are as follows:

10

- TBN = 140 mg KOH/g
- Calcium = 5.0 wt %
- Viscosity at 100°C = 120 mm²/s
- Sediments = 0.03 % volume

15

Comparative Example F

This example follows the procedure of Example 1 except 50 g calcium stearate was substituted by 50 g iso-stearate. The analytical results are as follows:

20

- TBN = 140 mg KOH/g
- Calcium = 5.0 wt %
- Viscosity at 100°C = 101 mm²/s
- Sediments = 0.02 % volume

25

Comparative Example G

Example G was carried out as described in Example 1 except a higher quantity of calcium stearate is added, i.e., 95 g instead of 50 g calcium stearate. This corresponds to about 9 wt %, based on the total additive composition.

30

950 g of the product obtained after separation of hydrocarbyl phenol was loaded in a 5 liter glass reactor, heated up to 60°C, then 15 g of 2-ethylhexanol and 95 g (versus 50 g as in Example 1) were added under agitation. The batch procedure was the same as in Example 1.

5

Analytical results for the distilled products were as follows:

10

- TBN = 148 mg KOH/g
- Calcium = 5.30 wt %
- Viscosity = 205 mm²/s
- Sediments = 0.25 % volume

15

The higher amount of calcium stearate at about 9 wt % creates sediment and solubility problems in the lubricating oil formulations due to the incomplete dispersion of calcium stearate.

Comparative Example H

20

The additive composition of the present invention was compared to a known carboxylate detergent-dispersant described in Example 1 of U.S. Patent No. 6,348,438 to illustrate the performance differences between two carboxylates having different TBN and superalkalinization ratios. The carboxylate detergent-dispersant in Example 1 of U.S. Patent No. 6,348,348 has a high TBN value (348) that means a high level of superalkalinization. i.e., salt/soap ratio is 1.63.

25

The TBN and superalkalinization ratio of the additive composition of the present invention is less than about 200 and less than about 1.4:1, respectively.

Example 4

30

Lubricating oil formulations (Formulations 1, 2 and 3) were prepared with the products of Examples 1, 2 and 3 as shown in Table II. Each formulation contained the following base composition:

Polybutene bissuccinimide ..8.0 wt %
 Zinc dithiophosphate0.69 wt %
 Calcium sulfonate.....1.36 wt %
 Oxidation inhibitor.....0.70 wt %
 5 Polymer dispersant.....2.0 wt %
 Anti-foam agent.....0.0025 wt %
 Viscosity index improver.....6.0 wt %
 Group III base oilSufficient to provide 100 wt %

10 The additive composition from Examples 1, 2 and 3 were added according to the wt % indicated in Table II. Each formulation was examined in the ASTM D4684 MRV (Mini Rotary Viscometer), MAO 73 Panel Coker, ASTM D6594 HTCBT (High Temperature Corrosion Bench Test) and MAO 23 Compatibility Tests. These tests are further described below.

15

The ASTM D4684 MRV test covers the measurement of the yield stress ($0 < Y < 35$ max) and viscosity (60,000 cp max) of engine oils after cooling at controlled rates over a period not exceeding 45 h to a final test temperature between -10 and -40°C. In the MRV test an engine oil sample is held at 80° C and then cooled at a programmed cooling rate to a final test temperature. A low torque is applied to the rotor shaft to measure the yield stress. A higher torque is then applied to determine the apparent viscosity of the sample. The viscosity measurements are made at shear stress of 525 Pa over a shear rate of 0.4 to 15 s⁻¹.

25

The MAO 73 Panel Coker test evaluates the tendency of the lubricant to form carbon deposits when in contact with metallic surfaces at high temperature. An oil sample is preheated in a sump (170°C) and then intermittently projected (by the mean of a rotating oil stirrer) on an aluminum test plate heated at high temperature (300°C) for a period of 48 h. The amount of deposit is weighed at the end of test. The lower the number, the better the result. Excellent results means less than 50 mg of deposit; poor results means more than 200 mg of deposit.

The ASTM D6594 HTCBT test is used to test diesel engine lubricants to determine their tendency to corrode various metals, specifically alloys of lead and copper commonly used in cam followers and bearings. Four metal
5 specimens of copper, lead, tin and phosphor bronze are immersed in a measured amount of engine oil. The oil, at an elevated temperature (170 °C), is blown with air (5 l/h) for a period of time (168 h). When the test is completed, the copper specimen and the stressed oil are examined to detect corrosion and corrosion products, respectively. The concentrations of copper, lead, and tin in
10 the new oil and stressed oil and the respective changes in metal concentrations are reported. To be a pass the concentration of lead should not exceed 120 ppm and the copper 20 ppm.

The ASTM D97 Pour-point Test is used to determine the minimum of
15 temperature at which the oil remains fluid. After preliminary heating, the sample is cooled at a specified rate and examined at intervals of 3°C for flow characteristics. The lowest temperature at which movement of the specimen is observed is recorded as the pour-point. The pour-point of the petroleum specimen is an index of the lowest temperature of its utility for certain
20 applications.

The MAO 23 Compatibility Test is used to evaluate the storage stability of lubricating oils. The formulated oil is placed in an oven at 80°C for a period of a month, then the appearance and the sediment are rated after a month
25 comparatively to standard samples. The ratings are as follows:

- Appearance: clear and bright (1) , cloud (3) , very cloud (6)
- Sediment: no sediment (0), light (1) , medium (2), high (3)
- Rating 1/0 means: appearance clear and bright (1)/no
30 sediment (0)

The lower the rating of the appearance and the lower the rating of the sediment, the better the product. A good result is an appearance rating of 2 max and a sediment rating of 1 max.

- 5 The results of these tests are presented in Table II.

Comparative Example I

- 10 Comparative lubricating oil formulations (Formulations A to H) were prepared with the products of Comparative Examples A to H as shown in Table III. Each formulation contained the following base composition:

	Polybutene bissuccinimide ..8.0 wt %
	Zinc dithiophosphate0.69 wt %
15	Calcium sulfonate1.36 wt %
	Oxidation inhibitor0.70 wt %
	Polymer dispersant2.0 wt %
	Anti-foam agent0.0025 wt %
	Viscosity index improver6.0 wt %
20	Group III base oilSufficient to provide 100 wt %

- 25 Comparative Examples A to H were added according to the wt % indicated in Table III. Each formulation was examined in the ASTM D4684 MRV (Mini Rotary Viscometer), MAO 73 Panel Coker, ASTM D6594 HTCBT (High Temperature Corrosion Bench Test) and MAO 23 Compatibility Tests. These tests are described in Example 4 above.

Table II

Component	Examples ^a		
	1	2	3
Polybutene Bissuccinimide	8%	8%	8%
Zinc Dithiophosphate	0.69%	0.69%	0.69%
Calcium Sulfonate	1.36%	1.36%	1.36%
Oxidation Inhibitor	0.70%	0.70%	0.70%
Polymer Dispersant	2%	2%	2%
Product of Invention ^b	4.48%	4.44%	4.51%
Anti-Foam Agent	0.0025%	0.0025%	0.0025%
Viscosity Index Improver	6.00%	6.00%	6.00%
Base Oil / Group III (Fortum +Total)	QSP 100	QSP 100	QSP 100
Performance Analyses	Base Oil / Group III (Nexbase 3060 Total)		
MRV Yield Stress ASTM D4684	0<Y<=35	0<Y<=35	0<Y<=35
MRV Viscosity ASTM D4684	42910	42910	46000
Panel Coker MAO 73 (mg)	30	30	30
HCTBT ASTM D6594			
▪ Copper in oil (ppm)	5	4	5
▪ Lead in oil (ppm)	80	81	79
Pour-point ASTM D 97 (°C)	- 33	- 33	- 33
Compatibility MAO 23	1/0	1/0	1/0

^a% are wt %.

- ^b 5 ^bUnsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of
- 10 less than about 200 and a sediment value of less than about 0.2 % by volume.

Table III

Component	Comparative Examples ^a							
	A	B	C	D	E	F	G	H
Polybutene Bissuccinimide	8%	8%	8%	8%	8%	8%	8%	8%
Zinc Dithiophosphate	0.69%	0.69%	0.69%	0.69%	0.69%	0.69%	0.69%	0.69%
Calcium Sulfonate	1.36%	1.36%	1.36%	1.36%	1.36%	1.36%	1.36%	1.36%
Oxidation Inhibitor	0.70%	0.70%	0.70%	0.70%	0.70%	0.70%	0.70%	0.70%
Polymer Dispersant	2.00%	2.00%	2.00%	2.00%	2.00%	2.00%	2.00%	2.00%
Carboxylate	4.49%	4.60%	4.35%	4.54%	6.07%	6.22%	4.23%	1.87%
Anti-Foam Agent	0.0025%	0.0025%	0.0025%	0.0025%	0.0025%	0.0025%	0.0025%	0.0025%
Viscosity Index Improver	6.00%	6.00%	6.00%	6.00%	6.00%	6.00%	6.00%	6.00%
Base Oil / Group III (Fortum +Total)	QSP 100%	QSP 100%	QSP 100%	QSP 100%	QSP 100%	QSP 100%	QSP 100%	QSP 100%
Performance Analyses	Base Oil / Group III (Nexbase 3060 Total)							
MRV Yield Stress ASTM D4684	>350	>350	70<Y<=105	>350	>350	>350	0<Y<=35	0<Y<=35
MRV Viscosity ASTM D4684	Frozen	Frozen	84485	Frozen	Frozen	Frozen	21000	22500
Panel Coker MAO 73 (mg)	30	25	30	25	25	30	30	305
HTCBT ASTM D6594	5	5	4	5	5	4	6	6
▪ Copper in oil (ppm)								
▪ Lead in (ppm)	78	77	79	79	78	78	82	81
Pour-point ASTM D97 (°C)	-24	-24	-27	-27	-24	-24	-33	-33
Compatibility MAO 23	1/0	1/0	3/2	1/0	1.0	1/0	6/2	1/0

^a% are wt %.

The results of the above data indicate that the additive composition of the present invention comprising an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume provides excellent low temperature viscosity as well as corrosion and detergency properties when compared to lubricating oil formulations without the additive composition of the present invention. The results indicate that having a high TBN, too low or too high a superalkalinization ratio, and too high a sediment value will not give the good low temperature viscosity, corrosion and detergent properties. Finally, the present invention is unique to a certain alkaline earth metal salt of a linear, saturated carboxylic acid, i.e. calcium stearate. Alkaline earth metal salt of carboxylic acids having unsaturation (calcium oleate) or branching (calcium iso-stearate) were inferior toward contributing to the good low temperature viscosity, corrosion and detergent properties. Moreover, the addition of alkaline earth metal salt of the linear, saturated carboxylic acid must occur in the presence of a solvent for the proper incorporation of the carboxylic acid into the unsulfurized carboxylic detergent-dispersant additive.

CLAIMS:

1. An additive composition comprising an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.
2. The additive composition according to claim 1, wherein the unsulfurized carboxylate detergent-dispersant additive comprises:
 - a) less than about 30 wt % hydrocarbyl phenol,
 - b) from about 10 wt % to 50 wt % alkaline earth metal hydrocarbyl phenate, and
 - c) from about 15 wt % to 60 wt % alkaline earth metal single aromatic-ring hydrocarbyl salicylate.
3. The additive composition according to claim 2, wherein the hydrocarbyl group on the hydrocarbyl phenol, hydrocarbyl phenate and hydrocarbyl salicylate is independently derived from a linear olefin, an isomerized olefin, a branched chain olefin or a mixture thereof.
4. The additive composition according to claim 3, wherein the hydrocarbyl group is an alkyl group.
5. The additive composition according to claim 4, wherein the alkyl group has from about 12 to 40 carbon atoms.

6. The additive composition according to claim 5, wherein the alkyl group has from about 18 to 30 carbon atoms.
7. The additive composition according to claim 6, wherein the alkyl group is derived from an isomerized olefin.
8. The additive composition according to claim 4, wherein the alkyl group is a branched alkyl group having at least 9 carbon atoms.
9. The additive composition according to claim 8, wherein the alkyl group is a branched alkyl group having from about 9 to 24 carbon atoms.
10. The additive composition according to claim 9, wherein the alkyl group is a branched alkyl group having from about 10 to 18 carbon atoms.
11. The additive composition according to any one of claims 1 to 10, wherein the alkaline earth metal of the alkaline earth metal hydrocarbyl phenate and the alkaline earth metal single aromatic-ring hydrocarbyl salicylate is independently selected from the group consisting of calcium, magnesium, barium, or strontium.
12. The additive composition according to claim 11, wherein the alkaline earth metal of the alkaline earth metal hydrocarbyl phenate and the alkaline earth metal single aromatic-ring hydrocarbyl salicylate is calcium.
13. The additive composition according to claim 1, wherein the alkaline earth metal of the alkaline earth metal salt of the linear, saturated carboxylic acid is calcium.

14. The additive composition according to claim 13, wherein the linear, saturated carboxylic acid is stearic acid.
15. The additive composition according to claim 1, wherein the alkaline earth metal salt of the linear, saturated carboxylic acid is present at a concentration of from about 3.5 wt % to 7.0 wt % based on the total additive composition.
16. The additive composition according to claim 15, wherein the alkaline earth metal salt of linear, saturated carboxylic acid is present at a concentration of from about 4.0 wt % to 6.0 wt % based on the total additive composition.
17. The additive composition according to any one of the preceding claims, wherein linear, saturated carboxylic acid is stearic acid.
18. The additive composition according to any one of the preceding claims, wherein the superalkalinization ratio is less than about 1:1.
19. The additive composition according to any one of claims 1 to 17, wherein the superalkalinization ratio is less than about 0.2 to 1.
20. The additive composition according to any one of the preceding claims, wherein the TBN is less than about 160.
21. The additive composition according to any one of claims 1 to 19, wherein the TBN is less than about 140.
22. A lubricating oil composition comprising:
 - a) a major amount of base oil of lubricating viscosity; and
 - b) a minor amount of an unsulfurized carboxylate detergent-

dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

23. The lubricating oil composition according to claim 22, wherein the unsulfurized carboxylate detergent-dispersant additive comprises:
 - a) less than about 30 wt % hydrocarbyl phenol,
 - b) from about 10 wt % to 50 wt % alkaline earth metal hydrocarbyl phenate, and
 - c) from about 15 wt % to 60 wt % alkaline earth metal single aromatic-ring hydrocarbyl salicylate.
24. The lubricating oil composition according to claim 23, wherein the hydrocarbyl group on the hydrocarbyl phenol, hydrocarbyl phenate and hydrocarbyl salicylate is independently derived from a linear olefin, an isomerized olefin, a branched chain olefin or a mixture thereof.
25. The lubricating oil composition according to claim 24, wherein the hydrocarbyl group is an alkyl group.
26. The lubricating oil composition according to claim 25, wherein the alkyl group has from about 12 to 40 carbon atoms.
27. The lubricating oil composition according to claim 26, wherein the alkyl group has from about 18 to 30 carbon atoms.

28. The lubricating oil composition according to claim 27, wherein the alkyl group is derived from an isomerized olefin.
29. The lubricating oil composition according to claim 25, wherein the alkyl group is a branched alkyl group having at least 9 carbon atoms.
30. The lubricating oil composition according to claim 29 wherein alkyl group is a branched alkyl group having from about 9 to 24 carbon atoms.
31. The lubricating oil composition according to claim 30, wherein alkyl group is a branched alkyl group having from about 10 to 18 carbon atoms.
32. The lubricating oil composition according to any one of claims 23 to 31, wherein the alkaline earth metal of the alkaline earth metal hydrocarbyl phenate and alkaline earth metal single aromatic-ring hydrocarbyl salicylate is independently selected from the group consisting of calcium, magnesium, barium, or strontium.
33. The lubricating oil composition according to claim 32, wherein the alkaline earth metal of the alkaline earth metal hydrocarbyl phenate and the alkaline earth metal single aromatic-ring hydrocarbyl salicylate is calcium.
34. The lubricating oil composition according to claim 22, wherein the alkaline earth metal of the alkaline earth metal salt of linear, saturated carboxylic acid is calcium.
35. The lubricating oil composition according to claim 34, wherein the linear, saturated carboxylic acid is stearic acid.

36. The lubricating oil composition according to claim 22, wherein the alkaline earth metal salt of the linear, saturated carboxylic acid is present at a concentration of from about 3.5 wt % to 7.0 wt % based on the total additive composition.
37. The lubricating oil composition according to claim 36, wherein the alkaline earth metal salt of linear, saturated carboxylic acid is present at a concentration of from about 4.0 wt % to 6.0 wt % based on the total additive composition.
38. The lubricating oil composition according to any one of claims 22 to 37, wherein linear, saturated carboxylic acid is stearic acid.
39. The lubricating oil composition according to any one of claims 22 to 38, wherein the superalkalinization ratio is less than about 1:1.
40. The lubricating oil composition according to any one of claims 22 to 38, wherein the superalkalinization ratio is less than about 0.2 to 1.
41. The lubricating oil composition according to any one of claims 22 to 40, wherein the TBN is less than about 160.
42. The lubricating oil composition according to any one of claims 22 to 40, wherein the TBN is less than about 140.
43. A method for producing an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than

about 0.2 % by volume, said method comprising:

- a) neutralizing one or more hydrocarbyl phenols using an alkaline earth metal base to form an intermediate product,
- b) carboxylating the intermediate product of a) using carbon dioxide so that at least about 5 wt % of the original hydrocarbyl phenol starting material has been converted to alkaline earth single aromatic-ring hydrocarbyl salicylate,
- c) separating at least about 10 wt % of the starting hydrocarbyl phenols from the product obtained in b), and
- d) adding an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms in the presence of a solvent selected from the group consisting of aromatic hydrocarbons, aliphatic hydrocarbons and monoalcohols to produce the unsulfurized carboxylate detergent-dispersant additive.

44. The method according to claim 43, wherein the unsulfurized carboxylate detergent-dispersant additive comprises:

- a) less than about 30 wt % hydrocarbyl phenol,
- b) from about 10 wt % to 50 wt % alkaline earth metal hydrocarbyl phenate, and
- c) from about 15 wt % to 60 wt % alkaline earth metal single aromatic-ring hydrocarbyl salicylate.

45. The method according to claim 44, wherein the hydrocarbyl group on the hydrocarbyl phenol, hydrocarbyl phenate and hydrocarbyl salicylate is independently derived from a linear olefin, an isomerized olefin, a branched chain olefin or a mixture thereof.

46. The method according to claim 45, wherein the hydrocarbyl group is an alkyl group.

47. The method according to claim 46, wherein the alkyl group has from about 12 to 40 carbon atoms.
48. The method according to claim 47, wherein the alkyl group has from about 18 to 30 carbon atoms.
49. The method according to claim 48, wherein the alkyl group is derived from an isomerized olefin.
50. The method according to claim 46, wherein the alkyl group is a branched alkyl group having at least 9 carbon atoms.
51. The method according to claim 50, wherein the alkyl group is a branched alkyl group having from about 9 to 24 carbon atoms.
52. The method according to claim 51, wherein the alkyl group is a branched alkyl group having from about 10 to 18 carbon atoms.
53. The method according to any one of claims 44 to 52, wherein the alkaline earth metal of the alkaline earth metal hydrocarbyl phenate and the alkaline earth metal single aromatic-ring hydrocarbyl salicylate is independently selected from the group consisting of calcium, magnesium, barium, or strontium.
54. The method according to claim 53, wherein the alkaline earth metal of the alkaline earth metal hydrocarbyl phenate and the alkaline earth metal single aromatic-ring hydrocarbyl salicylate is calcium.
55. The method according to claim 43, wherein the alkaline earth metal of the alkaline earth metal salt of linear, saturated carboxylic acid is calcium.

56. The method according to claim 55, wherein the linear, saturated carboxylic acid is stearic acid.
57. The method according to claim 43, wherein the alkaline earth metal salt of the linear, saturated carboxylic acid is present at a concentration of from about 3.5 wt % to 7.0 wt % based on the total additive composition.
58. The method composition according to claim 57, wherein the alkaline earth metal salt of linear, saturated carboxylic acid is present at a concentration of from about 4.0 wt % to 6.0 wt % based on the total additive composition.
59. The method according to any one of claims 43 to 58, wherein linear, saturated carboxylic acid is stearic acid.
60. The method according to any one of claims 43 to 59, wherein the superalkalinization ratio is less than about 1:1.
61. The method according to any one of claims 43 to 59, wherein the superalkalinization ratio is less than about 0.2 to 1.
62. The method according to any one of claims 43 to 61, wherein the TBN is less than about 160.
63. The method according to any one of claims 43 to 61, wherein the TBN is less than about 140.
64. The method according to claim 43, wherein the solvent in step d) is 2-ethylhexanol.
65. A product produced according to the method of claim 43.

66. A method of improving low temperature viscosity while maintaining corrosion and detergent properties of a lubricating oil composition in an internal combustion engine, said method comprising operating the internal combustion engine with a lubricating oil composition comprising:

- a) a major amount of base oil of lubricating viscosity; and
- b) a minor amount of an unsulfurized carboxylate detergent-dispersant additive having been modified by incorporation of from about 3.2 wt % to 7.5 wt %, based on the total additive composition, of an alkaline earth metal salt of a linear, saturated carboxylic acid having from about 16 to about 20 carbon atoms and wherein the additive composition has a superalkalinization ratio of less than about 1.4:1, a TBN of less than about 200 and a sediment value of less than about 0.2 % by volume.

67. The method according to claim 66, wherein the lubricating oil composition is a low emission diesel lubricant.