

- (51) International Patent Classification:
C08G 59/68 (2006.01) C09D 163/00 (2006.01)
- (21) International Application Number:
PCT/BR2024/050150
- (22) International Filing Date:
12 April 2024 (12.04.2024)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
23167821.0 13 April 2023 (13.04.2023) EP
- (71) Applicant: ACTEGA DO BRASIL TINTAS E VERNIZES LTDA. [BR/BR]; Rua Nossa Senhora da Penha No. 800 - 850 - São Paulo - Brazil, 18147-000 Araçariгуama (BR).
- (72) Inventors: GALHARDO, Antonio; 06460 Barueri, Barueri (BR). ALAN VIEIRA; 06460 Barueri, Barueri (BR).
- (74) Agent: VAZ E DIAS ADVOGADOS & ASSOCIADOS; Rua da Assembleia 10 - Seção 2422 Centro - Rio de Janeiro/RJ, Rio de Janeiro (BR).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, MG, MK, MN, MU, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, CV, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SC, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, ME, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:
— with international search report (Art. 21(3))

(54) Title: UV LACQUER FOR DIRECT TO METAL APPLICATION

(57) Abstract: A UV-curable lacquer was developed that shows improved adhesion to metal substrates. The lacquer composition comprises a) A mixture of different epoxy resins, b) An acrylate compound, c) A photoinitiator, d) Polycaprolactone triol, and e) Cellulose acetate butyrate.