

AUDIO SIGNAL CLASSIFICATION METHOD AND APPARATUS

TECHNICAL FIELD

5 [0002] The present invention relates to the field of digital signal processing technologies, and in particular, to an audio signal classification method and apparatus.

BACKGROUND

[0003] To reduce resources occupied by a video signal during storage or transmission, an audio signal is compressed at a transmit end and then transmitted to a receive end, and the receive end
10 restores the audio signal by means of decompressing.

[0004] In an audio processing application, audio signal classification is an important technology that is applied widely. For example, in an audio encoding/decoding application, a relatively popular codec is a type of hybrid of encoding and decoding currently. This codec generally includes an encoder (such as CELP) based on a speech generating model and an encoder based on conversion
15 (such as an encoder based on MDCT). At an intermediate or low bit rate, the encoder based on a speech generating model can obtain relatively good speech encoding quality, but has relatively poor music encoding quality, while the encoder based on conversion can obtain relatively good music encoding quality, but has relatively poor speech encoding quality. Therefore, the hybrid codec encodes a speech signal by using the encoder based on a speech generating model, and encodes a
20 music signal by using the encoder based on conversion, thereby obtaining an optimal encoding effect on the whole. Herein, a core technology is audio signal classification, or encoding mode selection as far as this application is specifically concerned.

[0005] The hybrid codec needs to obtain accurate signal type information before the hybrid codec can obtain optimal encoding mode selection. An audio signal classifier herein may also be
25 roughly considered as a speech/music classifier. A speech recognition rate and a music recognition rate are important indicators for measuring performance of the speech/music classifier. Particularly

for a music signal, due to diversity/complexity of its signal characteristics, recognition of the music signal is generally more difficult than that of a speech signal. In addition, a recognition delay is also one of very important indicators. Due to fuzziness of characteristics of speech/music in a short time, it generally needs to take a relatively long time before the speech/music can be recognized relatively accurately. Generally, at an intermediate section of a same type of signals, a longer recognition delay indicates more accurate recognition. However, at a transition section of two types of signals, a longer recognition delay indicates lower recognition accuracy, which is especially severe in a situation in which a hybrid signal (such as a speech having background music) is input. Therefore, having both a high recognition rate and a low recognition delay is a necessary attribute of a high-performance speech/music recognizer. In addition, classification stability is also an important attribute that affects encoding quality of a hybrid encoder. Generally, when the hybrid encoder switches between different types of encoders, quality deterioration may occur. If frequent type switching occurs in a classifier in a same type of signals, encoding quality is affected relatively greatly; therefore, it is required that an output classification result of the classifier should be accurate and smooth. Additionally, in some applications, such as a classification algorithm in a communications system, it is also required that calculation complexity and storage overheads of the classification algorithm should be as low as possible, to satisfy commercial requirements.

[0006] The ITU-T standard G.720.1 includes a speech/music classifier. This classifier uses a main parameter: a frequency spectrum fluctuation variance `var_flux` as a main basis for signal classification, and uses two different frequency spectrum peakiness parameters `p1` and `p2` as an auxiliary basis. Classification of an input signal according to `var_flux` is completed in an FIFO `var_flux` buffer according to local statistics of `var_flux`. A specific process is summarized as follows: First, a frequency spectrum fluctuation flux is extracted from each input audio frame and buffered in a first buffer, and flux herein is calculated in four latest frames including a current input frame, or may be calculated by using another method. Then, a variance of flux of `N` latest frames including the current input frame is calculated, to obtain `var_flux` of the current input frame, and `var_flux` is buffered in a second buffer. Then, a quantity `K` of frames whose `var_flux` is greater than a first threshold among `M` latest frames including the current input frame in the second buffer is counted. If a ratio of `K` to `M` is greater than a second threshold, it is determined that the current input frame is a speech frame; otherwise the current input frame is a music frame. The auxiliary parameters `p1` and `p2` are mainly used to modify classification, and are also calculated for each input audio frame. When `p1` and/or `p2` is greater than a third threshold and/or a fourth threshold, it is directly determined that the current input audio frame is a music frame.

[0007] Disadvantages of this speech/music classifier are as follows: on one hand, an absolute

recognition rate for music still needs to be improved, and on the other hand, because target applications of the classifier are not specific to an application scenario of a hybrid signal, there is also still room for improvement in recognition performance for a hybrid signal.

[0008] Many existing speech/music classifiers are designed based on a mode recognition principle. This type of classifiers generally extract multiple (a dozen to several dozens) characteristic parameters from an input audio frame, and feed these parameters into a classifier based on a Gaussian hybrid model, or a neural network, or another classical classification method to perform classification.

[0009] This type of classifiers have a relatively solid theoretical basis, but generally have relatively high calculation or storage complexity, and therefore, implementation costs are relatively high.

SUMMARY

[0010] An objective of embodiments of the present invention is to provide an audio signal classification method and apparatus, to reduce signal classification complexity while ensuring a classification recognition rate of a hybrid audio signal.

[0011] According to a first aspect, an audio signal classification method is provided, where the method includes:

determining, according to voice activity of a current audio frame, whether to obtain a frequency spectrum fluctuation of the current audio frame and store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory, where the frequency spectrum fluctuation denotes an energy fluctuation of a frequency spectrum of an audio signal;

updating, according to whether the audio frame is percussive music or activity of a historical audio frame, frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory; and

classifying the current audio frame as a speech frame or a music frame according to statistics of a part or all of effective data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory.

[0012] In a first possible implementation manner, the determining, according to voice activity of a current audio frame, whether to obtain a frequency spectrum fluctuation of the current audio frame and store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory includes:

if the current audio frame is an active frame, storing the frequency spectrum fluctuation of the current audio frame in the frequency spectrum fluctuation memory.

[0013] In a second possible implementation manner, the determining, according to voice activity of a current audio frame, whether to obtain a frequency spectrum fluctuation of the current audio frame and store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory includes:

5 if the current audio frame is an active frame, and the current audio frame does not belong to an energy attack, storing the frequency spectrum fluctuation of the current audio frame in the frequency spectrum fluctuation memory.

[0014] In a third possible implementation manner, the determining, according to voice activity of a current audio frame, whether to obtain a frequency spectrum fluctuation of the current audio
10 frame and store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory includes:

if the current audio frame is an active frame, and none of multiple consecutive frames including the current audio frame and a historical frame of the current audio frame belongs to an energy attack, storing the frequency spectrum fluctuation of the audio frame in the frequency
15 spectrum fluctuation memory.

[0015] With reference to the first aspect or the first possible implementation manner of the first aspect or the second possible implementation manner of the first aspect or the third possible implementation manner of the first aspect, in a fourth possible implementation manner, the updating, according to whether the current audio frame is percussive music, frequency spectrum fluctuations
20 stored in the frequency spectrum fluctuation memory includes:

if the current audio frame belongs to percussive music, modifying values of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory.

[0016] With reference to the first aspect or the first possible implementation manner of the first aspect or the second possible implementation manner of the first aspect or the third possible
25 implementation manner of the first aspect, in a fifth possible implementation manner, the updating, according to activity of a historical audio frame, frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory includes:

if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and a previous audio frame is an inactive
30 frame, modifying data of other frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory except the frequency spectrum fluctuation of the current audio frame into ineffective data; or

if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and three consecutive historical frames before

the current audio frame are not all active frames, modifying the frequency spectrum fluctuation of the current audio frame into a first value; or

if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and a historical classification result is a music signal and the frequency spectrum fluctuation of the current audio frame is greater than a second value, modifying the frequency spectrum fluctuation of the current audio frame into the second value, where the second value is greater than the first value.

[0017] With reference to the first aspect or the first possible implementation manner of the first aspect or the second possible implementation manner of the first aspect or the third possible implementation manner of the first aspect or the fourth possible implementation manner of the first aspect or the fifth possible implementation manner of the first aspect, in a sixth possible implementation manner, the classifying the current audio frame as a speech frame or a music frame according to statistics of a part or all of effective data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory includes:

obtaining an average value of a part or all of the effective data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory; and

when the obtained average value of the effective data of the frequency spectrum fluctuations satisfies a music classification condition, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame.

[0018] With reference to the first aspect or the first possible implementation manner of the first aspect or the second possible implementation manner of the first aspect or the third possible implementation manner of the first aspect or the fourth possible implementation manner of the first aspect or the fifth possible implementation manner of the first aspect, in a seventh possible implementation manner, the audio signal classification method further includes:

obtaining a frequency spectrum high-frequency-band peakiness, a frequency spectrum correlation degree, and a linear prediction residual energy tilt of the current audio frame, where the frequency spectrum high-frequency-band peakiness denotes a peakiness or an energy acutance, on a high frequency band, of a frequency spectrum of the current audio frame; the frequency spectrum correlation degree denotes stability, between adjacent frames, of a signal harmonic structure of the current audio frame; and the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases; and

determining, according to the voice activity of the current audio frame, whether to store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt in memories,

where the classifying the audio frame according to statistics of a part or all of data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory includes:

obtaining an average value of the effective data of the stored frequency spectrum fluctuations, an average value of effective data of stored frequency spectrum high-frequency-band peakiness, an average value of effective data of stored frequency spectrum correlation degrees, and a variance of effective data of stored linear prediction residual energy tilts separately; and

when one of the following conditions is satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0019] According to a second aspect, an audio signal classification apparatus is provided, where the apparatus is configured to classify an input audio signal, and includes:

a storage determining unit, configured to determine, according to voice activity of the current audio frame, whether to obtain and store a frequency spectrum fluctuation of the current audio frame, where the frequency spectrum fluctuation denotes an energy fluctuation of a frequency spectrum of an audio signal;

a memory, configured to store the frequency spectrum fluctuation when the storage determining unit outputs a result that the frequency spectrum fluctuation needs to be stored;

an updating unit, configured to update, according to whether a speech frame is percussive music or activity of a historical audio frame, frequency spectrum fluctuations stored in the memory; and

a classification unit, configured to classify the current audio frame as a speech frame or a music frame according to statistics of a part or all of effective data of the frequency spectrum fluctuations stored in the memory.

[0020] In a first possible implementation manner, the storage determining unit is specifically configured to: when it is determined that the current audio frame is an active frame, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

[0021] In a second possible implementation manner, the storage determining unit is specifically configured to: when it is determined that the current audio frame is an active frame, and the current audio frame does not belong to an energy attack, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

[0022] In a third possible implementation manner, the storage determining unit is specifically configured to: when it is determined that the current audio frame is an active frame, and none of multiple consecutive frames including the current audio frame and a historical frame of the current audio frame belongs to an energy attack, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

[0023] With reference to the second aspect or the first possible implementation manner of the second aspect or the second possible implementation manner of the second aspect or the third possible implementation manner of the second aspect, in a fourth possible implementation manner, the updating unit is specifically configured to: if the current audio frame belongs to percussive music, modify values of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory.

[0024] With reference to the second aspect or the first possible implementation manner of the second aspect or the second possible implementation manner of the second aspect or the third possible implementation manner of the second aspect, in a fifth possible implementation manner, the updating unit is specifically configured to: if the current audio frame is an active frame, and a previous audio frame is an inactive frame, modify data of other frequency spectrum fluctuations stored in the memory except the frequency spectrum fluctuation of the current audio frame into ineffective data; or

if the current audio frame is an active frame, and three consecutive frames before the current audio frame are not all active frames, modify the frequency spectrum fluctuation of the current audio frame into a first value; or

if the current audio frame is an active frame, and a historical classification result is a music signal and the frequency spectrum fluctuation of the current audio frame is greater than a second value, modify the frequency spectrum fluctuation of the current audio frame into the second value, where the second value is greater than the first value.

[0025] With reference to the second aspect or the first possible implementation manner of the second aspect or the second possible implementation manner of the second aspect or the third possible implementation manner of the second aspect or the fourth possible implementation manner of the second aspect or the fifth possible implementation manner of the second aspect, in a sixth possible implementation manner, the classification unit includes:

a calculating unit, configured to obtain an average value of a part or all of the effective data of the frequency spectrum fluctuations stored in the memory; and

a determining unit, configured to compare the average value of the effective data of the frequency spectrum fluctuations with a music classification condition; and when the average value

of the effective data of the frequency spectrum fluctuations satisfies the music classification condition, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame.

[0026] With reference to the second aspect or the first possible implementation manner of the second aspect or the second possible implementation manner of the second aspect or the third possible implementation manner of the second aspect or the fourth possible implementation manner of the second aspect or the fifth possible implementation manner of the second aspect, in a seventh possible implementation manner, the audio signal classification apparatus further includes:

a parameter obtaining unit, configured to obtain a frequency spectrum high-frequency-band peakiness, a frequency spectrum correlation degree, a voicing parameter, and a linear prediction residual energy tilt of the current audio frame, where the frequency spectrum high-frequency-band peakiness denotes a peakiness or an energy acutance, on a high frequency band, of a frequency spectrum of the current audio frame; the frequency spectrum correlation degree denotes stability, between adjacent frames, of a signal harmonic structure of the current audio frame; the voicing parameter denotes a time domain correlation degree between the current audio frame and a signal before a pitch period; and the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases; where

the storage determining unit is further configured to determine, according to the voice activity of the current audio frame, whether to store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt in memories;

the storage unit is further configured to: when the storage determining unit outputs a result that the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt need to be stored, store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt; and

the classification unit is specifically configured to obtain statistics of effective data of the stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of stored linear prediction residual energy tilts, and classify the audio frame as a speech frame or a music frame according to the statistics of the effective data.

[0027] With reference to the seventh possible implementation manner of the second aspect, in an eighth possible implementation manner, the classification unit includes:

a calculating unit, configured to obtain an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored

linear prediction residual energy tilts separately; and

a determining unit, configured to: when one of the following conditions is satisfied, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0028] According to a third aspect, an audio signal classification method is provided, where the method includes:

performing frame division processing on an input audio signal;

obtaining a linear prediction residual energy tilt of a current audio frame, where the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases;

storing the linear prediction residual energy tilt in a memory; and

classifying the audio frame according to statistics of a part of data of prediction residual energy tilts in the memory.

[0029] In a first possible implementation manner, before the storing the linear prediction residual energy tilt in a memory, the method further includes:

determining, according to voice activity of the current audio frame, whether to store the linear prediction residual energy tilt in the memory; and storing the linear prediction residual energy tilt in the memory when it is determined that the linear prediction residual energy tilt needs to be stored.

[0030] With reference to the third aspect or the first possible implementation manner of the third aspect, in a second possible implementation manner, the statistics of the part of the data of the prediction residual energy tilts is a variance of the part of the data of the prediction residual energy tilts; and the classifying the audio frame according to statistics of a part of data of prediction residual energy tilts in the memory includes:

comparing the variance of the part of the data of the prediction residual energy tilts with

a music classification threshold, and when the variance of the part of the data of the prediction residual energy tilts is less than the music classification threshold, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame.

[0031] With reference to the third aspect or the first possible implementation manner of the third aspect, in a third possible implementation manner, the audio signal classification method further includes:

obtaining a frequency spectrum fluctuation, a frequency spectrum high-frequency-band peakiness, and a frequency spectrum correlation degree of the current audio frame, and storing the frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, and the frequency spectrum correlation degree in corresponding memories,

where the classifying the audio frame according to statistics of a part of data of prediction residual energy tilts in the memory includes:

obtaining statistics of effective data of stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of the stored linear prediction residual energy tilts, and classifying the audio frame as a speech frame or a music frame according to the statistics of the effective data, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on the effective data stored in the memories.

[0032] With reference to the third possible implementation manner of the third aspect, in a fourth possible implementation manner, the obtaining statistics of effective data of stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of the stored linear prediction residual energy tilts, and classifying the audio frame as a speech frame or a music frame according to the statistics of the effective data includes:

obtaining an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

when one of the following conditions is satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is

greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0033] With reference to the third aspect or the first possible implementation manner of the third aspect, in a fifth possible implementation manner, the audio signal classification method further includes:

obtaining a frequency spectrum tone quantity of the current audio frame and a ratio of the frequency spectrum tone quantity on a low frequency band, and storing the frequency spectrum tone quantity and the ratio of the frequency spectrum tone quantity on the low frequency band in corresponding memories,

where the classifying the audio frame according to statistics of a part of data of prediction residual energy tilts in the memory includes:

obtaining statistics of the stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately; and

classifying the audio frame as a speech frame or a music frame according to the statistics of the linear prediction residual energy tilts, the statistics of the frequency spectrum tone quantities, and the ratio of the frequency spectrum tone quantity on the low frequency band, where the statistics refer to a data value obtained after a calculation operation is performed on data stored in the memories.

[0034] With reference to the fifth possible implementation manner of the third aspect, in a sixth possible implementation manner, the obtaining statistics of the stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately includes:

obtaining a variance of the stored linear prediction residual energy tilts; and

obtaining an average value of the stored frequency spectrum tone quantities; and

the classifying the audio frame as a speech frame or a music frame according to the statistics of the linear prediction residual energy tilts, the statistics of the frequency spectrum tone quantities, and the ratio of the frequency spectrum tone quantity on the low frequency band includes:

when the current audio frame is an active frame, and one of the following conditions is satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame:

the variance of the linear prediction residual energy tilts is less than a fifth threshold; or

the average value of the frequency spectrum tone quantities is greater than a sixth threshold; or

the ratio of the frequency spectrum tone quantity on the low frequency band is less than a seventh threshold.

[0035] With reference to the third aspect or the first possible implementation manner of the third aspect or the second possible implementation manner of the third aspect or the third possible implementation manner of the third aspect or the fourth possible implementation manner of the third aspect or the fifth possible implementation manner of the third aspect or the sixth possible implementation manner of the third aspect, in a seventh possible implementation manner, the obtaining a linear prediction residual energy tilt of a current audio frame includes:

obtaining the linear prediction residual energy tilt of the current audio frame according to the following formula:

$$epsP_tilt = \frac{\sum_{i=1}^n epsP(i) \cdot epsP(i+1)}{\sum_{i=1}^n epsP(i) \cdot epsP(i)},$$

where $epsP(i)$ denotes prediction residual energy of i^{th} -order linear prediction of the current audio frame; and n is a positive integer, denotes a linear prediction order, and is less than or equal to a maximum linear prediction order.

[0036] With reference to the fifth possible implementation manner of the third aspect or the sixth possible implementation manner of the third aspect, in an eighth possible implementation manner, the obtaining a frequency spectrum tone quantity of the current audio frame and a ratio of the frequency spectrum tone quantity on a low frequency band includes:

counting a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 8 kHz and have frequency bin peak values greater than a predetermined value, to use the quantity as the frequency spectrum tone quantity; and

calculating a ratio of a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 4 kHz and have frequency bin peak values greater than the predetermined value to the quantity of the frequency bins of the current audio frame that are on the frequency band from 0 to 8 kHz and have frequency bin peak values greater than the predetermined value, to use the ratio as the ratio of the frequency spectrum tone quantity on the low frequency band.

[0037] According to a fourth aspect, a signal classification apparatus is provided, where the apparatus is configured to classify an input audio signal, and includes:

a frame dividing unit, configured to perform frame division processing on an input audio signal;

a parameter obtaining unit, configured to obtain a linear prediction residual energy tilt of a current audio frame, where the linear prediction residual energy tilt denotes an extent to which

linear prediction residual energy of the audio signal changes as a linear prediction order increases;
a storage unit, configured to store the linear prediction residual energy tilt; and
a classification unit, configured to classify the audio frame according to statistics of a part of data of prediction residual energy tilts in a memory.

5 **[0038]** In a first possible implementation manner, the signal classification apparatus further includes:

a storage determining unit, configured to determine, according to voice activity of the current audio frame, whether to store the linear prediction residual energy tilt in the memory, where
the storage unit is specifically configured to: when the storage determining unit
10 determines that the linear prediction residual energy tilt needs to be stored, store the linear prediction residual energy tilt in the memory.

[0039] With reference to the fourth aspect or the first possible implementation manner of the fourth aspect, in a second possible implementation manner, the statistics of the part of the data of the prediction residual energy tilts is a variance of the part of the data of the prediction residual
15 energy tilts; and

the classification unit is specifically configured to compare the variance of the part of the data of the prediction residual energy tilts with a music classification threshold, and when the variance of the part of the data of the prediction residual energy tilts is less than the music classification threshold, classify the current audio frame as a music frame; otherwise classify the
20 current audio frame as a speech frame.

[0040] With reference to the fourth aspect or the first possible implementation manner of the fourth aspect, in a third possible implementation manner, the parameter obtaining unit is further configured to: obtain a frequency spectrum fluctuation, a frequency spectrum high-frequency-band peakiness, and a frequency spectrum correlation degree of the current audio frame, and store the
25 frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, and the frequency spectrum correlation degree in corresponding memories; and

the classification unit is specifically configured to obtain statistics of effective data of stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation
30 degrees, and statistics of effective data of the stored linear prediction residual energy tilts, and classify the audio frame as a speech frame or a music frame according to the statistics of the effective data, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on the effective data stored in the memories.

[0041] With reference to the third possible implementation manner of the fourth aspect, in a

fourth possible implementation manner, the classification unit includes:

a calculating unit, configured to obtain an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

a determining unit, configured to: when one of the following conditions is satisfied, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0042] With reference to the fourth aspect or the first possible implementation manner of the fourth aspect, in a fifth possible implementation manner, the parameter obtaining unit is further configured to obtain a frequency spectrum tone quantity of the current audio frame and a ratio of the frequency spectrum tone quantity on a low frequency band, and store the frequency spectrum tone quantity and the ratio of the frequency spectrum tone quantity on the low frequency band in memories; and

the classification unit is specifically configured to obtain statistics of the stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately; and classify the audio frame as a speech frame or a music frame according to the statistics of the linear prediction residual energy tilts, the statistics of the frequency spectrum tone quantities, and the ratio of the frequency spectrum tone quantity on the low frequency band, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on data stored in the memories.

[0043] With reference to the fifth possible implementation manner of the fourth aspect, in a sixth possible implementation manner, the classification unit includes:

a calculating unit, configured to obtain a variance of effective data of the stored linear prediction residual energy tilts and an average value of the stored frequency spectrum tone quantities; and

a determining unit, configured to: when the current audio frame is an active frame, and one of the following conditions is satisfied, classify the current audio frame as a music frame;

otherwise classify the current audio frame as a speech frame: the variance of the linear prediction residual energy tilts is less than a fifth threshold; or the average value of the frequency spectrum tone quantities is greater than a sixth threshold; or the ratio of the frequency spectrum tone quantity on the low frequency band is less than a seventh threshold.

5 **[0044]** With reference to the fourth aspect or the first possible implementation manner of the fourth aspect or the second possible implementation manner of the fourth aspect or the third possible implementation manner of the fourth aspect or the fourth possible implementation manner of the fourth aspect or the fifth possible implementation manner of the fourth aspect or the sixth possible implementation manner of the fourth aspect, in a seventh possible implementation manner,
10 the parameter obtaining unit obtains the linear prediction residual energy tilt of the current audio frame according to the following formula:

$$epsP_tilt = \frac{\sum_{i=1}^n epsP(i) \cdot epsP(i+1)}{\sum_{i=1}^n epsP(i) \cdot epsP(i)},$$

where $epsP(i)$ denotes prediction residual energy of i^{th} -order linear prediction of the current audio frame; and n is a positive integer, denotes a linear prediction order, and is less than or
15 equal to a maximum linear prediction order.

[0045] With reference to the fifth possible implementation manner of the fourth aspect or the sixth possible implementation manner of the fourth aspect, in an eighth possible implementation manner, the parameter obtaining unit is configured to count a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 8 kHz and have frequency bin peak
20 values greater than a predetermined value, to use the quantity as the frequency spectrum tone quantity; and the parameter obtaining unit is configured to calculate a ratio of a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 4 kHz and have frequency bin peak values greater than the predetermined value to the quantity of the frequency bins of the current audio frame that are on the frequency band from 0 to 8 kHz and have frequency bin
25 peak values greater than the predetermined value, to use the ratio as the ratio of the frequency spectrum tone quantity on the low frequency band.

[0046] In the embodiments of the present invention, an audio signal is classified according to long-time statistics of frequency spectrum fluctuations; therefore, there are relatively few parameters, a recognition rate is relatively high, and complexity is relatively low. In addition, the
30 frequency spectrum fluctuations are adjusted with consideration of factors such as voice activity and percussive music; therefore, the present invention has a higher recognition rate for a music signal, and is suitable for hybrid audio signal classification.

BRIEF DESCRIPTION OF DRAWINGS

[0047] To describe the technical solutions in the embodiments of the present invention or in the prior art more clearly, the following briefly introduces the accompanying drawings required for describing the embodiments or the prior art. Apparently, the accompanying drawings in the following description show merely some embodiments of the present invention, and a person of ordinary skill in the art may still derive other drawings from these accompanying drawings without creative efforts.

[0048] FIG. 1 is a schematic diagram of dividing an audio signal into frames;

[0049] FIG. 2 is a schematic flowchart of an embodiment of an audio signal classification method according to the present invention;

[0050] FIG. 3 is a schematic flowchart of an embodiment of obtaining a frequency spectrum fluctuation according to the present invention;

[0051] FIG. 4 is a schematic flowchart of another embodiment of an audio signal classification method according to the present invention;

[0052] FIG. 5 is a schematic flowchart of another embodiment of an audio signal classification method according to the present invention;

[0053] FIG. 6 is a schematic flowchart of another embodiment of an audio signal classification method according to the present invention;

[0054] FIG. 7 to FIG. 10 are specific classification flowcharts of audio signal classification according to the present invention;

[0055] FIG. 11 is a schematic flowchart of another embodiment of an audio signal classification method according to the present invention;

[0056] FIG. 12 is a specific classification flowchart of audio signal classification according to the present invention;

[0057] FIG. 13 is a schematic structural diagram of an embodiment of an audio signal classification apparatus according to the present invention;

[0058] FIG. 14 is a schematic structural diagram of an embodiment of a classification unit according to the present invention;

[0059] FIG. 15 is a schematic structural diagram of another embodiment of an audio signal classification apparatus according to the present invention;

[0060] FIG. 16 is a schematic structural diagram of another embodiment of an audio signal classification apparatus according to the present invention;

[0061] FIG. 17 is a schematic structural diagram of an embodiment of a classification unit according to the present invention;

[0062] FIG. 18 is a schematic structural diagram of another embodiment of an audio signal classification apparatus according to the present invention; and

[0063] FIG. 19 is a schematic structural diagram of another embodiment of an audio signal classification apparatus according to the present invention.

5

DESCRIPTION OF EMBODIMENTS

[0064] The following clearly and completely describes the technical solutions in the embodiments of the present invention with reference to the accompanying drawings in the embodiments of the present invention. Apparently, the described embodiments are merely some but not all of the embodiments of the present invention. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of the present invention without creative efforts shall fall within the protection scope of the present invention.

[0065] In the field of digital signal processing, audio codecs and video codecs are widely applied in various electronic devices, for example, a mobile phone, a wireless apparatus, a personal digital assistant (PDA), a handheld or portable computer, a GPS receiver/navigator, a camera, an audio/video player, a video camera, a video recorder, and a monitoring device. Generally, this type of electronic device includes an audio encoder or an audio decoder, where the audio encoder or decoder may be directly implemented by a digital circuit or a chip, for example, a DSP (digital signal processor), or be implemented by software code driving a processor to execute a process in the software code. In an audio encoder, an audio signal is first classified, different types of audio signals are encoded in different encoding modes, and then a bitstream obtained after the encoding is transmitted to a decoder side.

[0066] Generally, an audio signal is processed in a frame division manner, and each frame of signal represents an audio signal of a specified duration. Referring to FIG. 1, an audio frame that is currently input and needs to be classified may be referred to as a current audio frame, and any audio frame before the current audio frame may be referred to as a historical audio frame. According to a time sequence from the current audio frame to historical audio frames, the historical audio frames may sequentially become a previous audio frame, a previous second audio frame, a previous third audio frame, and a previous Nth audio frame, where N is greater than or equal to four.

[0067] In this embodiment, an input audio signal is a broadband audio signal sampled at 16 kHz, and the input audio signal is divided into frames by using 20 ms as a frame, that is, each frame has 320 time domain sampling points. Before a characteristic parameter is extracted, an input audio signal frame is first downsampled at a sampling rate of 12.8 kHz, that is, there are 256 sampling points in each frame. Each input audio signal frame in the following refers to an audio signal frame

obtained after downsampling.

[0068] Referring to FIG. 2, an embodiment of an audio signal classification method includes:

[0069] S101: Perform frame division processing on an input audio signal, and determine, according to voice activity of a current audio frame, whether to obtain a frequency spectrum fluctuation of the current audio frame and store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory, where the frequency spectrum fluctuation denotes an energy fluctuation of a frequency spectrum of an audio signal.

[0070] Audio signal classification is generally performed on a per frame basis, and a parameter is extracted from each audio signal frame to perform classification, to determine whether the audio signal frame belongs to a speech frame or a music frame, and perform encoding in a corresponding encoding mode. In an embodiment, a frequency spectrum fluctuation of a current audio frame may be obtained after frame division processing is performed on an audio signal, and then it is determined according to voice activity of the current audio frame whether to store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory. In another embodiment, after frame division processing is performed on an audio signal, it may be determined according to voice activity of a current audio frame whether to store a frequency spectrum fluctuation in a frequency spectrum fluctuation memory, and when the frequency spectrum fluctuation needs to be stored, the frequency spectrum fluctuation is obtained and stored.

[0071] The frequency spectrum fluctuation flux denotes a short-time or long-time energy fluctuation of a frequency spectrum of a signal, and is an average value of absolute values of logarithmic energy differences between corresponding frequencies of a current audio frame and a historical frame on a low and mid-band spectrum, where the historical frame refers to any frame before the current audio frame. In an embodiment, a frequency spectrum fluctuation is an average value of absolute values of logarithmic energy differences between corresponding frequencies of a current audio frame and a historical frame of the current audio frame on a low and mid-band spectrum. In another embodiment, a frequency spectrum fluctuation is an average value of absolute values of logarithmic energy differences between corresponding frequency spectrum peak values of a current audio frame and a historical frame on a low and mid-band spectrum.

[0072] Referring to FIG. 3, an embodiment of obtaining a frequency spectrum fluctuation includes the following steps:

[0073] S1011: Obtain a frequency spectrum of a current audio frame.

[0074] In an embodiment, a frequency spectrum of an audio frame may be directly obtained; in another embodiment, frequency spectrums, that is, energy spectrums, of any two subframes of a current audio frame are obtained, and a frequency spectrum of the current audio frame is obtained

by using an average value of the frequency spectrums of the two subframes.

[0075] S1012: Obtain a frequency spectrum of a historical frame of the current audio frame.

[0076] The historical frame refers to any audio frame before the current audio frame, and may be the third audio frame before the current audio frame in an embodiment.

5 **[0077]** S1013: Calculate an average value of absolute values of logarithmic energy differences between corresponding frequencies of the current audio frame and the historical frame on a low and mid-band spectrum, to use the average value as a frequency spectrum fluctuation of the current audio frame.

[0078] In an embodiment, an average value of absolute values of differences between
10 logarithmic energy of all frequency bins of a current audio frame on a low and mid-band spectrum and logarithmic energy of corresponding frequency bins of a historical frame on the low and mid-band spectrum may be calculated.

[0079] In another embodiment, an average value of absolute values of differences between
15 logarithmic energy of frequency spectrum peak values of a current audio frame on a low and mid-band spectrum and logarithmic energy of corresponding frequency spectrum peak values of a historical frame on the low and mid-band spectrum may be calculated.

[0080] The low and mid-band spectrum is, for example, a frequency spectrum range of 0 to $f_s/4$ or 0 to $f_s/3$.

[0081] An example in which an input audio signal is a broadband audio signal sampled at 16
20 kHz and the input audio signal uses 20 ms as a frame is used, former FFT of 256 points and latter FFT of 256 points are performed on a current audio frame of every 20 ms, two FFT windows are overlapped by 50%, and frequency spectrums (energy spectrums) of two subframes of the current audio frame are obtained, and are respectively marked as $C^0(i)$ and $C^1(i)$, $i = 0, 1, \dots, 127$, where $C^x(i)$ denotes a frequency spectrum of an x^{th} subframe. Data of a second subframe of a previous
25 frame needs to be used for FFT of a first subframe of the current audio frame, where

$$C^x(i) = \text{rel}^2(i) + \text{img}^2(i),$$

where $\text{rel}(i)$ and $\text{img}(i)$ denote a real part and an imaginary part of an FFT coefficient of the i^{th} frequency bin respectively. The frequency spectrum $C(i)$ of the current audio frame is obtained by averaging the frequency spectrums of the two subframes, where

$$C(i) = \frac{1}{2}(C^0(i) + C^1(i)).$$

30 **[0082]** The frequency spectrum fluctuation flux of the current audio frame is an average value of absolute values of logarithmic energy differences between corresponding frequencies of the current audio frame and a frame 60 ms ahead of the current audio frame on a low and mid-band

spectrum in an embodiment, and the interval may not be 60 ms in another embodiment, where

$$flux = \frac{1}{42} \sum_{i=0}^{42} [10 \log(C(i)) - 10 \log(C_{-3}(i))]$$

where $C_{-3}(i)$ denotes a frequency spectrum of the third historical frame before the current audio frame, that is, a historical frame 60 ms ahead of the current audio frame when a frame length is 20 ms in this embodiment. Each form similar to $X_{-n}()$ in this specification denotes a parameter X of the n^{th} historical frame of the current audio frame, and a subscript 0 may be omitted for the current audio frame. $\log(.)$ denotes a logarithm with 10 as a base.

[0083] In another embodiment, the frequency spectrum fluctuation flux of the current audio frame may also be obtained by using the following method, that is, the frequency spectrum fluctuation flux is an average value of absolute values of logarithmic energy differences between corresponding frequency spectrum peak values of the current audio frame and a frame 60 ms ahead of the current audio frame on a low and mid-band spectrum, where

$$flux = \frac{1}{K} \sum_{i=0}^K [10 \log(P(i)) - 10 \log(P_{-3}(i))]$$

where $P(i)$ denotes energy of the i^{th} local peak value of the frequency spectrum of the current audio frame, a frequency bin at which a local peak value is located is a frequency bin, on the frequency spectrum, whose energy is greater than energy of an adjacent higher frequency bin and energy of an adjacent lower frequency bin, and K denotes a quantity of local peak values on the low and mid-band spectrum.

[0084] The determining, according to voice activity of a current audio frame, whether to store a frequency spectrum fluctuation in a frequency spectrum fluctuation memory may be implemented in multiple manners:

[0085] In an embodiment, if a voice activity parameter of the audio frame denotes that the audio frame is an active frame, the frequency spectrum fluctuation of the audio frame is stored in the frequency spectrum fluctuation memory; otherwise the frequency spectrum fluctuation is not stored.

[0086] In another embodiment, it is determined, according to the voice activity of the audio frame and whether the audio frame is an energy attack, whether to store the frequency spectrum fluctuation in the memory. If a voice activity parameter of the audio frame denotes that the audio frame is an active frame, and a parameter denoting whether the audio frame is an energy attack denotes that the audio frame does not belong to an energy attack, the frequency spectrum fluctuation of the audio frame is stored in the frequency spectrum fluctuation memory; otherwise the frequency spectrum fluctuation is not stored. In another embodiment, if the current audio frame is an active frame, and none of multiple consecutive frames including the current audio frame and a

historical frame of the current audio frame belongs to an energy attack, the frequency spectrum fluctuation of the audio frame is stored in the frequency spectrum fluctuation memory; otherwise the frequency spectrum fluctuation is not stored. For example, if the current audio frame is an active frame, and none of the current audio frame, a previous audio frame and a previous second audio frame belongs to an energy attack, the frequency spectrum fluctuation of the audio frame is stored in the frequency spectrum fluctuation memory; otherwise the frequency spectrum fluctuation is not stored.

[0087] A voice activity flag `vad_flag` denotes whether a current input signal is an active foreground signal (speech, music, or the like) or a silent background signal (such as background noise or mute) of a foreground signal, and is obtained by a voice activity detector VAD. `vad_flag = 1` denotes that the input signal frame is an active frame, that is, a foreground signal frame; otherwise, `vad_flag = 0` denotes a background signal frame. Because the VAD does not belong to inventive content of the present invention, a specific algorithm of the VAD is not described in detail herein.

[0088] A voice attack flag `attack_flag` denotes whether the current audio frame belongs to an energy attack in music. When several historical frames before the current audio frame are mainly music frames, if frame energy of the current audio frame increases relatively greatly relative to that of a first historical frame before the current audio frame, and increases relatively greatly relative to average energy of audio frames that are within a period of time ahead of the current audio frame, and a time domain envelope of the current audio frame also increases relatively greatly relative to an average envelope of audio frames that are within a period of time ahead of the current audio frame, it is considered that the current audio frame belongs to an energy attack in music.

[0089] According to the voice activity of the current audio frame, the frequency spectrum fluctuation of the current audio frame is stored only when the current audio frame is an active frame, which can reduce a misjudgment rate of an inactive frame, and improve a recognition rate of audio classification.

[0090] When the following conditions are satisfied, `attack_flag` is set to 1, that is, it denotes that the current audio frame is an energy attack in a piece of music:

$$\begin{cases} etot - etot_{-1} > 6 \\ etot - lp_speech > 5 \\ mode_mov > 0.9 \\ log_max_spl - mov_log_max_spl > 5 \end{cases},$$

where `etot` denotes logarithmic frame energy of the current audio frame; `etot-1` denotes logarithmic frame energy of a previous audio frame; `lp_speech` denotes a long-time moving average of the logarithmic frame energy `etot`; `log_max_spl` and `mov_log_max_spl` denotes a time domain

maximum logarithmic sampling point amplitude of the current audio frame and a long-time moving average of the time domain maximum logarithmic sampling point amplitude respectively; and mode_mov denotes a long-time moving average of historical final classification results in signal classification.

5 **[0091]** The meaning of the foregoing formula is: when several historical frames before the current audio frame are mainly music frames, if frame energy of the current audio frame increases relatively greatly relative to that of a first historical frame before the current audio frame, and increases relatively greatly relative to average energy of audio frames that are within a period of time ahead of the current audio frame, and a time domain envelope of the current audio frame also
10 increases relatively greatly relative to an average envelope of audio frames that are within a period of time ahead of the current audio frame, it is considered that the current audio frame belongs to an energy attack in music.

[0092] The logarithmic frame energy $etot$ is denoted by logarithmic total subband energy of an input audio frame:

$$15 \quad etot = 10 \log \left(\sum_{j=0}^{19} \left[\frac{1}{hb(i) - lb(i) + 1} \cdot \sum_{i=lb(j)}^{hb(j)} C(i) \right] \right),$$

where $hb(j)$ and $lb(j)$ denote a high frequency boundary and a low frequency boundary of the j^{th} subband in a frequency spectrum of the input audio frame respectively; and $C(i)$ denotes the frequency spectrum of the input audio frame.

[0093] The long-time moving average $mov_log_max_spl$ of the time domain maximum
20 logarithmic sampling point amplitude of the current audio frame is only updated in an active voice frame:

$$\begin{aligned} mov_log_max_spl = & \\ \begin{cases} 0.95 \cdot mov_log_max_spl_{-1} + 0.05 \cdot log_max_spl & log_max_spl > mov_log_max_spl_{-1} \\ 0.995 \cdot mov_log_max_spl_{-1} + 0.005 \cdot log_max_spl & log_max_spl \leq mov_log_max_spl_{-1} \end{cases} \end{aligned}$$

[0094] In an embodiment, the frequency spectrum fluctuation flux of the current audio frame is buffered in an FIFO flux historical buffer. In this embodiment, the length of the flux historical
25 buffer is 60 (60 frames). The voice activity of the current audio frame and whether the audio frame is an energy attack are determined, and when the current audio frame is a foreground signal frame and none of the current audio frame and two frames before the current audio frame belongs to an energy attack of music, the frequency spectrum fluctuation flux of the current audio frame is stored in the memory.

30 **[0095]** Before flux of the current audio frame is buffered, it is checked whether the following conditions are satisfied:

$$\begin{cases} vad_flag \neq 0 \\ attack_flag \neq 1 \\ attack_flag_{-1} \neq 1 \\ attack_flag_{-2} \neq 1, \end{cases}$$

if the conditions are satisfied, flux is buffered; otherwise flux is not buffered.

[0096] vad_flag denotes whether the current input signal is an active foreground signal or a silent background signal of a foreground signal, and vad_flag = 0 denotes a background signal frame; and attack_flag denotes whether the current audio frame belongs to an energy attack in music, and attack_flag = 1 denotes that the current audio frame is an energy attack in a piece of music.

[0097] The meaning of the foregoing formula is: the current audio frame is an active frame, and none of the current audio frame, the previous audio frame, and the previous second audio frame belongs to an energy attack.

[0098] S102: Update, according to whether the audio frame is percussive music or activity of a historical audio frame, frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory.

[0099] In an embodiment, if a parameter denoting whether the audio frame belongs to percussive music denotes that the current audio frame belongs to percussive music, values of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory are modified, and valid frequency spectrum fluctuation values in the frequency spectrum fluctuation memory are modified into a value less than or equal to a music threshold, where when a frequency spectrum fluctuation of an audio frame is less than the music threshold, the audio is classified as a music frame. In an embodiment, the valid frequency spectrum fluctuation values are reset to 5. That is, when a percussive sound flag percus_flag is set to 1, all valid buffer data in the flux historical buffer is reset to 5. Herein, the valid buffer data is equivalent to a valid frequency spectrum fluctuation value. Generally, a frequency spectrum fluctuation value of a music frame is relatively small, while a frequency spectrum fluctuation value of a speech frame is relatively large. When the audio frame belongs to percussive music, the valid frequency spectrum fluctuation values are modified into a value less than or equal to the music threshold, which can improve a probability that the audio frame is classified as a music frame, thereby improving accuracy of audio signal classification.

[0100] In another embodiment, the frequency spectrum fluctuations in the memory are updated according to activity of a historical frame of the current audio frame. Specifically, in an embodiment, if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and a previous audio frame is an inactive

frame, data of other frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory except the frequency spectrum fluctuation of the current audio frame is modified into ineffective data. When the previous audio frame is an inactive frame while the current audio frame is an active frame, the voice activity of the current audio frame is different from that of the historical frame, a frequency spectrum fluctuation of the historical frame is invalidated, which can reduce an impact of the historical frame on audio classification, thereby improving accuracy of audio signal classification.

[0101] In another embodiment, if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and three consecutive frames before the current audio frame are not all active frames, the frequency spectrum fluctuation of the current audio frame is modified into a first value. The first value may be a speech threshold, where when the frequency spectrum fluctuation of the audio frame is greater than the speech threshold, the audio is classified as a speech frame. In another embodiment, if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and a classification result of a historical frame is a music frame and the frequency spectrum fluctuation of the current audio frame is greater than a second value, the frequency spectrum fluctuation of the current audio frame is modified into the second value, where the second value is greater than the first value.

[0102] If flux of the current audio frame is buffered, and the previous audio frame is an inactive frame ($vad_flag = 0$), except the current audio frame flux newly buffered in the flux historical buffer, the remaining data in the flux historical buffer is all reset to -1 (equivalent to that the data is invalidated).

[0103] If flux is buffered in the flux historical buffer, and three consecutive frames before the current audio frame are not all active frames ($vad_flag = 1$), the current audio frame flux just buffered in the flux historical buffer is modified into 16; that is, it is checked whether the following conditions are satisfied:

$$\begin{cases} vad_flag_{-1} = 1 \\ vad_flag_{-2} = 1 \\ vad_flag_{-3} = 1 \end{cases},$$

if the conditions are not satisfied, the current audio frame flux just buffered in the flux historical buffer is modified into 16; and

if the three consecutive frames before the current audio frame are all active frames ($vad_flag = 1$), it is checked whether the following conditions are satisfied:

$$\begin{cases} mode_mov > 0.9 \\ flux > 20 \end{cases};$$

if the conditions are satisfied, the current audio frame flux just buffered in the flux historical buffer is modified into 20; otherwise no operation is performed,

where mode_mov denotes a long-time moving average of historical final classification results in signal classification; mode_mov > 0.9 denotes that the signal is in a music signal, and flux is limited according to the historical classification result of the audio signal, to reduce a probability that a speech characteristic occurs in flux and improve stability of determining classification.

[0104] When the three consecutive historical frames before the current audio frame are all inactive frames, and the current audio frame is an active frame, or when the three consecutive frames before the current audio frame are not all active frames, and the current audio frame is an active frame, classification is in an initialization phase. In an embodiment, to make the classification result prone to speech (music), the frequency spectrum fluctuation of the current audio frame may be modified into a speech (music) threshold or a value close to the speech (music) threshold. In another embodiment, if a signal before a current signal is a speech (music) signal, the frequency spectrum fluctuation of the current audio frame may be modified into a speech (music) threshold or a value close to the speech (music) threshold, to improve stability of determining classification. In another embodiment, to make the classification result prone to music, the frequency spectrum fluctuation may be limited, that is, the frequency spectrum fluctuation of the current audio frame may be modified, so that the frequency spectrum fluctuation is not greater than a threshold, to reduce a probability of determining that the frequency spectrum fluctuation is a speech characteristic.

[0105] The percussive sound flag percus_flag denotes whether a percussive sound exists in an audio frame. That percus_flag is set to 1 denotes that a percussive sound is detected, and that percus_flag is set to 0 denotes that no percussive sound is detected.

[0106] When a relatively acute energy protrusion occurs in the current signal (that is, several latest signal frames including the current audio frame and several historical frames of the current audio frame) in both a short time and a long time, and the current signal has no obvious voiced sound characteristic, if the several historical frames before the current audio frame are mainly music frames, it is considered that the current signal is a piece of percussive music; otherwise, further, if none of subframes of the current signal has an obvious voiced sound characteristic and a relatively obvious increase also occurs in the time domain envelope of the current signal relative to a long-time average of the time domain envelope, it is also considered that the current signal is a piece of percussive music.

[0107] The percussive sound flag *percus_flag* is obtained by performing the following step:

[0108] Logarithmic frame energy *etot* of an input audio frame is first obtained, where the logarithmic frame energy *etot* is denoted by logarithmic total subband energy of the input audio frame:

$$5 \quad etot = 10 \log \left(\sum_{j=0}^{19} \left[\frac{1}{hb(i) - lb(i) + 1} \cdot \sum_{i=lb(j)}^{hb(j)} C(i) \right] \right),$$

where *hb(j)* and *lb(j)* denote a high frequency boundary and a low frequency boundary of the j^{th} subband in a frequency spectrum of the input frame respectively, and *C(i)* denotes the frequency spectrum of the input audio frame.

[0109] When the following conditions are satisfied, *percus_flag* is set to 1; otherwise
10 *percus_flag* is set to 0:

$$\left\{ \begin{array}{l} etot_{-2} - etot_{-3} > 6 \\ etot_{-2} - etot_{-1} > 0 \\ etot_{-2} - etot > 3 \\ etot_{-1} - etot > 0 \\ etot_{-2} - lp_speech > 3 \\ 0.5 \cdot voicing_{-1}(1) + 0.25 \cdot voicing(0) + 0.25 \cdot voicing(1) < 0.75 \\ mode_mov > 0.9 \end{array} \right. ,$$

or

$$\left\{ \begin{array}{l} etot_{-2} - etot_{-3} > 6 \\ etot_{-2} - etot_{-1} > 0 \\ etot_{-2} - etot > 3 \\ etot_{-1} - etot > 0 \\ etot_{-2} - lp_speech > 3 \\ 0.5 \cdot voicing_{-1}(1) + 0.25 \cdot voicing(0) + 0.25 \cdot voicing(1) < 0.75 \\ voicing_{-1}(0) < 0.8 \\ voicing_{-1}(1) < 0.8 \\ voicing(0) < 0.8 \\ log_max_spl_{-2} - mov_log_max_spl_{-2} > 10 \end{array} \right. ,$$

15 where *etot* denotes logarithmic frame energy of the current audio frame; *lp_speech* denotes a long-time moving average of the logarithmic frame energy *etot*; *voicing(0)*, *voicing₋₁(0)*, and *voicing₋₁(1)* denote normalized open-loop pitch correlation degrees of a first subframe of a current input audio frame and first and second subframes of a first historical frame respectively, and a voicing parameter *voicing* is obtained by means of linear prediction and analysis, represents a time domain correlation degree between the current audio frame and a signal before a pitch period,

and has a value between 0 and 1; mode_mov denotes a long-time moving average of historical final classification results in signal classification; log_max_spl₂ and mov_log_max_spl₂ denote a time domain maximum logarithmic sampling point amplitude of a second historical frame and a long-time moving average of the time domain maximum logarithmic sampling point amplitude respectively. lp_speech is updated in each active voice frame (that is, a frame whose vad_flag = 1), and a method for updating lp_speech is:

$$lp_speech = 0.99 \cdot lp_speech_{-1} + 0.01 \cdot etot$$

[0110] The meaning of the foregoing two formulas is: when a relatively acute energy protrusion occurs in the current signal (that is, several latest signal frames including the current audio frame and several historical frames of the current audio frame) in both a short time and a long time, and the current signal has no obvious voiced sound characteristic, if the several historical frames before the current audio frame are mainly music frames, it is considered that the current signal is a piece of percussive music; otherwise, further, if none of subframes of the current signal has an obvious voiced sound characteristic and a relatively obvious increase also occurs in the time domain envelope of the current signal relative to a long-time average thereof, it is also considered that the current signal is a piece of percussive music.

[0111] The voicing parameter voicing, that is, a normalized open-loop pitch correlation degree, denotes a time domain correlation degree between the current audio frame and a signal before a pitch period, may be obtained by means of ACELP open-loop pitch search, and has a value between 0 and 1. This belongs to the prior art and is therefore not described in detail in the present invention. In this embodiment, a voicing is calculated for each of two subframes of the current audio frame, and the voicings are averaged to obtain a voicing parameter of the current audio frame. The voicing parameter of the current audio frame is also buffered in a voicing historical buffer, and in this embodiment, the length of the voicing historical buffer is 10.

[0112] mode_mov is updated in each active voice frame and when more than 30 consecutive active voice frames have occurred before the frame, and an updating method is:

$$mode_mov = 0.95 \cdot mode_mov_{-1} + 0.05 \cdot mode$$

where mode is a classification result of a current input audio frame, and has a binary value, where "0" denotes a speech category, and "1" denotes a music category.

[0113] S103: Classify the current audio frame as a speech frame or a music frame according to statistics of a part or all of data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory. When statistics of effective data of the frequency spectrum fluctuations satisfy a speech classification condition, the current audio frame is classified as a speech frame; when the statistics of the effective data of the frequency spectrum fluctuations satisfy

a music classification condition, the current audio frame is classified as a music frame.

[0114] The statistics herein is a value obtained by performing a statistical operation on a valid frequency spectrum fluctuation (that is, effective data) stored in the frequency spectrum fluctuation memory,. For example, the statistical operation may be an operation for obtaining average value or a variance. Statistics in the following embodiments have similar meaning.

[0115] In an embodiment, step S103 includes:

obtaining an average value of a part or all of the effective data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory; and

when the obtained average value of the effective data of the frequency spectrum fluctuations satisfies a music classification condition, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame.

[0116] For example, when the obtained average value of the effective data of the frequency spectrum fluctuations is less than a music classification threshold, the current audio frame is classified as a music frame; otherwise the current audio frame is classified as a speech frame.

[0117] Generally, a frequency spectrum fluctuation value of a music frame is relatively small, while a frequency spectrum fluctuation value of a speech frame is relatively large. Therefore, the current audio frame may be classified according to the frequency spectrum fluctuations. Certainly, signal classification may also be performed on the current audio frame by using another classification method. For example, a quantity of pieces of effective data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory is counted; the frequency spectrum fluctuation memory is divided, according to the quantity of the pieces of effective data, into at least two intervals of different lengths from a near end to a remote end, and an average value of effective data of frequency spectrum fluctuations corresponding to each interval is obtained, where a start point of the intervals is a storage location of the frequency spectrum fluctuation of the current frame, the near end is an end at which the frequency spectrum fluctuation of the current frame is stored, and the remote end is an end at which a frequency spectrum fluctuation of a historical frame is stored; the audio frame is classified according to statistics of frequency spectrum fluctuations in a relatively short interval, and if the statistics of the parameters in this interval are sufficient to distinguish a type of the audio frame, the classification process ends; otherwise the classification process is continued in the shortest interval of the remaining relatively long intervals, and the rest can be deduced by analogy. In a classification process of each interval, the current audio frame is classified according to a classification threshold corresponding to each interval, the current audio frame is classified as a speech frame or a music frame, and when the statistics of the effective data of the frequency spectrum fluctuations satisfy the speech classification condition, the

current audio frame is classified as a speech frame; when the statistics of the effective data of the frequency spectrum fluctuations satisfy the music classification condition, the current audio frame is classified as a music frame.

[0118] After signal classification, different signals may be encoded in different encoding modes.

5 For example, a speech signal is encoded by using an encoder based on a speech generating model (such as CELP), and a music signal is encoded by using an encoder based on conversion (such as an encoder based on MDCT).

[0119] In the foregoing embodiment, because an audio signal is classified according to long-time statistics of frequency spectrum fluctuations, there are relatively few parameters, a recognition rate is relatively high, and complexity is relatively low. In addition, the frequency spectrum fluctuations are adjusted with consideration of factors such as voice activity and
10 percussive music; therefore, the present invention has a higher recognition rate for a music signal, and is suitable for hybrid audio signal classification.

[0120] Referring to FIG. 4, in another embodiment, after step S102, the method further
15 includes:

[0121] S104: Obtain a frequency spectrum high-frequency-band peakiness, a frequency spectrum correlation degree, and a linear prediction residual energy tilt of the current audio frame, and store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt in memories, where the frequency spectrum high-frequency-band peakiness denotes a peakiness or an energy acutance, on a high
20 frequency band, of a frequency spectrum of the current audio frame; the frequency spectrum correlation degree denotes stability, between adjacent frames, of a signal harmonic structure; and the linear prediction residual energy tilt denotes the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the input audio signal changes as a linear
25 prediction order increases.

[0122] Optionally, before these parameters are stored, the method further includes: determining, according to the voice activity of the current audio frame, whether to store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt in the memories; and if the current audio frame is an active frame, storing the
30 parameters; otherwise skipping storing the parameters.

[0123] The frequency spectrum high-frequency-band peakiness denotes a peakiness or an energy acutance, on a high frequency band, of a frequency spectrum of the current audio frame. In an embodiment, the frequency spectrum high-frequency-band peakiness ph is calculated by using the following formula:

$$ph = \sum_{i=64}^{126} p2v_map(i),$$

where $p2v_map(i)$ denotes a peakiness of the i^{th} frequency bin of a frequency spectrum, and the peakiness $p2v_map(i)$ is obtained by using the following formula:

$$p2v_map(i) = \begin{cases} 20\log(peak(i)) - 10\log(vl(i)) - 10\log(vr(i)) & peak(i) \neq 0 \\ 0 & peak(i) = 0 \end{cases},$$

5 where $peak(i) = C(i)$ if the i^{th} frequency bin is a local peak value of the frequency spectrum; otherwise $peak(i) = 0$; and $vl(i)$ and $vr(i)$ denote local frequency spectrum valley values $v(n)$ that are most adjacent to the i^{th} frequency bin on a high-frequency side and a low-frequency side of the i^{th} frequency bin respectively, where

$$peak(i) = \begin{cases} C(i) & C(i) > C(i-1), C(i) > C(i+1) \\ 0 & else \end{cases}, \text{ and}$$

$$10 \quad v = \forall C(i) \quad C(i) < C(i-1), C(i) < C(i+1).$$

[0124] The frequency spectrum high-frequency-band peakiness ph of the current audio frame is also buffered in a ph historical buffer, and in this embodiment, the length of the ph historical buffer is 60.

[0125] The frequency spectrum correlation degree cor_map_sum denotes stability, between 15 adjacent frames, of a signal harmonic structure, and is obtained by performing the following steps:

[0126] First, a floor-removed frequency spectrum $C'(i)$ of an input audio frame $C(i)$ is obtained, where

$$C'(i) = C(i) - floor(i),$$

20 where $floor(i)$ denotes a spectrum floor of a frequency spectrum of the input audio frame, where $i = 0, 1, \dots, 127$; and

$$floor(i) = \begin{cases} C(i) & C(i) \in v \\ vl(i) + (i - idx[vl(i)]) \cdot \frac{vr(i) - vl(i)}{idx[vr(i)] - idx[vl(i)]} & else \end{cases},$$

where $idx[x]$ denotes a location of x on the frequency spectrum, where $idx[x] = 0, 1, \dots, 127$.

[0127] Then, between every two adjacent frequency spectrum valley values, a correlation $cor(n)$ 25 between the floor-removed frequency spectrum of the input audio frame and a floor-removed frequency spectrum of a previous frame is obtained, where

$$cor(n) = \frac{\left(\sum_{i=lb(n)}^{hb(n)} C'(i) \cdot C'_{-1}(i) \right)^2}{\left(\sum_{i=lb(n)}^{hb(n)} C'(i) \cdot C'(i) \right) \cdot \left(\sum_{i=lb(n)}^{hb(n)} C'_{-1}(i) \cdot C'_{-1}(i) \right)},$$

where $lb(n)$ and $hb(n)$ respectively denote endpoint locations of the n^{th} frequency spectrum valley value interval (that is, an area located between two adjacent valley values), that is, locations limiting two frequency spectrum valley values of the valley value interval.

5 **[0128]** Finally, the frequency spectrum correlation degree cor_map_sum of the input audio frame is calculated by using the following formula:

$$cor_map_sum = \sum_{i=0}^{127} cor(inv[lb(n) \leq i, hb(n) \geq i]),$$

where $inv[f]$ denotes an inverse function of a function f .

[0129] The linear prediction residual energy tilt $epsP_tilt$ denotes an extent to which linear prediction residual energy of the input audio signal changes as a linear prediction order increases, and may be calculated and obtained by using the following formula:

$$epsP_tilt = \frac{\sum_{i=1}^n epsP(i) \cdot epsP(i+1)}{\sum_{i=1}^n epsP(i) \cdot epsP(i)},$$

where $epsP(i)$ denotes prediction residual energy of i^{th} -order linear prediction; and n is a positive integer, denotes a linear prediction order, and is less than or equal to a maximum linear prediction order. For example, in an embodiment, $n = 15$.

[0130] Therefore, step S103 may be replaced with the following step:

[0131] S105: Obtain statistics of effective data of the stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of stored linear prediction residual energy tilts, and classify the audio frame as a speech frame or a music frame according to the statistics of the effective data, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on the effective data stored in the memories, where the calculation operation may include an operation for obtaining an average value, an operation for obtaining a variance, or the like.

25 **[0132]** In an embodiment, this step includes:

obtaining an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum

high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

when one of the following conditions is satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0133] Generally, a frequency spectrum fluctuation value of a music frame is relatively small, while a frequency spectrum fluctuation value of a speech frame is relatively large; a frequency spectrum high-frequency-band peakiness value of a music frame is relatively large, and a frequency spectrum high-frequency-band peakiness of a speech frame is relatively small; a frequency spectrum correlation degree value of a music frame is relatively large, and a frequency spectrum correlation degree value of a speech frame is relatively small; a change in a linear prediction residual energy tilt of a music frame is relatively small, and a change in a linear prediction residual energy tilt of a speech frame is relatively large. Therefore, the current audio frame may be classified according to the statistics of the foregoing parameters. Certainly, signal classification may also be performed on the current audio frame by using another classification method. For example, a quantity of pieces of effective data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory is counted; the memory is divided, according to the quantity of the pieces of effective data, into at least two intervals of different lengths from a near end to a remote end, an average value of effective data of frequency spectrum fluctuations corresponding to each interval, an average value of effective data of frequency spectrum high-frequency-band peakiness, an average value of effective data of frequency spectrum correlation degrees, and a variance of effective data of linear prediction residual energy tilts are obtained, where a start point of the intervals is a storage location of the frequency spectrum fluctuation of the current frame, the near end is an end at which the frequency spectrum fluctuation of the current frame is stored, and the remote end is an end at which a frequency spectrum fluctuation of a historical frame is stored; the audio frame is classified according to statistics of effective data of the foregoing parameters in a relatively short interval, and if the statistics of the parameters in this interval are sufficient to distinguish the type of the audio frame, the classification process ends; otherwise the classification process is continued in the shortest interval of the remaining relatively long intervals, and the rest

can be deduced by analogy. In a classification process of each interval, the current audio frame is classified according to a classification threshold corresponding to each interval, and when one of the following conditions is satisfied, the current audio frame is classified as a music frame; otherwise the current audio frame is classified as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0134] After signal classification, different signals may be encoded in different encoding modes. For example, a speech signal is encoded by using an encoder based on a speech generating model (such as CELP), and a music signal is encoded by using an encoder based on conversion (such as an encoder based on MDCT).

[0135] In the foregoing embodiment, an audio signal is classified according to long-time statistics of frequency spectrum fluctuations, frequency spectrum high-frequency-band peakiness, frequency spectrum correlation degrees, and linear prediction residual energy tilts; therefore, there are relatively few parameters, a recognition rate is relatively high, and complexity is relatively low. In addition, the frequency spectrum fluctuations are adjusted with consideration of factors such as voice activity and percussive music, and the frequency spectrum fluctuations are modified according to a signal environment in which the current audio frame is located; therefore, the present invention improves a classification recognition rate, and is suitable for hybrid audio signal classification.

[0136] Referring to FIG. 5, another embodiment of an audio signal classification method includes:

[0137] S501: Perform frame division processing on an input audio signal.

[0138] Audio signal classification is generally performed on a per frame basis, and a parameter is extracted from each audio signal frame to perform classification, to determine whether the audio signal frame belongs to a speech frame or a music frame, and perform encoding in a corresponding encoding mode.

[0139] S502: Obtain a linear prediction residual energy tilt of a current audio frame, where the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases.

[0140] In an embodiment, the linear prediction residual energy tilt epsP_tilt may be calculated and obtained by using the following formula:

$$epsP_tilt = \frac{\sum_{i=1}^n epsP(i) \cdot epsP(i+1)}{\sum_{i=1}^n epsP(i) \cdot epsP(i)},$$

where $epsP(i)$ denotes prediction residual energy of i^{th} -order linear prediction; and n is a positive integer, denotes a linear prediction order, and is less than or equal to a maximum linear prediction order. For example, in an embodiment, $n = 15$.

5 **[0141]** S503: Store the linear prediction residual energy tilt in a memory.

[0142] The linear prediction residual energy tilt may be stored in the memory. In an embodiment, the memory may be an FIFO buffer, and the length of the buffer is 60 storage units (that is, 60 linear prediction residual energy tilts can be stored).

10 **[0143]** Optionally, before the storing the linear prediction residual energy tilt, the method further includes: determining, according to voice activity of the current audio frame, whether to store the linear prediction residual energy tilt in the memory; and if the current audio frame is an active frame, storing the linear prediction residual energy tilt; otherwise skipping storing the linear prediction residual energy tilt.

15 **[0144]** S504: Classify the audio frame according to statistics of a part of data of prediction residual energy tilts in the memory.

[0145] In an embodiment, the statistics of the part of the data of the prediction residual energy tilts is a variance of the part of the data of the prediction residual energy tilts, and therefore step S504 includes:

20 comparing the variance of the part of the data of the prediction residual energy tilts with a music classification threshold, and when the variance of the part of the data of the prediction residual energy tilts is less than the music classification threshold, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame.

25 **[0146]** Generally, a change in a linear prediction residual energy tilt value of a music frame is relatively small, and a change in a linear prediction residual energy tilt value of a speech frame is relatively large. Therefore, the current audio frame may be classified according to statistics of the linear prediction residual energy tilts. Certainly, signal classification may also be performed on the current audio frame with reference to another parameter by using another classification method.

30 **[0147]** In another embodiment, before step S504, the method further includes: obtaining a frequency spectrum fluctuation, a frequency spectrum high-frequency-band peakiness, and a frequency spectrum correlation degree of the current audio frame, and storing the frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, and the frequency spectrum correlation degree in corresponding memories. Therefore, step S504 is specifically:

obtaining statistics of effective data of stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of the stored linear prediction residual energy tilts, and classifying the audio frame as a speech frame or a music frame according to the statistics of the effective data, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on the effective data stored in the memories.

[0148] Further, the obtaining statistics of effective data of stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of the stored linear prediction residual energy tilts, and classifying the audio frame as a speech frame or a music frame according to the statistics of the effective data includes:

obtaining an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

when one of the following conditions is satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0149] Generally, a frequency spectrum fluctuation value of a music frame is relatively small, while a frequency spectrum fluctuation value of a speech frame is relatively large; a frequency spectrum high-frequency-band peakiness value of a music frame is relatively large, and a frequency spectrum high-frequency-band peakiness of a speech frame is relatively small; a frequency spectrum correlation degree value of a music frame is relatively large, and a frequency spectrum correlation degree value of a speech frame is relatively small; a change in a linear prediction residual energy tilt value of a music frame is relatively small, and a change in a linear prediction residual energy tilt value of a speech frame is relatively large. Therefore, the current audio frame may be classified according to the statistics of the foregoing parameters.

[0150] In another embodiment, before step S504, the method further includes: obtaining a

frequency spectrum tone quantity of the current audio frame and a ratio of the frequency spectrum tone quantity on a low frequency band, and storing the frequency spectrum tone quantity and the ratio of the frequency spectrum tone quantity on the low frequency band in corresponding memories. Therefore, step S504 is specifically:

5 obtaining statistics of the stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately; and

 classifying the audio frame as a speech frame or a music frame according to the statistics of the linear prediction residual energy tilts, the statistics of the frequency spectrum tone quantities, and the ratio of the frequency spectrum tone quantity on the low frequency band, where the
10 statistics refer to a data value obtained after a calculation operation is performed on data stored in the memories.

[0151] Further, the obtaining statistics of the stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately includes: obtaining a variance of the stored linear prediction residual energy tilts; and obtaining an average value of the stored
15 frequency spectrum tone quantities. The classifying the audio frame as a speech frame or a music frame according to the statistics of the linear prediction residual energy tilts, the statistics of the frequency spectrum tone quantities, and the ratio of the frequency spectrum tone quantity on the low frequency band includes:

 when the current audio frame is an active frame, and one of the following conditions is
20 satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame:

 the variance of the linear prediction residual energy tilts is less than a fifth threshold; or
 the average value of the frequency spectrum tone quantities is greater than a sixth
threshold; or

25 the ratio of the frequency spectrum tone quantity on the low frequency band is less than a seventh threshold.

[0152] The obtaining a frequency spectrum tone quantity of the current audio frame and a ratio of the frequency spectrum tone quantity on a low frequency band includes:

 counting a quantity of frequency bins of the current audio frame that are on a frequency
30 band from 0 to 8 kHz and have frequency bin peak values greater than a predetermined value, to use the quantity as the frequency spectrum tone quantity; and

 calculating a ratio of a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 4 kHz and have frequency bin peak values greater than the predetermined value to the quantity of the frequency bins of the current audio frame that are on the frequency band

from 0 to 8 kHz and have frequency bin peak values greater than the predetermined value, to use the ratio as the ratio of the frequency spectrum tone quantity on the low frequency band. In an embodiment, the predetermined value is 50.

[0153] The frequency spectrum tone quantity N_{tonal} denotes a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 8 kHz and have frequency bin peak values greater than a predetermined value. In an embodiment, the quantity may be obtained in the following manner: counting a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 8 kHz and have peak values $p2v_map(i)$ greater than 50, that is, N_{tonal} , where $p2v_map(i)$ denotes a peakiness of the i^{th} frequency bin of the frequency spectrum, and for a calculating manner of $p2v_map(i)$, refer to description of the foregoing embodiment.

[0154] The ratio $ratio_N_{\text{tonal_lf}}$ of the frequency spectrum tone quantity on the low frequency band denotes a ratio of a low-frequency-band tone quantity to the frequency spectrum tone quantity. In an embodiment, the ratio may be obtained in the following manner: counting a quantity $N_{\text{tonal_lf}}$ of the current audio frame that is on a frequency band from 0 to 4 kHz and has $p2v_map(i)$ greater than 50. $ratio_N_{\text{tonal_lf}}$ is a ratio of $N_{\text{tonal_lf}}$ to N_{tonal} , that is, $N_{\text{tonal_lf}}/N_{\text{tonal}}$. $p2v_map(i)$ denotes a peakiness of the i^{th} frequency bin of the frequency spectrum, and for a calculating manner of $p2v_map(i)$, refer to description of the foregoing embodiment. In another embodiment, an average of multiple stored N_{tonal} values and an average of multiple stored $N_{\text{tonal_lf}}$ values are separately obtained, and a ratio of the average of the $N_{\text{tonal_lf}}$ values to the average of the N_{tonal} values is calculated to be used as the ratio of the frequency spectrum tone quantity on the low frequency band.

[0155] In this embodiment, an audio signal is classified according to long-time statistics of linear prediction residual energy tilts. In addition, both classification robustness and a classification recognition speed are taken into account; therefore, there are relatively few classification parameters, but a result is relatively accurate, complexity is low, and memory overheads are low.

[0156] Referring to FIG. 6, another embodiment of an audio signal classification method includes:

[0157] S601: Perform frame division processing on an input audio signal.

[0158] S602: Obtain a frequency spectrum fluctuation, a frequency spectrum high-frequency-band peakiness, a frequency spectrum correlation degree, and a linear prediction residual energy tilt of a current audio frame.

[0159] The frequency spectrum fluctuation flux denotes a short-time or long-time energy fluctuation of a frequency spectrum of a signal, and is an average value of absolute values of logarithmic energy differences between corresponding frequencies of a current audio frame and a

historical frame on a low and mid-band spectrum, where the historical frame refers to any frame before the current audio frame. The frequency spectrum high-frequency-band peakiness ph denotes a peakiness or an energy acutance, on a high frequency band, of a frequency spectrum of the current audio frame. The frequency spectrum correlation degree cor_map_sum denotes stability, between
5 adjacent frames, of a signal harmonic structure. The linear prediction residual energy tilt $epsP_tilt$ denotes an extent to which linear prediction residual energy of the input audio signal changes as a linear prediction order increases. For a specific method for calculating these parameters, refer to the foregoing embodiment.

[0160] Further, a voicing parameter may be obtained; and the voicing parameter voicing
10 denotes a time domain correlation degree between the current audio frame and a signal before a pitch period. The voicing parameter voicing is obtained by means of linear prediction and analysis, represents a time domain correlation degree between the current audio frame and a signal before a pitch period, and has a value between 0 and 1. This belongs to the prior art, and is therefore not described in detail in the present invention. In this embodiment, a voicing is calculated for each of
15 two subframes of the current audio frame, and the voicings are averaged to obtain a voicing parameter of the current audio frame. The voicing parameter of the current audio frame is also buffered in a voicing historical buffer, and in this embodiment, the length of the voicing historical buffer is 10.

[0161] S603: Store the frequency spectrum fluctuation, the frequency spectrum
20 high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt in corresponding memories.

[0162] Optionally, before these parameters are stored, the method further includes:

[0163] In an embodiment, it is determined according to the voice activity of the current audio
frame whether to store the frequency spectrum fluctuation in the frequency spectrum fluctuation
25 memory. If the current audio frame is an active frame, the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory.

[0164] In another embodiment, it is determined, according to the voice activity of the audio
frame and whether the audio frame is an energy attack, whether to store the frequency spectrum
fluctuation in the memory. If the current audio frame is an active frame, and the current audio frame
30 does not belong to an energy attack, the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory. In another embodiment, if the current audio frame is an active frame, and none of multiple consecutive frames including the current audio frame and a historical frame of the current audio frame belongs to an energy attack, the frequency spectrum fluctuation of the audio frame is stored in the frequency spectrum fluctuation memory;

otherwise the frequency spectrum fluctuation is not stored. For example, if the current audio frame is an active frame, and neither a previous frame of the current audio frame nor a second historical frame of the current audio frame belongs to an energy attack, the frequency spectrum fluctuation of the audio frame is stored in the frequency spectrum fluctuation memory; otherwise the frequency spectrum fluctuation is not stored.

[0165] For definitions and obtaining manners of the voice activity flag `vad_flag` and the voice attack flag `attack_flag`, refer to description of the foregoing embodiment.

[0166] Optionally, before these parameters are stored, the method further includes:

determining, according to the voice activity of the current audio frame, whether to store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt in the memories; and if the current audio frame is an active frame, storing the parameters; otherwise skipping storing the parameters.

[0167] S604: Obtain statistics of effective data of stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of stored linear prediction residual energy tilts, and classify the audio frame as a speech frame or a music frame according to the statistics of the effective data, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on the effective data stored in the memories, where the calculation operation may include an operation for obtaining an average value, an operation for obtaining a variance, or the like.

[0168] Optionally, before step S604, the method may further include:

updating, according to whether the current audio frame is percussive music, the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory. In an embodiment, if the current audio frame is percussive music, valid frequency spectrum fluctuation values in the frequency spectrum fluctuation memory are modified into a value less than or equal to a music threshold, where when a frequency spectrum fluctuation of an audio frame is less than the music threshold, the audio is classified as a music frame. In an embodiment, if the current audio frame is percussive music, valid frequency spectrum fluctuation values in the frequency spectrum fluctuation memory are reset to 5.

[0169] Optionally, before step S604, the method may further include:

updating the frequency spectrum fluctuations in the memory according to activity of a historical frame of the current audio frame. In an embodiment, if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and a previous audio frame is an inactive frame, data of other frequency spectrum

fluctuations stored in the frequency spectrum fluctuation memory except the frequency spectrum fluctuation of the current audio frame is modified into in effective data. In another embodiment, if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and three consecutive frames before the current audio frame are not all active frames, the frequency spectrum fluctuation of the current audio frame is modified into a first value. The first value may be a speech threshold, where when the frequency spectrum fluctuation of the audio frame is greater than the speech threshold, the audio is classified as a speech frame. In another embodiment, if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and a classification result of a historical frame is a music frame and the frequency spectrum fluctuation of the current audio frame is greater than a second value, the frequency spectrum fluctuation of the current audio frame is modified into the second value, where the second value is greater than the first value.

[0170] For example, if a previous frame of the current audio frame is an inactive frame ($\text{vad_flag} = 0$), except the current audio frame flux newly buffered in the flux historical buffer, the remaining data in the flux historical buffer is all reset to -1 (equivalent to that the data is invalidated). If three consecutive frames before the current audio frame are not all active frames ($\text{vad_flag} = 1$), the current audio frame flux just buffered in the flux historical buffer is modified into 16. If the three consecutive frames before the current audio frame are all active frames ($\text{vad_flag} = 1$), a long-time smooth result of a historical signal classification result is a music signal and the current audio frame flux is greater than 20, the frequency spectrum fluctuation of the buffered current audio frame is modified into 20. For calculation of the active frame and the long-time smooth result of the historical signal classification result, refer to the foregoing embodiment.

[0171] In an embodiment, step S604 includes:

obtaining an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

when one of the following conditions is satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is

greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0172] Generally, a frequency spectrum fluctuation value of a music frame is relatively small,

5 while a frequency spectrum fluctuation value of a speech frame is relatively large; a frequency spectrum high-frequency-band peakiness value of a music frame is relatively large, and a frequency spectrum high-frequency-band peakiness of a speech frame is relatively small; a frequency spectrum correlation degree value of a music frame is relatively large, and a frequency spectrum correlation degree value of a speech frame is relatively small; a linear prediction residual energy tilt
10 value of a music frame is relatively small, and a linear prediction residual energy tilt value of a speech frame is relatively large. Therefore, the current audio frame may be classified according to the statistics of the foregoing parameters. Certainly, signal classification may also be performed on the current audio frame by using another classification method. For example, a quantity of pieces of effective data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation
15 memory is counted; the memory is divided, according to the quantity of the pieces of effective data, into at least two intervals of different lengths from a near end to a remote end, an average value of effective data of frequency spectrum fluctuations corresponding to each interval, an average value of effective data of frequency spectrum high-frequency-band peakiness, an average value of effective data of frequency spectrum correlation degrees, and a variance of effective data of linear
20 prediction residual energy tilts are obtained, where a start point of the intervals is a storage location of the frequency spectrum fluctuation of the current frame, the near end is an end at which the frequency spectrum fluctuation of the current frame is stored, and the remote end is an end at which a frequency spectrum fluctuation of a historical frame is stored; the audio frame is classified according to statistics of the effective data of the foregoing parameters in a relatively short interval,
25 and if parameter statistics in this interval are sufficient to distinguish a type of the audio frame, the classification process ends; otherwise the classification process is continued in the shortest interval of the remaining relatively long intervals, and the rest can be deduced by analogy. In a classification process of each interval, the current audio frame is classified according to a classification threshold corresponding to each interval, and when one of the following conditions is satisfied, the current
30 audio frame is classified as a music frame; otherwise the current audio frame is classified as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the

variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0173] After signal classification, different signals may be encoded in different encoding modes. For example, a speech signal is encoded by using an encoder based on a speech generating model (such as CELP), and a music signal is encoded by using an encoder based on conversion (such as an encoder based on MDCT).

[0174] In this embodiment, classification is performed according to long-time statistics of frequency spectrum fluctuations, frequency spectrum high-frequency-band peakiness, frequency spectrum correlation degrees, and linear prediction residual energy tilts. In addition, both classification robustness and a classification recognition speed are taken into account; therefore, there are relatively few classification parameters, but a result is relatively accurate, a recognition rate is relatively high, and complexity is relatively low.

[0175] In an embodiment, after the frequency spectrum fluctuation flux, the frequency spectrum high-frequency-band peakiness ph , the frequency spectrum correlation degree cor_map_sum , and the linear prediction residual energy tilt $epsP_tilt$ are stored in the corresponding memories, classification may be performed according to a quantity of pieces of effective data of the stored frequency spectrum fluctuations by using different determining processes. If the voice activity flag is set to 1, that is, the current audio frame is an active voice frame, the quantity N of the pieces of effective data of the stored frequency spectrum fluctuations is checked.

[0176] If a value of the quantity N of the pieces of effective data of the frequency spectrum fluctuations stored in the memory changes, a determining process also changes.

[0177] (1) Referring to FIG. 7, if $N = 60$, an average value of all data in the flux historical buffer is obtained and marked as $flux60$, an average value of 30 pieces of data at a near end is obtained and marked as $flux30$, and an average value of 10 pieces of data at the near end is obtained and marked as $flux10$. An average value of all data in the ph historical buffer is obtained and marked as $ph60$, an average value of 30 pieces of data at a near end is obtained and marked as $ph30$, and an average value of 10 pieces of data at the near end is obtained and marked as $ph10$. An average value of all data in the cor_map_sum historical buffer is obtained and marked as cor_map_sum60 , an average value of 30 pieces of data at a near end is obtained and marked as cor_map_sum30 , and an average value of 10 pieces of data at the near end is obtained and marked as cor_map_sum10 . In addition, a variance of all data in the $epsP_tilt$ historical buffer is obtained and marked as $epsP_tilt60$, a variance of 30 pieces of data at a near end is obtained and marked as $epsP_tilt30$, and a variance of 10 pieces of data at the near end is obtained and marked as $epsP_tilt10$. A quantity $voicing_cnt$ of pieces of data whose value is greater than 0.9 in the voicing historical buffer is

obtained. The near end is an end at which the foregoing parameters corresponding to the current audio frame are stored.

[0178] First, it is checked whether flux10, ph10, epsP_tilt10, cor_map_sum10, and voicing_cnt satisfy the following conditions: $\text{flux10} < 10$ or $\text{epsPtilt10} < 0.0001$ or $\text{ph10} > 1050$ or $\text{cor_map_sum10} > 95$, and $\text{voicing_cnt} < 6$. If the conditions are satisfied, the current audio frame is classified as a music type (that is, Mode = 1). Otherwise, it is checked whether flux10 is greater than 15 and whether voicing_cnt is greater than 2, or whether flux10 is greater than 16. If the conditions are satisfied, the current audio frame is classified as a speech type (that is, Mode = 0). Otherwise, it is checked whether flux30, flux10, ph30, epsP_tilt30, cor_map_sum30, and voicing_cnt satisfy the following conditions: $\text{flux30} < 13$ and $\text{flux10} < 15$, or $\text{epsPtilt30} < 0.001$ or $\text{ph30} > 800$ or $\text{cor_map_sum30} > 75$. If the conditions are satisfied, the current audio frame is classified as a music type. Otherwise, it is checked whether flux60, flux30, ph60, epsP_tilt60, and cor_map_sum60 satisfy the following conditions: $\text{flux60} < 14.5$ or $\text{cor_map_sum30} > 75$ or $\text{ph60} > 770$ or $\text{epsP_tilt10} < 0.002$, and $\text{flux30} < 14$. If the conditions are satisfied, the current audio frame is classified as a music type; otherwise the current audio frame is classified as a speech type.

[0179] (2) Referring to FIG. 8, if $N < 60$ and $N \geq 30$, an average value of N pieces of data at a near end in the flux historical buffer, an average value of N pieces of data at a near end in the ph historical buffer, and an average value of N pieces of data at a near end in the cor_map_sum historical buffer are separately obtained and marked as fluxN, phN, and cor_map_sumN. In addition, a variance of N pieces of data at a near end in the epsP_tilt historical buffer is obtained and marked as epsP_tiltN. It is checked whether fluxN, phN, epsP_tiltN, and cor_map_sumN satisfy the following condition: $\text{fluxN} < 13 + (N - 30)/20$ or $\text{cor_map_sumN} > 75 + (N - 30)/6$ or $\text{phN} > 800$ or $\text{epsP_tiltN} < 0.001$. If the condition is satisfied, the current audio frame is classified as a music type; otherwise the current audio frame is classified as a speech type.

[0180] (3) Referring to FIG. 9, if $N < 30$ and $N \geq 10$, an average value of N pieces of data at a near end in the flux historical buffer, an average value of N pieces of data at a near end in the ph historical buffer, and an average value of N pieces of data at a near end in the cor_map_sum historical buffer are separately obtained and marked as fluxN, phN, and cor_map_sumN. In addition, a variance of N pieces of data at a near end in the epsP_tilt historical buffer is obtained and marked as epsP_tiltN.

[0181] First, it is checked whether a long-time moving average mode_mov of a historical classification result is greater than 0.8. If yes, it is checked whether fluxN, phN, epsP_tiltN, and cor_map_sumN satisfy the following condition: $\text{fluxN} < 16 + (N - 10)/20$ or $\text{phN} > 1000 - 12.5 \times (N - 10)$ or $\text{epsP_tiltN} < 0.0005 + 0.000045 \times (N - 10)$ or $\text{cor_map_sumN} > 90 - (N - 10)$.

Otherwise, a quantity voicing_cnt of pieces of data whose value is greater than 0.9 in the voicing historical buffer is obtained, and it is checked whether the following conditions are satisfied: $\text{fluxN} < 12 + (\text{N} - 10)/20$ or $\text{phN} > 1050 - 12.5 \times (\text{N} - 10)$ or $\text{epsP_tiltN} < 0.0001 + 0.000045 \times (\text{N} - 10)$ or $\text{cor_map_sumN} > 95 - (\text{N} - 10)$, and $\text{voicing_cnt} < 6$. If any group of the foregoing two groups of conditions is satisfied, the current audio frame is classified as a music type; otherwise the current audio frame is classified as a speech type.

[0182] (4) Referring to FIG. 10, if $\text{N} < 10$ and $\text{N} > 5$, an average value of N pieces of data at a near end in the ph historical buffer and an average value of N pieces of data at a near end in the cor_map_sum historical buffer are obtained and marked as phN and cor_map_sumN, and a variance of N pieces of data at a near end in the epsP_tilt historical buffer is obtained and marked as epsP_tiltN. In addition, a quantity voicing_cnt6 of pieces of data whose value is greater than 0.9 among six pieces of data at a near end in the voicing historical buffer is obtained.

[0183] It is checked whether the following conditions are satisfied: $\text{epsP_tiltN} < 0.00008$ or $\text{phN} > 1100$ or $\text{cor_map_sumN} > 100$, and $\text{voicing_cnt} < 4$. If the conditions are satisfied, the current audio frame is classified as a music type; otherwise the current audio frame is classified as a speech type.

[0184] (5) If $\text{N} \leq 5$, a classification result of a previous audio frame is used as a classification type of the current audio frame.

[0185] The foregoing embodiment is a specific classification process in which classification is performed according to long-time statistics of frequency spectrum fluctuations, frequency spectrum high-frequency-band peakiness, frequency spectrum correlation degrees, and linear prediction residual energy tilts, and a person skilled in the art can understand that, classification may be performed by using another process. The classification process in this embodiment may be applied to corresponding steps in the foregoing embodiment, to serve as, for example, a specific classification method of step 103 in FIG. 2, step 105 in FIG. 4, or step 604 in FIG. 6.

[0186] Referring to FIG. 11, another embodiment of an audio signal classification method includes:

[0187] S1101: Perform frame division processing on an input audio signal.

[0188] S1102: Obtain a linear prediction residual energy tilt and a frequency spectrum tone quantity of a current audio frame and a ratio of the frequency spectrum tone quantity on a low frequency band.

[0189] The linear prediction residual energy tilt epsP_tilt denotes an extent to which linear prediction residual energy of the input audio signal changes as a linear prediction order increases; the frequency spectrum tone quantity Ntonal denotes a quantity of frequency bins of the current

audio frame that are on a frequency band from 0 to 8 kHz and have frequency bin peak values greater than a predetermined value; the ratio ratio_Ntonal_lf of the frequency spectrum tone quantity on the low frequency band denotes a ratio of a low-frequency-band tone quantity to the frequency spectrum tone quantity. For specific calculation, refer to description of the foregoing embodiment.

[0190] S1103: Store the linear prediction residual energy tilt epsP_tilt, the frequency spectrum tone quantity, and the ratio of the frequency spectrum tone quantity on the low frequency band in corresponding memories.

[0191] The linear prediction residual energy tilt epsP_tilt and the frequency spectrum tone quantity of the current audio frame are buffered in respective historical buffers, and in this embodiment, lengths of the two buffers are also both 60.

[0192] Optionally, before these parameters are stored, the method further includes: determining, according to voice activity of the current audio frame, whether to store the linear prediction residual energy tilt, the frequency spectrum tone quantity, and the ratio of the frequency spectrum tone quantity on the low frequency band in the memories; and storing the linear prediction residual energy tilt in a memory when it is determined that the linear prediction residual energy tilt needs to be stored. If the current audio frame is an active frame, the parameters are stored; otherwise the parameters are not stored.

[0193] S1104: Obtain statistics of stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately, where the statistics refer to a data value obtained after a calculation operation is performed on data stored in the memories, where the calculation operation may include an operation for obtaining an average value, an operation for obtaining a variance, or the like.

[0194] In an embodiment, the obtaining statistics of stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately includes: obtaining a variance of the stored linear prediction residual energy tilts; and obtaining an average value of the stored frequency spectrum tone quantities.

[0195] S1105: Classify the audio frame as a speech frame or a music frame according to the statistics of the linear prediction residual energy tilts, the statistics of the frequency spectrum tone quantities, and the ratio of the frequency spectrum tone quantity on the low frequency band.

[0196] In an embodiment, this step includes:

when the current audio frame is an active frame, and one of the following conditions is satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame:

the variance of the linear prediction residual energy tilts is less than a fifth threshold; or
the average value of the frequency spectrum tone quantities is greater than a sixth
threshold; or

the ratio of the frequency spectrum tone quantity on the low frequency band is less than
a seventh threshold.

[0197] Generally, a linear prediction residual energy tilt value of a music frame is relatively small, and a linear prediction residual energy tilt value of a speech frame is relatively large; a frequency spectrum tone quantity of a music frame is relatively large, and a frequency spectrum tone quantity of a speech frame is relatively small; a ratio of a frequency spectrum tone quantity of a music frame on a low frequency band is relatively low, and a ratio of a frequency spectrum tone quantity of a speech frame on the low frequency band is relatively high (energy of the speech frame is mainly concentrated on the low frequency band). Therefore, the current audio frame may be classified according to the statistics of the foregoing parameters. Certainly, signal classification may also be performed on the current audio frame by using another classification method.

[0198] After signal classification, different signals may be encoded in different encoding modes. For example, a speech signal is encoded by using an encoder based on a speech generating model (such as CELP), and a music signal is encoded by using an encoder based on conversion (such as an encoder based on MDCT).

[0199] In the foregoing embodiment, an audio signal is classified according to long-time statistics of linear prediction residual energy tilts and frequency spectrum tone quantities and a ratio of a frequency spectrum tone quantity on a low frequency band; therefore, there are relatively few parameters, a recognition rate is relatively high, and complexity is relatively low.

[0200] In an embodiment, after the linear prediction residual energy tilt epsP_tilt , the frequency spectrum tone quantity N_{tonal} , and the ratio ratio_Ntonal_lf of the frequency spectrum tone quantity on the low frequency band are stored in corresponding buffers, a variance of all data in the epsP_tilt historical buffer is obtained and marked as epsP_tilt60 . An average value of all data in the N_{tonal} historical buffer is obtained and marked as N_{tonal60} . An average value of all data in the ratio_Ntonal_lf historical buffer is obtained, and a ratio of the average value to N_{tonal60} is calculated and marked as ratio_Ntonal_lf60 . Referring to FIG. 12, a current audio frame is classified according to the following rule:

[0201] If a voice activity flag is 1 (that is, $\text{vad_flag} = 1$), that is, the current audio frame is an active voice frame, it is checked whether the following condition is satisfied: $\text{epsP_tilt60} < 0.002$ or $N_{\text{tonal60}} > 18$ or $\text{ratio_Ntonal_lf60} < 0.42$, if the condition is satisfied, the current audio frame is classified as a music type (that is, $\text{Mode} = 1$); otherwise the current audio frame is classified as a

speech type (that is, Mode = 0).

[0202] The foregoing embodiment is a specific classification process in which classification is performed according to statistics of linear prediction residual energy tilts, statistics of frequency spectrum tone quantities, and a ratio of a frequency spectrum tone quantity on a low frequency band, and a person skilled in the art can understand that, classification may be performed by using another process. The classification process in this embodiment may be applied to corresponding steps in the foregoing embodiment, to serve as, for example, a specific classification method of step 504 in FIG. 5 or step 1105 in FIG. 11.

[0203] The present invention provides an audio encoding mode selection method having low complexity and low memory overheads. In addition, both classification robustness and a classification recognition speed are taken into account.

[0204] Associated with the foregoing method embodiment, the present invention further provides an audio signal classification apparatus, and the apparatus may be located in a terminal device or a network device. The audio signal classification apparatus may perform the steps of the foregoing method embodiment.

[0205] Referring to FIG. 13, the present invention provides an embodiment of an audio signal classification apparatus, where the apparatus is configured to classify an input audio signal, and includes:

a storage determining unit 1301, configured to determine, according to voice activity of the current audio frame, whether to obtain and store a frequency spectrum fluctuation of the current audio frame, where the frequency spectrum fluctuation denotes an energy fluctuation of a frequency spectrum of an audio signal;

a memory 1302, configured to store the frequency spectrum fluctuation when the storage determining unit outputs a result that the frequency spectrum fluctuation needs to be stored;

an updating unit 1304, configured to update, according to whether a speech frame is percussive music or activity of a historical audio frame, frequency spectrum fluctuations stored in the memory; and

a classification unit 1303, configured to classify the current audio frame as a speech frame or a music frame according to statistics of a part or all of effective data of the frequency spectrum fluctuations stored in the memory; and when statistics of effective data of the frequency spectrum fluctuations satisfy a speech classification condition, classify the current audio frame as a speech frame; or when the statistics of the effective data of the frequency spectrum fluctuations satisfy a music classification condition, classify the current audio frame as a music frame.

[0206] In an embodiment, the storage determining unit 1301 is specifically configured to: when

determined that the current audio frame is an active frame, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

[0207] In another embodiment, the storage determining unit is specifically configured to: when it is determined that the current audio frame is an active frame, and the current audio frame does not belong to an energy attack, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

[0208] In another embodiment, the storage determining unit is specifically configured to: when it is determined that the current audio frame is an active frame, and none of multiple consecutive frames including the current audio frame and a historical frame of the current audio frame belongs to an energy attack, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

[0209] In an embodiment, the updating unit is specifically configured to: if the current audio frame belongs to percussive music, modify values of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory.

[0210] In another embodiment, the updating unit is specifically configured to: if the current audio frame is an active frame, and a previous audio frame is an inactive frame, modify data of other frequency spectrum fluctuations stored in the memory except the frequency spectrum fluctuation of the current audio frame into ineffective data; or if the current audio frame is an active frame, and three consecutive frames before the current audio frame are not all active frames, modify the frequency spectrum fluctuation of the current audio frame into a first value; or if the current audio frame is an active frame, and a historical classification result is a music signal and the frequency spectrum fluctuation of the current audio frame is greater than a second value, modify the frequency spectrum fluctuation of the current audio frame into the second value, where the second value is greater than the first value.

[0211] Referring to FIG. 14, in an embodiment, the classification unit 1303 includes:

a calculating unit 1401, configured to obtain an average value of a part or all of the effective data of the frequency spectrum fluctuations stored in the memory; and

a determining unit 1402, configured to compare the average value of the effective data of the frequency spectrum fluctuations with a music classification condition; and when the average value of the effective data of the frequency spectrum fluctuations satisfies the music classification condition, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame.

[0212] For example, when the obtained average value of the effective data of the frequency spectrum fluctuations is less than a music classification threshold, the current audio frame is

classified as a music frame; otherwise the current audio frame is classified as a speech frame.

[0213] In the foregoing embodiment, because an audio signal is classified according to long-time statistics of frequency spectrum fluctuations, there are relatively few parameters, a recognition rate is relatively high, and complexity is relatively low. In addition, the frequency spectrum fluctuations are adjusted with consideration of factors such as voice activity and percussive music; therefore, the present invention has a higher recognition rate for a music signal, and is suitable for hybrid audio signal classification.

[0214] In another embodiment, the audio signal classification apparatus further includes:

a parameter obtaining unit, configured to obtain a frequency spectrum high-frequency-band peakiness, a frequency spectrum correlation degree, and a linear prediction residual energy tilt of the current audio frame, where the frequency spectrum high-frequency-band peakiness denotes a peakiness or an energy acutance, on a high frequency band, of a frequency spectrum of the current audio frame; the frequency spectrum correlation degree denotes stability, between adjacent frames, of a signal harmonic structure of the current audio frame; and the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases; where

the storage determining unit is further configured to determine, according to the voice activity of the current audio frame, whether to store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt;

the storage unit is further configured to: when the storage determining unit outputs a result that the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt need to be stored, store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt; and

the classification unit is specifically configured to obtain statistics of effective data of the stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of stored linear prediction residual energy tilts, and classify the audio frame as a speech frame or a music frame according to the statistics of the effective data; and when the statistics of the effective data of the frequency spectrum fluctuations satisfy a speech classification condition, classify the current audio frame as a speech frame; or when the statistics of the effective data of the frequency spectrum fluctuations satisfy a music classification condition, classify the current audio frame as a music frame.

[0215] In an embodiment, the classification unit specifically includes:

a calculating unit, configured to obtain an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

a determining unit, configured to: when one of the following conditions is satisfied, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0216] In the foregoing embodiment, an audio signal is classified according to long-time statistics of frequency spectrum fluctuations, frequency spectrum high-frequency-band peakiness, frequency spectrum correlation degrees, and linear prediction residual energy tilts; therefore, there are relatively few parameters, a recognition rate is relatively high, and complexity is relatively low. In addition, the frequency spectrum fluctuations are adjusted with consideration of factors such as voice activity and percussive music, and the frequency spectrum fluctuations are modified according to a signal environment in which the current audio frame is located; therefore, the present invention improves a classification recognition rate, and is suitable for hybrid audio signal classification.

[0217] Referring to FIG. 15, the present invention provides another embodiment of an audio signal classification apparatus, where the apparatus is configured to classify an input audio signal, and includes:

a frame dividing unit 1501, configured to perform frame division processing on an input audio signal;

a parameter obtaining unit 1502, configured to obtain a linear prediction residual energy tilt of a current audio frame, where the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases;

a storage unit 1503, configured to store the linear prediction residual energy tilt; and

a classification unit 1504, configured to classify the audio frame according to statistics of a part of data of prediction residual energy tilts in a memory.

[0218] Referring to FIG. 16, the audio signal classification apparatus further includes:

a storage determining unit 1505, configured to determine, according to voice activity of the current audio frame, whether to store the linear prediction residual energy tilt in the memory, where

5 the storage unit 1503 is specifically configured to: when the storage determining unit determines that the linear prediction residual energy tilt needs to be stored, store the linear prediction residual energy tilt in the memory.

[0219] In an embodiment, the statistics of the part of the data of the prediction residual energy tilts is a variance of the part of the data of the prediction residual energy tilts; and

10 the classification unit is specifically configured to compare the variance of the part of the data of the prediction residual energy tilts with a music classification threshold, and when the variance of the part of the data of the prediction residual energy tilts is less than the music classification threshold, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame.

15 **[0220]** In another embodiment, the parameter obtaining unit is further configured to: obtain a frequency spectrum fluctuation, a frequency spectrum high-frequency-band peakiness, and a frequency spectrum correlation degree of the current audio frame, and store the frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, and the frequency spectrum correlation degree in corresponding memories; and

20 the classification unit is specifically configured to obtain statistics of effective data of stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of the stored linear prediction residual energy tilts, and classify the audio frame as a speech frame or a music frame according to the statistics of the effective data, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on the effective data stored in the memories.

[0221] Referring to FIG. 17, specifically, in an embodiment, the classification unit 1504 includes:

30 a calculating unit 1701, configured to obtain an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

a determining unit 1702, configured to: when one of the following conditions is satisfied,

classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0222] In another embodiment, the parameter obtaining unit is further configured to obtain a frequency spectrum tone quantity of the current audio frame and a ratio of the frequency spectrum tone quantity on a low frequency band, and store the frequency spectrum tone quantity and the ratio of the frequency spectrum tone quantity on the low frequency band in memories; and

the classification unit is specifically configured to obtain statistics of the stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately; and classify the audio frame as a speech frame or a music frame according to the statistics of the linear prediction residual energy tilts, the statistics of the frequency spectrum tone quantities, and the ratio of the frequency spectrum tone quantity on the low frequency band, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on data stored in the memories.

[0223] Specifically, the classification unit includes:

a calculating unit, configured to obtain a variance of effective data of the stored linear prediction residual energy tilts and an average value of the stored frequency spectrum tone quantities; and

a determining unit, configured to: when the current audio frame is an active frame, and one of the following conditions is satisfied, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame: the variance of the linear prediction residual energy tilts is less than a fifth threshold; or the average value of the frequency spectrum tone quantities is greater than a sixth threshold; or the ratio of the frequency spectrum tone quantity on the low frequency band is less than a seventh threshold.

[0224] Specifically, the parameter obtaining unit obtains the linear prediction residual energy tilt of the current audio frame according to the following formula:

$$epsP_tilt = \frac{\sum_{i=1}^n epsP(i) \cdot epsP(i+1)}{\sum_{i=1}^n epsP(i) \cdot epsP(i)},$$

where $epsP(i)$ denotes prediction residual energy of i^{th} -order linear prediction of the

current audio frame; and n is a positive integer, denotes a linear prediction order, and is less than or equal to a maximum linear prediction order.

[0225] Specifically, the parameter obtaining unit is configured to count a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 8 kHz and have frequency bin peak values greater than a predetermined value, to use the quantity as the frequency spectrum tone quantity; and the parameter obtaining unit is configured to calculate a ratio of a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 4 kHz and have frequency bin peak values greater than the predetermined value to the quantity of the frequency bins of the current audio frame that are on the frequency band from 0 to 8 kHz and have frequency bin peak values greater than the predetermined value, to use the ratio as the ratio of the frequency spectrum tone quantity on the low frequency band.

[0226] In this embodiment, an audio signal is classified according to long-time statistics of linear prediction residual energy tilts. In addition, both classification robustness and a classification recognition speed are taken into account; therefore, there are relatively few classification parameters, but a result is relatively accurate, complexity is low, and memory overheads are low.

[0227] The present invention provides another embodiment of an audio signal classification apparatus, where the apparatus is configured to classify an input audio signal, and includes:

a frame dividing unit, configured to perform frame division processing on an input audio signal;

a parameter obtaining unit, configured to obtain a frequency spectrum fluctuation, a frequency spectrum high-frequency-band peakiness, a frequency spectrum correlation degree, and a linear prediction residual energy tilt of a current audio frame, where the frequency spectrum fluctuation denotes an energy fluctuation of a frequency spectrum of the audio signal; the frequency spectrum high-frequency-band peakiness denotes a peakiness or an energy acutance, on a high frequency band, of a frequency spectrum of the current audio frame; the frequency spectrum correlation degree denotes stability, between adjacent frames, of a signal harmonic structure of the current audio frame; and the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases;

a storage unit, configured to store the frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt; and

a classification unit, configured to obtain statistics of effective data of stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics

of effective data of stored linear prediction residual energy tilts, and classify the audio frame as a speech frame or a music frame according to the statistics of the effective data, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on the effective data stored in the memories, where the calculation operation may include an operation for obtaining an average value, an operation for obtaining a variance, or the like.

[0228] In an embodiment, the audio signal classification apparatus may further include:

a storage determining unit, configured to determine, according to voice activity of the current audio frame, whether to store the frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt of the current audio frame; and

the storage unit is specifically configured to: when the storage determining unit outputs a result that the frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt need to be stored, store the frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt.

[0229] Specifically, in an embodiment, the storage determining unit determines, according to the voice activity of the current audio frame, whether to store the frequency spectrum fluctuation in the frequency spectrum fluctuation memory. If the current audio frame is an active frame, the storage determining unit outputs a result that the parameter needs to be stored; otherwise the storage determining unit outputs a result that the parameter does not need to be stored. In another embodiment, the storage determining unit determines, according to the voice activity of the audio frame and whether the audio frame is an energy attack, whether to store the frequency spectrum fluctuation in the memory. If the current audio frame is an active frame, and the current audio frame does not belong to an energy attack, the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory. In another embodiment, if the current audio frame is an active frame, and none of multiple consecutive frames including the current audio frame and a historical frame of the current audio frame belongs to an energy attack, the frequency spectrum fluctuation of the audio frame is stored in the frequency spectrum fluctuation memory; otherwise the frequency spectrum fluctuation is not stored. For example, if the current audio frame is an active frame, and neither a previous frame of the current audio frame nor a second historical frame of the current audio frame belongs to an energy attack, the frequency spectrum fluctuation of the audio frame is stored in the frequency spectrum fluctuation memory; otherwise the frequency spectrum fluctuation is not stored.

[0230] In an embodiment, the classification unit includes:

a calculating unit, configured to obtain an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

a determining unit, configured to: when one of the following conditions is satisfied, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

[0231] For a specific manner for calculating the frequency spectrum fluctuation, the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt of the current audio frame, refer to the foregoing method embodiment.

[0232] Further, the audio signal classification apparatus may further include:

an updating unit, configured to update, according to whether a speech frame is percussive music or activity of a historical audio frame, the frequency spectrum fluctuations stored in the memory. In an embodiment, the updating unit is specifically configured to: if the current audio frame belongs to percussive music, modify values of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory. In another embodiment, the updating unit is specifically configured to: if the current audio frame is an active frame, and a previous audio frame is an inactive frame, modify data of other frequency spectrum fluctuations stored in the memory except the frequency spectrum fluctuation of the current audio frame into ineffective data; or if the current audio frame is an active frame, and three consecutive frames before the current audio frame are not all active frames, modify the frequency spectrum fluctuation of the current audio frame into a first value; or if the current audio frame is an active frame, and a historical classification result is a music signal and the frequency spectrum fluctuation of the current audio frame is greater than a second value, modify the frequency spectrum fluctuation of the current audio frame into the second value, where the second value is greater than the first value.

[0233] In this embodiment, classification is performed according to long-time statistics of

frequency spectrum fluctuations, frequency spectrum high-frequency-band peakiness, frequency spectrum correlation degrees, and linear prediction residual energy tilts. In addition, both classification robustness and a classification recognition speed are taken into account; therefore, there are relatively few classification parameters, but a result is relatively accurate, a recognition rate is relatively high, and complexity is relatively low.

[0234] The present invention provides another embodiment of an audio signal classification apparatus, where the apparatus is configured to classify an input audio signal, and includes:

a frame dividing unit, configured to perform frame division processing on an input audio signal;

a parameter obtaining unit, configured to obtain a linear prediction residual energy tilt and a frequency spectrum tone quantity of a current audio frame and a ratio of the frequency spectrum tone quantity on a low frequency band, where the linear prediction residual energy tilt epsP_tilt denotes an extent to which linear prediction residual energy of the input audio signal changes as a linear prediction order increases; the frequency spectrum tone quantity N_{tonal} denotes a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 8 kHz and have frequency bin peak values greater than a predetermined value; and the ratio $\text{ratio_}N_{\text{tonal_lf}}$ of the frequency spectrum tone quantity on the low frequency band denotes a ratio of a low-frequency-band tone quantity to the frequency spectrum tone quantity, where for specific calculation, refer to description of the foregoing embodiment;

a storage unit, configured to store the linear prediction residual energy tilt, the frequency spectrum tone quantity, and the ratio of the frequency spectrum tone quantity on the low frequency band; and

a classification unit, configured to obtain statistics of stored linear prediction residual energy tilts and statistics of stored frequency spectrum tone quantities separately; and classify the audio frame as a speech frame or a music frame according to the statistics of the linear prediction residual energy tilts, the statistics of the frequency spectrum tone quantities, and the ratio of the frequency spectrum tone quantity on the low frequency band, where the statistics of the effective data refer to a data value obtained after a calculation operation is performed on data stored in memories.

[0235] Specifically, the classification unit includes:

a calculating unit, configured to obtain a variance of effective data of the stored linear prediction residual energy tilts and an average value of the stored frequency spectrum tone quantities; and

a determining unit, configured to: when the current audio frame is an active frame, and

one of the following conditions is satisfied, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame: the variance of the linear prediction residual energy tilts is less than a fifth threshold; or the average value of the frequency spectrum tone quantities is greater than a sixth threshold; or the ratio of the frequency spectrum tone quantity on the low frequency band is less than a seventh threshold.

[0236] Specifically, the parameter obtaining unit obtains the linear prediction residual energy tilt of the current audio frame according to the following formula:

$$epsP_tilt = \frac{\sum_{i=1}^n epsP(i) \cdot epsP(i+1)}{\sum_{i=1}^n epsP(i) \cdot epsP(i)},$$

where $epsP(i)$ denotes prediction residual energy of i^{th} -order linear prediction of the current audio frame; and n is a positive integer, denotes a linear prediction order, and is less than or equal to a maximum linear prediction order.

[0237] Specifically, the parameter obtaining unit is configured to count a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 8 kHz and have frequency bin peak values greater than a predetermined value, to use the quantity as the frequency spectrum tone quantity; and the parameter obtaining unit is configured to calculate a ratio of a quantity of frequency bins of the current audio frame that are on a frequency band from 0 to 4 kHz and have frequency bin peak values greater than the predetermined value to the quantity of the frequency bins of the current audio frame that are on the frequency band from 0 to 8 kHz and have frequency bin peak values greater than the predetermined value, to use the ratio as the ratio of the frequency spectrum tone quantity on the low frequency band.

[0238] In the foregoing embodiment, an audio signal is classified according to long-time statistics of linear prediction residual energy tilts and frequency spectrum tone quantities and a ratio of a frequency spectrum tone quantity on a low frequency band; therefore, there are relatively few parameters, a recognition rate is relatively high, and complexity is relatively low.

[0239] The foregoing audio signal classification apparatus may be connected to different encoders, and encode different signals by using the different encoders. For example, the audio signal classification apparatus is connected to two encoders, encodes a speech signal by using an encoder based on a speech generating model (such as CELP), and encodes a music signal by using an encoder based on conversion (such as an encoder based on MDCT). For a definition and an obtaining method of each specific parameter in the foregoing apparatus embodiment, refer to related description of the method embodiment.

[0240] Associated with the foregoing method embodiment, the present invention further

provides an audio signal classification apparatus, and the apparatus may be located in a terminal device or a network device. The audio signal classification apparatus may be implemented by a hardware circuit, or implemented by software in cooperation with hardware. For example, referring to FIG. 18, a processor invokes an audio signal classification apparatus to implement classification on an audio signal. The audio signal classification apparatus may perform the various methods and processes in the foregoing method embodiment. For specific modules and functions of the audio signal classification apparatus, refer to related description of the foregoing apparatus embodiment.

[0241] An example of a device 1900 in FIG. 19 is an encoder. The device 1900 includes a processor 1910 and a memory 1920.

[0242] The memory 1920 may include a random memory, a flash memory, a read-only memory, a programmable read-only memory, a non-volatile memory, a register, or the like. The processor 1910 may be a central processing unit (Central Processing Unit, CPU).

[0243] The memory 1920 is configured to store an executable instruction. The processor 1910 may execute the executable instruction stored in the memory 1920, and is configured to:

[0244] For other functions and operations of the device 1900, refer to processes of the method embodiments in FIG. 3 to FIG. 12, which are not described again herein to avoid repetition.

[0245] A person of ordinary skill in the art may understand that all or some of the processes of the methods in the embodiments may be implemented by a computer program instructing related hardware. The program may be stored in a computer-readable storage medium. When the program runs, the processes of the methods in the embodiments are performed. The foregoing storage medium may include: a magnetic disk, an optical disc, a read-only memory (Read-Only Memory, ROM), or a random access memory (Random Access Memory, RAM).

[0246] In the several embodiments provided in the present application, it should be understood that the disclosed system, apparatus, and method may be implemented in other manners. For example, the described apparatus embodiment is merely exemplary. For example, the unit division is merely logical function division and may be other division in actual implementation. For example, a plurality of units or components may be combined or integrated into another system, or some features may be ignored or not performed. In addition, the displayed or discussed mutual couplings or direct couplings or communication connections may be implemented by using some interfaces. The indirect couplings or communication connections between the apparatuses or units may be implemented in electronic, mechanical, or other forms.

[0247] The units described as separate parts may or may not be physically separate, and parts displayed as units may or may not be physical units, may be located in one position, or may be distributed on a plurality of network units. Some or all of the units may be selected according to

actual needs to achieve the objectives of the solutions of the embodiments.

[0248] In addition, functional units in the embodiments of the present invention may be integrated into one processing unit, or each of the units may exist alone physically, or two or more units are integrated into one unit.

- 5 **[0249]** The foregoing are merely exemplary embodiments of the present invention. A person skilled in the art may make various modifications and variations to the present invention without departing from the spirit and scope of the present invention.

CLAIMS

1. An audio signal classification method, comprising:

determining, according to voice activity of a current audio frame, whether to obtain a
5 frequency spectrum fluctuation of the current audio frame and store the frequency spectrum
fluctuation in a frequency spectrum fluctuation memory, wherein the frequency spectrum
fluctuation denotes an energy fluctuation of a frequency spectrum of an audio signal;

updating, according to whether the audio frame is percussive music or activity of a historical
audio frame, frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory;

10 and

classifying the current audio frame as a speech frame or a music frame according to statistics
of a part or all of effective data of the updated frequency spectrum fluctuations stored in the
frequency spectrum fluctuation memory.

2. The method according to claim 1, wherein the determining, according to voice activity of a
15 current audio frame, whether to obtain a frequency spectrum fluctuation of the current audio frame
and store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory
comprises:

if the current audio frame is an active frame, storing the frequency spectrum fluctuation of the
current audio frame in the frequency spectrum fluctuation memory.

20 3. The method according to claim 1, wherein the determining, according to voice activity of a
current audio frame, whether to obtain a frequency spectrum fluctuation of the current audio frame
and store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory
comprises:

25 if the current audio frame is an active frame, and the current audio frame does not belong to an
energy attack, storing the frequency spectrum fluctuation of the current audio frame in the
frequency spectrum fluctuation memory.

4. The method according to claim 1, wherein the determining, according to voice activity of a
current audio frame, whether to obtain a frequency spectrum fluctuation of the current audio frame
and store the frequency spectrum fluctuation in a frequency spectrum fluctuation memory
30 comprises:

if the current audio frame is an active frame, and none of multiple consecutive frames
comprising the current audio frame and a historical frame of the current audio frame belongs to an
energy attack, storing the frequency spectrum fluctuation of the current audio frame in the

frequency spectrum fluctuation memory.

5. The method according to any one of claims 1 to 4, wherein the updating, according to activity of a historical audio frame, frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory comprises:

5 if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and a previous audio frame is an inactive frame, modifying data of other frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory except the frequency spectrum fluctuation of the current audio frame into ineffective data; or

10 if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and three consecutive historical frames before the current audio frame are not all active frames, modifying the frequency spectrum fluctuation of the current audio frame into a first value; or

15 if it is determined that the frequency spectrum fluctuation of the current audio frame is stored in the frequency spectrum fluctuation memory, and a historical classification result is a music signal and the frequency spectrum fluctuation of the current audio frame is greater than a second value, modifying the frequency spectrum fluctuation of the current audio frame into the second value.

6. The method according to any one of claims 1 to 4, wherein the updating, according to whether the current audio frame is percussive music, frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory comprises:

20 if the current audio frame belongs to percussive music, modifying values of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory.

7. The method according to any one of claims 1 to 6, wherein the classifying the current audio frame as a speech frame or a music frame according to statistics of a part or all of effective data of the updated frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory comprises:

obtaining an average value of a part or all of the effective data of the frequency spectrum fluctuations stored in the updated frequency spectrum fluctuation memory; and

30 when the obtained average value of the effective data of the updated frequency spectrum fluctuations satisfies a music classification condition, classifying the current audio frame as a music frame.

8. The method according to any one of claims 1 to 6, further comprising:

obtaining a frequency spectrum high-frequency-band peakiness, a frequency spectrum correlation degree, and a linear prediction residual energy tilt of the current audio frame, wherein

the frequency spectrum high-frequency-band peakiness denotes a peakiness or an energy acutance, on a high frequency band, of a frequency spectrum of the current audio frame; the frequency spectrum correlation degree denotes stability, between adjacent frames, of a signal harmonic structure of the current audio frame; and the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases; and

determining, according to the voice activity of the current audio frame, whether to store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt in a memory,

wherein the classifying the audio frame according to statistics of a part or all of effective data of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory comprises:

obtaining an average value of the effective data of the stored frequency spectrum fluctuations, an average value of effective data of stored frequency spectrum high-frequency-band peakiness, an average value of effective data of stored frequency spectrum correlation degrees, and a variance of effective data of stored linear prediction residual energy tilts separately; and

when a classifying condition comprising one of the following conditions is satisfied, classifying the current audio frame as a music frame; otherwise classifying the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.

9. An audio signal classification apparatus, wherein the apparatus is configured to classify an input audio signal, and comprises:

a storage determining unit, configured to determine, according to voice activity of a current audio frame, whether to obtain and store a frequency spectrum fluctuation of the current audio frame, wherein the frequency spectrum fluctuation denotes an energy fluctuation of a frequency spectrum of an audio signal;

a memory, configured to store the frequency spectrum fluctuation when the storage determining unit outputs a result that the frequency spectrum fluctuation needs to be stored;

an updating unit, configured to update, according to whether the audio frame is percussive music or activity of a historical audio frame, frequency spectrum fluctuations stored in the memory;

and

a classification unit, configured to classify the current audio frame as a speech frame or a music frame according to statistics of a part or all of effective data of the updated frequency spectrum fluctuations stored in the memory.

5 10. The apparatus according to claim 9, wherein the storage determining unit is specifically configured to: when it is determined that the current audio frame is an active frame, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

11. The apparatus according to claim 9, wherein the storage determining unit is specifically configured to: when it is determined that the current audio frame is an active frame, and the current
10 audio frame does not belong to an energy attack, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

12. The apparatus according to claim 9, wherein the storage determining unit is specifically configured to: when it is determined that the current audio frame is an active frame, and none of multiple consecutive frames comprising the current audio frame and a historical frame of the
15 current audio frame belongs to an energy attack, output a result that the frequency spectrum fluctuation of the current audio frame needs to be stored.

13. The apparatus according to any one of claims 9 to 12, wherein the updating unit is specifically configured to: if the current audio frame is an active frame, and a previous audio frame is an inactive frame, modify data of other frequency spectrum fluctuations stored in the memory
20 except the frequency spectrum fluctuation of the current audio frame into ineffective data; or

if the current audio frame is an active frame, and three consecutive frames before the current audio frame are not all active frames, modify the frequency spectrum fluctuation of the current audio frame into a first value; or

if the current audio frame is an active frame, and a historical classification result is a music
25 signal and the frequency spectrum fluctuation of the current audio frame is greater than a second value, modify the frequency spectrum fluctuation of the current audio frame into the second value.

14. The apparatus according to any one of claims 9 to 12, wherein the updating unit is specifically configured to: if the current audio frame belongs to percussive music, modify values of the frequency spectrum fluctuations stored in the frequency spectrum fluctuation memory.

30 15. The apparatus according to any one of claims 9 to 14, wherein the classification unit comprises:

a calculating unit, configured to obtain an average value of a part or all of the effective data of the updated frequency spectrum fluctuations stored in the memory; and

a determining unit, configured to compare the average value of the effective data of the

frequency spectrum fluctuations with a music classification condition; and when the average value of the effective data of the updated frequency spectrum fluctuations satisfies the music classification condition, classify the current audio frame as a music frame.

16. The apparatus according to any one of claims 9 to 14, further comprising:

5 a parameter obtaining unit, configured to obtain a frequency spectrum high-frequency-band peakiness, a frequency spectrum correlation degree, a voicing parameter, and a linear prediction residual energy tilt of the current audio frame, wherein the frequency spectrum high-frequency-band peakiness denotes a peakiness or an energy acutance, on a high frequency band, of a frequency spectrum of the current audio frame; the frequency spectrum correlation
10 degree denotes stability, between adjacent frames, of a signal harmonic structure of the current audio frame; the voicing parameter denotes a time domain correlation degree between the current audio frame and a signal before a pitch period; and the linear prediction residual energy tilt denotes an extent to which linear prediction residual energy of the audio signal changes as a linear prediction order increases; wherein

15 the storage determining unit is further configured to determine, according to the voice activity of the current audio frame, whether to store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt in memories;

the memory is further configured to: when the storage determining unit outputs a result that the
20 frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt need to be stored, store the frequency spectrum high-frequency-band peakiness, the frequency spectrum correlation degree, and the linear prediction residual energy tilt; and

the classification unit is specifically configured to obtain statistics of effective data of the
25 stored frequency spectrum fluctuations, statistics of effective data of stored frequency spectrum high-frequency-band peakiness, statistics of effective data of stored frequency spectrum correlation degrees, and statistics of effective data of stored linear prediction residual energy tilts, and classify the audio frame as a speech frame or a music frame according to the statistics of the effective data.

17. The apparatus according to claim 16, wherein the classification unit comprises:

30 a calculating unit, configured to obtain an average value of the effective data of the stored frequency spectrum fluctuations, an average value of the effective data of the stored frequency spectrum high-frequency-band peakiness, an average value of the effective data of the stored frequency spectrum correlation degrees, and a variance of the effective data of the stored linear prediction residual energy tilts separately; and

a determining unit, configured to: when a classifying condition comprising one of the following conditions is satisfied, classify the current audio frame as a music frame; otherwise classify the current audio frame as a speech frame: the average value of the effective data of the frequency spectrum fluctuations is less than a first threshold; or the average value of the effective data of the frequency spectrum high-frequency-band peakiness is greater than a second threshold; or the average value of the effective data of the frequency spectrum correlation degrees is greater than a third threshold; or the variance of the effective data of the linear prediction residual energy tilts is less than a fourth threshold.