

DATA PROCESSING METHODS, APPARATUSES, AND TERMINAL DEVICES

TECHNICAL FIELD

5 [0001] Embodiments of the present specification relate to the field of computer technologies, and in particular, to data processing methods, apparatuses, and terminal devices.

BACKGROUND

10 [0002] With the continuous development of mobile payment technologies, mobile payment is gradually changing people's daily travel modes. More public transportation is beginning to support mobile payment. Users can use two-dimensional codes generated by mobile terminals to take public transportation. Specifically, when taking public transportation, a user can use a mobile terminal to generate a two-dimensional code, scan the code at an entry station, and scan the code at an exit station, thereby completing the payment. In related technologies, a mobile terminal can generate only
15 one two-dimensional code each time for one user to take public transportation. As such, when multiple persons traveling together take public transportation and one of them makes payment, the user usually needs to perform the operation multiple times so that the mobile terminal generates multiple two-dimensional codes. Consequently, user operations are cumbersome and user experience is poor.

20 SUMMARY

[0003] A purpose of embodiments of the present specification is to provide data processing methods, apparatuses, and terminal devices, so as to simplify user operations and improve user experience.

25 [0004] To achieve the previous purpose, some embodiments of the present specification provide a data processing method, including the following: providing a service code management interface; receiving a specified quantity that is input by a user in the service code management interface; generating the specified quantity of service codes, where the specified quantity of service codes include the same user identification

information; and displaying the specified quantity of service codes.

[0005] To achieve the previous purpose, some embodiments of the present specification provide a data processing apparatus, including the following: a providing unit, configured to provide a service code management interface; a receiving unit,
5 configured to receive a specified quantity that is input by a user in the service code management interface; a generating unit, configured to generate the specified quantity of service codes, where the specified quantity of service codes include the same user identification information; and a displaying unit, configured to display the specified quantity of service codes.

10 **[0006]** To achieve the previous purpose, some embodiments of the present specification provide a terminal device, including the following: a displaying component, configured to display a service code management interface and a service code; and a processor, coupled to the displaying component, and configured to: control
15 the displaying component to display the service code management interface; receive a specified quantity that is input by a user in the service code management interface; generate the specified quantity of service codes, where the specified quantity of service codes include the same user identification information; and control the displaying component to display the specified quantity of service codes.

[0007] It can be seen from the technical solutions provided in the previous
20 embodiments of the present specification that, in some embodiments of the present specification, the mobile terminal can provide the service code management interface; can receive the specified quantity that is input by the user in the service code management interface; can generate the specified quantity of service codes, where the specified quantity of service codes include the same user identification information;
25 and can display the specified quantity of service codes. As such, when multiple persons traveling together take public transportation and one of them makes payment, the user performs the operation once so that the mobile terminal generates multiple service codes, thereby simplifying user operations and improving user experience.

BRIEF DESCRIPTION OF DRAWINGS

30 **[0008]** To describe the technical solutions in some embodiments of the present specification or in the existing technology more clearly, the following briefly describes

the accompanying drawings needed for describing some embodiments or the existing technology. Clearly, the accompanying drawings in the following descriptions merely show some embodiments of the present specification, and a person of ordinary skill in the art can still derive other drawings from these accompanying drawings without creative efforts.

[0009] FIG. 1 is a flowchart illustrating a data processing method, according to some embodiments of the present specification;

[0010] FIG. 2 is a schematic diagram illustrating a functional structure of a data processing apparatus, according to some embodiments of the present specification;

10 [0011] FIG. 3 is a schematic diagram illustrating a functional structure of a terminal device, according to some embodiments of the present specification;

[0012] FIG. 4 is a schematic diagram illustrating an electronic metro card, according to some embodiments of the present specification;

15 [0013] FIG. 5 is a schematic diagram illustrating a service code management interface, according to some embodiments of the present specification;

[0014] FIG. 6 is a schematic diagram illustrating a service code display interface, according to some embodiments of the present specification;

[0015] FIG. 7 is a schematic diagram illustrating a label, according to some embodiments of the present specification; and

20 [0016] FIG. 8 is a schematic diagram illustrating an enlarged display interface, according to some embodiments of the present specification.

DESCRIPTION OF EMBODIMENTS

[0017] The following clearly describes the technical solutions in some embodiments of the present specification with reference to the accompanying drawings in some
25 embodiments of the present specification. Clearly, the described embodiments are merely some but not all of some embodiments of the present specification. All other embodiments obtained by a person of ordinary skill in the art based on some embodiments of the present specification without creative efforts shall fall within the protection scope of the present specification.

30 [0018] Some embodiments of the present specification provide a data processing

system. The data processing system can implement a public transportation charging service. For example, the public transportation corresponding to the public transportation charging service can be a metro, a bus, a tram, a high-speed railway, etc. Specifically, the public transportation charging service can be a segmented charging service or a one ticket price charging service.

[0019] In some embodiments, the data processing system can include a mobile terminal. The mobile terminal can have a service code generation function. A service code can include a graphical code, and the graphical code can include a bar code, a two-dimensional code, etc. The mobile terminal can be implemented in a form of hardware or software, or can be implemented in a form of a combination of hardware and software. For example, the mobile terminal can be a hardware device such as a smartphone, a tablet electronic device, a portable computer, a personal digital assistant (PDA), or a smart wearable device. The mobile terminal can also be an application program running on the hardware device.

[0020] In some embodiments, the data processing system can further include a station-entry toll terminal. The station-entry toll terminal can have a service code scanning and recognition function. The station-entry toll terminal can be implemented in a form of hardware or software, or can be implemented in a form of a combination of hardware and software. For example, the station-entry toll terminal can be a hardware device such as a smartphone, a tablet electronic device, a portable computer, a personal digital assistant (PDA), an in-vehicle device, a POS machine (such as a merchant POS machine, a bus POS machine, or a metro POS machine), or a smart self-service terminal (kiosk) (such as a metro ticket vending machine or a train ticket vending machine). The station-entry toll terminal can also be an application program running on the hardware device.

[0021] In some embodiments, the data processing system can further include a station-exit toll terminal. The station-exit toll terminal can have a service code scanning and recognition function. The station-exit toll terminal can be implemented in a form of hardware or software, or can be implemented in a form of a combination of hardware and software. For example, the station-exit toll terminal can be a hardware device such as a smartphone, a tablet electronic device, a portable computer, a personal digital assistant (PDA), an in-vehicle device, a POS machine (such as a merchant POS machine, a bus POS machine, or a metro POS machine), or a smart self-service terminal (kiosk)

(such as a metro ticket vending machine or a train ticket vending machine). The station-exit toll terminal can also be an application program running on the hardware device. It is worthwhile to note that, the station-exit toll terminal and the station-entry toll terminal can be the same or different. For example, when the public transportation corresponding to the public transportation charging service is metro, the station-exit toll terminal and the station-entry toll terminal can be different terminals. When the public transportation corresponding to the public transportation charging service is bus, the station-exit toll terminal and the station-entry toll terminal can be the same terminal.

[0022] In some embodiments, the data processing system can further include a charging server. The charging server can communicate with the station-entry toll terminal and the station-exit toll terminal. The charging server can be a server, or a server cluster that includes multiple servers.

[0023] In some embodiments, the data processing system can further include a payment server. The payment server can communicate with the mobile terminal. The payment server can be a server, or a server cluster that includes multiple servers.

[0024] Some embodiments of the present specification provide a data processing method. The data processing method is implemented by the data processing system.

[0025] In some embodiments, the mobile terminal can provide a service code management interface. The mobile terminal can receive a specified quantity that is input by a user in the service code management interface; can generate the specified quantity of service codes; and can display the specified quantity of service codes. Specifically, the specified quantity can be multiple. Each service code can include user identification information. For example, the user identification information can be a user account, a code of the user account, or any other form of information that can be used to deduce the user account. For example, the user account can be an ALIPAY account, a WeChat account, a bus card number, a metro card number, an all-in-one city card number, etc. The user identification information included in the specified quantity of service codes can be the same. Each service code can represent one service order initiated by the mobile terminal. Each service code can include order identification information, and the order identification information can be used to identify a service order represented by the service code. Order identification information in different service codes can be different.

[0026] In some embodiments, after arriving at the entry station, the user can use a

service code that has not been scanned and recognized by the station-entry toll terminal for code scanning by the station-entry toll terminal at the entry station, so as to take public transportation at the entry station. Considering that the mobile terminal can display multiple service codes, the user can perform code scanning multiple times, so that multiple persons (for example, the user and the user's parents, etc.) traveling together take public transportation at the entry station. A quantity of times the user scans the code can be less than or equal to the specified quantity. Each time the user scans a service code, the station-entry toll terminal can obtain the service code through scanning; can identify the service code to obtain user identification information and order identification information; and can send the user identification information, the order identification information, and entry station information to the charging server. The entry station information can be used to identify the entry station, and can be, for example, a name or a number of the entry station. The charging server can receive the user identification information, the order identification information, and the entry station information, so as to charge a user account corresponding to the user identification information.

[0027] In some embodiments, after arriving at the exit station, the user can use the service code that has been scanned and recognized by the station-entry toll terminal but has not been scanned and recognized by the station-exit toll terminal for code scanning by the station-exit toll terminal at the exit station, so as to leave the exit station. Considering that multiple persons traveling together may not leave at the same exit station, the user can perform code scanning once or multiple times, so that one or more of the multiple persons traveling together leave the exit station. Each time the user scans a service code, the station-exit toll terminal can obtain the service code through scanning; can identify the service code to obtain user identification information and order identification information; and can send the user identification information, the order identification information, and exit station information to the charging server. The exit station information can be used to identify the exit station, and can be, for example, a name or a number of the exit station. The charging server can receive the user identification information, the order identification information, and the exit station information; can determine a charging amount based on the previously received entry station information that corresponds to both the user identification information and the order identification information, and a charging rule; and can send a payment request to the payment server. The payment request can include the user identification

information, the order identification information, and the charging amount. Certainly, the payment request can further include other information, such as payee account information. The payment server can receive the payment request; can deduct money from a user account corresponding to the user identification information based on the charging amount; and can send payment result information to the mobile terminal. The payment result information can include the order identification information. Certainly, the payment result information can further include other information, such as the user identification information and/or the charging amount.

[0028] Further references can be made to FIG. 1, FIG. 4, FIG. 5, FIG. 6, FIG. 7, and FIG. 8. Some embodiments of the present specification further provide another data processing method. The data processing method can be performed by a mobile terminal. The data processing method can include the following steps.

[0029] Step S10: Provide a service code management interface.

[0030] In some embodiments, the service code management interface can be provided by the mobile terminal for a user to set a quantity of service codes to be generated. The mobile terminal can display the service code management interface after receiving an interface display instruction.

[0031] The interface display instruction can be automatically generated by the mobile terminal. For example, the mobile terminal can run an application program.

After the application program is started, the interface display instruction can be generated by default.

[0032] Alternatively, the interface display instruction can be generated through triggering by a user operation. For example, the mobile terminal can generate the interface display instruction after detecting that one or any combination of multiple specified keys is pressed, tapped, double-tapped, or swiped. The specified key can be a virtual key or a physical key. For example, the virtual key can be a button control or a graphic control, etc. The physical key can be a press button, a rocker button, a dial, a slider switch, or a joystick, etc. For another example, the mobile terminal can further generate the interface display instruction after recognizing a predetermined gesture. For example, the predetermined gesture can be swiping left, swiping right, etc. For another example, the mobile terminal can have a gyroscope and/or an acceleration sensor. The mobile terminal can further generate the interface display instruction after detecting a predetermined motion state by using a gyroscope and/or an acceleration sensor. For

example, the predetermined motion state can be shaking, etc.

[0033] Step S12: Receive a specified quantity that is input by a user in the service code management interface.

[0034] In some embodiments, the specified quantity can be a quantity of service codes to be generated by the mobile terminal. Specifically, the specified quantity can be multiple, for example, two, three, or five. The mobile terminal can receive, in any method, the specified quantity that is input by the user in the service code management interface. For example, the service code management interface can include a text box. The user can input the specified quantity in the text box. The mobile terminal can receive the specified quantity that is input by the user in the text box. For another example, the user can input first audio information in the service code management interface. The mobile terminal can receive the first audio information that is input by the user; and can recognize the first audio information to obtain the specified quantity.

[0035] Step S14: Generate the specified quantity of service codes.

[0036] In some embodiments, for the description of the service code, references can be made to the previous embodiments. The mobile terminal can generate the specified quantity of service codes after receiving a service code generation instruction. A process of generating the service code generation instruction can be similar to a process of generating the interface display instruction. The mobile terminal can generate the specified quantity of service codes by using a service code generation algorithm. Depending on different generated service codes, the service code generation algorithms can be the same or different. For example, when a two-dimensional code is generated, the service code generation algorithm can be a quick response code (QR code) algorithm. A person skilled in the art should understand that, the QR code algorithm here is only an example, and in fact any algorithm that can generate a two-dimensional code can be applied here. Certainly, when other service codes are generated, the service code generation algorithm can also be other algorithms, which are not listed here one by one. In addition, the mobile terminal can generate the specified quantity of service codes offline. Alternatively, the mobile terminal can generate the specified quantity of service codes by interacting with a payment server online. For the description of the payment server, references can be made to the previous embodiments.

[0037] Step S16: Display the specified quantity of service codes.

[0038] In some embodiments, the mobile terminal can display the specified quantity of service codes in any method. For example, the mobile terminal can provide a service

code display interface; and can display the specified quantity of service codes in the service code display interface.

[0039] In some implementations of some embodiments, after receiving a first label generation instruction for a first service code, the mobile terminal can generate a first label for the first service code; and can display the first label. The first service code can include a service code that has been scanned and recognized by the station-entry toll terminal but has not been scanned and recognized by the station-exit toll terminal. The first label can be used to indicate that a service order represented by the first service code is in a charging state. For example, the first label can be "entered".

[0040] The first label generation instruction can be generated through triggering by a user operation. For example, the user can trigger the service code that has been scanned and recognized by the station-entry toll terminal but has not been scanned and recognized by the station-exit toll terminal. After detecting the trigger operation, the mobile terminal can use a service code corresponding to the trigger operation as a first service code; and can generate a first label generation instruction for the first service code. For example, the trigger operation can include a tap operation, a double-tap operation, a press operation, a swipe operation, an operation of pressing and holding for more than a predetermined time (also referred to as a touch and hold operation), etc.

[0041] Alternatively, the first label generation instruction can be generated after tolling start information sent by the payment server is received. Specifically, the user can use a service code that has not been scanned and recognized by the station-entry toll terminal for code scanning by the station-entry toll terminal at the entry station. The station-entry toll terminal can obtain the service code through scanning; can identify the service code to obtain user identification information and order identification information; and can send the user identification information, the order identification information, and entry station information to the charging server. The charging server can receive the user identification information, the order identification information, and the entry station information; and can send the tolling start information to the payment server. The tolling start information can include the order identification information.

Certainly, the tolling start information can further include other information, such as the user identification information and/or the entry station information. The payment server can receive the tolling start information; and can send the tolling start information to the mobile terminal. The mobile terminal can receive the tolling start information; can use a service code that includes the order identification information in

the tolling start information as a first service code; and can generate a first label generation instruction for the first service code.

[0042] In some implementations of some embodiments, after receiving a second label generation instruction for a second service code, the mobile terminal can generate a second label for the second service code; and can display the second label. The second service code can include a service code that has been scanned and recognized by the station-exit toll terminal. The second label can be used to indicate that a service order represented by the second service code is in a payment end state. For example, the second label can be "exited".

[0043] The second label generation instruction can be generated through triggering by a user operation. For example, the user can trigger the service code that has been scanned and recognized by the station-exit toll terminal. After detecting the trigger operation, the mobile terminal can use a service code corresponding to the trigger operation as a second service code; and can generate a second label generation instruction for the second service code. For example, the trigger operation can include a tap operation, a double-tap operation, a press operation, a swipe operation, an operation of pressing and holding for more than a predetermined time (also referred to as a touch and hold operation), etc.

[0044] Alternatively, the second label generation instruction can be generated after payment result information sent by the payment server is received. Specifically, the user can use the service code that has been scanned and recognized by the station-entry toll terminal but has not been scanned and recognized by the station-exit toll terminal for code scanning by the station-exit toll terminal at the exit station. The station-exit toll terminal can obtain the service code through scanning; can identify the service code to obtain user identification information and order identification information; and can send the user identification information, the order identification information, and exit station information to the charging server. The charging server can receive the user identification information, the order identification information, and the exit station information; can determine a charging amount based on the previously received entry station information that corresponds to both the user identification information and the order identification information, and a charging rule; and can send a payment request to the payment server. The payment request can include the user identification information, the order identification information, and the charging amount. The payment server can receive the payment request; can deduct money from a user account

corresponding to the user identification information based on the charging amount; and can send payment result information to the mobile terminal. The payment result information can include the order identification information. The mobile terminal can receive the payment result information; can use a service code that includes the order identification information in the payment result information as a second service code; and can generate a second label generation instruction for the second service code.

[0045] In some implementations of some embodiments, after receiving a third label generation instruction for a third service code, the mobile terminal can generate a third label for the third service code; and can display the third label. The third service code can include a service code that has not been scanned and recognized by the station-entry toll terminal. The third label can be used to indicate that a service order represented by the third service code is in a canceled state. For example, the third label can be "canceled".

[0046] The third label generation instruction can be generated through triggering by a user operation. For example, the user can trigger the service code that has not been scanned and recognized by the station-entry toll terminal. After detecting the trigger operation, the mobile terminal can use a service code corresponding to the trigger operation as a third service code; and can generate a third label generation instruction for the third service code. For example, the trigger operation can include a tap operation, a double-tap operation, a press operation, a swipe operation, an operation of pressing and holding for more than a predetermined time (also referred to as a touch and hold operation), etc.

[0047] In some implementations of some embodiments, after receiving an enlarged display instruction for a fourth service code, the mobile terminal can enter an enlarged display interface for enlarged display of the fourth service code. In the enlarged display interface, the fourth service code is in an enlarged display state, facilitating code scanning by the user. The fourth service code can include a service code that has not been scanned and recognized by the station-entry toll terminal, and a service code that has been scanned and recognized by the station-entry toll terminal but has not been scanned and recognized by the station-exit toll terminal.

[0048] The enlarged display instruction can be generated through triggering by a user operation. For example, the user can trigger the service code that has not been scanned and recognized by the station-entry toll terminal. After detecting the trigger operation, the mobile terminal can use a service code corresponding to the trigger

operation as a fourth service code; and can generate an enlarged display instruction for the fourth service code. For example, the trigger operation can include a tap operation, a double-tap operation, a press operation, a swipe operation, an operation of pressing and holding for more than a predetermined time (also referred to as a touch and hold operation), etc. For another example, the user can trigger the service code that has been scanned and recognized by the station-entry toll terminal but has not been scanned and recognized by the station-exit toll terminal. After detecting the trigger operation, the mobile terminal can use a service code corresponding to the trigger operation as a fourth service code; and can generate an enlarged display instruction for the fourth service code.

[0049] Alternatively, the enlarged display instruction can be generated after second audio information is received. Specifically, as described previously, the mobile terminal can display the specified quantity of service codes. At least one service code in the specified quantity of service codes can have a label. The label can include a first label, a second label, a third label, etc. As such, the user can input the second audio information. The mobile terminal can receive audio information that is input by a user; can recognize the second audio information to obtain a target label; can use a service code that has the target label as a fourth service code; and can generate an enlarged display instruction for the fourth service code. For example, the second audio information can be "display the service code that has been used for entry", and then the target label can be the first label "entered". For another example, the second audio information can be "display the service code that has been used for exit", and then the target label can be the second label "exited".

[0050] In some implementations of some embodiments, as described previously, the mobile terminal can display the specified quantity of service codes. At least one service code in the specified quantity of service codes can have a label. The label can include a first label, a second label, a third label, etc. As such, after receiving a label broadcast instruction for a fifth service code, the mobile terminal can broadcast a label that the fifth service code has. The fifth service code can include a service code that has been scanned and recognized by the station-entry toll terminal, but has not been scanned and recognized by the station-exit toll terminal, and a service code that has been scanned and recognized by the station-exit toll terminal.

[0051] The label broadcast instruction can be generated through triggering by a user operation. For example, the user can trigger the service code that has been scanned and

recognized by the station-entry toll terminal but has not been scanned and recognized by the station-exit toll terminal. After detecting the trigger operation, the mobile terminal can use a service code corresponding to the trigger operation as a fifth service code; and can generate a label broadcast instruction for the fifth service code. For another example, the user can trigger the service code that has been scanned and recognized by the station-exit toll terminal. After detecting the trigger operation, the mobile terminal can use a service code corresponding to the trigger operation as a fifth service code; and can generate a label broadcast instruction for the fifth service code.

[0052] In some embodiments, the mobile terminal can provide the service code management interface; can receive the specified quantity that is input by the user in the service code management interface; can generate the specified quantity of service codes, where the specified quantity of service codes include the same user identification information; and can display the specified quantity of service codes. As such, when multiple persons traveling together take public transportation and one of them makes payment, the user performs the operation once so that the mobile terminal generates multiple service codes, thereby simplifying user operations and improving user experience.

[0053] References are made to FIG. 2. Some embodiments of the present specification provide a data processing apparatus. The data processing apparatus can include the following units: a providing unit 20, configured to provide a service code management interface; a receiving unit 22, configured to receive a specified quantity that is input by a user in the service code management interface; a generating unit 24, configured to generate the specified quantity of service codes, where the specified quantity of service codes include the same user identification information; and a displaying unit 26, configured to display the specified quantity of service codes.

[0054] References are made to FIG. 3. Some embodiments of the present specification provide a terminal device. The terminal device can include a displaying component and a processor.

[0055] In some embodiments, the displaying component can include but is not limited to a liquid crystal display (LCD), a cathode ray tube (CRT) display, a light emitting diode (LED) display, etc. The displaying component can be configured to display a service code management interface and a service code.

[0056] In some embodiments, the processor can be implemented in any proper

method. For example, the processor can take the form of, for example, a microprocessor or processor, a computer readable medium storing computer readable program code (such as software or firmware) executable by the microprocessor or processor, a logic gate, a switch, an application specific integrated circuit (ASIC), a programmable logic controller, and an embedded microcontroller. The processor can be coupled to the displaying component, and configured to: control the displaying component to display the service code management interface; receive a specified quantity that is input by a user in the service code management interface; generate the specified quantity of service codes, where the specified quantity of service codes include the same user identification information; and control the displaying component to display the specified quantity of service codes.

[0057] Some embodiments of the present specification are described in a progressive way. For same or similar parts of some embodiments, mutual references can be made to some embodiments. Each embodiment focuses on a difference from the other embodiments. Particularly, data processing apparatus embodiments and terminal device embodiments are basically similar to method embodiments, and therefore are described briefly. For related parts, references can be made to related descriptions in the method embodiments.

[0058] In the 1990s, whether a technical improvement is a hardware improvement (for example, an improvement to a circuit structure, such as a diode, a transistor, or a switch) or a software improvement (an improvement to a method procedure) can be clearly distinguished. However, as technologies develop, current improvements to many method procedures can be considered as direct improvements to hardware circuit structures. A designer usually programs an improved method procedure into a hardware circuit, to obtain a corresponding hardware circuit structure. Therefore, a method procedure can be improved by using a hardware entity module. For example, a programmable logic device (PLD) (for example, a field programmable gate array (FPGA)) is such an integrated circuit, and a logical function of the PLD is determined by a user through device programming. The designer performs programming to "integrate" a digital system to a PLD without requesting a chip manufacturer to design and produce an application-specific integrated circuit chip. In addition, at present, instead of manually manufacturing an integrated chip, this type of programming is mostly implemented by using "logic compiler" software. The programming is similar to a software compiler used to develop and write a program. Original code needs to be

written in a particular programming language for compilation. The language is referred to as a hardware description language (HDL). There are many HDLs, such as the Advanced Boolean Expression Language (ABEL), the Altera Hardware Description Language (AHDL), Confluence, the Cornell University Programming Language (CUPL), HDCal, the Java Hardware Description Language (JHDL), Lava, Lola, MyHDL, PALASM, and the Ruby Hardware Description Language (RHDL). The very-high-speed integrated circuit hardware description language (VHDL) and Verilog2 are most commonly used. A person skilled in the art should also understand that a hardware circuit that implements a logical method procedure can be readily obtained once the method procedure is logically programmed by using the some described hardware description languages and is programmed into an integrated circuit.

[0059] The system, apparatus, module, or unit illustrated in the previous embodiments can be implemented by using a computer chip or an entity, or can be implemented by using a product having a certain function. A typical implementation device is a computer. Specifically, for example, the computer can be a personal computer, a laptop computer, a cellular phone, a camera phone, a smart phone, a personal digital assistant, a media player, a navigation device, an e-mail device, a game console, a tablet computer, a wearable device, or any combination of these devices.

[0060] It can be seen from the descriptions of the implementations that a person skilled in the art can clearly understand that the present specification can be implemented by using software and a necessary general hardware platform. Based on such an understanding, the technical solutions in the present specification essentially or the part contributing to the existing technology can be implemented in a form of a software product. The computer software product can be stored in a storage medium, such as a ROM/RAM, a magnetic disk, or an optical disc, and includes some instructions for instructing a computer device (can be a personal computer, a server, or a network device) to perform the methods described in some embodiments or in some parts of some embodiments of the present specification.

[0061] The present specification can be applied to many general-purpose or special-purpose computer system environments or configurations, for example, a personal computer, a server computer, a handheld device or a portable device, a tablet device, a multi-processor system, a microprocessor-based system, a set-top box, a programmable consumer electronic device, a network PC, a minicomputer, a mainframe computer, and a distributed computing environment including any one of the previous systems or

devices.

[0062] The present specification can be described in the general context of computer-executable instructions, for example, a program module. Generally, the program module includes a routine, a program, an object, a component, a data structure, etc.

5 executing a specific task or implementing a specific abstract data type. The present specification can also be practiced in distributed computing environments. In the distributed computing environments, tasks are performed by remote processing devices connected through a communications network. In a distributed computing environment, the program module can be located in both local and remote computer storage media
10 including storage devices.

[0063] Although the present specification is described by using some embodiments, a person of ordinary skill in the art knows that many variations of the present specification can be made without departing from the spirit of the present specification. It is expected that the appended claims include these variations without departing from
15 the spirit of the present specification.

CLAIMS

What is claimed is:

1. A data processing method, comprising the following:
providing a service code management interface;
5 receiving a specified quantity that is input by a user in the service code management interface;
generating the specified quantity of service codes, wherein the specified quantity of service codes comprise the same user identification information; and
displaying the specified quantity of service codes.
- 10 2. The method according to claim 1, wherein the method further comprises the following:
after receiving a first label generation instruction for a first service code, generating a first label for the first service code, wherein the first label is used to indicate that a service order represented by the first service code is in a charging state; and
15 displaying the first label.
3. The method according to claim 2, wherein each service code further comprises order identification information; correspondingly, the first label generation instruction is generated after tolling start information is received; and the tolling start information comprises order identification information in the first service code.
- 20 4. The method according to claim 1, wherein the method further comprises the following:
after receiving a second label generation instruction for a second service code, generating a second label for the second service code, wherein the second label is used to indicate that a service order represented by the second service code is in a payment
25 end state; and
displaying the second label.
5. The method according to claim 4, wherein each service code further comprises order identification information; correspondingly, the second label generation instruction is generated after payment result information is received; and the payment
30 result information comprises order identification information in the second service code.
6. The method according to claim 1, wherein the method further comprises the following:
after receiving a third label generation instruction for a third service code,

generating a third label for the third service code, wherein the third label is used to indicate that a service order represented by the third service code is in a canceled state; and

displaying the third label.

5 7. The method according to claim 1, wherein the method further comprises the following:

after receiving an enlarged display instruction for a fourth service code, entering an enlarged display interface for enlarged display of the fourth service code.

10 8. The method according to claim 1, wherein at least one service code in the specified quantity of service codes has a label; correspondingly, the method further comprises the following:

after receiving a label broadcast instruction for a fifth service code, broadcasting a label that the fifth service code has.

15 9. The method according to claim 1, wherein each service code further comprises order identification information; and order identification information in different service codes is different.

10. A data processing apparatus, comprising the following:

a providing unit, configured to provide a service code management interface;

20 a receiving unit, configured to receive a specified quantity that is input by a user in the service code management interface;

a generating unit, configured to generate the specified quantity of service codes, wherein the specified quantity of service codes comprise the same user identification information; and

a displaying unit, configured to display the specified quantity of service codes.

25 11. A terminal device, comprising the following:

a displaying component, configured to display a service code management interface and a service code; and

30 a processor, coupled to the displaying component, and configured to: control the displaying component to display the service code management interface; receive a specified quantity that is input by a user in the service code management interface; generate the specified quantity of service codes, wherein the specified quantity of service codes comprise the same user identification information; and control the displaying component to display the specified quantity of service codes.