

Description

This invention relates to a water-tight slide fastener which comprises a pair of oppositely disposed support tapes, a row of fastener coupling elements, each having a coupling head and an upper leg portion, a lower leg portion and a heel portion and secured by sewing threads to and along an inner longitudinal edge of each of the respective support tapes and a filling core extending through spaces defined in said row of coupling elements and initially filling said spaces except for the region of said coupling head, said support tape being coated with a water-resistant coating material on one of its surfaces and on its longitudinal marginal edges.

A water-tight slide fastener of this type is disclosed in EP-A-0 111 788. This prior art slide fastener is rendered water-tight, to prohibit entry of water into an article to which the slide fastener is applied, by coating one or both surfaces of the fastener tapes with a suitable water-resistant or repellant coating material and further by maintaining the confronting edges of the opposed tapes in intimate abutting, sealing contact with each other when the fastener is closed.

However, the prior art water-tight slide fastener has a drawback in that due to tight sealing closure of the confronting tape edges, the slider is subject to increased sliding resistance and would often become sluggish, if not impossible, in its reciprocating movement to open or close the fastener. Another drawback is found in that the fastener when subjected to severe lateral pull is apt to lose its sealing effect at the junction of the two opposed tape edges along which rows of coupling elements are mounted.

The US-A-3 914 827 discloses a water-tight slide fastener with a core string consisting of a rubber-like material which should be resiliently compressible. After closure of the slide fastener this resiliently compressible core string ought to close the spaces existing between the coupling elements in order to prevent penetration of water. This aim, however, ought to be achieved only incompletely.

The US-A-4 153 980 describes a conventional non-water-tight slide fastener according to which close to the coupling elements threads are provided for being impregnated with a lubricant. This lubricant ought to reduce friction of the slider.

The present invention seeks to provide a water-tight slide fastener constructed on a unique inventive concept that water-tightness is achieved basically at the region of the fastener where its coupling elements are located, in addition to the provision of a water-tight tape web, whereby the slider retains its smooth reciprocating movement and the

fastener is rendered highly resistant to lateral pull or transverse pressure tending to spread apart the opposed halves of the fastener.

According to the invention these objects are achieved with a water-tight slide fastener of the type mentioned above, characterized in that said core is capable of swelling upon contact with a liquid and completely filling up said spaces against entry of the liquid into the interior of an article to which the fastener is applied.

The above and other objects and features of the invention will be better understood from the following detailed description taken in conjunction with the accompanying drawings in which like reference numerals refer to like or corresponding parts throughout the several views.

Figure 1 is a transverse cross-sectional view on enlarged scale of a water-tight slide fastener embodying the invention, showing the fastener in dry condition;

Figure 2 is a view similar to Figure 1 but showing the fastener in wet condition;

Figure 3 is a plan view of a portion of the slide fastener shown in Figure 2;

Figure 4 is a view similar to Figure 1 but showing a modified form of water-tight slide fastener; and

Figure 5 is a transverse cross-sectional view of a water-tight slide fastener of a concealed construction.

Referring now to the drawings and Figure 1 in particular, there is shown a slide fastener 10 which has a water-tight function according to the present invention.

The slide fastener 10 is conventional in that it comprises a pair of oppositely disposed support tapes 11 and a row of fastener coupling elements 12 secured by sewing threads or seams 13 to and along an inner longitudinal edge of each of the respective support tapes 11, the opposed rows of coupling elements 12 being taken into and out of coupling engagement with each other by a slider not shown. The support tape may be a fabric of woven or knitted structure. It is coated on its back surface including sewn seams 13 and on the inner longitudinal marginal edge 14 with a layer of material 15 which is air-permeative but liquid-impermeative such as for example a polyurethane resin.

The coupling elements 12 are in the form of a continuous helical coil as presently shown in the illustrated embodiments, although the invention is not limited thereto. The coupling element 12 taken as an individual unit comprises a coupling head portion 12a, an upper leg portion 12b, a lower leg portion 12c and a heel portion 12d connecting the leg portions to adjacent counterparts in the row of elements 12.

Designated at 16 is a filling core or cord which

extends longitudinally through spaces or gaps 17 defined in the row of coupling elements 12 and fills that region of space 17 which is defined by the leg portions 12b, 12c and the heel portion 12d, initially leaving the space unfilled adjacent to the coupling head 12a as shown in Figure 1. The filling core 16 is formed from a polymeric fibrous material which is highly water absorptive and capable of swelling to a multiple gravity upon wetting with water as shown in Figures 2 and 3 and further highly water retentive against pressure in normal use.

An example of such polymeric material is commercially available under the tradename of Lanceal-F of Japan Exlan Industries Ltd.

Figure 4 shows a modification of water-tight slide fastener 10 which includes a plurality of water-absorptive strands 18 of a similar fibrous material to the filling core 16, the strands 18 being provided along each of the longitudinal marginal tape edges 14 disposed in confronting relation as warp yarns either woven or knitted into the tape system to enhance water-tightness of the fastener 10.

Figure 5 shows a concealed type of slide fastener 10 which carries a row of coupling elements 12 on and along a folded edge portion 14', to which the principles of the invention are applied in which each of the tapes 11 is coated with the water-tight layer 15 on one of its surfaces including the folded edge portion 14' and provided with the water-absorptive strands 18 at the confronting abutting edges of the opposed tapes 11.

When the slide fastener 10 thus constructed is put to use in a water or other liquid phase environment as in the case of ski wear, jogging wear, sports bags and the like, the filling core 16 swells in volume to an extent sufficient to fill up the spaces or gaps in between the individual coupling elements 12 in the opposed rows thereby preventing entry or permeation of liquids into the interior of the garment or other articles to which the slide fastener 10 is applied. Because of the physical characteristics of the material of the filling core 16, this fastener component absorbs and retains water against leaking under the influence of pressure in normal use of the fastener 10 and allows the slider to move smoothly regardless of whether the core 16 is dry or wet.

Claims

1. A water-tight slide fastener (10) which comprises a pair of oppositely disposed support tapes (11), a row of fastener coupling elements (12), each having a coupling head (12a), and an upper leg portion (12b), a lower leg portion (12c) and a heel portion (12d) and secured by sewing threads (13) to and along an inner

longitudinal edge of each of the respective support tapes (11), and a filling core (16) extending through spaces (17) defined in said row of coupling elements (12) and initially filling said spaces (17) except for the region of said coupling head (12a) said support tape (11) being coated with a water-resistant coating material on one of its surfaces and on its longitudinal marginal edge (14),

characterized in that said core (16) is capable of swelling upon contact with a liquid and completely filling up said spaces (16) against entry of the liquid into the interior of an article to which the fastener (10) is applied.

2. A water-tight slide fastener (10) according to claim 1 which further comprises a plurality of water-absorptive strands (18) extending along each of said marginal edges (14) in confronting relation.
3. A water-tight slide fastener (10) according to claim 2 wherein said strands (18) are warp yarns woven or knitted into said tape (11).
4. A water-tight slide fastener (10) according to claim 1 wherein said coating material is a polyurethane resin.
5. A water-tight slide fastener (10) according to claim 1 wherein said filling core (16) is formed from a highly water-absorptive and -retentive fibrous material.

Revendications

1. Fermeture à glissière étanche à l'eau (10) qui comprend une paire de rubans de support (11) disposés en face l'un de l'autre, une rangée d'éléments d'accouplement (12) comportant chacun une tête d'accouplement (12a) et une partie (12b) formant un jambage supérieur, une partie (12c) formant un jambage inférieur et une partie (12d) formant un talon, et fixés au moyen de fils de couture (13) sur un bord longitudinal intérieur, et le long de celui-ci, lequel appartient aux rubans de support (11) respectifs, et une âme de remplissage (16) qui s'étend dans les espaces (17) définis dans ladite rangée d'éléments d'accouplement (12) et remplissant initialement lesdits espaces (17) à l'exception de la zone de ladite tête d'accrochage (12a), ledit ruban de support (11) étant revêtu sur une de ses surfaces et sur son bord marginal longitudinal (14) d'un matériau de revêtement étanche à l'eau,

caractérisé en ce que ladite âme (16) est apte à gonfler au contact d'un liquide et à



extends longitudinally through spaces or gaps 17 defined in the row of coupling elements 12 and fills that region of space 17 which is defined by the leg portions 12b, 12c and the heel portion 12d, initially leaving the space unfilled adjacent to the coupling head 12a as shown in Figure 1. The filling core 16 is formed from a polymeric fibrous material which is highly water absorptive and capable of swelling to a multiple gravity upon wetting with water as shown in Figures 2 and 3 and further highly water retentive against pressure in normal use.

An example of such polymeric material is commercially available under the tradename of Lanceal-F of Japan Exlan Industries Ltd.

Figure 4 shows a modification of water-tight slide fastener 10 which includes a plurality of water-absorptive strands 18 of a similar fibrous material to the filling core 16, the strands 18 being provided along each of the longitudinal marginal tape edges 14 disposed in confronting relation as warp yarns either woven or knitted into the tape system to enhance water-tightness of the fastener 10.

Figure 5 shows a concealed type of slide fastener 10 which carries a row of coupling elements 12 on and along a folded edge portion 14', to which the principles of the invention are applied in which each of the tapes 11 is coated with the water-tight layer 15 on one of its surfaces including the folded edge portion 14' and provided with the water-absorptive strands 18 at the confronting abutting edges of the opposed tapes 11.

When the slide fastener 10 thus constructed is put to use in a water or other liquid phase environment as in the case of ski wear, jogging wear, sports bags and the like, the filling core 16 swells in volume to an extent sufficient to fill up the spaces or gaps in between the individual coupling elements 12 in the opposed rows thereby preventing entry or permeation of liquids into the interior of the garment or other articles to which the slide fastener 10 is applied. Because of the physical characteristics of the material of the filling core 16, this fastener component absorbs and retains water against leaking under the influence of pressure in normal use of the fastener 10 and allows the slider to move smoothly regardless of whether the core 16 is dry or wet.

Claims

1. A water-tight slide fastener (10) which comprises a pair of oppositely disposed support tapes (11), a row of fastener coupling elements (12), each having a coupling head (12a), and an upper leg portion (12b), a lower leg portion (12c) and a heel portion (12d) and secured by sewing threads (13) to and along an inner

longitudinal edge of each of the respective support tapes (11), and a filling core (16) extending through spaces (17) defined in said row of coupling elements (12) and initially filling said spaces (17) except for the region of said coupling head (12a) said support tape (11) being coated with a water-resistant coating material on one of its surfaces and on its longitudinal marginal edge (14),

characterized in that said core (16) is capable of swelling upon contact with a liquid and completely filling up said spaces (16) against entry of the liquid into the interior of an article to which the fastener (10) is applied.

2. A water-tight slide fastener (10) according to claim 1 which further comprises a plurality of water-absorptive strands (18) extending along each of said marginal edges (14) in confronting relation.
3. A water-tight slide fastener (10) according to claim 2 wherein said strands (18) are warp yarns woven or knitted into said tape (11).
4. A water-tight slide fastener (10) according to claim 1 wherein said coating material is a polyurethane resin.
5. A water-tight slide fastener (10) according to claim 1 wherein said filling core (16) is formed from a highly water-absorptive and -retentive fibrous material.

Revendications

1. Fermeture à glissière étanche à l'eau (10) qui comprend une paire de rubans de support (11) disposés en face l'un de l'autre, une rangée d'éléments d'accouplement (12) comportant chacun une tête d'accouplement (12a) et une partie (12b) formant un jambage supérieur, une partie (12c) formant un jambage inférieur et une partie (12d) formant un talon, et fixés au moyen de fils de couture (13) sur un bord longitudinal intérieur, et le long de celui-ci, lequel appartient aux rubans de support (11) respectifs, et une âme de remplissage (16) qui s'étend dans les espaces (17) définis dans ladite rangée d'éléments d'accouplement (12) et remplissant initialement lesdits espaces (17) à l'exception de la zone de ladite tête d'accrochage (12a), ledit ruban de support (11) étant revêtu sur une de ses surfaces et sur son bord marginal longitudinal (14) d'un matériau de revêtement étanche à l'eau,

caractérisé en ce que ladite âme (16) est apte à gonfler au contact d'un liquide et à



remplir complètement lesdits espaces (17) à l'encontre de la pénétration d'un liquide dans l'intérieur de l'article sur lequel la fermeture (10) est montée.

2. Fermeture à glissière (10) étanche à l'eau selon la revendication 1 qui comprend en outre une pluralité de plages (18) susceptibles d'absorber l'eau qui s'étendent le long de chacun desdits bords marginaux (14), qui se font face.
3. Fermeture à glissière (10) étanche à l'eau selon la revendication 2 dans laquelle lesdites plages (18) sont des fils de chaîne tissés ou tricotés dans ledit ruban (11).
4. Fermeture à glissière (10) étanche à l'eau selon la revendication 1 dans laquelle ledit matériau de revêtement est une résine polyuréthane.
5. Fermeture à glissière (10) étanche à l'eau selon la revendication 1 dans laquelle ladite âme de remplissage (16) est réalisée à partir d'un matériau qui absorbe et retient fortement l'eau.

3. Wasserdichter Reißverschluß (10) nach Anspruch 2, wobei die besagten Stränge (18) Kettgarne sind, die in das Tragband (11) eingewebt oder eingewirkt sind.

4. Wasserdichter Reißverschluß (10) nach Anspruch 1, wobei das besagte Beschichtungsmaterial ein Polyurethankunststoff ist.

5. Wasserdichter Reißverschluß (10) nach Anspruch 1, wobei der besagte Füllkern (16) aus einem Fasermaterial gebildet ist, der eine hohe Wassersaugfähigkeit und Wasserrückhaltefähigkeit hat.

Patentansprüche

1. Wasserdichter Reißverschluß (10), umfassend zwei gegenüberliegend angeordnete Tragbänder (11), eine Reihe von Kuppelgliedern (12), die jeweils einen Kupplungskopf (12a), einen oberen Schenkel (12b), einen unteren Schenkel (12c) und einen Verbindungsbereich (12d) aufweisen und die mit Nähfäden (13) an einem inneren Längsrand eines jeden betreffenden Tragbandes (11) befestigt sind, und einen Füllkern (16) der sich durch die in der Reihe von Kuppelgliedern (12) begrenzten Hohlräume (17) erstreckt und der diese Hohlräume (17) mit Ausnahme des Bereichs der Kupplungsköpfe (12a) anfänglich ausfüllt, wobei das Tragband (11) auf einer Seite und entlang seinem Längsrand (14) mit einem wasserdichten Beschichtungsmaterial beschichtet ist, dadurch gekennzeichnet, daß der Kern (16) bei Berührung mit einer Flüssigkeit quellfähig ist und die besagten Zwischenräume (17) gegen das Eindringen der Flüssigkeit in das Innere des Gegenstandes, an dem der Reißverschluß (10) befestigt ist, vollständig ausfüllt.
2. Wasserdichter Reißverschluß (10) nach Anspruch 1, ferner umfassend mehrere das Wasser aufsaugende Stränge (18), die sich in gegenüberliegender Beziehung entlang jedem der besagten Längsränder (14) erstrecken.