

GARMENT AND BRASSIERE ACCESSORY

CROSS REFERENCE TO RELATED APPLICATION

[0001] This is a continuation application of U.S. Patent Application No. 12/778,212, filed on May 12, 2010, the disclosure of which is incorporated hereby in its entirety.

BACKGROUND OF THE INVENTION

[0002] This invention relates to women's garments, undergarments and brassieres, more particularly, a device that attaches to a brassiere and simulates a camisole or tank top and covers a user's chest area and/or cleavage, thereby allowing the user to wear short-cut tops and dresses in formal or any other situations that require a modest attire.

[0003] There are many environments, such as work, school, church, etc., where it is considered inappropriate for women to wear low short-cut tops or dresses that reveal too much cleavage. Many women own dresses and/or tops that are formal, but low cut. Therefore a woman can be very limited in her options with regard to clothes for work and so forth. Past attempts have been made to develop garments that attach to brassieres or prevent the low cut tops or dresses to cover exposed cleavage.

[0004] However, many of these garments do not attach securely to brassieres to ensure that the garments will not come loose and also do not fit snugly against a woman's chest. A further problem with past garments is that they are not adjustable and thus are not adaptable to different chest sizes and/or different sizes of brassieres. An even further problem with past garments is that some use securing means, such as adhesives, strings, bows, etc., to attach the garments to the brassiere or to the outer garment. These past securing means have been prone to failure due to the fact that securing means, such as adhesives, do not always adhere and do not allow a user to re-use the garment without applying new adhesive. Further, securing means, such as bows, show through the outer garment, thereby making it obvious that a woman is wearing a cleavage covering device that simulates a tank

top or camisole. An even further problem with past devices is that they do not attach to strapless brassieres.

[0005] Therefore, a need exists for an undergarment that securely attaches to a wearers brassiere, is adjustable to a woman's chest and/or bra size, gives the appearance of being an actual undergarment such as a tank-top, provides a re-usable securing means and can be worn even without a brassiere.

[0001] The relevant prior art includes the following references:

<u>Patent No.</u>	<u>Inventor</u>	<u>Issue/Publication Date</u>
(U.S. unless stated otherwise)		
2007/0281585	Calamari et al.	12-06-2007
4,955,846	Greenberg	09-11-1990

SUMMARY OF THE INVENTION

[0006] The primary object of the present invention are to provide a garment and brassiere accessory that securely attaches to a wearer's brassiere.

[0007] Another object of the present invention is to provide a garment and brassiere accessory that is adjustable to a woman's chest and/or bra size.

[0001] An even further object of the present invention is to provide a garment and brassiere accessory that gives the appearance of being an actual undergarment, such as a tank top.

[0008] Another object of the present invention is to provide a garment and brassiere accessory that provides a re-usable securing means.

[0009] An even further object of the present invention is to provide a garment and brassiere accessory that provides a securing means that is not visible through an outer garment.

[0010] Another object of the present invention is to provide a garment and brassiere accessory that fits securely against a woman's chest.

[0011] An even further object of the present invention is to provide a garment and brassiere

accessory that will attach to a strapless brassiere.

[0012] An additional object of the present invention is to provide a garment and brassiere accessory that allows attachment of jewelry to the garment.

[0013] An even further object of the present invention is to provide a garment and brassiere accessory that can be instantly taken on or off.

[0001] An additional object of the present invention is to provide a garment and brassiere accessory that can be worn without a brassiere.

[0014] The present invention fulfills the above and other objects by providing a garment and brassiere accessory that is substantially triangular in shape having a front surface, a rear surface, an upper edge, side edges, upper corners and a lower corner. Attachment straps extend outward from the upper corners. The attachment straps may be looped around the shoulder straps of a brassiere or in the case of a strapless brassiere, around the side straps of the brassiere. The attachment straps have securing means, such as snaps, buttons, hook and loop fastener, etc., located thereon. After looping the attachment straps around the shoulder straps of a brassiere, the securing means located on the attachment straps are secured to a corresponding securing means located along the upper edge of the garment and brassiere accessory. There may be a plurality of securing means located along the upper edge to allow a user to adjust the length of the loops made by the attachment straps and, thus, the width of the garment and brassiere accessory. A securing means is also located on the lower corner of the device. The lower corner may be looped around the center portion of a brassiere. After looping the lower corner around the center portion of a brassiere, the securing means located on the lower corner is secured to a corresponding securing means located on the rear side of the garment and brassiere accessory.

[0015] There may be a plurality of securing means located on the rear side of the garment and brassiere accessory to allow a user to adjust the length of the loop made by the lower corner and,

thus, the height of the garment and brassiere accessory.

[0016] An upper band of elastomeric material is located along the upper edge of the garment and brassiere accessory. The elastomeric material keeps the garment and brassiere accessory securely against a woman's chest while being worn. The garment and brassiere accessory is preferably constructed from two layers of material, an outer layer and an inner layer. An advantage of having multiple layers of material is that the outer layer hides the securing means as well as any wrinkles or indentations caused by the stress of the lower corner pulling on the inner layer while the garment and brassiere accessory is being worn.

[0017] Additional features of the present invention include extension straps that attach to the attachment straps and allow a user to adapt the garment and brassiere accessory to a larger chest and/or brassiere size. The extension straps may also be used so that a woman can still wear the garment and brassiere accessory without a brassiere. For example, a long extension strap that goes around the woman's back may be attached to the attachment straps of the garment and brassiere accessory. The garment and brassiere accessory may also include attachment means for attaching jewelry to the garment. The above and other objects, features and advantages of the present invention should become even more readily apparent to those skilled in the art upon a reading of the following detailed description in conjunction with the drawings wherein there is shown and described illustrative embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] In the following detailed description, reference will be made to the attached drawings in which:

FIG. 1 is a rear view of a garment and brassiere accessory of the present invention;

FIG. 2 is a rear view of a garment and brassiere accessory of the present invention attached to a brassiere;

FIG. 3 is a front view of a garment and brassiere accessory of the present invention attached to a brassiere;

FIG. 4 is a side cross sectional view along line 4-4 of **FIG. 3** of a garment and brassiere accessory of the present invention attached to a brassiere;

FIG. 5 is a front view of a garment and brassiere accessory of the present invention attached to a bikini top;

FIG. 6 is a front view of a garment and brassiere accessory of the present invention for use with strapless brassieres;

FIG. 8 is a front view of a garment and brassiere accessory of the present invention having jewelry attached thereto; and

FIG. 9 is a front view of a brassiere having jewelry attached thereto via extension straps of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0019] For purposes of describing the preferred embodiment, the terminology used in reference to the numbered components in the drawings is as follows:

- | | |
|------------------|---------------------|
| 1. body | 14. shoulder straps |
| 2. front surface | 15. side straps |
| 3. rear surface | 16. center portion |
| 4. upper edge | 17. outer layer |

- | | |
|---------------------|----------------------|
| 5. side edge | 18. inner layer |
| 6. upper corner | 19. indentation |
| 7. lower corner | 20. extension strap |
| 8. attachment strap | 21. jewelry |
| 9. securing means | 22. attachment means |
| 10. snap | 23. bikini top |
| 11. upper band | 24. linking means |
| 12. lower band | 25. first end |
| 13. brassiere | 26. second end |

[0020] With reference to **FIG. 1**, a rear view of a garment and brassiere accessory of the present invention is shown. The garment and brassiere accessory comprises a body **1** that is substantially triangular in shape. The body **1** comprises a front surface **2** (as shown in **FIG. 3**), a rear surface **3**, an upper edge **4**, side edges **5**, upper corners **6** and a lower corner **7**. Attachment straps **8** extend outward from the upper corners **6**. A plurality of securing means **9**, such as snaps **10**, buttons, hook and loop fasteners, hook and eye fasteners, etc., are located along the upper edge **4** of the garment and brassiere accessory and attachment straps **8**. Also, a securing means **9** is also located on the lower corner **7** of the garment and brassiere accessory. In addition, a plurality of securing means **9** are located on the rear surface **3** of the garment and brassiere accessory directly above the lower corner **7**. An upper band **11** preferably having elastomeric qualities is located along the upper edge **4** of the garment and brassiere accessory. The upper band **11** keeps the garment and brassiere accessory securely against a woman's chest while being worn. A lower band **12** preferably having elastomeric qualities is located on the rear surface **3** of the garment and brassiere accessory and provides reinforcement for the securing means **9** that are located on the rear surface **3** of the garment and brassiere accessory directly above the lower corner **7**.

[0021] With reference to **FIGS. 2 and 3**, a rear view and a front view of a garment and brassiere accessory of the present invention attached to a brassiere **13**, respectively, are shown. To secure the garment and brassiere accessory to a brassiere **13**, the attachment straps **8** are looped around shoulder straps **14** of the brassiere **13** or in the case of a strapless brassiere, looped around or looped under and over side straps **15** of the brassiere **13**. The attachment straps **8** are then secured to the upper edge **4** of the garment and brassiere accessory by attaching the securing means **9** located on the attachment straps **8**, which as shown here are snaps **10**, to corresponding securing means **9** located along the upper edge **4** of the garment and brassiere accessory. Then the lower corner **7** is looped around a center portion **16** of the brassiere **13**. The lower corner **7** is then secured to the rear surface **3** of the garment and brassiere accessory by attaching the securing means **9** located on the lower corner **7** to corresponding securing means **9** located along the rear surface **3** of the garment and brassiere accessory.

[0022] With reference to **FIG. 4**, a side cross sectional view along line 4-4 of **FIG. 3** of a garment and brassiere accessory of the present invention attached to a brassiere **13** is shown. The garment and brassiere accessory is preferably constructed from two layers of material, an outer layer **17** and an inner layer **18**, both preferably made of a stretchable cloth-like material. An advantage of having an outer layer **17** and an inner layer **18** is that the outer layer **17** hides the securing means **9** as well as any wrinkles or indentations **19** caused by the stress of the lower corner **7** pulling downward on the inner layer **17** while the garment and brassiere accessory is being worn.

[0023] With reference to **FIG. 5**, a front view of a garment and brassiere accessory of the present invention attached to a bikini top **23** is shown. The garment and brassiere accessory is worn with the rear surface **3** facing outward when worn on a bikini top **23**. To secure the garment and brassiere accessory to the bikini top **23**, the attachment straps **8** are looped around shoulder straps

14 of the bikini top 23. The attachment straps 8 are then secured to the upper edge 4 of the garment and brassiere accessory by attaching the securing means 9 located on the attachment straps 8, which as shown here are decorative snaps 23, to corresponding securing means 9 located along the upper edge 4 of the garment and brassiere accessory. Then the lower corner 7 is looped around a center portion 16 of the bikini top 23. The lower corner 7 is then secured to the rear surface 3 of the garment and brassiere accessory by attaching the securing means 9 located on the lower corner 7 to corresponding securing means 9 located along the rear surface 3 of the garment and brassiere accessory. A decorative piece of jewelry 21 is attached to the securing means 9 located on the lower corner 7.

[0024] With reference to **FIG. 6**, a front view of a garment and brassiere accessory of the present invention for use with strapless brassieres. The garment and brassiere accessory comprises a body 1 that is substantially rectangular in shape. The body 1 comprises a front surface 2, a rear surface 3, an upper edge 4, side edges 5, upper corners 6 and lower corners 7. Attachment straps 8 extend outward from the upper corners 6. Securing means 9, such as snaps 10, buttons, hook and loop fasteners, hook and eye fasteners, etc., are located on the attachment straps 8. The attachment straps 8 are used in conjunction with an extension strap 20 that allows a user to secure the upper edge 4 of the garment and brassiere accessory around the user's back. Also, attachment straps 8 having securing means 9 extend downward from the lower corners 7 of the garment and brassiere accessory. In addition, securing means 9 are located on the rear surface 3 of the garment directly above the lower corners 7. The attachment straps 8 located on the lower corners 7 may be looped around or looped under and over side straps 15 of the brassiere 13. An upper band 11 preferably having elastomeric qualities is located along the upper edge 4 of the garment and brassiere accessory. The upper band 11 keeps the garment and brassiere accessory securely against a woman's chest while being worn.

[0025] In another embodiment, an extension strap 20 of the present invention is shown. The extension strap 20 can be made in various lengths or sizes. The extension strap 20 has securing means 9 located on opposite ends that attach to the securing means 9 located on the garment and brassiere accessory allow a user to adapt the garment and brassiere accessory to a larger chest and/or brassiere 13 size. Extension straps 20 may also be used so that a woman can still wear the garment and brassiere accessory without a brassiere 13. For example, a long extension strap 20 may be attached to the attachment straps 8 of the garment and brassiere accessory and be worn around the back of a user.

[0026] With reference to FIG. 8, a front view of a garment and brassiere accessory of the present invention having jewelry 21 attached thereto is shown. The garment and brassiere accessory may have an attachment means 22, such as loops, hooks, clasps, etc., that allow a user to attach a piece of jewelry 21 or a plurality of linking means 24, such as a rope, ribbon, wire, chain, pearls, beads, etc., having a first end 25 and a second end 26, to the garment and brassiere accessory or directly to a brassiere. The attachment means 22 are preferably located near the upper corners 6 of the garment and brassiere accessory.

[0027] Finally with reference to FIG. 9, a front view of a brassiere 13 having jewelry 21 attached thereto via extension straps 20 of the present invention is shown. Jewelry 21 or a plurality of linking means 24, such as a rope, ribbon, wire, chain, pearls, beads, etc., having a first end 25 and a second end 26, is attached to the brassiere 13 by looping the extension straps 20 around the shoulder straps 14 of the brassiere 13 and through the an attachment means 22, which as shown here are rings.

[0028] It is to be understood that while a preferred embodiment of the invention is illustrated, it is not to be limited to the specific form or arrangement of parts herein described and shown. It will be apparent to those skilled in the art that various changes may be made without departing from the scope of the invention and the invention is not be considered limited to what is shown and described in the specification and drawings.

CLAIMS

What is claimed is:

1. A garment and brassiere accessory comprising:
a body having a front surface, a rear surface, an upper edge, at least two side edges, and at least two upper corners and at least one lower corner;
at least one fastener located along the upper edge;
at least one fastener located on the rear surface;
at least one attachment strap extending from each of the at least two upper corners, the attachment strap having a proximal portion overlapping the body and a distal portion extending away from the body; and
a plurality of fasteners located on the proximal portion of the attachment strap and at least one fastener located on the distal portion of the attachment strap.
2. The garment and brassiere accessory of claim 1 further comprising:
an upper band located along the upper edge of the body.
3. The garment and brassiere accessory of claim 2 wherein:
said upper band has elastomeric qualities.
4. The garment and brassiere accessory of claim 1 further comprising:
a lower band located on the rear surface of the body.
5. The garment and brassiere accessory of claim 4 wherein:

said lower band has elastomeric qualities.

6. The garment and brassiere accessory of claim 1 wherein:
the body further comprises at least one outer layer and at least one inner layer.

7. The garment and brassiere accessory of claim 1 further comprising:
an extension strap for extending the length of the at least one attachment strap.

8. The garment and brassiere accessory of claim 1 further comprising:
an attachment portion for attaching a piece of jewelry to the garment and brassiere
accessory.

9. The garment and brassiere accessory of claim 1 wherein:
the body further comprises at least one lower corner.

10. The garment and brassiere accessory of claim 9 further comprising:
at least one fastener located on the at least one lower corner.

11. A garment and brassiere accessory comprising:
a body having a front surface, a rear surface, an upper edge, at least two side edges, and
at least two upper corners;
at least one fastener located on the rear surface;
at least one attachment strap extending from each of the at least two upper corners, the
attachment strap having a proximal portion overlapping the body and a distal portion extending
away from the body; and

a plurality of fasteners located on the proximal portion of the attachment strap and at least one fastener located on the distal portion of the attachment strap;

wherein at least a portion of the body comprises at least one inner layer and at least one outer layer; and

the upper edge has elastomeric qualities.

12. The garment and brassiere accessory of claim 11 further comprising:
an upper band located along the upper edge of the body.

13. The garment and brassiere accessory of claim 12 wherein:
said upper band has elastomeric qualities.

14. The garment and brassiere accessory of claim 11 further comprising:
a lower band located on the rear surface of the body.

15. The garment and brassiere accessory of claim 14 wherein:
said lower band has elastomeric qualities.

16. The garment and brassiere accessory of claim 11 further comprising:
an extension strap for extending the length of the at least one attachment strap.

17. The garment and brassiere accessory of claim 11 further comprising:
an attachment portion for attaching a piece of jewelry to the garment and brassiere accessory.

18. A garment and brassiere accessory comprising:
a body having a front surface, a rear surface, an upper edge, at least two side edges, and at least two upper corners and at least one lower corner;
at least one fastener located along the upper edge;
at least one fastener located on the at least two side edges; and
at least one attachment strap extending from each of the at least two side edges, the attachment strap having a proximal portion overlapping the body and a distal portion extending away from the body.

19. The garment and brassiere accessory of claim 18, wherein at least a portion of the body comprises at least one inner layer and at least one outer layer.

20. The garment and brassiere accessory of claim 18, further comprising a plurality of fasteners located on the proximal portion of the attachment strap and at least one fastener located on the distal portion of the attachment strap.