



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: A62C 35/68	A1	(11) International Publication Number: WO 99/34872 (43) International Publication Date: 15 July 1999 (15.07.99)
(21) International Application Number: PCT/FI99/00007 (22) International Filing Date: 7 January 1999 (07.01.99) (30) Priority Data: 980034 9 January 1998 (09.01.98) ✓ FI (71)(72) Applicant and Inventor: SUNDHOLM, Göran [FI/FI]; Ilmari Kiannon kuja 3, FIN-04310 Tuusula (FI). (74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: HOLDER FOR MOUNTING A SPRAY HEAD**(57) Abstract**

The invention relates to a holder (1) for mounting a spray head for fire fighting, which holder comprises a body (8), a first end (9), a second end (10) and a passage (11) between the first and the second end for conducting extinguishing medium from the first end to the second end, for receiving the spray head at the second end of the body of the channel (17) in such a way that a housing (18) of the spray head is inserted into the channel, the first end being intended to receive a conduit (3) conducting extinguishing medium. For the purpose of preventing the extinguishing medium from flowing out of the conduit (3) leading to the spray head, when the spray head is detached from the holder (1), the holder comprises a displaceable element (12) mounted in the passage (11), which element can be displaced from a first position, in which the element closes the passage, to a second position, in which the element keeps the passage open, the element being arranged to be in the first position, when the spray head is not mounted, and to be displaced to the second position, when the spray head is being mounted to the holder. The invention also relates to a combination of a holder and a spray head.

