

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number
WO 2004/022920 A1

(51) International Patent Classification⁷: **F01D 1/08**,
25/00, H02P 9/14, H02K 17/42, F25B 11/02, 1/04, 1/053

(21) International Application Number:
PCT/AU2003/001144

(22) International Filing Date:
5 September 2003 (05.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
521263 6 September 2002 (06.09.2002) NZ
521717 30 September 2002 (30.09.2002) NZ
523733 21 January 2003 (21.01.2003) NZ
524220 17 February 2003 (17.02.2003) NZ

(71) Applicant and
(72) Inventor: **DRYSDALE, Kenneth, William, Patterson**
[AU/AU]; 8A Elm Avenue, Belrose, Sydney, NSW (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **EVES, Paul, Thomas** [AU/AU]; 2 Meadow Road, Watanobbi, NSW (AU). **CASEY, Robert, Thomas** [AU/AU]; 4 Jingara Place, Sylvania, NSW (AU).


(74) Agent: **BALDWIN SHELSTON WATERS**; P.O. Box 5999, Wellesley Street, Auckland (NZ).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: APPARATUS, METHOD AND SOFTWARE FOR USE WITH AN AIR CONDITIONING CYCLE



(57) Abstract: A turbine (21) for generating power includes a rotor (23) in a rotor chamber and at least one nozzle (22) for supplying a fluid to drive the rotor (23). The flow of the fluid from the nozzle exit (12) is periodically interrupted by at least one flow interrupter means (7, 11), thereby raising a pressure of the fluid inside the nozzle (22). Two such turbines (21) could be used in a thermodynamic cycle; the first turbine located downstream of a compressor and upstream of a heat exchanger and the second turbine located downstream of an evaporator and upstream of the compressor.



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments*

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*