

Description

The invention relates to a process for the removal of urea, ammonia and carbon dioxide from dilute aqueous solutions.

In the preparation of urea from ammonia and carbon dioxide a urea synthesis solution is formed at high temperature and at the pressure belonging to it, which solution still contains a substantial quantity of free ammonia and non-converted ammonium carbamate. The carbamate is decomposed, in one or more pressure steps, into ammonia and carbon dioxide, which are driven off, for the larger part, with the free ammonia present, and usually recirculated. In the final decomposition step an aqueous urea solution is obtained which still contains dissolved quantities of ammonia and carbon dioxide, which are subsequently removed by expansion to atmospheric or lower pressure. The aqueous urea solution is concentrated by evaporation and/or crystallization and further processed. During the evaporation a gas mixture is formed containing, beside water vapour, entrained fine urea drops and ammonia and carbon dioxide.

Like the gas mixture separated out in the expansion of the urea solution after the final decomposition step, this gas mixture is condensed, and the so-called process condensate thus obtained is partly returned into the process for absorbing the gas mixture carried off from the final decomposition step. The remaining part is discharged. The process condensate also incorporates the water fed into the process as steam for operating the ejectors in the evaporation section, washing water, flushing water on the stuffing boxes of the carbamate pumps, etc. Per mole of urea one mole of water is formed. So in a urea plant with a capacity of 1500 tonnes of urea per day 450 tonnes of water is formed per day. In addition about 300 tonnes of water per day is fed in, so that per day roughly 750 tonnes of water in all must be carried off.

The 2—9% by weight of NH_3 , 0.8—6% by weight of CO_2 and 0.3—1.5% by weight of urea present in this water on the one side represent important quantities of raw materials and product and would, on the other side, load the surface water into which this waste water would be discharged to a degree no longer permitted by the governments in many countries. It is therefore necessary, before the discharge, to remove the larger part of the ammonia and the urea.

To this end the process condensate can be subjected to a treatment described in Industrial Wastes, September/October 1976 pages 44—47, in which treatment the process condensate already freed by desorption at low pressure of part of the ammonia and carbon dioxide is passed at higher pressure into the bottom of a reaction column and is heated herein by means of steam fed likewise to the bottom, owing to which urea will hydrolyze. The solution thus obtained is carried off from the top of the reaction column. In addition to a small quantity of non-hydrolyzed

urea, it contains ammonia and carbon dioxide, which are removed, after expansion of the solution to the said low pressure, in a second desorption column by stripping with steam. The gas mixture thus separated off is used as stripping medium in the first desorption step. The bottom product of the second desorption column is discharged after heat exchange with the process condensate to be treated. Under practical circumstances this waste flow then still contains about 50 ppm NH_3 and 50 ppm urea. Also with very long residence times, for which inefficiently large reaction columns would be required, it is impossible to reach a urea content lower than 20—25 ppm.

Now, the object of the invention is to provide a process by means of which both the ammonia content and the urea content of dilute aqueous solutions can be reduced to lower than 10 ppm. To this end a combination of features is applied comprising:

1. The urea-containing solution which is subjected to the hydrolysis treatment contains amounts of ammonia and carbon dioxide which have been reduced as far as possible.

2. The urea-containing solution is countercurrently contacted with an inert gas that provides the heat required for the hydrolysis and simultaneously acts as stripping agent, so that the ammonia and carbon dioxide resulting from the hydrolysis reaction are expelled from the solution.

3. The gaseous mixture containing ammonia and carbon dioxide thus obtained in the hydrolysis is discharged as soon as it is formed. So, the invention relates to a process for the removal of urea, ammonia and carbon dioxide from dilute aqueous solutions comprising removal of ammonia and carbon dioxide in a pre-desorption zone at a pressure of 1—5 bar, hydrolysis of urea in a reaction column at a pressure of at least 10 bar while supplying heat followed by desorption of ammonia and carbon dioxide from the aqueous solution discharged from the reaction column. The process is characterized in that the solution obtained in the pre-desorption zone is passed at a pressure of up to 30 bar into the top of a reaction column and is caused to flow downward therein countercurrently to a gas stream the heat content of which is sufficient to maintain in the top of the reaction column a temperature of between 170 and 220°C and in the bottom of the reaction column a temperature of between 180 and 230°C, a gas mixture containing ammonia, carbon dioxide and water vapour is carried off from the top of the reaction column and a substantially urea-free aqueous solution of ammonia and carbon dioxide is discharged from the bottom of the reaction column, and subsequently, at a pressure of 1—5 bar, ammonia and carbon dioxide are removed from the solution discharged from the reaction column. The ammonia and carbon dioxide must be removed from the solution to be treated to such a degree that in the bottom zones of the reaction column, where the

252 kg CO₂ and 829 kg water vapour and which is a temperature of 181°C, and subsequently with 5562 kg gas mixture from desorption column 6, the composition of which was: 421 kg NH₃, 5 kg CO₂ and 5136 kg water vapour and the temperature of which was 136°C. Via the top of column 4 2293 kg NH₃, 1720 kg CO₂ and 2528 kg water vapour were carried off. This gas mixture was condensed completely and of the solution thus obtained, which has a temperature of 54°C, part, consisting of 876 kg NH₃, 657 kg CO₂ and 966 kg H₂O, was returned as reflux into the desorption column. The remaining part, which contained, beside 1562 kg H₂O, 1417 kg NH₃ and 1063 kg CO₂, was returned to the urea plant.

So in the pre-desorption step already 75% of the original quantity of NH₃ had been removed.

Beside 30,349 kg water, the desorbed solution contained 310 kg NH₃, 31 kg CO₂ and 319 kg urea, was brought by means of pump 9 to a pressure of 12.26 bar and passed, after heating from 135°C to 183°C in heat exchanger 10, into the top of reaction column 5. The quantity of steam passed into the bottom of this reaction column was 1700 kg, its temperature was 225°C and the pressure 24.5 bar. The urea present in the feed was hydrolyzed almost completely to NH₃ and CO₂. A gas mixture with the said composition was carried out and expanded from 14.7 bar to 3.43 bar.

The bottom product from the reaction column consisted of 31,127 kg water, 419 kg NH₃ and 6 kg CO₂ and was used for pre-heating the feed stream of the reaction column, in which process the temperature fell from 193°C to 146°C. By expansion in the top of description column 6, the pressure was lowered again to 3.43 bar, in which process the temperature further decreased to 136°C. In this desorption column this solution was stripped with 5000 kg steam of 147°C. In this process the said 5562 kg gas mixture was formed, which was passed into the bottom of the pre-desorption column. The water carried off from the bottom of desorption column 6 was used first for pre-heating the process condensate to be treated, in which treatment the temperature fell from 139°C to 63°C, and was subsequently cooled with cooling water to 40°C, upon which it was carried off. It contained 6 ppm NH₃ and 8 ppm urea.

Claims

1. Process for the removal of urea, ammonia and carbon dioxide from dilute aqueous solutions comprising removal of ammonia and carbon dioxide in a pre-desorption zone at a pressure of 1—5 bar, hydrolysis of urea in a reaction column at a pressure of at least 10 bar while supplying heat followed by desorption of ammonia and carbon dioxide from the aqueous solution discharged from the reaction column, characterized in that the solution obtained in the pre-desorption zone is passed at a pressure of up to 30 bar into the top of the reaction column and caused to flow downward therein countercurrently to an inert gas stream the heat content of which is sufficient

to maintain in the top of the reaction column a temperature of between 170 and 220°C and in the bottom of the reaction column a temperature of between 180 and 230°C, a gas mixture containing ammonia, carbon dioxide and water vapour is carried off from the top of the reaction column and a substantially urea-free aqueous solution of ammonia and carbon dioxide is discharged from the bottom of the reaction column, and subsequently, at a pressure of 1—5 bar, ammonia and carbon dioxide are removed from the solution discharged from the reaction column.

2. Process according to claim 1, characterized in that in the reaction column steam is used as the said gas stream.

3. Process according to claim 2, characterized in that steam with a pressure of 15—42 bar is used.

4. Process according to any one of the claims 1—3, characterized in that ammonia and carbon dioxide are removed from the solution carried off from the bottom of the reaction column by countercurrently stripping with steam.

5. Process according to any one of the claims 1—4, characterized in that the solution to be fed to the reaction column is pre-heated by heat exchange with the solution carried off from the bottom of the reaction column.

6. Process according to any one of the claims 1—5, characterized in that, after expansion to a pressure of 1—5 bar, the gas mixture carried off from the top of the reaction column is passed into the pre-desorption zone.

7. Process according to any one of the claims 1—6, characterized in that the gas mixture containing the ammonia and carbon dioxide separated from the solution carried off from the bottom of the reaction column is passed into the pre-desorption zone.

8. Process according to any one of the claims 1—7, characterized in that the gas mixture carried off from the pre-desorption is condensed and the dilute aqueous solution of ammonia and carbon dioxide thus obtained is worked-up, at least in part, in the preparation of urea.

Patentansprüche

1. Verfahren zum Entfernen von Harnstoff, Ammoniak und Kohlendioxid aus verdünnten wässrigen Lösungen, bestehend aus dem Entfernen von Ammoniak und Kohlendioxid in einer Vor-desorptionszone bei einem Druck von 1—5 bar, Hydrolyse von Harnstoff in einer Reaktionsssäule bei einem Druck von mindestens 10 bar, unter Zuführung von Wärme mit nachfolgender Desorption von Ammoniak und Kohlendioxid aus der wässrigen Lösung, die aus der Reaktionskolonne abgeführt wurde, dadurch gekennzeichnet, dass die in der Vordesorptionszone erhaltene Lösung bei einem Druck bis zu 30 bar oben in die Reaktionskolonne eingeführt wird und hierin im Gegenstrom zu einem Inertgasstrom nach unten fließt, dessen Wärme ausreicht, im Kopf der Reaktionskolonne eine Temperatur zwischen 170 und 220°C und am Boden der Reaktionskolonne

11

252 kg CO₂ and 829 kg water vapour and which is a temperature of 181°C, and subsequently with 5562 kg gas mixture from desorption column 6, the composition of which was: 421 kg NH₃, 5 kg CO₂ and 5136 kg water vapour and the temperature of which was 136°C. Via the top of column 4 2293 kg NH₃, 1720 kg CO₂ and 2528 kg water vapour were carried off. This gas mixture was condensed completely and of the solution thus obtained, which has a temperature of 54°C, part, consisting of 876 kg NH₃, 657 kg CO₂ and 966 kg H₂O, was returned as reflux into the desorption column. The remaining part, which contained, beside 1562 kg H₂O, 1417 kg NH₃ and 1063 kg CO₂, was returned to the urea plant.

So in the pre-desorption step already 75% of the original quantity of NH₃ had been removed.

Beside 30,349 kg water, the desorbed solution contained 310 kg NH₃, 31 kg CO₂ and 319 kg urea, was brought by means of pump 9 to a pressure of 12.26 bar and passed, after heating from 135°C to 183°C in heat exchanger 10, into the top of reaction column 5. The quantity of steam passed into the bottom of this reaction column was 1700 kg, its temperature was 225°C and the pressure 24.5 bar. The urea present in the feed was hydrolyzed almost completely to NH₃ and CO₂. A gas mixture with the said composition was carried out and expanded from 14.7 bar to 3.43 bar.

The bottom product from the reaction column consisted of 31,127 kg water, 419 kg NH₃ and 6 kg CO₂ and was used for pre-heating the feed stream of the reaction column, in which process the temperature fell from 193°C to 146°C. By expansion in the top of description column 6, the pressure was lowered again to 3.43 bar, in which process the temperature further decreased to 136°C. In this desorption column this solution was stripped with 5000 kg steam of 147°C. In this process the said 5562 kg gas mixture was formed, which was passed into the bottom of the pre-desorption column. The water carried off from the bottom of desorption column 6 was used first for pre-heating the process condensate to be treated, in which treatment the temperature fell from 139°C to 63°C, and was subsequently cooled with cooling water to 40°C, upon which it was carried off. It contained 6 ppm NH₃ and 8 ppm urea.

Claims

1. Process for the removal of urea, ammonia and carbon dioxide from dilute aqueous solutions comprising removal of ammonia and carbon dioxide in a pre-desorption zone at a pressure of 1—5 bar, hydrolysis of urea in a reaction column at a pressure of at least 10 bar while supplying heat followed by desorption of ammonia and carbon dioxide from the aqueous solution discharged from the reaction column, characterized in that the solution obtained in the pre-desorption zone is passed at a pressure of up to 30 bar into the top of the reaction column and caused to flow downward therein countercurrently to an inert gas stream the heat content of which is sufficient

to maintain in the top of the reaction column a temperature of between 170 and 220°C and in the bottom of the reaction column a temperature of between 180 and 230°C, a gas mixture containing ammonia, carbon dioxide and water vapour is carried off from the top of the reaction column and a substantially urea-free aqueous solution of ammonia and carbon dioxide is discharged from the bottom of the reaction column, and subsequently, at a pressure of 1—5 bar, ammonia and carbon dioxide are removed from the solution discharged from the reaction column.

2. Process according to claim 1, characterized in that in the reaction column steam is used as the said gas stream.

3. Process according to claim 2, characterized in that steam with a pressure of 15—42 bar is used.

4. Process according to any one of the claims 1—3, characterized in that ammonia and carbon dioxide are removed from the solution carried off from the bottom of the reaction column by countercurrently stripping with steam.

5. Process according to any one of the claims 1—4, characterized in that the solution to be fed to the reaction column is pre-heated by heat exchange with the solution carried off from the bottom of the reaction column.

6. Process according to any one of the claims 1—5, characterized in that, after expansion to a pressure of 1—5 bar, the gas mixture carried off from the top of the reaction column is passed into the pre-desorption zone.

7. Process according to any one of the claims 1—6, characterized in that the gas mixture containing the ammonia and carbon dioxide separated from the solution carried off from the bottom of the reaction column is passed into the pre-desorption zone.

8. Process according to any one of the claims 1—7, characterized in that the gas mixture carried off from the pre-desorption is condensed and the dilute aqueous solution of ammonia and carbon dioxide thus obtained is worked-up, at least in part, in the preparation of urea.

Patentansprüche

1. Verfahren zum Entfernen von Harnstoff, Ammoniak und Kohlendioxid aus verdünnten wässrigen Lösungen, bestehend aus dem Entfernen von Ammoniak und Kohlendioxid in einer Vor-desorptionszone bei einem Druck von 1—5 bar, Hydrolyse von Harnstoff in einer Reaktionssäule bei einem Druck von mindestens 10 bar, unter Zuführung von Wärme mit nachfolgender Desorption von Ammoniak und Kohlendioxid aus der wässrigen Lösung, die aus der Reaktionskolonne abgeführt wurde, dadurch gekennzeichnet, dass die in der Vordesorptionszone erhaltene Lösung bei einem Druck bis zu 30 bar oben in die Reaktionskolonne eingeführt wird und hierin im Gegenstrom zu einem Inertgasstrom nach unten fließt, dessen Wärme ausreicht, im Kopf der Reaktionskolonne eine Temperatur zwischen 170 und 220°C und am Boden der Reaktionskolonne



(12)

eine Temperatur von 180 bis 230°C aufrechtzuerhalten, vom Kopf der Reaktionskolonne ein Ammoniak, Kohlendioxid und Wasserdampf enthaltendes Gasgemisch und vom Boden der Reaktionskolonne eine im wesentlichen harstofffreie wässrige Lösung von Ammoniak und Kohlendioxid abgeführt werden und anschließend bei einem Druck von 1—5 bar aus der aus der Reaktionskolonne abgeführten Lösung Ammoniak und Kohlendioxid entfernt werden.

2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, dass der Gasstrom in der Reaktionskolonne Dampf ist.

3. Verfahren nach Anspruch 2, dadurch gekennzeichnet, dass Dampf mit einem Druck von 15—42 bar verwendet wird.

4. Verfahren nach Anspruch 1 bis 3, dadurch gekennzeichnet, dass aus der aus dem Boden der Reaktionskolonne abgeführten Lösung Ammoniak und Kohlendioxid durch Strippen mit Dampf im Gegenstrom entfernt werden.

5. Verfahren nach Anspruch 1 bis 4, dadurch gekennzeichnet, dass die der Reaktionskolonne zuzuführende Lösung durch Wärmeaustausch mit der aus dem Boden der Kolonne abgeführten Lösung vorerwärmt wird.

6. Verfahren nach Anspruch 1 bis 5, dadurch gekennzeichnet, dass das aus dem Kopf der Reaktionskolonne abgeführte Gasgemisch nach Expansion auf einen Druck von 1—5 bar in die Vordesorptionszone eingeleitet wird.

7. Verfahren nach Anspruch 1 bis 6, dadurch gekennzeichnet, dass das aus der Bodenlösung der Reaktionskolonne abgeschiedene ammoniak- und kohlendioxidhaltige Gasgemisch in die Vordesorptionszone eingeführt wird.

8. Verfahren nach Anspruch 1 bis 7, dadurch gekennzeichnet, dass das aus der Vordesorption abgeführte Gasgemisch kondensiert und die so anfallende verdünnte wässrige Lösung aus Ammoniak und Kohlendioxid wenigstens teilweise bei der Harnstoffherzeugung aufgearbeitet wird.

Revendications

1. Procédé d'élimination d'urée, d'ammoniac et de dioxyde de carbone de solutions aqueuses diluées comportant l'élimination d'ammoniac et de dioxyde de carbone dans une zone de prédésorption à une pression de 1 à 5 bars, l'hydrolyse d'urée dans une colonne de réaction à une pression d'au moins 10 bars, tout en apportant la chaleur et la désorption de l'ammoniac et du

dioxyde de carbone de la solution aqueuse évacuée de la colonne de réaction, caractérisé en ce que la solution obtenue dans la zone de prédésorption est introduite à une pression jusqu'à 30 bars en haut de la colonne de réaction et est amenée à s'y écouler vers le bas à contre-courant d'un courant gazeux, la chaleur de ce courant gazeux étant suffisante pour maintenir en haut de la colonne de réaction une température comprise entre 170 et 220°C et en bas de la colonne de réaction une température comprise entre 180 et 230°C, alors que du sommet de la colonne, on évacue un mélange de gaz contenant de l'ammoniac, du dioxyde de carbone et de la vapeur d'eau et que du fond de la colonne, on évacue une solution aqueuse d'ammoniac et de dioxyde de carbone, pratiquement exempte d'urée, et qu'ensuite on élimine de cette solution, évacuée du fond de la colonne, l'ammoniac et le dioxyde de carbone à une pression de 1 à 5 bars.

2. Procédé selon la revendication 1, caractérisé en ce que le courant de gaz dans la colonne de réaction est de la vapeur.

3. Procédé selon la revendication 2, caractérisé en ce qu'on utilise de la vapeur ayant une pression de 15—42 bars.

4. Procédé selon l'une des revendications 1 à 3, caractérisé en ce qu'on élimine de la solution évacuée du fond de la colonne de réaction l'ammoniac et le dioxyde de carbone par entraînement à la vapeur à contre-courant.

5. Procédé selon l'une des revendications 1 à 4, caractérisé en ce que la solution à amener à la colonne de réaction est préchauffée par échange de chaleur avec la solution évacuée du fond de la colonne de réaction.

6. Procédé selon l'une des revendications 1 à 5, caractérisé en ce que le mélange de gaz évacué du sommet de la colonne de réaction est détendu jusqu'à une pression de 1—5 bars et puis introduit dans la zone de prédésorption.

7. Procédé selon l'une des revendications 1 à 6, caractérisé en ce que le mélange de gaz contenant de l'ammoniac et du dioxyde de carbone, qui est séparé de la solution de fond de la colonne de réaction, est introduit dans la zone de prédésorption.

8. Procédé selon l'une des revendications 1 à 7, caractérisé en ce que le mélange de gaz évacué de la prédésorption est condensé et que la solution aqueuse diluée d'ammoniac et de dioxyde de carbone ainsi obtenue est traitée au moins partiellement lors de la préparation d'urée.



* C L M S *