

【DESCRIPTION】

【Invention Title】

WASHING MACHINE

【Technical Field】

5 Embodiments of the present disclosure relate to a washing machine, and more particularly, to a washing machine provided with an improved wire connection structure capable of electrically connecting electrical components.

【Background Art】

 Generally, a washing machine is a device configured to wash laundry by
10 rotating a rotating tub of a cylindrical shape, which accommodates the laundry and washing water. The washing machine includes a drum washing machine in which a rotating tub is horizontally disposed and configured to raise upward laundry along an inner circumferential surface thereof and drop the laundry downward when the rotating tub is rotated in forward and reverse directions about a horizontal axis,
15 thereby washing the laundry; and a vertical washing machine in which a rotating tub provided with a pulsator therein is vertically arranged and configured to wash laundry using a water stream generated by the pulsator when the rotating tub is rotated in forward and reverse directions about a vertical axis.

 The drum washing machine may include a cabinet configured to form an
20 exterior, a cylindrical tub installed inside the cabinet and configured to accommodate washing water, a drum rotatably installed inside the tub and configured to wash laundry, a drive motor disposed in rear of the tub and configured to rotate the drum, and a door installed at a front surface of the cabinet. An opening communicating

with the drum is provided at the cabinet, and the door is able to open and close the opening.

Generally, electrical components are disposed inside the cabinet. However, while washing machines having various designs are realized, there is a case in which
5 electrical components disposed inside the cabinet and electrical components disposed at an outside of the cabinet are electrically connected using a wire.

【Disclosure】

【Technical Problem】

According to one aspect of the present disclosure, there is provided a washing
10 machine with an improved structure capable of electrically connecting electrical components inside a door and electrical components inside a cabinet.

According to another aspect of the present disclosure, there is provided a washing machine with an improved structure capable of connecting electrical components inside a door and electrical components inside a cabinet using a wire
15 without hindering an aesthetic exterior of the washing machine.

According to still another aspect of the present disclosure, there is provided a washing machine with an improved structure capable of allowing a wire to pass through a hinge assembly to electrically connect electrical components inside a door and electric components inside a cabinet.

20 **【Technical Solution】**

A washing machine according to the spirit of the present disclosure may include a first electrical component; a cabinet configured to form an exterior and having an opening through which laundry is introduced; a door provided with a

second electrical component and configured to open and close the opening; a wire configured to electrically connect the first electrical component and the second electrical component; and a hinge configured to couple the door to the cabinet to allow the door to be pivotable about a rotating axis, and having a wire guide portion
5 configured to guide the wire.

The second electrical component may be provided inside the door.

The door may be pivotable about a single rotation axis.

The wire guide portion may be formed and recessed into the hinge to allow the wire to be insertable into the wire guide portion.

10 The wire guide portion may be formed to pass through the hinge.

The hinge may include a hinge body coupled to the cabinet; and at least one hinge arm extending from the hinge body and at which the wire guide portion is formed.

The at least one hinge arm may include a first surface facing the cabinet, and
15 the wire guide portion may be formed and recessed along at least a portion of the first surface.

The at least one hinge arm may include a second surface that is directed downward in a rotating axis direction, and the wire guide portion may be formed and recessed along at least a portion of the second surface.

20 The hinge may further include at least one protrusion that is formed to protrude from the at least one hinge arm in a rotating axis direction to form the rotating axis.

The at least one protrusion may include a first protrusion formed to protrude upward from the at least one hinge arm in the rotating axis direction; and a second portion formed to protrude downward from the at least one hinge arm in the rotating axis direction, wherein a wire inlet may be formed on at least one of the first
5 protrusion and the second protrusion to allow the wire to enter the wire guide portion.

A wire outlet may be formed at one surface of the hinge body, which faces the cabinet, to allow the wire to exit from the wire guide portion.

A through-hole may be formed at one surface of the cabinet to which the hinge body is coupled, and the wire exiting from the wire outlet may pass through
10 the through-hole to enter the cabinet.

The hinge may include a hinge cover detachably coupled to the wire guide portion to prevent the wire, which is inserted into the wire guide portion, from being exposed to the outside.

The hinge may include a hinge body coupled to the cabinet; and at least one
15 hinge arm extending from the hinge body toward a front side of the washing machine, wherein the wire guide portion may be formed to pass through the hinge body.

A washing machine according to the spirit of the present disclosure may include a cabinet configured to form an exterior and having an opening through which laundry is introduced; a door provided to open and close the opening; a hinge
20 configured to pivotably couple the door to the cabinet; and a wire passing through the hinge, wherein one end portion of the wire may be positioned inside the door, and the other end portion thereof may include a wire that is positioned inside the cabinet.

A first electrical component may be provided inside the cabinet, a second electrical component may be provided inside the door, and the wire may electrically connect the first electrical component and the second electrical component.

5 A wire guide portion, through which the wire passes, may be formed and recessed into the hinge.

A wire guide portion, through which the wire passes, may be formed at the hinge and may pass therethrough.

The hinge may include a hinge body coupled to the cabinet; and at least one hinge arm extending from the hinge body and at which a wire guide portion through
10 which the wire passes is formed.

The at least one hinge arm may include a first arm extending from the hinge body toward a front side of the washing machine; and a second arm extending from the first arm and bent toward an outside of the washing machine, wherein the wire guide portion may be formed and recessed along at least one of one surface of the
15 first arm and one surface of the second arm.

The wire guide portion may be consecutively formed and recessed along at least one of the one surface of the first arm and the one surface of the second arm.

The door may be pivotable about a single rotating axis, and the hinge may further include at least one protrusion that is formed to protrude from the at least one
20 hinge arm in a rotating axis direction to form the rotating axis.

The at least one hinge arm may include a first arm extending from the hinge body toward a front side of the washing machine; and a second arm extending from the first arm and bent toward outside the washing machine, wherein the at least one

protrusion may be formed to protrude from the second arm in the rotating axis direction.

A wire inlet may be formed on at least one of the protrusions to allow the wire to enter the wire guide portion.

5 A wire outlet may be formed at one surface of the hinge body, which faces the cabinet, to allow the wire to exit from the wire guide portion.

The hinge may include a hinge cover detachably coupled to the wire guide portion to prevent the wire, which is inserted into the wire guide portion, from being exposed to the outside.

10 A washing machine according to the spirit of the present disclosure may include a cabinet having an opening through which laundry is introduced; a door provided with an electrical component and provided to open and close the opening; a wire electrically connected to the electrical component; and a hinge configured to couple the door to the cabinet and having a wire guide portion through which the
15 wire passes.

The door may be pivotable about a single rotation axis.

【Advantageous Effects】

While the electric components provided inside the door and the electric components provided inside the cabinet are connected by the wire, the wire is
20 allowed to pass through the hinge such that the wire can be prevented from being significantly exposed to the outside.

The wire is inserted into the wire guide portion formed at the hinge such that the wire can pass through the hinge in a simple and easy manner.

The wire cover is coupled to the wire guide portion such that foreign materials can be prevented from flowing into the wire guide portion.

The wire cover detachably coupled to the wire guide portion is used and thus, while the wire is inserted into the wire guide portion, a work may be performed in a state in which the wire cover is removed such that work efficiency can be improved, and, when the wire is inserted into the wire guide portion, the wire cover is coupled to the wire guide portion such that the wire can be stably accommodated in a wire accommodating space.

【Description of Drawings】

FIG. 1 is one exemplified diagram illustrating a state in which a display is applied to a washing machine according to one embodiment of the present disclosure.

FIG. 2 is another exemplified diagram illustrating a state in which a light emitting portion is applied to the washing machine according to one embodiment of the present disclosure.

FIG. 3 is a perspective view illustrating a state in which a door of the washing machine according to one embodiment of the present disclosure is open.

FIG. 4 is an exploded perspective view illustrating a coupling relationship between the door and a hinge of the washing machine according to one embodiment of the present disclosure.

FIG. 5 is an enlarged diagram of a part of FIG. 4.

FIG. 6 is a diagram illustrating FIG. 5 when viewed at a different angle.

FIG. 7 is an exploded perspective view illustrating a hinge according to a first example in the washing machine according to one embodiment of the present disclosure.

FIG. 8 is an exploded perspective view illustrating the hinge according to the first example shown in FIG. 7 when viewed at a different angle in the washing machine according to one embodiment of the present disclosure.

FIG. 9 is a diagram illustrating a coupling structure of the hinge according to the first example in the washing machine according to one embodiment of the present disclosure.

FIG. 10 is a diagram schematically illustrating a connection state of a wire in the washing machine according to one embodiment of the present disclosure.

FIG. 11 is a diagram schematically illustrating the connection state of the wire when viewed from a front side of a glass holder in the washing machine according to one embodiment of the present disclosure.

FIG. 12 is a diagram schematically illustrating the connection state of the wire when viewed from a rear side of the glass holder in the washing machine according to one embodiment of the present disclosure.

FIG. 13 is a diagram illustrating a coupling structure of a hinge according to a second example in the washing machine according to one embodiment of the present disclosure.

FIG. 14 is a diagram illustrating a coupling structure of a hinge according to a third example in the washing machine according to one embodiment of the present disclosure.

FIG. 15 is a diagram illustrating a coupling structure of a hinge according to a fourth example in the washing machine according to one embodiment of the present disclosure.

FIG. 16 is an exploded perspective view illustrating a hinge according to a fifth example in the washing machine according to one embodiment of the present disclosure.

FIG. 17 is a diagram illustrating a coupling structure of the hinge according to the fifth example in the washing machine according to one embodiment of the present disclosure.

FIG. 18 is a diagram illustrating a coupling structure of a hinge according to a sixth example in the washing machine according to one embodiment of the present disclosure.

【Modes of the Invention】

It may be formed to extend from a front surface of a hinge body 110 by a predetermined length.

At least one hinge arm 120 may further include a second arm 122 extending from a first arm 121 and bent toward an outside of a washing machine 1.

According to another aspect, the at least one hinge arm 120 may include a first surface 123. The first surface 123 may face a cabinet 10. Specifically, the first surface 123 may face a front surface of the cabinet 10.

The at least one hinge arm 120 may further include a second surface 124. The second surface 124 may be directed downward in a rotating axis direction X.

The at least one hinge arm 120 may further include a third surface 125. The third surface 125 may be directed upward in the rotating axis direction X.

The at least one hinge arm 120 may further include a fourth surface 126. The fourth surface 126 may face a door 20.

5 The second surface 124 and the third surface 125 may respectively connect the first surface 123 and the fourth surface 126. Specifically, the second surface 124 may connect a lower end portion of the first surface 123 and a lower end portion of the fourth surface 126. The third surface 125 may connect an upper end portion of the first surface 123 and an upper end portion of the fourth surface 126.

10 A hinge 100 may further include at least one protrusion 130. The at least one protrusion 130 may be formed to protrude from the at least one hinge arm 120 in the rotating axis direction X. The at least one protrusion 130 may form a rotating axis 195.

15 The at least one protrusion 130 may include a first protrusion 131 and a second protrusion 132. The first protrusion 131 may be formed to protrude upward from the at least one hinge arm 120 in the rotating axis direction X. The second protrusion 132 may be formed to protrude downward from the at least one hinge arm 120 in the rotating axis direction X. Specifically, the first protrusion 131 may be formed to protrude upward from one end of the second arm 122 in the rotating axis
20 direction X, and the second protrusion 132 may be formed to protrude downward from one end of the second arm 122 in the rotating axis direction X. That is, the first protrusion 131 and the second protrusion 132 may respectively extend upward and downward from the second arm 122 in the rotating axis direction X.

The hinge 100 may further include a wire guide portion 140 configured to guide a wire 400.

The wire guide portion 140 may be formed at the hinge 100. The wire guide portion 140 may be formed and recessed into the hinge 100 to allow the wire 400 to
5 pass through the wire guide portion 140. In other words, the wire guide portion 140 may be formed and recessed into the hinge 100 to allow the wire 400 to be inserted into the wire guide portion 140.

The wire guide portion 140 may be formed at the at least one hinge arm 120. The wire guide portion 140 may be formed and recessed along at least one of one
10 surface of the first arm 121 and one surface of the second arm 122. The wire guide portion 140 may be consecutively formed and recessed along the at least one of one surface of the first arm 121 and one surface of the second arm 122.

The wire guide portion 140 may be formed and recessed along at least a portion of the first surface 123.

15 The hinge 100 may further include a wire inlet 150. The wire inlet 150 may be formed to communicate with the wire guide portion 140 to allow the wire 400 to enter the wire guide portion 140. The wire inlet 150 may be formed on at least one of the at least one protrusion 130. That is, the wire inlet 150 may be formed on at least one of the first protrusion 131 and the second protrusion 132. Preferably, the
20 wire inlet 150 may be formed at the second protrusion 132.

The hinge 100 may further include a wire outlet 160. The wire outlet 160 may be formed at one surface 112 of the hinge body 110, which faces the cabinet 10, to allow the wire 400 to exit from the wire guide portion 140. The wire outlet 160

may be formed to communicate with the wire guide portion 140 to allow the wire 400 to exit from the wire guide portion 140.

The hinge 100 may further include a hinge cover 170. The hinge cover 170 may be detachably coupled to the wire guide portion 140. The hinge cover 170
5 may serve to prevent foreign materials from flowing into the wire guide portion 140. Also, the hinge cover 170 may serve to prevent the wire 400 inserted into the wire guide portion 140 from being exposed to the outside. The hinge cover 170 may be detachably coupled to the wire guide portion 140 and form a portion of an exterior of the hinge 100. Thus, the hinge cover 170 detachably coupled to the wire guide
10 portion 140 is used, and thus, while the wire 400 is inserted into the wire guide portion 140, a work may be performed in a state in which the hinge cover 170 is removed such that work performance may be improved, and, when the wire 400 has been inserted into the wire guide portion 140, the hinge cover 170 is coupled to the wire guide portion 140 such that the wire 400 may be stably accommodated in the
15 wire guide portion 140.

The hinge cover 170 may include a cover body 171.

The hinge cover 170 may further include at least one coupling rib 172. The at least one coupling rib 172 may extend from the cover body 171. Preferably, the at least one coupling rib 172 may include a first coupling rib 172a extending upward
20 from the cover body 171 in the rotating axis direction X and a second coupling rib 172b extending downward from the cover body 171 in the rotating axis direction.

The at least one coupling rib 172 may be coupled to at least one coupling recess 127 formed at the at least one hinge arm 120. The at least one coupling rib

172 may be fitted into and coupled to the at least one coupling recess 127. The at least one coupling recess 127 may be formed on a plane the same as one surface of the at least one hinge arm 120, at which the wire guide portion 140 is formed. As one example, when the wire guide portion 140 is formed at the first surface 123 of the at least one hinge arm 120, the at least one coupling recess 127 may also be formed at the first surface 123 of the at least one hinge arm 120.

The hinge cover 170 may further include at least one support rib 173. The at least one support rib 173 may extend from the cover body 171. The at least one support rib 173 may be hooked and coupled to one surface of the at least one hinge arm 120. The at least one support rib 173 may include a bent portion 174 with a bent shape to allow the hinge cover 170 to be coupled to the wire guide portion 140. As one example, when the wire guide portion 140 is formed at the first surface 123 of the at least one hinge arm 120, the at least one support rib 173 may extend downward from the cover body 171 in the rotating axis direction X, and, at this point, the bent portion 174 may be hooked and coupled to the second surface 124 of the at least one hinge arm 120. As another example, when the wire guide portion 140 is formed at the first surface 123 of the at least one hinge arm 120, the at least one support rib 173 may extend upward from the cover body 171 in the rotating axis direction X, and, at this point, the bent portion 174 may be hooked and coupled to the third surface 125 of the at least one hinge arm 120.

The hinge cover 170 may be stably coupled to the wire guide portion 140 by the at least one coupling rib 172 and the at least one support rib 173.

One end portion of the hinge cover 170 may form the wire inlet 150 in association with the at least one protrusion 130. Specifically, the at least one protrusion 130 may include an incised portion 175, and one end portion of the hinge cover 170 may be coupled to the incised portion 175 to form the wire inlet 150 in association with the at least one protrusion 130.

The other end portion of the hinge cover 170 may form a part of the wire outlet 160. In other words, the other end portion of the hinge cover 170 may form the wire outlet 160 in association with the hinge body 110.

The hinge 100 may further include at least one protrusion cover 180. The at least one protrusion cover 180 may be coupled to enclose the at least one protrusion 130. The at least one protrusion cover 180 may be detachably coupled to the at least one protrusion 130 to prevent abrasion or damage of the at least one protrusion 130 serving as the rotating axis 195.

The washing machine 1 may further include a fixing ring 190 coupled to the at least one protrusion 130. The fixing ring 190 may be coupled to enclose the at least one protrusion 130 from the outside. The fixing ring 190 may be coupled to the at least one protrusion 130 at which the wire inlet 150 is formed. The fixing ring 190 may have a cylindrical shape with an open bottom. However, the shape of the fixing ring 190 is not limited to the describe above, and may be variously modified. The fixing ring 190 may simultaneously enclose at least one protrusion forming the wire inlet 150 and one end portion of the hinge cover 170. The at least one protrusion 130 and the one end portion of the hinge cover 170 may be firmly coupled by the fixing ring 190.

The at least one hinge arm 120 may include a first hinge arm 128 positioned downward in the rotating axis direction X, and a second hinge arm 129 positioned upward in the rotating axis direction X. As shown in FIGS. 7 to 9, the wire guide portion 140 of the hinge 100 according to the first example may be formed at the first
5 hinge arm 128. Specifically, the wire guide portion 140 of the hinge 100 according to the first example may be formed and recessed into the first surface 123 of the first hinge arm 128.

FIG. 10 is a diagram schematically illustrating a connection state of a wire in the washing machine according to one embodiment of the present disclosure, and
10 FIG. 11 is a diagram schematically illustrating the connection state of the wire when viewed from a front side of a glass holder in the washing machine according to one embodiment of the present disclosure. FIG. 12 is a diagram schematically illustrating the connection state of the wire when viewed from a rear side of the glass holder in the washing machine according to one embodiment of the present
15 disclosure. In FIG. 10, the wire 400 disposed inside the washing machine 1 is illustrated by a solid line to help understanding of the present disclosure.

As shown in FIGS. 10 to 12, the wire 400 may pass through the hinge 100. Specifically, one end portion of the wire 400, which passes through the hinge 100, may be positioned inside the door 20, and the other end portion of the wire 400,
20 which passes through the hinge 100, may be positioned inside the cabinet 10.

The wire 400 may be electrically connected to an electrical component. In other words, the wire 400 may electrically connect a first electrical component 200 and a second electrical component 300.

The wire 400 may include a first wire 410 and a second wire 420 connected to the first wire 410. The first wire 410 may pass through the hinge 100 to be connected to the second wire 420. One end portion of the first wire 410 may be connected to the second electrical component 300 provided inside the door 20, and
5 the other end portion of the first wire 410 may be connected to the second wire 420. In other words, the first wire 410 and the second wire 420 may be connected to each other through coupling between a connector 411 provided at the other end portion of the first wire 410 and a connector 421 provided at a one end portion of the second wire 420. The coupling between the first wire 410 and the second wire 420 may be
10 made inside the cabinet 10. The second wire 420 may include a main wire harness.

While the first electrical component 200 and the second electrical component 300 are connected, at least a portion of the wire 400 may be disposed along a circumferential direction of the door 20. As one example, at least a portion of the wire 400 positioned inside the door 20 may be disposed along a circumferential
15 direction of the door 20.

A through-hole 10a (See, FIG. 4) may be formed at the cabinet 10. Specifically, the through-hole 10a may be formed at one surface of the cabinet 10 to which the hinge body 110 is coupled, that is, at the front surface of the cabinet 10. The wire 400 passing through the hinge 100 may pass through the through-hole 10a
20 to enter the cabinet 10.

The wire 400 connected to the second electrical component 300 reaches the hinge 100, and the wire 400 reaching the hinge 100 passes through the hinge 100 to be connected to the first electrical component 200 provided inside the cabinet 10.

In other words, the one end portion of the wire 400 may be connected to the second electrical component 300, and the other end portion thereof may pass through the hinge 100 to be connected to the first electrical component 200. As described above, since the first electrical component 200 and the second electrical component 300 may be electrically connected by the wire 400 passing through the hinge 100, it may be prevented that most of the wire 400 is exposed to the outside to hinder an aesthetic beauty of the washing machine 1.

The wire 400 connected to the second electrical component 300 provided at the door 20 reaches the hinge 100 along the circumferential direction of the door 20. The wire 400 reaching the hinge 100 is inserted into the wire guide portion 140 through the wire inlet 150. The wire 400 inserted into the wire guide portion 140 passes through the wire outlet 160 and the through-hole 10a, which is provided at the one surface of the cabinet 10 to correspond to the wire outlet 160, to exit inside the cabinet 10. The wire 400 exiting from the cabinet 10 is connected to the first electrical component 200 provided inside the cabinet 10.

FIG. 13 is a diagram illustrating a coupling structure of a hinge according to a second example in the washing machine according to one embodiment of the present disclosure. Hereinafter, a description overlapping with that of the hinge 100 according to the first example will be omitted.

As shown in FIG. 13, a wire guide portion 540 of a hinge 500 according to a second example may be formed at the second hinge arm 129 positioned upward in the rotating axis direction X. Specifically, the wire guide portion 540 of the hinge

500 according to the second example may be formed and recessed into the first surface 123 of the second hinge arm 129.

FIG. 14 is a diagram illustrating a coupling structure of a hinge according to a third example in the washing machine according to one embodiment of the present disclosure. Hereinafter, a description overlapping with that of the hinge 100 according to the first example will be omitted.

As shown in FIG. 14, a wire guide portion 640 may be formed to pass through a hinge 600. In other words, the wire guide portion 640 may be formed at the hinge 600 in a form of a hole to allow the wire 400 to pass through the wire guide portion 640.

Specifically, the wire guide portion 640 may be formed to pass through the at least one hinge arm 120. The wire guide portion 640 may be formed to pass through the at least one hinge arm 120 in a direction approximately perpendicular to the rotating axis 195. The wire inlet 150 may be formed at the fourth surface 126 of the at least one hinge arm 120. The wire outlet 160 may be formed at the one surface 112 of the hinge body 110, which faces the cabinet 10. The wire inlet 150 and the wire outlet 160 may be formed to communicate with the wire guide portion 640.

FIG. 14 illustrates a case in which the wire guide portion 640 is formed at the first hinge arm 128, but the wire guide portion 640 may be formed on at least one of the first hinge arm 128 and the second hinge arm 129.

FIG. 15 is a diagram illustrating a coupling structure of a hinge according to a fourth example in the washing machine according to one embodiment of the present

disclosure. Hereinafter, a description overlapping with that of the hinge 100 according to the first example will be omitted.

As shown in FIG. 15, a wire guide portion 740 may be formed to pass through a hinge 700. In other words, the wire guide portion 740 may be formed at
5 the hinge 700 in a form of a hole to allow the wire 400 to pass through the wire guide portion 740.

Specifically, the wire guide portion 740 may be formed to pass through the hinge body 110. The wire guide portion 740 may be formed to pass through the hinge body 110 in a direction approximately perpendicular to the rotating axis 195.
10 The wire inlet 150 may be formed at one surface 113 of the hinge body 110, which faces the door 20. The wire outlet 160 may be formed at the one surface 112 of the hinge body 110, which faces the cabinet 10. The wire inlet 150 and the wire outlet 160 may be formed to communicate with the wire guide portion 740.

FIG. 15 illustrates a case in which the wire guide portion 740 is formed below
15 the first hinge arm 128, but the wire guide portion 740 may be formed between the first hinge arm 128 and the second hinge arm 129, or over the second hinge arm 129.

FIG. 16 is an exploded perspective view illustrating a hinge according to a fifth example in the washing machine according to one embodiment of the present disclosure, and FIG. 17 is a diagram illustrating a coupling structure of the hinge
20 according to the fifth example in the washing machine according to one embodiment of the present disclosure. Hereinafter, a description overlapping with that of the hinge 100 according to the first example will be omitted.

As shown in FIGS. 16 and 17, a wire guide portion 840 may be formed and recessed into a hinge 800 to allow the wire 400 to be inserted into the wire guide portion 840. Specifically, the wire guide portion 840 may be formed and recessed into the at least one hinge arm 120.

5 The wire guide portion 840 may be formed and recessed along at least a portion of the second surface 124 of the at least one hinge arm 120, wherein the at least a portion is directed downward in the rotating axis direction X.

 The wire inlet 150 may be formed at the at least one protrusion 130. Specifically, the at least one protrusion 130 may include the incised portion 175, and
10 the one end portion of the hinge cover 170 may be coupled to the incised portion 175 to form the wire inlet 150 in association with the at least one protrusion 130.

 The wire outlet 160 may be formed at the one surface 112 of the hinge body 110, which faces the cabinet 10, to allow the wire 400 to exit from the wire guide portion 840.

15 The wire inlet 150 and the wire outlet 160 may be formed to communicate with the wire guide portion 840.

 The hinge 800 may further include an additional wire outlet 841. The additional wire outlet 841 may be formed at a side surface of the hinge body 110. Specifically, the additional wire outlet 841 may be formed at one side surface of the
20 hinge body 110, which is directed to the rotating axis 195. The additional wire outlet 841 may also be formed to communicate with the wire guide portion 840.

 The wire 400 is inserted into the wire inlet 150 to be directed upward in the rotating axis direction X. The wire 400 inserted into the wire inlet 150 is moved

toward an inside of the cabinet 10 in a direction approximately perpendicular to the rotating axis direction X. In other words, the wire 400 inserted into the wire inlet 150 is moved toward the inside of the cabinet 10 along one surface of the second arm 122. Thereafter, the wire 400 is moved toward the rear side of the washing machine 1. In other words, the wire 400 is moved toward the rear side of the washing machine 1 along one side of the first arm 121. The wire 400, which is moved toward the rear side of the washing machine 1 along the one side of the first arm 121, may pass through the wire outlet 160 or the additional wire outlet 841 to enter the cabinet 10. After the wire 400 is inserted into the wire guide portion 840, the hinge cover 170 may be detachably coupled to the wire guide portion 840.

As shown in FIGS. 16 and 17, the wire guide portion 840 may be formed and recessed into the first hinge arm 128. Specifically, the wire guide portion 840 may be formed and recessed along at least a portion of the second surface 124 of the first hinge arm 128.

FIG. 18 is a diagram illustrating a coupling structure of a hinge according to a sixth example in the washing machine according to one embodiment of the present disclosure. Hereinafter, descriptions overlapping with those of the hinge 100 according to the first example and the hinge 800 according to the fifth example will be omitted.

As shown in FIG. 18, a wire guide portion 940 of a hinge 900 may be formed and recessed into the second hinge arm 129. Specifically, the wire guide portion 940 may be formed and recessed along at least a portion of the second surface 124 of the second hinge arm 129.

Hereinbefore, specific embodiments are shown and described. However, the present disclosure is not limited to these specific embodiments, and various modified embodiments can be devised from those skilled in the art without departing from the gist of a technical spirit that is defined by the appended claims.

【CLAIMS】

【Claim 1】

A washing machine comprising:

a first electrical component;

5 a cabinet configured to form an exterior and having an opening through
which laundry is introduced;

a door provided with a second electrical component and configured to open
and close the opening;

10 a wire configured to electrically connect the first electrical component and the
second electrical component; and

a hinge configured to couple the door to the cabinet to allow the door to be
pivotable about a rotating axis, and having a wire guide portion configured to guide
the wire.

【Claim 2】

15 The washing machine of claim 1, wherein the second electrical component is
provided inside the door.

【Claim 3】

The washing machine of claim 1, wherein the door is pivotable about a single
rotation axis.

20 **【Claim 4】**

The washing machine of claim 1, wherein the wire guide portion is formed and recessed into the hinge to allow the wire to be insertable into the wire guide portion.

【Claim 5】

5 The washing machine of claim 1, wherein the wire guide portion is formed to pass through the hinge.

【Claim 6】

 The washing machine of claim 1, wherein the hinge includes:
 a hinge body coupled to the cabinet; and
10 at least one hinge arm extending from the hinge body and at which the wire guide portion is formed.

【Claim 7】

 The washing machine of claim 6, wherein:
 the at least one hinge arm includes a first surface facing the cabinet, and
15 the wire guide portion is formed and recessed along at least a portion of the first surface.

【Claim 8】

 The washing machine of claim 6, wherein:
 the at least one hinge arm includes a second surface that is directed
20 downward in a rotating axis direction, and
 the wire guide portion is formed and recessed along at least a portion of the second surface.

【Claim 9】

The washing machine of claim 6, wherein the hinge further includes at least one protrusion that is formed to protrude from the at least one hinge arm in a rotating axis direction to form the rotating axis.

【Claim 10】

5 The washing machine of claim 9, wherein the at least one protrusion includes:
a first protrusion formed to protrude upward from the at least one hinge arm in the rotating axis direction; and

a second portion formed to protrude downward from the at least one hinge arm in the rotating axis direction,

10 wherein a wire inlet is formed on at least one of the first protrusion and the second protrusion to allow the wire to enter the wire guide portion.

【Claim 11】

The washing machine of claim 10, wherein a wire outlet is formed at one surface of the hinge body, which faces the cabinet, to allow the wire to exit from the
15 wire guide portion.

【Claim 12】

The washing machine of claim 11, wherein:

a through-hole is formed at one surface of the cabinet to which the hinge body is coupled, and

20 the wire exiting from the wire outlet passes through the through-hole to enter the cabinet.

【Claim 13】

The washing machine of claim 1, wherein the hinge includes a hinge cover detachably coupled to the wire guide portion to prevent the wire, which is inserted into the wire guide portion, from being exposed to the outside.

【Claim 14】

- 5 The washing machine of claim 1, wherein the hinge includes:
- a hinge body coupled to the cabinet; and
- at least one hinge arm extending from the hinge body toward a front side of the washing machine,
- wherein the wire guide portion is formed to pass through the hinge body.