CLAIMS

What is claimed is:

1. A connector fitting for fluid handling comprising:

a coupling leg defining a bore that extends therethrough, said coupling leg and said bore being concentric about a leg axis, said coupling leg including a neck portion, a shoulder portion extending distal to said neck portion, a threaded portion extending distal to said shoulder portion, and a nipple portion extending distal to said threaded portion, said neck portion including locking features extending radially outward therefrom; and

a nut threadably engaged with said threaded portion of the coupling leg,

wherein said coupling leg and said nut are made of a melt processible resin.

2. The connector fitting of claim 1, wherein said locking features include a plurality of protrusions that are distributed about said leg axis at uniform angular intervals, and optionally a flange portion concentric about the respective leg axis and extending radially outward from the neck portion.

3. The connector fitting of claim 2, wherein each of said plurality of protrusions (i) extend distally from said flange portion and proximally from said shoulder portion, (ii) include opposing flat sides that face tangentially about said leg axis and a flat top that faces radially outward from said leg axis, or (iii) both (i) and (ii).

4. The connector fitting of claim 1, wherein said locking features include a flange extending radially outward from said neck portion and a plurality of partitions extending distally from said flange, said flange and said plurality of partitions cooperating to define a plurality of pockets.

5. The connector fitting of claim 1, wherein said locking features include a plurality of spacers on opposing sides of the neck portion, said spacers extending orthogonal to said leg axis and including first and second opposing ends, wherein said first opposing

ends of said plurality of spacers define a first plane, and said second opposing ends of said plurality of spacers define a second plane, said first plane and said second plane being parallel to each other and on opposing sides of said coupling leg.

6. A wrench for tightening the connector fitting of claim 2, the wrench comprising:

a first head having a body portion;

a first leg and a second leg extending in opposing directions from said body portion;

a first tooth that cooperates with the first leg to define a first notch on the first leg;

a second tooth that cooperates with the body portion to define a second notch on said body portion; and

an end boss defined at a distal end of said second leg,

wherein said first notch, said second notch, and said end boss are centered about a rotation axis.

7. A method of installing the connector fitting of claim 2, comprising:

providing at least one wrench of claim 6;

providing a set of installation instructions, said installation instructions comprising:

securing said connector fitting by bringing said first notch of the wrench into contact with a first of said plurality of protrusions, said second notch into contact with a second of said plurality of protrusions, and said boss end into contact with a third of said plurality of notches; and

tightening said nut onto said threaded portion of said coupling leg.

8. The connector fitting of claim 1, wherein the connector fitting is made from at least one of perfluoroalkoxy alkane (PFA), ethylene tetrafluoroethylene (ETFE), and fluorinated ethylene propylene (FEP).

9. A wrench for use with fittings used in fluid handling systems comprising:

a body,

at least two pins extending perpendicularly from the body, the pins dimensioned and configured to mate with at least two tubular portions disposed on the body of a fluid handling fitting, and optionally two opposing legs perpendicular to the body and the pins are opposingly distributed on the legs, dimensioned and configured to mate with at least one tubular portion on the fitting.

10. A wrench for use with fittings used in fluid handling systems comprising:

a body,

at least two opposing legs extending perpendicularly from the body, the legs comprising a first leg and a second leg dimensioned and configured such that the first leg is configured to engage a first end of a first spacer and the first end of a second spacer and the second leg is configured to engage the second end of the first spacer and the second end of the second spacer, said first spacer and said second spacer being disposed on the neck portion of a connector fitting.