



(51) International Patent Classification:
G02B 6/28 (2006.01) **G02B 6/293** (2006.01)

(21) International Application Number:
PCT/US2010/026750

(22) International Filing Date:
10 March 2010 (10.03.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/383,159 20 March 2009 (20.03.2009) US

(71) Applicant (for all designated States except US): **ALCATEL-LUCENT USA INC.** [US/US]; 600-700 Mountain Avenue, Murray Hill, NJ 07974-0636 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **DOERR, Christopher, Richard** [US/US]; 17 Johnson Terrace, Middletown, NJ 07748 (US).

(74) Agent: **MC CABE, John, F.**; Alcatel-Lucent USA Inc., Docket Administrator - Room 3D-201, 600-700 Mountain Avenue, Murray Hill, NJ 07974-0636 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: OPTICAL INTERLEAVERS AND DE-INTERLEAVERS

FIG. 1



(57) Abstract: An apparatus includes one or more optical de-interleavers. Each optical de-interleaver includes an optical component having a first pair of optical input and output ports and a second pair of optical input and output ports and a 1x2 optical coupler. Each optical output port of the optical component is optically connected to a corresponding optical port of the 1x2 optical coupler. The optical component is constructed to operate as a first optical filter for light propagating between the optical ports of the first pair and is constructed to operate as a second optical filter for light propagating between the optical ports of the second pair. The first and second optical filters have substantially regularly spaced and interleaved passbands.

