

9900724-7

20/02/99

**PUBLISHED
INTERNATIONAL APPLICATION**

WO 99/01616



159159



ACTION

Description

Track and process for aligning a rail track section

The invention relates to a track having a rail track section diverging from the usual basic course, in particular a stock rail altered in its course by being led away from a track center-line. The invention further relates to a process for aligning a rail track section to a course alteration purposefully diverging from the basic course of the track, in particular for providing a course alteration for avoidance of an abrading movement between wheels of rolling stock traversing the track and the rail track section by changing the wheel contact point on the rail.

An array for controlled guidance of a wheel axis or bogie of rolling stock traversing a switch is known from EP 0 295 573 B1. To permit a substantially pure rolling movement between the wheel and the rail in the transition area between stock rail and tongue, while ensuring optimum travel comfort, it is proposed that at least the course of a stock rail in the area of the switch diverges from the basic course such that the wheel contact point is influenced effectively for a purposeful alignment of the wheel axis/bogie axis to the track longitudinal axis or median between main and secondary track in such a way that an abrading movement between wheel and rail is largely avoided. The purposeful course alteration is preferably achieved in that the stock rail is led away from the track center-line.

The track center-line can here follow a straight or a curve if the switch itself is in the curve of a track. Depending on the curvature radius or length of the switch, the depth of the protrusion can be between 5 and 30 mm. Due to the minor divergence from the basic course, work must be with high precision to set the required course alteration and hence prevent an abrading movement between the wheel and the rail.

The problem underlying the present invention is to develop a track or process for aligning a rail track section of the type mentioned at the outset such that a precise alignment of the course of the rail track section can be checked with measures of simple design.

The problem is solved in accordance with the invention in that the rail track section has a cutout in the longitudinal direction of the track and parallel to the basic course of the latter whose course when the rail track section is arranged parallel to the basic course is inversely the same to the required course alteration.

In accordance with the invention, the rail track section to be subjected to a required course alteration is first aligned parallel to the basic course in order to then provide, for example by milling, a cutout such as a groove in the longitudinal direction, preferably in the rail head, and on that side opposite the running edge, the depth of which cutout varies depending on the required course alteration, namely following a curvature that runs opposite to that in the installed state of the rail track section. As a result of this, it is now necessary when installing the rail track section to have an alignment such that the cutout runs parallel to a measurement straight with its surface that is parallel to the running edge or rail web, the rail track section having undergone the required course alteration corresponding to the alignment of the reference surface of the cutout such as a groove bottom on a straight - or curve.

Since the cutout such as a groove has its greatest depth in the area of the required

maximum course alteration, there should then be no limiting wall on the running surface side when this cutout is provided in the rail head, so that rail material cannot break out. Additionally and in a particularly noteworthy embodiment of the design, this cutout should rise in the direction of the rail head running surface as the groove depth increases.

In particular when the cutout runs in a rail head side flank, it is provided that it starts at the beginning of the course alteration of the rail track section approximately 10 to 20 mm, preferably 12 to 16 mm, in particular approximately 14 mm below the rail head running surface. In the area of the maximum course alteration of the rail track section, the cutout should have, in its limiting wall parallel to the rail web, a distance to the rail head running surface of 5 to 5.5 mm, based on a maximum course alteration relative to a basic course in the form of a straight of 10 to 20 mm.

Accordingly, the cutout permitting in simple manner a check of the required course alteration should be a step machined, for example milled, out of the rail head flank, said step having a side limiting surface that is vertical to the rail web and whose bottom surface running vertical or nearly vertical to the side limiting surface extends as far as the upper side of the rail head.

The process for aligning a rail track section of the type described above is characterized in accordance with the invention by the following process steps:

- aligning of a rail track section parallel to the basic course,
- provision of a cutout in the rail track section, where the cutout runs with its bottom opposite to the required course alteration relative to the basic course,
- aligning of the section such that the cutout runs with its bottom parallel to the basic course, and

- fixing of the rail track section.

To permit simple checking as to whether the course alteration follows the required geometry, it is furthermore provided that along the rail track section a measurement straight is disposed parallel to the basic course, that the distance between the measurement straight and the cutout or its bottom running parallel to the central axis of the rail track section is measured for alignment of the rail track section to the required course alteration, and that the rail track section has the required course alteration when the distance between the measurement straight and the cutout or its bottom is constant over the entire length of the rail track section.

The following description and drawing show a preferred embodiment of the invention:

In the drawing,

Fig. 1 shows a rail track section aligned with a normal basic course,

Fig. 2 shows the rail track section according to Fig. 1, but with changed course alteration,

Fig. 3 shows a section along the line A-A in Fig. 1,

Fig. 4 shows a section along the line G-G in Fig. 1, and

Fig. 5 shows a section along the line S-S in Fig. 1.

According to EP 0 295 573 B1, the wheel contact point of rolling stock traversing a track

in the area of a switch can be influenced such that the stock rail undergoes a purposeful course alteration by being led away from the track center-line, thereby largely avoiding an abrading movement between wheel and rail. Appropriate course alterations can be in the range between 5 and 30 mm by protrusions in the stock rail. To ensure that the required course alteration of an appropriate rail track section such as a stock rail is precisely set, it is provided in the teachings in accordance with the invention that a rail track section 10 to be subjected to a course alteration is initially aligned parallel to the basic course, i.e. in particular to a straight. The corresponding rail track section 19 is shown in a plan view in Fig. 1. The rail foot 12, rail web 14 and rail head 15 with running surface 16 and its edges 18 and 20 can be seen. The edge 18 is the running edge in the installed state of the rail track section 10.

To permit inspection of whether the rail track section 10 with the course alteration in the installed track diverges to the required extent from the basic course, a groove or step in the longitudinal direction of the rail track section 10 is machined, for example milled, in the rail head 15 on the side of the edge 20 in its second flank 22, with the bottom surface 26 of such groove running parallel to the rail central axis, i.e. parallel to the web 14, being provided with a curved course such that when the rail track section 10 in the embodiment is curved outwards (upwards in the drawing) the groove bottom 26 is aligned parallel to the usual basic course, as made clear by Fig. 2. In other words, the groove bottom 26 or a corresponding reference line in the case of the rail track section 10 following the basic course and the running edge 18 in the case of the rail track section 10 following the required course alteration are mirror-symmetrical to a straight running parallel to the basic course.

In other words, the cutout 24, i.e. its bottom 26, has in the case of the rail track section 10 aligned with the basic course a geometry that is inversely the same as the curved course of

the rail track section 10 in accordance with Fig. 2.

If it is to be checked whether the rail track section 10 has the required course alteration, i.e. in a switch a stock rail has a protrusion outwards away from the switch tongue, all that is necessary is to arrange a measuring line parallel to the basic course and to check the distance between this line and the groove bottom 26. If the distance Y between the measuring line and the groove bottom 26 is equal, this ensures that the rail track section 10 has the required course alteration.

Since with increasing course alteration the depth of the groove 24 increases, it must be assured that the rail head does not break out in this area. It is therefore provided in accordance with the invention that the groove 24 rises towards the running surface 16 with increasing depth, as is made clear by the sectional views in Figs. 3 to 5.

For example, Fig. 3 shows a section through the rail track section 10 in the area of the basic course that is not changed even after bending of the rail track section 10. As Fig. 3 makes clear, the rail head 15 has a normal geometry.

Relative to the intersection of running surface 16 and flank 22, the groove or step 24 is milled at a distance X from the zero point NP thus formed, where with increasing groove depth the distance from the zero point NP decreases, as made clear in Figs. 4 and 5.

The distance T or V of the limiting surface 28 on the foot side vertical to the web 14 therefore decreases with increasing groove depth, while the distance U or W between side flank 22 and bottom 26 parallel to the web 14 from the rail head running surface increases.

ClaimsTrack and process for aligning a rail track section

1. A track having a rail track section (10) diverging from the usual basic course, in particular a stock rail altered in its course by being led away from a track center-line,-

wherein

{ the rail track section (10) has a cutout (24) in the longitudinal direction of the track and parallel to the basic course of the latter whose course when the rail track section is arranged parallel to the basic course is inversely the same as the required course alteration.

2. Track according to Claim 1,

wherein

the cutout (24) is a groove with groove side wall absent on the running surface side.

3. Track according to Claim 1 or Claim 2,

wherein

the cutout (24) rises with increasing groove depth (U, W) in the direction of the rail head running surface (16).

THIS SHEET HAS BEEN
REPLACED

4. Track according to at least one of the preceding claims,
w h e r e i n
the cutout (24) is arranged in the rail head side flank (22).
5. Track according to at least one of the preceding claims,
w h e r e i n
the rail head side flank (22) has the cutout (24) that is opposite to the running edge (18).
6. Track according to at least one of the preceding claims,
w h e r e i n
the cutout (24) starts at the beginning of the course alteration of the rail track section (10) approximately 10 to 20 mm, preferably 12 to 16 mm, in particular approximately 14 mm below the rail head running surface.
7. Track according to at least one of the preceding claims,
w h e r e i n
the cutout (24) in the area of the required maximum course alteration of the rail track section (10) runs at a distance below the rail head running surface of 5 to 5.5 mm with its side wall (28) vertical or substantially vertical to the rail web (14).
8. Track according to at least one of the preceding claims,
w h e r e i n
the cutout (24) is a step machined, for example milled, into the rail head flank (22).

9. Track according to at least one of the preceding claims;

wherein

the step (24) has a side limiting surface (28) that is vertical to the rail web (14) and a bottom surface (26) running parallel or nearly parallel to the rail web, said surface extending as far as the rail head running surface (16).

10. Process for aligning a rail track section to a course alteration purposefully diverging from the basic course of the track, in particular for providing a course alteration for avoidance of an abrading movement between wheels of rolling stock traversing the track and the rail track section by changing the wheel contact point on the rail

characterized by the process steps,

- aligning of a rail track section parallel to the basic course,
- provision of a cutout in the rail track section, where the cutout runs with its bottom opposite to the required course alteration relative to the basic course,
- aligning of the section such that the cutout runs with its bottom parallel to the basic course, and
- fixing of the rail track section.

THIS SHEET HAS BEEN
REPLACED

11. Process according to Claim 10,

w h e r e i n

along the rail track section a measurement straight is disposed parallel to the basic course, wherein the distance between the measurement straight and the cutout or its bottom running parallel to the central axis of the rail track section is measured for alignment of the rail track section to the required course alteration, and wherein the rail track section has the required course alteration when the distance between the measurement straight and the cutout or its bottom is constant over the entire length of the rail track section.