

Description

This invention relates to a strap retainer for retaining a strap, belt or the like in place on a substrate such as a bag, knapsack, garment, tent or the like.

There have been proposed numerous lash devices including strap retainers in which contrivances have been incorporated to reduce wearing of the sewn thread attaching the device to the substrate and to eliminate curling up of the edges of the device. A typical such device is disclosed in U. S. Patent 4,488,333 which provides a thin patch-like plate having a recessed attaching area defined between a raised peripheral border region and a plurality of projections and a uniform recessed underside defined by a continuous narrow peripheral marginal edge. While the thread sewn in the attaching area is protected by the projections against abrasive wear with an extraneous object, the portions of the thread that are exposed in the recessed underside are still liable to abrasive wear. Furthermore, with a thin flexible substrate, the thread sewn thereto through the underside of the plate urges the substrate to move inwardly of the marginal peripheral edge of the plate, resulting in a gap between the substrate and the plate which would in turn lead to curling up of the edge of the plate.

With the foregoing problems of the prior art in view, the present invention seeks to provide an improved strap retainer which is free from curling up or otherwise being deformed and which is capable of protecting the sewing thread against abrasive wear.

According to the present invention, there is provided a strap retainer for retaining a strap to a substrate, comprising a flexible plate adapted to be attached to the substrate and having a groove defined in an upper surface of said plate and extending along a peripheral edge of said plate for receiving therein a sewing thread, at least one retaining mound integral with said plate and raised above said upper surface of said plate so as to define therebetween a pair of laterally aligned apertures for the passage therethrough of the strap, and a support ridge projecting from a bottom surface of said plate and extending along said peripheral edge of said plate, characterized in that said support ridge is disposed inwardly of and immediately adjacent to said groove.

Many other advantages and features of the present invention will become manifest to those versed in the art upon making reference to the detailed description and the accompanying sheets of drawings in which preferred structural embodiments incorporating the principles of the present invention are shown by way of illustrative example

and in which like reference numerals refer to like or corresponding parts throughout the several views.

Figure 1 is a plan view of a strap retainer constructed in accordance with the principles of the invention;

Figure 2 is a cross-sectional view taken along the line II-II of Figure 1;

Figure 3 is a cross-sectional view taken along the line III-III of Figure 1;

Figure 4 is a bottom view of the strap retainer of Figure 1;

Figure 5 is a plan view of the strap retainer shown attached to a substrate;

Figure 6 is an enlarged cross-sectional view of a peripheral portion of the strap retainer shown in Figure 5;

Figure 7 is a plan view of a modified form of strap retainer embodying the invention;

Figure 8 is a cross-sectional view taken along the line XIII-XIII of Figure 7;

Figure 9 is a bottom view of the strap retainer of Figure 7;

Figure 10 is a plan view of the strap retainer of Figure 7 shown attached to a substrate; and

Figure 11 is an enlarged cross-sectional view of a peripheral portion of the strap retainer of Figure 7.

Referring now to the drawings and Figure 1 in particular, there is shown a strap retainer 10 embodying the invention which is made of a flexible material such as plastic or leather material and which is in the form of a thin square plate. The strap retainer or plate 10 has integral therewith a rectangular strap retaining mound 11 centrally disposed and oriented to define a triangular area with each of four corners of the square plate 10. The retaining mound 11 is slightly raised above the upper surface of the plate 10 to provide a pair of elongated parallel apertures 12 on opposite longitudinal sides of the mound 11 for the passage therethrough of a strap or belt indicated in broken lines at 13 in Figure 1.

A sewing groove 14 is formed in the upper surface of the plate 10 and extending continuously and closely along the peripheral edges of the plate 10 for receiving a thread 15 which secures the plate 10 to a substrate such as a garment fabric 16 as shown Figure 5, the groove 14 serving to protect the thread 15 from exposure to abrasive wear. The thread 15 being located closely adjacent to the marginal edges of the plate 10 holds the latter flat against the substrate 16 and against curling up.

Designated at 17 is a sewing groove which extends continuously around the peripheral edges of the rectangular mound 11 and which is adapted to receive a sewn thread 18 securing inner portions of the retainer 10 to the substrate 16.

Figure 4 shows the reverse side of the strap

retainer 10. The retainer 10 includes a plurality of support ridges 19 extending in parallel with the marginal edge lines of the retainer 10 and slightly protruding above the lower surface of the retainer 10. There is also provided a similar ridge 20 on the bottom surface of the plate 10 in surrounding relation to the peripheral edges of the retaining mound 11. The ridges 19 particularly with their corners 19' and together with the ridge 20 serve to hold the retainer 10 from slipping or otherwise moving relative to the substrate 16 during sewing attachment of the two parts that can thus be joined together in the proper intended position.

The outermost ridge 19a in particular is located immediately adjacent to but inwardly of the outermost sewing groove 14 as shown in Figures 2, 3 and 6, so that the thread 15 when sewn through the groove 14 anchors the substrate 16 against the ridge 19a and lies below the bottom face of the substrate to evade abrasive contact, as better shown in Figure 6.

The bottom peripheral edge portions 10' of the retainer 10 are rendered flat and smooth so that these edge portions can be held in intimate engagement with the substrate 16 without developing an objectionable gap therebetween.

Referring to Figure 7 - II inclusive, there is shown a modified form of strap retainer 21 which is rectangular in shape and generally similar to the retainer 10 except that it includes three retaining mounds 22, 23 and 24, the outer mounds 22 and 24 being of a similar size and the center mound 23 being somewhat narrower. The retainer 21 is substantially similar in construction and function to the retainer 10 already described. The support ridges 19 are interconnected by cross bars 25 at suitable intervals to provide multiple joints 26 which serve to hold the retainer 21 in place during sewing of the same to the substrate 16. The outermost ridge 19a is likewise located immediately adjacent to and inwardly of the sewing groove 14 as better shown in Figure 11 for reasons already advanced.

The shape of the retainer 10 or 21 may be circular, in which instance the ridges 19, 20 may be provided preferably in concentric relation to such a circular retainer.

Claims

1. A strap retainer (10; 21) for retaining a strap (13) to a substrate (16), comprising a flexible plate (10; 21) adapted to be attached to the substrate (16) and having a groove (14) defined in an upper surface of said plate and extending along a peripheral edge of said plate for receiving therein a sewing thread (15), at least one retaining mound (11; 22-24) integral with said plate (10; 21) and raised above said upper

surface of said plate so as to define therebetween a pair of laterally aligned apertures (12) for the passage therethrough of the strap (13), and a support ridge (19a) projecting from a bottom surface of said plate (10; 21) and extending along said peripheral edge of said plate, characterized in that said support ridge (19a) is disposed inwardly of and immediately adjacent to said groove (14).

2. A strap retainer according to claim 1, said plate (10; 21) further including at least one first ridge (19) disposed inwardly of and extending parallel with said support ridge (19a).
3. A strap retainer according to claim 2, said plate (10) further including a second ridge (20) disposed on said bottom surface thereof and extending in surrounding relation to said mound (11), said first and second ridges (19, 20) intersecting each other.
4. A strap retainer according to claim 2, said plate (21) further including a plurality of cross bars (25) extending between said support ridge (19a) and said first ridge (19).

Revendications

1. Dispositif de maintien de bande (10 ; 21) pour maintenir une bande (13) sur un substrat (16), comportant une plaque flexible (10 ; 21) adaptée pour être fixée au substrat (16) et ayant une rainure (14) définie dans une surface supérieure de ladite plaque et s'étendant le long d'un bord périphérique de ladite plaque pour recevoir à l'intérieur de celle-ci un fil à coudre (15), au moins une saillie de maintien (11 ; 22 à 24) faisant une seule pièce avec ladite plaque (10 ; 21) et s'élevant au-dessus de la surface supérieure de ladite plaque de façon à définir entre elles une paire d'ouvertures latéralement alignées (12) pour le passage à travers celles-ci de la bande (13) et une arête de support (19a) s'étendant depuis une surface inférieure de ladite plaque (10 ; 21) et s'étendant le long dudit bord périphérique de ladite plaque, caractérisé en ce que ladite arête de support (19a) est disposée vers l'intérieur de ladite rainure (14) et immédiatement adjacente à celle-ci.
2. Dispositif de maintien de bande selon la revendication 1, ladite plaque (10 ; 21) comportant de plus au moins une première arête (19) disposée à l'intérieur de ladite arête de support (19a) et s'étendant parallèlement à celle-ci.



retainer 10. The retainer 10 includes a plurality of support ridges 19 extending in parallel with the marginal edge lines of the retainer 10 and slightly protruding above the lower surface of the retainer 10. There is also provided a similar ridge 20 on the bottom surface of the plate 10 in surrounding relation to the peripheral edges of the retaining mound 11. The ridges 19 particularly with their corners 19' and together with the ridge 20 serve to hold the retainer 10 from slipping or otherwise moving relative to the substrate 16 during sewing attachment of the two parts that can thus be joined together in the proper intended position.

The outermost ridge 19a in particular is located immediately adjacent to but inwardly of the outermost sewing groove 14 as shown in Figures 2, 3 and 6, so that the thread 15 when sewn through the groove 14 anchors the substrate 16 against the ridge 19a and lies below the bottom face of the substrate to evade abrasive contact, as better shown in Figure 6.

The bottom peripheral edge portions 10' of the retainer 10 are rendered flat and smooth so that these edge portions can be held in intimate engagement with the substrate 16 without developing an objectionable gap therebetween.

Referring to Figure 7 - 11 inclusive, there is shown a modified form of strap retainer 21 which is rectangular in shape and generally similar to the retainer 10 except that it includes three retaining mounds 22, 23 and 24, the outer mounds 22 and 24 being of a similar size and the center mound 23 being somewhat narrower. The retainer 21 is substantially similar in construction and function to the retainer 10 already described. The support ridges 19 are interconnected by cross bars 25 at suitable intervals to provide multiple joints 26 which serve to hold the retainer 21 in place during sewing of the same to the substrate 16. The outermost ridge 19a is likewise located immediately adjacent to and inwardly of the sewing groove 14 as better shown in Figure 11 for reasons already advanced.

The shape of the retainer 10 or 21 may be circular, in which instance the ridges 19, 20 may be provided preferably in concentric relation to such a circular retainer.

Claims

1. A strap retainer (10; 21) for retaining a strap (13) to a substrate (16), comprising a flexible plate (10; 21) adapted to be attached to the substrate (16) and having a groove (14) defined in an upper surface of said plate and extending along a peripheral edge of said plate for receiving therein a sewing thread (15), at least one retaining mound (11; 22-24) integral with said plate (10; 21) and raised above said upper

surface of said plate so as to define therebetween a pair of laterally aligned apertures (12) for the passage therethrough of the strap (13), and a support ridge (19a) projecting from a bottom surface of said plate (10; 21) and extending along said peripheral edge of said plate, characterized in that said support ridge (19a) is disposed inwardly of and immediately adjacent to said groove (14).

2. A strap retainer according to claim 1, said plate (10; 21) further including at least one first ridge (19) disposed inwardly of and extending parallel with said support ridge (19a).
3. A strap retainer according to claim 2, said plate (10) further including a second ridge (20) disposed on said bottom surface thereof and extending in surrounding relation to said mound (11), said first and second ridges (19, 20) intersecting each other.
4. A strap retainer according to claim 2, said plate (21) further including a plurality of cross bars (25) extending between said support ridge (19a) and said first ridge (19).

Revendications

1. Dispositif de maintien de bande (10 ; 21) pour maintenir une bande (13) sur un substrat (16), comportant une plaque flexible (10 ; 21) adaptée pour être fixée au substrat (16) et ayant une rainure (14) définie dans une surface supérieure de ladite plaque et s'étendant le long d'un bord périphérique de ladite plaque pour recevoir à l'intérieur de celle-ci un fil à coudre (15), au moins une saillie de maintien (11 ; 22 à 24) faisant une seule pièce avec ladite plaque (10 ; 21) et s'élevant au-dessus de la surface supérieure de ladite plaque de façon à définir entre elles une paire d'ouvertures latéralement alignées (12) pour le passage à travers celles-ci de la bande (13) et une arête de support (19a) s'étendant depuis une surface inférieure de ladite plaque (10 ; 21) et s'étendant le long dudit bord périphérique de ladite plaque, caractérisé en ce que ladite arête de support (19a) est disposée vers l'intérieur de ladite rainure (14) et immédiatement adjacente à celle-ci.
2. Dispositif de maintien de bande selon la revendication 1, ladite plaque (10 ; 21) comportant de plus au moins une première arête (19) disposée à l'intérieur de ladite arête de support (19a) et s'étendant parallèlement à celle-ci.



3. Dispositif de maintien de bande selon la revendication 2, ladite plaque (10) comportant de plus une deuxième arête (20) disposée sur ladite surface inférieure de celle-ci et s'étendant autour de la saillie (11), lesdites première et deuxième arêtes (19, 20) se coupant mutuellement. 5
4. Dispositif de maintien de bande selon la revendication 2, ladite plaque (21) comportant de plus une pluralité d'entretoises (25) s'étendant entre ladite arête de support (19a) et ladite première arête (19). 10

Patentansprüche

1. Bandhalter (10;21) zum Festlegen eines Bandes (13) an einem Untergrund (16), umfassend eine flexible Platte (10;21), die an dem Untergrund (16) befestigbar ist und an der Oberseite eine Nut (14) aufweist, die sich längs des Umfangsrandes der Platte erstreckt, um einen Nähfaden (15) aufzunehmen, mindestens eine Befestigungserhebung (11;22-24), die mit der Platte (10;21) einstückig ist und über die besagte Oberseite der Platte vorspringt, um dazwischen zwei seitlich fluchtende Öffnungen (12) für den Durchtritt des Bandes (13) zu begrenzen, und eine Stützrippe (19a), die von der Unterseite der Platte (10;21) vorspringt und sich längs des besagten Umfangsrandes der Platte erstreckt, dadurch gekennzeichnet, daß die Stützrippe (19a) innerhalb und unmittelbar neben der Nut (14) angeordnet ist. 15
20
25
30
2. Bandhalter nach Anspruch 1, wobei die Platte (10;21) ferner mindestens eine erste Rippe (19) umfaßt, die innerhalb der Stützrippe (19a) angeordnet ist und parallel zu dieser verläuft. 35
40
3. Bandhalter nach Anspruch 2, wobei die Platte (10) ferner eine zweite Rippe (20) umfaßt, die an deren Unterseite angeordnet ist und die Befestigungserhebung (11) umgibt, wobei sich die ersten und zweiten Rippen (19,20) schneiden. 45
4. Bandhalter nach Anspruch 2, wobei die Platte (21) ferner mehrere Querstege (25) umfaßt, die sich zwischen der Stützrippe (19a) und der ersten Rippe (19) erstrecken. 50