



(51) International Patent Classification:

G01N 21/88 (2006.01) *G01B 11/00* (2006.01)
H01L 31/042 (2006.01) *G06T 7/00* (2006.01)

(21) International Application Number:

PCT/US2011/031951

(22) International Filing Date:

11 April 2011 (11.04.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/324,590 15 April 2010 (15.04.2010) US
13/047,587 14 March 2011 (14.03.2011) US

(71) Applicant (for all designated States except US): **KLA-TENCOR CORPORATION** [US/US]; KLA-Tencor Corporation, Legal Department, One Technology Drive, Milpitas, CA 95035 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DE GREEVE, Johan** [BE/BE]; Latstraat 4, 3360 Lovenjoel (BE). **SWERTS, Benjamin** [BE/BE]; Waasdonk 21, 2100 Deurne (BE).

(74) Agent: **MCANDREWS, Kevin**; KLA-Tencor Corp., Legal Department, One Technology Drive, Milpitas, CA 95035 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: APPARATUS AND METHODS FOR SETTING UP OPTICAL INSPECTION PARAMETERS




FIG. 1

(57) Abstract: Provided are novel methods and systems for setting up ranges of optical inspection parameters. These ranges may be later used for inspection of photovoltaic cells for discoloration, for example. A set of values corresponding to an inspection parameter, such as hue, saturation, and intensity, is obtained from a set-up image. The image includes multiple set-up areas, e.g., a defined group of pixels, wherein each set-up area is assigned a corresponding value in the set. A test image is then constructed from multiple test areas that are also associated with the values in the set. Each test area is assigned a color from a set of user defined colors based on the corresponding value and user defined ranges. A user interface includes both a range diagram and test image, which are used to adjust the ranges in the diagram that result in modification of the test image.



GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

(88) Date of publication of the international search report:

2 February 2012

Published:

— *with international search report (Art. 21(3))*