

Description

Title of Invention: THE METHOD FOR PRODUCING VALUABLE AROMATICS AND LIGHT PARAFFINS FROM HYDROCARBONACEOUS OILS DERIVED FROM OIL, COAL OR WOOD

Technical Field

- [1] The present invention relates to a method of producing aromatics and paraffins from hydrocarbonaceous oils derived from oil, coal or wood.

Background Art

- [2] The demand for aromatics, for example, benzene/toluene/xylene, is increasing at a yearly average of 4 ~ 6% all over the world, which is a drastic increasing trend that is two times the GDP and three times the demand for general petroleum products. Such an increase is based on the dramatically increasing demand for aromatics in China.
- [3] Conventional aromatics (benzene/toluene/xylene) have been produced from pyrolysis gasoline obtained together with fundamental oil products including ethylene, propylene, etc., in naphtha pyrolysis plants using a naphtha feed, or from reformat in catalytic naphtha reformer.
- [4] However, because of the drastic increase in the demand for aromatics as noted above, Shortage of naphtha supply are intensifying in the worldwide market including China since 2007, conventional techniques using naphtha cannot meet the increasing aromatic demand because naphtha can be obtained by atmospheric distillation of crude oil only. Hence, there is a need for alternative feed for aromatics, which is usable as a replacement for naphtha, and furthermore, a need to increase the yield of aromatics and light paraffins is receiving attention.

Disclosure of Invention

Technical Problem

- [5] Under such circumstances, the present inventors have ascertained that aromatic components such as benzene, toluene or xylene, the demand for which is increasing, may be prepared from oils derived from oil, coal or wood, and therefore the present invention has been devised in response to the need by the market for the above techniques.
- [6] Accordingly, an object of the present invention is to provide a novel method of producing high-concentration aromatics using oils derived from oil, coal or wood containing a large amount of components having high aromaticity, instead of using a conventional naphtha feed for aromatics.

Solution to Problem

- [7] In order to accomplish the above object, the present invention provides a method of producing aromatics and light paraffins from oils derived from oil, coal or wood, comprising (a) introducing the oils derived from oil, coal or wood into a hydrogenation and reaction area, so that polycyclic aromatic components are partially saturated and cracked; (b) separating components obtained in (a) into hydrocarbonaceous components having 11 or more carbons, hydrocarbonaceous components having 6 ~ 10 carbons, and hydrocarbonaceous components having 5 or fewer carbons; and (c) recirculating the hydrocarbonaceous components having 11 or more carbons separated in (b) back to (a), feeding the hydrocarbonaceous components having 6 ~ 10 carbons to an aromatic separation process and a transalkylation process so that at least a portion of the aromatics is recovered, and feeding the hydrocarbonaceous components having 5 or fewer carbons to a light separation process thus obtaining aromatics and paraffins.

Advantageous Effects of Invention

- [8] A method of producing aromatics and paraffins according to the present invention enables the production of high-concentration aromatics such as benzene, toluene and xylene using oils including light cycle oil obtained by fluid catalytic cracking of oil, pyrolysis gasoline obtained by thermal cracking of naphtha, heavy aromatics from a reformer, coal tar or light oil resulting from coal carbonation, or aromatic compounds resulting from wood pyrolysis, carbonation, destructive distillation, etc., instead of using the conventional naphtha feed for aromatics, and thereby the method according to the present invention can overcome the limitations put on the throughput of aromatics.
- [9] In particular, among a variety of aromatics/paraffins, valuable aromatics, for example, benzene, toluene and xylene, and light paraffins such as propane, butane or the like can be selectively produced, and byproducts which are relatively valueless can be recovered and reprocessed so that their values are increased, thereby greatly increasing the value of the final products.

Brief Description of Drawings

- [10] FIG. 1 is a schematic block flow diagram showing a production process according to an embodiment of the present invention; and
- [11] FIG. 2 is a schematic block flow diagram showing a production process according to another embodiment of the present invention, including aromatic separation, transalkylation, xylene process and then the recirculation of unconverted oils.

Mode for the Invention

- [12] Hereinafter, a detailed description will be given of the present invention.
- [13] The present invention pertains to a method of producing aromatic components

including benzene, toluene or xylene from oils derived from oil, coal or wood. According to the present invention, oils derived from oil may mainly include oils containing aromatic compounds such as light cycle oil (LCO), pyrolysis gasoline, heavy aromatics, etc., and oils derived from coal or wood include but are not limited to oils containing aromatic compounds such as coal tar or light oil, wood tar, etc., and all oils containing aromatic components derivable from oil, coal or wood may be used. For example, it is possible to use any materials selected from the group consisting of oils derived from oil, such as raw pyrolysis gasoline (RPG), heavy raw pyrolysis gasoline (heavy RPG), treated pyrolysis gasoline (TPG), reformat, heavy aromatics, kerosene, jet oil, atmospheric gas oil, FCC gasoline, light cracked naphtha, heavy cracked naphtha, FCC decanted oil, vacuum gas oil, coker gas oil, coker diesel, coker naphtha, heavy and reduced petroleum crude oil, petroleum atmospheric distillation bottom, petroleum vacuum distillation bottom, asphalt, bitumen, tar sand oil, shale oil, liquid/solid products obtained by coal liquefaction or coal carbonation, such as coal tar, tar oil, light oil, phenolic oil or carbolic oil, naphthalene oil, wash oil, anthracene oil, light anthracene oil, heavy anthracene oil and pitch, products derived from wood carbonation, such as wood tar, hardwood tar, resinous tar, and combinations thereof.

[14] The schematic block flow diagram for the method according to the present invention is shown in FIG. 1. With reference to FIG. 1, the oils are introduced into a hydrogenation and reaction area. As the amount of aromatic components of the oils is increased, valuable aromatics may be favorably produced.

[15] According to the present invention, polycyclic aromatic components may be partially saturated and cracked in the hydrogenation and reaction area. The hydrogenation and reaction area includes a hydroprocessing unit and a hydrocracking unit. As such, hydroprocessing and hydrocracking may be performed in any sequence whatsoever. Specifically, the feed may be introduced into the hydroprocessing unit and then the hydrocracking unit, or into the hydrocracking unit and then the hydroprocessing unit.

[16] The hydroprocessing unit of the hydrogenation and reaction area is configured such that hydrogen is supplied from the outside, and the oils are hydrotreated in the presence of a hydroprocessing catalyst. The hydroprocessing reaction achieves the partial saturation of aromatic components including two or more aromatic rings. Such hydroprocessing must not saturate an aromatic component having one aromatic ring. This is because the aromatic component having one aromatic ring is a valuable aromatic component or may be converted into a valuable aromatic component by transalkylation which will be described later.

[17] In the hydroprocessing unit, the aromatic components including two or more aromatic rings are saturated in such a manner that the aromatic rings other than only one aromatic ring are saturated. This is because it is not easy to perform the cracking

of the unnecessary aromatic rings in the subsequent hydrocracking unit.

- [18] To obtain the above results, the hydroprocessing unit may operate under conditions including a reaction pressure of 20 ~ 100 kg/cm², a reaction temperature of 150 ~ 450°C, and a liquid hourly space velocity (LHSV) of 0.1 ~ 4.5 hr⁻¹.
- [19] Also a catalyst used in the hydroprocessing unit may comprise a carrier composed of either or both of alumina and silica, and one or more metals selected from the group consisting of metals of Groups 6, 9, and 10. Particularly useful are one or more metals selected from the group consisting of cobalt, molybdenum, nickel and tungsten.
- [20] Upon hydroprocessing, not only partial saturation of the aromatic rings but also desulfurization, denitrogenation and deoxygenation that are conducted to remove impurities such as sulfides, nitrogen or oxygen compounds from the oils may be carried out. For this process of producing aromatics, the removal of impurities is very important, and all impurities like sulfur, nitrogen and oxygen should be removed before being fed to the transalkylation process. Generally Oxygen level of oils from tar and wood is very high. Hence, the impurities in the oils may be easily removed without the need to also remove the impurities.
- [21] Upon hydroprocessing, the partially saturated feed is fed to the hydrocracking unit. A hydrocracking catalyst used in the hydrocracking unit may be composed of one or more kinds of zeolite having a pore size of 4 Å (Angstroms) or more, which may be optionally modified with a binder and one or more metals selected from among metals of Groups 6, 9 and 10. The zeolite may include but is not limited to, MOR, MEL, FAU, BEA, etc., and the binder may include silica, alumina, clay, etc., which may be used alone or in combinations thereof.
- [22] Hydrocracking plays a role in breaking a naphthenic ring or a long branch with two or more carbons attached to a 1-ring aromatic compound, in the presence of added hydrogen. As such, hydrocracking does not produce olefins, unlike catalytic cracking. According to the reaction mechanism, the cracked naphthenic ring is an unsaturated hydrocarbon (i.e. an olefin), which is unstable and thus easily binds with the other hydrocarbons around it. This reaction hinders the production of a desired aromatic component or may cause polymerization to produce coke thus undesirably deactivate the catalyst. Thus, hydrogen is added to the unsaturated hydrocarbon, which is thus converted into a saturated hydrocarbon that is stable. For this reason, hydrocracking requires a supply of hydrogen unlike catalytic cracking. The purpose of hydroprocessing is, for the aromatic components having two or more aromatic rings, partially saturating the aromatic rings other than the one aromatic ring, so that the naphthenic ring may be broken thus forming valuable aromatic components or materials that can be used to make aromatic components in subsequent procedures.
- [23] To obtain the above results, the hydrocracking unit may operate under conditions

including a reaction pressure of 400 ~ 4500 psig, a reaction temperature of 200 ~ 500°C, and LHSV of 0.1 ~ 10.

- [24] The products obtained from the hydrogenation and reaction area are separated into i) hydrocarbonaceous components having 11 or more carbons, ii) hydrocarbonaceous components having 6 ~ 10 carbons and iii) hydrocarbonaceous components having 5 or fewer carbons, by means of a main separation column. The hydrocarbonaceous components having 11 or more carbons thus separated are recirculated back to the hydrogenation and reaction area, and the hydrocarbonaceous components having 6 ~ 10 carbons are fed to an aromatic separation process and a transalkylation process, and the hydrocarbonaceous components having 5 or fewer carbons are fed to a light separation process.
- [25] Heavy oils having 11 or more carbons may be converted into valuable aromatic components or valuable paraffin components, and are thus recirculated back to the hydrogenation and reaction area. Among the heavy oils obtained by the main separation column, the amount of oils passing through the hydroprocessing unit and the hydrocracking unit may vary depending on the feed but is about 40% of the total of supplied oils, and after recirculation, the amount of oils which should be further recirculated is less than just 15% of the total.
- [26] The hydrocarbonaceous components having 5 or fewer carbons that were separated by the main separation column are further separated into off-gas and paraffin components by light separation. The paraffin components include 2 or more carbons such as ethane, propane, butane, etc.
- [27] The hydrocarbonaceous components having 6 ~ 10 carbons that were separated by the main separation column are fed to the aromatic separation process and the transalkylation process. As such, among the hydrocarbonaceous components having 6 ~ 10 carbons, saturated hydrocarbons including cyclohexane are fed to an additional reformer. A portion of the oils reformed to be unsaturated using the reformer is fed to the aromatic separation process and the transalkylation process, and the unconverted oils may be fed to the main separation column or the light separation process. The reformer functions to convert the saturated hydrocarbons into aromatic components at about 400 ~ 600°C using a Pt/Al₂O₃, Pt-Re/Al₂O₃ or Pt-Sn/Al₂O₃ catalyst in a hydrogen atmosphere. The products obtained by the reformer may include benzene, toluene and xylene, and such unsaturated hydrocarbons are fed to the aromatic separation process and the transalkylation process.
- [28] The hydrocarbonaceous components having 6 ~ 10 carbons separated by the main separation column (and the reformer) are transferred to the aromatic separation process and the transalkylation process. As such, aromatic separation and transalkylation may be performed in any sequence whatsoever. Specifically, (i) the hydrocarbonaceous

components having 6 ~ 10 carbons may be separated into benzene, toluene, xylene, and hydrocarbonaceous components having 9 or more carbons in the aromatic separation process, after which a portion of the separated oils is transferred to the transalkylation process, thus obtaining a mixture comprising benzene, toluene, xylene, and hydrocarbonaceous components having 9 or more carbons, after which this mixture is further mixed with the remainder of the oils that were not transferred to the transalkylation process, followed by feeding the resulting mixture to the aromatic separation process, thereby recovering the desired aromatics, or (ii) the hydrocarbonaceous components having 6 ~ 10 carbons may be directly transferred to the transalkylation process, thus obtaining a mixture comprising benzene, toluene, xylene, and hydrocarbonaceous components having 9 or more carbons, after which this mixture may be fed to the aromatic separation process, thus recovering the desired aromatics.

- [29] Upon the transalkylation, dealkylation of alkylaromatic compounds having 9 or more carbons and the transalkylation between benzene and aromatic compounds having 9 or more carbons occur simultaneously along with disproportionation of toluene in the presence of a catalyst and transalkylation between toluene and aromatic compounds having 9 or more carbons.
- [30] Such dealkylation is an important reaction that produces toluene necessary for disproportionation and transalkylation. Also, transalkylation between benzene and aromatic compounds having 9 or more carbons is regarded as important because it produces toluene and xylene.
- [31] On the other hand, olefins including ethylene, propylene, etc., produced by dealkylation, have to be rapidly hydrogenated. Unless such olefins are rapidly hydrogenated, they are re-alkylated to aromatic compounds, ultimately lowering the rate of conversion of aromatic compounds having 9 or more carbons. Furthermore, olefins themselves may cause polymerization or the like, undesirably facilitating the production of coke that deactivates the catalyst.
- [32] The catalyst used for transalkylation is not limited, but may include a catalyst disclosed in US Patent No. 6,867,340 by the present applicant.
- [33] Specifically transalkylation is performed using a catalyst comprising a carrier composed of 10 ~ 95 wt% of beta-zeolite or modernite having a molar ratio of silica/alumina adjusted to 20 ~ 200 based on alumina and 5 ~ 90 wt% of one or more inorganic binders selected from the group consisting of gamma-alumina, silica, silica alumina, bentonite, kaolin, clinoptilolite and montmorillonite, and a hydrogenation metal composed of, based on 100 parts by weight of the carrier, 0.001 ~ 0.5 parts by weight of one or more metals selected from the group consisting of platinum, tin, indium and lead. The other properties of the catalyst are to be found in the above

literature.

- [34] After transalkylation, the aromatic components having 11 or more carbons, which are not used as materials to make valuable aromatic components, are recovered, and then may be fed to the hydrogenation and reaction area. Also, benzene, toluene, xylene and hydrocarbons having 9 or more carbons produced by transalkylation may be fed to a xylene process which will be described later via the aromatic separation process. In the xylene process, separating para-xylene from xylene mixture (composed of ortho-xylene, meta-xylene and para-xylene) and isomerizing the xylene mixture other than para-xylene into para-xylene may be performed.
- [35] Also, para-xylene (p-X) separation for separating only para-xylene from xylene mixture may be performed using a technique known in the art, such as adsorption, crystallization, etc.
- [36] Because para-xylene is much more valuable than ortho-xylene or meta-xylene, the separation and recovery of only para-xylene is favorable.
- [37] The xylene components including ortho-xylene and meta-xylene, except for para-xylene, may be transferred to the xylene isomerization process. Among the xylene mixture produced by aromatic separation, para-xylene, meta-xylene, and ortho-xylene are in a state of equilibrium. Because only para-xylene is separated by the above separation, the xylene mixture other than para-xylene are equilibrated using a catalyst, whereby para-xylene which is economically valuable may be additionally obtained.
- [38] On the other hand, the method according to the present invention may include recovering at least a portion of aromatics, for example, benzene and xylene mixture, from among aromatics resulting from transalkylation and xylene process, and recirculating the unconverted oils. Specifically, a portion of benzene and toluene among aromatics resulting from transalkylation may be recirculated back to the aromatic separation process and may thus be further fed to the transalkylation process, and also may be recirculated back to the hydrogenation and reaction area from the aromatic separation process. Moreover, in the xylene isomerization process, oils which were not isomerized into para-xylene may be recirculated back to the aromatic separation process, and thus may be fed to the transalkylation process or the xylene process.
- [39] Accordingly, all of the oils obtained from the xylene isomerization process may be recirculated back to the transalkylation process and the para-xylene separation process via the aromatic separation process, thus additionally obtaining para-xylene.
- [40] Specifically, the recirculation procedure from the transalkylation process and the xylene isomerization process to the aromatic separation process may increase the yield of para-xylene, and improvements in the yield of paraffins and valuable aromatics are possible without performing additional treatment and without wasting any materials thanks to the recirculation from the aromatic separation process to the hydrogenation

and reaction area.

[41] According to embodiments of the present invention, as a feed, LCO derived from oil or coal tar derived from coal is introduced into the hydrogenation and reaction area that performs hydroprocessing and hydrocracking. The oils cracked in the hydrogenation and reaction area are fed to the main separation column so that they are separated into (i) components having 6 ~ 10 carbons, (ii) light paraffin components, and (iii) hydrocarbonaceous components having 11 or more carbons.

[42] After being separated by the main separation column, (iii) the oils having 11 or more carbons are mixed with the above feed and then recirculated back to the hydrogenation and reaction area.

[43] By such recirculation, aromatic components having two or more rings may be cracked to a 1-ring aromatic component using hydroprocessing and hydrocracking catalysts, and hydrocarbonaceous groups having two or more carbons or naphthenic rings may also be cracked and converted into valuable aromatic components or materials to make valuable aromatic components.

[44] When the recirculation is performed in this way, the amount of aromatic components having two or more rings may be drastically reduced, compared to when recirculation is not performed. Furthermore, the amount thereof which is converted into valuable aromatics or materials to make valuable aromatics may be considerably increased.

[45] Also, because the composition of (i) the components having 6 ~ 10 carbons varies depending on the feed used in examples, the aromatic separation process, the transalkylation process, and the xylene process may be differently configured to suit the properties of the components, and the unconverted oils are recirculated to the hydrogenation and reaction area.

[46] When the configuration of these processes is changed and the recirculation is additionally used as mentioned above, unnecessary components are prevented from accumulating upon transalkylation and xylene process, and the components which are not used as materials to make valuable aromatic components may be converted into valuable aromatic components, thus increasing the yield of valuable aromatics. The recirculation effects are described in detail in the following Examples 1 and 2.

[47] In order to additionally explain the principle of the present invention, the examples are described below, but the present examples are not supposed to limit the scope of the present invention as envisioned by the present inventors.

[48]

[49] **EXAMPLE**

[50] **[Example 1] Production of Valuable Aromatics and Light Paraffins from LCO**

[51] **Production of Valuable Aromatics and Light Paraffins from LCO using Hydrogenation Reaction, Aromatic Separation, and Transalkylation**

[52] LCO used in this example was composed of cracked oils resulting from fluid catalytic cracking (FCC). The properties, compositions and yield of the oils resulting from FCC may differ depending on the feed and operating conditions in an FCC unit. In the present example, LCO having a boiling point of 170 ~ 360°C among the oils resulting from FCC was prepared as shown in Table 1 below.

[53] Table 1

[Table 1]

Composition	Feed Amount
Paraffin	4.68
Ethane	0.00
Propane	0.00
Butane	0.00
Naphthene	0.50
Total of Aromatics	84.12
Total of 1-ring Aromatics	39.02
1-ring Aromatic without naphthenic ring	26.95
B	0.02
T	0.34
X	1.72
C9	7.61
C10	11.55
1-ring Aromatic with one naphthenic ring	12.07
1-ring Aromatic with two naphthenic rings	0.00
Total of 2-ring Aromatics	40.98
2-ring Aromatic without naphthenic ring	38.40
2-ring Aromatic with one naphthenic ring	2.58
2-ring Aromatic with two naphthenic rings	0.00
Total of 3-ring Aromatics	4.12
Others	10.70

[54] The above feed was introduced into a hydroprocessing unit. Hydroprocessing was performed in a fixed-bed reactor in the presence of a nickel-molybdenum combined catalyst. The hydroprocessing reaction conditions are shown in Table 2 below.

[55] Table 2

[Table 2]

Catalyst	NiMo/Al ₂ O ₃
Operating Conditions	
Reaction Pressure, kg/	60
LHSV, hr ⁻¹	1.5
Reaction Temperature, °C	300

[56] After hydroprocessing, the composition was changed as shown in Table 3 below.

[57] Table 3

[Table 3]

Composition	Feed Amount	After Hydroprocessing
Paraffin	4.68	5.38
Ethane	0.00	0.01
Propane	0.00	0.01
Butane	0.00	0.01
Naphthene	0.50	1.74
Total of Aromatics	84.12	80.02
Total of 1-ring Aromatics	39.02	71.33
1-ring Aromatic without naphthenic ring	26.95	27.28
B	0.02	0.00
T	0.34	0.10
X	1.72	0.84
C9	7.61	5.08
C10	11.55	10.39
1-ring Aromatic with one naphthenic ring	12.07	39.89
1-ring Aromatic with two naphthenic rings	0.00	4.16
Total of 2-ring Aromatics	40.98	8.03
2-ring Aromatic without naphthenic ring	38.40	4.29
2-ring Aromatic with one naphthenic ring	2.58	3.60
2-ring Aromatic with two naphthenic rings	0.00	0.13
Total of 3-ring Aromatics	4.12	0.66
Others	10.70	13.63

[58] As is apparent from Table 3, before hydroprocessing, the amount of the components including two or more aromatic rings was considerable but was drastically reduced after hydroprocessing. Also the amount of the 1-ring aromatic component was

increased about 80%, and in particular, the amount of the 1-ring aromatic component having the naphthenic ring was increased from about 12.07 to about 39.89, namely at least 230%, based on a value of 100 for the feed. The 1-ring aromatic component having the naphthenic ring may be formed into a valuable aromatic component or a direct material to make the valuable aromatic component by breaking the naphthenic ring in the hydrocracking unit.

[59] The products obtained from the hydroprocessing unit were supplied to a hydrocracking reactor, so that hydrocracking was carried out. The catalyst used herein was a combination of cobalt and beta-zeolite, and the reaction temperature was 380°C, and the reaction pressure was 1200 psig.

[60] After hydrocracking, the composition was changed as shown in Table 4 below.

[61] Table 4

[Table 4]

Composition	Feed Amount	After Hydroprocessing	After Hydrocracking
Paraffin	4.68	5.38	40.85
Ethane	0.00	0.01	0.41
Propane	0.00	0.01	8.20
Butane	0.00	0.01	19.25
Naphthene	0.50	1.74	1.51
Total of Aromatics	84.12	80.02	59.98
Total of 1-ring Aromatics	39.02	71.33	55.52
1-ring Aromatic without naphthenic ring	26.95	27.28	52.72
B	0.02	0.00	1.79
T	0.34	0.10	9.04
X	1.72	0.84	16.44
C9	7.61	5.08	15.14
C10	11.55	10.39	8.34
1-ring Aromatic with one naphthenic ring	12.07	39.89	2.50
1-ring Aromatic with two naphthenic rings	0.00	4.16	0.30
Total of 2-ring Aromatics	40.98	8.03	4.41
2-ring Aromatic without naphthenic ring	38.40	4.29	2.57
2-ring Aromatic with one naphthenic ring	2.58	3.60	1.84
2-ring Aromatic with two naphthenic rings	0.00	0.13	0.00
Total of 3-ring Aromatics	4.12	0.66	0.06
Others	10.70	13.63	1.99

[62] As is apparent from Table 4, compared to the feed before hydrocracking, namely, the

feed after hydroprocessing, the amount of benzene and xylene which are valuable aromatic components was increased by 2000% or more. Also, the amount of toluene/C9/C10 which are the materials used to make the benzene/xylene by subsequent transalkylation was increased by about 109%. Upon hydrocracking, only paraffin, not olefin, was produced.

- [63] Among the components produced by hydrocracking, light paraffins were recovered, and components having 6 ~ 10 carbons were fed to the transalkylation process. The catalyst used in the transalkylation process was composed of a carrier comprising 50 wt% of mordenite having a molar ratio of silica/alumina of 90 and 50 wt% of gamma-alumina binder and 0.05 parts by weight of platinum and 0.5 parts by weight of tin supported thereon. The composition of the products obtained by transalkylation is shown in Table 5 below.

- [64] Table 5

[Table 5]

Composition	Feed Amount	After Hydroprocessing	After Hydrocracking	After Transalkylation
Paraffin	4.68	5.38	40.85	49.18
Ethane	0.00	0.01	0.41	5.08
Propane	0.00	0.01	8.20	10.95
Butane	0.00	0.01	19.25	20.18
Naphthene	0.50	1.74	1.51	0.02
Total of Aromatics	84.12	80.02	59.98	53.76
Total of 1-ring Aromatics	39.02	71.33	55.52	49.30
1-ring Aromatic without naphthenic ring	26.95	27.28	52.72	47.26
B	0.02	0.00	1.79	7.95
T	0.34	0.10	9.04	0.00
X	1.72	0.84	16.44	34.89
C9	7.61	5.08	15.14	0.00
C10	11.55	10.39	8.34	2.83
1-ring Aromatic with one naphthenic ring	12.07	39.89	2.50	1.74
1-ring Aromatic with two naphthenic rings	0.00	4.16	0.30	0.30
Total of 2-ring Aromatics	40.98	8.03	4.41	4.41
2-ring Aromatic without naphthenic ring	38.40	4.29	2.57	2.57
2-ring Aromatic with one naphthenic ring	2.58	3.60	1.84	1.84
2-ring Aromatic with two naphthenic rings	0.00	0.13	0.00	0.00
Total of 3-ring Aromatics	4.12	0.66	0.06	0.06
Others	10.70	13.63	1.99	1.99

[65] As is apparent from Table 5, compared to the feed before transalkylation, the feed after transalkylation had benzene as the valuable aromatic component, the amount of which was increased by 345%, and xylene which further increased in amount by 112%. Because the transalkylation was not a cracking procedure, there was an additional increase in the amount of light paraffins not olefins.

[66]

[67] **Production of Valuable Aromatics and Light Paraffins from LCO by Recirculation of Hydrocarbons having 11 or more Carbons**

[68] In the process of producing valuable aromatics, the same feed and reaction conditions were applied, with the exception that the hydrocarbonaceous components having 11 or more carbons resulting from hydroprocessing and hydrocracking were recirculated back to the hydrogenation and reaction area.

[69] The LCO feed (A0), the product (A1) obtained without recirculating hydrocarbons having 11 or more carbons, and the product (A2) obtained by recirculating hydrocarbons having 11 or more carbons are shown in Table 6 below.

[70] Table 6

[Table 6]

Composition	A0	A1	A2
Paraffin	4.68	49.18	55.98
Ethane	0.00	5.08	5.78
Propane	0.00	10.95	12.47
Butane	0.00	20.18	22.97
Naphthene	0.50	0.02	0.02
Total of Aromatics	84.12	53.76	49.69
Total of 1-ring Aromatics	39.02	49.30	49.69
1-ring Aromatic without naphthenic ring	26.95	47.26	49.69
B	0.02	7.95	9.05
T	0.34	0.00	0.00
X	1.72	34.89	39.72
C9	7.61	0.00	0.00
C10	11.55	2.83	0.91
1-ring Aromatic with one naphthenic ring	12.07	1.74	0.00
1-ring Aromatic with two naphthenic rings	0.00	0.30	0.00
Total of 2-ring Aromatics	40.98	4.41	0.00
2-ring Aromatic without naphthenic ring	38.40	2.57	0.00
2-ring Aromatic with one naphthenic ring	2.58	1.84	0.00
2-ring Aromatic with two naphthenic rings	0.00	0.00	0.00
Total of 3-ring Aromatics	4.12	0.06	0.00
Others	10.70	1.99	0.00

[71] As is apparent from Table 6, recirculation was additionally performed, whereby the aromatic components having two or more rings were excluded and as the valuable aromatic components, benzene was increased by 14% and xylene was further increased by 14%. The total of light paraffins was increased by about 14%. Therefore, higher yields of the valuable aromatics and light paraffins could be obtained because of recirculation.

[72]

[73] **Production of Valuable Aromatics and Light Paraffins from LCO by Recirculation of Unconverted Oils after Transalkylation**

[74] In the process of producing valuable aromatics by recirculating the hydrocarbonaceous components having 11 or more carbons to the hydroprocessing unit, the same feed and reaction conditions were applied, with the exception that, among valuable aromatic components resulting from transalkylation, a portion of benzene,

toluene and xylene was recovered via the aromatic separation process, and the remainder thereof was repetitively recirculated back to the transalkylation process and the hydrogenation and reaction area.

[75] The LCO feed (A0), the product (A1) obtained without recirculating hydrocarbons having 11 or more carbons, the product (A2) obtained by recirculating hydrocarbons having 11 or more carbons, and the product (A3) obtained by recirculating unconverted heavy oils after transalkylation are shown in Table 7 below.

[76] Table 7

[Table 7]

Composition	A0	A1	A2	A3
Paraffin	4.68	49.18	55.98	56.50
Ethane	0.00	5.08	5.78	5.83
Propane	0.00	10.95	12.47	12.51
Butane	0.00	20.18	22.97	23.02
Naphthene	0.50	0.02	0.02	0.02
Total of Aromatics	84.12	53.76	49.69	49.17
Total of 1-ring Aromatics	39.02	49.30	49.69	49.17
1-ring Aromatic without naphthenic ring	26.95	47.26	49.69	49.17
B	0.02	7.95	9.05	9.14
T	0.34	0.00	0.00	0.00
X	1.72	34.89	39.72	40.02
C9	7.61	0.00	0.00	0.00
C10	11.55	2.83	0.91	0.00
1-ring Aromatic with one naphthenic ring	12.07	1.74	0.00	0.00
1-ring Aromatic with two naphthenic rings	0.00	0.30	0.00	0.00
Total of 2-ring Aromatics	40.98	4.41	0.00	0.00
2-ring Aromatic without naphthenic ring	38.40	2.57	0.00	0.00
2-ring Aromatic with one naphthenic ring	2.58	1.84	0.00	0.00
2-ring Aromatic with two naphthenic rings	0.00	0.00	0.00	0.00
Total of 3-ring Aromatics	4.12	0.06	0.00	0.00
Others	10.70	1.99	0.00	0.00

[77] As is apparent from Table 7, recirculation was carried out two times, whereby the amount of benzene and xylene which are valuable aromatic components was increased by 0.4 wt%, and the amount of light paraffins such as ethane, propane and butane was increased by 0.14 w%, compared to when recirculation was performed one time. Therefore, higher yields of the valuable aromatics could be obtained by carrying out

recirculation two times.

[78]

[79] **Production of Valuable Aromatics and Light Paraffins from LCO by Xylene Process after Transalkylation**

[80] In the recirculation of unconverted oils after transalkylation, the same feed and reaction conditions were applied, with the exception that the xylene mixture obtained by transalkylation were treated with Xylene Process comprising para-xylene separation and xylene isomerization.

[81] The LCO feed (A0), the product (A1) obtained without recirculating hydrocarbons having 11 or more carbons, the product (A2) obtained by recirculating hydrocarbons having 11 or more carbons, the product (A3) obtained by recirculating unconverted heavy oils after transalkylation, and the product (A4) obtained by xylene isomerization and separation are shown in Table 8 below.

[82] Table 8

[Table 8]

Composition	A0	A1	A2	A3	A4
Paraffin	4.68	49.18	55.98	56.50	57.02
Ethane	0.00	5.08	5.78	5.83	6.10
Propane	0.00	10.95	12.47	12.51	12.63
Butane	0.00	20.18	22.97	23.02	23.02
Naphthene	0.50	0.02	0.02	0.02	0.02
Total of Aromatics	84.12	53.76	49.69	49.17	48.66
Total of 1-ring Aromatics	39.02	49.30	49.69	49.17	48.66
1-ring Aromatic without naphthenic ring	26.95	47.26	49.69	49.17	48.66
B	0.02	7.95	9.05	9.14	9.86
T	0.34	0.00	0.00	0.00	0.00
Mixed-X	1.45	34.07	39.72	39.04	38.80 (*)
EB	0.27	0.82	0.94	0.98	0.00
C9	7.61	0.00	0.00	0.00	0.00
C10	11.55	2.83	0.91	0.00	0.00
1-ring Aromatic with one naphthenic ring	12.07	1.74	0.00	0.00	0.00
1-ring Aromatic with two naphthenic rings	0.00	0.30	0.00	0.00	0.00
Total of 2-ring Aromatics	40.98	4.41	0.00	0.00	0.00
2-ring Aromatic without naphthenic ring	38.40	2.57	0.00	0.00	0.00
2-ring Aromatic with one naphthenic ring	2.58	1.84	0.00	0.00	0.00
2-ring Aromatic with two naphthenic rings	0.00	0.00	0.00	0.00	0.00
Total of 3-ring Aromatics	4.12	0.06	0.00	0.00	0.00
Others	10.70	1.99	0.00	0.00	0.00

(*) Para-Xylene

[83]

[84]

As is apparent from Table 8, almost of the xylene mixture could be converted into para-xylene which is a valuable product by para-xylene separation and xylene isomerization, and ethylbenzene (EB) which is an impurity in the xylene component was completely removed and converted into benzene. Therefore, the yield and purity of valuable aromatic, Para-xylene could be increased by additionally carrying out xylene process.

[85]

[86]

[Example 2] Production of Valuable Aromatics and Light Paraffins from Coal Tar

[87]

Production of Valuable Aromatics and Light Paraffins from Coal Tar using hydroprocessing and hydrocracking Reaction, Aromatic Separation, and Transalkylation

[88] The properties and compositions of oils derived from coal used in this example may differ depending on the feed and operating conditions. In the present example, as oils resulting from coal carbonation, coal tar having a boiling point of 78 ~ 350°C and having the composition shown in Table 9 below was prepared.

[89] Table 9

[Table 9]

Composition	Feed Amount
Paraffin	0.77
Ethane	0.00
Propane	0.77
Butane	0.00
Naphthene	0.00
Total of Aromatics	99.23
Total of 1-ring Aromatics	9.73
1-ring Aromatic without naphthenic ring	6.30
B	2.05
T	0.70
X	1.59
C9	1.65
C10	0.30
1-ring Aromatic with one naphthenic ring	3.43
1-ring Aromatic with two naphthenic rings	0.00
Total of 2-ring Aromatics	89.50
2-ring Aromatic without naphthenic ring	66.92
2-ring Aromatic with one naphthenic ring	22.58
2-ring Aromatic with two naphthenic rings	0.00
Total of 3-ring Aromatics	0.00
Others	0.00

[90] The coal tar having the above composition was introduced into a hydroprocessing unit. Hydroprocessing was performed in a fixed-bed reactor using a nickel-molybdenum combined catalyst. The hydroprocessing reaction conditions are shown in Table 10 below.

[91] Table 10

[Table 10]

Catalyst	NiMo/Al ₂ O ₃
Operating Conditions	
Reaction Pressure, kg/	60
LHSV, hr ⁻¹	1.5
Reaction Temperature, °C	300

[92] After hydroprocessing, the composition was changed as shown in Table 11 below.

[93] Table 11

[Table 11]

Composition	Feed Amount	After Hydroprocessing
Paraffin	0.77	0.81
Ethane	0.00	0.00
Propane	0.77	0.81
Butane	0.00	0.00
Naphthene	0.00	0.00
Total of Aromatics	99.23	104.47
Total of 1-ring Aromatics	9.73	83.73
1-ring Aromatic without naphthenic ring	6.30	6.63
B	2.05	2.16
T	0.70	0.74
X	1.59	1.68
C9	1.65	1.73
C10	0.30	0.32
1-ring Aromatic with one naphthenic ring	3.43	61.59
1-ring Aromatic with two naphthenic rings	0.00	15.51
Total of 2-ring Aromatics	89.50	20.74
2-ring Aromatic without naphthenic ring	66.92	12.48
2-ring Aromatic with one naphthenic ring	22.58	8.26
2-ring Aromatic with two naphthenic rings	0.00	0.00
Total of 3-ring Aromatics	0.00	0.00
Others	0.00	0.00

[94] As is apparent from Table 11, before hydroprocessing, the amount of the components including two or more aromatic rings was considerable but was drastically reduced after hydroprocessing. Also the amount of the 1-ring aromatic component was

increased about 7.6 times or more, and in particular, the amount of the 1-ring aromatic component having the naphthenic ring was increased from about 3.43 to about 61.59, namely 17 times, based on a value of 100 for the feed. The 1-ring aromatic component having the naphthenic ring may be formed into a valuable aromatic component or a direct material to make the valuable aromatic component by breaking the naphthenic ring in the hydrocracking unit.

[95] The products obtained from the hydroprocessing unit were supplied to a hydrocracking reactor, so that hydrocracking was carried out. The catalyst used herein was a combination of cobalt and beta-zeolite, and the reaction temperature was 370°C, and the reaction pressure was 1100 psig.

[96] After the cracking, the composition was changed as shown in Table 12 below.

[97] Table 12

[Table 12]

Composition	Feed Amount	After Hydroprocessing	After Hydrocracking
Paraffin	0.77	0.81	35.63
Ethane	0.00	0.00	0.30
Propane	0.77	0.81	9.80
Butane	0.00	0.00	14.51
Naphthene	0.00	0.00	0.90
Total of Aromatics	99.23	104.47	70.70
Total of 1-ring Aromatics	9.73	83.73	50.39
1-ring Aromatic without naphthenic ring	6.30	6.63	47.72
B	2.05	2.16	19.95
T	0.70	0.74	9.36
X	1.59	1.68	9.58
C9	1.65	1.73	5.51
C10	0.30	0.32	2.99
1-ring Aromatic with one naphthenic ring	3.43	61.59	2.67
1-ring Aromatic with two naphthenic rings	0.00	15.51	0.00
Total of 2-ring Aromatics	89.50	20.74	20.29
2-ring Aromatic without naphthenic ring	66.92	12.48	20.27
2-ring Aromatic with one naphthenic ring	22.58	8.26	0.02
2-ring Aromatic with two naphthenic rings	0.00	0.00	0.00
Total of 3-ring Aromatics	0.00	0.00	0.02
Others	0.00	0.00	0.56

[98] As is apparent from Table 12, compared to the feed before the cracking, namely, the

feed after hydroprocessing, the amount of benzene and xylene which are valuable aromatic components was increased by about 670% or more. Also, the amount of toluene/C9/C10, which are the materials used to make the benzene/xylene by subsequent transalkylation, was increased by about 540%. In the hydrocracking unit, only paraffins, not olefins, were produced.

[99] Among the components produced by hydrocracking, the light paraffins were recovered, and components having 6 ~ 10 carbons were fed to the aromatic separation process, so that benzene was separated and the remaining components were fed to the transalkylation process. In Example 1, because the amount of the benzene component is not large, even when the components having 6 ~ 10 carbons are directly fed to the transalkylation process without separation of benzene, a load on the transalkylation process is small and the process is simplified. However, in the present example, because the amount of the benzene component is large, when the components having 6 ~ 10 carbons are fed to the transalkylation process without the separation of benzene, the load on the transalkylation process is large, undesirably increasing the investment cost and comparatively decreasing the yield of valuable aromatics.

[100] The catalyst used upon transalkylation was composed of a carrier comprising 50 wt% of mordenite having a molar ratio of silica/alumina of 90 and 50 wt% of gamma-alumina binder and 0.05 parts by weight of platinum and 0.5 parts by weight of tin supported thereon. The composition of the products obtained by transalkylation is shown in Table 13 below.

[101] Table 13

[Table 13]

Composition	Feed Amount	After Hydroprocessing	After Hydrocracking	After Transalkylation
Paraffin	0.77	0.81	35.63	40.82
Ethane	0.00	0.00	0.30	3.07
Propane	0.77	0.81	9.80	11.43
Butane	0.00	0.00	14.51	15.06
Naphthene	0.00	0.00	0.90	0.01
Total of Aromatics	99.23	104.47	70.70	66.77
Total of 1-ring Aromatics	9.73	83.73	50.39	46.46
1-ring Aromatic without naphthenic ring	6.30	6.63	47.72	44.82
B	2.05	2.16	19.95	28.20
T	0.70	0.74	9.36	0.00
X	1.59	1.68	9.58	15.01
C9	1.65	1.73	5.51	0.00
C10	0.30	0.32	2.99	1.33
1-ring Aromatic with one naphthenic ring	3.43	61.59	2.67	1.64
1-ring Aromatic with two naphthenic rings	0.00	15.51	0.00	0.00
Total of 2-ring Aromatics	89.50	20.74	20.29	20.29
2-ring Aromatic without naphthenic ring	66.92	12.48	20.27	20.27
2-ring Aromatic with one naphthenic ring	22.58	8.26	0.02	0.02
2-ring Aromatic with two naphthenic rings	0.00	0.00	0.00	0.00
Total of 3-ring Aromatics	0.00	0.00	0.02	0.02
Others	0.00	0.00	0.56	0.56

[102] As is apparent from Table 13, compared to the feed before transalkylation, the feed after transalkylation had benzene as the valuable aromatic component, the amount of which was increased by 41%, and xylene which further increased in amount by 57%. Because the transalkylation was not a cracking procedure, there was a additional increase in the amount of light paraffins not olefins.

[103]

[104] **Production of Valuable Aromatics and Light Paraffins from Coal Tar by Recirculation of Hydrocarbons having 11 or more Carbons**

[105] In the process of producing valuable aromatics, the same feed and reaction conditions were applied, with the exception that the hydrocarbonaceous components having 11 or more carbons resulting from hydroprocessing and hydrocracking were recirculated back to the hydrogenation and reaction area.

[106] The coal tar feed (A0), the product (A1) obtained without recirculating hydrocarbons

having 11 or more carbons, and the product (A2) obtained by recirculating hydrocarbons having 11 or more carbons are shown in Table 14 below.

[107] Table 14

[Table 14]

Composition	A0	A1	A2
Paraffin	0.77	40.82	53.21
Ethane	0.00	3.07	4.03
Propane	0.77	11.43	14.74
Butane	0.00	15.06	19.76
Naphthene	0.00	0.01	0.01
Total of Aromatics	99.23	66.77	57.48
Total of 1-ring Aromatics	9.73	46.46	57.48
1-ring Aromatic without naphthenic ring	6.30	44.82	57.48
B	2.05	28.20	36.99
T	0.70	0.00	0.00
X	1.59	15.01	19.69
C9	1.65	0.00	0.00
C10	0.30	1.33	0.79
1-ring Aromatic with one naphthenic ring	3.43	1.64	0.00
1-ring Aromatic with two naphthenic rings	0.00	0.00	0.00
Total of 2-ring Aromatics	89.50	20.29	0.00
2-ring Aromatic without naphthenic ring	66.92	20.27	0.00
2-ring Aromatic with one naphthenic ring	22.58	0.02	0.00
2-ring Aromatic with two naphthenic rings	0.00	0.00	0.00
Total of 3-ring Aromatics	0.00	0.02	0.00
Others	0.00	0.56	0.00

[108] As is apparent from Table 14, recirculation was additionally performed, whereby the aromatic components having two or more rings were excluded and as the valuable aromatic components, benzene was increased by 31% and xylene was further increased by 31%. Also, the total of light paraffins was increased by about 30%. Therefore, higher yields of the valuable aromatics and light paraffins could be obtained because of recirculation.

[109]

[110] **Production of Valuable Aromatics and Light Paraffins from Coal Tar by Recirculation of Unconverted Oils after Transalkylation**

[111] In the process of producing valuable aromatics by recirculating the hydrocarbonaceous components having 11 or more carbons to the hydroprocessing unit, the same feed and reaction conditions were applied, with the exception that among valuable aromatic components resulting from transalkylation, a portion of the benzene, toluene and xylene was recovered via the aromatic separation process, and the

remainder thereof was repetitively recirculated back to the transalkylation process and the hydrogenation and reaction area.

[112] The coal tar feed (A0), the product (A1) obtained without recirculating hydrocarbons having 11 or more carbons, the product (A2) obtained by recirculating hydrocarbons having 11 or more carbons, and the product (A3) obtained by recirculating unconverted heavy oils after transalkylation are shown in Table 15 below.

[113] Table 15

[Table 15]

Composition	A0	A1	A2	A3
Paraffin	0.77	40.82	53.21	53.66
Ethane	0.00	3.07	4.03	4.07
Propane	0.77	11.43	14.74	14.78
Butane	0.00	15.06	19.76	19.80
Naphthene	0.00	0.01	0.01	0.01
Total of Aromatics	99.23	66.77	57.48	57.02
Total of 1-ring Aromatics	9.73	46.46	57.48	57.02
1-ring Aromatic without naphthenic ring	6.30	44.82	57.48	57.02
B	2.05	28.20	36.99	37.07
T	0.70	0.00	0.00	0.00
X	1.59	15.01	19.69	19.96
C9	1.65	0.00	0.00	0.00
C10	0.30	1.33	0.79	0.00
1-ring Aromatic with one naphthenic ring	3.43	1.64	0.00	0.00
1-ring Aromatic with two naphthenic rings	0.00	0.00	0.00	0.00
Total of 2-ring Aromatics	89.50	20.29	0.00	0.00
2-ring Aromatic without naphthenic ring	66.92	20.27	0.00	0.00
2-ring Aromatic with one naphthenic ring	22.58	0.02	0.00	0.00
2-ring Aromatic with two naphthenic rings	0.00	0.00	0.00	0.00
Total of 3-ring Aromatics	0.00	0.02	0.00	0.00
Others	0.00	0.56	0.00	0.00

[114] As is apparent from Table 15, recirculation was carried out two times, whereby the amount of benzene and xylene which are valuable aromatic components was increased by 0.3 wt%, and the amount of light paraffins such as ethane, propane and butane was increased by 0.12 w%, compared to the product (A2) when recirculation was performed one time. Therefore, higher yields of the valuable aromatics could be obtained by carrying out recirculation two times.

[115]

[116] **Production of Valuable Aromatics and Light Paraffins from Coal Tar by Xylene Process after Transalkylation**

[117] In the recirculation of unconverted oils after transalkylation, the same feed and

reaction conditions were applied, with the exception that the xylene mixture obtained by transalkylation were treated with xylene process comprising para-xylene separation and xylene isomerization.

[118] The coal tar feed (A0), the product (A1) obtained without recirculating hydrocarbons having 11 or more carbons, the product (A2) obtained by recirculating hydrocarbons having 11 or more carbons, the product (A3) obtained by recirculating unconverted heavy oils after transalkylation, and the product (A4) obtained by xylene isomerization and separation are shown in Table 16 below.

[119] Table 16

[Table 16]

Composition	A0	A1	A2	A3	A4
Paraffin	0.77	40.82	53.21	53.66	54.30
Ethane	0.00	3.07	4.03	4.07	4.59
Propane	0.77	11.43	14.74	14.78	14.84
Butane	0.00	15.06	19.76	19.80	19.80
Naphthene	0.00	0.01	0.01	0.01	0.01
Total of Aromatics	99.23	66.77	57.48	57.02	56.42
Total of 1-ring Aromatics	9.73	46.46	57.48	57.02	56.42
1-ring Aromatic without naphthenic ring	6.30	44.82	57.48	57.02	56.42
B	2.05	28.20	36.99	37.07	38.42
T	0.70	0.00	0.00	0.00	0.00
Mixed-X	0.97	13.64	19.69	18.11	18.00(*)
EB	0.63	1.38	1.81	1.85	0.00
C9	1.65	0.00	0.00	0.00	0.00
C10	0.30	1.33	0.79	0.00	0.00
1-ring Aromatic with one naphthenic ring	3.43	1.64	0.00	0.00	0.00
1-ring Aromatic with two naphthenic rings	0.00	0.00	0.00	0.00	0.00
Total of 2-ring Aromatics	89.50	20.29	0.00	0.00	0.00
2-ring Aromatic without naphthenic ring	66.92	20.27	0.00	0.00	0.00
2-ring Aromatic with one naphthenic ring	22.58	0.02	0.00	0.00	0.00
2-ring Aromatic with two naphthenic rings	0.00	0.00	0.00	0.00	0.00
Total of 3-ring Aromatics	0.00	0.02	0.00	0.00	0.00
Others	0.00	0.56	0.00	0.00	0.00

(*) Para-Xylene

[120]

[121] As is apparent from Table 16, almost all of the xylene mixture could be converted into para-xylene which is a valuable product by para-xylene separation and xylene isomerization, and ethylbenzene (EB) which is an impurity in the xylene component was

completely removed and converted into benzene. Therefore, the yield and purity of valuable aromatics could be increased by additionally carrying out xylene process.

[122] Although the embodiments of the present invention have been disclosed for illustrative purposes, those skilled in the art will appreciate that a variety of different modifications and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims. Accordingly, such modifications and substitutions should also be understood as falling within the scope of the present invention.

Claims

- [Claim 1] A method of producing aromatics and light paraffins, comprising:
(a) introducing oils derived from oil, coal or wood into a hydrogenation and reaction area, so that polycyclic aromatic components are partially saturated and cracked;
(b) separating components obtained in (a) into hydrocarbonaceous components having 11 or more carbons, hydrocarbonaceous components having 6 ~ 10 carbons, and hydrocarbonaceous components having 5 or fewer carbons; and
(c) recirculating the hydrocarbonaceous components having 11 or more carbons separated in (b) to (a), feeding the hydrocarbonaceous components having 6 ~ 10 carbons to an aromatic separation process and a transalkylation process so that at least a portion of aromatics is recovered, and feeding the hydrocarbonaceous components having 5 or fewer carbons to a light separation process thus obtaining paraffins.
- [Claim 2] The method of claim 1, wherein the hydrocarbonaceous components having 6 ~ 10 carbons separated in (b) are transferred to the aromatic separation process so that they are separated into benzene, toluene, xylene and hydrocarbonaceous components having 9 or more carbons, and a portion of the hydrocarbonaceous components is then fed to the transalkylation process to thus obtain a mixture comprising benzene, toluene, xylene and hydrocarbonaceous components having 9 or more carbons, which is then mixed with a remainder of the hydrocarbonaceous components which is not transferred to the transalkylation process, so that at least a portion of aromatics is recovered, or the hydrocarbonaceous components having 6 ~ 10 carbons separated in (b) are transferred to the transalkylation process thus obtaining a mixture comprising benzene, toluene, xylene and hydrocarbonaceous components having 9 or more carbons, which is then fed to the aromatic separation process.
- [Claim 3] The method of claim 1, further comprising (d) feeding xylene mixture separated in the aromatic separation process to a xylene process to recover at least a portion of aromatics, and recirculating oils that are not treated in the xylene process to the aromatic separation process.
- [Claim 4] The method of claim 3, wherein in the xylene process, separating para-xylene from the xylene mixture and isomerizing the xylene mixture other than para-xylene into para-xylene are performed.

- [Claim 5] The method of any one of claims 1 to 4, wherein the hydrogenation and reaction area in (a) includes a hydroprocessing unit and a hydrocracking unit.
- [Claim 6] The method of claim 5, wherein a catalyst used in the hydroprocessing unit is a catalyst comprising an alumina carrier and one or more metals selected from among metals of Groups 6, 9 and 10 supported thereon.
- [Claim 7] The method of claim 5, wherein a catalyst used in the hydrocracking unit is a modified zeolite catalyst having one or more metals selected from among Group 6 (Mo, W), Group 9 (Co), and Group 10 (Ni) supported thereon.
- [Claim 8] The method of claim 7, wherein the modified zeolite catalyst used in the hydrocracking unit is a catalyst comprising one or more kinds of zeolite having a pore size of 4 Å or more, which is modified with a binder.
- [Claim 9] The method of claim 8, wherein the modified zeolite catalyst used in the hydrocracking unit comprises one or more selected from among MOR, MEL, FAU, and BEA.
- [Claim 10] The method of any one of claims 1 to 4, wherein the oils derived from oil contain 15 ~ 99 wt% of aromatic components based on a total of hydrocarbonaceous components, and have a boiling point of 70 ~ 700°C.
- [Claim 11] The method of any one of claims 1 to 4, wherein the oils derived from coal or wood contain 40 ~ 99 wt% of aromatic components based on a total of hydrocarbonaceous components, and have a boiling point of 70 ~ 700°C.
- [Claim 12] The method of any one of claims 1 to 4, wherein the oils derived from oil, coal or wood are selected from among oils derived from oil including raw pyrolysis gasoline (RPG), heavy raw pyrolysis gasoline (heavy RPG), treated pyrolysis gasoline (TPG), reformat, heavy aromatics, kerosene, jet oil, atmospheric gas oil, FCC (fluid catalytic cracking) gasoline, light cracked naphtha, heavy cracked naphtha, FCC decanted oil, vacuum gas oil, coker gas oil, coker diesel, coker naphtha, heavy and reduced petroleum crude oil, petroleum atmospheric distillation bottom, petroleum vacuum distillation bottom, asphalt, bitumen, tar sand oil, shale oil, oils derived from coal or wood including coal tar, tar oil, light oil, phenolic oil or carbolic oil, naphthalene oil, wash oil, anthracene oil, light anthracene oil, heavy anthracene oil, pitch, wood tar, hardwood tar, resinous tar, and mixtures thereof.

- [Claim 13] The method of any one of claims 1 to 4, further comprising (e) recirculating oils having 11 or more carbons obtained in the aromatic separation process to (a).
- [Claim 14] The method of any one of claims 1 to 4, further comprising (c') feeding saturated hydrocarbons including cyclohexane among the hydrocarbonaceous components having 6 ~ 10 carbons separated in (b) to a reformer so that they are reformed and then fed to the aromatic separation process and the transalkylation process.
- [Claim 15] The method of claim 14, wherein the reformer is operated at a temperature of 400 ~ 600°C in a hydrogen atmosphere using a Pt/Al₂O₃, Pt-Re/Al₂O₃ or Pt-Sn/Al₂O₃ catalyst.
- [Claim 16] The method of claim 1, wherein the aromatics in (c) comprise benzene, toluene, xylene or mixtures thereof.
- [Claim 17] The method of claim 1, wherein a catalyst used in the transalkylation process is a catalyst comprising a carrier composed of 10 ~ 95 wt% of beta-zeolite or modernite having a molar ratio of silica/alumina adjusted to 20 ~ 200 based on alumina and 5 ~ 90 wt% of one or more inorganic binders selected from the group consisting of gamma-alumina, silica, silica alumina, bentonite, kaolin, clinoptilolite and montmorillonite, and a hydrogenation metal composed of, based on 100 parts by weight of the carrier, 0.001 ~ 0.5 parts by weight of one or more metals selected from the group consisting of platinum, tin, indium and lead.