20000216 11-2

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04N 5/00 — A1

(11) International Publication Number: WO 99/26409

(43) International Publication Date: 27 May 1999 (27.05.99)

(21) International Application Number: PCT/IB98/01883

(22) International Filing Date: 12 November 1998 (12.11.98)

(30) Priority Data:
97402765.8 17 November 1997 (17.11.97) EP

(71) Applicant *(for all designated States except US)*: CANAL+ SOCIETE ANONYME [FR/FR]; 85/89, quai André Citroën, F–75711 Paris Cedex 15 (FR).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: HAMERY, Dominique [FR/FR]; 3, parc de la Bérengère, F–92210 Saint Cloud (FR). TRANCHARD, Lionel [FR/FR]; 18, rue Martin Bernard, F–75013 Paris (FR). DECLERCK, Christophe [FR/FR]; 3, rue des Ormes Dancourt, F–28210 Senantes (FR).

(74) Agents: COZENS, Paul, Dennis et al.; Mathys & Squire, 100 Grays Inn Road, London WC1X 8AL (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: PACKET FILTERING

(57) Abstract

A method of filtering a packet data stream as transmitted in a digital audiovisual transmission system characterised in that transport packet data is filtered at a first stage by a digital filter (42) according to the characteristics of the transport packet header, selected filtered data being then passed directly to a memory element (44) within the receiver/decoder. In a second aspect, the method comprises filtering a packet data stream characterised in that transport packet data is filtered at a first stage by a first digital filter (42) according to the characteristics of the transport packet header, selected filtered data from the payload corresponding to a continuous flux of data then being passed to a second digital filter (45) for a second stage of filtering.

