

INTERLOCKING BLOCKCHAINS FOR AIRCRAFT PART HISTORY AND CURRENT AIRCRAFT CONFIGURATION

5

BACKGROUND INFORMATION

The present disclosure relates generally to systems and methods for maintaining, modifying, and tracking the operation of aircraft and other vehicles and parts for aircraft and other
10 vehicles. More particularly, the present disclosure relates to a system and method using interlocking blockchains for the maintenance, modification, and activity tracking of aircraft and other vehicles and parts for aircraft and other vehicles.

The current configuration or state of an aircraft comprises
15 all of the systems and parts currently installed on the aircraft. It is desirable that the current configuration of an aircraft is accurately known. For example, it is desirable for maintenance personnel to know the current configuration of an aircraft before performing maintenance operations on the
20 aircraft or making other modifications of the aircraft.

There is not a standardized or uniform approach for tracking the current configuration of an aircraft that is used by airlines and other aircraft operators. Some airlines and other aircraft operators may take an individual, self-developed
25 approach to rigorously determine the configuration of an aircraft when it is first received and then to track any changes that are made to the aircraft. Other airlines and other aircraft operators may not make a significant effort to track the current configuration of an aircraft continuously. In this
30 case, the airline or other operator of the aircraft may determine the current configuration of the aircraft by inspecting the aircraft when work is to be performed on the aircraft or when the current configuration of the aircraft needs to be known for some other reason.

It is also desirable to have accurate information regarding parts that may be installed on an aircraft, that are installed on an aircraft, or that have been installed on an aircraft. For example, it may be desirable to have accurate information regarding the creation of a part, use of a part, repair of a part, modification of a part, destruction or other ultimate disposition of a part, or of other events or combinations of events that affect a part for an aircraft.

A blockchain is a continuously growing list of records, called blocks, which are linked and secured using cryptography. Each block in a blockchain typically contains a cryptographic hash of the previous block, a timestamp, and transaction data. A blockchain is inherently resistant to modification of the data stored in the blockchain. A blockchain may be used as a decentralized, distributed, and public or private permissions based digital ledger for recording transactions across many computers. A blockchain is typically managed by a peer-to-peer network collectively adhering to a protocol for validating new blocks. Once recorded, the data in any given block cannot be altered retroactively without the alteration of all subsequent blocks, which requires collusion of the blockchain network. Therefore, there may be a need for a method and apparatus that take into account at least some of the issues discussed above, as well as other possible issues.

SUMMARY

An aspect of the disclosure provides a computer-implemented method of maintaining information regarding a part on a vehicle, the method comprising: receiving, by a computer, information regarding an installation of the part on the vehicle; recording the information for the part in part history blockchains for the part in a part history blockchain

network; recording, by the computer, the information regarding the installation of the part in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network; and receiving, by the computer for as long as the part is installed on the vehicle, a token from the part history blockchain network, and locking, by the computer, the part history blockchains for the part and thereby preventing adding additional information for the part to the part history blockchains for the part until the token returns back to the part history blockchain network.

Another aspect of the disclosure provides a computer-implemented method of recording information for a part, the method comprising: receiving, by a computer, a part installation notification by a part history blockchain network, wherein the part installation notification identifies the part and indicates that the part is installed on a vehicle, wherein the part history blockchain network comprises part history blockchains for the part that are configured to record the information for the part, and wherein configuration and activity history information for the vehicle is recorded in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network; sending a token from the part history blockchain network to the vehicle configuration and activity history blockchain network; and locking, by the computer for as long as the part is installed on the vehicle, the part history blockchains for the part and preventing adding additional information for the part to the part history blockchains for the part until the token is returned back to the part history blockchain network.

Another aspect of the disclosure provides an apparatus configured to record information for a part, such that the apparatus comprises a data processing system in a part history

blockchain network configured to: receive a part installation notification configured to identify the part and indicate an installation of the part on a vehicle, wherein the part history blockchain network comprises part history blockchains for the part that are configured to record the information for the part, and wherein vehicle configuration and activity history blockchains for the vehicle are configured to record configuration and activity history information for the vehicle in a vehicle configuration and activity history blockchain network; send a token from the part history blockchain network to the vehicle configuration and activity history blockchain network; and lock, responsive to receipt of the part installation notification for as long as the part is installed on the vehicle, the part history blockchains for the part to prevent an addition of more information for the part to the part history blockchains for the part until the token is returned back to the part history blockchain network.

Illustrative embodiments provide a method of installing a part on a vehicle. Information regarding installation of the part on the vehicle is received. Information for the part is recorded in part history blockchains for the part in a part history blockchain network. The information regarding the installation of the part is recorded in vehicle configuration

and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network. The part history blockchains for the part are locked to prevent adding information for the part to the part history blockchains for the part for as long as the part is installed on the vehicle.

Illustrative embodiments also provide a method of recording information for a part. A part history blockchain network comprises part history blockchains for the part that are configured to record the information for the part.

Configuration and activity history information for a vehicle is recorded in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network. A part installation notification is received by the part history blockchain network.

The part installation notification identifies the part and indicates that the part is installed on a vehicle. The part history blockchains for the part are locked in response to receiving the part installation notification to prevent adding the information for the part to the part history blockchains for the part for as long as the part is installed on the vehicle.

Illustrative embodiments also provide an apparatus for recording information for a part. A data processing system in a part history blockchain network is configured to receive a part installation notification. The part installation notification identifies the part and indicates that the part is installed on a vehicle. The part history blockchain network comprises part history blockchains for the part that are configured to record the information for the part. Configuration and activity history information for the vehicle is recorded in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network. The data processing system is configured to lock the part history blockchains for the part in response to receiving

the part installation notification to prevent adding the information for the part to the part history blockchains for the part for as long as the part is installed on the vehicle.

The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives, and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of interlocking blockchain networks in accordance with an illustrative embodiment;

Figure 2 is an illustration of a vehicle configuration and activity history tracking system in accordance with an illustrative embodiment;

Figure 3 is an illustration of a part history tracking system in accordance with an illustrative embodiment;

Figure 4 is an illustration of a flowchart of a process of installing a part on a vehicle using interlocking part history and vehicle configuration and activity history blockchains in accordance with an illustrative embodiment;

Figure 5 is an illustration of a flowchart of a process of removing a part from a vehicle using interlocking part history and vehicle configuration and activity history blockchains in accordance with an illustrative embodiment;

Figure 6 is an illustration of a flowchart of a process of storing part information for a part using interlocking part history and vehicle configuration and activity history blockchains in accordance with an illustrative embodiment; and

Figure 7 is an illustration of a block diagram of a data processing system in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

The illustrative embodiments recognize and take into account different considerations. For example, the illustrative embodiments recognize and take into account that the configuration of an aircraft may be known and documented when the aircraft is first delivered from an aircraft manufacturer to an operator of the aircraft. However, after delivery, the current aircraft configuration may not be known with certainty as changes are made to the aircraft for maintenance, repairs, or upgrades. The reliability of current aircraft configuration information may be questionable if record keeping has been inconsistent. If current aircraft configuration information cannot be relied upon as being accurate, maintenance personnel may have to spend time to inspect an aircraft and then research and review the actual parts installed on the aircraft before work is performed on the aircraft.

A related issue may occur when an aircraft is transferred from one operator to another. For example, if current aircraft configuration records cannot be relied upon, an airline that receives an aircraft from another airline may need to perform a significant amount of inspection work to confirm the current configuration of the aircraft being received.

Illustrative embodiments also recognize and take into account that currently the history and status of parts for an aircraft may be unclear or questionable, depending upon the

nature of the supplier of the parts. In some cases, history and status records for aircraft parts may be falsified or otherwise be inaccurate. For example, the history and status records for a part that is offered by a supplier for installation on an aircraft may actually be the records for another part that is currently already installed on an aircraft.

Illustrative embodiments use interlocking blockchains to improve the accuracy and reliability of records regarding the configuration and activity history of aircraft and other vehicles and of records regarding the history of parts for an aircraft or other vehicle. Illustrative embodiments provide a system and method whereby records in one blockchain are locked when a transition has occurred related to an item being tracked by or related to another item in another blockchain.

For example, illustrative embodiments provide interlocking blockchain networks for vehicle configuration and activity history records and part history records. Information describing events that make changes to a vehicle or otherwise affect the vehicle are recorded in vehicle configuration and activity history blockchains in a vehicle configuration and activity history blockchain network. Information describing events that change a part or otherwise affect the part are recorded in part history blockchains in a part history blockchain network.

Information regarding the installation of a part on a vehicle may be recorded in vehicle configuration and activity history blockchains in the vehicle configuration and activity history blockchain network and in part history blockchains for the part in the part history blockchain network. In response to the part being installed on the vehicle, the part history blockchains for the part in the part history blockchain network are locked, so that no changes to the part history for the part may be recorded in the part history blockchains. The part

history blockchains remain locked as long as the part is installed on the vehicle. Information regarding removal of the part from the vehicle may be recorded in the vehicle configuration and activity history blockchains in the vehicle configuration and activity history blockchain network. In response to the part being removed from the vehicle, the part history blockchains for the part in the part history blockchain network may be unlocked, so that information regarding removal of the part from the vehicle and information regarding subsequent events that change or otherwise affect the part may be recorded in the part history blockchains for the part in the part history blockchain network.

Part history blockchains and blockchain networks and vehicle configuration and activity history blockchains and blockchain networks in accordance with an illustrative embodiment are based upon blockchain technology that allows distributed record maintenance with ease of data transactions and high data veracity. Illustrative embodiments may be implemented in a cloud computing environment and widely distributed to make the use of interlocking blockchains for maintaining aircraft configuration and activity history records and aircraft part history records highly accessible to airlines, other aircraft operators, and maintenance, repair, and operations providers and systems. Illustrative embodiments may be interoperable with existing maintenance, repair, and operations systems via, for example, application programming interface calls.

Turning to **Figure 1**, an illustration of interlocking blockchain networks is depicted in accordance with an illustrative embodiment. Interlocking blockchain networks **100** include vehicle configuration and activity history blockchain network **102** and part history blockchain network **104**.

Vehicle configuration and activity history blockchain network **102** is configured to maintain records of information regarding events that affect the configuration of an aircraft or other vehicle or that otherwise affect the aircraft or other vehicle. Vehicle configuration and activity history blockchain network **102** comprises a plurality of nodes. A vehicle configuration and activity history blockchain network in accordance with an illustrative embodiment may comprise any appropriate number of nodes. In this example, vehicle configuration and activity history blockchain network **102** comprises nodes **108, 110, 112, 114, 116, 118, and 120**. A vehicle configuration and activity history blockchain network in accordance with an illustrative embodiment may have more or fewer nodes than illustrated in **Figure 1**.

Information for events that affect the configuration of a vehicle or that otherwise affect the vehicle may be recorded in vehicle configuration and activity history blockchains for the vehicle in vehicle configuration and activity history blockchain network **102**. Each node **108, 110, 112, 114, 116, 118, and 120** in vehicle configuration and activity history blockchain network **102** may store a full copy of the vehicle configuration and activity history blockchain for the vehicle. A more detailed description of an example of vehicle configuration and activity history blockchain network **102** is presented below with reference to **Figure 2**.

Part history blockchain network **104** is configured to maintain records of information regarding events that change or otherwise affect a part for an aircraft or other vehicle. Part history blockchain network **104** comprises a plurality of nodes. A part history blockchain network in accordance with an illustrative embodiment may comprise any appropriate number of nodes. In this example, part history blockchain network **104** comprises nodes **128, 130, 132, 134, 136, 138, and 140**. A part

history blockchain network in accordance with an illustrative embodiment may have more or fewer nodes than illustrated in **Figure 1**.

Information for events that change or otherwise affect a part may be recorded in part history blockchains for the part in part history blockchain network **104**. Each node **128, 130, 132, 134, 136, 138, and 140** in part history blockchain network **104** may store a full copy of the part history blockchain for the part. A more detailed description of an example of part history blockchain network **104** is presented below with reference to **Figure 3**.

The part history for a particular part may be maintained in part history blockchains for the part in part history blockchain network **104**. When that part is installed in a vehicle for which configuration and activity history information is maintained in vehicle configuration and activity history blockchain network **102**, locking transaction **142** may be implemented. As part of locking transaction **142**, token **144** representing the part may be passed from part history blockchain network **104** to vehicle configuration and activity history blockchain network **102** to indicate that the part is now installed on or otherwise associated with a particular vehicle. The part history blockchains for the part in part history blockchain network **104** are locked as part of locking transaction **142**. When part history blockchains for the part are locked, no further transactions or events that may change the part history blockchains for the part will be recognized, given that the part is installed on a vehicle. The part history blockchains for the part in part history blockchain network **104** may remain locked for as long as the part is installed on the vehicle.

When the part is removed from the vehicle, unlocking transaction **146** may be implemented. As part of unlocking

transaction **146**, token **144** representing the part may be passed back from vehicle configuration and activity history blockchain network **102** to part history blockchain network **104**. The part history blockchains for the part in part history blockchain network **104** are unlocked as part of unlocking transaction **146**. When part history blockchains for the part are unlocked, information for events that change or otherwise affect the part may be recorded in the part history blockchains for the part. For example, the first transaction that a part history blockchain for the part may accept after unlocking of the part history blockchain by unlocking transaction **146** may be a record of information regarding removal of the part from the vehicle.

The illustration of interlocking blockchain networks **100** in **Figure 1** is not meant to imply physical or architectural limitations to the manner in which illustrative embodiments may be implemented. Other components, in addition to or in place of the ones illustrated, may be used. Some components may be optional. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

Turning to **Figure 2**, an illustration of a vehicle configuration and activity history tracking system is depicted in accordance with an illustrative embodiment. Vehicle configuration and activity history tracking system **200** is configured to track accurately current configuration **202** of vehicle **204**. Vehicle configuration and activity history tracking system **200** may be configured to track current configuration **202** of any appropriate number of various types of vehicles.

For example, without limitation, vehicle configuration and activity history tracking system **200** may be an aircraft configuration and activity history tracking system configured to

track current configuration **202** of aircraft **205**. Vehicle configuration and activity history tracking system **200** may be used to track current configuration **202** of vehicle **204** other than aircraft **205**. In an alternative embodiment, vehicle
5 configuration and activity history tracking system **200** may be used to track the current configuration of a fixed or moveable platform other than a vehicle.

Aircraft **205** may be any appropriate type of aircraft that may be configured to perform any appropriate operation or
10 mission. For example, without limitation, aircraft **205** may be a commercial passenger aircraft, a cargo aircraft, a military aircraft, a personal aviation aircraft or any other appropriate type of aircraft. Aircraft **205** may be a fixed wing aircraft, a rotary wing aircraft, or a lighter-than-air aircraft. Aircraft
15 **205** may be a manned aircraft or an unmanned aircraft.

Vehicle configuration and activity history tracking system **200** comprises vehicle configuration and activity history blockchain network **206**. Vehicle configuration and activity history blockchain network **206** is an example of one possible
20 implementation of vehicle configuration and activity history blockchain network **102** in **Figure 1**. Vehicle configuration and activity history blockchain network **206** is a blockchain network that is set up to store and maintain configuration and activity history information for a number of vehicles. For example,
25 without limitation, vehicle configuration and activity history blockchain network **206** may be a blockchain network that is configured to store and maintain aircraft configuration and activity history information for aircraft **205**. In this case, vehicle configuration and activity history blockchain network
30 **206** may be an aircraft configuration and activity history blockchain network.

Vehicle configuration and activity history blockchain network **206** comprised a plurality of nodes. A vehicle

configuration and activity history blockchain network in accordance with an illustrative embodiment may comprise any appropriate number of nodes. In this example, vehicle configuration and activity history blockchain network **206**

5 comprises nodes **208, 210, 212, 214, 216, 218, and 220**. A vehicle configuration and activity history blockchain network in accordance with an illustrative embodiment may have more or fewer nodes than illustrated in **Figure 2**. Each of nodes **208, 210, 212, 214, 216, 218, and 220** in vehicle configuration and
10 activity history blockchain network **206** may be controlled by an entity that has agreed to participate in the operation and use of vehicle configuration and activity history blockchain network **206** for the purpose of accurately tracking the configuration and activity history of aircraft **205** or other vehicle **204** over time.

15 Vehicle configuration and activity history information is stored in blockchains in vehicle configuration and activity history blockchain network **206**. A unique vehicle configuration and activity history blockchain may be created for each aircraft **205** or other vehicle **204** for which configuration and activity
20 history information is to be tracked in vehicle configuration and activity history blockchain network **206**. A copy of the vehicle configuration and activity history blockchain for each vehicle **204** may be maintained at each node **208, 210, 212, 214, 216, 218, and 220** in vehicle configuration and activity history
25 blockchain network **206**. For example, each node **208, 210, 212, 214, 216, 218, and 220** in vehicle configuration and activity history blockchain network **206** may be configured to store a full copy of vehicle configuration and activity history blockchain
30 **222** for vehicle **204**. For example, without limitation, each node **208, 210, 212, 214, 216, 218, and 220** in vehicle configuration and activity history blockchain network **206** may be configured to store a full copy of vehicle configuration and activity history blockchain **222** for aircraft **205**. In this case, vehicle

configuration and activity history blockchain **222** is an aircraft configuration and activity history blockchain.

Only trusted entity **224** may have permission to access vehicle configuration and activity history blockchain network **206** to read information from and to submit changes to vehicle configuration and activity history blockchain **222** for vehicle **204**. For example, without limitation, trusted entity **224** may be the owner or operator of vehicle **204** or any another appropriate trusted entity. For example, without limitation, trusted entity **224** may be an airline or other operator or owner of aircraft **205** that may have permission to read information from and submit changes to vehicle configuration and activity history blockchain **222** for aircraft **205**. Another trusted entity **224**, such as the manufacturer of aircraft **205**, a provider of maintenance and repair operations for aircraft **205**, or another appropriate entity, also may have permission to read information from and submit changes to vehicle configuration and activity history blockchain **222** for aircraft **205**. Another trusted entity **224** may receive permission to access vehicle configuration and activity history blockchain network **206** for vehicle **204** from the owner of vehicle **204**.

Trusted entity **224** may use configuration and activity history tracking software **225** to access vehicle configuration and activity history blockchain **222** at one or more nodes **208**, **210**, **212**, **214**, **216**, **218**, and **220** of vehicle configuration and activity history blockchain network **206**. Configuration and activity history tracking software **225** may be configured to run on a data processing system to provide various functions for accessing vehicle configuration and activity history blockchain **222**, reading information from vehicle configuration and activity history blockchain **222**, using information read from vehicle configuration and activity history blockchain **222**, and storing new information in vehicle configuration and activity history

blockchain **222** in vehicle configuration and activity history blockchain network **206**. Configuration and activity history tracking software **225** may be implemented in any appropriate manner to perform the functions described herein.

5 Vehicle configuration and activity history blockchain **222** comprises a number of blocks. First block **230** in vehicle configuration and activity history blockchain **222** may be created when vehicle configuration and activity history blockchain **222** for vehicle **204** is added to vehicle configuration and activity
10 history blockchain network **206**. For example, without limitation, vehicle configuration and activity history blockchain **222** for aircraft **205** may be added to vehicle configuration and activity history blockchain network **206** when aircraft **205** is a new aircraft to be delivered from an aircraft
15 manufacturer to an aircraft operator. In this case, first block **230** in vehicle configuration and activity history blockchain **222** for aircraft **205** may include record **232** of an initial configuration information location where information identifying the initial configuration of aircraft **205** may be found. The
20 initial configuration information available at the initial configuration information location may describe both the initial components installed in aircraft **205** and any known inconsistencies in aircraft **205** at the end of production of aircraft **205** and before delivery of aircraft **205** from the
25 manufacturer to an operator of aircraft **205**.

 In the case of a vehicle configuration and activity history blockchain for an active aircraft or other vehicle that is not new being added to vehicle configuration and activity history blockchain network **206**, first block **230** in vehicle configuration
30 and activity history blockchain **222** may include record **232** of an initial configuration information location where a known current configuration of aircraft **205** or other vehicle **204** may be found. In any case, first block **230** of vehicle configuration and

activity history blockchain **222** may identify the initial configuration information location of the known first current configuration state for aircraft **205** or other vehicle **204** recorded in vehicle configuration and activity history blockchain **222**.

First block **230** in vehicle configuration and activity history blockchain **222** may be created and encrypted **233** using a conventional hash value. Subsequent blocks **242**, **244**, and **246** in vehicle configuration and activity history blockchain **222** may be created and encrypted **243**, **245**, **247**, respectively, using a hash value with each new block referencing the previous blocks in vehicle configuration and activity history blockchain **222**. As blocks are added to vehicle configuration and activity history blockchain **222** the robust nature of the encryption increases as the encryption of each subsequent block is based on the previous blocks. As a result, it becomes exponentially more difficult to fraudulently change any of blocks **230**, **242**, **244**, or **246** in vehicle configuration and activity history blockchain **222** without being detected.

Trusted entity **224** with the proper permissions to access vehicle configuration and activity history blockchain network **206** to provide updates to vehicle configuration and activity history blockchain **222** for vehicle **204** may submit transaction **254** to vehicle configuration and activity history blockchain network **206**. Transaction **254** may include new information about vehicle **204**. Transaction **254** may be generated in response to the occurrence of event **256** that may affect the configuration of vehicle **204** or that involves operation of vehicle **204** that it is desirable to record in vehicle configuration and activity history blockchain network **206**. The information included in transaction **254** for recording in vehicle configuration and activity history blockchain network **206** may include appropriate information describing event **256**.

For example, information included in transaction **254** for recording in vehicle configuration and activity history blockchain network **206** may include maintenance information, modification information, activity information, or any other appropriate information or combination of information related to the configuration or operation of vehicle **204**. Maintenance information may include information describing maintenance operations performed on vehicle **204**. For example, without limitation, maintenance information may include information regarding an inspection of parts, repair of parts, or replacement of parts on vehicle **204**. Modification information may identify changes to vehicle **204** other than by maintenance operations. Activity information may include information identifying operations of vehicle **204**. For example, without limitation, when vehicle **204** is aircraft **205**, activity information may identify operations performed by aircraft **205** such as take offs and landings completed, flight hours, changes of ownership, or other activities involving aircraft **205**.

Information included in any new transaction **254** added to vehicle configuration and activity history blockchain **222** in vehicle configuration and activity history blockchain network **206** is propagated **258** across vehicle configuration and activity history blockchain network **206** to all nodes **208, 210, 212, 214, 216, 218, and 220** in vehicle configuration and activity history blockchain network **206**. At each node **208, 210, 212, 214, 216, 218, and 220** a new block **246** may be added to the copy of vehicle configuration and activity history blockchain **222** maintained therein to include a record **252** of the new information provided by transaction **254** regarding vehicle **204**.

In accordance with an illustrative embodiment, event **256** may be the installation of a part on vehicle **204**. In this case, transaction **254** may include information identifying the part installed on vehicle **204** that is stored in vehicle configuration

and activity history blockchain **222** for vehicle **204** in vehicle configuration and activity history blockchain network **206**.

History information for the part being installed on vehicle **204** may be recorded in part history blockchain network **260**. In this
5 case, configuration and activity history tracking software **225** may be configured to send part installation notification **262** to part history blockchain network **260** to notify part history blockchain network **260** that the part has been installed on vehicle **204**. Part installation notification **262** may be provided
10 in any appropriate format and by any appropriate method to part history blockchain network **260**.

In response to receiving part installation notification **262**, part history blockchain network **260** may send token **264** to aircraft configuration and activity history blockchain network
15 **206** and may lock the part history blockchains for the part in part history blockchain network **260** to prevent any further changes to the information recorded in part history blockchain network **260** for the part. The part history blockchains for the part may remain locked until token **264** is returned to part
20 history blockchain network **260**.

Later, event **256** may be the removal of the part from vehicle **204**. In this case, transaction **254** may include information indicating that the part has been removed from vehicle **204** that is stored in vehicle configuration and activity
25 history blockchain **222** for vehicle **204** in vehicle configuration and activity history blockchain network **206**. In this case, configuration and activity history tracking software **225** may be configured to send part removal notification **266** to part history blockchain network **260** to notify part history blockchain network
30 **260** that the part that was installed on vehicle **204** has been removed. Part removal notification **266** may be provided in any appropriate format and by any appropriate method to part history blockchain network **260**.

Token **264** may be returned to part history blockchain network **260** along with or as part of part removal notification **266**. In response to receiving token **264**, part history blockchain network **260** may unlock the part history blockchains for the part in part history blockchain network **260** to allow changes to the information recorded in part history blockchain network **260** for the part.

Trusted entity **224** with the proper permissions to access vehicle configuration and activity history blockchain **222** for vehicle **204** will be able to access vehicle configuration and activity history blockchain network **206** and read information **268** from vehicle configuration and activity history blockchain **222** for vehicle **204**. First block **230** in vehicle configuration and activity history blockchain **222** for vehicle **204** provides record **232** which identifies the location information for the initial configuration of vehicle **204** when vehicle **204** joined vehicle configuration and activity history blockchain network **206**. Each of subsequent blocks **242**, **244**, and **246** includes record **248**, **250**, **252**, respectively, of every subsequent transaction submitted to vehicle configuration and activity history blockchain network **206** for vehicle **204**. Trusted entity **224** may thus determine the current configuration of vehicle **204** from this information.

Data veracity for vehicle configuration and activity history blockchain **222** at a node **208**, **210**, **212**, **214**, **216**, **218**, or **220** in vehicle configuration and activity history blockchain network **206** may be verified by checking the equivalent vehicle configuration and activity history blockchain at other nodes in vehicle configuration and activity history blockchain network **206** and comparing hash values for the last blocks in the blockchains. For example, to confirm the veracity of data from vehicle configuration and activity history blockchain **222** obtained from node **208** of vehicle configuration and activity history blockchain network **206**, trusted entity **224** may compare

the hash value for last block **246** in vehicle configuration and activity history blockchain **222** to the hash value of the last block in the corresponding vehicle configuration and activity history blockchain in one or more other nodes **210, 212, 214,**
5 **216, 218, or 220** in vehicle configuration and activity history blockchain network **206**.

The illustration of vehicle configuration and activity history tracking system **200** in **Figure 2** is not meant to imply physical or architectural limitations to the manner in which
10 illustrative embodiments may be implemented. Other components, in addition to or in place of the ones illustrated, may be used. Some components may be optional. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into
15 different blocks when implemented in an illustrative embodiment.

Turning to **Figure 3**, an illustration of a part history tracking system is depicted in accordance with an illustrative embodiment. Part history tracking system **300** is configured to track accurately the history of part **302**. Part history tracking
20 system **300** may be configured to track the history of any appropriate number of any appropriate various types of parts.

Part history tracking system **300** may be a vehicle part history tracking system that is configured to track the history of vehicle part **304**. Vehicle part **304** may be any appropriate
25 part for any appropriate vehicle. For example, vehicle part **304** may be a part for vehicle **204** in **Figure 2**. For example, without limitation, part history tracking system **300** may be an aircraft part history tracking system that is configured to track the history of aircraft part **305**. Aircraft part **305** may be any
30 appropriate part for any appropriate aircraft. For example, aircraft part **305** may be a part for aircraft **205** in **Figure 2**. In an alternative embodiment, part history tracking system **300** may

be configured to track the history of a part for a fixed or moveable platform other than a vehicle.

Part history tracking system **300** comprises part history blockchain network **306**. Part history blockchain network **306** is an example of one possible implementation of part history blockchain network **104** in **Figure 1** and part history blockchain network **260** in **Figure 2**. Part history blockchain network **306** is a blockchain network that is set up to store and maintain history information for a number of parts. For example, without limitation, part history blockchain network **306** may be a blockchain network that is configured to store and maintain aircraft part history information for aircraft part **305**. In this case, part history blockchain network **306** may be an aircraft part history blockchain network.

Part history blockchain network **306** comprised a plurality of nodes. A part history blockchain network in accordance with an illustrative embodiment may comprise any appropriate number of nodes. In this example, part history blockchain network **306** comprises nodes **308, 310, 312, 314, 316, 318, and 320**. A part history blockchain network in accordance with an illustrative embodiment may have more or fewer nodes than illustrated in **Figure 3**. Each of nodes **308, 310, 312, 314, 316, 318, and 320** in part history blockchain network **306** may be controlled by an entity that has agreed to participate in the operation and use of part history blockchain network **306** for the purpose of accurately tracking the history of part **302** over time.

Part history information is stored in blockchains in part history blockchain network **306**. A part history blockchain may be created for each part **302** for which history information is to be tracked in part history blockchain network **306**. A copy of the part history blockchain for each part **302** may be maintained at each node **308, 310, 312, 314, 316, 318, and 320** in part history blockchain network **306**. For example, each node **308,**

310, 312, 314, 316, 318, and 320 in part history blockchain network **306** may be configured to store a full copy of part history blockchain **322** for part **302**. For example, without limitation, each node **308, 310, 312, 314, 316, 318, and 320** in
5 part history blockchain network **306** may be configured to store a full copy of part history blockchain **322** for aircraft part **305**. In this case, part history blockchain **322** is an aircraft part history blockchain.

Only trusted entity **324** may have permission to access part
10 history blockchain network **306** to read information from and to submit changes to part history blockchain **322** for part **302**. For example, trusted entity **324** may be the owner of part **302** or any another entity that controls part **302**. For example, without limitation, trusted entity **324** may be a supplier of part **302** or
15 an owner of a vehicle into which vehicle part **304** may be installed. For example, trusted entity **324** may be an airline or other operator or owner of an aircraft into which aircraft part **305** may be installed. Another trusted entity **324**, such as the manufacturer of an aircraft or other vehicle, a provider of
20 maintenance and repair operations for an aircraft or other vehicle, or another appropriate entity, also may have permission to read information from and submit changes to part history blockchain **322** for part **302**. Another trusted entity **324** may receive permission to access part history blockchain network **306**
25 for part **302** from the owner of part **302**.

Trusted entity **324** may use part history tracking software **325** to access part history blockchain **322** at one or more nodes **308, 310, 312, 314, 316, 318, and 320** of part history blockchain network **306**. Part history tracking software **325** may be
30 configured to run on a data processing system to provide various functions for accessing part history blockchain **322**, reading information from part history blockchain **322**, using information read from part history blockchain **322**, and storing new

information in part history blockchain **322** in part history blockchain network **306**. Part history tracking software **325** may be implemented in any appropriate manner to perform the functions described herein.

5 Part history blockchain **322** comprises a number of blocks. First block **330** in part history blockchain **322** may be created when part history blockchain **322** for part **302** is added to part history blockchain network **306**. For example, without limitation, part history blockchain **322** for part **302** may be
10 added to part history blockchain network **306** when part **302** is originally created. In this case, first block **330** in part history blockchain **322** for part **302** may include record **332** of information describing the creation of part **302**, information describing part **302** at creation, or other appropriate initial
15 information or various combinations of information for part **302**. Alternatively, part history blockchain **322** for part **302** may be added to part history blockchain network **306** at some later time after part **302** is created. In any case, first block **330** in part history blockchain **322** for part **302** may include information that
20 describes part **302** at the time that part history blockchain **322** for part **302** is added to part history blockchain network **306**.

 First block **330** in part history blockchain **322** may be created and encrypted **333** using a conventional hash value. Subsequent blocks **342**, **344**, and **346** in part history blockchain
25 **322** may be created and encrypted **343**, **345**, **347**, respectively, using a hash value with each new block referencing the previous blocks in part history blockchain **322**. As blocks are added to part history blockchain **322** the robust nature of the encryption increases as the encryption of each subsequent block is based on
30 the previous blocks. As a result, it becomes exponentially more difficult to fraudulently change any of blocks **330**, **342**, **344**, or **346** in part history blockchain **322** without being detected.

Trusted entity **324** with the proper permissions to access part history blockchain network **306** to provide updates to part history blockchain **322** for part **302** may submit transaction **354** to part history blockchain network **306**. Transaction **354** may
5 include new information about part **302**. For example, without limitation, transaction **354** may be generated in response to the occurrence of event **356** that may change or otherwise affect or involve part **302** and that it is desirable to record in part history blockchain network **306**. The information included in
10 transaction **354** for recording in part history blockchain network **306** may include appropriate information describing event **356**. For example, information included in transaction **354** for recording in part history blockchain network **306** may include information regarding the creation, use, inspection, reworking,
15 destruction, or other disposition of part **302**.

Information included in any new transaction **354** to be added to part history blockchain **322** in part history blockchain network **306** is propagated **358** across part history blockchain network **306** to all nodes **308, 310, 312, 314, 316, 318, and 320**
20 in part history blockchain network **306**. At each node **308, 310, 312, 314, 316, 318, and 320** a new block **346** may be added to the copy of part history blockchain **322** maintained therein. The new information regarding part **302** as indicated in transaction **354** may be stored as record **352** of such information in newly added
25 block **346**.

In accordance with an illustrative embodiment, event **356** may be the installation of part **302** on a vehicle for which configuration and activity history information is recorded in vehicle configuration and activity history blockchain network
30 **360**. For example, event **356** may be the installation of vehicle part **304** on vehicle **204** for which configuration and activity history information is recorded in vehicle configuration and activity history blockchain network **206** in **Figure 2**. In this

case, part history blockchain network **306** may receive part installation notification **362** from vehicle configuration and activity history blockchain network **360** or from another appropriate source. Part installation notification **362** may
5 identify part **302** being installed on a vehicle and may include any other appropriate information regarding the installation of part **302**. In this case, transaction **354** may include any appropriate information regarding the installation of part **302** on a vehicle to be recorded in part history blockchain **322** for
10 part **302**.

In response to receiving part installation notification **362** or other information indicating that part **302** is installed, part history blockchain network **306** may send token **364** to aircraft configuration and activity history blockchain network **360** and
15 may lock part history blockchain **322** for part **302** in part history blockchain network **306** to prevent any further changes to the information recorded in part history blockchain network **306** for part **302**. Part history blockchain **322** for part **302** may remain locked until token **364** is returned to part history
20 blockchain network **306**, indicating that part **302** is removed from the vehicle in which it was installed. Therefore, information regarding the installation of part **302** in record **352** in part history blockchain **322** may be the last information for part **302** that is added to part history blockchain network **306** until part
25 **302** is removed from the vehicle on which it was installed and part history blockchain network **306** is unlocked to allow further information regarding part **302** to be recorded therein.

Later, event **356** may be the removal of part **302** from the vehicle on which it was installed. In this case, part history
30 blockchain network **306** may receive part removal notification **366** from vehicle configuration and activity history blockchain network **360** or from another appropriate source. Part removal notification **366** may indicate that part **302** is removed from the

vehicle on which it was installed and may include any other appropriate information regarding the removal of part **302** from the vehicle.

Token **364** may be returned to part history blockchain network **306** along with or as part of part removal notification **366**. In response to receiving token **364**, part history blockchain network **306** may unlock part history blockchain **322** for part **302** in part history blockchain network **306** to allow changes to the information recorded in part history blockchain network **306** for part **302**. In this case, the first transaction **354** to add new information for part **302** to part history blockchain network **306** after part history blockchain **322** for part **302** is unlocked may include information regarding the removal of part **302** from the vehicle on which it was installed.

Trusted entity **324** with the proper permissions to access part history blockchain **322** for part **302** will be able to access part history blockchain network **306** and read information **368** for part **302** from part history blockchain **322**. Blocks **330**, **342**, **344**, and **346** in part history blockchain **322** include records **332**, **348**, **350**, and **352**, respectively, of information regarding changes to part **302**, activities involving part **302**, or both, that has been submitted to part history blockchain network **306**. Trusted entity **324** may thus determine the current state of part **302** from this information.

Data veracity for part history blockchain **322** at a node **308**, **310**, **312**, **314**, **316**, **318**, or **320** in part history blockchain network **306** may be verified by checking the equivalent part history blockchain at other nodes in part history blockchain network **306** and comparing hash values for the last blocks in the blockchains. For example, to confirm the veracity of data from part history blockchain **322** obtained from node **308** of part history blockchain network **306**, trusted entity **324** may compare the hash value for last block **346** in part history blockchain **322**

to the hash value of the last block in the corresponding blockchain in one or more other nodes **310, 312, 314, 316, 318,** or **320** in part history blockchain network **306**.

The illustration of part history tracking system **300** in **Figure 3** is not meant to imply physical or architectural limitations to the manner in which illustrative embodiments may be implemented. Other components, in addition to or in place of the ones illustrated, may be used. Some components may be optional. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

Turning to **Figure 4**, an illustration of a flowchart of a process of installing a part on a vehicle using interlocking part history and vehicle configuration and activity history blockchains is depicted in accordance with an illustrative embodiment. Process **400** may be implemented, for example, in vehicle configuration and activity history blockchain network **102** in **Figure 1** or in vehicle configuration and activity history tracking system **200** in **Figure 2**.

Process **400** may begin with receiving information regarding the installation of a part on a vehicle, wherein part history information for the part is recorded in a part history blockchain network (operation **402**). The received information may identify the part installed on the vehicle and may include other information regarding the installation of the part on the vehicle. Information regarding the installation of the part on the vehicle may be recorded in a vehicle configuration and activity history blockchain for the part in a vehicle configuration and activity history blockchain network (operation **404**).

A part installation notification may be sent to the part history blockchain network in which part history information for

the part is recorded (operation **406**). The part installation notification may identify the part that is installed and indicate that the part is installed on a vehicle. The part history blockchain network may lock part history blockchains for the part therein to prevent any new information for the part from being recorded in the part history blockchain network for as long as the part is installed on a vehicle. The part history blockchain network may send a token to the vehicle configuration and activity history blockchain network. Part history blockchains for the part in the part history blockchain network may remain locked to prevent the addition of new information for the part until the token is returned to the part history blockchain network. The token thus may be received and saved by the vehicle configuration and activity history blockchain network (operation **408**), with the process terminating thereafter.

Turning to **Figure 5**, an illustration of a flowchart of a process of removing a part from a vehicle using interlocking part history and vehicle configuration and activity history blockchains is depicted in accordance with an illustrative embodiment. Process **500** may be implemented, for example, in vehicle configuration and activity history blockchain network **102** in **Figure 1** or in vehicle configuration and activity history tracking system **200** in **Figure 2**. Process **500** may be performed at some time after process **400** in **Figure 4** is performed. The part, vehicle, part history blockchain network, and vehicle configuration and activity history blockchain network referred to in the description of process **500** may be the same as referred to in the description of process **400** in **Figure 4**.

Process **500** may begin with receiving information regarding the removal of a part from a vehicle, wherein part history information for the part is recorded in a part history blockchain network (operation **502**). The received information

may identify the part that is removed from the vehicle and may include other information regarding the removal of the part from the vehicle. Information regarding the removal of the part from the vehicle may be recorded in a vehicle configuration and activity history blockchain for the part in a vehicle configuration and activity history blockchain network (operation **504**).

A part removal notification may be sent to the part history blockchain network in which part history information for the part is recorded (operation **506**). The part removal notification may identify the part that is removed and indicate that the part is removed from a vehicle on which it was installed. The token received from the part history blockchain network also may be returned back to the part history blockchain network (operation **508**), with the process terminating thereafter. In response to receiving the token, the part history blockchain network may unlock the part history blockchains for the part therein to allow new information for the part to be recorded in the part history blockchain network.

Turning to **Figure 6**, an illustration of a flowchart of a process of storing part information for a part using interlocking part history and vehicle configuration and activity history blockchains is depicted in accordance with an illustrative embodiment. Process **600** may be implemented, for example, in part history blockchain network **104** in **Figure 1** or in part history tracking system **300** in **Figure 3**.

Process **600** may begin with receiving a part installation notification for a part installed on a vehicle, wherein configuration and activity history information for the vehicle is recorded in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network (operation **602**). The part installation notification may identify the part, indicate that

the part is installed on a vehicle, and provide other appropriate information regarding the installation of the part on the vehicle. The part installation notification may be provided by the vehicle configuration and activity history blockchain network or by another appropriate source.

Information regarding the installation of the part on the vehicle may be recorded in part history blockchains for the part in a part history blockchain network (operation **604**). The part history blockchains for the part in the part history blockchain network then may be locked (operation **606**) to prevent any further additions to the information for the part from being recorded in the part history blockchain network. A token may be sent to the vehicle configuration and activity history blockchain network in which information for the vehicle on which the part is installed is recorded (operation **608**).

The part history blockchain network will remain locked to prevent the addition of information regarding the part until the token is returned, indicating that the part has been removed from the vehicle on which it was installed. Thus, it may be determined whether the token is received back from the vehicle configuration and activity history blockchain network (operation **610**). In response to a determination that the token has been returned, the part history blockchains for the part in the part history blockchain network may be unlocked (operation **612**) to allow additional information for the part to be added thereto.

A part removal notification may be received (operation **614**). The part removal notification may include information regarding the removal of the part from the vehicle. The part removal notification may be provided from the vehicle configuration and activity history blockchain network in which information for the vehicle from which the part is removed is recorded. Information regarding the removal of the part from the vehicle may be recorded in the part history blockchains for

the part in the part history blockchain network (operation **616**), with the process terminating thereafter. The information regarding the removal of the part thus may be the first information regarding the part that is recorded in the part history blockchain network after the part history blockchain network is unlocked at operation **612**.

Turning to **Figure 7**, an illustration of a block diagram of a data processing system is depicted in accordance with an illustrative embodiment. Data processing system **700** is an example of one possible implementation of a data processing system for performing the functions of interlocking blockchains as described herein. For example, without limitation, data processing system **700** is an example of one possible implementation of a data processing system for implementing vehicle configuration and activity history blockchain network **102** and part history blockchain network **104** in **Figure 1**.

In this illustrative example, data processing system **700** includes communications fabric **702**. Communications fabric **702** provides communications between processor unit **704**, memory **706**, persistent storage **708**, communications unit **710**, input/output (I/O) unit **712**, and display **714**. Memory **706**, persistent storage **708**, communications unit **710**, input/output (I/O) unit **712**, and display **714** are examples of resources accessible by processor unit **704** via communications fabric **702**.

Processor unit **704** serves to run instructions for software that may be loaded into memory **706**. Processor unit **704** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation. Further, processor unit **704** may be implemented using a number of heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **704** may be a symmetric multi-processor system containing multiple processors of the same type.

Memory **706** and persistent storage **708** are examples of storage devices **716**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and other suitable information either on a temporary basis or a permanent basis. Storage devices **716** also may be referred to as computer readable storage devices in these examples. Memory **706**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **708** may take various forms, depending on the particular implementation.

For example, persistent storage **708** may contain one or more components or devices. For example, persistent storage **708** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **708** also may be removable. For example, a removable hard drive may be used for persistent storage **708**.

Communications unit **710**, in these examples, provides for communications with other data processing systems or devices. In these examples, communications unit **710** is a network interface card. Communications unit **710** may provide communications through the use of either or both physical and wireless communications links.

Input/output (I/O) unit **712** allows for input and output of data with other devices that may be connected to data processing system **700**. For example, input/output (I/O) unit **712** may provide a connection for user input through a keyboard, a mouse, and/or some other suitable input device. Further, input/output (I/O) unit **712** may send output to a printer. Display **714** provides a mechanism to display information to a user.

Instructions for the operating system, applications, and/or programs may be located in storage devices **716**, which are in

communication with processor unit **704** through communications fabric **702**. In these illustrative examples, the instructions are in a functional form on persistent storage **708**. These instructions may be loaded into memory **706** for execution by processor unit **704**. The processes of the different embodiments may be performed by processor unit **704** using computer-implemented instructions, which may be located in a memory, such as memory **706**.

These instructions are referred to as program instructions, program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **704**. The program code in the different embodiments may be embodied on different physical or computer readable storage media, such as memory **706** or persistent storage **708**.

Program code **718** is located in a functional form on computer readable media **720** that is selectively removable and may be loaded onto or transferred to data processing system **700** for execution by processor unit **704**. Program code **718** and computer readable media **720** form computer program product **722** in these examples. In one example, computer readable media **720** may be computer readable storage media **724** or computer readable signal media **726**.

Computer readable storage media **724** may include, for example, an optical or magnetic disk that is inserted or placed into a drive or other device that is part of persistent storage **708** for transfer onto a storage device, such as a hard drive, that is part of persistent storage **708**. Computer readable storage media **724** also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory, that is connected to data processing system **700**. In some instances, computer readable storage media **724** may not be removable from data processing system **700**.

In these examples, computer readable storage media **724** is a physical or tangible storage device used to store program code **718** rather than a medium that propagates or transmits program code **718**. Computer readable storage media **724** is also referred to as a computer readable tangible storage device or a computer readable physical storage device. In other words, computer readable storage media **724** is a media that can be touched by a person.

Alternatively, program code **718** may be transferred to data processing system **700** using computer readable signal media **726**. Computer readable signal media **726** may be, for example, a propagated data signal containing program code **718**. For example, computer readable signal media **726** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, and/or any other suitable type of communications link. In other words, the communications link and/or the connection may be physical or wireless in the illustrative examples.

In some illustrative embodiments, program code **718** may be downloaded over a network to persistent storage **708** from another device or data processing system through computer readable signal media **726** for use within data processing system **700**. For instance, program code stored in a computer readable storage medium in a server data processing system may be downloaded over a network from the server to data processing system **700**. The data processing system providing program code **718** may be a server computer, a client computer, or some other device capable of storing and transmitting program code **718**.

The different components illustrated for data processing system **700** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented.

The different illustrative embodiments may be implemented in a data processing system including components in addition to and/or in place of those illustrated for data processing system **700**. Other components shown in **Figure 7** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code. As one example, data processing system **700** may include organic components integrated with inorganic components and/or may be comprised entirely of organic components excluding a human being. For example, a storage device may be comprised of an organic semiconductor.

In another illustrative example, processor unit **704** may take the form of a hardware unit that has circuits that are manufactured or configured for a particular use. This type of hardware may perform operations without needing program code to be loaded into a memory from a storage device to be configured to perform the operations.

For example, when processor unit **704** takes the form of a hardware unit, processor unit **704** may be a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device is configured to perform the number of operations. The device may be reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. With this type of implementation, program code **718** may be omitted, because the processes for the different embodiments are implemented in a hardware unit.

In still another illustrative example, processor unit **704** may be implemented using a combination of processors found in computers and hardware units. Processor unit **704** may have a number of hardware units and a number of processors that are
5 configured to run program code **718**. With this depicted example, some of the processes may be implemented in the number of hardware units, while other processes may be implemented in the number of processors.

In another example, a bus system may be used to implement
10 communications fabric **702** and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course, the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system.

15 Additionally, communications unit **710** may include a number of devices that transmit data, receive data, or both transmit and receive data. Communications unit **710** may be, for example, a modem or a network adapter, two network adapters, or some combination thereof. Further, a memory may be, for example,
20 memory **706**, or a cache, such as that found in an interface and memory controller hub that may be present in communications fabric **702**.

The flowcharts and block diagrams described herein illustrate the architecture, functionality, and operation of
25 possible implementations of systems, methods, and computer program products according to various illustrative embodiments. In this regard, each block in the flowcharts or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing
30 the specified logical function or functions. It should also be noted that, in some alternative implementations, the functions noted in a block may occur out of the order noted in the figures. For example, the functions of two blocks shown in

succession may be executed substantially concurrently, or the functions of the blocks may sometimes be executed in the reverse order, depending upon the functionality involved.

5 The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide
10 different features as compared to other desirable embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments
15 with various modifications as are suited to the particular use contemplated.

Further, the disclosure comprises embodiments according to the following clauses:

20 Clause 1: A method of installing a part on a vehicle, comprising:

receiving information regarding installation of the part on the vehicle, wherein information for the part is recorded in part history blockchains for the part in a part history
25 blockchain network;

recording the information regarding the installation of the part in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network; and

30 locking the part history blockchains for the part to prevent adding information for the part to the part history blockchains for the part for as long as the part is installed on the vehicle.

Clause 2: The method of clause 1, wherein locking the part history blockchains for the part comprises sending a part installation notification to the part history blockchain network, wherein the part installation notification identifies the part and indicates that the part is installed on the vehicle, and wherein the part history blockchain network locks the part history blockchains for the part in response to receiving the part installation notification.

Clause 3. The method of any of clauses 1-2 further comprising:
receiving information regarding removal of the part from the vehicle;
recording the information regarding the removal of the part from the vehicle in the vehicle configuration and activity history blockchains for the vehicle in the vehicle configuration and activity history blockchain network; and
unlocking the part history blockchains for the part to allow adding information for the part to the part history blockchains for the part in the part history blockchain network.

Clause 4. The method of clause 3 further comprising sending a part removal notification to the part history blockchain network, wherein the part removal notification identifies the part and indicates that the part is removed from the vehicle.

Clause 5. The method of any of clauses 1-4 further comprising receiving a token from the part history blockchain network, wherein the part history blockchains for the part will remain locked until the token is returned back to the part history blockchain network.

Clause 6. The method of clause 5 further comprising:
receiving information regarding removal of the part from
the vehicle;

5 recording the information regarding the removal of the
part from the vehicle in the vehicle configuration and activity
history blockchains for the vehicle in the vehicle configuration
and activity history blockchain network; and

 sending the token back to the part history blockchain
10 network to unlock the part history blockchains for the part to
allow adding information for the part to the part history
blockchains for the part in the part history blockchain network.

Clause 7. The method of any of clauses 1-6, wherein the
15 vehicle is an aircraft and the part is an aircraft part for the
aircraft.

Clause 8. A method of recording information for a part,
comprising:

20 receiving a part installation notification by a part
history blockchain network, wherein the part installation
notification identifies the part and indicates that the part is
installed on a vehicle, wherein the part history blockchain
network comprises part history blockchains for the part that are
25 configured to record the information for the part, and wherein
configuration and activity history information for the vehicle
is recorded in vehicle configuration and activity history
blockchains for the vehicle in a vehicle configuration and
activity history blockchain network; and

30 locking the part history blockchains for the part in
response to receiving the part installation notification to
prevent adding the information for the part to the part history

blockchains for the part for as long as the part is installed on the vehicle.

Clause 9. The method of clause 8, wherein the part installation notification comprises information regarding the installation of the part on the vehicle, and further comprising recording the information regarding the installation of the part on the vehicle in the part history blockchains for the part before locking the part history blockchains for the part.

Clause 10. The method of any of clauses 8-9 further comprising:

receiving a part removal notification by the part history blockchain network, wherein the part removal

notification identifies the part and indicates that the part is removed from the vehicle; and

unlocking the part history blockchains for the part in response to receiving the part removal notification to allow adding the information for the part to the part history

blockchains for the part in the part history blockchain network.

Clause 11. The method of clause 10, wherein the part removal notification comprises information regarding the removal of the part from the vehicle, and further comprising recording the information regarding the removal of the part from the vehicle in the part history blockchains for the part after unlocking the part history blockchains for the part.

Clause 12. The method of any of clauses 8-11 further comprising sending a token from the part history blockchain network to the vehicle configuration and activity history blockchain network, wherein the part history blockchains for the

part will remain locked until the token is returned back to the part history blockchain network.

Clause 13. The method of clause 12 further comprising:

5 receiving the token back from the vehicle configuration and activity history blockchain network by the part history blockchain network; and

unlocking the part history blockchains for the part in response to receiving the token back from the vehicle configuration and activity history blockchain network.

10

Clause 14. The method of any of clauses 8-13, wherein the vehicle is an aircraft and the part is an aircraft part for the aircraft.

15

Clause 15. An apparatus for recording information for a part, comprising a data processing system in a part history blockchain network configured to:

receive a part installation notification, wherein the part installation notification identifies the part and indicates that the part is installed on a vehicle, wherein the part history blockchain network comprises part history blockchains for the part that are configured to record the information for the part, and wherein configuration and activity history information for the vehicle is recorded in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network; and

20

25

lock the part history blockchains for the part in response to receiving the part installation notification to prevent adding the information for the part to the part history blockchains for the part for as long as the part is installed on the vehicle.

30

Clause 16. The apparatus of clause 15, wherein the part installation notification comprises information regarding the installation of the part on the vehicle, and wherein the data processing system is configured to record the information
5 regarding the installation of the part on the vehicle in the part history blockchains for the part before locking the part history blockchains for the part.

Clause 17. The apparatus of any of clauses 15-16,
10 wherein the data processing system is configured to:
receive a part removal notification, wherein the part removal notification comprises information regarding removal of the part from the vehicle, wherein the information regarding the removal of the part from the vehicle identifies the part and
15 indicates that the part is removed from the vehicle;
unlock the part history blockchains for the part in response to receiving the part removal notification to allow adding the information for the part to the part history blockchains for the part in the part history blockchain network;
20 and
record the information regarding the removal of the part from the vehicle in the part history blockchains for the part after unlocking the part history blockchains for the part.

25 Clause 18. The apparatus of any of clauses 15-17, wherein the data processing system is configured to send a token from the part history blockchain network to the vehicle configuration and activity history blockchain network, wherein the part history blockchains for the part will remain locked
30 until the token is returned back to the part history blockchain network.

Clause 19. The apparatus of clause 18, wherein the data processing system is configured to:

receive the token back from the vehicle configuration and activity history blockchain network; and

5 unlock the part history blockchains for the part in response to receiving the token back from the vehicle configuration and activity history blockchain network.

Clause 20. The apparatus of any of clauses 15-19,
10 wherein the vehicle is an aircraft and the part is an aircraft part for the aircraft.

CLAIMS:

1. A computer-implemented method of maintaining information regarding a part on a vehicle, the method comprising:

receiving, by a computer, information regarding an installation of the part on the vehicle;

recording the information for the part in part history blockchains for the part in a part history blockchain network;

recording, by the computer, the information regarding the installation of the part in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network; and

receiving, by the computer for as long as the part is installed on the vehicle, a token from the part history blockchain network, and locking, by the computer, the part history blockchains for the part and thereby preventing adding additional information for the part to the part history blockchains for the part until the token returns back to the part history blockchain network.

2. The method of claim 1, wherein locking the part history blockchains for the part comprises sending, by the computer, a part installation notification to the part history blockchain network, wherein the part installation notification identifies the part and indicates that the part is installed on the vehicle, and wherein the part history blockchain network locks the part history blockchains for the part in response to receiving the part installation notification.

3. The method of claim 1 further comprising:

receiving, by the computer, information regarding a removal of the part from the vehicle;

recording, by the computer, the information regarding the removal of the part from the vehicle in the vehicle

configuration and activity history blockchains for the vehicle in the vehicle configuration and activity history blockchain network; and

unlocking, by the computer, the part history blockchains for the part to allow adding the additional information for the part to the part history blockchains for the part in the part history blockchain network.

4. The method of claim 3 further comprising sending, by the computer, a part removal notification to the part history blockchain network, wherein the part removal notification identifies the part and indicates that the part is removed from the vehicle.

5. The method of claim 1 further comprising:

receiving, by the computer, information regarding a removal of the part from the vehicle;

recording, by the computer, the information regarding the removal of the part from the vehicle in the vehicle configuration and activity history blockchains for the vehicle in the vehicle configuration and activity history blockchain network; and

sending, by the computer, the token back to the part history blockchain network to unlock the part history blockchains for the part to allow adding the additional information for the part to the part history blockchains for the part in the part history blockchain network.

6. The method of claim 1, wherein the vehicle is an aircraft and the part is an aircraft part for the aircraft.

7. A computer-implemented method of recording information for a part, the method comprising:

receiving, by a computer, a part installation notification by a part history blockchain network, wherein the part installation notification identifies the part and indicates that the part is installed on a vehicle, wherein the part history blockchain network comprises part history blockchains for the part that are configured to record the information for the part, and wherein configuration and activity history information for the vehicle is recorded in vehicle configuration and activity history blockchains for the vehicle in a vehicle configuration and activity history blockchain network;

sending a token from the part history blockchain network to the vehicle configuration and activity history blockchain network; and

locking, by the computer for as long as the part is installed on the vehicle, the part history blockchains for the part and preventing adding additional information for the part to the part history blockchains for the part until the token is returned back to the part history blockchain network.

8. The method of claim 7, wherein the part installation notification comprises information regarding an installation of the part on the vehicle, and further comprising recording, by the computer, the information regarding the installation of the part on the vehicle in the part history blockchains for the part before locking the part history blockchains for the part.

9. The method of claim 7 further comprising:

receiving, by the computer, a part removal notification by the part history blockchain network, wherein the part removal notification identifies the part and indicates that the part is removed from the vehicle; and

unlocking, by the computer, the part history blockchains for the part in response to receiving the part removal notification to allow adding the additional information for the part to the part history blockchains for the part in the part history blockchain network.

10. The method of claim 9, wherein the part removal notification comprises information regarding a removal of the part from the vehicle, and further comprising, by the computer, recording the information regarding the removal of the part from the vehicle in the part history blockchains for the part after unlocking the part history blockchains for the part.

11. The method of claim 7 further comprising:

receiving, by the computer, the token back from the vehicle configuration and activity history blockchain network by the part history blockchain network; and

unlocking, by the computer, the part history blockchains for the part in response to receiving the token back from the vehicle configuration and activity history blockchain network.

12. The method of claim 7, wherein the vehicle is an aircraft and the part is an aircraft part for the aircraft.

13. An apparatus configured to record information for a part, such that the apparatus comprises a data processing system in a part history blockchain network configured to:

receive a part installation notification configured to identify the part and indicate an installation of the part on a vehicle, wherein the part history blockchain network comprises part history blockchains for the part that are configured to record the information for the part, and wherein vehicle configuration and activity history blockchains for the

vehicle are configured to record configuration and activity history information for the vehicle in a vehicle configuration and activity history blockchain network;

send a token from the part history blockchain network to the vehicle configuration and activity history blockchain network; and

lock, responsive to receipt of the part installation notification for as long as the part is installed on the vehicle, the part history blockchains for the part to prevent an addition of more information for the part to the part history blockchains for the part until the token is returned back to the part history blockchain network.

14. The apparatus of claim 13, wherein the part installation notification comprises information regarding the installation of the part on the vehicle, and wherein the data processing system is configured to record the information regarding the installation of the part on the vehicle in the part history blockchains for the part before locking the part history blockchains for the part.

15. The apparatus of claim 13, wherein the data processing system is configured to:

receive a part removal notification, wherein the part removal notification comprises information regarding a removal of the part from the vehicle, wherein the information regarding the removal of the part from the vehicle identifies the part and indicates that the part is removed from the vehicle;

unlock the part history blockchains for the part in response to receiving the part removal notification to allow adding additional information for the part to the part history blockchains for the part in the part history blockchain network; and

record the information regarding removal of the part from the vehicle in the part history blockchains for the part after unlocking the part history blockchains for the part.

16. The apparatus of claim 13, wherein the data processing system is configured to:

receive the token back from the vehicle configuration and activity history blockchain network; and

unlock the part history blockchains for the part in response to receiving the token back from the vehicle configuration and activity history blockchain network.

17. The apparatus of claim 13, wherein the vehicle is an aircraft and the part is an aircraft part for the aircraft.

18. The method of claim 1, further comprising a trusted entity with permission to access, read, and submit changes to the part history blockchains for the part.

19. The method of claim 7, further comprising a trusted entity with permission to access, read, and submit changes to the part history blockchains for the part.

20. The apparatus of claim 13, further comprising a trusted entity with permission to access, read, and submit changes to the part history blockchains for the part.