

DESCRIPTION**ANIMATION CONTROL APPARATUS**

5 The present invention relates to the generation of animated sequences by animation suites assembling those images from libraries of prestored components. In particular, the invention relates to a method and apparatus for enabling real-time interactive control of sequences of animated graphical images in an animated display, and to a method and apparatus for the control
10 and monitoring of generated sequences of body part motions.

 For the displayed case, the animation may comprise a simple two-dimensional cartoon with a largely static background over which characters are moved, with the character appearance over successive frames being called up
15 from a library of stored character poses. Where the character executes a repetitive action, for example walking across the screen, the suite may store the successive poses required for the walking action as a sequence to be looped, with associated updating of the character screen position.

 In a more complex animation, whether displayed or just modelled in
20 terms of related component movements, the subject (image) may be a three-dimensional model of, for example, a human or animal body. Again however, the basic body part shapes and movement sequences thereof are prestored and may be called up as required. An example of such an animation suite is "Life Forms", a compositional tool for the creation of dance choreography,
25 developed by the Simon Fraser University, B.C. Canada and marketed in various forms through Kinetic Effects Incorporated. Note that "Life Forms" is a trade mark of Kinetic Effects Inc of Seattle, USA, and all uses of the term herein acknowledge the fact. The development of "Life Forms" is described in a paper entitled "The Evolution of an Interface for Choreographers" by T.W.
30 Calvert and others from SFU, presented at InterChi '93, 24-29 April 1993.

 In order to improve the realism of animations and simulations, it has

been proposed to apply artificial intelligence (AI) techniques to control of the animations to make them more reactive to constraints of the virtual world within which they are modelled. Rule-based languages have been suggested as advantageous due to their facility for modelling constraint relationships.

5 Rule-based processor systems typically support behaviour languages in which behaviours are either simple operations performed on a value, or rules, where a rule defines logical and temporal relations between events (behaviour state changes). Accordingly, events associated with the condition portion of a rule (also known as the left hand side behaviours of a rule) cause subsequent
10 events associated with the response portion (right hand side behaviour) of the rule. An example of such a rule-based real time language is Real Time ABLE (RTA), described in Proceedings of the European Simulation Multiconference 1991 at pages 226-231. ABLE stands for Agent Behaviour Language and is a highly concurrent production rule language for simulating agents and multiple
15 agent systems. ABLE provides for tighter integration of time with the production rule system. The language may conveniently be compiled into a representation of a virtual asynchronous logic circuit which comprises a number of interconnected elements such as AND elements, OR elements, delay elements and so on. RTA uses a propagation technique as opposed to a
20 search strategy to obtain a fast production rule system. A further example of a rule-based language is given in "The Behaviour Language; User's Guide" by R A Brooks, AI Memo 1227, Massachusetts Institute of Technology Artificial Intelligence Laboratory, April 1990.

25 A problem which arises with the use of propagating rule-based systems is that of coordinating the event driven switching of rules and constraints with the more synchronous nature of the selection/rendering/display sequence of the animation generation.

30 It is therefore an object of the present invention to enable control of an animation or simulation suite by a rule-based processor system, whilst minimising discontinuities due to the differing timing systems.

In accordance with a first aspect of the present invention there is provided apparatus for controlling a computer-generated animation suite, the suite comprising stored libraries of image components and component motion parameters and means for generating sequences of image frames through
5 which one or more of the image components are moved in accordance with one or more of the motion parameters, the apparatus comprising: interface means connectable to the image generating means and including storage means holding a library of function specifications each of which, when called and applied to the image generating means, initiates one or a predetermined
10 sequence of image component movements; and a propagating rule-based processor connected to the interface means and containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied; wherein the processor is coupled to receive data relating to one or more features of a generated image
15 frame, said data satisfying the condition portion of at least one rule, and wherein the calling of each of the interface function specifications is the response portion of a respective rule.

In order to avoid synchronisation problems, timing management means are preferably provided to initiate generation of each successive image frame
20 by the animation suite following initiation and completion of a predetermined period of rule firing propagation in the rule-based processor. For real time operation of the animation suite, the timing management means may suitably be arranged to initiate generation of successive image frames at a substantially constant frequency such as 30 frames per second.

25 In accordance with a second aspect of the present invention there is provided apparatus for controlling a computer-generated simulation suite, the suite comprising stored libraries of body components and component relative motion parameters and means for generating motion sequences for one or more of the body components in which the components are moved in
30 accordance with one or more of the motion parameters, the apparatus comprising: interface means connectable to the sequence generating means



and including storage means holding a library of function specifications each of which, when called and applied to the image generating means, initiates one or a predetermined sequence of body component movements; and a propagating rule-based processor connected to the interface means and
5 containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied; wherein the processor is coupled to receive data relating to one or more features of a body component during a motion sequence, which data satisfies the condition portion of at least one rule, and wherein the calling of each of the
10 interface function specifications is the response portion of a respective rule.

Suitably, the data to the processor is received via the interface means and specifies one or more predetermined conjunctions of image or body component features, and the propagating rule-based processor is suitably of a type comprising means for modelling an asynchronous logic circuit as a
15 plurality of circuit elements the functions of which are governed by the set of rules (for example a processor supporting an RTA rule-set).

The apparatus according to either aspect of the invention preferably includes user interface means, connected to the rule-based processor, by use of which a user may selectively modify the set of rules, or may selectively call
20 one or more of the interface function specifications, the processor holding a subset of the rules each having a respective one of the interface function specifications as their respective response portion and each having a different predetermined user input as their respective condition portion.

Also in accordance with the first and second aspects of the present
25 invention there are provided methods for controlling an animation suite and a simulation suite respectively, as defined in the attached claims to which reference should now be made.

Further features and advantages of the present invention will become
30 apparent from reading of the following description of preferred embodiments of the present invention, given by way of example only, and with reference to the



accompanying drawings in which:

Figure 1 is a block schematic diagram of a rule-based processor and animation suite linked by an interface unit embodying the present invention;

Figure 2 is a schematic representation of user interface options in relation to apparatus such as that of Figure 1;

Figure 3 is a flow chart illustrating timing management in the apparatus of Figure 1;

Figure 4 is a schematic representation of the components of a simulation suite arrangement according to an alternative embodiment of the invention; and

Figure 5 is a table listing commands of a function set held by the interface unit of Figure 1.

Figure 1 shows apparatus embodying the present invention providing an interfacing link between a rule-based processor containing a population of RTA rules and an animation suite modelling a human form and its movements. Through the interfacing link, the processor is enabled to control a basic set of features associated with a single or multi-character animation.

The rule-based processor 10 has associated with it a random access memory (RAM) 12 which provides a number of discrete storage areas, a first of which 14 holds a table containing details of the various elements of the asynchronous logic circuit representation of the compiled population of RTA rules. Each of the behaviours (register elements), time annotations (delay elements) logic function elements and rules has a row in the table. Each row in the table identifies the element number, a state flag of the device, a queued status flag of the device, the internal status, and a propagate function start address. When the state of the element to which the row of the table relates changes (referred to herein as an event), a propagate function is executed to effect any appropriate changes to all of the elements which may be affected by such a change. These propagate functions are conveniently arranged at certain memory locations or start addresses. Changing the state of elements by propagation in such a manner rather than by searching for all of the

elements affected by an event allows the apparatus to operate efficiently.

The propagate functions starting at the start addresses are stored in another area 16 of the RAM 12; the RAM also provides further storage areas for future element state changes 18, an event stack 20, and a program store 22. The program store 22 holds the set of rules for an agent, each in the form of at least one specific behaviour defining a condition and at least one further behaviour defining the associated response. The program store 22 and the propagate functions 16 could, if desired, be stored in another memory device, for example a read only memory.

The RAM 12 is connected to the processor 10 by a data bus 24 and an address bus 26 in known manner. Also in known manner, a clock (CLK) 28 is connected to the processor. The processor 10 operates on the agent rules from program store 22 responding to the satisfaction of condition behaviours by generating one or more further behaviours defining the associated response. A user interface device (UID) 30 enables input of control data and commands as will be described.

The storage area 18 for future agent element state changes is arranged as a two row table containing a plurality of time slots and element numbers. Any number of elements numbers can be stored to correspond to a particular time slot and the states of these elements will all be changed during that time slot. The table may be arranged for a consecutive sequence of time slots, but it is preferred to use a stack containing only those time slots for which element numbers are stored, with the facility to insert element numbers and time slots as required due to operation of the program.

Generally, all of an agent's element state changes except those corresponding to delay elements will be executed in the current time slot although other element state changes can be also delayed if desired. Those element state changes which are to occur without a time delay may be placed in the event stack 20 for execution in the near future - i.e. later in the current time slot, but before moving to the next time slot for which an event is specified.

The animation suite, indicated generally at 32, comprises a graphics engine, a component store 36, and a display driver 38 which outputs a signal for display on monitor/CRT 40. The component store 36 provides short term memory for current frame or sequence generation and holds the relevant image component and movement parameter information called up from mass storage 52 which may be, for example, a CD-ROM store. In an alternative embodiment (to be described), the animation suite may also have a user interface and clock source: in the embodiment shown, however, these functions are handled via an interface unit 42 linking the suite to the rule-based processor.

In operation, the animation suite generates images by initially selecting a skeleton (wire frame model) from a library of skeletons held in component store 36 and determining its initial position and orientation within the virtual world. Where the skeleton is of an articulated nature, for example when modelling the human body, the determination may be a staged process starting with the angles of the various joints to produce an initial pose and then positioning and orienting the posed skeleton within the virtual world. The final stage is to "flesh out" the skeleton which may be done by conventional rendering techniques or by fitting of surfaces from the component store 36.

In order to provide for control of the suite by the rule-based processor 10, the interface unit 42 maintains a function set in a memory 44 accessed by a local processor 46, which processor is connected via respective data buses 48,50 to the rule-based processor 10 and the graphics engine 34. The interface unit processor 46 links each of the functions to the control set of the graphics engine 34, such that each specifies a particular operation or sequence of operations to be performed by the suite when called. Where a sequence is specified, it may apply to a whole "body" or to components thereof; in the human body example, this would allow one sequence to specify a walking motion for the legs with another specifying a swinging movement of the arms, which sequences may be run independently of each other.

The control set functions also provide 'handles' for the rule-based processor, enabling the implementation of a function to be specified as the

response portion of a rule, such that the rules define a relationship between user input and real-time playback of an animated sequence. By applying constraint functions of the rule-based system, relationships can also be specified between actions of an animated character and features of the virtual world in which it is modelled and also between the actions of two or more separately modelled characters.

The UID may take various forms depending on the form and level of interaction required and, rather than reading directly into the rule-based processor as shown in Figure 1, it may be connected to the graphics engine of the animation suite or interfaced directly to the RTA program store. Figure 2 schematically represents the link between an RTA rule set 60, the virtual world 62 in which the animation is generated, and the hardware 64 handling the generation of images. The user input may be to each one of the three stages (indicated by UI.1, UI.2, and UI.3) or combinations thereof depending on the application.

Input UI.1 to the RTA rule set would enable control of the animated character in terms of how it reacts to constraints imposed by the virtual world. Input UI.2 to the virtual world would enable control and alteration of the feature with which the animated character interacts on the basis of the RTA rule set. Input UI.3 to the hardware would allow variation in the appearance of the animated character by control of the operation of rendering the images.

The physical construction of the UID would also depend on the form of interaction and control, and may range from a mouse or joystick, through keypads or keyboards, to a sensor array allowing modelling of physical objects in the virtual world.

The timing control of the RTA and animation program is as shown by the flow chart of Figure 3. Initially, the RTA time slot is incremented (100) such that rule firings due to condition changes since the last time slot (as well as those queued for that particular time slot) can begin to propagate through the rule set. Next, at 102, the image frame based on the called-up functions from the previous propagation time slot is calculated, rendered, and displayed.

Once this has occurred, the user interface is checked (104) and any newly-entered commands or data are logged for handling during the next RTA propagation slot. The timer then waits (at 106) until a predetermined time and then (at 108) it sends a frame advance signal to the animation suite. The
5 timing control then loops back to the first process of initiating the next RTA propagation slot.

For real-time running of an animation, the frame advance signal is preferably of a substantially constant frequency (such as 30 frames/sec). By controlling the frame advance in dependence on the RTA propagation,
10 however, slower frame updates may be accommodated where particularly complex rule constraints or image details exist. Alternatively, for applications where RTA propagation time plus generation and rendering time will always be less than one frame period, the frame advance signal may be generated as a periodic signal by a clock within the animation suite, with the steps of initiating
15 an RTA propagation slot and checking for user input being synchronised to this.

In an alternative embodiment, the system may be concerned specifically with the inter-relationships between the moving body components and the full rendition of the graphical images may not be required. In this case, the generalised system arrangement may be as shown in Figure 4, with an RTA
20 rule population 120, body component animation engine 130 and simulation suite connected together, and with the simulation suite further being coupled to a model of the virtual world 150. As shown in dashed outline, a graphics engine 160 might be provided to display the output from the simulation suite.

The contents of the function set will to some extent be dependent on the
25 form of animation. The table of Figure 5 gives a non-exhaustive list of preferred commands for a function set where the animation suite is generating a sequence of frames modelling the movement of a three-dimensional body within a three-dimensional virtual world. The implementation of these commands is as follows:

30 - Create: This creates a new figure based on an identified one of a stored library of skeletons (wire frame models). The response to this command

should be an identification ("Figure") for the new figure.

- Delete: Deletes the identified figure.
- Set Sequence: This specifies a movement sequence for a given figure, with the sequence to commence n frames from the current frame. If no offset is specified, any currently active sequence is replaced by the new sequence,
5 although an "interrupt" period is preferably provided to enable interpolation between the figure pose and position at the interrupt and that at the start of the new sequence. A time warp factor (see below) may also be specified.
- Set Loop Mode: This indicates whether a current sequence for a given figure
10 is to be looped (for example a walking action) or whether it is just to be played through once.
- Set Warp Factor: This specifies an extended or reduced period over which the current sequence is to be played out. If it has the capability, this may be handled by the graphics engine interpolating intermediate frames based on
15 specified ones. Alternatively, the warp may be handled in RTA by either changing the time annotations of individual rules or by speeding up the entire rule population, that is to say by increasing the frequency at which the successive RTA time periods are called.
- Advance Time: This advances the position of the current sequence by n
20 frames.
- Display: This calls the graphics engine to render a frame for the current figure position within the sequence.
- Bounds: This calculates a boundary box in three-dimensions around the figure in its position at the current frame of the sequence.
- 25 - Get Position: This calculates the current position of the figure within the virtual world; this is particularly useful where the character has been following a lengthy sequence.
- Get Orientation: This calculates the current orientation of the figure within the virtual world (i.e. which way the figure is facing).
- 30 - Get Pose: This calculates the current pose of the figure, that is to say the position and orientation of the various body components in relation to one

another.

- Set Position: This allows positioning of the figure within the virtual world.
- Set Orientation: This allows orienting of the figure at a specified position within the virtual world.

5 As will be appreciated, many more functions may be specified depending on the particular application. For example, functions would generally be required for initialisation of the system and data loading, and may also be required for diagnostic functions.

10 From reading the present disclosure, other modifications and variations will be apparent to persons skilled in the art. Such modifications and variations may involve other features which are already known in the art and which may be used instead of or in addition to features already described herein. For example, whilst shown in Figure 1 as two separate devices, it will be recognised that the rule-based processor 10 and interface processor 46 may
15 be a single device, although preferably with multi-tasking capability. Additionally, although Figure 1 shows local mass storage 52 for image component details and a local store 22 for the rule population, it will be understood that either or both may be supplied from remote storage over, for example, a data network with the animation suite and/or rule-based processor
20 being provided with a suitable interface to that network.

25 Although claims have been formulated in this application to particular combinations of features, it should be understood that the scope of the disclosure of the present application also includes any novel feature or combination of features disclosed herein either explicitly or implicitly, whether
30 or not relating to the same invention as presently claimed in any claim and whether or not it mitigates any or all of the same technical problems as does the presently claimed invention. The applicants hereby give notice that new claims may be formulated to such features and/or combinations of such features during prosecution of the present application or of any further application derived therefrom.



THIS SHEET HAS BEEN
REPLACED

WO 97/07483

PCT/IB96/00808

12

CLAIMS

1. Apparatus for controlling a computer-generated animation suite, the suite comprising stored libraries of image components and component
5 motion parameters and means for generating sequences of image frames through which one or more of the image components are moved in accordance with one or more of the motion parameters, the apparatus comprising:

interface means connectable to the image generating means and including storage means holding a library of function specifications each of
10 which, when called and applied to the image generating means, initiates one or a predetermined sequence of image component movements; and

a propagating rule-based processor connected to the interface means and containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied;

15 wherein the processor is coupled to receive data relating to one or more features of a generated image frame, said data satisfying the condition portion of at least one rule, and wherein the calling of each of the interface function specifications is the response portion of a respective rule.

20 2. Apparatus as claimed in Claim 1, wherein said data is received via the interface means and specifies one or more predetermined conjunctions of image frame features.

3. Apparatus for controlling a computer-generated simulation suite, the suite comprising stored libraries of body components and component
25 relative motion parameters and means for generating motion sequences for one or more of the body components in which the components are moved in accordance with one or more of the motion parameters, the apparatus comprising:

30 interface means connectable to the sequence generating means and including storage means holding a library of function specifications each of





THIS SHEET HAS BEEN
REPLACED

WO 97/07483

PCT/IB96/00808

13

which, when called and applied to the image generating means, initiates one or a predetermined sequence of body component movements; and

a propagating rule-based processor connected to the interface means and containing a set of rules each defining a response to a given condition with
5 the processor generating a response when the associated condition is satisfied;
wherein the processor is coupled to receive data relating to one or more features of a body component during a motion sequence, which data satisfies the condition portion of at least one rule, and wherein the calling of each of the interface function specifications is the response portion of a respective rule.

10

4. Apparatus as claimed in Claim 3, wherein said data is received via the interface means and specifies one or more predetermined conjunctions of body component features.

15

5. Apparatus as claimed in Claim 1 or Claim 3, wherein said propagating rule-based processor comprises means for modelling an asynchronous logic circuit as a plurality of circuit elements the functions of which are governed by said set of rules.

20

6. Apparatus as claimed in Claim 1 or Claim 3, further comprising user interface means, connected to the rule-based processor, by use of which a user may selectively modify the set of rules.

25

7. Apparatus as claimed in Claim 1 or Claim 3, further comprising user interface means, connected to the rule-based processor, by use of which a user may selectively call one or more of the interface function specifications, the processor holding a subset of the rules each having a respective one of the interface function specifications as their respective response portion and each having a different predetermined user input as their respective condition
30 portion.

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

WO 97/07483

PCT/IB96/00808

14

8. Apparatus as claimed in Claim 1, further comprising timing management means arranged to initiate generation of each successive image frame by the animation suite following initiation and completion of a predetermined period of rule firing propagation in the rule-based processor.

5

9. Apparatus as claimed in Claim 8, wherein the timing management means is arranged to initiate generation of successive image frames at a substantially constant frequency.

10

10. A method of controlling a computer-generated animation suite, the suite comprising stored libraries of image components and component motion parameters and means for generating sequences of image frames through which one or more of the image components are moved in accordance with one or more of the motion parameters, the method comprising:

15

providing a library of function specifications each of which, when called and applied to the image generating means, initiates one or a predetermined sequence of image component movements; and

20

providing a propagating rule-based processor containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied;

25

wherein data relating to one or more predetermined image frame features comprises the condition portion of at least one rule, and wherein the calling of each of the library of function specifications is the response portion of a respective rule.

30

11. A method as claimed in Claim 10, wherein said data is received from the animation suite and specifies one or more predetermined conjunctions of image frame features.

12. A method as claimed in Claim 11, wherein the or one of the predetermined conjunctions specifies a proximity or range of proximity values

This Sheet Has Been Replaced





between two image components.

13. A method of controlling a computer-generated simulation suite, the suite comprising stored libraries of body components and component relative
5 motion parameters and means for generating motion sequences for one or more of the body components in which the components are moved in accordance with one or more of the motion parameters, the method comprising:

providing a library of function specifications each of which, when called and applied to the sequence generating means, initiates one or a
10 predetermined sequence of body component movements; and

providing a propagating rule-based processor containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied;

wherein data relating to one or more body component features during a
15 motion sequence satisfies the condition portion of at least one rule, and wherein the calling of each of the library of function specifications is the response portion of a respective rule.

14. A method as claimed in Claim 13, wherein said data is received
20 from the simulation suite and specifies one or more predetermined conjunctions of body component features.

15. A method as claimed in Claim 13, wherein a further library of function specifications is provided, each being the response portion of a
25 respective rule, and the calling of each causes the simulation suite to output information relating to one or more body component features.

16. A method as claimed in Claim 15, wherein the simulation suite models motion of one or more body components within a three-dimensional
30 virtual world and the information output in response to the calling of one of the further library of function specifications specifies an instantaneous position of



the, or one of the, body components within the virtual world.

17. A method as claimed in Claim 15, wherein the simulation suite models motion of one or more body components within a three-dimensional virtual world and the information output in response to the calling of one of the
5 further library of function specifications specifies an instantaneous orientation of the, or one of the, body components within the virtual world.

18. A method as claimed in Claim 15, wherein the simulation suite
10 models motion of two or more body components within a three-dimensional virtual world and the information output in response to the calling of one of the further library of function specifications specifies an instantaneous relative orientation of said at least two body components.

1/4




FIG. 1

2/4




FIG. 2




FIG. 3

3/4




FIG. 4

4/4

Command	Variables	Function
Create	Skeleton	Creates a new figure
Delete	Figure	Deletes the given figure
Set Sequence	Figure, Sequence, Offset (n), (Warp)	Sets the sequence for a given figure
Set Loop Mode	Figure, Loop	Specifies whether the current sequence loops
Set Warp Factor	Figure, Warp	Sets the time warp factor
Advance Time	Figure, Offset (n)	Advances the position of the current sequence
Display	Figure	Draws the figure for the current sequence position
Bounds	Figure, Position	Calculates the bounding box for the current sequence position
Get Position	Figure	Calculates the current position of the figure in world space
Get Orientation	Figure	Calculates the current orientation of the figure in world space
Get Pose	Figure	Calculates the current pose of the figure
Set Position	Figure, Position	Sets the current position of the figure in world space
Set Orientation	Figure, Orientation	Sets the current orientation of the figure in world space

FIG. 5

09 FEB 1999

3

9703414-4

In accordance with a first aspect of the present invention there is provided apparatus for controlling a computer-generated animation suite, the suite comprising stored libraries of image components and component motion parameters and means for generating sequences of image frames through which one or more of the image components are moved in accordance with one or more of the motion parameters, the apparatus comprising:

interface means connectable to the image generating means and including storage means holding a library of function specifications each of which, when called and applied to the image generating means, initiates one or a predetermined sequence of image component movements; and

a propagating rule-based processor connected to the interface means and containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied, the processor being further coupled to receive data relating to one or more features of a generated image frame, with said data satisfying the condition portion of at least one rule, and the calling of each of the interface function specifications comprising the response portion of a respective rule;

wherein the apparatus further comprises user interface means, connected to the rule-based processor, by use of which a user may selectively call one or more of the interface function specifications, the processor holding a subset of the rules each having a respective one of the interface function specifications as their respective response portion and each having a different predetermined user input as their respective condition portion.

In order to avoid synchronisation problems, timing management means are preferably provided to initiate generation of each successive image frame by the animation suite following initiation and completion of a predetermined period of rule firing propagation in the rule-based processor. For real time operation of the animation suite, the timing management means may suitably be arranged to initiate generation of successive image frames at a substantially constant frequency such as 30 frames per second.

In accordance with a second aspect of the present invention there is provided apparatus for controlling a computer-generated simulation suite, the suite comprising stored libraries of body components and component relative motion parameters and means for generating motion sequences for one or more of the body components in

09 FEB 1999

4

9703414-4

which the components are moved in accordance with one or more of the motion parameters, the apparatus comprising:

interface means connectable to the sequence generating means and including storage means holding a library of function specifications each of which, when called and applied to the image generating means, initiates one or a predetermined sequence of body component movements; and

5 a propagating rule-based processor connected to the interface means and containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied, the processor being further coupled to receive data relating to one or more features of a
10 body component during a motion sequence, with said data satisfying the condition portion of at least one rule, and with the calling of each of the interface function specifications comprising the response portion of a respective rule;

wherein the apparatus further comprises user interface means, connected to the
15 rule-based processor, by use of which a user may selectively call one or more of the interface function specifications, the processor holding a subset of the rules each having a respective one of the interface function specifications as their respective response portion and each having a different predetermined user input as their respective condition portion.

20 Suitably, the data to the processor is received via the interface means and specifies one or more predetermined conjunctions of image or body component features, and the propagating rule-based processor is suitably of a type comprising means for modelling an asynchronous logic circuit as a plurality of circuit elements the functions of which are governed by the set of rules (for example a processor supporting
25 an RTA rule-set).

The apparatus according to either aspect of the invention preferably includes user interface means, connected to the rule-based processor, by use of which a user may selectively modify the set of rules. _____

30 Further features and advantages of the present invention will become apparent from reading of the following description of preferred embodiments of the present invention, given by way of example only, and with reference to the

REPLACEMENT SHEET

019 FEB 1999

9703414-4

CLAIMS



1. Apparatus for controlling a computer-generated animation suite, the suite comprising stored libraries of image components and component
5 motion parameters and means for generating sequences of image frames through which one or more of the image components are moved in accordance with one or more of the motion parameters, the apparatus comprising:

interface means connectable to the image generating means and including storage means holding a library of function specifications each of
10 which, when called and applied to the image generating means, initiates one or a predetermined sequence of image component movements; and

a propagating rule-based processor connected to the interface means and containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied,
15 the processor being further coupled to receive data relating to one or more features of a generated image frame, with said data satisfying the condition portion of at least one rule, and the calling of each of the interface function specifications comprising the response portion of a respective rule;

wherein the apparatus further comprises user interface means,
20 connected to the rule-based processor, by use of which a user may selectively call one or more of the interface function specifications, the processor holding a subset of the rules each having a respective one of the interface function specifications as their respective response portion and each having a different predetermined user input as their respective condition portion.

25

2. Apparatus as claimed in Claim 1, wherein said data is received via the interface means and specifies one or more predetermined conjunctions of image frame features.

30 3. Apparatus for controlling a computer-generated simulation suite, the suite comprising stored libraries of body components and component relative motion parameters and means for generating motion sequences for one



REPLACEMENT SHEET

REPLACEMENT SHEET

09 FEB 1999

13

9703414-4

or more of the body components in which the components are moved in accordance with one or more of the motion parameters, the apparatus comprising:

5 interface means connectable to the sequence generating means and including storage means holding a library of function specifications each of which, when called and applied to the image generating means, initiates one or a predetermined sequence of body component movements; and

10 a propagating rule-based processor connected to the interface means and containing a set of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied, the processor being further coupled to receive data relating to one or more features of a body component during a motion sequence, with said data satisfying the condition portion of at least one rule, and with the calling of each of the interface function specifications comprising the response portion of a

15 respective rule;

wherein the apparatus further comprises user interface means, connected to the rule-based processor, by use of which a user may selectively call one or more of the interface function specifications, the processor holding a subset of the rules each having a respective one of the interface function

20 specifications as their respective response portion and each having a different predetermined user input as their respective condition portion.

4. Apparatus as claimed in Claim 3, wherein said data is received via the interface means and specifies one or more predetermined conjunctions of

25 body component features.

5. Apparatus as claimed in Claim 1 or Claim 3, wherein said propagating rule-based processor comprises means for modelling an asynchronous logic circuit as a plurality of circuit elements the functions of which

30 are governed by said set of rules.

6. Apparatus as claimed in Claim 1 or Claim 3, further comprising



REPLACEMENT SHEET

REPLACEMENT SHEET

09 FEB 1999

14

9703414-4

user interface means, connected to the rule-based processor, by use of which a user may selectively modify the set of rules.

5 7. Apparatus as claimed in Claim 1, further comprising timing management means arranged to initiate generation of each successive image frame by the animation suite following initiation and completion of a predetermined period of rule firing propagation in the rule-based processor.

10 8. Apparatus as claimed in Claim 7, wherein the timing management means is arranged to initiate generation of successive image frames at a substantially constant frequency.


9703414-4

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: G06T 15/70, G09G 1/16		A1	(11) International Publication Number: WO 97/07483
			(43) International Publication Date: 27 February 1997 (27.02.97)
(21) International Application Number: PCT/IB96/00808		(61) Designated States: AU, CA, CN, JP, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 16 August 1996 (16.08.96)			
(30) Priority Data: 9517115.3 21 August 1995 (21.08.95) GB		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE).			
(72) Inventors: ALLEN, Richard, John; 44 Earlswood Road, Redhill, Surrey (GB). GALLERY, Richard, David; 18 Farguharson Road, Croydon, Surrey CR0 2UH (GB).			
(74) Agent: WHITE, Andrew, G.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).			

(54) Title: ANIMATION CONTROL APPARATUS



(57) Abstract

A method and apparatus are described for controlling a computer-generated animation suite (32), where the suite generates sequences of image frames from stored libraries of image components and component motion parameters. An interface (42) includes a store (44) of function specifications each of which, when called and applied to the animation suite, initiates one or a predetermined sequence of image component movements. A rule-based processor (10) comprises means for modelling an asynchronous logic circuit as a plurality of circuit elements, the functions of which are governed by a stored set (14, 22) of rules each defining a response to a given condition with the processor generating a response when the associated condition is satisfied. Predetermined conjunctions of image frame features are specified as the condition portion of some of the rules, and the calling of each of the interface function specifications is the response portion of a respective rule. A method and apparatus for the control of a motion simulation suite are also described.