

9703339-3



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E21C 35/18	A1	(11) International Publication Number: WO 96/27072 (43) International Publication Date: 6 September 1996 (06.09.96)
--	-----------	---

(21) International Application Number: PCT/US96/02707

(22) International Filing Date: 26 February 1996 (26.02.96)

(30) Priority Data:

(1) 08/394,908 ✓

27 February 1995 (27.02.95) ✓

US ✓

Published

With international search report.


(71) Applicant: CHAMPION EQUIPMENT CO. [US/US]; 8140
Rosecrans Avenue, Paramount, CA 90723 (US).(72) Inventors: KOSOBRODOV, Yuriy; 4646 Los Feliz Boulevard,
Los Angeles, CA 90027 (US). JUE, Vincent; 22 Silver
Saddle Lane, Rollin Hills E., CA 90274 (US).(74) Agent: ZBOROVSKY, Ilya; 6 Schoolhouse Way, Dix Hills,
NY 11746 (US).

1 PD.

(54) Title: METHOD OF CUTTING AND CUTTING ROTATIVE BIT ✓

(57) Abstract

A cutting, self-rotating, and self-sharpening tool has a rotatable cutting element (2), generally circular, which is mounted and displaced so that the cutting element (2) has an attack angle between 90° and 120°, and a skew angle between 5° and 40°. The cutting element (2) has a convex front face and relief and rake angles that vary along the perimeter of the cutting edge.



DescriptionMethod of Cutting and Cutting Rotative BitTechnical Field

5 The present invention generally relates to a method and design of cutting and cutting rotative bits, which can be used for excavation, planing and drilling of rock and soil and other non-metallic brittle materials, for destruction, production and treatment of construction materials, and which can
10 be mounted on corresponding equipment, intended for cutting and crushing of the above mentioned materials.

Background Art

15 Generally, the cutting process mechanism is as shown in FIG. 1. Cutting of a material, like rock, is carried out due to thrust force T and normal component C_n of the cutting force, generated by an equipment drive. Under the action of these forces, the tool simultaneously moves in horizontal and
20 vertical directions generating complicated stresses that overwhelm rock resistance.

Under the action of the force C_n , distributed over the bit front face, compressive stresses are formed in the rock which are not large enough for
25 destruction but preload the rock to resist further strain.

Under the action of the force T , shear stress is produced in the rock due to the high level of load concentration generated by the bit's cutting
30 edge. This shear stress provides generation and development of destructive cracks in the brittle material.

- 2 -

1 At the same time, both forces C_n and T
generate a confined zone of superpressurized rock,
located next to the bit cutting edge. This so-
called kernal is an accumulator of energy which can
5 discharge in an explosive way when accumulated
energy exceeds ultimate rock resistance.

 Because the previously mentioned destructive
cracks propagate from the cutting edge in the
direction of lowest resistance, they initially tend
10 toward the open surface of the rock. However,
these cracks cannot bypass the enhanced resistance
of the volume of the rock compressed by C_n .
Consequently, the destructive cracks pass around
the compressed rock and reach the open surface at
15 a distance L from the bit front face, isolating the
stressed volume of rock and separating this chip
from the entire rock massif.

 Under continuous, combined action of
compressive and shear stresses, successive rock
20 chips are separated from the rock mass in a whole
or nearly whole condition chiefly due to long,
active destructive cracks and kernal explosion
after sufficient energy is accumulated to overcome
the crack shortfall.

25 Therefore, in an effective rock cutting
process, it is necessary to maintain a significant
load concentration at the bit cutting edge. This
is provided by a positive relief angle δ of the bit
so that normal force, T , acts only on a thin line
30 of contact between rock and bit cutting edge. This
line contact is critical since cutting ability
degrades rapidly with relatively small wear in this
area. A sizeable width to this contact area
greatly decreases stress concentration in the rock
35 and greatly inhibits long crack generation.

- 3 -

1 The effective cutting bit must have an optimal
combination of high cutting ability and high
durability of the cutting element, reliable
protection from overloading, preservation of the
5 bit positive relief angle, and maintenance of other
initial parameters throughout the lifetime of the
cutting bit.

A plurality of tools have been developed with
the objective of achieving some of the above
10 mentioned qualities.

The first group of rock-destructing tools is
comprised of cutting bits with non-rotatable
cutting elements. U.S. Patent 1,174,433 discloses
a non-rotating cutter which has a convex front
15 face. But it has a positive rake angle; the angle
between its longitudinal axis and the cut (treated)
surface behind a bit (defined as attack angle) is
less than 90°. It has a short cutting edge,
positive rake angle and small included angle.
20 Compared to the present invention, this bit has low
durability and wear resistance and it only can be
used for destruction of the soft and not abrasive
rock.

U.S. Patents 4,538,691 and 4,678,237 disclose
25 non-rotating cutting tools having rock-destructing
elements with a flat front face and substantial
negative rake angle, providing protection of the
bit from overloading due to operation of a lifting
force. However, the described bit has a low
30 cutting ability and requires significant thrust
force for penetration into rock. Its attack angle
does not exceed 90°.

U.S. Patent 4,538,690; 4,558,753 and 4,593,777
disclose non-rotating cutting bits, having a rock-
35 destructing element with a concave front face,

- 4 -

1 oriented at a large negative rake angle, which is
used to increase bit durability (including
protection against overload). However, this bit
also has low cutting and penetration ability. The
5 bit is oriented at an attack angle that is less
than 90°.

The second group of patented rock-destructing
tools is comprised of round bits with symmetrical
cutting elements, which can rotate around its own
10 longitudinal axes.

In the first sub-group of these rotating
tools, the bits' rock-destructing elements have a
conical shape (direct cone) and destroy rock by
their convex-shaped back faces, as disclosed, for
15 example, in U.S. Patent 3,650,656; 3,807,804 and
4,804,231. Russian Patent 1,671,850-A1 discloses
the same so-called conical bit type, which has
limited contact area, dependent on attack angle,
that can be changed from 0 to 90°. Described bits
20 are of a crushing type that operate without
generation of long destructive cracks. The bits
are oriented at an attack angle which does not
exceed 90°. They have convex front and back faces;
zero or negative relief angle and positive rake
25 angle. Their self-rotation is not reliable.
Therefore they cannot self-sharpen. These bits
have significantly higher specific energy
requirements for rock destruction compared to the
present invention.

30 The second sub-group of the rotatable tools
includes bits, which destroy rock by their front
faces, as disclosed, for example, in U.S. Patent
5,078,219. This bit has a convex back face,
positive relief angle and an attack angle close to
35 zero. The bit is a cutting tool when its cutting

- 5 -

1 edge is a sharp one. However, the bit design does
not protect it against fast dulling. Bit self-
sharpening is impossible since there is no
correction of the bit's worn area. As discussed
4 previously, a sizeable width of this contact area
for normal force, T, greatly reduces cutting
ability.

The third sub-group of the rotatable tools is
represented by chisel bits, as disclosed, for
10 example, in German patents 3,336,154-A1 and
3,234,521-A1. These bits have a replaceable
cutting sleeve of a tubular chisel shape with a
sharpened front end. The bits have a rather small
included angle, a sizeable positive rake angle and
15 a small relief angle. Therefore, these bits have
low durability and wear resistance and they can
only be applied for destruction of soft, not
abrasive rock. Compared to the present invention,
the bits have an attack angle much less than 90°,
20 a front face which is concave, a back face which is
convex, and the bit cannot self-sharpen.

Disclosure of Invention

Accordingly, it is an object of the present
invention to provide a method of cutting and a
25 cutting rotative bit, which avoids the
disadvantages of the prior art.

More particularly, it is an object of the
present invention to provide a method of cutting
and a cutting rotative bit which ensures high
30 durability and maintenance of the bit's high
initial cutting ability for the entire service
life, independent of normal bit wear along
engagement surfaces.

In keeping with these objects and with others
35 which will become apparent hereinafter, one feature

- 6 -

1 of the present invention resides, briefly stated,
in a method of cutting in accordance with which a
cutting rotative bit is used with a body and a
generally circular cutting element or multiple
5 elements, connected with the body wherein the
cutting element has a convex front face, and in the
inventive method the cutting rotative bit is
oriented so that an attack angle of the bit's
cutting element exceeds 90'. (Attack angle is the
10 angle between the longitudinal axis of the bit and
the cut surface behind the bit).

When the method is performed and the tool is
designed in accordance with the present invention,
the following advantages are provided:

- 15 - Significant cutting ability of the bit,
which provides highly efficient
destruction of the rock and other
similar material;
- Continuous, forced self-rotation of the
20 bit around its own longitudinal axis,
which provides increased bit cutting
edge length and uniform wear along its
back face;
- Continuous, forced self-sharpening of
25 the bit, that maintains the initial
positive relief angle, of the bit along
its whole cutting edge by grinding away
interfering cutting element material
along its back face;
- 30 - Increased durability of the bit
resulting in high bit reliability and
longevity and increased range of working
material that may be engaged because of
highly rational force transmission
35 through the cutting element of the bit.

- 7 -

- 1 Stress in the brittle cutting element is
 almost entirely compressive;
 - Effective operation of the bit until a
 large proportion of the cutting element
5 is consumed by normal wear providing
 long bit service life.

 The novel features which are considered as
 characteristic for the invention are set forth in
 particular in the appended claims. The invention
10 itself, however, both as to its construction and
 its method of operation, together with additional
 objects and advantages thereof, will be best
 understood from the following description of
 specific embodiments when read in connection with
15 the accompanying drawings.

Brief Description of the Drawings

 FIG. 1 is a view schematically showing the
 mechanism of rock destruction;

 FIG. 2 is a view, showing a cutting device
20 provided with the cutting rotative bit in
 accordance with the present invention;

 FIG. 3a is a view, showing the inventive
 cutting rotative bit with cutting element, having
 the front face of a cylindrical shape and back face
25 of a flat shape;

 FIG. 3b is a view, showing the inventive
 cutting rotative bit with cutting element, having
 the front face of an inverse conical shape and back
 face of a flat shape;

30 FIG. 3c is a view, showing the inventive
 cutting rotative bit with cutting element, having
 the front face of a direct conical shape and a back
 face of a flat shape;

 FIG. 3d is a view, showing the inventive
35 cutting rotative bit with cutting element, having

- 8 -

1 the front face of a cylindrical shape and a back
face of a concave shape;

FIG. 3e is a view, showing the inventive
cutting rotative bit with cutting element, having
5 the front face of a cylindrical shape and a back
face of a convex shape;

FIG. 4a is a view, showing the inventive
cutting rotative bit with a simple cutting element
on a cylindrical bit body;

10 FIG. 4b is a view, showing the inventive
cutting rotative bit with multiple cutting elements
on a stepped cylindrical body;

FIG. 4c is a view, showing the inventive
cutting rotative bit with cutting element, having
15 the round smooth shape in cross-section;

FIG. 4d is a view, showing the inventive
cutting rotative bit with cutting element, having
the polygonal shape in cross-section;

FIG. 4e is a view, showing the inventive
20 cutting rotative bit with cutting element, having
a daisy shape in cross-section;

FIG. 5a is a plan view of the inventive
cutting rotative bit, showing skew angle;

FIG. 5b is a view, showing the main
25 longitudinal section of the cutting rotative bit
and all vertical plane angles in accordance with
the present invention;

FIG. 5c is a view, showing cross-section of
the inventive cutting rotative bit; and

30 FIG. 6 is a perspective view of the inventive
cutting rotative bit while cutting.

Best Mode of Carrying Out the Invention

A cutting tool (FIGS. 2, 3 and 4) in
accordance with the present invention has a body
35 which is identified with reference numeral 1 and a

- 9 -

1 cutting element or an insert which is identified
with reference numeral 2. The body is further
provided with a tail part 3 which contributes to
rotation of the bit about its longitudinal axis and
5 can be used to hold the cutting tool.

As can be seen from FIG. 2, the tail part of
the bit is arranged in a tool holder 4 and retained
by a retainer 5. The tool holder or a plurality of
tool holders are aligned with respect to each other
10 and attached to a cutter support 6. The main
angles, providing the spatial orientation of each
cutting rotative bit, are determined by mounting of
the tool holder to the cutter support as will be
discussed hereinbelow. The tail portion 3 of the
15 bit and therefore the cutting rotative bit are held
in the tool holder rotatably around its
longitudinal axis and fixed in the axial direction.

The cylindrical or conical body is made, as a
rule, from alloyed steel, which has a substantial
20 elasticity and strength.

The insert 2 (FIG. 3) is ring-shaped and can
be formed as a solid ring or a composite ring,
composed of individual segments. The inner opening
of the ring can be cylindrical or conical while its
25 surface, which is in contact with the body, may be
flat or curved. In other embodiments of this
invention, the entire bit can be exclusively made
of one material.

The upper surface of the insert can be flat,
30 as shown in FIGS. 3a, 3b, 3c. It can also be
concave, as shown in FIG. 3d or convex,, as shown
in FIG. 3e. The outer surface of the ring which is
the front face of the bit always has a convex shape
formed by a generatrix of a cylinder, as shown in
35 FIGS. 3a, 3d, and 3e, or direct cone, as shown in

- 10 -

1 FIG. 3c or inverse cone, as shown in FIG. 3b.

Outer contour of the cutting element can be straight one, as shown in FIG. 4a, or stepped one, as shown in FIG. 4b.

5 Shape of the cutting element in cross-section can be round, as shown, in FIG. 4c, or polygonal, as shown in FIG. 4d, or daisy-shaped, as shown in FIG. 4e.

The insert, as a rule, is made of hard wear
10 resistant materials, preferably sintered hard alloys of the tungsten carbide group. The convex shape of the front face of the insert is preferable, since the cutting forces are directed toward the center of the ring and are resolved into mainly
15 safe compressive stresses, instead of tensile stresses which are very dangerous for brittle materials like the hard alloys the insert is composed of.

The convex shape of the front face of the bit
20 also contributes to more efficient removal of the destroyed rock from the cutting zone due to dispersing of cuttings to both sides of the bit.

The connection of the insert to the body can be performed by brazing, in particular for the
25 composite ring, with use of high temperature brazing filler metal, or performed with interference for press fit. The ring-shaped insert provides semi-closed containment of brazing materials to ensure durable and reliable joining of
30 the body and insert which is particularly important in condition of dynamic loads. The press fitting on the other hand, eliminates residual thermal stresses which are characteristic of high temperature brazing due to different expansion
35 coefficients of the joined elements.

- 11 -

1 The solid bits which are not subdivided into
the body and insert are recommended for cutting of
non-abrasive materials. It must be subjected to a
special thermal treatment, for example, isothermic
5 quenching to provide different hardness of the body
portion and cutting element portion of the bit.

The main new feature of the present invention
is that the inventive method is performed so that
the cutting rotative bit is oriented to the surface
10 of the rock to be cut at an attack angle β which
exceeds 90° , as shown in FIGS. 2 and 5b.

Skew angle α shown in FIGS. 5a and 5c, is
measured in the plane of the cut rock surface and
is the angle between the projection of the bit
15 longitudinal axis and the direction of bit motion.

The skew angle determines a cutting force C ,
providing the rock cutting ($C = Q \cos \alpha$) and
rotating (crushing) force Q_{rot} , promoting rotation
of the bit around its own longitudinal axis
20 $Q_{rot} = Q \sin \alpha$).

The tool attack angle β , in combination with
tool skew angle α provides favorable conditions for
optimization of the main parameters of the tool
(including a rake angle φ and a relief angle δ of
25 the bit cutting edge).

The spatial orientation of the tool which is
determined by attack angle β and skew angle α
imparts the following properties:

- The front face of the bit is the convex
30 surface of the insert, while the back
face of the tool is the end surface of
the insert;
- The rotation of the tool around its
longitudinal axis (FIGS. 5b and 5c)
35 occurs due to rolling of the bit cutting

- 12 -

- 1 edge along the corresponding surface of
the rock under the action of the rotary
moment M_{rot} . M_{rot} is the couple of the
frictional force generated by force Q_{rot}
5 (and thrust force) and tangential force Q .
- The direction of the rectilinear motion
of the tool does not coincide with the
direction of cutting (breaking) of the
rock, which is different for each point
10 of the cutting edge of the tool, as
shown in FIG. 5c.
- Instantaneous values of rake angle φ_1 and
a relief angle δ_1 vary continuously from
point to point along bit cutting edge
15 (arc AE, FIG. 5c).

At the point B (FIG. 5c) the relief angle δ_b
has its maximum positive value. Moving away from
the point B to the right and to the left, this
angle reduces ($\sin \delta_1 = \sin \delta_b \cos \epsilon_1$) and assumes
20 its zero value at point D and a negative value at
point E. The geometrical correction of the relief
angle of the tool by introducing the positive angle
 $\Delta\delta$ (FIG. 5b; $\Delta\delta = \cos \beta \sin \alpha$) provides a positive
relief angle along the whole cutting edge of the
25 bit (the arc AE in FIG. 5c). Therefore, this
condition, necessary for high rock stress
concentration at the cutting edge, is maintained.

Under the condition $|\Delta\delta| = |\delta_0|$, the relief
angle of the tool at the point E is zero.
30 Therefore, on the radial line at E, self-sharpening
occurs because of continuous removal of back face
material that would interfere with maintaining the
positive relief angle along the entire cutting
edge. Self-sharpening proceeds around point E at
35 the same time as wear occurs along the remainder of

- 13 -

1 the cutting edge.

At the point B in FIG. 5c, the rake angle ϕ_b has its maximum negative value. Moving from point B to the right or to the left increases this angle so as to assume its zero value at the point D and its positive value at the point E. Therefore, at the point E the thrust force per unit length will be maximal, when compared with remaining points of the cutting edge of the tool over the arc AE in FIG. 5c. Therefore, the intensity of friction and wear is maximum at E and, in combination with the zero value of the relief angle, provides conditions which are close to machine tool sharpening. With the introduction of the positive angle of correction $\Delta\phi$, FIG. 5b, the effect of self-sharpening is further increased.

The negative rake angle of the tool, which is maximal in central part of the cutting edge, contributes to the self-protection against overloading. A negative rake angle generates a lifting force which lifts the tool from the rock. Such overloading is usually caused by the increase of the hardness of the rock to be broken.

The continuous rotation of the tool around its longitudinal axis is reliable due to the following factors:

- Absence of substantial resistance to the rotation along the back face of the tool due to the positive relief angle; and
- Use of substantial cutting force C (as compared with the thrust force), which is produced by the drive of the cutting equipment to form the significant Q_{rot} .

The nature and the axial direction of wear of the tool along the back face in combination with

- 14 -

1 the continuous renewal by self-sharpening to
initial values of the relief angle along the whole
cutting edge of the tool provides for efficient
operation of the tool in the cutting mode until the
5 wear substantially consumes the insert.

The attack angle in accordance with the
present invention can be within the range of 90° to
120°. The skew angle can be within the range of 5°
to 40°. The rake angle can be within the range of
10 plus 15° to minus 15°. The relief angle can be
within the range from 0 to 20°. The included angle
can be within the range of 50° to 100°.

While the invention has been illustrated and
described as embodied in a method of cutting and a
15 cutting rotative bit, it is not intended to be
limited to the details shown, since various
modifications and structural changes may be made
without departing in any way from the spirit of the
present invention.



- 15 -

THIS SHEET HAS BEEN
REPLACED

Claims

- 1 1. A cutting self-rotating and self-sharpening
 tool, comprising a rotatable cutting element;
 and means for holding said cutting element so
 that said cutting element has an attack angle
5 exceeding 90°, and a skew angle at least 5°.
2. A cutting self-rotating and self-sharpening
 tool as defined in claim 1, wherein said
 cutting element has a convex front face.
3. A cutting self-rotating and self-sharpening
10 tool as defined in claim 2, wherein said
 convex front face has a shape selected from
 the group consisting of a cylindrical shape,
 a direct conical shape and an inverse conical
 shape.
- 15 4. A cutting self-rotating and self-sharpening
 tool as defined in claim 1, wherein said
 cutting element has a back face with a shape
 selected from the group consisting of a
 convex shape, a concave shape, a flat shape
20 and a combination of said shapes.
5. A cutting self-rotating and self-sharpening
 tool as defined in claim 1, wherein said
 cutting element has a longitudinal section
 with an outer shape selected from the group
25 consisting of a straight shape and a stepped
 shape.

This Sheet Has Been Replaced





- 16 -

- 1 6. A cutting self-rotating and self-sharpening
tool as defined in claim 1, wherein said
cutting element has a transverse section with
an outer shape selected from the group
5 consisting of a round shape, a polygonal
shape and a daisy shape.
7. A cutting self-rotating and self-sharpening
tool as defined in claim 1, wherein said
cutting element has the attack angle between
10 90° and 120°.
8. A cutting self-rotating and self-sharpening
tool as defined in claim 1, wherein said
cutting element has the skew angle between 5°
and 40°.
- 15 9. A cutting self-rotating and self-sharpening
tool as defined in claim 1, wherein said
cutting element has a relief angle between
-15° and 15°.
10. A cutting self-rotating and self-sharpening
20 tool as defined in claim 1, wherein said
cutting element has has a relief angle
between 0 and 20°.
11. A cutting self-rotating and self-sharpening
tool as defined in claim 1, wherein said
25 cutting element has an included angle between
50° and 100°.

This Sheet Has Been Replaced.




- 17 -


- 1 12. A cutting self-rotating and self-sharpening
tool as defined in claim 11, wherein said
relief angle has a positive angular
correction, providing cutting element self-
5 sharpening, determined from formula $\Delta\delta \leq \arcsin(\sin \alpha \cos \beta)$, where α is a skew
angle, β is an attack angle.
- 10 13. A method of cutting, comprising the steps of
providing a rotatable cutting element;
mounting said cutting element by mounting
means; and displacing said mounting means so
that said cutting element has an attack angle
exceeding 90°, and a skew angle.
- 15 14. A method as defined in claim 13, wherein said
mounting includes mounting said cutting
element so as to provide the attack angle of
said cutting element between 90° and 120°.
- 20 15. A method as defined in claim 13, wherein said
mounting includes mounting said cutting
element so as to provide a skew angle of said
cutting element between 10° and 40° for both
sides of inclination.
- 25 16. A method as defined in claim 13, wherein said
mounting includes mounting said cutting
element so as to provide a rake angle of said
cutting element between -15° and 15°.
- 30 17. A method as defined in claim 1, wherein said
mounting includes mounting said cutting
element so as to provide a relief angle of
said cutting element between 0 and 20°.













1/6




2/6







5/6



6/6




FIG. 6



Claims

- 0 1. A cutting self-rotating and self-sharpening tool,
comprising a rotatable cutting element; and means
for holding said cutting element so that a longitudinal
axis of said cutting element is oriented regarding a
5 surface to be cut at an attack angle exceeding 90°
and is oriented regarding a cutting direction at a
skew angle at least 5° .
2. A cutting self-rotating and self-sharpening tool as
defined in claim 1, wherein said cutting element has
a convex front face.
- 10 3. A cutting self-rotating and self-sharpening tool as
defined in claim 2, wherein said convex front face
has a shape selected from the group consisting of a
cylindrical shape, a direct conical shape and an
inverse conical shape.
- 15 4. A cutting self-rotating and self-sharpening tool as
defined in claim 1, wherein said cutting element has
a back face with a shape selected from the group
consisting of a convex shape, a concave shape, a
flat shape and a combination of said shapes.
- 20 5. A cutting-self rotating and self-sharpening tool as
defined in claim 1, wherein said cutting element has
a longitudinal section with an outer shape selected
from the group consisting of a straight shape and a
stepped shape.



-16-


6. A cutting self-rotating and self-sharpening tool as defined in claim 1, wherein said cutting element has a transverse section with an outer shape selected from the group consisting of a round shape, a polygonal shape and a daisy shape.
7. A cutting self-rotating and self-sharpening tool as defined in claim 1, wherein said cutting element has the attack angle between 90° and 120° .
8. A cutting self-rotating and self-sharpening tool as defined in claim 1, wherein said cutting element has the skew angle between 5° and 40° .
9. A cutting self-rotating self-sharpening tool as defined in claim 1, wherein said cutting element has a relief angle between -15° and 15° .
10. A cutting self-rotating and self-sharpening tool as defined in claim 1, wherein said cutting element has a relief angle between 0 and 20° .
11. A cutting self-rotating and self-sharpening tool as defined in claim 1, wherein said cutting element has an included angle between 50° and 100° .



- 1 12. A cutting self-rotating and self-sharpening
tool as defined in claim 10, wherein said
relief angle has a positive angular
correction, providing cutting element self-
5 sharpening, determined from formula $\Delta\delta \leq \arcsin(\sin \alpha \cos \beta)$, where α is a skew
angle, β is an attack angle.
- 10 13. A method of cutting, comprising the steps of
providing a rotatable cutting element;
mounting said cutting element by mounting
means; and displacing said mounting means so
that said cutting element has an attack angle
exceeding 90° , and a skew angle.
- 15 14. A method as defined in claim 13, wherein said
mounting includes mounting said cutting
element so as to provide the attack angle of
said cutting element between 90° and 120° .
- 20 15. A method as defined in claim 13, wherein said
mounting includes mounting said cutting
element so as to provide a skew angle of said
cutting element between 10° and 40° for both
sides of inclination.
- 25 16. A method as defined in claim 13, wherein said
mounting includes mounting said cutting
element so as to provide a rake angle of said
cutting element between -15° and 15° .
- 30 17. A method as defined in claim 13, wherein said
mounting includes mounting said cutting
element so as to provide a relief angle of
said cutting element between 0 and 20° .



- 15 -



Claims

- 1 1. A cutting self-rotating and self-sharpening
 tool, comprising a rotatable cutting element;
 and means for holding said cutting element so
5 that said cutting element has an attack angle
 exceeding 90°, and a skew angle ~~at least 5°~~.
2. A cutting self-rotating and self-sharpening
 tool as defined in claim 1, wherein said
 cutting element has a convex front face.
- 10 3. A cutting self-rotating and self-sharpening
 tool as defined in claim 2, wherein said
 convex front face has a shape selected from
 the group consisting of a cylindrical shape,
 a direct conical shape and an inverse conical
 shape.
- 15 4. A cutting self-rotating and self-sharpening
 tool as defined in claim 1, wherein said
 cutting element has a back face with a shape
 selected from the group consisting of a
20 convex shape, a concave shape, a flat shape
 and a combination of said shapes.
5. A cutting self-rotating and self-sharpening
 tool as defined in claim 1, wherein said
 cutting element has a longitudinal section
25 with an outer shape selected from the group
 consisting of a straight shape and a stepped
 shape.

AMENDED SHEET