CLAIMS

1. A nasogastric tube positioning system comprising a nasogastric tubing having first and second ends, a power supply part located at or adjacent the first end, and a transducer part located at or adjacent the second end for transmitting or receiving an ultrasound-based signal, and a control module comprising an at least one detector portion and a processor, wherein ultrasound-based signals are transmittable between the transducer part and the at least one detector portion, the processor being adapted to record the time taken for the ultrasound-based signal to travel between the transducer part and the at least one detector portion, and to calculate a distance between the transducer part and the at least one detector portion to thereby locate the transducer part.

2. A nasogastric tube positioning system according to claim 1, wherein the transducer part is sealed within a distal tip located at the second end.

3. A nasogastric tube positioning system according to claim 2, wherein the distal tip is at least substantially dome shaped.

4. A nasogastric tube positioning system according to any one of the preceding claims, wherein the power supply part is a power connector for connecting a power supply to the transducer part.

5. A nasogastric tube positioning system according to any one of claims 1 to 3, wherein the power supply part is a power supply for supplying power to the transducer part.

6. A nasogastric tube positioning system according to any one of the preceding claims, wherein the tubing comprises a first lumen extending along a length of the tubing, and one or more apertures extending through the tubing into the first lumen at or adjacent the second end thereof, the first lumen allowing fluids including food and medicine to be transferred therethrough and from the one or more apertures.

7. A nasogastric tube positioning system according to claim 6, wherein the tubing comprises a second lumen extending along the length of the tubing and separate

from the first lumen, the second lumen supporting a wiring system therein electrically connecting the power supply part to the transducer part.

8. A nasogastric tube positioning system according to claim 7, wherein the wiring system is a twisted wire pair.

9. A nasogastric tube positioning system according to any one of the preceding claims, wherein a radiopaque line extends along the length of the tubing.

10. A nasogastric tube positioning system according to any one of the preceding claims, wherein the control module comprises two said detector portions located a fixed distance apart.

11. A nasogastric tube positioning system according to any one of the preceding claims, wherein the control module is a handheld scanner having a housing for accommodating the detector portions.

12. A nasogastric tube positioning system according to any one of the preceding claims, further comprising a power supply within the housing for providing electrical power to the transducer part and the detector portions.

13. A nasogastric tube positioning system according to any one of the preceding claims, further comprising a display screen for showing when the detector portions are shaped equidistant from the transducer part.

14. A nasogastric tube positioning system according to any one of the preceding claims, further comprising a device for displaying a light or audio signal when the detector portions are shaped equidistant from the transducer part.