

DATA CODE AND APPARATUS FOR READING SAID DATA CODE

The present invention relates to a data code and apparatus for reading said data code.

Hitherto, conventional bar codes have been used for printing a code onto various products and for use in all aspects of manufacturing and at point of sale retail stores. The bar code system comprises a plurality of parallel, aligned bars, each bar having a given width to represent a particular number, or character.

The bar code is read by illuminating the code with a beam of light and the reflected light is read by an optical sensor. The sensor may be, for example, of a fixed beam type in which the object having the code printed thereon is moved in front of it. Alternatively, the sensor may be of the moving type whereby the object having the code printed thereon is fixed and the sensor is moved across the code.

The reflected light forms analogue signals which is converted by the sensor to digital signals and then these signals are image processed by a microprocessor to extract the relevant information. This results in the optical sensor being relatively complex and expensive. Since the bar widths are used to represent numbers or

characters, the bar code must be printed with great accuracy to ensure that the code accurately represents the information required. Furthermore, a user merely looking at the code is unable to decipher the information written thereon since the naked eye is unable to accurately determine the widths of the bars.

A code has been proposed, which is described in pending PCT application no. JP87/0007. The code comprises at least one unit being divided into at least two regions having substantially similar dimensions, whereby each characteristic of the code has a particular arrangement of shaded and/or blank regions. One known disadvantage with this code is that only decimal notation such as numerals 0-9 may be represented. Another known disadvantage with this code is that the orientation of each unit can not be determined and hence inaccurate data may be extracted.

In addition, one well known code is binary notation, which is especially used in computing or microprocessing fields. However, most users are not used to working in binary, but are highly proficient in using decimal notation. Conversion from decimal to binary and vice versa is not easily computed manually and is usually done by a machine. Hitherto, there are no known codes which easily allow a user to convert between decimal and

binary notation.

An object of the present invention is to provide a data code and apparatus for reading such a data code which alleviates the aforementioned disadvantages.

According to the present invention there is provided a method of encoding successive elements of data, such as numbers, in material form using, for each element, the same data code comprising at least one unit, the or each unit being divided into regions having similar dimensions, the areas of the regions combining to constitute the area of the unit or units, and one such unit having at least four such regions, each region of the entire code corresponding to a different column of the data element expressed in binary notation commencing with the lowest order column and thereafter the successive columns, the same region of the code always being used to represent the same binary column in one-to-one correspondence, and the number of regions being at least five, the method comprising shading each unit with a particular arrangement of shaded regions so that the code represents directly that particular binary number.

According to the present invention there is also provided a data code comprising at least one unit, the or each unit being divided into regions having similar dimensions, the areas of the regions combining to constitute the area of the unit or units, and one such unit having at least four such regions, each region corresponding to a different column of binary notation commencing with the lowest order column and thereafter the successive columns, the same region of the code always being representative of the same binary column in one-to-one correspondence, and each unit having a

particular arrangement of shaded regions so that the code represents directly a particular binary number; the code further comprising means for distinguishing the orientation of said data code comprising a shaded bar dissecting the or each square unit into two parts having two regions each.

According to the present invention there is also provided an apparatus for reading a data code, comprising at least one unit, the or each unit being divided into regions having similar dimensions, the areas of the regions combining to constitute the area of the unit or units, and one such unit having at least four such regions, each region corresponding to a different column of binary notation commencing with the lowest order column and thereafter the successive columns, the same region of the code always being representative of the same binary column, in one-to-one correspondence, and each unit having a particular arrangement of shaded regions so that the code represents directly a particular binary number, the apparatus comprising, means for illuminating the data code, an image sensor comprising an optical system coupled to an array of photoreceptors for receiving the illumination from the data code and for producing a signal dependent upon the illumination received, means for storing said signal and display means for sequentially displaying said signal.

The invention also provides a method, as claimed in Claim 12, of encoding successive elements of data.

Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a schematic representation of an embodiment the data code, in which each unit of the data code corresponds to the respective decimal, hexadecimal or binary notation;

Figure 2 illustrates each region of the data code representing binary or decimal notation as shown in Figure 1;

Figure 3 illustrates examples of the data code according to Figure 1;

Figure 4 illustrates a positional arrangement of the data code shown in Figure 1;

Figure 5 schematically represents variations of a unit;

Figure 6 schematically illustrates the data code representing each letter of the Roman Alphabet;

Figure 7 illustrates units of a data code according to an embodiment of the present invention;

Figure 8 illustrates each unit being coupled to means for distinguishing the orientation of the units of the embodiment shown in figure 6;

Figure 9 illustrates examples of the preferred embodiment shown in Figure 6 having known symbols printed thereon;

Figure 10 illustrates a data code and apparatus for reading thereof according to a second preferred embodiment of the present invention;

Figure 11 is a schematic block diagram of the apparatus shown in figure 10;

Figure 12 is a schematic diagram of the apparatus according to a third preferred embodiment;

Figure 13 is a schematic block diagram of the circuit of the apparatus shown in figure 12.

An embodiment of the data code is shown in figure 1 and comprises a number of units 2 each being divided into four equal regions 4, so that the areas of the regions 4 combine to constitute the area of the units 2. Each of the regions 4 of any unit 2 may be shaded by being manually written, to create a unique arrangement of shaded and blank regions to define a particular unit and hence a particular characteristic of the data code. Each of the decimal numbers 0 to 9 are represented by a particular combination of blank and shaded regions.

Each of the units shown in figure 1 comprises four regions, however more regions may be used for each unit. Furthermore, each region may form a rectangular, circular or triangular shape, but each of the regions must have substantially similar dimensions for a particular data code.

Each of the units 2 of the data code is used to represent decimal, hexadecimal or binary notation as shown in figure 1. Here each region represents a column of binary notation starting with the lowest order column, 1, and successive columns 2, 4, 8. Hence numerals in decimal or other binary notation can be represented. If, respective regions for each unit always represent the same column then the value of a unit can be determined at a glance.

Figure 2, further illustrates the data code being used to represent decimal, hexadecimal or binary notation. The decimal numbers 1, 2, 4 and 8 may be printed onto the data code sheet before any one of the regions are shaded. These numbers are directly related to binary or hexadecimal notations once each region 4 is used to represent a column of notation, for example the 1, 10, 100, 1000 in binary notation. For example, 4a represents column 2^0 , equivalent to the decimal or hexadecimal number 0 or the binary number 1; b

represents column 2^1 , equivalent to the decimal or hexadecimal number 2 or the binary number 10; region 4c represents column $2^2 = 4 = 100$; and similarly region d represents $2^3 = 8 = 1000$. A number of units may be used to represent larger numbers. Accordingly each unit 2 may be used to represent decimal, hexadecimal, or binary notation.

As shown in figure 3 the unit 2 may also have decimal notation printed on each of the regions 4. Thus in figure 3a regions 4b, 4c, and 4d are shaded thus indicating that the unit represents the decimal number 14 (since $2 + 4 + 8 = 14$) and the binary number 1110. Similarly the unit illustrated in figure 3b represents the decimal number 13 and the binary number 1101 and the unit in figure 3c represents the decimal number 250 and the binary number 11111010. Thus the data code easily enables a user to identify a binary or a decimal notation merely viewing the data code.

Computers are generally based on hexadecimal notation and the data code is applicable to such notation and therefore directly compatible with computers.

Figure 4 illustrates possible positional arrangements of the data code in decimal notation or hexadecimal notation when printed on a sheet 1.

Figure 5 illustrates a number of different types of units which may be used in the data code but the present invention is not limited just to these types of units. Any one of these units may be used to form a data code applicable to the notation which the code is representing. For example, a notation requiring 6 regions for each unit may be denoted by units 5a and 5b. Accordingly, the following types of notation can be represented by a minimum number of regions or bits:

NOTATION TYPES	MINIMUM NUMBER OF REGIONS OR BITS
Decimal notation type	4 bits
Roman alphabet (Capitals), decimal and punctuation marks	6 bits
Japanese kana characters and punctuation marks	7 bits
Roman characters, including capitals and lower case, kana characters, decimals and punctuation marks	8 bits
Frequently used ideographs, kana characters, Roman characters and punctuation marks	12 or 16 bits
Morse signals	6 bits

Braille

6 bits

For example, figure 6 illustrates the Roman Alphabet of capitals in terms of binary notation and the data code. For example, the letter N may be represented by the binary notation 00100011 or by the 2 units. The data code therefore facilitates reading, understanding and remembering codes of the Roman alphabet in capitals.

Figure 7 illustrates a data code according to an embodiment. The regions 4 of each of the units 2 include means for distinguishing the orientation of the unit, such as a bar 6. The bar 6 facilitates reading of the code and enables the code to be correctly positioned. If the sensor reads the first column whilst viewing position a, then the sensor will recognise that the centre of the unit is not aligned with the origin of its two dimensional axis and thus will adjust the reading of the columns until it is aligned. As shown in figure 8, the bar 6 should be aligned along the X axis having the centre of each unit aligned with the origin of the two dimensional axis in the sensor. However, this embodiment enables the data code to be read easily even if the data code is placed at an angle r to a reader. For example, in figure 8c alignment of the data code using the bar 6 enables the sensor to compensate for the code being at an angle r .

Each unit of the data code may also have known characters or punctuation marks written in some or all of the regions as shown in figure 9. This further enables the data code to be easily read and interpreted.

The data code facilitates reading and understanding of decimal, hexadecimal and binary notation in both education and industry. The data code may be written by hand and may be used to operate electronic devices thereby making such devices more accessible. Furthermore, the data code may be used as an interface language between characters of different languages.

Figures 10 to 13 illustrate a data code printed on a sheet 1 and apparatus for reading said data code. Referring to figure 10 and 11, the apparatus 8 illuminates each unit of the data code using a light source 9, such as an LED lamp or a laser beam. The reflected light is received by respective photoreceptors 10, such as a Mos-type sensor or CDD. The photoreceptors 10 are coupled to a decoder 12 having input terminals 1, 2, 4, 8 corresponding to each photoreceptor 10 for the appropriate region 4. The input signals are extracted in binary column order and sent to a CPU 14 for displaying or converting the

digital signals into the appropriate numbers, characters or symbols for a suitable display 16.

The photoreceptors 10 are responsive to the variations in the regions since less light is reflected back from a shaded region. The photoreceptors will record the binary number 1 in response to the light received from a shaded region and the binary number 0 in response to the light being received from a blank region. In conjunction with each region representing a column of binary notion, the apparatus 8 can read directly from the data code, the binary numbers, thereby obviating any analogue to digital conversion. Each unit 2 is illuminated by the light source 9 controlled by a switch 18 which illuminates each unit 2 in turn. This enables the photoreceptors 10 to submit signals in succession.

Alternatively, as shown in figure 12 and 13, the signals from the illuminated data code, may be received by an image sensor 20 via an optical system 22, the sensor 20 comprises photoreceptors 10 in a two dimensional array. The sensor produces a signal which is outputted in a time series and stored in a memory 32. The stored data is displayed sequentially to reveal the data code. Circuit 24 shown in figure 13 enables the signals to be co-ordinated and comprises a clock 26, a vertical synchronising circuit 28 and a horizontal

synchronising circuit 30. Each signal received at the terminals 1, 2, 4 and 8 of the decoder 12 is sent to the CPU 34 via the buffer memory and control unit 32.

These reading methods enable the system to avoid analogue to digital conversion as required by the prior art systems.

The foregoing description has been given by way of example only, and it will be appreciated by persons skilled in the art that modifications may be made without departing from the scope of the present invention.



CLAIMS

1. A method of encoding successive elements of data, such as numbers, in material form using, for each element, the same data code comprising at least one unit, the or each unit being divided into regions having similar dimensions, the areas of the regions combining to constitute the area of the unit or units, and one such unit having at least four such regions, each region of the entire data code corresponding to a different column of the data element expressed in binary notation commencing with the lowest order column and thereafter the successive columns, the same region of the code always being used to represent the same binary column in one-to-one correspondence, and the number of regions being at least five, the method comprising shading each unit with a particular arrangement of shaded regions so that the code represents directly that particular binary number.

2. A data code comprising at least one unit, the or each unit being divided into regions having similar dimensions, the areas of the regions combining to constitute the area of the unit or units, and one such unit having at least four such regions, each region corresponding to a different column of binary notation commencing with the lowest order column and thereafter the successive columns, the same region of the code always being representative of the same binary column in one-to-one correspondence, and each unit having a particular arrangement of shaded regions so that the code represents directly a particular binary number; the code further comprising means for distinguishing the orientation of said data code comprising a shaded bar dissecting the or each unit into two parts having two regions each.



3. A method of encoding or a data code as claimed in claim 1 or claim 2, in which the or each unit with at least four regions comprises a square having four regions, each of which regions comprising a square.
4. A method of encoding or a data code as claimed in claim 1 or claim 2, in which each region comprises any one of a rectangle, circle or triangle.
5. A method of encoding or a data code as claimed in any one of the preceding claims in which the numeric value of each region is printed thereon.
6. An apparatus for reading a data code, comprising at least one unit, the or each unit being divided into regions having similar dimensions, the areas of the regions combining to constitute the area of the unit or units, and one such unit having at least four such regions, each region corresponding to a different column of binary notation commencing with the lowest order column and thereafter the successive columns, the same region of the code always being representative of the same binary column, in one-to-one correspondence, and each unit having a particular arrangement of shaded regions so that the code represents directly a particular binary number, the apparatus comprising, means for illuminating the data code, an image sensor comprising an optical system coupled to an array of photoreceptors for receiving the illumination from the data code and for producing a signal dependent upon the illumination received, means for storing said signal and display means for sequentially displaying said signal.
7. An apparatus as claimed in Claim 6, further comprising a switch coupled to the illuminating means for enabling the regions to be read sequentially.

16-1



8. An apparatus as claimed in Claim 6 or 7, in which the array of photoreceptors is a two-dimensional array.

9. An apparatus as claimed in Claim 6, further comprising means for co-ordinating the signals produced by said image sensor.

10. A data code substantially as hereinbefore described with reference to any one of Figures 1 to 9.

11. An apparatus substantially as hereinbefore described with reference to any one of Figures 10 to 13.

12. A method of encoding successive elements of data, such as numbers, in material form using, for each element, the same data code comprising at least one unit, the or each unit being divided into regions having similar dimensions, the areas of the regions combining to constitute the area of the unit or units, and one such unit having at least four such regions, each region corresponding to a different column of the data element expressed in binary notation commencing with the lowest order column and thereafter the successive columns, the same region of the code always being used to represent the same binary column in one-to-one correspondence, the method comprising shading each unit with a particular arrangement of shaded regions so that the code represents directly that particular binary number, in which each region comprises any one of a non-square rectangle, circle or triangle.
