

METHOD AND APPARATUS FOR ASSEMBLING SHOE COMPONENTS

FIELD

The disclosure relates to a method and an apparatus for assembling shoe components.

5

BACKGROUND

A shoe is mainly composed of shoe components, such as an upper and a sole, and may further include other shoe components, such as a reinforcing member, an eyestay, a tongue, a decorative piece, etc. These shoe components are usually bonded by hot pressing adhesive. However, if the hot pressing adhering process is done manually, not only is the quality difficult to stabilize, but also the process is time consuming, so that the cost of assembly is increased.

Referring to FIG. 1, a system 1 for applying heat and pressure to a three-dimensional article, as disclosed in Chinese Patent Publication No. 107518525, mainly includes an intermediate member 11 and a base member 12 oppositely connected to each other and cooperatively defining an airtight space 13 for receiving a footwear unit 2. The intermediate member 11 has a flexible film 111 for covering the footwear unit 2. External pressure (for example, vacuum pressure) may be applied to the flexible film 111 so that the footwear unit 2 may be pressed by the flexible film 111 and be integrally connected.

Although the aforesaid system 1 can improve the deficiencies found in manually making the shoe, it still has the following drawbacks:

1. Since air in the airtight space 13 is discharged
5 through a hole (not shown) in the base member 12, the position of the footwear unit 2 on the base member 12 should not block the hole, so that the placement of the footwear unit 2 on the base member 12 is restricted.

2. In the processing method of the system 1, there
10 is need to wait for the footwear unit 2 to finish adhering and then remove from the base member 12 before the next process may be performed, so that the process efficiency thereof is limited.

3. To construct the airtight space 13, the base
15 member 12 and the intermediate member 11 must be provided, so that the structure of the system 1 is not only complicated, but the cost thereof is also increased.

SUMMARY

20 Therefore, an object of the present disclosure is to provide a method and an apparatus for assembling shoe components that can alleviate at least one of the drawbacks of the prior art.

According to one aspect of this disclosure, a method
25 for assembling shoe components includes the steps of: providing at least two shoe components, a shoe last and

a film unit, at least one of the at least two shoe components having an adhesive layer; placing the at least two shoe components on an outer surface of the shoe last; removably covering an assembly of the at least two shoe components and the shoe last with the film unit such that the film unit and the shoe last cooperatively define a confining space therebetween; and pumping air out of the confining space and heating the at least two shoe components to shrink and deform the film unit so as to press the at least two shoe components to adhere tightly to each other.

According to another aspect of this disclosure, an apparatus for assembling at least two shoe components includes a shoe last, a film unit, a vacuum unit and a heating unit. The shoe last has a shoe last body for placing of the at least two shoe components on an outer surface thereof. The film unit is provided for removably covering an assembly of the shoe last and the at least two shoe components, and cooperates with the shoe last to define a confining space therebetween. The vacuum unit is provided for pumping air out of the confining space to shrink and deform the film unit for pressing the at least two shoe components tightly to each other. The heating unit is provided for transmitting heat to the at least two shoe components so as to adhere the at least two shoe components tightly to each other.

BRIEF DESCRIPTION OF THE DRAWINGS

The features and advantages of the disclosure will become apparent in the following detailed description of the embodiments with reference to the accompanying
5 drawings, of which:

FIG. 1 is a sectional view of a system for applying heat and pressure to a three-dimensional article disclosed in Chinese Patent Publication No. 107518525;

FIG. 2 is an exploded perspective view of an
10 apparatus for assembling shoe components according to the first embodiment of this disclosure and the shoe components;

FIG. 3 illustrates a film unit of the first embodiment covering an assembly of a shoe last and the
15 shoe components;

FIG. 4 is a sectional view of the first embodiment;

FIG. 5 is a flow diagram, illustrating the steps involved in a method of the first embodiment for assembling shoe components;

FIG. 6 illustrates the shoe last and the film unit
20 being removed after the shoe components are assembled;

FIG. 7 is an exploded perspective view of a film unit of an apparatus for assembling shoe components according to the second embodiment of this disclosure
25 and an assembly of a shoe last and shoe components;

FIG. 8 is an assembled sectional view of the second embodiment;

FIG. 9 is a fragmentary sectional view of an apparatus for assembling shoe components according to the third embodiment of this disclosure; and

FIG. 10 is a view similar to FIG. 9, but with air being pumped out of a confining space.

DETAILED DESCRIPTION

Before the present disclosure is described in greater detail with reference to the accompanying embodiments, it should be noted herein that like elements are denoted by the same reference numerals throughout the disclosure.

Referring to FIGS. 2 to 4, an apparatus according to the first embodiment of the present disclosure is configured to assemble a plurality of shoe components 3 so as to form a shoe 100 (see FIG. 6). In this embodiment, the shoe components 3 are exemplified to include an upper 31, a tongue 32, a sole 33, an eyestay 34, a pair of reinforcing members 35, and a decorative member 36. The apparatus of this embodiment includes an airtight unit 400, a vacuum unit 6 and a heating unit 7.

The airtight unit 400 includes a shoe last 4 and a film unit 5. The shoe last 4 has a shoe last body 41 defining a cavity 410. The shoe last body 41 has an air port 412 formed in a top end surface 411 thereof and communicating with the cavity 410, a plurality of vent

holes 413 communicating with the air port 412 through the cavity 410, and two positioning portions 414 formed on the top end surface 411 and located on two opposite sides of the air port 412. In this embodiment, each
5 positioning portion 414 is a recessed hole. The shoe components 3 are placed on an outer surface of the shoe last body 41 at predetermined positions.

The film unit 5 of this embodiment includes a flexible air barrier film 51 for removably covering an
10 assembly of the shoe last body 41 and the shoe components 3. The air barrier film 51 cooperates with the shoe last body 41 to define a confining space 510 therebetween, and includes four covering portions 511 formed on front, rear, left and right sides thereof and overlapping each
15 other on the top end surface 411 of the shoe last body 41, and six fixed portions 512 formed on the covering portions 511. The confining space 510 communicates with the vent holes 413, and also communicates with the cavity 410 and the air port 412 through the vent holes
20 413. Each of the left and right covering portions 511 is formed with two fixed portions 512 corresponding to the positioning portions 414, and a notch 513 between the fixed portions 512 and corresponding to the air port 412. Each of the front and rear covering portions 511
25 is formed with one fixed portion 512 corresponding to one of the positioning portions 414. In this embodiment, each fixed portion 512 is a through hole.

Two fixing elements 42 are used to fix the covering portions 511 of the air barrier film 51 to the top end surface 411 of the shoe last body 41. In this embodiment, each fixing element 42 is a bolt. The bolts or fixing elements 42 are extended through the through holes or
5 fixed portions 512 of the overlapped covering portions 511 and are press-fitted into the respective positioning portions 414 of the shoe last body 41.

It should be noted herein that the number of the
10 fixed portions 512 is not limited to six, and may be four in other embodiment, but is not limited thereto.

The vacuum unit 6 of this embodiment is a vacuum pump having an air nozzle 61 removably connected to the air port 412 of the shoe last body 41. The air nozzle 61
15 communicates with the confining space 510 through the air port 412 and the vent holes 413 for pumping air out of the confining space 510.

The heating unit 7 is provided to transmit heat to the shoe components 3 so as to adhere the shoe components
20 3 tightly to each other. In this embodiment, the heating unit 7 includes four heaters 71 (only three are shown in FIG. 4) disposed around an outer side of the film unit 5. It should be noted herein that the heating unit 7 is not limited to being disposed on the outer side
25 of the film unit 5. In other embodiment, the heating unit 7 may be a heating tube provided on the shoe last body 41, and is not limited thereto.

Referring to FIG. 5, in combination with FIGS. 2 to 4, a method for assembling the shoe components 3 using the apparatus of the first embodiment includes steps 81 to 85.

5 In step 81, the shoe components 3, the shoe last 4 and the film unit 5 are provided. The shoe components 3 are exemplified to include the upper 31, the tongue 32, the sole 33, the eyestay 34, the pair of reinforcing members 35 and the decorative member 36.

10 In step 82, the shoe components 3 are placed on the outer surface of the shoe last body 41 at the predetermined positions. Each shoe component 3 has an adhesive layer. The upper 31 is first placed on the outer surface of the shoe last body 41, followed by the tongue
15 32, the sole 33, the eyestay 34, the reinforcing members 35 and the decorative member 36.

 In step 83, the assembly of the shoe last body 41 and the shoe components 3 are placed on top of the air barrier film 51, and the four covering portions 511 of
20 the air barrier film 51 are folded toward the top end surface 411 of the shoe last body 41 to overlap each other with the left and right covering portions 511 at the bottom, the rear covering portion 511 at the top, and the front covering portion 511 below the rear
25 covering portion 511 but on top of the left and right covering portions 511. At this time, the fixed portions 512 of the covering portions 511 face the corresponding

positioning portions 414. Two fixing elements 42 are then inserted through the fixed portions 512 of the covering portions 511, and are press-fitted into the respective positioning portions 414, thereby fixing
5 the air barrier film 51 to the shoe last body 41. The air barrier film 51 cooperates with the shoe last body 41 to define the confining space 510 at this time.

In step 84, the air nozzle 61 of the vacuum unit 6 is connected to the air port 412 of the shoe last body
10 41, and the heaters 71 are activated to transmit heat to the shoe components 3. Through this, the air in the confining space 510 is sucked by the air nozzle 61 and is discharged through the air port 412 after passing through the vent holes 413 and the cavity 410 of the
15 shoe last body 41, and the air barrier film 51 is shrunk and deformed under the action of negative pressure, so that the shoe components 3 are pressed to adhere tightly to each other.

In step 85, after the shoe components 3 are assembled
20 and cooled, the fixing elements 42 are removed from the respective positioning portions 414, and the shoe last body 41 and the air barrier film 51 are detached from the assembled shoe components 3, as shown in FIG. 6. The shoe 100 is obtained in this embodiment.

25 It is worth to mention herein that a step of injecting air (not shown) may be performed after step 84 and before step 85. High pressure air may be injected

into the cavity 410 through the connection of the air nozzle 61 of the vacuum unit 6 with the air port 412, and may pass through the vent holes 413 toward the shoe components 3. Through this, the air barrier film 51 may
5 be quickly cooled and detached from the shoe components 3, and the shoe last 4 may be easily removed from the shoe 100.

Referring to FIGS. 7 and 8, the second embodiment of the apparatus and the method of this disclosure are
10 generally identical to the first embodiment. However, in this embodiment, the film unit 5 includes two flexible air barrier films 52, 53 having peripheral ends 521, 531. The air barrier film 52 further has a through hole 522 corresponding to the air port 412 of
15 the shoe last body 41.

In step 83, the air barrier films 52, 53 are disposed opposite to each other to removably cover the assembly of the shoe last body 41 and the shoe components 3 therebetween with the peripheral ends 521, 531 thereof
20 overlapping each other. The air barrier films 52, 53 cooperate with the shoe last body 41 to define the confining space 510 at this time.

In step 84, the air nozzle 61 of the vacuum unit 6 is inserted through the through hole 522 in the air
25 barrier film 52 and is removably connected to the air port 412 of the shoe last body 41, and the heaters 71 (see FIG. 4) are activated to transmit heat to the shoe

components 3. Through this, the air in the confining space 510 is sucked by the air nozzle 61 and is discharged through the air port 412 after passing through the vent holes 413 and the cavity 410 of the shoe last body 41, and the air barrier films 52, 53 are
5 shrunk and deformed under the action of negative pressure, so that the shoe components 3 are pressed to adhere tightly to each other so as to form the shoe 100 (see FIG. 6).

10 In step 85, after the shoe components 3 are assembled and cooled, the overlapped peripheral ends 521, 531 of the air barrier films 52, 53 are separated from each other to detach the air barrier films 52, 53 from the assembled shoe components 3, and the shoe last body 41
15 is also detached from the assembled shoe components 3.

Referring to FIGS. 9 and 10, the third embodiment of the apparatus and the method of this disclosure are generally identical to the second embodiment. However, in this embodiment, the apparatus is exemplified to
20 assemble the upper 31 and the pair of reinforcing members 35 (only one reinforcing member 35 is shown). Further, the shoe last body 43 of the shoe last 4 has a solid structure. The shoe last 4 further has a spacer portion 44 formed around the outer surface of the shoe
25 last body 43 in proximity to a top end thereof and cooperating with the shoe last body 43 and the film unit 5 to define the confining space 510. The spacer portion

44 has an air port 441 communicating with the confining space 510. The air nozzle 61 of the vacuum unit 6 (see FIG. 2) is removably connected to the air port 441 for pumping air out of the confining space 510.

5 In step 82, the upper 31 is first placed on the outer surface of the shoe last body 43, after which the pair of reinforcing members 35 are placed on two opposite sides of the upper 31.

10 In step 83, the air barrier film 52 is sleeved around the assembly of the shoe last body 41, the upper 31 and the reinforcing members 35, and the air barrier film 53 is disposed opposite to the air barrier film 52 and cooperate with the same to removably cover the assembly of the shoe last body 43, the upper 31 and the
15 reinforcing members 35 therebetween with the peripheral ends 521, 531 thereof overlapping each other. The air barrier films 52, 53 cooperate with the shoe last body 43 and the spacer portion 44 to define the confining space 510 at this time.

20 In step 84, the air nozzle 61 of the vacuum unit 6 (see FIG. 8) is removably connected to the air port 441, and the heaters 71 (see FIG. 4) are activated to transmit heat to the upper 31 and the reinforcing members 35. Through this, the air in the confining space 510 is
25 sucked by the air nozzle 61 and is discharged through the air port 441, and the air barrier films 52, 53 are shrunk and deformed under the action of negative

pressure, as shown in FIG. 10, so that the upper 31 and the reinforcing members 35 are pressed to adhere tightly to each other.

5 The advantages of this disclosure can be summarized as follows:

1. The confining space 510 is defined by the shoe last body 41 and the film unit 5 in the first and second embodiments, and is defined by the shoe last body 43, the film unit 5 and the spacer portion 44 in the third
10 embodiment. Further, the air port 412, 441 may be formed in the shoe last body 41 or the spacer portion 44. Thus, the placement position of the shoe last 4 on the film unit 5 is not restricted, and has more freedom in the use of space and process.

15 2. This disclosure may use one vacuum unit 6 and one heating unit 7 to press and heat a plurality of airtight units 400. That is, after one of the airtight units 400 is pressed and heated, the vacuum unit 6 may be removed, followed by the film unit 5, so that the pressing and
20 heating of another one of the airtight units 400 may proceed, thereby greatly increasing the production efficiency of the disclosure.

3. Since the shoe last 4 is an essential component for shoemaking, the components of this disclosure can
25 be simplified, thereby effectively reducing the equipment cost.

While the disclosure has been described in

connection with what are considered the exemplary
embodiments, it is understood that this disclosure is
not limited to the disclosed embodiments but is
intended to cover various arrangements included within
5 the spirit and scope of the broadest interpretation so
as to encompass all such modifications and equivalent
arrangements.

CLAIMS:

1. A method for assembling shoe components, comprising:
 - providing at least two shoe components, a shoe last and a film unit, at least one of the at least
 - 5 two shoe components having an adhesive layer, the shoe last having a shoe last body, the film unit including at least one flexible air barrier film;
 - placing the at least two shoe components on an outer surface of the shoe last body;
 - 10 removably covering an assembly of the at least two shoe components and the shoe last with the at least one flexible air barrier film such that the at least one flexible air barrier film and the shoe last cooperatively define a confining space
 - 15 therebetween; and
 - pumping air out of the confining space using a vacuum unit and heating the at least two shoe components to shrink and deform the at least one flexible air barrier film so as to press the at least
 - 20 two shoe components to adhere tightly to each other;
 - wherein the shoe last body has an air port formed in an end surface thereof, a plurality of vent holes communicating with the air port and the confining space, and two positioning portions formed on the
 - 25 end surface and located on two opposite sides of the air port;
 - wherein the vacuum unit is removably connected

to the air port for pumping the air out of the confining space; and

5 wherein the at least one flexible air barrier film has at least one fixed portion removably fixed to the end surface of the shoe last body and corresponding in position to the positioning portions.

10 2. The method as claimed in Claim 1, wherein the film unit includes two opposite flexible air barrier films removably covering the assembly of the at least two shoe components and the shoe last therebetween, the flexible air barrier films having peripheral ends overlapping each other.

15 3. An apparatus for assembling at least two shoe components comprising:

20 a shoe last having a shoe last body for placing of the at least two shoe components on an outer surface thereof;

a film unit including at least one flexible air barrier film for removably covering an assembly of said shoe last and the at least two shoe components, said at least one flexible air barrier film cooperating with said shoe last to define a confining space therebetween;

a vacuum unit for pumping air out of said

confining space to shrink and deform said at least one flexible air barrier film for pressing the at least two shoe components tightly to each other; and

5 a heating unit for transmitting heat to the at least two shoe components so as to adhere the at least two shoe components tightly to each other;

wherein said shoe last body has an air port formed in an end surface thereof, a plurality of vent holes communicating with said air port and said confining space, and two positioning portions formed on said end surface and located on two opposite sides of said air port;

15 wherein said vacuum unit is removably connected to said air port for pumping the air out of said confining space; and

20 wherein said at least one flexible air barrier film has at least one fixed portion removably fixed to said end surface of said shoe last body and corresponding in position to said positioning portions.

4. The apparatus as claimed in Claim 3, wherein said film unit includes two opposite flexible air barrier films removably covering the assembly of said shoe last and the at least two shoe components therebetween, said flexible air barrier films having peripheral ends overlapping each other.