Description

Technical Field

The present invention relates generally to electrical switches, and more particularly to non-contact piezoelectric switches and interface circuits therefor.

Background Art

Switches are increasingly being used in a variety of application and particularly in groups for the control of household appliances, industrial control applications, and alphanumeric keyboards, for example. For these applications, a small size low cost, high reliability switch, which is relatively insensitive to outside electromagnetic interference, is desired.

Conventional metal contact switches have, of course, been used for some time. With these conventional metal contact switches, the contact resistance tends to increase with age, and also is affected by external environmental conditions, such as temperature and moisture. This tends to create long-term reliability problems due to increasing contact resistance. An example of a multiple contact switching apparatus is US—A—3,240,885 (Grunfelder, et al) Multiple Switching Apparatus, issued March 15, 1966.

Non-contact switches have also existed for some time. An example of such a non-contact touch switch would be a capacitance sensor. However, in order for capacitance sensors to work properly, the touch surface must be kept clean from dirt, grease, or other contaminants. Further, the capacitance sensor might not work if the operator is wearing gloves. A still further disadvantage with capacitance sensors is that most are not readily configured into a matrix array, and further that they provide no tactile sensation of switch activation.

To solve some of these problems, non-contact piezoelectric switches have been developed. In general, an impact imparted upon a piezoelectric ceramic generates a voltage which may be utilized to indicate switch closure. Examples of these piezoelectric switches are US—A—4,078,187 (Kanisawa) Piezoelectric Switching Device, issued March 7, 1978; US—A—3,648,279 (Watson) Multielectrode Transducer Element, issued March 7, 1972; and US—A—3,303,290 (Suloway) Signaling Arrangements Employing Piezoelectric Devices. An improved type of non-contact piezoelectric switch has replaced the piezoelectric ceramic material with a piezoelectric polymeric material; for example, polyvinylidene fluoride. Some of these piezoelectric polymeric switches have been arranged in keyboard type arrangements. An example is US—A—3,935,485 (Yoshida, et al) entitled "Piezoelectric Key Board Switch" issued January 27, 1976, which includes a single layer of piezoelectric polymer film having electrodes on both surfaces. A second example is US—A—3,940,637 (Ohigashi, et al) Polymeric Piezoelectric Key Actuated Device, issued February 24, 1976, which also includes a single piezoelectric polymer film having electrodes on both surfaces thereof. US—A—3,940,637 also discloses two such polymer films having electrodes on opposing surfaces thereof with the film layers being separated by an insulating layer and in which the two outer sets of electrodes are adapted to be connected to ground potential. Other examples of piezoelectric non-contact switches include US—A—3,382,338, (Arseneault, et al) Push Button Actuator for Elastomeric Switch, issued May 7, 1968; US—A—3,798,473 (Murayama, et al) Polymer-Type Electro-Acoustic Transducer Element, issued March 19, 1974; and US—A—3,832,580 (Yamamuro, et al) High Molecular Weight, Thin Film Piezoelectric Transducers, issued August 27, 1974.

A disadvantage to the above-described apparatus, especially when configured in a multilayer piezoelectric polymer film structure is that the devices are not shielded and are therefore sensitive to outside electromagnetic disturbances. Since the signal generated by the strained piezoelectric polymer film material is relatively small the device is particularly sensitive to outside interference.

Since the signal pulse generated by the strained piezoelectric polymeric material is relatively small, it therefore needs to be amplified by associated electronic circuitry in order to produce a signal which may be transmitted to other electronic components to indicate switch closure. An example of such associated electrical circuitry is illustrated in US—A—4,078,187, (Kanisawa, et al) Piezoelectric Switching Device, issued March 7, 1978. A disadvantage in this electrical circuit, however, is that it is not as sensitive as possible, and its threshold is not readily adjustable.

Disclosure of Invention

According to this invention there is provided a pressure sensitive apparatus for producing electrical signals on two electrodes, comprising a first conductive layer adapted to be connected to ground potential; a first piezoelectric polymer film layer disposed adjacent to said first conductive layer; a first electrode layer having at least one electrode and disposed on the opposite side of said first piezoelectric polymer film layer from the first conductive layer; a second electrode layer having at least one electrode; a second piezoelectric polymer film layer disposed adjacent to said second electrode layer; an insulating layer separating the two film layers; and a second conductive layer adapted to be connected to ground potential and disposed on the opposite side of said second piezoelectric polymer film layer from the second electrode layer characterized by said first electrode layer and the second electrode layer are disposed adjacent to said insulating layer.

The piezoelectric polymer film layer may be constructed of polyvinylidene fluoride and the apparatus may also further include support layers sandwiching the layers previously described, each having an opening at the position where the

two electrodes are located. The layers can be integrally bonded together or the layers may be held together by the mechanically affixing of the support layers to each other or by a combination thereof.

The layered structure just described may be constructed by taking an insulating layer and sandwiching that insulating layer between two piezoelectric polymer films, each having one of the electrodes on one surface thereof and having a conductive plane on the other surface thereof, adapted to be connected to ground with the electrodes in closest proximity to the insulating film.

The apparatus may also have an electrical sensing circuit coupled to one of the two electrodes and to its associated conductive plane utilized as signal ground for amplifying the electrical signal. This electrical sensing circuit may be either a high impedance voltage sensing interface or may be a low impedance current sensing interface. Both interfaces may be adjustable for sensitivity.

The apparatus for producing an electrical signal may be configured in a matrix keyboard, having switch positions arranged in a plurality of rows and columns. Such a pressure sensitive keyboard switch is comprised of an insulating film, two piezoelectric polymer films each having electrodes on one surface thereof, adapted to be connected to ground, one disposed on each side of the insulating film with the electrodes in closest proximity to the insulating film with each of the electrodes on one of the two piezoelectric polymer films being a strip and constituting one of the rows of the keyboard switch positions and each of the electrodes on the other of the two piezoelectric polymer films, being a strip constituting one of the columns of the keyboard switch positions. The apparatus also includes two support substrates, each having an opening at each of said keyboard switch positions, one of the two support substrates disposed on each side of the two piezoelectric polymer films.

Such an apparatus provides all of the advantages of using piezoelectric polymeric materials. It is suitable for matrix encoding and provides outside ground planes to provide for electrical shielding. Further, it is also easier to insulate the described apparatus because of the ground planes being in existence on the outside of the layered structure instead of signal electrodes.

The sensing circuits described provide both a high impedance interface which is voltage sensitive and adjustable, and current sensing low impadence interface. The electrical sensing circuits coupled to the layered structure, allows the complete structure to simulate an ordinary contact switch, and which provides none of the disadvantages of an ordinary contact switch.

The structure described does not suffer from contact oxidation. The functioning of the structure is insensitive to an operator wearing gloves, and is insensitive to the build-up of dirt and grease.

Brief Description of the Drawings

The foregoing objects, advantages, construction and operation of the present invention will become more readily apparent from the following description and accompanying drawings in which:

Figure 1 is a cross sectional view of the layered structure of the non-contact piezoelectric switch;

Figure 2 is an exploded perspective view of the layered structure;

Figure 3 is a perspective view of an assembled layered structure;

Figure 4 is one electrical sensing circuit featuring an adjustable MOS circuit;

Figure 5 is an electrical sensing circuit featuring a unipolar operational amplifier;

Figure 6 is an electrical sensing circuit featuring an alternative unipolar operational amplifier;

Figure 7 is an electrical sensing circuit featuring a bipolar operational amplifier;

Figure 8 is an electrical sensing circuit featuring an alternative bipolar operational amplifier;

Figure 9 is an electrical sensing circuit featuring a current actuated operational amplifier;

Figure 10 is an electrical sensing circuit featuring an alternative current activated operational amplifier;

Figure 11 is an electrical sensing circuit featuring a "Norton" operational amplifier.

Figure 12 is an electrical sensing circuit featuring an alternative "Norton" operational amplifier;

Figure 13 is an electrical sensing circuit featuring another alternative "Norton" operational amplifier; and

Figure 14 is an electrical sensing circuit featuring still another alternative "Norton" operational amplifier.

Best Mode for Carrying Out the Invention

Figure 1 illustrates a preferred embodiment for obtaining the layered piezoelectric structure. The layers consist of a conductive plane 10, a piezoelectric polymer film 12, an electrode layer 14, an insulating layer 16, another electrode layer 18, another piezoelectric polymer film 20, and another conductive plane 22. This particular layered structure may be accomplished by taking the insulating layer 16 and sandwiching it with two piezoelectric polymer films 12 and 20, each coated with a conductive plane 10 and 22 on one side and coated with at least one electrode 14 and 18 on the other side. The sandwich is then brought together with the electrode layers 14 and 18 in closest proximity to the insulating layer 16. The resulting sandwich provides the conductive planes 10 and 22 on the outside surfaces of the structure. This alows both for immunity from electromagnetic interference, and for ease of insulating the structure to support substrates.

The insulating layer 16 in Figure 1 is constructed from any thin insulating film such as thin polyethylene or thin mylar. If polyethylene is used a thickness of about 25 micrometers is preferred. The piezoelectric polymer films 12 and 20 are constructed of polyvinylidene fluoride and in a

preferred embodiment are each approximately 25 micrometers thick. This is thick enough to provide for mechanical stability and for electrical output but still thin enough to allow for deflection upon stress by an operator. The conductive planes 10 and 22 are metallized, as, for example, nickel, or aluminum. In a preferred embodiment aluminum is deposited in a layer approximately 0.1 micrometers thick. The electrodes 14 and 18 are deposited on the piezoelectric polymer films 12 and 20 in the desired pattern and are comprised of a suitable metal, again for example, nickel or aluminum. In a preferred embodiment aluminum is deposited in a layer approximately 0.1 micrometers thick. Again this thickness is chosen to provide physical stability.

Figure 2 represents a perspective view of an exploded layered structure. Again, the insulating layer 16 is provided in the middle of the structure with two piezoelectric polymer films and 12 and 20 provided on each side. For ease of illustration, the two conductive planes 10 and 22 are not specifically shown. The electrode layer 18 is shown deposited on the top of piezoelectric polymer film layer 20 and the electrode pattern layer 14 is shown by dotted lines deposited on the lower side of piezoelectric polymer film 12. Notice that this construction places the electrode layers 14 and 18 in closest proximity to insulating layer 16. It is also to be noted that the electrode pattern 14 consists of a plurality of strips while the electrode pattern 18 also consists of a plurality of strips positioned orthogonal to the strips of electrodes 14. This allows a matrix encoded keyboard switch arrangement whereby the electrode pattern 14 represents the rows of switch positions, and the electrode pattern 18 represents the columns of the switch positions. Thus, the activation of any individual switch position would activate one row of electrode layer 14 and one column of electrode layer 18.

This layered structure in Figure 2 is further sandwiched together by two support substrates 24 and 26. These support substrates are shown having openings 28 at each switch position in the matrix. This allows contact with the layered structure at each individual switch position and the piezoelectric film to be strained producing an electrical signal on the electrode layers 14 and 18. These support substrates 24 and 26 may be constructed of a punched aluminum sheet, a punched or molded plastic sheet or other suitably, relatively rigid material to provide support for the polymeric layers structure. Support substrates 24 and 26 are shown with openings 28 punched out or molded out to provide for the depression of the piezoelectric layered structure upon operator contact to provide for straining the piezoelectric polymeric material. An alternative embodiment would provide for one of the support substrates, for example, support substrate 26 instead of having complete openings 28 to have a flexible covering, a recessed area or a simple dimple to allow for depression of the piezoelectric polymeric material.

Although Figure 2 illustrates openings 28 as complete passages, it is to be emphasized that the purpose of the openings 28 is to allow the piezoelectric polymer film 12 and 20 to be physically strained at individual switch positions. This requires that the piezoelectric polymer film 12 and 20 be allowed to deflect from both support substrates 24 and 26 and that access for straining be allowed for one support substrate, e.g., 24. Thus the scope of the present invention contemplates flexible substances and other straining apparatus in place of complete passages as openings 23 in support substrate 24 and contemplates an even broader range of materials as openings 28 in support substrate 26. In addition to flexible substances the openings 28 in support substrate 26 may comprise simply a recess, a concave socket or a bubble which would allow the piezoelectric film 12 and 20 to deflect while being strained from the opposite side.

A perspective view of the completely assembled layered structure 30 is illustrated in Figure 3. The layers may be held together merely by pressure between the support substrates which would be affixed to each other mechanically, or with a suitable adhesive bonding between the layers which could include thermal or ultrasonic bonding of the piezoelectric film layer structure.

In a preferred embodiment a combination of bonding and support substrate pressure is utilized. Each piezoelectric polymer film including the conductive plane and the electrode is integrally bonded to its associated support substrate. The resulting three piece structure (two parts of piezoelectric polymer films bonded to a support substrate and one part insulating layer) is then sandwiched together utilizing pressure from the outside support substrates which are mechanically affixed to each other, for example with screws or similar device.

Pressure on the individual switch position induces a strain in the piezoelectric polymer films. This strain causes a change in the film net polarization resulting in a charge on the electrodes covering the strained area. The charge signal is processed either as a voltage by a high impedance electrical interface, or as a current by a low impedance electrical interface. In either case, an electrical sensing circuit is coupled to one of the electrodes and to its associated conductive plane preferably at the edges of the piezoelectric polymeric material. For the purposes of these electrical sensing circuits, the conductive plane serves a signal ground for its associated electrode, namely all of the electrodes located on the electrode layer nearest the particular conductive plane.

One such electrical sensing circuit providing an adjustable sensitivity high-impedance interface to the electrodes as illustrated in Figure 4. Here a single input MOS digital gate, for example, CMOS hex inverter type 4609 manufactured by National Semiconductor is shown connected between a positive voltage source and signal ground. The digital gate may alternatively be part of a more

complex logic element. The piezoelectric polymer film material 52 is shown having an electrode 44 and a conductive plane 46. Electrode 44 is coupled directly to the input 51 of gate 50. Conductive plane 46 is coupled directly to signal ground. Resistor 60, coupled between the positive supply of gate 50 and signal ground, provides a bias for the input 51 of gate 50. Resistor 60 has an adjustable tap 51 and resistance 62 is shown connected between input 51 and adjustable tap 61. Resistor 62 is preferably on the order of 10 megaohms and resistor 60 is preferably small relative to resistor 62, for example on the order of 100 kilohms. This provides a bias for input 51 by providing a quiescent voltage on input 51 so that the charge necessary to be provided by the piezoelectric polymer material 52 is small because only a small voltage is required in addition to the quiescent voltage on input 51 to provide the digital threshold for gate 50. Thus less pressure is required upon the piezoelectric polymeric material 52 and the apparent touch sensitivity is increased.

Figures 5 through 14 illustrate electrical sensing circuits in which a polarity of electrode for the piezoelectric polymer is indicated and is important. In all cases the polarity is indicated by positive electrode 54 and negative electrode 56. It is to be understood, however, that the electrical sensing circuits are always connected utilizing an electrode and the associated conductive plane. The conductive plane is always the side coupled to signal ground. For ease of illustration, polarity of the piezoelectric film 52 is merely indicated by positive electrode 54 and negative electrode 56 without regard to which is actually the conductive plane. It is recognized, of course, that the polarity achieved may be reversed by straining the piezoelectric film in the opposite direction.

Figure 5 illustrates a similar adjustable sensitivity high impedance electrical sensing circuit as in Figure 4. Here a comparator 64 with inputs 66 and 68 is connected between a positive voltage source and signal ground. An example of a comparator circuit 64 is type LM393 manufactured by National Semiconductor. Alternatively an operational amplifier with no feedback may be utilized to provide the comparison function. An example of an operational amplifier used as a comparator is type LM348 manufactured by National Semiconductor. The piezoelectric polymeric material 52 is shown having a positive electrode and a negative electrode 56. Positive electrode 54 is coupled to input 66 while negative electrode 56 is coupled directly to signal ground. Resistor 70 is coupled between the positive supply voltage and input 68, and resistor 72 is coupled between input 68 and signal ground. Resistor 72 also has an adjustable tap 73. Resistor 74 is coupled between input 66 and signal ground. Resistor 74 is preferably 10 megaohms and resistors 70 and 72 are preferably 50 kilohms each. Resistors 70, 72 and 74 provide an adjustable bias for operational amplifier 64 to provide for increased sensitivity and adjustable sensitivity in much the same manner that resistors 60 and 62 did in Figure 4 for gate 50.

Figure 6 illustrates an alternative electrical sensing circuit similar to that circuit illustrates in Figure 5. However in Figure 6, positive electrode 54 of piezoelectric polymer film 52 is coupled to signal ground while negative electrode 56 is coupled to input 66 of comparator 64. Resistors 70 and 72 are reversed, however, to account for the opposite polarity of the film 52. This positions resistor 74, which is still coupled to adjustable tap 73, between input 68 and the positive supply voltage.

A similar circuit is illustrated in Figure 7 using a bipolar powered comparator 76 connected between a positive voltage source and a negative voltage source. Again, an operational amplifier with no feedback may be used as a comparator. Again, a piezoelectric polymeric material 52 is shown having a positive electrode 54 and a negative electrode 56. Positive electrode 54 is coupled to input 78 and negative electrode 56 is coupled to input 80 of comparator 76. Input 80 is also made reference to signal ground. Resistor 82 is coupled between the negative supply voltage and input 80. Resistor 82 has an adjustable tap 83 and provides for a bias for input 80. Resistor 84 is coupled between input 78 and the adjustable tap 83 and provides for an adjustable bias for negative input 78. Resistor 84 is preferably 10 megaohms and resistor 82 is preferably smaller as for example 100 kilohms.

Figure 8 illustrates an alternative electrical sensing circuit which is similar to that circuit illustrated in Figure 7. However in Figure 8, positive electrode 54 is coupled to signal ground while negative electrode 56 is coupled to input 66. To account for the change in polarity, resistors 82 and 84 have been reversed.

Figure 9 illustrates a similar bipolar powered operational 86 which again is coupled between a positive supply voltage and a negative supply voltage, which provides a low impedance interface to provide a current sensing circuit. Again, piezoelectric polymeric material 52 has a positive electrode 54 and a negative electrode 56. Positive electrode 54 is coupled to inverting input 88 while negative electrode 56 is coupled to non-inverting input 90 which is also referenced to signal ground. Bias resistor 92, preferably several megaohms, is coupled between output 93 of the operational amplifier 86 and inverting input 88. Bias resistor 94, also preferably several megaohms, is coupled between negative input 88 and the negative supply voltage. Both resistor 92 and resistor 94 may be adjusted or made adjustable to allow for variable sensitivity.

Figure 10 illustrates an alternative electrical sensing circuit which is similar to Figure 9. However, in Figure 10 positive electrode 54 is coupled to signal ground while negative electrode 56 is coupled to inverting input 88. To account for the change in polarity resistor 94 is coupled to the positive supply voltage rather than the negative supply voltage.

In Figure 11 a similar circuit is illustrated. This time using a "Norton" amplifier, for example, Type No. LM 3900 manufactured by National Semiconductor. Again, piezoelectric polymeric material 52 is shown having a positive electrode 54 and a negative electrode 56. The "Norton" amplifier 96 is connected between a positive supply voltage and signal ground. Positive electrode 54 is coupled to inverting input 98 and negative electrode 56 is coupled to signal ground. Bias is provided by resistor 100, preferably in the range of 500 kilohms to 10 megaohms coupled between non-inverting input 102 and positive supply voltage. Resistor 100 may be adjusted or made adjustable to provide for variable sensitivity.

Alternatively, positive electrode 54 may be coupled to non-inverting input 102 and bias provided by resistor 100 coupled between inverting input 98 and the positive supply voltage, as in Figure 12.

A similar arrangement is shown in Figure 13 where the polarity of the piezoelectric polymer film is reversed from Figure 11 and 12. Here, positive electrode 54 is coupled to signal ground while negative electrode 56 is coupled to inverting input 98. Again bias is provided by resistor 100 coupled between non-inverting input 102 and the positive supply voltage. To account to the change in polarity, however, additional bias resistor 104 is required coupled between negative electrode 56 and the positive supply voltage. Both resistors 100 and 104 are preferably in the range of 500 kilohms to 10 megaohms and may be adjusted or made adjustable to provide for variable sensitivity.

Again alternatively, negative electrode 56 may be coupled to non-inverting input 102 and bias provided by resistor 100 coupled between inverting input 98 and the positive supply voltage and by resistor 104 coupled between negative electrode 56 and the positive supply voltage, as in Figure 14.

Of course, it is to be recognized that the polarity of the piezoelectric polymer film 52 may be reversed merely by straining the film in the opposite direction. Or the reverse polarity may be achieved by making the electrical sensing circuit responsive to the release of strain to the film rather than commencement of strain to the film.

It is also to be recognized that while two electrodes are always shown in Figures 4 through 14, in all cases it is contemplated that the electrical connection desired is between an electrode (either positive or negative responsive) and its associated conductive plane.

One of the electrical sensing circuits described may be connected to one of the electrodes on each electrode layer illustrated and described in Figures 1 through 3 to provide for sensing of a signal on two of the electrodes (a row and a column) to identify a single switch position which has been activated, thus a matrix encoded non-contact piezoelectric switch.

Thus, it can be seen that there has been shown and described a novel apparatus for producing electrical signals. It is to be understood, however, that various changes, modifications, and substitutions in the form and details of the described apparatus can be made by those skilled in the art without departing from the scope of the invention as defined by the following claims:

Claims

1. A pressure sensitive apparatus for producing electrical signals on two electrodes (14, 18), comprising a first conductive layer (10) adapted to be connected to ground potential; a first piezoelectric polymer film layer (12) disposed adjacent to said first conductive layer; a first electrode layer (14) having at least one electrode and disposed on the opposite side of said first piezoelectric polymer film layer (12) from the first conductive layer; a second electrode layer (18) having at least one electrode; a second piezoelectric polymer film layer (20) disposed adjacent to said second electrode layer (18); and insulating layer (16) separating the two films layers (12, 20); and a second conductive layer (22) adapted to be connected to ground potential and disposed on the opposite side of said second piezoelectric polymer film layer (20) from the second electrode layer (18) characterized in that said first electrode layer (14) and the second electrode layer (18) are disposed adjacent to said insulating layer (16).

2. An apparatus as in claim 1 which is further characterized by two support substrates (24, 26), one disposed on each side of said two piezoelectric polymer films (12, 20), each of said two support substrates having an opening (28) where said two electrodes (14, 18) are located.

3. An apparatus as in claim 2 wherein said two support substrates (24, 26) are mechanically affixed to each other.

4. An apparatus as in claim 2 wherein each of said two piezoelectric polymer films (12, 20) and the associated one of said two support substrates (24, 26) are integrally bonded together, and said two support substrates (24, 26) are mechanically affixed to each other.

5. An apparatus as in claims 1 and 2 wherein said two piezoelectric polymer films (12, 20) are polyvinylidene fluoride.

6. An apparatus as in claim 2 which is further characterized by an electrical sensing circuit coupled to one of said two electrodes (14, 18) and coupled to said conductive plane (10, 22) for amplifying one of said electrical signals, said conductive plan (10, 22) being utilized as signal ground.

7. An apparatus as in claim 6 wherein said electrical sensing circuit is characterized by a high impedance interface to said one of said two electrodes and which provides for an adjustable sensitivity.

8. An apparatus as in claim 6 wherein said electrical sensing circuit comprises a low impedance interface to said one of said two electrodes.

In Figure 11 a similar circuit is illustrated. This time using a "Norton" amplifier, for example, Type No. LM 3900 manufactured by National Semiconductor. Again, piezoelectric polymeric material 52 is shown having a positive electrode 54 and a negative electrode 56. The "Norton" amplifier 96 is connected between a positive supply voltage and signal ground. Positive electrode 54 is coupled to inverting input 98 and negative electrode 56 is coupled to signal ground. Bias is provided by resistor 100, preferably in the range of 500 kilohms to 10 megaohms coupled between non-inverting input 102 and positive supply voltage. Resistor 100 may be adjusted or made adjustable to provide for variable sensitivity.

Alternatively, positive electrode 54 may be coupled to non-inverting input 102 and bias provided by resistor 100 coupled between inverting input 98 and the positive supply voltage, as in Figure 12.

A similar arrangement is shown in Figure 13 where the polarity of the piezoelectric polymer film is reversed from Figure 11 and 12. Here, positive electrode 54 is coupled to signal ground while negative electrode 56 is coupled to inverting input 98. Again bias is provided by resistor 100 coupled between non-inverting input 102 and the positive supply voltage. To account to the change in polarity, however, additional bias resistor 104 is required coupled between negative electrode 56 and the positive supply voltage. Both resistors 100 and 104 are preferably in the range of 500 kilohms to 10 megaohms and may be adjusted or made adjustable to provide for variable sensitivity.

Again alternatively, negative electrode 56 may be coupled to non-inverting input 102 and bias provided by resistor 100 coupled between inverting input 98 and the positive supply voltage and by resistor 104 coupled between negative electrode 56 and the positive supply voltage, as in Figure 14.

Of course, it is to be recognized that the polarity of the piezoelectric polymer film 52 may be reversed merely by straining the film in the opposite direction. Or the reverse polarity may be achieved by making the electrical sensing circuit responsive to the release of strain to the film rather than commencement of strain to the film.

It is also to be recognized that while two electrodes are always shown in Figures 4 through 14, in all cases it is contemplated that the electrical connection desired is between an electrode (either positive or negative responsive) and its associated conductive plane.

One of the electrical sensing circuits described may be connected to one of the electrodes on each electrode layer illustrated and described in Figures 1 through 3 to provide for sensing of a signal on two of the electrodes (a row and a column) to identify a single switch position which has been activated, thus a matrix encoded non-contact piezoelectric switch.

Thus, it can be seen that there has been shown and described a novel apparatus for producing electrical signals. It is to be understood, however, that various changes, modifications, and substitutions in the form and details of the described apparatus can be made by those skilled in the art without departing from the scope of the invention as defined by the following claims:

Claims

1. A pressure sensitive apparatus for producing electrical signals on two electrodes (14, 18), comprising a first conductive layer (10) adapted to be connected to ground potential; a first piezoelectric polymer film layer (12) disposed adjacent to said first conductive layer; a first electrode layer (14) having at least one electrode and disposed on the opposite side of said first piezoelectric polymer film layer (12) from the first conductive layer; a second electrode layer (18) having at least one electrode; a second piezoelectric polymer film layer (20) disposed adjacent to said second electrode layer (18); and insulating layer (16) separating the two films layers (12, 20); and a second conductive layer (22) adapted to be connected to ground potential and disposed on the opposite side of said second piezoelectric polymer film layer (20) from the second electrode layer (18) characterized in that said first electrode layer (14) and the second electrode layer (18) are disposed adjacent to said insulating layer (16).

2. An apparatus as in claim 1 which is further characterized by two support substrates (24, 26), one disposed on each side of said two piezoelectric polymer films (12, 20), each of said two support substrates having an opening (28) where said two electrodes (14, 18) are located.

3. An apparatus as in claim 2 wherein said two support substrates (24, 26) are mechanically affixed to each other.

4. An apparatus as in claim 2 wherein each of said two piezoelectric polymer films (12, 20) and the associated one of said two support substrates (24, 26) are integrally bonded together, and said two support substrates (24, 26) are mechanically affixed to each other.

5. An apparatus as in claims 1 and 2 wherein said two piezoelectric polymer films (12, 20) are polyvinylidene fluoride.

6. An apparatus as in claim 2 which is further characterized by an electrical sensing circuit coupled to one of said two electrodes (14, 18) and coupled to said conductive plane (10, 22) for amplifying one of said electrical signals, said conductive plan (10, 22) being utilized as signal ground.

7. An apparatus as in claim 6 wherein said electrical sensing circuit is characterized by a high impedance interface to said one of said two electrodes and which provides for an adjustable sensitivity.

8. An apparatus as in claim 6 wherein said electrical sensing circuit comprises a low impedance interface to said one of said two electrodes.

* C L M S *

9. A pressure sensitive apparatus as in claim 2 characterized by said apparatus having a plurality of keyboard switch positions arranged in a plurality of rows and columns, said electrode of said first electrode layer (14) being a strip constituting one of said rows of said plurality of keyboard switch positions and by said electrode of said second electrode layer (18) being a strip constituting one of said columns of said plurality of keyboard switch positions and by said opening (28) of said two support substrates (24, 26) being at one of said plurality of keyboard switch positions.

Patentansprüche

1. Druckempfindliche Vorrichtung zum Erzeugen von elektrischen Signalen an zwei Elektroden (14, 18) mit einer ersten leitfähigen Schicht (10), die an ein Erdpotential anschließbar ist; einer aus einer im Bereich der ersten leitfähigen Schicht angeordneten ersten aus einem piezoelektrischen Polymerfilm bestehenden Schicht (12); einer ersten Elektrodenschicht (14), die mindestens eine Elektrode besitzt und auf der der ersten leitfähigen Schicht entgegengesetzten Seite der ersten aus einem piezoelektrischen Polymerfilm bestehenden Schicht (12) angeordnet ist; einer zweiten Elektrodenschicht (18) mit mindestens einer Elektrode; einer zweiten aus einem piezoelektrischen Polymerfilm (20) bestehenden Schicht, die im Bereich der zweiten Elektrodenschicht (18) angeordnet ist; einer die beiden Filmschichten (12, 20) voneinander trennenden Isolierschicht (16) und einer zweiten leitenden Schicht (22), die an ein Erdpotential anschließbar und die auf der der zweiten Elektrodenschicht (18) entgegengesetzten Seite der zweiten aus einem piezoelektrischen Polymerfilm bestehenden Schicht (20) angeordnet ist, dadurch gekennzeichnet, daß die erste Elektrodenschicht (14) und die zweite Elektrodenschicht (18) im Bereich der Isolierschicht (16) angeordnet sind.

2. Vorrichtung nach Anspruch 1, gekennzeichnet durch zwei Stützsubstrate (24, 26), die auf entgegengesetzten Seiten der beiden piezoelektrischen Polymerfilme (12, 20) angeordnet sind und die je eine Ausnehmung (28) haben, in deren Bereich die beiden Elektroden (14, 18) angeordnet sind.

3. Vorrichtung nach Anspruch 2, dadurch gekennzeichnet, daß die beiden Stützsubstrate (24, 26) mechanisch aneinander befestigt sind.

4. Vorrichtung nach Anspruch 2, dadurch gekennzeichnet, daß jede der beiden piezoelektrischen Polymerfilme (12, 20) und das ihr jeweils zugeordnete der beiden Stützsubstrate (24, 26) einstückig miteinander verbunden sind und daß die beiden Stützsubstrate (24, 26) mechanisch aneinander befestigt sind.

5. Vorrichtung nach Anspruch 1 und 2, dadurch gekennzeichnet, daß die beiden piezoelektrischen Polymerfilme (12, 20) aus Polyvinylidenfluorid bestehen.

6. Vorrichtung nach Anspruch 2, gekennzeichnet durch eine an eine der beiden Elektroden (14, 18) und an eine leitfähige Ebene (10, 22) angekoppelte elektrische Meßschaltung zum Verstärken eines der genannten elektrischen Signale, wobei die leitfähige Ebene (10, 22) als Signalerde verwendet wird.

7. Vorrichtung nach Anspruch 6, dadurch gekennzeichnet, daß die elektrische Meßschaltung über eine Schnittstelle mit hoher Impedanz an die genannte eine der beiden Elektroden angekoppelt ist und daß die Empfindlichkeit einstellbar ist.

8. Vorrichtung nach Anspruch 6, dadurch gekennzeichnet, daß die elektrische Meßschaltung an die genannte eine der beiden Elektroden über eine Schnittstelle von niedriger Impedanz angekoppelt ist.

9. Druckempfindliche Vorrichtung nach Anspruch 2, dadurch gekennzeichnet, daß sie eine Mehrzahl von Tastenschaltstellen besitzt, die in einer Mehrzahl von Zeilen und Spalten angeordnet sind, daß die Elektrode der ersten Elektrodenschicht (14) ein Streifen ist, der eine der Zeilen der Mehrzahl der Tastenschaltstellen bildet, und daß die Öffnung (28) in den beiden Stützsubstraten (24, 26) an einer der in einer Mehrzahl vorhandenen Tastenschaltstellen angeordnet ist.

Revendications

1. Appareil sensible à la pression pour produire des signaux électriques sur deux électrodes (14, 18), comprenant une première couche conductrice (10) prévue pour être reliée à un potentiel de terre, une première couche (12) de film de polymère piézoélectrique adjacente à ladite première couche conductrice, une première couche d'électrode (14) comportant au moins une électrode et disposée sur la face de ladite première couche (12) de film de polymère piézoélectrique qui est à l'opposé de la première couche conductrice, une deuxième couche d'électrode (18) comportant au moins une électrode, une deuxième couche (20) de film de polymère piézoélectrique adjacente à ladite deuxième couche d'électrode (18), une couche isolante (16) séparant les deux couches de film (12, 20), et, une deuxième couche conductrice (22) prévue pour être reliée au potentiel de terre et disposée sur la face de ladite deuxième couche (20) de film de polymère piézoélectrique qui est à l'opposé de la deuxième couche d'électrode (18), caractérisé en ce que ladite première couche d'électrode (14) et ladite deuxième couche d'électrode (18) sont disposées de manière à être adjacentes à ladite couche isolante (16).

2. Appareil suivant la revendication 1, caractérisé en outre en ce que qu'il comprend deux substrats de maintien (24, 26), disposés un de chaque côté desdits deux films de polymère piézoélectrique (12, 20), chacun de ces deux substrats de maintien présentant une ouverture (28) à l'endroit où sont placées lesdites deux électrodes (14, 18).

3. Appareil suivant la revendication 2, dans lequel lesdits deux substrats de maintien (24, 26) sont fixés mécaniquement l'un à l'autre.

* C L M S *

4. Appareil suivant la revendication 2, dans lequel chacun desdits deux films de polymère piézoélectrique (12, 20) et le substrat associé desdits deux substrats de maintien (24, 26) sont liés ensemble de façon intégrale, lesdits deux substrats de maintien (24, 26) étant fixés mécaniquement l'un à l'autre.

5. Appareil suivant les revendications 1 et 2, dans lequel lesdits deux films de polymère piézoélectrique (12, 20) sont de fluorure de polyvinylidène.

6. Appareil suivant la revendication 2, caractérisé en outre en ce qu'il comprend un circuit de détection électrique raccordé à l'une desdites deux électrodes (14, 18) et raccordé audit plan conducteur (10, 22) pour amplifier l'un desdits signaux électriques, ledit plan conducteur (10, 22) étant utilisé comme terre de signal.

7. Appareil suivant la revendication 6, dans lequel ledit circuit de détection électrique est caractérisé en ce qu'il comprend une interface de haute impédance, avec l'une desdites deux électrodes et qui procure une sensibilité réglable.

8. Appareil suivant la revendication 6, dans lequel ledit circuit de détection électrique constitue une interface de faible impédance avec l'une desdites deux électrodes.

9. Appareil sensible à la pression suivant la revendication 2, caractérisé en ce qu'il présente une pluralité de positions d'interrupteur de clavier agencées en une pluralité de rangées et de colonnes, ladite electrode de ladite première couche d'électrode (14) étant une bande qui constitue une desdites rangées de ladite pluralité de positions d'interrupteur de clavier, et ladite électrode de ladite deuxième couche d'électrode (18) étant une bande qui constitue une desdites colonnes de ladite pluralité de positions d'interrupteur de clavier, ladite ouverture (28) desdits deux substrats de maintien (24, 26) étant située à une position de ladite pluralité de positions d'interrupteur de clavier.

* C L M S *