

METHOD AND APPARATUS FOR SHUFFLING AND HANDLING CARDS**PRIORITY CLAIM**

This application claims the benefit of United States Provisional Patent Application
5 Serial No. 61/978,685, filed April 11, 2014, for “METHOD AND APPARATUS FOR
SHUFFLING AND DEALING CARDS.”

BACKGROUND

The present application relates to structure and use of mechanical card shufflers.
10 Mechanical shufflers have been known for over 100 years. Some mechanical
shufflers in recent years have had a capability of dispensing two or more cards together as a
hand for each of several players including the dealer.

Card games played in casinos utilize one or more decks of cards, with each deck
usually consisting of 52 to 54 cards. For certain games, specialized decks of fewer cards or
15 decks including one or two jokers in addition to the normal 52 are used. Other card games
require cards to be dealt to players from as many as six or eight ordinary decks shuffled
together as one combined, large, random group of cards at the beginning of play.

New decks of cards are normally delivered to a gaming table in a sequential
arrangement in order of suit and rank, but the cards must be shuffled before beginning play
20 so that they are in a random arrangement unknown to any of the players.

Various mechanisms have been designed for placing cards from a deck into a
different, shuffled, order for use in play, sometimes by using a random number generator to
define a random order of cards for a “shuffled” deck and then using a computer controlled
mechanism to identify each card in a deck being shuffled and to place each card in its
25 designated space.

Casinos prefer to use mechanical shufflers instead of having dealers manually
shuffle the cards for several reasons: a major reason is to save time otherwise spent on
shuffling, since the earnings of a casino depend upon the number of hands that can be
played during a gaming session. Another reason is to be able to avoid or detect cheating.
30 Partly for that reason, it is also desirable to be able to review the order in which cards have
been dealt, and some available mechanical shufflers have the capacity to determine the
order of cards in a shuffled deck and retain it in a computer memory. Known mechanical
shufflers, however, have suffered from several shortcomings, such as simply being slower

- 2 -

than desired, or being so large that they impede a supervisor's view of the game table or players' hands, or impede a casino security system surveillance camera's field of view. Other mechanical shufflers frequently jam and thus fail to provide a shuffled deck ready for use in play without a delay while the shuffler is cleared and a complete deck is then

5 shuffled. Casinos frequently replace the decks of cards in play, but nervous or careless players may bend cards, or spill drinks, making cards likely to stick together, leading to some shuffler jamming.

What is desired, then, is an easily operated, dependable, and efficient shuffler able to handle playing cards that have been bent or that tend to stick to one another, and that is

10 small enough not to require a specially built table or complex installation of the shuffler for it to be reliably usable in a casino situation, and a shuffler able to present shuffled cards either as a complete shuffled deck or as hands of a desired number of cards for each player or the dealer. It is also desired for such a shuffle to have the ability to shuffle multiple decks of cards and make them available for play quickly enough that it is unnecessary to

15 utilize a "multi batch" system of shuffling and dealing.

DISCLOSURE

Disclosed herein is a mechanical shuffler that in one embodiment includes a programmable computer-controlled mechanism for placing each card of a deck to be

20 shuffled into a randomly selected one of a remaining plurality of empty receptacles in a dealing rack portion of the mechanism and in which cards can be removed from the dealing rack either as a complete shuffled deck or in a predetermined lesser number of cards as a player's or dealer's hand, or a predetermined number of cards or single cards for use in any stage of play of a game.

25 In one embodiment of the mechanism disclosed herein, a card shuffler includes a dealing rack defining a plurality of single-card receptacles; a deck-crib capable of containing a plurality of cards and located adjacent to and aligned with the dealing rack; a card moving mechanism associated with the deck-crib and operable to move a series of cards individually from the deck-crib to a selected one of the single-card receptacles; a

30 motor arranged to move the dealing rack relative to the deck-crib so as to move a selected one of the single-card receptacles into a position of alignment with the card mover; and a controller arranged to select at random one of the plurality of empty receptacles in the

dealing rack and to cause the motor to move the dealing rack to place the randomly selected receptacle into a position of alignment with the card moving mechanism.

In one embodiment of the shuffler, the controller may be programmed to move the dealing rack to a position presenting all of the cards in the dealing rack where they can be removed simultaneously as a shuffled complete deck of playing cards.

In one embodiment of the shuffler, the controller may be programmed to present a hand consisting of one or more cards in a position where they can be removed individually or simultaneously from the dealing rack to be dealt to a player or dealer.

In one embodiment, the shuffler may include a card reader capable of identifying each card as it is moved or about to be moved from the deck-crib to the dealing rack, and the controller may be programmed to record in digital computer memory the location of the particular single-card receptacle in the dealing rack to which each identified card is moved from the deck-crib.

In one embodiment, the shuffler can be used to shuffle two to eight ordinary decks of cards. In one embodiment, the shuffler has a moving deck-crib, used to place cards into randomly selected single-card receptacles in horizontally oriented stationary dealing rack.

The present application also discloses a method of shuffling a large number of cards in incremental, sequentially shuffled small groups of cards that have been played from a large shuffled group of cards.

The foregoing and other features and advantages of the invention will be more readily understood upon consideration of the following detailed description of the invention taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an isometric view of a playing card handling device, or shuffler, which is an embodiment of at least one aspect of the present invention, shown with a deck of cards beginning to be shuffled and as seen from above the left end corner of the rear side of the device.

FIG. 2 is an isometric view of the shuffler shown in FIG. 1, from the upper right end of its front, or player-facing side, and showing a second deck of cards held in a discard bin.

FIG. 3 is an isometric view taken from the upper right front of the shuffler shown in FIGS. 1 and 2, with its cover removed so that some of the operative components of the shuffler are in view.

FIG. 4 is a view of the shuffler shown in FIGS. 1-3, from the upper left rear, with
5 the cover removed and a deck in position in the deck-crib portion of the shuffler.

FIG. 5 is an isometric partially exploded view of the deck-crib and card mover portions of the shuffler shown in FIGS. 1-4, taken from the upper right front.

FIG. 6 is an isometric partially exploded view of portions of the shuffler shown in FIGS. 1-5, including the dealing rack, an associated blocking wall, and a card shield
10 mechanism, taken from the upper right rear, at an enlarged scale.

FIG. 7 is a sectional view of the shuffler shown in FIGS. 1-5 taken on line 7-7 in FIG. 1, with the shuffler about to begin shuffling a deck of cards held in the deck-crib.

FIG. 8 is a sectional view, at an enlarged scale, of portions of the deck-crib and the dealing rack, taken on line 8-8 in FIG. 5.

FIG. 9 is a sectional view at an enlarged scale of the deck-crib and the dealing rack,
15 taken on line 9-9 in FIG. 5.

FIG. 10 is a sectional view of the shuffler shown in FIGS. 1-5, taken along line 7-7 in FIG. 1, with shuffled cards in the dealing rack and the card shield lowered.

FIG. 11 is a section view taken along line 7-7 in FIG. 1, with the dealing rack in
20 position for removal of a shuffled complete deck.

FIG. 12 is a sectional view taken from the right end of the shuffler as shown in FIG. 1, showing positions of some components of the shuffler during a shuffling operation.

FIG. 13 is a simplified diagram of arrangement of electrical components of the shuffler shown in FIG. 1.

FIG. 14 is a flow chart for operating the shuffler to shuffle a deck of cards.
25

FIG. 15 is a flow chart showing operation of the shuffler in presenting shuffled cards.

FIG. 16 is a simplified flow chart of operation of the shuffler in performing optional steps before presenting hands of cards.

FIG. 17 is a flow chart showing operation of the shuffler to perform incremental shuffling of a plurality of cards.
30

FIG. 18 is a simplified flow chart of operation of the shuffler including use of a card reader.

FIG. 19 is an isometric view from the upper left front of a card shuffler for producing a shuffled group of several decks of cards.

FIG. 19A is a partially cut-away isometric view from the upper right front of a card shuffler of a slightly different arrangement.

5 FIG. 20 is an isometric view similar to that of FIG. 19, but showing an access cover open and a card presentation tray, from which a group of shuffled cards is ready to be removed, in an extended position.

FIG. 21 is an isometric view taken in the same direction as FIG. 20, but with the covers removed from the shuffler and with no cards in the card presentation tray.

10 FIG. 22 is a top plan view of the card shuffler shown in FIGS. 19-21, with the covers removed.

FIG. 23 is a front elevational view of the shuffler shown in FIGS. 19-21 with the covers removed.

15 FIG. 24 is a rear elevational view of the shuffler shown in FIGS. 19-21 with the covers removed.

FIG. 25 is a partially cutaway left end elevational view of the shuffler shown in FIGS. 19-21, with the covers removed.

FIG. 25A is a view similar to FIG. 25, showing an alternative embodiment of a portion of the card presentation tray.

20 FIG. 26 is a partially cutaway right end elevational view of the shuffler shown in FIGS. 19-21, with the covers removed.

FIG. 27 is an isometric view from the upper right of the deck-crib and associated motors of the shuffler shown in FIGS. 19-26, with the covers and several portions of the mechanisms omitted for the sake of clarity.

25 FIG. 28 is a side, partial sectional view, with several portions of the mechanisms removed, of the deck-crib and card mover mechanism of FIG. 22, showing a card being moved from the deck-crib into the dealing rack.

FIG. 29 is a top plan view of a detail of the deck-crib shown in FIG. 22, showing a card beginning to be moved into a single-card receptacle.

30 FIG. 30 is a sectional view taken along line 30-30 in FIG. 20, with the covers of the card shuffler omitted for clarity.

FIG. 31 is a detail view taken in the direction of line 31-31 in FIG. 22.

FIG. 32 is a detail view similar to FIG. 31, but showing the card pusher bar in a raised position, ready to push a group of shuffled cards out of the receiving rack with the card presentation tray.

FIG. 33 is a simplified diagram of arrangement of electrical components of the shuffler shown in FIG. 19.

FIG. 34 is a flow chart for operating the shuffler shown in FIG. 21 to shuffle a multi-deck group of playing cards.

FIG. 35 is a simplified flow chart showing use of a card reader in conjunction with the shuffler.

FIG. 36 is an isometric view of the front of a card shuffler including a shuffler pusher mechanism for ensuring a card is transferred to the dealing rack and a card presentation pusher for making cards in the dealing rack available to the dealer.

FIG. 37 is an isometric view from the rear of the card shuffler shown in FIG. 36.

FIG. 38 is a top plan view of the card shuffler shown in FIGS. 36 and 37.

FIG. 39 is a sectional view, taken along line 39–39 in FIG. 38.

FIG. 40 is a sectional detail view taken along line 39–39 in FIG. 38, at an enlarged scale, showing the card mover mechanism in the process of moving a card.

FIG. 41 is a sectional view taken along line 39–39 of FIG. 38 showing the shuffler with the dealing rack raised and the card presentation pusher moved to present a group of cards.

FIG. 42 is a sectional view taken along line 39–39 of FIG. 38, showing a modified version of the shuffler with a belt-driven auxiliary card pusher.

MODE(S) FOR CARRYING OUT THE INVENTION

An embodiment of a card handling device, called a shuffler 10 herein for the sake of convenience, is shown in FIGS. 1-5 as designed to be a single deck shuffler for use in Blackjack, Poker, and “novelty” or non-traditional, games such as Pai Gow Poker, Three Card Poker, Caribbean Stud, and many others. The shuffler 10 can be modified to handle multiple decks of cards for other games and formats, as described below under Multi-Deck Embodiment.

The shuffler 10 has two main components, a deck-crib 12 and a dealing rack assembly 14, that operate together and are associated with a base 16. The deck-crib 12 is the starting position for each deck or group of cards to be shuffled and secures the

unshuffled ones of the cards face down in a stack 13 during the shuffling process. The dealing rack 14 receives all the cards as they are shuffled and holds them until they are presented to be dealt, either as an entire deck or as hands for individual players, or until they are removed to be reshuffled. The dealing rack 14 may, then, also be called a
5 receiving rack. The dealing rack assembly 14 may include a frame 18 with a pair of upstanding opposite end members 20 and 22 interconnected by a horizontal bottom 24. Extending from each end member 20 and 22 toward the other are respective sets of thin partial shelves 26 and 28 defining a set of, for example, 54 or 55 receptacles 30 to receive a deck of 52 shuffled cards 32, as well as, optionally, a cut card and one or two jokers. (The
10 shuffler 10 will be discussed from this point on as if only 52 cards are being shuffled). Both long sides of the dealing rack 14 are open, as may be seen in FIGS. 1-4, leaving a card removal gap 33 shown in FIGS. 4 and 6 between the left shelves 26 and right shelves 28 to facilitate card removal. The middle portions of the backs of shuffled cards 32 may be seen in the gap 33 as the dealing rack 14 moves during the process of shuffling as
15 shown in FIG. 1, and the shuffled cards 32 are in view after the process of shuffling has been completed. The dealing rack 14 is easily accessible from the top of the shuffler 10, through an opening in its cover 44, as may be seen in FIGS. 1 and 2.

The deck-crib 12 and dealing rack 14 are closely aligned alongside each other, separated, for example by a small distance 35 (FIG. 8) preferably in the range of 0.020 to
20 0.090 inch (0.0508 cm to 0.2286 cm), or of about 0.040 inch (0.1016 cm) in one embodiment, although a distance 35 as great as 0.25 inch (0.635 cm) may be generally satisfactory. As shown in FIG. 3, the deck-crib 12 is a stationary component, supported on the base 16 by a pair of parallel upright members 34 and 36 that also act as ends of the deck-crib 12. The deck-crib 12 includes a bottom member 38 defining a pair of
25 openings 40, as shown in FIGS. 5 and 7.

A small shelf 42 may extend outward as a part of the body shell or cover 44 of the shuffler 10, adjacent the bottom 38 of the deck-crib 12, to receive and support a deck or stack 13 of cards placed into the deck-crib 12 through an opening 46 defined by the outer
body or cover 44. The shelf 42 may be located level with the bottom 38 of the deck-crib 12
30 and protects and hides the identity of the lowermost card of the stack 13 during the shuffle, while keeping part of the deck visible at all times through the opening 46, as shown in FIGS. 1 and 7. A finger notch 48 may be provided in the shelf 42 to allow for easy removal of the deck 13 if required.

A card mover mechanism associated with the deck-crib 12 includes a drive shaft 50 carried in suitable bearings mounted adjacent to the uprights 34 and 36, beneath the bottom member 38 of the deck-crib 12, and a pair of drive rollers 52 are mounted on the drive shaft 50 for rotation therewith. As shown in FIGS. 8 and 9, the drive rollers 52 are aligned
5 with the openings 40 in the bottom member 38 so as to protrude slightly, such as about 0.030 inch (0.0762 cm) radially above the top surface of the bottom member 38, and thus have an upper surface 53, a part of the drive roller 52 above the bottom member 38 in position to engage the bottom surface of the bottom or last card of the unshuffled stack 13. This relationship is shown somewhat exaggerated in FIGS. 7-11. The drive rollers 52
10 should have a high-friction surface that may be of a material such as a rubber-like plastic, such as a urethane of 55A durometer hardness, or a suitable silicone rubber.

The rollers 52 are positioned under the long edge of the cards closest to the dealing rack 14, so as to propel the bottom or last card of the unshuffled stack 13 into one of the receptacles 30 of the dealing rack 14.

15 The drive shaft 50 is driven by a motor 54, which may be a two phase stepper motor, and which may be coupled to the card mover drive shaft 50 by a suitable coupling 56. A power supply 57 may be located on the base 16 beneath the deck-crib 12, as may be seen in FIGS. 7, 10, and 11. By incorporating a suitable battery power supply the shuffler 10 may be made in a portable version (not shown). A simplified diagram of
20 the electrical and electronic arrangement of the shuffler 10 is shown in FIG. 13.

An upstanding card stop 58, a vertical partial wall, seen most clearly in FIG. 5, extends upward above the bottom member 38 as an inner wall of the deck-crib 12 and separates the deck-crib 12 from the dealing rack 14. The card stop wall 58 may have a thickness 59 in the range of, for example, 0.08-0.2 inch (0.2032–0.0508 cm), if made of a
25 plastic resin, or less if of metal, and has a lower edge surface or margin 60 that is located at a predetermined distance above the upper surfaces 53 of the drive rollers 52, as shown in FIGS. 8 and 9. The card stop 58 thus defines an upper side of an outfeed or card transfer slot 62 large enough for a single card from the deck 13 to pass through from deck-crib 12 to dealing rack 14, but small enough, that is, with the lower margin 60 located close
30 enough to the upper surfaces 53 of the drive rollers, to prevent more than one card from the deck 13 from passing through the slot 62 at one time. For example, for a deck of ordinary cards each having a thickness of 0.012 inch (0.0304 cm) the effective opening or gap height 64 of the slot 62 should be about 0.018-0.023 inch (0.0457–0.0584 cm) above the

top surfaces 53 of the drive rollers 52, thus allowing a single card to pass through the slot 62, even if it had originally been slightly bent, but preventing two cards from passing through together. A ramp or lip 63 may be provided as shown in broken line at the end of the bottom 38, beneath the margin 60 of the card stop wall 58 to establish a bottom of the slot 62. Each time an empty single-card receptacle 30 is lined up with the bottom card of the unshuffled stack 13, the rollers 52 impart just enough velocity to propel a card from the stack 13 all the way through the slot 62 into the aligned receptacle 30. The rollers 52 may then immediately reverse briefly to hold the next bottom card in place in the stack 13 until the dealing rack 14 is moved and another randomly selected receptacle 30 is lined up with the slot 62.

Alternatively, the drive rollers 52 may not need to propel the bottom card of the unshuffled stack 13 all the way into the receptacle 30, but just far enough to clear the rollers 52 and the stack 13, and then the next bottom card from the stack 13 would be moved a short distance by the rollers 52 to push the uncleared previous card all the way into the receptacle 30. Thus, for this embodiment of the shuffler 10 the complete action of the rollers 52 would start with a forward spin to propel the card, a short reverse to square-up the stack 13, a short spin forward, moving the next card a short distance to push the previous card all the way into the receptacle 30, and a final short reverse, after which the dealing rack 14 can freely move to present the next selected empty receptacle 30 to receive a card.

In order to keep the cards of a deck or stack 13 in the deck-crib 12 flat and close together, a deck follower including two idler rollers 66 applies constant pressure to the top of the stack 13 ensuring that each card remains flat as it is propelled into an empty receptacle 30, even if severely warped. Due to the closeness of the deck-crib 12 to the dealing rack 14, there is not enough room or chance for a card to flex, as it is moving from a forced flat plane and immediately into an empty receptacle 30. The pair of rollers 66 may be supported by suitable bearings carried on an idler arm 68 of an appropriate weight. The idler arm 68 may have a deep groove 70 defined in an upper, outer, margin, and a pivot rod 72 may be received in the groove 70, so that the idler arm 68 is free to pivot and translate about the pivot rod 72. The pivot rod 72 may be mounted parallel with the bottom 38 and the card stop 58, with its ends in corresponding holes defined in the uprights 34 and 36. The uprights 34 and 36 may define respective slots 74, and suitable pins such as screws 76 may extend through the slots 74 into the idler arm 68. The slots 74

- 10 -

thus guide the idler arm 68 downwardly along the card stop wall 58 to keep the rollers 66 in contact with the uppermost card of a stack 13 in the deck-crib 12. The rollers 66 may be located in alignment with the openings 40 and the drive rollers 52 so as to keep the cards of the stack 13 in contact with the drive rollers 52.

5 The dealing rack assembly, shown in FIGS. 1-6 and in section view in FIG. 7, is located adjacent to the deck-crib 12, with the opposite ends 20 and 22 of the frame 18 of the dealing rack 14 aligned with the uprights 34 and 36 of the deck-crib 12, so that a card from the stack 13 may be moved through the slot 62 beneath the card stop 58 into one of the receptacles 30 defined by aligned corresponding ones of the left and right shelves 26
10 and 28.

 The dealing rack 14 is moved up and down by stepper motor technology, within a range defined by a lift tower 80 mounted on the base 16. The lift tower 80 supports a guide rod 82 extending from the base 16 upward to a pillow block 84 mounted at the top of the lift tower 80, as may be seen in FIGS. 6 and 7. A lead screw 86 is supported in suitable
15 bearings mounted in the base 16 and in the pillow block 84 and extends parallel with the guide rod 82 through a carrier lift block 88 including a lead screw nut 90. The carrier lift block 88 is securely fastened to the end member 22 of the dealing rack 14 and is guided along the guide rod 82 by suitable bearings, so that movement of the lead screw 86 in the lead screw nut 90 causes the dealing rack 14 to rise or descend along the guide rod 82. A
20 suitable stepper motor 92 mounted on the base 16 as shown in FIGS. 4, 10, 11, and 12 is connected drivingly with the lead screw 86, as by a suitable endless belt 94 and pulleys 96 in the bottom part of the base 16.

 The dealing rack 14 may include, in the embodiment illustrated, intended for shuffling an ordinary deck of 52 ordinary playing cards and possibly one or two jokers or a
25 cut card, 55 left shelves 26 and 55 right shelves 28, establishing 55 receptacles 30 each capable of receiving and holding a single card. For the sake of clarity, fewer shelves 26 and 28 are shown in the drawings, so that shuffled cards 32 can be shown more clearly in some of the receptacles 30 in the drawings. A protective upper member 98 may extend from each of the ends 20 and 22 toward the opposite end, above the respective shelves 26
30 and 28. Each shelf 26 and 28 extends longitudinally with respect to a card and the bottom 24 of the dealing rack 14, toward the opposite end member 20 or 22 with a length 99 of, for example, about 0.5 inch (1.27 cm) (FIG. 1). This length 99 is enough to ensure that even a warped card can be received and will lie flat in any of the receptacles 30

between shelves. Since each shuffled card 32 is held in a separate receptacle 30, a moist card is less likely to contaminate other cards so that a deck of cards may be used longer before it is replaced. Each shelf 26 and 28 may be constructed with a minimum thickness, in order that the height 100 of the entire dealing rack 14 be kept to a minimum, so that an
5 entire deck of shuffled cards 32 may be removed easily by a dealer. Thus, for example, each shelf 26 or 28 may have a thickness 102 of about 0.018 inch (0.0457 cm), for example, as required for ample strength according to the material of which the dealing rack 14 is constructed.

It is desirable that the dealing rack 14 be constructed of a material which is of low
10 density, in order to minimize the mass which has to be raised and lowered during operation of the shuffler 10. The dealing rack 14 may, for example, be of aluminum such as a 7075-T6 aluminum alloy, machined to form individual card receptacles 30. It will be apparent that other materials could also be used. For example, the bottom 24 may be of aluminum while the ends 22 and 24 and the shelves 26 and 28 may be constructed of a
15 strong plastics resin having a low coefficient of friction and which is resilient enough to withstand pressures encountered as a dealer grasps and removes a deck of shuffled cards 32. For example, a suitable material that can be molded and machined to satisfactory tolerances is a polyoxymethylene resin available from DuPont under the name Delrin®. As another option, the dealing rack 14 may be constructed as an assembly with the
20 shelves 26 and 28 fashioned separately and attached to the frame 18. For example, a laminate of alternating spacers and shelves 26 or 28 may be fitted on alignment posts (not shown) and fastened to the floor 24.

Desirably the separation between successive ones of the shelves 26 or 28 will be about equal to the gap height 64 of the slot 62, in the range of at least 0.014 inch (0.0355
25 cm) to less than 0.024 inch (0.0609 cm), or about 0.018 inch (0.0457 cm), thus greater than the thickness of an individual playing card, and less than twice the thickness of an individual playing card, but no less than the gap height 64 of the slot 62. To facilitate receipt of a card in a receptacle 30, an edge 104 of each shelf nearest to the deck-crib 12 may be rounded or tapered as shown in FIG. 8 to lead a card into the receptacle 30. Based
30 on the above measurements, the total height of the dealing rack 14 may be only about 2 inches (5.08 cm), easily small enough to allow a dealer to remove an entire shuffled single deck of playing cards from the dealing rack 14.

- 12 -

Referring now also to FIGS. 6 and 10, adjacent the dealing rack assembly 14, on an outfeed side of the dealing rack 14, opposite the location of the deck-crib 12, there is a blocking wall 106 mounted on and extending upwardly above the base 16. A movable card shield 108 in the form of a generally flat panel may be slidably disposed in a pair of channels 110 extending vertically along the inner side of the blocking wall 106. The shield 108 can be moved between a lowered position, in which an upper margin of the shield 108 is aligned with the top margin 112 of the blocking wall 106, and a raised position, in which the shield 108 extends upward alongside the entire height of the dealing rack 14 when the dealing rack 14 is in an uppermost position, as shown in FIGS. 1-4. The card shield 108 is located closely alongside the opposite or far side of the dealing rack, spaced away from the deck-crib 12, and serves to prevent a shuffled card 32 from protruding from the far side of the dealing rack 14 as a result of being moved too far by the drive rollers 52.

The card shield 108 is movable between its raised position and its lowered position by being carried along with the dealing rack 14, as when the controller 134, through an electrical signal, causes a suitable latch to be engaged, such as when the plunger of a bistable solenoid 114 shown in FIGS. 6, 10, 11, and 12 is extended into a socket or hole 116 in the shield 108. The shield 108 may be stable in each of those positions, as a pair of magnets 118 in the blocking wall 106 can act on ferromagnetic screws 119 in the shield 108 to hold it in the raised position when the plunger of the solenoid 114 is retracted from the hole 116, and gravity or other magnets (not shown) or other means will keep it in the lowered position. During the process of shuffling a deck 13 of cards or when a completely shuffled deck of cards 32 is in the dealing rack 14, the shield 108 is normally in its raised position as shown in FIGS. 1, 2, 3, and 4, where it hides shuffled cards 32 in the dealing rack from being seen by players during the course of shuffling the cards. When shuffling is finished the dealing rack 14 is raised, the plunger of the solenoid 114 engages the hole 116, and the dealing rack 14 automatically moves the shield 108 to its lowered position alongside the blocking wall 106. The plunger of the solenoid 114 is then retracted from the socket 116 to release the shield. Each time the dealing rack 14 is cleared, and a stack or deck 13 is in the deck-crib 12 and ready to be shuffled, at the beginning of a shuffling operation the dealing rack 14 automatically fetches the shield 108 and raises it to hide the vertical movement of the dealing rack 14 from view during shuffling. Other

- 13 -

mechanisms could also be used to move the card shield 108 at the appropriate times, but should be small and simple to construct and operate.

When the body cover 44 is in place as shown in FIGS. 1 and 2 an opening into a card removal cavity 120 is available above a deck or stack 13 of cards in the deck-crib 12, so that the top card of a stack 13 remaining in the deck-crib 12 might be seen by looking down into the card removal cavity 120. The opening gives the dealer access to the shuffled cards 32, and the card removal cavity may be defined by inwardly sloping sides 122 to guide the dealer's fingers into a position aligned with the exposed edges of the shuffled cards 32 in the gap 33 (see FIGS. 4 and 6). To verify that a complete shuffle has occurred, a dealer or supervisor or some players, depending on their locations relative to the shuffler 10 can see the full dealing rack 14 and the back of the deck-crib 12 and may be able to view the deck-crib 12 from the front through the card removal cavity 120. The body cover 44 also may include a discard rack 126 as a convenient place for holding cards that have been "burned" or played until an appropriate time to place them into the deck-crib 12. Since some games do not involve discards before reshuffling, the discard rack 126 may be a separate detachable piece.

As may be seen best in FIGS. 6, 7, 8, and 9, various sensors are provided in the shuffler 10 to monitor and help control operation of the shuffler 10. A deck sensor 130, which may be located in or beneath an aperture 131 in the bottom member 38 of the deck-crib 12, senses the presence or absence of one or more cards to be shuffled and may be connected to provide a signal to a controller 134, to inform the controller 134 when to commence or cease shuffling. The controller 134 is shown as a circuit board in FIGS. 7 and 12. The deck sensor 130 shown in FIGS. 8 and 9 may, for example, be an SMT reflective sensor with an LED emitter and a Schmitt trigger, such as OSRAM part No. SFH 9240.

A card counting sensor 132, which may be similar to the sensor 130, is aligned with a corresponding opening 133 in the bottom member 38 adjacent the card stop wall 58, where it can sense the presence of a card 32 in the slot 62, (FIGS. 8, 9) and thus can be used to sense whether the slot 62 is open or blocked by a card. It may also provide a signal to the controller 134 which can be used to count each card as it is moved from the deck-crib 12 through the slot 62 into the dealing rack 14.

A third sensor, an empty rack sensor 136, shown best in FIG. 6, may include an emitter 136e and a detector 136d mounted on the blocking wall 106 at opposite sides of the

- 14 -

dealing rack 14, aligned with the location where the bottom receptacle 30 of the dealing rack 14 will be located when the dealing rack 14 is in its uppermost position. A similar sensor, a receptacle status and alignment sensor 138 including a paired emitter 138e and detector 138d may be located beneath the sensor pair 136 and aligned with the height of the
5 outfeed slot 62 of the deck-crib 12, where it can sense and inform the controller 134 whether a receptacle 30 is aligned with the slot 62 and thus provide information to the controller 134 for use in moving the dealing rack 14 to bring a receptacle 30 into alignment. The receptacle position sensor 138 can also detect whether a receptacle 30 is empty or a card is present in a receptacle 30 of the dealing rack 14 aligned with the slot 62
10 at a particular time, in order to signal to the controller 134 whether the dealing rack 14 can be moved. Vertical slots 140, also shown in FIG. 6, may be defined in the ends 20 and 22 of the dealing rack 14 to provide a clear path through the dealing rack 14 between the emitters and detectors of the sensors 136 and 138.

The empty rack sensor 136 is used after a shuffle is completed to sense and provide
15 a signal to the controller 134 that a hand of cards has been removed from the dealing rack 14, or that an entire shuffled deck of cards 32 has been removed from the dealing rack 14 following shuffling. Since the shuffled cards in the dealing rack 14 are close together, when several cards are presented above the top margin 112 of the blocking wall 106, the bottom card, held in the receptacle 30 aligned with the empty rack
20 sensor 136, can be reasonably easily removed by the dealer only by removing all the cards above it. Absence of the card 32 from the bottom exposed receptacle 30, as detected by the empty rack sensor 136, thus indicates removal of all the cards that had been presented.

The controller 134 can be programmed so the dealer can control all pre-game settings, live game functions, and special features and security functions of the shuffler 10
25 by the use of a single switch, for example a pushbutton switch that may be called a dealer manager or “DM” button 144 (see FIGS. 1 and 2), and that is connected electrically with the controller 134. The DM button 144 may incorporate signal lights to indicate status of the shuffler 10 during operation. For example, the DM button 144 may include signal lights in the form of LEDs 146, 148 and 150 to display green, red, and yellow lights,
30 respectively, each indicating a different status of the shuffler 10. For example, a green light 146 may be used to indicate that the shuffler 10 is in a normal operating mode. A red light 148 may indicate that the shuffler 10 is in a “problem” or “security” mode of operation and that the dealer must press the DM button 144 to cause the shuffler 10 to

revert to the normal operating mode. A yellow signal light 150, if included, may be used to indicate that the shuffler 10 is in a waiting mode, waiting for the dealer to press the DM button 144 to place the shuffler 10 back into a normal operating mode.

5 The controller 134 of the shuffler 10 may be programmed to operate the shuffler 10 in a selected one of various shuffling modes, including two-deck batch mode, traditional one-deck mode, one deck incremental mode, and continuously complete single deck mode. Shuffled cards can be presented to the dealer in various modes, including a complete deck removal mode, a programmed single hand removal mode, and a random number hand removal mode.

10 The shuffler 10 must be preset before live play, establishing various parameters of the functions of the shuffler 10 for a game for which it is to be used. In a pre-game settings mode several subsidiary modes can be selected and defined, including the dealing sequence (and defining, for example, up to three additional betting phases that may involve dealing extra cards), shuffling mode, card removal mode, card cutting mode, burn card mode, 15 starting position for the deal mode, and more.

Once preset and powered, the shuffler 10 requires only the “dealer manager button” or DM button 144, for usage in live play. The DM button 144 may be set to use only the green light 146 and the red light 148 for Poker and Blackjack, and may also use the yellow light 150 for novelty games. The DM button 144 is used to direct the sequence of cards 20 dealt according to pre-game settings, and signals to the controller 134 to move the dealing rack accordingly, in accordance with the programming of the controller 134.

As an option five binary dip switches shown schematically in FIG. 3 can provide inputs to preset the controller 134 for all games and dealing sequences, one switch 156 to provide the controller 134 an input regarding the players, and four switches 158, 160, 162, 25 and 164 to provide inputs regarding the dealer, including three additional betting rounds if needed. Utilizing a 5-place binary format (up/down, in/out, etc.) each switch can be set for the numbers zero to 15, to provide ample flexibility in setting the numbers of cards to be dealt, though from one to eight in the first two switches 156 and 158 (players and dealer) and from one to five in the last three switches 160, 162, and 164 (betting rounds) would be 30 likely to be more than sufficient.

The controller 134, as shown in FIGS. 12 and 13, includes a computer such as a suitably programmed digital microcomputer 170 electrically interconnected with the DM button 144, the sensors 130, 132, 136, and 138, the signal lights 146, 148, and 150, and the

- 16 -

switches 156, 158, 160, 162, and 164, (see FIGS. 3 and 13) and programmed to control the motors 54 and 92, and the solenoid 114. To provide a truly random shuffle, and to facilitate approval from appropriate gaming labs, a random number generator (RNG), such as the accepted RNG known as the Mother Of All Random Number Generators may be
5 incorporated in the controller 134 in association with the microcomputer 170.

As an optional feature, the shuffler 10 may also be equipped with a card reader 180 that may be located beneath the bottom member 38 of the deck-crib 12, as shown in FIGS. 7, 10, and 11. Such a card reader could incorporate various technologies, including bar code technology, optical character recognition (OCR), intelligent character recognition
10 (ICR), optical mark recognition (OMR), encoded or marked cards, digital camera technology, and others. A suitable aperture 182, as shown in FIG. 5, or multiple apertures may be provided in the bottom member 38 of the deck-crib 12 to expose a portion of each playing card including the suit and rank indicia or special markings. Each lowermost card in the deck-crib 12 can be scanned by the card reader 180, either before or while it is
15 moved to a receptacle 30. The card reader 180 may be connected electrically with the microcomputer 170 of the controller 134 so as to store in computer memory the identity of each shuffled card 32 and to correlate the card identity with the location of the particular receptacle 30 into which it is moved from the deck-crib 12. Ultimately, the identity of a card dealt to a particular player or the dealer may be determined through use of the
20 microcomputer 170 and using the shuffler 10 to present groups of cards 32 as hands for players, as will be described more fully below.

For some games the dealer will usually use the complete deck removal mode and remove the entire deck of shuffled cards 32 from the dealing rack 14 before beginning play. When the shuffler 10 is set for the complete deck removal mode, upon completion of
25 shuffling, the shield 108 is lowered to rest alongside the blocking wall 106 and the dealing rack 14 is raised to its fully raised position as shown in FIG. 11. The card removal cavity 120 communicates with the gap 33 between the left partial shelves 26 and the right partial shelves 28 of the dealing rack 14 so that the dealer can insert his fingers into the card removal cavity 120 to grasp the edges of all of the shuffled cards 32 in the gap 33 and
30 then slide the entire deck of shuffled cards 32 outward over the top 112 of the blocking wall 106.

Once the entire deck of shuffled cards 32 has been removed from the dealing rack 14 a signal from the empty rack sensor 136 that the lowest receptacle 30 of the dealing

rack 14 is empty is received by the microcomputer 170, which then commences the shuffling procedure if there is another deck 13 of cards in the deck-crib 12.

The open and visible structure of the deck-crib 12 and dealing rack 14, combined with the locations of the deck sensor 130, card counting sensor 132, empty rack sensor 136 and dealing rack alignment sensor 138, make it simple to locate and clear a jam or identify a malfunction. Should a card not be moved completely from the deck-crib 12 to a single-card receptacle 30 the sensor 132 should provide an indication in the form of an electrical signal to the controller 134. Should a controller malfunction result in a receptacle selection error the dealing rack 14 can be raised to its uppermost position to allow all cards to be removed easily, and all cards can always be removed easily from the deck-crib 12.

The shuffling steps are directed by the controller 134 as shown in simplified form in flow diagrams in FIGS. 14 and 15. The controller 134 prepares to begin shuffling by lowering the dealing rack 14 to its lowermost position, there extending the solenoid plunger 114 to engage the socket 116, followed by raising of the card shield 108 to its raised position above the blocking wall 106, and then retracting the solenoid plunger 114 so that the card shield 108 will remain up held by the attraction of the magnets 118 for the screws 119, while the cards in the deck-crib 12 can be shuffled. Referring also to FIGS. 4-11, to shuffle the cards in the deck-crib 12, for the first or lowermost card in the stack 13 the random number generator associated with or incorporated in the controller microcomputer 170 randomly selects one receptacle 30 from the 52 empty receptacles 30 in the dealing rack 14 and causes the stepper motor 92 to run for the required distance as tabulated in the microcomputer to drive the lead screw 86 far enough to move the dealing rack 14 along the guide rod 82 by acting on the lead screw nut 90 engaged with the lead screw 86 and mounted in the lift guide block 88. The dealing rack 14 is moved to place the randomly selected receptacle 30 directly adjacent to slot 62, aligning the receptacle 30 in position to receive the bottom card or last card from the unshuffled stack 13.

The alignment of the dealing rack 14 to the deck-crib 12 may be monitored throughout the shuffle. To align each receptacle 30 precisely the laser sensor 138 may sense the bottom or top of a shelf 26 or 28 and send a signal to the microcomputer 170 as an alignment datum. From that datum, the microcomputer 170 may tell the stepper motor 92 to move up or down a certain number of steps to align the center of the respective receptacle 30 with the slot 62 of the deck-crib 12. Alternatively, there may be one datum related to a particular receptacle 30 and the controller 134 may move the dealing rack 14 up

or down a number of steps times the number of receptacles 30 from the datum to align the dealing rack 14 in a position aligned with the next selected receptacle 30. It may be necessary to make calibration adjustments throughout the shuffle, and such adjustments can be tabulated in the memory of the microcomputer 170. The dealing rack 14 could thus

5 have a home position datum at a certain receptacle 30 and be programmed to go slightly short of alignment for any other receptacle 30 so the sensor 138 would always be blocked by the shelf 26 or 28 when it arrived. The stepper motor 92 would then adjust the position of the dealing rack 14 in incremental steps until the shelf no longer blocks the signal from the sensor emitter 138e. When the sensor detector 138d acquires the signal, it would then

10 tell the controller 134 the receptacle 30 is aligned with the deck-crib 12 and a card can be moved from the stack 13 to the dealing rack 14, and the position tabulation in the microcomputer 170 could be updated.

When the motor 92 has run the ordered distance and the sensor 138 determines that the randomly selected receptacle 30 is aligned with the slot 62 the sensor 138 sends a signal

15 to the controller microcomputer 170. In response to receipt of that signal, the controller microcomputer 170 causes the card mover stepper motor 54 to rotate, driving the feed drive shaft 50 and the drive rollers 52, in contact with the face, or bottom side of the bottom card in the deck-crib 12, far enough to move the bottom card in the deck-crib 12 away from the deck 13, through the slot 62, and into the aligned receptacle 30 of the dealing rack 14. The

20 controller 134 may be programmed optionally to cause the motor 54 to rotate the drive rollers 52 far enough immediately thereafter to move the next subsequent bottom card from the deck 13 a small distance if necessary, pushing the card that has just earlier been removed completely from the deck-crib 12 a small distance to clear it from the slot 62, and then reversing the motor 54 to move the subsequent card back into position at the bottom of

25 the deck 13. The dealing rack 14 is then clear to be moved upward or downward to place another receptacle 30 into a position of alignment with the slot 62 to receive a subsequent card from the deck 13.

As shown in FIGS. 36-41, an auxiliary card pusher 460 may be included in the shuffler to ensure that the bottom card is delivered through the entire distance from the

30 deck-crib into the empty single card receptacle 30 of the dealing rack 14. A card presentation pusher 430 may also be included in the shuffler to push shuffled cards a part of the way out of the dealing rack 14 to make the cards available for the dealer to grasp them easily. The card presentation pusher 430 will push any cards that have been raised by

movement of the dealing rack to a position where those cards are ready to be presented for dealing or as a part of a deck to be cut.

Once the first card is shuffled to the dealing rack 14, only 51 empty receptacles 30 remain, and the microcomputer 170 randomly selects a receptacle 30 for the next card, from the remaining 51 empty receptacles. The microcomputer 170 then again directs the stepper motor 92 to drive the lead screw 86 to move the dealing rack 14 to align the designated receptacle 30 for the second card with the slot 62, and once the receptacle is determined to be aligned with the slot 62 the controller microcomputer 170 again causes the motor 54 to move the bottom card from the deck 13 into the receptacle in the manner described above. This sequence is repeated until each of the 52 cards has been inserted into a respective randomly selected receptacle 30, one card at a time, one card per receptacle. As a security measure to hinder tracking of cards, the controller 134 may be set to cause the dealing rack 14 to be moved to position a receptacle 30 in alignment with the slot 62, as a fake insertion, without moving a card into the receptacle at one or more times during the shuffle.

Once the entire deck 13 has been moved from the deck-crib 12 into the dealing rack 14, a memory component of the microcomputer 170 contains a record of the sequence of placement of cards into the receptacles 30. If the shuffler 10 also includes a card reader 180 the suit and rank of each card can also have been stored in the memory together with the location in the dealing rack 14 to which that card has been moved.

Because the distances through which the dealing rack 14 has to be moved are small, each movement of the dealing rack 14 during shuffling being no greater than about two inches (5.08 cm) and most movements being significantly less, from the location of one receptacle 30 to the location of the next receptacle 30 into which a card is to be placed, the total time to shuffle the 52 cards of a complete deck 13, placing each into a randomly selected receptacle 30, may be about 15 seconds. When the last card of a stack 13 is moved from the deck-crib 12, the deck sensor 130 sends a signal to the controller 134, whose microcomputer 170 then determines based on the signals received from the card counter sensor 132 (see FIGS. 8-9, and 11) whether the deck has apparently been correctly shuffled.

Once all 52 receptacles 30 are filled and the shuffle is complete, in the "complete deck removal mode" the card shield 108 is lowered and the dealing rack 14 is automatically raised upward above the blocking wall 106 so that all 52 receptacles 30 are

accessible from the front and back, as shown in FIG. 11. The dealer can then slide all 52 shuffled cards 32 out of the dealing rack 14 over the top 112 of the blocking wall 106 on the side of the dealing rack 14 opposite from and spaced apart from the deck-crib 12 as a complete deck which can now be presented to the players for the cut (Blackjack) or cut by
5 the dealer (Poker). Play then continues in the traditional format with the dealer dealing from the shuffled deck.

In order to protect the cards from view before shuffling and to protect cards in the dealing rack 14 from view during shuffling, before the deck is placed into the deck-crib 12, the deck may be placed, face down, on a plastic cut card, and the deck and the cut card can
10 be placed in the deck-crib 12 together. The controller 134 can be programmed to always put the cut card into the top receptacle 30 of the dealing rack 14 before moving the playing cards to randomly selected receptacles 30.

As an additional option when the shuffler is in the whole deck removal mode, the controller 134 may be programmed to cut the deck of shuffled cards 32, also shown in
15 FIG. 16. When a shuffle is complete, and when the shuffler 10 presents the shuffled cards 32, the controller 134 will automatically select a randomly selected number of cards to cut from the deck of shuffled cards 32, within an acceptable range, which may be defined and programmed to be in accord with applicable regulations, since cutting too thin or too deep may not be considered a valid cut. The controller 134 would cause the dealing
20 rack 14 to rise to present the randomly selected number of cards above the blocking wall 106 to be removed by the dealer, and the dealer would remove those cards, constituting the upper part of the deck. Immediately after removal of those cards, the controller 134 would raise the dealing rack 14 to its highest position for the removal of the remaining cards, the lower part of the shuffled deck, to be placed atop the upper part of the
25 deck thus emulating the classic cut. Optionally, the cut could instead be initiated by the dealer's signal using the DM button 144 according to a programmed protocol.

Alternatively, in an interactive deck cutting mode, upon completion of the shuffle the controller 134 causes the dealing rack 14 to rise slowly or to rise and fall through a range of positions waiting for a player to call out "cut." At this call the dealer hits the DM
30 button 144 to stop the dealing rack 14, allowing the cards to be cut at this point. The player has thus "cut the cards" without intervention by the random number generator of the controller 134. Verbally calling out "cut" (or the use of player hand signals) is just one way for the players to interact with the shuffler 10 in this regard. As another option, for

example, the player making a cut could utilize a small remote-control unit shaped and sized, for example, like half a billiard ball with a button on the top. Pressing the button would remotely stop the dealing rack 14 as it slowly rises, allowing the shuffled cards 32 to be cut at a point chosen by a player.

5 In whole deck removal in a two-deck batch playing mode, once the shuffling operation is completed and a subsequent deck 13 is placed into the deck-crib 12, the signal of the empty rack sensor 136 to the controller 134 indicating that the shuffled deck has been removed from the dealing rack 14 results in the controller 134 commencing the shuffling procedure for the subsequent deck 13.

10 Blackjack and Poker are usually dealt in “complete deck removal mode.” Once the shuffler 10 is turned on, provided the dealing rack 14 is empty, placing a deck 13 into the deck-crib 12 will automatically prompt a shuffle after a preset time, such as three seconds, has been measured by the controller 134. Since the time to shuffle a deck is so short (10-15 seconds), it is unnecessary stop a shuffle mid-way and manually clear both the
15 deck-crib 12 and dealing rack 14 before resuming play after an interruption.

 Shuffling for the two-deck batch system for play in the complete deck removal mode can continue without any interaction from the dealer, since the deck sensor 130 signals to the controller 134 as each deck 13 is inserted into the deck-crib 12. The deck sensor 130 also senses when the deck-crib 12 is again empty, and the controller 134 in
20 response then causes the dealing rack 14 to lower the card shield 108 and then move to its highest position for deck removal. When the sensor 136 then detects that the dealing rack 14 is empty and ready to receive cards, the controller 134 automatically causes the shuffler 10 to raise the deck shield 108 and begin shuffling. Alternatively, the shuffle can be initiated manually, by the use of the DM switch 144.

25 The controller 134 may be programmed so that, if for any reason the game needs to be stopped, pressing the DM button 144 in a programmed sequence, such as twice within a programmed time such as one second, signals to the controller 134 to light the red LED 148, stop the shuffling routine, and move the dealing rack 14 to its highest position. In this mode, the shuffler 10 will not operate until the DM button 144 is pressed again,
30 signaling to the controller 134 to resume, which makes the controller 134 turn on the green LED 146.

 For Poker and Blackjack, the green light 146 is always on unless the game is stopped, as by pressing the DM button 144 twice, as for security reasons; or if too many

- 22 -

cards are present or cards are missing as detected by the controller 134 in response to card count signals from the sensor 132, and the shuffler 10 stops automatically in response; or when there is a jam or malfunction and the shuffler 10 stops automatically, as in response to excessive current being drawn by one of the motors 54 and 92.

5 A two-deck batch system allows one deck to be shuffled while the other is being dealt and the game is being played. The shuffler 10 may instead be used for traditional single-deck Blackjack and other games where multiple rounds are dealt before reshuffling instead of using the batch system requiring two decks in rotation. For this mode, the controller 134 may also be programmed to shuffle the cards from each round, fewer than a
10 complete deck, incrementally, immediately after a round has been played, commencing the incremental shuffle as soon as the cards from a round are inserted into the deck-crib 12 and a preset timed delay has elapsed, or the dealer has pressed the DM button 144, placing the cards from each round into randomly selected receptacles 30 in the dealing rack 14. This is in contrast to the traditional procedure in any multiple round game where the cards from
15 each round are placed into the discard rack, and after one or more rounds, combined with the remaining unplayed cards and shuffled as a complete deck. Shuffling the cards from each round after it has been played has the effect of shuffling portions of the deck as the game progresses. After all rounds are played from the deck being used, the shuffling process no longer involves all 52 cards but only the remaining undealt cards and the cards
20 from the last round played. The same incremental method of shuffling could be used for shuffling cards as they are played from a multi-deck shoe, to reduce the time needed eventually to complete the shuffling process, and thus make it unnecessary to use a multi-deck batch system. Also, in a multi-deck system, the tail end of the shuffled multi-deck group of cards is usually not played, and that portion of the group of cards
25 could be placed into the shuffler and be shuffled as the first increment even before beginning to deal a round from the front end of the multi-deck group. The same could be done with the cards at the bottom of a single deck after it has been cut.

For example, as illustrated in simplified flow diagram form in FIG. 17, if the first round uses 15 cards, these cards are inserted directly into the deck-crib 12 (instead of the
30 discard rack 126), and after, for example, a programmed delay, or upon a signal initiated by the dealer, using the DM button 144, they are automatically and randomly distributed into the dealing rack 14 (while the second round is dealt). If the second round consists of 11 cards, then 11 more cards are inserted into the deck-crib 12 and randomly distributed to

open receptacles 30 (while the third round is dealt). Assuming that a third and final round is dealt before shuffling, since 26 cards have already been shuffled (15+11), only 26 more cards, including cards from the third round, need be shuffled to complete the entire shuffling process, and make the complete deck available for play.

5 With this approach, the biggest savings in shuffling speed will occur with one player since a complete round may only consist of 5 or 6 cards. If the dealer dealt down to the 40th card before dealing the last round, the shuffler 10 would only have to shuffle 12 remaining cards to complete the shuffle. At a full table where only two rounds are generally dealt before reshuffling, and assuming that 26 cards are used to deal a round, the
10 shuffler 10 would only have to shuffle the 26 cards of the second round to complete the process.

 Using the shuffler 10 for such incremental shuffling in such a one deck system can maintain the dependent nature of Blackjack or other games. If the four aces were played in the first round, they could not be dealt in later rounds before the entire deck has been
15 shuffled.

 The shuffler 10 can be used, in what may be called a continuous shuffling manner, to provide a shuffled complete deck for each round of play, where actual play of the game does not require additional cards to be dealt during play. As soon as a hand has been dealt to each player and to the dealer, the remaining shuffled cards may be placed into the
20 deck-crib 12 and shuffling may be initiated automatically by the controller 134 upon receipt of a signal from the deck-crib sensor 130 and a programmed delay, or by the dealer's pressing of the DM button 144. The cards not dealt for the round being played are already shuffled by the time the round of play is completed and the cards that have just been used in play can then be placed into the deck-crib 12 and shuffled. This completes
25 shuffling of the entire deck, which can then be used for the next round of play, in significantly less time than waiting for an entire deck to be shuffled.

 In one embodiment of the shuffler 10, the DM button 144 may be used for the entire pre-game process of setting the shuffler 10 for a particular novelty game. The controller 134 could be programmed to enter into a pre-game settings mode, in response to
30 a selected pattern and durations of pushing the DM button 144. Other patterns can be used in the pre-game settings mode to set the shuffler 10 for use in play of a card game by entering pre-game settings through the DM button 144 to establish how the shuffler 10 is intended to operate for a particular game. For example, settings for a hand removal mode

- 24 -

may be entered into the controller 134 to cause the shuffler 10 to present serially to the dealer, during play, a desired number of cards for each player, and for the dealer, for a game such as one of many games termed novelty games, in which a certain number of cards are dealt to each player and either the same or a different number of cards may be dealt to the dealer, and in which a prescribed number of additional cards may be dealt at one or more later times.

Once in a pre-game settings mode, in one embodiment of the shuffler 10 a deck 13 could be placed into the deck-crib 12 and shuffled, and the supervisor could then hit the DM button 144 once for each card required in a hand for each of the players; thus in a game where each player is dealt three cards, the DM button 144 would be hit three times. Following a prescribed delay thereafter, such as three seconds, the dealing rack 14 could move and present three cards which may be removed and spread on the table for confirmation, ending phase one. As a second phase, to set the controller 134 for the dealer's hand the same procedure is followed. If there are no additional phases or betting rounds requiring additional cards, the DM button 144 would then be pressed twice and then held down for a predetermined longer time to get out of the pre-game settings mode (the same procedure used to get into the pre-game settings mode). The controller 134 in such an embodiment might be programmed to allow up to five additional phases to be handled as described, for example. Having the dealing rack 14 present the desired number of cards after the number of cards to be presented is set for each hand or following phase gives visual confirmation.

With another alternative embodiment of the controller 134, once the shuffler 10 is in the pre-game settings mode the controller 134 could delay for a time such as three seconds and then blink one light, such as the green LED 146, one time every three seconds thereafter. To set up for a game where the players are each dealt three cards, after the third blink, the supervisor would then hit the DM button 144 twice to establish a setting of "three cards for each of the players." Then, after another delay of three seconds, the programmed controller 134 could cause the green LED 146 to resume blinking. If the dealer is to be dealt five cards, after the fifth blink, the supervisor would hit the DM button 144 twice to establish "five cards for the dealer." If there were no additional betting rounds, the supervisor could then hit the DM button 144 twice to clear "additional betting round number 1," and then twice more to clear "additional betting round number 2," and twice more to clear the "last additional betting round number 3." That is, after the appropriate

number of blinks equal to the number of cards required for a particular stage of the dealing sequences (five total stages), the DM button 144 is hit twice to set a number of cards or clear a stage. After the fifth (final) stage is established or cleared, the shuffler 10 would revert to normal play mode and be ready for play. The foregoing is only one more of
5 several possible ways to input this information, and as another option, the controller 134 could also be programmed to respond to a setting by blinking a certain one of the color LEDs 146, 148, or 150, or rapidly blinking sequences could signify “cleared” or be used for verification.

In an embodiment of the shuffler 10 that includes the five switches 156, 158, 160,
10 162, and 164, mentioned above, they may be used with the shuffler 10 in the pre-game settings mode. The switch 156, then, may be utilized to set the shuffler 10 to deliver a certain number of cards for each player, and the switch 158 may be utilized to set the number of cards to be presented for the dealer. The three additional similar switches 160, 162, and 164 may be set to instruct the controller 134 to deliver additional numbers of
15 cards to the dealer or players in a prescribed sequence according to the rules of a game that is to be played. For example, switch 156 may be set to make available a hand of three cards to each player. Switch 158 may also be set to provide three cards to the dealer. In a game where no additional cards are to be dealt, switches 160, 162, and 164 may then all be set to zero. For a different game, for example, Texas Hold'em Bonus, switch 156 may be
20 set to provide two cards to each player and switch 158 to provide two cards to the dealer, followed by switches 160 set to provide three community cards to be placed on the table as the “flop” and switches 162 and 164 each set to provide one more card when prompted by use of the DM button 144, a single card for the “turn” when prompted and another single card for the “river” when prompted a second time. The controller 134 may be programmed
25 so that after the “river” card is dealt, completing the deal for a round, the controller 134 would cause the dealing rack 14 to rise automatically to its highest position, allowing the remaining cards to be reshuffled.

Novelty games may be dealt by the shuffler 10 in a “hand removal mode,” in which the cards can be removed one “hand” at a time. This mode may be established for the
30 shuffler 10 as described above by the pre-game settings of the switches 156-164, or by the use of the DM button 144. In the case of the shuffler 10 being set to the hand removal mode, for a novelty card game, numbers of cards preset into the controller 134 can be dealt to individual players and to the dealer as hands. Once the deck 13 has been completely

- 26 -

transferred from the deck-crib 12 to randomly selected receptacles 30 in the dealing rack 14, the shield 108 is placed in its lowered position, in which an upper edge of the shield 108 may be aligned alongside the top margin 112 of the blocking wall 106, and the dealing rack 14 is initially kept in its lowermost position alongside the blocking wall 106.

5 The controller 134 may be programmed so that at that time a different one of the lights associated with the DM button 144, for example, the yellow LED 150, is illuminated. In that case, once the dealer presses the DM button 144 the yellow LED 150 is extinguished, the green LED 146 is lighted. The controller 134 then causes the stepper motor 92 to drive the lead screw 86, and the dealing rack 14 is raised to a position exposing a number of

10 receptacles 30 containing the number of cards that a player is to be dealt. (Alternatively, and ordinarily, the controller 134 would be programmed to raise the dealing rack 14 as soon as a programmed delay time has elapsed after the shuffling operation has been carried out.) The dealer can then remove those cards from the dealing rack 14 by sliding them out across the top margin 112 of the wall 106 and would place them on the table before the first

15 player. Once the first player's cards have been removed from the dealing rack 14 the empty rack sensor 136 can sense that the lowest receptacle 30 above the top 112 of the wall 106 is empty. The sensor 136 then sends a signal to the controller 134, which raises the dealing rack 14 so as to present the receptacles 30 containing the selected number of cards for the next player's hand, ready to be removed. Alternatively, the dealer could press

20 the DM button 144 to signal to the controller that it is appropriate to raise the dealing rack 14 to present the receptacles 30 containing the selected number of cards for the next player's hand. As yet other alternatives, an additional sensor (not shown) could be located in the card removal cavity 120 to detect the dealer's hand as it removes cards from the dealing rack 14, or a sensor could be located where it can detect the passage of cards out

25 from the dealing rack and send an electrical signal to the controller to initiate raising the dealing rack 14.

The microcomputer 170 may be programmed in one embodiment so that for every round dealt, the dealer must press the DM button 144 before dealing to the last player. This action signals the shuffler 10 to present one last player hand followed finally by the

30 dealer's hand. After the dealer's hand is removed, the controller 134 moves the dealing rack 14 to its uppermost position so that the remaining unplayed shuffled cards 32 can be removed and placed into the discard rack 126 or deck-crib 12.

- 27 -

After each hand is removed from the dealing rack 14 by the dealer, the sensor 136 signals the controller 134 to cause the dealing rack 14 to rise again, presenting another complete player hand to be dealt. Once all hands have been dealt (including the dealer's), following a programmed delay, or upon the dealer pressing the DM button 144, the dealing
5 rack 14 is automatically raised to its uppermost position, as shown in FIG. 11, allowing all remaining cards to be removed and be placed in the discard rack 126 or deck-crib 12. Immediately after the dealing rack 14 is cleared of all remaining unplayed cards and while players are making decisions about their hands, if the shuffler 10 is operating in the two-deck batch mode, the next shuffle begins.

10 In this hand removal mode of operation the controller 134 may provide a visual signal change during the dealing procedure. That is, upon completion of the shuffle, the green light 146 goes dark and the yellow light 150 is lighted by the controller 134 the instant the dealing rack presents the first player's hand. The yellow light serves as a reminder to the dealer to press the DM button 144 once before dealing to the last player.
15 Once the DM button 144 is pressed, the green light 146 turns on, showing that the shuffler 10 has returned to the normal operating mode. The shuffler 10 then presents the last player hand, and when the empty rack sensor 136 detects that hand has been removed or upon a prompt from pushing the DM button 144, the controller 134 raises the dealing rack 14 to present the dealer's hand.

20 Previously known shufflers are capable of dealing hands where the dealing sequence is definite and predictable and thus easy to program in advance. For playing certain games, however, the shuffler 10 may be set to present cards in a "dynamic game" mode. For example, some games (such as Baccarat) may not require that the players or dealer be dealt individual hands. The shuffler 10 can be programmed to present rounds of
25 one or more cards to be dealt to the center of the table where the players wager on various outcomes, and the shuffler 10 can continue to deal these rounds unaffected by timed delays until a particular result ends the hand, or until the dealer presses the DM button 144 to manually end the hand, or until the shuffler 10 reaches a predetermined point in the deck of shuffled cards 32 and automatically moves the dealing rack 14 to its highest position to end
30 the hand. As another example, for stages of play following a first deal of a predetermined number of cards to the players and dealer, the controller 134 may be set to present three cards--to be used by all players--for an additional betting round and then continue presenting three cards for subsequent betting rounds until a series of rounds is terminated

by one of the methods described. Such a round may even consist of a random number of cards as selected by the controller 134, or there may be multiple drawing phases for each player. Other formats are possible. Also, with a card reader 180 included in the shuffler 10, a particular card combination or some other game-rule-identified event can be used as a trigger to signal to the controller 134 to end the hand and automatically raise the dealing rack 14 so that the remaining cards can be reshuffled. Thus, dynamic-game capabilities can be set during the pregame settings, and the shuffler 10 can handle games with more than five stages, and games in which the outcome path or number of cards needed to complete a hand, phase, or round cannot be predicted or programmed in advance.

10 As another example, Blackjack is a game normally dealt from the hand even if the cards have been shuffled by machine. Blackjack has a dynamic game format because it is impossible to predict how players will play their hands, e.g. hit, stand, double, and split, or to predict how many cards will be required to complete each player's turn. Assuming that the shuffler 10 presents two cards at a time for each player as the initial deal, the controller 134 would be set to present one card at a time for a first additional betting round and would be locked into the dynamic format procedure. Thus after the players and dealer are each dealt two cards, the shuffler would thereafter present one card at a time and continue to present one card at a time until the process is terminated.

20 With the microcomputer 170 of the controller 134 programmed in a slightly different manner, in any novelty game where the players and dealer receive the same number of cards, the dealer need not press the DM button 144 at any time during or after the deal. If the shuffler 10 is preset to deal three-card hands, for example, the dealing rack 14 would rise to present three cards for each player, and three cards for the dealer, simply presenting three cards each time the empty rack sensor 136 detects that the lowest receptacle 30 above the top margin 112 of the blocking wall 106 is empty. After the dealer's hand is removed, the dealing rack 14 will again rise to present three cards, but these cards will never be dealt. If those cards are not removed from the dealing rack 14 as sensed by the empty rack sensor 136 during a programmed delay time, such as 3-5 seconds, the dealing rack 14 will automatically rise the rest of the way to its highest point for the removal of all remaining shuffled cards 32. That is, elapse of the programmed delay time immediately following the removal of the dealer's hand, or the dealer's pressing of the DM button 144, signals the controller 134 to automatically raise the dealing rack 14 to its highest position.

In one embodiment of the shuffler 10 the controller 134 may also be programmed for the hand removal mode so that in any game where the pre-game settings of the shuffler 10 are that the players and dealer are dealt different numbers of cards, the DM button 144 needs to be pressed before the dealer's hand is removed. For example, in a game where the players are each dealt three cards and the dealer is dealt five cards, the dealing rack 14 would present three cards for each player, and three cards for the dealer, but before removing these cards the dealer would hit the DM button 144, thus signaling the dealing rack 14 to present two additional cards, according to the pre-game setting, allowing the dealer to remove a complete hand of five cards. With the pre-game settings made for a game requiring that the dealer be dealt fewer cards than the players, the dealing rack 14 would lower accordingly after the dealer hits the DM button 144. As a further option for security, the controller may present an additional card for the dealer, and the bottom card can be "burned," or discarded, so that the dealer's actual bottom card will not be "flashed."

The shuffler 10 can allow new interactive games in which combined hands of varying numbers of cards can instantly be provided. For example, a game might have two phases. In the first phase each player is dealt the required number of cards. In the second phase, each player decides whether to forfeit his bet and end the hand, or to increase his bet and draw one to three cards. As each player verbally expresses a decision to draw cards or indicates a decision with hand signals, the dealer accordingly presses the DM button 144 one to three times within a programmed time, and the proper number of cards is presented to be dealt. A remote player console (not shown) linked to the shuffler 10 could also handle this task.

As another game for which the shuffler 10 would be useful, all players and the dealer may be dealt three cards, after which in a draw stage the dealing rack 14 would be raised to present from one to three cards as randomly selected by the controller 134; the shuffler 10 would be set in pre-game setup mode to present three cards to each player and the dealer, and then convert to "random" mode. In the random mode, each time the DM button 144 is pressed, the shuffler 10 randomly presents from one to three cards.

As another example, a game could include dealing each player from one to three cards, as determined randomly by the controller 134. Players would still have a chance to win with just one card--and winning with one card would garner bigger payoff--while being dealt three cards improves their chances. The shuffler 10 could easily be programmed to deal the requested number of cards to each player for such a game.

In another game for which the shuffler 10 could be programmed, the rules would dictate that community cards, to be used by all players as in Hold'em, be presented in a number, such as from one to five cards, randomly selected by the shuffler 10. That is, the shuffler 10 can be programmed and directed by pre-game settings to present cards in
5 random numbers.

In some card games, immediately following the shuffle and cut, one or more cards may be burned (discarded) before starting the deal. The shuffler 10 offers four burn card options: (a) no burn card (default setting); (b) burn one card, the traditional play in Blackjack, assuming the game is dealt by the shuffler 10 in hand removal mode--otherwise
10 it is easier just to manually burn a card; (c) burn one to ten cards in Baccarat: turn the top card face up; if that card is a 3, the dealer presses the DM button 144 three times to increment three cards, which are removed and burned; if the card is a 9, the dealer presses the DM button 144 nine times to burn nine cards; and if the card is a ten-valued card (10, J, Q, K), the DM button 144 must be pressed ten times to burn ten cards; and (d) as a
15 correction function, should a dealer make an error, the dealer could provide a programmed signal through the DM button 144 to have an appropriate number of cards presented to be discarded, at any time during a game. Burning the first cards in Baccarat, without a card reader 180, can be done by pressing the DM button 144 accordingly, say five times, each time within a second; then after a one second delay, the dealing rack 14 would
20 automatically increment five cards. This procedure could be automatic using a card reader 180; the dealing rack 14 would present one card as the burn card indicator that would be removed and turned face up, and then automatically rise to present the number of cards to be burned as indicated (and determined by the controller 134 based on knowing the rank of the top card). The capability to burn cards during live play has many
25 benefits--for example, when the dealer deals past a live player, but the player insists on receiving a hand, or when a supervisor, for any reason, decides to intervene and ask the dealer to burn three cards. A supervisor could put the shuffler 10 in this special burn card mode by using the DM button 144, for example by hitting the DM button 144 three times and holding it down until the red LED 148 is lighted. The dealer would then be instructed
30 to hit the DM button 144 as many times as corresponds to the number of cards that are needed to rectify a situation, which are presented by the dealing rack 14 and dealt to the player. The supervisor would then again hit the DM button 144 three times and hold it down until the green LED 146 turns on, thus restoring the game to normal mode.

The shuffler 10 can be used to randomly designate where the dealing is to begin. If the shuffler 10 has been preset to deal Pai Gow Poker, once the cards have been shuffled, instead of automatically presenting seven cards, the dealing rack 14 presents a randomly selected number of from one to seven cards. These cards are removed by the dealer and spread face down in front of all to be counted. If one card is presented, the starting position for the deal is position number "1" (dealer). If two cards are presented to be spread, the starting position for the deal is position number "2" (generally the player to the dealer's immediate right). The number of cards randomly incremented (one to seven) determines the position to receive the first dealt hand. Instead of discarding these cards, they are used as part of the first dealt seven-card hand. Thus, the controller 134 of the shuffler 10 is programmed so that if one card is initially selected, the moment this card is removed from the dealing rack 14, the dealing rack 14 rises and presents six more cards to complete the first hand (seven cards) to be dealt. If two cards are initially presented, the moment these cards are removed from the dealing rack 14, the dealing rack 14 is raised to present five more cards to complete the first hand, and so forth. In the case of seven cards being initially presented, no additional cards are required for the first hand. So, from one to seven cards are initially presented to determine the player position to receive the first hand dealt, and then the number of cards needed to complete a seven-card hand are presented--if necessary--to complete dealing the hand. Once the complete first hand is removed from it, the dealing rack 14 automatically presents seven cards for each of the other hands until a predetermined delay time passes without the next hand being removed, or until the dealer hits the DM button 144 (after the last hand). Although the dealing rack 14 would have automatically presented another hand of seven cards, they will not be utilized, and the dealing rack 14 will then be raised to its highest point to present all the remaining cards for removal, to be shuffled for the next round of play.

The controller 134 may also be programmed to automatically require a deck to be reshuffled, so that in playing a single-deck game, such as Blackjack, where more than a single round may be played before reshuffling, once a predetermined number of cards have been dealt from the shuffled cards 32, when the DM button 144 is hit to signal to the controller 134 that a round is complete, the dealing rack 14 automatically rises to its highest position so that the remaining cards 32 can be removed from the dealing rack 14 to be placed into the deck-crib 12. This automatic prompt of a reshuffle can reassure players that the dealer is not choosing an advantageous time to reshuffle.

ADDITIONAL FEATURES AND OPERATION

The shuffler 10 can also be built with a dealing rack (not shown) that has movable sides. Once the shuffle is completed and dealing rack is filled and raised to its uppermost position, the sides 20, 22 may be moved apart by a motor such as a solenoid controlled by the controller 134, allowing the shuffled cards 32 to coalesce into a traditional stack ready for complete deck removal, as for dealing Blackjack and Poker. Alternatively, the stack may be raised to a required height to present only a desired number of cards that can be removed and dealt while other cards are retained in the stack.

The shuffler 10 can also be made for use in multi-deck games, such as to shuffle two to eight decks. Converting the shuffler 10 to a two-deck shuffler would require a simple modification to a taller configuration. Converting the shuffler to handle four to eight decks, however, may require that the shuffler be mounted to the side of the table to keep a low profile--hiding most of the vertical movement of the dealing rack.

Alternatively, the shuffler may be reoriented by essentially turning it on its side, to have the dealing rack 14 move horizontally, with cards standing on their sides in the deck-crib 12. Cards would then be available at a side, rather than the top, of the reoriented shuffler.

As one alternative, the deck-crib 12 and dealing rack 14 may both be rotated by ninety degrees and aligned to handle the cards in a "short end to short end" configuration thus elongating and reducing the width of the shuffler 10, although this arrangement would require each card to be moved further to clear the deck-crib 12 and occupy a receptacle 30.

The shuffler 10 can be built in a somewhat smaller version still fully capable for use for Poker. Since individual hands are not dealt from the shuffler 10 for Poker and there is no reason to facilitate the single hand removal dealing action, the motors 54 and 92 and the DM button 144 could be on the same side without making use of the shuffler 10 inconvenient for the dealer. There would be no need for the card shield 108 to be lowered for player hand presentation, and saloon-style spring-loaded swinging doors or a similar door design would therefore suffice. The DM button 144 would rarely be used and would need to show only two colors. No discard rack 126 and no internal pre-game settings switches 156, 158, 160, 162, and 164 are needed. Only 52 receptacles 30 are needed in the dealing rack 14. In short, a poker model could be stripped down to the barest minimum without giving up anything; a poker shuffler only needs to shuffle and allow for easy loading and unloading.

For such a Poker-only version of the shuffler 10, given its smaller size, a possible installation option is for the shuffler 10 to be built directly into the poker chip-tray. Since bins or holders traditionally built into poker chip-trays for two decks of cards would not be needed, the shuffler 10 could be installed in their usual place in a custom made chip-tray.

- 5 The shuffler 10 could be recessed into such a chip-tray far enough that the card opening 46 of the deck-crib 12 is level with the chip-tray, directly facing the dealer's belly, conveniently available to the dealer.

- 10 Rake-slides are standard pieces of equipment found on poker tables, used to allow chips to drop into under-table drop boxes. For a casino-style Poker table, another possible installation option is to mount the shuffler 10 on a special base or add-on base (not shown) that straddles the rake-slide. This base would support the shuffler 10 above the rake-slide in an arrangement that would not interfere with the normal operation of the rake-slide.

- 15 For another embodiment, the shuffler 10 could also include a cover (not shown) movable over the open top and card removal cavity 120 and the open front of the body 44, to protect the front and top, perhaps contoured around the DM button 144 and arranged to slide away from the dealer automatically to extend past the machine and make the shuffled cards 52 available, after a shuffling process is complete.

- 20 In one embodiment, the shuffler 10 could be mounted in a recess or cavity defined in a gaming table. With the base 16 of the shuffler 10 sitting below table level, the blocking wall 106 and the opening 46 to the deck-crib 12 would be exposed just slightly higher than table level. This would allow the cards both to be inserted into the deck-crib 12 and removed from the dealing rack 14 practically at tabletop level--a desirable security goal that prevents flashing.

- 25 As an alternative to the rollers 52, a card feed belt may be used to push the bottom card of the stack 13 using an elongated "caterpillar tread" endless card feed belt with nibs that protrude by less than the thickness of a card and thus can push only one card, or that can contact the face of the lowermost card with this same tread design and one or more contact point(s) of some kind. Drive wheels for the belt may be driven by the stepper motor 54 to control the card feed belt.

- 30 The shuffler 10 may utilize video projection devices coupled with input devices for programming. For example, a standard touchpad 176 or trackpad utilizing a tactile sensor could be included in the body 44 of the shuffler 10 and a small aperture would allow the projection of the output on to a clipboard, screen, piece of paper, or other suitable device,

allowing the pre-game settings, diagnostics, hand histories, and other tasks to be managed and viewed.

If the shuffler 10 is equipped with a card reader 180, several additional functions are possible. If a player is dealt a jackpot hand, the shuffler 10, if equipped with a card
5 reader 180, can be programmed to redeal the cards that it had presented for the player claiming to have a jackpot hand, from the “second deck” of the batch game, or from an additional, separate deck, for a visual confirmation of the initial dealing sequence leading to a jackpot.

In an embodiment of the shuffler 10 equipped with the card reader 180, the
10 post-shuffle position of every card 32 can be recovered from the memory of the controller microcomputer 170, as shown in simplified flow diagram form in FIG. 18. During shuffling, each card is identified as it is moved to a respective randomly selected receptacle 30 in the dealing rack 14, and the location, or identity, of the receptacle is associated with the identity of the card in the memory component of the
15 microcomputer 170 in the controller 134. This means that not only can the shuffler 10 identify individual cards for deck verification, but it can also be programmed to evaluate the deck’s card order after the shuffle, and to retain “hand histories” for time periods as required by governmental regulation authorities. Thus, in a game where each player is dealt five cards (standard poker rankings), software of the controller 134 could be designed
20 to consider the suit and rank of each of the five cards in the top five receptacles 30 of the dealing rack 14 after the shuffle, the next group of five cards, the next group of five cards, etc. Should a player hit a jackpot, to verify that everything is legitimate, the supervisor could ask the dealer to hit the DM button 144 in a prescribed pattern, such as three times. The controller 134 can be programmed so that if the green light 146 starts rapidly blinking
25 it means that a jackpot hand was “present” in the last shuffled order. The controller 134 could also be programmed to have the green light 147 blink slowly to show the number of players needed for the cards dealt to include a jackpot hand. If the red light 148 starts rapidly blinking, there is a problem, as the shuffler 10 is indicating that there was no jackpot hand in the last shuffled order.

30 In the game of Blackjack, the players and dealers are dealt two cards with one of the dealer’s cards dealt face up (upcard) while the other remains face down (holecard). To prevent or detect cheating, devices are utilized to determine the value of the holecard when Blackjack is possible, that is, any time the upcard is an Ace or a card with a value of 10.

When the shuffler 10 is equipped with a card reader 180 the controller 134 can be set up to memorize the location of each card as it is placed into dealing rack 14, and the shuffler 10 can eliminate the need for the separate peeking devices currently in use. Using the “no-peek” capabilities of the shuffler 10 requires that the card reader 180 be capable of determining the rank of the cards and requires the shuffler 10 pre-game settings to provide for hand removal mode and dealing the cards to the players and the dealer from the dealing rack 14, presenting two cards together for each player and the dealer.

Traditionally, the first card dealt to the dealer by hand is the “upcard,” but a safer procedure for using the shuffler 10 is to reverse the roles of the dealer’s cards and have the upcard be the lower one of the two cards removed from the dealing rack 14. Since it will be turned face up anyway, exposing the bottom card of a pair being removed from the dealing rack 14 is irrelevant, and the bottom card hides the identity of the top card.

Each round of Blackjack play consists of two phases. The first phase consists of dealing two cards to each player and the dealer, and the dealer turning the lowermost card face up. The second phase is the decisional phase where players can hit, double, and split; this phase ends with the dealer drawing to his or her hand if required by the house rules.

After two cards have been presented by the shuffler 10 and dealt to all players and the dealer, the dealing rack 14 will automatically and instantly rise to present two additional cards, as it does not know how many players are present. With the controller 134 appropriately programmed, a two-second delay during the deal without the removal of these two next cards will signal the controller 134 that the initial phase is over (players and dealer have all been dealt two cards).

At the end of the initial phase, signaled by the above-mentioned two-second delay after the dealing rack 14 has presented two additional cards, the dealing rack 14 will then automatically prepare for the next phase, by moving down by one single-card receptacle 30, leaving only a single card available to the dealer for the decisional phase where the cards are dealt one at a time, if the dealer’s upcard face value is anything from 2 to 9.

When the dealer’s upcard is a ten-valued card (10, Jack, Queen, or King) the dealer is required to “peek,” that is, to determine immediately whether the dealer has blackjack; when the dealer’s upcard is an ace, the dealer is required to first offer insurance to the players before peeking for a blackjack.

- 36 -

Since the controller 134 has available in the memory of the microcomputer 170 the post-shuffle card order and how much the dealing rack has moved since the shuffle, it knows how many hands have been dealt. If the dealing rack 14 rose five times, the controller 134 knows that there are three players, the dealer, and one additional rejected
5 presentation of two cards. Consider the following post-shuffle sequence: 2-5, 7-A, 4-J, 6-K
...

Once the shuffler 10 determines the number of players in the game, it looks at the sequence and sees that the dealer has a K (king) in the upcard position and a 6 in the hole. Since the dealer does not have blackjack, play continues normally following the
10 two-second delay, and the controller 134 may provide a signal to all, such as the DM button green light 146 blinking three times for "GO" to signal this status.

Now consider the following sequence: 2-5, 7-A, 4-J, A-K . . .

This time the dealer has blackjack (King upcard and Ace in the hole) so play must stop; the hand is over and the dealer must turn over the holecard to reveal the blackjack. In
15 this case, once the microcomputer considers the dealer's hand the controller 134 provides a signal such as the DM button light 148 blinking red three times for "STOP."

In all rounds where the dealer's upcard is an Ace, insurance must be offered to the players, a process that can take several seconds. The controller 134 should be programmed so that when the dealer's upcard is an Ace, after all players have made their decisions
20 regarding insurance, the dealer must hit the DM button 144 to ask the controller 134 for the dealer's status--specifically, is the holecard a ten-valued card? Only when the dealer has an upcard Ace would the shuffler 10 need to be prompted, as all other blackjack combinations (ten-valued upcard) are handled automatically and without interaction from the dealer.

25 As the players hit, double, and split, one card is dealt per player decision. After the last player has acted, the dealer's hand is revealed and additional cards are drawn to the dealer if required by the rules. The controller 134 may be programmed so that the end of the round can be signaled to the controller 134 by the dealer hitting the DM button 144 as the played cards are scooped and placed in the discard rack 126 or deck-crib 12. As this
30 occurs, the dealing rack 14 would already have a single card presented, but hitting the DM button 144 signals the controller to cause the dealing rack 14 to rise to also present another card so that two cards are ready for removal to begin the next round.

The shuffler 10 can also be used to sort a deck to facilitate confirming that it is

- 37 -

complete, by placing the shuffler 10 into the required mode and placing a randomly ordered deck into the deck-crib 12. The card reader 180 identifies the bottom card and always places it in the top receptacle 30, barely requiring the dealing rack 14 to move as it begins to shuffle or sort already in the lowermost, home position. For example, assume the
5 bottom card is the six of diamonds. Then assume the next card happens to be the ten of clubs; it is placed in the 5th receptacle 30, leaving the 2nd, 3rd and 4th receptacles 30 open for the other sixes. The next card up is the ace of spades. It is placed in the 9th position, leaving the 6th, 7th, and 8th receptacles 30 for the other tens. If the next card up is one of the remaining sixes, it goes to the 2nd receptacle 30, and if the next card is one of the
10 remaining tens, it goes to the 6th receptacle 30, and so on. When the process is complete, the deck will have been sorted into groups of equal ranks, but in no particular order or sequence of ranks. When sorted and grouped by rank, and in no particular order of ranks, it is just as easy to verify a complete deck as when sorted into a new deck sequence. Cards can be sorted into any other desired, more or less specific, sequence as well. For example,
15 the cards could be sorted to a “new deck” order, or sorted into groups according to rank, as all aces, all kings, etc., through all deuces, but without considering suit order in each rank.

As a security tool to detect wagering opportunities for card counters, the shuffler 10 can use the location of each of the shuffled cards 32, identified by the card reader 180 and with identity and post-shuffle location stored in digital memory by the microcomputer 170,
20 to evaluate the entire post-shuffle order before the first card is dealt. As a security assurance feature, the shuffler 10 can evaluate the entire shuffled deck by utilizing the card location information in the digital memory of the microcomputer 170 to inform the pit or house surveillance personnel of impending “rich decks” (*i.e.*, containing more tens and aces than usual and therefore providing mathematical advantages to card counters) long
25 before they occur, giving house management a chance to direct their attention accordingly, before play with the rich deck happens instead of having to wait until it happens. This can make a significant difference, as every card room supervisor is responsible for watching multiple games, every surveillance operator is responsible for watching multiple monitors, and such advance notice can help with time management.

30 Knowledge of the entire post-shuffle card order can also be used for new games on which players can gamble. For example, a single-deck game could have the players bet on the number of aces that will appear in the first 20 cards. The controller 134 could be programmed so that after the shuffle, if all four aces happen to fall in the first 20 cards, the

- 38 -

DM button 144 would flash four times, alerting players to this fact. If only three aces happen to be in the first 20 cards, the DM button 144 could flash three times, and so on. Depending on the number (from zero to four) of aces randomly shuffled into the top 20 cards, the game could have five different paths, based on knowledge of the shuffled order, and each path could offer a different wagering opportunity. This is an example of a game that depends on knowledge of the post-shuffle card order, and is thus an example of a game that could be dealt by the shuffler 10 including a card reader 180.

Computer-related image recognition technology such as the Tangam System is used in casino surveillance systems to identify the cards as they are dealt, number of active players in a hand, player ID cards, markers, etc. This technology, including cameras in surveillance or some other viewing structure, connected to the shuffler 10 via a standard wireless or hard-wired link, could be used to control certain aspects of the shuffler, resulting in a remote control shuffling platform/format. For example, in a game where the dealer and players receive different numbers of cards, the controller 134 would be signaled in advance how many players are to be dealt hands, and could automatically adjust the dealing-rack--without dealer intervention--to present the correct number of cards to the dealer at the appropriate time. Other advantages are possible. Utilizing such a system to control the shuffler 10 would eliminate the need for any input from the dealer. Systems such as Tangam use camera imaging and video recording to reconstruct everything that happens on a game.

The shuffler 10, equipped with a card reader 180, could handle all televised poker games, or other games, and the resulting combined system would be capable of handling any number of players, any rules, or any procedural oddities, while achieving the same audience viewpoint without a special camera-table. A single camera or the card reader 180 built into the shuffler 10 could replace two to eleven cameras used currently for televising players' hands, and televised Poker and other games where players hands are normally hidden from each other could be played on any table and broadcast accordingly.

The shuffler 10, in one embodiment, could include a simple digital signal hookup from the controller 134 to a properly programmed computer in a control station. This could not only provide a more contemporaneous, efficient way to observe and record the proceedings during these games, it could provide perspective never seen before, as the shuffler 10 would be able to display all possible results, including hands that are not played out. For example, a player discarding his hand before the last card is dealt will often ask

the dealer to turn over the last card just to see what would have happened. Though this custom is generally frowned upon, the shuffler 10 could handle such a request with ease and without actually exposing the card, simply by referring to the order of shuffled cards 32 stored in memory in the controller 134.

5 Pai Gow Poker is a popular Asian game played in most casinos. The players and the dealer are each dealt seven cards. Players arrange their cards into two poker hands: a five-card hand and a two-card hand. The most important rule governing play is that the five-card hand must always be the higher ranking hand (traditional poker rankings apply). After the players set their hands, the dealer flips his cards face up and sets the hand
10 according to house rules. If both of a player's hands win, the player wins; if both of a player's hands lose, the player loses; and winning one hand while losing the other results in a tie (called a "copy"). Should the player's hand and the dealer's hand rank equally, the house wins.

 In Pai Gow Poker, the dealer's hand of seven cards is dealt and ordinarily arranged
15 by the dealer according to house rules after being turned face up. This can take several steps depending on the complexity of the hand. For example, consider a very simple hand A-A-K-9-8-5-4 and a corresponding house rule. House rules may dictate that for any hand with one pair, the pair must be played in the five-card hand (referred to as the "high hand" or "back hand"), and the two highest non-pair cards must be placed in the two-card hand
20 (referred to as the "low hand" or "front hand"). According to these house rules, this hand would be arranged: A-A-8-5-4 K-9.

 In a less simple hand with two pairs and a spade flush: As, Js, Jd, Ts, Th, 6s, 3s, the house rule is always play a flush in back (the five card hand) unless you have two pairs and both are tens or higher, then play two pairs (one pair in the front hand and one pair in the
25 back hand). According to house rules, the spade flush is not played and the hand would be arranged: Js-Jd-As-6s-3s Ts-Th. The casinos want to bring the strength of the two hands as close together as possible as this produces higher average front and back hands, and has been shown to be most profitable, since to win a round both parts of the hand must win. Playing the flush in the back hand leaves Jd-Th for the front hand, a very weak,
30 overall losing front hand.

 The microcomputer 170 of the shuffler 10 equipped with the card reader 180 can be programmed to arrange the dealer's hand according to the house rules. Where the dealer has little experience dealing Pai Gow Poker, this could be very helpful. The arrangement

of the dealer's hand according to house rules may be presented by the properly programmed shuffler 10 by keying on the two cards that will be played as the front hand, and having the dealing rack 14 present the hand in steps, if necessary, of from one to three raises of the dealing rack 14, then removing and stacking the cards into the proper arrangement. For example, with the dealer's hand consisting of seven shuffled cards 32 lying in the top seven occupied receptacles 30 in the dealing rack 14, the shuffler 10, because of the card reader 180, knows the order of the cards and knows how the dealer's hand should be arranged according to the house rules. In the simplest case, if the two "front" hand cards are presented in the first and last positions (cards number 1 and number 7 from the top of the dealing rack 14), the dealer's entire seven-card hand can be removed in a single group, resulting in the desired order F-X-X-X-X-X-F ("F" refers to cards in the front hand).

If the two front cards randomly fall together, but lie in any other position, the dealer's hand can be dealt in two steps by simply raising the dealing rack 14 in the first step to present enough cards to include, as the bottom card presented in the dealing rack 14, the uppermost front hand card of the dealer's seven-card hand. That group of one to six cards is removed from the dealing rack 14 and dropped face down on the table. The dealing rack 14 is then raised to present the remaining one to six cards needed to complete the dealer's seven-card hand. These cards are removed and dropped on top of those cards previously removed, still face down, so that the second front hand card will be at the top of the dealer's seven-card hand as it will be stacked on the table face down. For the dealer's hand X-X-F-F-X-X-X, as in the top seven occupied receptacles 30, the dealing rack 14 would thus first present XXF, followed by FXXX, resulting in the hand finally being stacked on the table in the order: F-X-X-X-X-X-F.

Even when the front hand cards are separated, the controller 134 can cause the shuffler 10 to present them so as to result in the desired order when stacked. For X-F-X-X-X-F-X, the dealing rack 14 would present XF, followed by XXX, followed by FX, resulting in the order: F-X-X-X-X-X-F. For X-X-X-X-F-X-F, the dealing rack 14 would present the cards XXXXF, followed by X, followed by F, resulting in the order: F-X-X-X-X-X-F when the three presentations are stacked on the table.

In these examples, the two front hand cards always end up on the top and bottom of the dealer's hand as stacked on the table. In this arrangement, the dealer can take the top card, slide it under the other six cards, and then turn the entire seven-card hand face up.

When the seven cards are then spread from left to right, the two cards furthest to the right will always be in place to be played up front according to house rules. The same principles could apply to arranging a dealer's hand in a required order for other card games.

In Poker, the dealer would remove the entire deck from the dealing rack and cut it
5 by hand (about half the deck is cut to the cut-card and the remaining half is placed on top to complete the cut). If cutting only one card were permissible, a random cut produces one of 51 possible orders. But with the identity of just a single card exposed at a predetermined position in the hand communicated to the controller 134, the card's position and identity reduces the possible orders to only ten in Hold'em (from two to eleven players), or seven in
10 Stud (from two to eight players), etc.

Assume a Hold'em game with a "bad-beat" jackpot (for example, two players split the jackpot when one has four of a kind and loses to a straight flush or higher). Assume the "river" card, the last card dealt in Hold'em, is the exposed card or "key-card." If this card happened to be the ace of spades, the shuffler 10 could reconstruct the orders for two to
15 eleven players given the position of this card. With two players, the ace of spades had to be the 12th card in the post-shuffle order since each player is dealt two cards, the board (cards face up on the table) consists of five cards, and there are three burned cards. For three players, the ace of spades had to be the 14th card in the post-shuffle position, and so on. With knowledge of the identity and location of a single card (played or unplayed), it is
20 possible to "back up" and reconstruct the hands for two to eleven players. To provide a requested jackpot confirmation, the dealer could, for example, press the DM button 144 three times, or as otherwise programmed, to place the shuffler 10 into the jackpot verification mode, and if a jackpot hand was identified, the DM button 144 would flash a signal, for example, rapidly blink the green light 146 for a second or two, stop for a second
25 or two, and then slowly blink two to eleven times to indicate the number of players that must be present for the jackpot to be valid.

With the capability of the shuffler 10 to record in memory the entire post-shuffle order of the shuffled cards 32, it is possible to use this capability to verify a jackpot hand even in games where the cards are cut randomly after the shuffle, by the players
30 (Blackjack), or dealer (Poker), so long as the identity of a key card can be verified and communicated to the microcomputer 170.

The rank and suit of the river card, or any other key card that would provide the shuffler 10 a reference point, may be entered into the microcomputer 170 through a

keypad 184, either incorporated in the shuffler 10 or provided separately and connected through a suitable digital communication cable or wireless connection. Identification to the controller 134 of a single card in a key position allows confirmation that a jackpot hand was present in the post-shuffle card order.

- 5 Also using the keypad 184 (see FIG. 2) to enter the number of hands dealt in a particular round into the microcomputer 170 allows the lone applicable jackpot hand to be verified.

- 10 As can be understood from the foregoing, the shuffler 10, particularly when equipped with a card reader 180, is very versatile and flexible. By use of suitable programming of the microcomputer 170, the shuffler 10 can be set up, by use of suitable patterns of numbers and durations of pushes on the DM button 144, to select among various options at several levels. The shuffler 10 can thus be set for use simply to shuffle a deck to be dealt from the dealer's hand or so that the shuffler 10 can present the cards for complex games such as Pai Gow Poker, as outlined below. Thus, with a programmed
- 15 sequence of pressing the DM button 144 to enter the desired pre-game settings mode, a desired setting can be entered for various options within a category by pressing the DM button 144 a corresponding number of times within an available time such as two or three seconds. A list of some possible categories of set-up options in a possible order of entering selections to set up the shuffler 10, and related options within categories follows:

20

SHUFFLE –

(In each category of setup options, for example, to select an available option from the following choices the supervisor would press the DM button 144 one, two, three, or four times.)

- 25 (1) two-deck batch (default),
 (2) one-deck – traditional,
 (3) one-deck – incremental,
 (4) one-deck – continuous;

30 CUTTING THE CARDS

- (1) no cut (default),
 (2) shuffler randomly cuts the cards,
 (3) interactive player cut;

BURNING A CARD(S) –

- (1) no burn cards (default),
- (2) one burn card – Blackjack,
- 5 (3) one to ten burn cards as indicated by the top card – Baccarat;

DEALING STARTING POSITION –

- (1) traditional deal - always start to the dealer's left (default),
 - (2) randomize the position of the starting hand in Pai Gow Poker;
- 10

DEALING DIRECTION –

- (1) traditional – clockwise (default),
 - (2) Asian style – counterclockwise;
- 15 DEALING SEQUENCE (novelty games - hand removal mode only) –
- (1) number of cards in players' hands,
 - (2) number of cards in dealer's hand,
 - (3) if required, number of cards in additional betting round number "1",
 - (4) if required, number of cards in additional betting round number "2",
 - 20 (5) if required, number of cards in additional betting round number "3",
 - (6) any game with a random deal or phase as directed by RANDOM MODE;

DEALER'S HAND –

- (1) no special arrangement of dealer's hand (default),
- 25 (2) arrangement of dealer's hand according to house rules for Pai Gow Poker (using an included card reader 180),
- (3) no-peek Blackjack (using an included card reader 180);

AUTOMATIC SHUFFLE UP –

- 30 (1) dealer uses DM button 144 to raise dealing rack 14 to remove cards for the next shuffle (default),
- (2) automatically raises the dealing rack 14 after round including the 26th card presented,

- 44 -

(3) automatically raises the dealing rack 14 after round including the 34th card presented,

(4) automatically raises the dealing rack 14 after round including the 40th card presented;

5

RANDOM MODE –

(1) sets the number of cards or range of numbers of cards to be presented to the players,

10 (2) sets the number of cards or range of numbers of cards to be presented to the dealer,

(3) if required, sets the number of cards or range of numbers of cards to be presented in additional betting round number “1”,

(4) if required, sets number of cards or range of numbers of cards to be presented in additional betting round number “2”,

15 (5) if required, sets number of cards or range of numbers of cards to be presented in additional betting round number “3”;

SECURITY MODES –

(1) normal pre-game settings (default),

20 (2) fake insertion mode,

(3) extra card dealt to dealer’s hand,

(4) dealer’s hand not dealt until all players have acted,

(5) fake insertion mode AND extra card dealt to dealer’s hand,

(6) fake insertion mode AND dealer’s hand not dealt until all players have acted;

25

ADDITIONAL GAME FEATURES –

(1) no special features (default),

(2) jackpot query,

(3) jackpot redeal,

30 (4) sorting,

(5) predeal deck composition evaluation,

(6) dynamic game dealing.

MULTI-DECK EMBODIMENT

As mentioned briefly above, the shuffler 10 can be made for use in multi-deck games, by modifying the dealing rack 14 to include a larger number of single-card receptacles 30. Because of the resulting increase in height of the shuffler 10, however, it
5 may instead be desirable to move the dealing rack 14 to a horizontal orientation, for shuffling two or more decks of cards 32 together.

In a multi-deck shuffler 210 shown in FIGS. 19-26, there is a deck-crib 212 that moves relative to a receiving rack 214, similar to the dealing rack 14 of the shuffler 10, but not actually used for dealing in this shuffler 210, with the receiving rack 214 oriented at 90
10 degrees from the arrangement of the dealing rack 14 in the shuffler 10, so that cards 32 in the deck-crib 212 and the receiving rack 214 are on edge in a horizontal stack. The multi-deck shuffler 210 includes a base 216 supporting a frame 218 of the receiving rack 214. The receiving rack 214 is larger than the dealing rack 14 of the shuffler 10 and has sufficient single-card receptacles to receive several standard decks of cards. For
15 example, in the shuffler 210 as shown herein, there may be 314 individual single-card receptacles 220, in order to receive six decks of playing cards 32, as well as a pair of cut cards 222, with all of the playing cards and cut cards 222 on edge and their planar surfaces facing one another. The frame 218 of the receiving rack 214 is mounted fixedly on the base 216, and the deck-crib 212 is arranged to be moved along the receiving rack 214 as
20 required to place individual ones of a group of cards being shuffled into randomly selected single-card receptacles 220, as will be explained subsequently.

In the multi-deck shuffler 210 as illustrated each playing card 32 and cut card 222 is held on edge, with one of its longer side edges down and with the shorter top and bottom edges of each card extending vertically, although the cards could be arranged with their top
25 or bottom edges down and their side edges extending vertically. The orientation shown in the drawings results in the multi-deck group of shuffled playing cards being presented in the conventional orientation used in a card-dealing shoe in casinos.

As shown in FIG. 19, the multi-deck shuffler 210 includes an outer cover 224 to which an access cover 226 is attached, as by hinges, so that it may be raised as shown in
30 FIG. 20 to provide access to the deck-crib 212. An opening 228 is defined by the access cover 226, to permit groups of playing cards 32 to be inserted through the opening 228 into the deck-crib 212, to be shuffled. A fin-like bumper 229 extends upward on the cover 224 along the opening 228 to protect cards from being exposed to view.

A discard rack or tray 230 may be located on the top of the access cover 226 adjacent to the opening 228, and a depressed area may be provided in the top of the access cover 226 adjacent and extending underneath the discard tray to facilitate picking up cards from the discard tray 230.

5 A card presentation tray 232, a portion of the receiving rack 214, has an outer wall 234 that is part of the front side of the shuffler 210, as may be seen best in FIG. 20. The height 236 of the multi-deck shuffler 210, not including the discard tray 230, may be, for example, about 5.5 inches (13.97 cm), less than three times the width of a playing card, and the shuffler 210 is thus unlikely to interfere with the dealer's or a supervisor's view of
10 the playing table when the multi-deck shuffler 210 is in a normal location to the right of the dealer. The depth 238 of the shuffler 210, with the card presentation tray 232 retracted as shown in FIG. 19, may be, for example, about 8.5 inches (21.59 cm), or less than three times the length of a playing card. The width 240 of the shuffler 210 depends upon the number of cards for which the receiving rack 214 is designed, and in the embodiment
15 shown in the drawings of this application, in which the receiving rack 214 is designed for six decks of playing cards 32, the width 240 may be about sixteen inches (40.64 cm). Including the card presentation tray 232 extended as shown in FIG. 20, the depth 238a of the multi-deck shuffler 210 may be, for example, about 12.5 inches (31.75 cm). The depth 238 of the shuffler 210 between the dealer and the shuffled playing cards 32 may be
20 about 8.3 inches (21.082 cm). The size of the shuffler 210 is thus small enough not to intrude excessively.

The multi-deck shuffler 210 is intended to shuffle six decks of playing cards into a single randomly shuffled arrangement of 312 cards, and to do so with a minimum delay of playing by shuffling six or more smaller increments of a large group of cards 32
25 sequentially before presenting the entire group of shuffled cards. The resulting multi-deck group of shuffled cards 32 is thus equally as randomly arranged, as would be the case if all 312 cards had been shuffled simultaneously in a single operation. Since in multi-deck systems of play the tail end of a shuffled multi-deck group of cards is usually not played, that portion of the shuffled multi-deck group of cards can be put back into the shuffler and
30 shuffled even before beginning to deal from the front end, and the cards 32 from each round of play can be shuffled while play continues using remaining ones of a previously shuffled large group of shuffled cards 32. The shuffling operation, while not continuous, is equally as random in the eventual placement of each card 32 into the receiving rack 214 as

- 47 -

though all 312 cards 32 were placed into the deck-crib 212 at one time. Use of a deck-crib 212 of a smaller size, however, allows the multi-deck shuffler 210 to have a smaller overall size, since a larger deck-crib 212 would require a greater width 240.

Once the entire group of several decks of cards has been shuffled, the card
5 presentation tray 232 is extended to the position shown in FIG. 20, and the shuffled cards, no longer separated from each other in the single-card receptacles 220, may be removed manually from the card presentation tray 232, as by simply sweeping them together horizontally toward the far, or left, end of the presentation tray 232. A finger 241 on the
10 upper left corner of the wall 234 makes the cards 32 lean toward the opposite, right, end of the presentation tray 232 as it is moved. The shuffled cards 32 may, for example, be removed onto the table top, into a dealing shoe, or onto a ramp that might be attached to the base of the multi-deck shuffler 210 or attached to the card presentation tray 232 and movable along with it. A mechanical pusher could be provided to push the shuffled cards together and toward one end of the card presentation tray 232, if desired, although such
15 additional attachments and mechanisms are not essential to the present invention and are therefore not depicted in the drawings nor described in detail.

Referring to FIGS. 21-26, in which the main cover 224 and the access cover 226 have been removed, the base 216 supports the frame 218 of the receiving rack 214. A top member 242 of the frame 218 supports divider members 244 in the form of thin, planar
20 leaves extending downwardly by a height 246 of about 1.75 inch (4.445 cm), or about $\frac{3}{4}$ of the width of a playing card. The top member 242 has a length determined by the number, thickness, and spacing of the leaves 244 defining the single-card receptacles 220, and each leaf 244 has a front-to-rear depth 248 which may be less than the length of a playing card, yet should be great enough to align each playing card 32 in one of the single-card
25 receptacles 220 so that the shuffled cards are parallel with one another. For example the depth 248 may be about 1.9 inches (4.826 cm), or about one half the length of a playing card 32. The leaves 244 may have thicknesses and be of material similar to those of the partial shelves 26 and 28 of the shuffler 10, and may be similarly spaced apart, but may also be thinner, for example having a thickness of about 0.010 inch (0.0254 cm), as they
30 are not required to support the weight of a card 32.

A rear face 250 of the receiving rack 214 may be defined by the rear margin of the top member 242 of the frame 218 and the vertical rear edges of the leaves 244. The rear edges are all aligned with and coplanar with each other, in a vertical plane extending

- 48 -

parallel with the width 240 of the shuffler 210, slightly forward of the midpoint of its depth 238.

5 The deck-crib 212 is supported for movement parallel with the rear face 250 of the receiving rack 214, through a range allowing a card mover portion of the deck-crib 212 to place a card 32 into any of the single-card receptacles 220. The deck-crib 212 is supported by and slides along a guide rod 252 that extends parallel with the rear face 250, supported by a pair of upstanding end walls 254 and 256, and is also supported, and moved, by a lead screw 258 that extends parallel with the guide rod 252 and is supported for rotation in suitable bearings in the end walls 254 and 256.

10 Mounted on the end wall 256 and with its shaft extending through an opening defined in the end wall 256 is a motor 260, such as a stepper motor, arranged to drive the lead screw 258 through an endless belt 262 and corresponding pulleys as seen best in FIG. 21. The lead screw 258 moves the deck-crib 212 along the receiving rack 214 to align it with a selected single-card receptacle 220.

15 The deck-crib 212 includes a generally horizontal base portion 268 having a generally planar upper surface and including bearings 270 disposed around the guide rod 252 to keep the base portion aligned with it. A drive nut 272 is engaged with the threads of the lead screw 258, so that when the stepper motor 260 rotates the lead screw 258 the deck-crib 212 is moved along the guide rod 252.

20 A planar end member 274 of the deck-crib 212, corresponding with the bottom member 38 of the deck-crib 12 in the shuffler 10 described previously, extends upward from the right end of the base 268. An upright planar member or wall 276 is mounted on the base 268 parallel with the end member 274 and spaced apart from it toward the opposite, or left, end of the base 268. A planar deck follower 278 is mounted to slide on a pair of horizontal guide rods 280 supported by and extending between the end member 274 and the upright planar member 276. A precisely controllable motor 282, which may be a linear actuator stepping motor, may be mounted on the upright wall 276 and is connected with the deck follower 278, to move the deck follower 278 toward and away from the end member 274. A pressure sensor 284 is arranged to measure the force used to urge the deck follower 278 toward the upright planar end member 274. The motor 282 is controlled to provide an appropriate amount of pressure to urge a group of playing cards 32, held in the space 286 between the deck follower 278 and the upright planar end member 274, toward each other and toward the end member 274, to permit a card mover mechanism 288 to

25

30

move the individual card 32 that is closest to the planar end member 274, referred to for convenience as the bottom card, from the deck-crib 212 into a selected one of the single-card receptacles 220 with which the deck-crib 212 is aligned.

The card mover mechanism 288 includes a motor such as a stepper motor 290
5 mounted on the base 268 of the deck-crib 212. Two sets of frictional drive members 292 and 294, which may be O-rings of a suitable elastic material such as a silicone rubber, are located near the front portion of the fixed upright end wall 274 of the deck-crib 212. The drive members 292 and 294 have driving surfaces facing toward the card follower 278 and protruding slightly beyond the plane of the end wall 274, similar to the drive rollers 52 of
10 the shuffler 10, for example protruding about 0.030 inch (0.0762 cm). The frictional drive members 292 and 294 extend around respective sets of pulleys 296 and 298 carried on an idler shaft 300, and respective sets of pulleys 304 and 306 carried on and driven by a card mover drive shaft 302. The shafts 300 and 302 are parallel and are arranged for the shaft 302 to drive the frictional drive members 292 and 294. The drive members 292 and
15 294 thus can engage a card 32 along driving surfaces that are as long as the center-to-center spacing between the shafts 300 and 302. The drive shaft 302 extends downward through bearings mounted in the base 268 of the deck-crib 212. The motor 290 has a rotating shaft extending vertically downward through an opening through the base 268. A driven pulley 304 mounted on the lower end of the drive shaft 302 is driven by a belt 310 driven
20 by a pulley 312 on the shaft of the motor 290.

A pair of idler rollers 314 are carried on a shaft 316 mounted in the forward portion of the sliding card follower 278. The idler rollers 314 are aligned with and located opposite the drive members 292 and 294, protruding radially beyond the surface of the deck follower by a small distance, similar to the rollers 66 of the shuffler 10, and are free to
25 rotate as driven by the card mover driving members 292 and 294 or by movement of a playing card between them and the idler rollers 314.

A deck-crib front plate 318 is upright and perpendicular to the end wall 274 and upright wall 276 and is attached to the base 268 and the upright wall 276, so that they can support each other as a rigid assembly. The front plate 318 acts as a card stop, similar to
30 the card stop 58 of the shuffler 10 described above, and includes a right end face 320 located so that together with the frictional drive members 292, 294 it defines an outfeed or card transfer slot 322 having a gap width 324 similar to the gap height 64 of the shuffler 10, large enough to permit only a single card to pass out through the slot 322 at

- 50 -

one time, from the space 286 between the end member 274 and the sliding card follower 278. A portion 325 of the end face 320 may be indented so as to avoid friction caused by contact with a card 32 passing through the outfeed slot 322.

5 The front plate or card stop 318 is spaced apart from the rear edges of the leaves 244 of the receiving rack 214 by a gap 326, equivalent to the gap 35 of the shuffler 10 and which may be of a similar size, such as in the range of 0.020–0.25 inch (0.0508–0.635 cm), or more preferably 0.020–0.090 (0.0508–0.2286 cm), or about 0.040 inch (0.1016 cm), so as to optimize the distance through which a card 32 must be moved.

10 The card presentation tray 232 is located beneath the array of single-card receptacles 220 of the receiving rack 214 and is movable from its retracted position, shown in FIG. 19, where it is located during the process of shuffling cards, to a card presentation position shown in FIG. 20, by moving along a pair of support rails 328 and 330, which may be rods extending forward from uprights 332 mounted on the base 216 beneath the deck-crib 212 to uprights 334 mounted near the front of the base 216. The presentation
15 tray 232 includes a rigid, planar, horizontal bottom member 336 extending between and supported by end walls 338 and 340, above the support rails 328 and 330. The outer wall 234 is mounted to the bottom member 336. End walls 338 and 340 extend a distance below the bottom member 336 and rearward toward the deck-crib 212, and include slide bearings engaging the support rails 328 and 330 and thus supporting the card presentation
20 tray 232. The end wall 340 may extend upward above the bottom member 336 by a distance such as about 0.6 inch (0.1524 cm), to retain and support a group of shuffled playing cards 32.

Referring next to FIGS. 22 and 30–32, a precisely controllable motor such as a stepper motor 346 is mounted on the base 216 beneath the guide rod 252 and is connected
25 to drive a lead screw 348 aligned horizontally and extending forward beneath the bottom member 336 of the card presentation tray 232 when the card presentation tray 232 is in the retracted position shown in FIG. 22. The lead screw 348 is connected to the stepper motor 346, which is mounted in a support member 350. An outer, or front, end of the lead screw 348 extends through a drive nut 352 mounted on a bracket 354 carried on the
30 underside of the rear margin of the bottom member 336.

A card pusher bar 358 is attached to the rear margin of the bottom member 336, as by a pair of fasteners such as screws 360 mounted in the bottom member 336 and extending through vertically oriented elongated holes 362. The card pusher bar 358 can be

- 51 -

raised or allowed to drop relative to the bottom member 336 by a cam 364 moved by the lead screw 348 through an angle defined by limit stops, such as the ends of an arcuate slot 366 in the cam and a member such as a screw 368 mounted in the bracket 354 and extending into the slot 366. It will be understood that rotation of the cam can be limited in other ways, such as, for example, by shaping portions of the cam to contact portions of the bracket 354. The shape of the cam 364 is designed so that rotation of the lead screw 348 in the direction required to drive the card presentation tray 232 outward toward the card presentation position shown in FIG. 19 will raise the card pusher bar 358 before the tray moves too far. A collar attached to the cam 364 and surrounding the lead screw 348 may include a slip clutch 369, which may be as simple as a screw having a resilient tip adjusted to bear on the lead screw 348 sufficiently to carry the cam 364 through the required angle of movement and then slip on the lead screw as it continues to rotate in the direction required to move the card presentation tray 232. A top margin of the card pusher bar 358 may be chamfered, so as to engage the rounded corners of cards 32 and move them forward if necessary as the bar is raised. The card pusher bar 358, when raised, will bear on the rear corners and a portion of the upright ends of the shuffled cards 32 to push them forward from the single-card receptacles 220 as the card presentation tray 232 moves forward toward the presentation position, so that the cards can be removed from the card presentation tray 232 by the dealer. The raised card pusher bar 358 is low enough, and the bottoms of the depending leaves 244 defining the single-card receptacles are high enough, to provide clearance beneath the leaves 244 for the card pusher bar 358. Once the cards have been removed from the card presentation tray 232, when the lead screw 348 is rotated in the reverse direction it will move the cam 364 in the opposite direction through the available angle of movement, allowing the card pusher bar 358 to move downward as the card presentation tray 232 is retracted beneath the frame 218.

As shown in FIGS. 24, 25, and 26 the card pusher bar 358 in its lowered position is flush with the top surface of the card presentation tray bottom member 336. As a variation, as shown in FIG. 25A, instead of the card pusher bar 358 and its associated cam arrangement, a raised ridge 359 may be provided at the rear end of the bottom member 336. The ridge 359 may have a height of about 0.25 inch (0.635 cm), for example, above the top face of the bottom member 336, with the upper face of the ridge aligned with or slightly lower than the height of the top of the base 268 of the deck-crib 212, so that a card 32 fed into one of the single-card receptacles 220 with sufficient speed will proceed past the

ridge 359 and come to rest with its bottom edge resting on the top surface of the bottom member 336, to be carried forward with the presentation tray 232. This configuration requires the top face of the bottom member 336 to be lower, by at least the height of the ridge, than it needs to be in the configuration shown in FIGS. 25 and 26.

5 A controller 370 may be located on the base 216, along with required power supplies. The controller 370 is connected electrically to the several motors 260, 282, 290 and 346, and is also connected electrically to a dealer manager DM button 372 located in the main cover 224 above the controller 370.

10 Operation of the shuffler 210 is similar in many ways to operation of the shuffler 10 described above.

 An empty tray sensor 376 may be utilized to provide an electrical signal to the controller 370 indicating that a shuffled six-deck group of cards has been removed from the card presentation tray 232, and the controller 370 may be programmed either to retract the card presentation tray 232 after a predetermined delay time, or to accept a command from
15 the dealer manager button 372 to cause the card presentation tray 232 to be retracted after such a predetermined delay time. The card presentation tray is retracted by operation of the motor 346, driving the lead screw 348.

 Once the card presentation tray 232 has been retracted and cards are present in the deck-crib 212, the controller will commence the process of shuffling the cards that are in
20 the deck-crib 212. An optical sensor 390, for example an IR laser/detector pair located on the receiving rack 214, determines whether the gap 326 is obstructed, and seeing that the gap is unobstructed, sends an electrical signal to the controller 370, which confirms that the deck-crib 212 is free to move to a different position along the receiving rack 214.

 A status indication may be provided by a separate status indication light, such as a
25 LED lamp 374 located on the main cover 224, or by a similar indication provided by signal lamps included in the dealer manager button 372, similar to the dealer manager button 144 in the shuffler 10 described above. Such an indicator might show red while the shuffling process is proceeding with respect to one group of cards that have been placed into the deck-crib 212, and green when the deck-crib 212 is ready to allow a group of cards 32 to be
30 inserted.

 An optical sensor 380 is located in the deck-crib 212. When a group of cards is inserted into the deck-crib 212 to be shuffled the sensor 380 detects the presence of at least one card and provides an electrical signal to the controller 370, which, after a preset delay

- 53 -

time of, for example, three seconds, energizes the motor 282 to move the deck follower 278 toward the end wall 274. The pressure sensor 284 sends a pressure signal to the controller 370, and when the controller 370 determines that the cards are urged toward the end wall 274 with enough pressure to ensure that the frictional drive members 292 and 294 will engage the face of the adjacent, bottom, card 32, the controller stops the motor 282. Once a card 32 has been moved from the deck-crib 212 the controller 370 will determine whether the pressure, as sensed by the sensor 284, is still appropriate and, based on the signals from the sensor 284, will cause the motor 282 to move the deck follower 278 as required from time to time.

10 With the card receiving rack 214 empty there are, for example, 314 empty single-card receptacles 220 available. As with the shuffler 10 described above, a random number generator in the controller 370 randomly selects one of the empty single-card receptacles 220 and sends an appropriate signal to the stepper motor 260, causing the stepper motor 260 to rotate the lead screw 258 appropriately to move the deck-crib 212 so that the slot 322 is aligned with the selected single-card receptacle 220 of the receiving rack 214.

 A card receptacle alignment sensor 386 associated with the deck-crib 212 determines whether the outfeed, or card transfer slot 322 is properly aligned with the selected single-card receptacle 220. If alignment is not correct, the controller 370 will send additional order signals to the stepper motor to move the deck-crib 212 until the card receptacle alignment sensor 386 indicates that alignment is satisfactory.

 Once the card outfeed slot 322 is properly aligned, the controller 370 will cause the card mover motor 290 to move the drive shaft 302, and with it the frictional drive members 292 and 294, far enough to move the bottom card 32 out of the deck-crib 212 through the slot 322 with enough speed to continue across the gap 326 between the deck-crib 212 and the receiving rack 214 and into the selected single-card receptacle 220 far enough to pass effectively over and beyond the card pusher bar 358, where the outer wall 234 of the card presentation tray 232 will prevent the card 32 from going too far. The controller 370 is programmed to limit the amount of rotation of the drive shaft 302 to prevent the subsequent bottom card 32 in the deck-crib from moving into the gap between the deck-crib 212 and the receiving rack 214.

 Once a card 32 has been placed into one of the single-card receptacles 220, the controller 370 then causes the random number generator to select another single-card

- 54 -

receptacle 220 from among the remaining empty ones. The open gap sensor 390 again verifies that the deck-crib 212 can again be moved, and the next bottom card 32 is then placed in the next selected single-card receptacle 220 by the same steps just described. This sequence of steps is repeated, with random selection of one of the remaining open
5 single-card receptacles 220 after each card 32 is moved, until all of the cards that had been placed into the deck-crib 212 have been moved into respective randomly selected single-card receptacles 220 and the deck-crib sensor 380 detects and sends a signal to the controller 370 indicating that there are no more cards left in the deck-crib 212. The controller then directs the stepper motor 260 to move the deck-crib 212 to the card
10 receiving position at the left end of the shuffler 210 and sends a signal directing the motor 282 to again retract the deck follower 278 to make the space 286 available for the next group of cards 32 to be placed into the deck-crib 212 to be shuffled. Most of the cards of a large group are thus shuffled as smaller groups while game play continues, and shuffling the final group will result in quicker readiness to continue play than the time
15 required to load and unload two sets of six decks in a batch rotation system.

The controller 370 may be programmed so that when the card presentation tray 232 is first retracted in an empty condition a pair of cut cards 222, plastic cards similar to playing cards but without faces, inserted at the bottom of the first group of cards 32 inserted into the deck-crib 212, will be placed into the two extreme end single-card
20 receptacles 220 in the receiving rack 214 before any actual playing cards are placed into randomly selected single-card receptacles 220.

In addition to the controls to cause the shuffler 210 to operate as described above, an additional sensor 392 may be provided on the deck-crib 212 to count the number of cards transferred from the deck-crib 212 to the receiving rack 214 in order to determine
25 that the correct number of cards have been shuffled and that the multi-deck group of cards is thus complete. An optical scanner 394 may also be associated with the deck-crib 212 to determine the identity, the rank or suit or both, of each card as it is transferred from the deck-crib 212 to the receiving rack 214, and to communicate each card identity to the controller 370. The identity of each card can be associated with the selected single-card
30 receptacle 220 to which that card has been delivered and the association can be stored within the memory of the controller 370.

For Blackjack, the shuffler 210, equipped to identify and store in computer memory the locations of cards, can be used advantageously together with a dealing shoe (not

- 55 -

shown) equipped with a counter to provide to the controller 370 the number of cards that have been dealt at any given time. The dealer could query the order of the cards in the shuffled multi-deck group being dealt from the shoe, as by pushing the dealer manager button 372 in a predetermined fashion, and the shuffler 210 could then flash the dealer manager button 372 according to whether the last card dealt, always the dealer's hole card in Blackjack, was a card with a value of ten or not. The dealer manager button 372 could blink red to indicate that the hand is over and that the dealer can show the hole card and reveal a Blackjack. If the last card dealt is not a ten-value card, the dealer manager button could blink green, indicating that the hand can continue because there is no Blackjack in the dealer's hand. If the dealer shows a ten, the dealer manager button 372 could be pushed with a different sequence to query whether the last card dealt was an Ace. Such a system, the shuffler 210 coupled with a card-counting shoe, enables a "no-peek" Blackjack capability, so long as the shuffled six-deck group of cards is not cut before being dealt from the shoe.

In a multi-deck card shuffler 396 shown in FIG. 19A, which is another embodiment to the shuffler 210, the stepper motor 346 and lead screw 348 may be located near an end of a base portion, generally similar to one side of the card presentation tray, so that the guide rod and lead screw for the card presentation tray may be located lower and closer to the base in order to reduce the overall height of the shuffler. The width of the shuffler 396 in such a configuration is greater than that of the shuffler 210, to provide room at the end for the stepper motor driving the card presentation tray. Other card presentation tray movement arrangements may also be provided using, for example, scissors-like or pantograph linkage mechanisms of minimum height, or linkages attached to the card presentation tray 232 at an end, so that the deck-crib and dealing rack may be mounted lower and closer to the base 216 of such a shuffler, although such variations are not shown nor described in detail herein.

As another alternative (not shown) to the card shuffler 210 as described above, the divider leaves 244 could be replaced by dividers with a smaller depth, as well as additional dividers extending upward from the card presentation tray, leaving an opening between the upper and lower dividers through which a mechanism could be moved to push shuffled cards 32 forward onto a presentation tray. The dividers defining the individual single-card receptacles 220 could also be mounted on the bottom alone, leaving room above the dividers for a card ejection mechanism.

Although opening a new multi-deck card game in a casino can be very time-consuming using the conventional methods, the multi-deck shuffler 210 can greatly reduce the time required, since each deck of cards, after being inspected, “washed”, and squared, can be placed directly into the shuffler 210, and each card will be placed in a randomly selected single-card receptacle 220 among 312 randomly available positions. There is thus no interrelation between the original position of an individual card and a new deck and the eventual position after shuffling using the multi-deck shuffler 210, but the shuffling process can take place incrementally, without waiting until all six decks have been prepared.

Referring now to FIGS. 36-42, a shuffler 410 is generally similar to the shuffler 10, but is shown herein without its cover, in order to more clearly disclose its operation, which may be controlled by a controller that may be similar to the controller 124 and therefore is not described here with particularity. The shuffler 410 has a base 412 supporting a deck-crib 414 and a dealing rack assembly 416, which may also be referred to as a receiving rack assembly. As with the dealing rack assembly 14 described above, the dealing rack assembly 416 may include a frame 418 mounted on the base 412 and including a pair of opposite end members 420 and 422, arranged to be raised and lowered, and to which shelves 424 are attached.

The shelves 424 extend from one end member 420 to the other end member 422, defining a set of single-card receptacles 426. The dealing rack assembly 416 may include, for example, 54 single-card receptacles 426. Each shelf 424 defines a notch 428 and the notches are aligned with each other to define collectively a receptacle 429 in which a card presentation pusher 430 can be received, as will be explained in greater detail presently. A blocking wall 432, similar to the blocking wall 106 in the shuffler 10, may be mounted on the base 412, and there may also be a card shield 434, associated with the blocking wall 432, that functions in generally the same manner as the movable card shield 108 in the card shuffler 10.

At the opposite, or rear, side of the base 412, associated with the deck-crib 414, the card mover mechanism is in some ways similar to both of the card mover mechanisms associated with the deck-crib 12 and with the deck-crib 212. Cards to be shuffled can be inserted into the rear of the deck-crib 414, where open spaces may be provided to allow a dealer to grasp and remove unshuffled cards when necessary to clear a rare jam. The card mover mechanism may include a drive motor 436, which may be a stepper motor, driving a

- 57 -

feed driveshaft 438 arranged to drive a pair of cylindrical frictional drive rollers 442, which may be of rubber or rubber-like material, similar to the drive rollers 51 of the card shuffler 10. Upper, outer surfaces of the drive rollers 442 are located slightly above the upper card-facing surface 448 of the bottom or deck support wall member 450 of the deck-crib 414, so as to press against the adjacent bottom surface of the closest playing card 452 in the deck-crib 414.

The deck-crib 414 is constructed with a card stop 454 defining an outfeed or card transfer slot 456 similar to the slot 62 described above, with a gap height 458 similar to the gap height 64 in the shuffler 10, so as to permit only a single card to be fed out from the deck-crib 414 toward one of the single-card receptacles 426, as in the card shuffler 10. In one embodiment, the card stop 454 may be adjustable to vary the card the gap height 458 as necessary depending on the thickness of cards to be shuffled.

Associated with the bottom or deck support member 450 there is also an auxiliary card shuffling pusher 460, separately driven and controlled, but coordinated by the controller with the movement of the drive rollers 442, to ensure that each single playing card 452 is moved separately and completely out of the deck-crib and into the single-card receptacle 426 aligned with the slot 456. The auxiliary card pusher 460 is mounted with respect to the bottom or deck support member 450 so as to be movable reciprocatingly toward and away from the card stop 454. As shown in the embodiment depicted in FIGS. 36-41, moving member or shuttle 461 of the auxiliary shuffling card pusher 460 may be disposed so as to slide in a pair of ways 462 defined in the upper surface 448 of the bottom or deck support member 450, and may extend through a slot 464 defined in the bottom member 450, with a bottom or outer portion 466 thus made available to be driven. The shuttle 461 extends upward above the card-facing surface 448 of the bottom or outfeed wall member 450 a distance of, for example 0.020–0.030 inch (0.0508–0.0762 cm), slightly beyond the plane of the rollers 442, and a forward portion of the shuttle 461 extends beneath a small rear portion of the playing cards located in the rear of the deck-crib, opposite and spaced apart from the card stop 454, when the shuttle 461 is in a retracted position, as shown in FIG. 39.

A portion 467 of the upper surface 448 may be sloped toward the card stop 454, so as to provide a slightly raised portion 468 supporting the rear portion, the portion of the cards 452 in the deck-crib spaced further away from the card stop 454, so that the cards 452 in the deck-crib 414 remain substantially level, supported by the raised portion 468 and the

rollers 442, except when one of the cards 452 is being moved into one of the single-card receptacles 426.

Once the playing card 452 has been moved at least part of the way by the rollers 442 driven by the feed driveshaft 438, in a manner similar to that depicted in FIG. 8
5 with respect to the shuffler 10, a card-contacting face 463 of the auxiliary card pusher shuttle 461 moves toward the dealing rack and pushes the single card 452 the remainder of the distance out of the deck-crib and into the aligned single-card receptacle 426 of the dealing rack 416.

More specifically, once the drive rollers 442, if used, move the adjacent single one
10 of the cards 452 slightly farther than the distance by which the card-contacting face 463 is located beyond the rear edges of the playing cards 452, the rear edge of the single card being moved by the drive rollers 442 can move slightly away from the remaining playing cards 452 toward the bottom or deck support member 450. At that time the auxiliary card pusher shuttle 461 begins to move toward the card stop 454, and the card-contacting
15 face 463 can engage the rear edge of the single card as shown in FIG. 40. As the shuttle 461 moves toward the card stop 454 it moves the remaining cards in the deck-crib 414, other than the single card being moved, slightly away from the bottom or deck support member 450, reducing the ability of the remaining cards 452 to press the single card being moved against the drive rollers 442, and the auxiliary card pusher 460
20 then pushes the single card the remaining distance from the deck-crib 414, through the gap 456 and completely into the aligned one of the single-card receptacles 426 of the dealing rack 416.

There is a clearance distance 35', similar to the clearance 35 in the card shuffler 10, between the card stop 454 and the nearest edge of one of the shelves 424. Preferably this
25 clearance is as small as practical. For example the clearance 35' may be in the range of 0.02–0.25 inch (0.0508–0.635 cm), and preferably not more than about 0.09 inch (0.2286 cm), and more preferably not more than about 0.04 inch (0.1016 cm). As a result of this small clearance distance 35', a single card being moved from the deck-crib into the aligned one of the single-card receptacles 426 of the dealing rack or receiving rack 416 is only
30 required to move no more than the dimension of the playing card 452 in the direction of movement, plus the thickness of the card stop 454 and the clearance distance 35'. Thus the card-contacting face 463 of the auxiliary card pusher 460 needs to move only a very small distance past the outer surface of the card stop 454 to ensure that the single card 352 moved

- 59 -

from the deck-crib 414 is lodged entirely in the selected single-card receptacle 426, and the auxiliary card pusher shuttle 461 can immediately be retracted to its position at the rear of the deck-crib 414.

The auxiliary card pusher may, as shown in FIGS. 36-41, be powered by an
5 appropriate electric motor 470, which may be a stepper motor operated by numerical control by a controller appropriately programmed as described above in connection with the previously described shufflers. Alternatively, the electric motor 470 may be a DC motor and may be controlled with the use of a linear encoder. The electric motor 470 may be arranged to drive the auxiliary card pusher 460 by rotating a screw 472 engaged in the
10 shuttle 461 member as shown in FIGS. 39-41 so as to cause the shuttle 461 to move reciprocatingly in the ways 462 defined in the bottom or deck support member 450. Limit switches (not shown) may be used to communicate to the controller that the shuttle 461 has reached the intended position at each end of its range of travel. Alternatively, the electric motor 470 may be mounted on the base 412 of the card shuffler 410 and be coupled to the
15 shuttle 461 through a drive belt arrangement 474 as shown in FIG. 42.

The plurality of cards 452 may be urged toward the bottom or deck support member 450 of the deck-crib 414 by a card follower mechanism that may include rollers and a weighted or spring-biased idler arm similar to the rollers 66 and idler arm 68 incorporated in the card shuffler 10, or by the use of a card-pressing member such as a
20 weight 476 with a pressure face 478 that is generally planar, at least near the card stop 454, that can act to flatten a playing card 452 that has become warped during the course of previous play and might thus not easily be pushed into the slot 456 in the card stopped 454. That is, a card pressing member including a flat pressure face 478, and that is weighted or spring-biased so as to concentrate pressure near the card stop 454, may be used to flatten a
25 single card 452 sufficiently so that it can enter into the slot 456 easily and be moved into a single-card receptacle 426 in the process of shuffling the cards 452. It should be realized that a damaged card 452 may still not be sufficiently flattened to pass into the slot 456, and so the controller may be set for the card mover to repeatedly attempt to move a card 452 into a single-card receptacle, but to stop the shuffler after a set number of attempts so that
30 the dealer can remove the cards 452 from the deck-crib and straighten the bottom card, and restart the shuffling process.

As mentioned above, the card shuffler 410 also includes a card presentation pusher 430 that might be manually operated, but is preferably controlled automatically by

the controller and driven by an electric motor 482, through an appropriate linkage. Such an electric motor 482 may be mounted on a support member attached to the base 412, above the deck-crib 414, as shown in FIGS. 36-39, or it might instead be mounted in a further-removed or offset location if it is desired thereby to provide better access to the deck-crib 414. As shown, the electric motor 482 may in one embodiment be arranged to rotate a drive screw 483 to move the card presentation pusher 430 reciprocatingly between its retracted position as shown in FIGS. 36-39 and an extended position shown in FIG. 41, in which the card presentation pusher 430 extends into the a receptacle 429 defined in the dealing rack 416. The receptacle 429 may extend from the rear edge of each shelf 424, closer to the deck-crib 414, for a desired distance into the dealing rack 416, so that the card presentation pusher 430 can cause the shuffled cards in the single-card receptacles 426 raised above a margin 484 of the blocking wall 432 to extend from the dealing rack 416 above the margin 484 of the blocking wall 432 and beyond it far enough for a dealer to be able to grasp the presented cards easily.

For example, the card presentation pusher receptacle can be made deep enough so that cards can be pushed out beyond the shelves 424 of the dealing rack 416 by about 80% of their width, and at least about 60% of their width, or to be pushed even further, and desirably about 85% or 90% of their width, without falling out of the dealing rack 416.

Alternatively, the notches 428 defining the card presentation pusher receptacle 429 can be made deeper, so that the card presentation pusher 430 can push a selected group or hand of shuffled cards so that they extend far enough from the dealing rack to fall free onto the upper margin of the blocking wall and the top of the gaming table, ready for a dealer to slide the cards to a player.

The shuffler 410 may advantageously be mounted in a recessed position with respect to a gaming table, so that the upper margin 484 of the blocking wall 432 is located a small distance, for example no more than about 0.25 inch (0.635 cm), above the upper surface 486 of the gaming table, so that cards extending from the dealing rack may easily be grasped by a dealer to be passed to a player. Similarly, the shuffler 410 might be mounted on a poker table in a location straddling a chip tray, as mentioned above with respect to the shuffler 10.

It will be understood that the card shuffler described in the foregoing several paragraphs could be arranged more similarly to the arrangement of the card shuffler shown in FIGS. 20-30, with the dealing rack extending generally horizontally, rather than

- 61 -

vertically, and with one of the dealing rack and the deck-crib moving horizontally with respect to the other in the process of shuffling a deck or a plurality of cards.

The terms and expressions which have been employed in the foregoing specification are used therein as terms of description and not of limitation, and there is no
5 intention in the use of such terms and expressions of excluding equivalents of the features shown and described or portions thereof, it being recognized that the scope of the invention is defined and limited only by the claims which follow.

Embodiments of the disclosure may further be characterized, without limitation, as follows:

- 10 Embodiment 1. A card shuffler comprising:
- (a) a base;
 - (b) a deck-crib capable of containing a plurality of playing cards stacked together in contact with one another and with one of said plurality of cards adjacent a deck support member of the deck-crib;
 - 15 (c) a dealing rack located adjacent to said deck-crib and defining a plurality of single-card receptacles;
 - (d) a card mover associated with said deck-crib and operable to move a single card from said deck-crib to one of said of said plurality of single-card receptacles that is aligned with said deck-crib, said card mover including:
 - 20 (i) a primary card-contacting drive member in position to engage a surface of a card located adjacent to said deck support member of said deck-crib, and said card mover also including:
 - (ii) an auxiliary card pusher including a card-contacting member movable reciprocally in said deck-crib toward and away from said dealing rack;
 - 25 (e) a first motor arranged to move one of said dealing rack and said deck-crib relative to the other and to place said card mover and one of said single-card receptacles into alignment with each other; and
 - (f) a second motor drivingly connected to said auxiliary card pusher.

- Embodiment 2. The card shuffler of embodiment 1 wherein said deck support
30 member of said deck-crib includes a card-facing surface and the card mover includes a frictional drive element protruding into the deck-crib beyond the card-facing surface of said deck support member of said deck-crib.

Embodiment 3. The card shuffler of embodiment 1 or 2 including a controller arranged to cause the first motor to move the dealing rack.

Embodiment 4. The card shuffler of embodiment 1 or 2 wherein said dealing rack is movable to a position with respect to a blocking wall in which at least one of said
5 single-card receptacles is exposed above an upper margin of said blocking wall.

Embodiment 5. The card shuffler of embodiment 2 wherein the card-contacting member protrudes into the deck-crib beyond the frictional drive element, far enough to disengage from the frictional drive element a card adjacent to the single card being pushed while the single card is pushed into said one of said single card receptacles by the auxiliary
10 card pusher.

Embodiment 6. The card shuffler of embodiment 1 including a card presentation pusher and wherein said dealing rack defines a presentation pusher receptacle.

Embodiment 7. The card shuffler of embodiment 6, including a blocking wall located adjacent a side of said dealing rack opposite said deck-crib, the blocking wall
15 having a blocking wall margin, and wherein said dealing rack is movable to a position with respect to said blocking wall wherein at least one of said plurality of single-card receptacles is exposed beyond said blocking wall margin in a position from which every card in each exposed one of said plurality of single-card receptacles can be slid out simultaneously from the dealing rack by the card presentation pusher.

Embodiment 8. The card shuffler of embodiment 7, in combination with a game
20 table, wherein said base is mounted in a recessed position in a top of said game table and said blocking wall margin is located at a predetermined height above said top.

Embodiment 9. The card shuffler of embodiment 1 wherein said deck-crib includes an outfeed side that defines a card transfer slot.

Embodiment 10. The card shuffler of embodiment 9 including a controller, wherein
25 said controller is arranged to receive an input signal and to cause said dealing rack to move a predetermined distance in response to said input signal and thereby to place a predetermined number of said single-card receptacles of said dealing rack into a card-presenting position in which any cards in said single-card receptacles in said
30 card-presenting position can be presented by said card presentation pusher to be removed simultaneously from said dealing rack.

Embodiment 11. The shuffler of embodiment 9 wherein said outfeed side of said deck-crib includes a card block wall and said card mover includes a drive roller having an

upper surface and wherein said card transfer slot has a gap height, between said upper surface and a lower surface of said card block wall, that is greater than a thickness of a card and less than twice said thickness of said card.

Embodiment 12. The shuffler of embodiment 11 wherein said dealing rack is
5 separated from said card block wall by a clearance distance in the range of 0.02–0.25 inch (0.0508–0.635 cm).

Embodiment 13. The shuffler of embodiment 12 wherein said clearance distance is not more than about 0.09 inch (0.2286 cm).

Embodiment 14. The shuffler of embodiment 12 wherein said clearance distance is
10 not more than about 0.04 inch (0.1016 cm).

Embodiment 15. The shuffler of embodiment 11 wherein a card in said deck-crib has a width and is required to move only a distance equal to said width plus a thickness of said card block wall plus said clearance distance, in moving from said deck-crib into a single-card receptacle aligned with said card mover.

Embodiment 16. The card shuffler of embodiment 1 including a controller
15 interconnected with said motor and wherein the controller includes a random number generator arranged to randomly select an empty one of said plurality of single-card receptacles and cause said motor to align said one of said single-card receptacles with said card mover.

Embodiment 17. The card shuffler of embodiment 1 including a card shield located
20 alongside said dealing rack and arranged to move automatically to and remain in a first, extended, position during a shuffling operation and to move to a second, retracted, position thereafter.

Embodiment 18. The card shuffler of embodiment 1, in combination with a game
25 table, wherein said base is mounted in a recessed position in a top of said game table.

Embodiment 19. The card shuffler of embodiment 1 further including:

(a) a controller arranged to:

- (i) randomly select an empty one of said plurality of single-card receptacles of said dealing rack;
- 30 (ii) thereafter cause said first motor to move one of said dealing rack and said deck-crib to place said randomly selected empty one of said plurality of single-card receptacles into alignment with said card mover; and

- 64 -

(iii) thereafter cause said card mover and said auxiliary card pusher to move a single card from said deck-crib into said randomly selected empty one of said plurality of single-card receptacles.

Embodiment 20. The card shuffler of embodiment 1 including a screw drive
5 interconnecting said second motor drivingly with said auxiliary card pusher, so as to cause said card-contacting member to move said single card entirely into said one of said plurality of single-card receptacles that is aligned with said card mover.

Embodiment 21. The card shuffler of embodiment 1 further including a controller,
interconnected with said second motor so as to operate said auxiliary card pusher to move
10 said single card entirely into said one of said plurality of single-card receptacles that is aligned with said card mover.

Embodiment 22. The card shuffler of embodiment 1 wherein said dealing rack includes a plurality of shelves defining said single-card receptacles between adjacent ones of said shelves, each of said shelves defining a notch along a margin thereof, and said
15 notches jointly defining a presentation pusher receptacle in a side of said dealing rack facing toward said deck-crib.

Embodiment 23. The card shuffler of embodiment 1 further including a blocking wall extending along and adjacent a side of said dealing rack spaced apart from and facing away from said card mover and a card presentation pusher located, with respect to said
20 dealing rack, so as to push a card located in said dealing rack to a position in which said card remains engaged in said dealing rack, but extends above said blocking wall.

Embodiment 24. The card shuffler of embodiment 23 including a controller arranged to cause the first motor to move the dealing rack.

Embodiment 25. The card shuffler of embodiment 23 wherein said dealing rack is
25 movable to a position with respect to said blocking wall in which at least one of said single-card receptacles is exposed above an upper margin of said blocking wall.

Embodiment 26. The shuffler of embodiment 23 wherein said single-card receptacles are located in said dealing rack so as to hold at least one of said plurality of cards in a position of readiness to be removed therefrom manually to be dealt to a player
30 after said at least one of said plurality of cards has been moved by said card presentation pusher to a position in which said at least one of said plurality of cards remains engaged in said dealing rack, but extends above said blocking wall.

Embodiment 27. The shuffler of embodiment 1 wherein each single card of a plurality of cards contained in said deck-crib is separately moved only once, from said deck-crib to a selected one of said plurality of single-card receptacles, in order to shuffle said plurality of cards.

5 Embodiment 28. The card shuffler of embodiment 1 including a deck follower in the deck-crib arranged to urge said plurality of playing cards toward said deck support member.

Embodiment 29. The card shuffler of embodiment 28 wherein said deck follower includes a card-pressing member with sufficient weight to flatten a warped playing card.

10 Embodiment 30. The card shuffler of embodiment 28 wherein said deck follower includes a spring urging a card-pressing member toward said deck support member.

Embodiment 31. The card shuffler of embodiment 28 wherein said deck follower has a card-pressing member including a flat card-contacting portion located adjacent a card block wall of said deck-crib.

15 Embodiment 32. A card shuffler comprising:

(a) a base;

(b) a deck-crib supported by said base and capable of containing a plurality of cards arranged in a pack parallel and in contact with one another;

20 (c) a receiving rack associated with said base and defining a plurality of single-card receptacles in a linear array adjacent one another and located adjacent to said deck-crib, one of said deck-crib and said receiving rack being movable in a straight line with respect to said base and parallel with and along the other one of said deck-crib and said receiving rack;

25 (d) a card mover incorporated in the deck-crib and operable selectively to move ones of said plurality of cards from said the deck-crib to selected ones of said plurality of single-card receptacles;

(e) a card presentation pusher supported by said base, and located in operative proximity to said receiving rack;

30 (f) a motor associated with said base and arranged to move said card presentation pusher reciprocally relative to said receiving rack; and

(g) a controller interconnected with said motor and arranged to cause said motor to move said card presentation pusher so as to move a card in said receiving

- 66 -

rack a distance great enough to make said card available to be removed from said receiving rack.

Embodiment 33. The card shuffler of embodiment 32 wherein said card presentation pusher makes a card in said receiving rack available to be grasped at a side of the receiving rack located opposite from the card mover.

Embodiment 34. The card shuffler of embodiment 32 wherein said motor is drivingly connected with said card presentation pusher through a screw drive.

Embodiment 35. The card shuffler of embodiment 32 wherein said controller is arranged to receive an input signal and to cause the receiving rack to move a predetermined distance in response to said input signal and thereby to place a predetermined number of said single-card receptacles of said receiving rack into a card-presenting position in which any cards in said single-card receptacles in said card-presenting position can be moved by said card presentation pusher and thereby made available to be removed simultaneously from said receiving rack.

Embodiment 36. The card shuffler of embodiment 32 including a shuffling motor associated with said base and arranged to move one of said receiving rack and said deck-crib relative to the other; and

wherein said controller is interconnected with said card mover and at least one of said deck-crib and said receiving rack and arranged to:

- (i) randomly select an empty one of said single-card receptacles of said receiving rack;
- (ii) thereafter cause said shuffling motor to move one of said deck-crib and said receiving rack relative to the other in a straight line and to align one of said card mover and said randomly selected empty one of said plurality of single-card receptacles with the other;
- (iii) thereafter cause said card mover to move a single card from said deck-crib into said randomly selected empty one of said plurality of single-card receptacles while said card mover and said single-card receptacle are aligned with each other; and
- (iv) thereafter sequentially repeat steps (i), (ii), and (iii), until said deck-crib has been emptied of cards.

Embodiment 37. A method of shuffling a first plurality of playing cards comprising:

- 67 -

- (a) selecting a second plurality of playing cards from the first plurality and placing the second plurality of cards into a deck-crib including an outfeed slot, with a bottom one of said second plurality of cards aligned with said outfeed slot;
- 5 (b) providing a receiving rack including a plurality of single-card receptacles arranged parallel with and adjacent one another;
- (c) providing a controller including a digital computer having a memory component;
- 10 (d) causing said controller to automatically randomly select an empty one of said plurality of single-card receptacles;
- (e) automatically, in response to selection of an empty one of said plurality of single-card receptacles, moving one of said receiving rack and said deck-crib in a straight line relative to the other of said receiving rack and said deck-crib to align said selected empty one of said plurality of
- 15 single-card receptacles and said outfeed slot of said deck-crib with each other; and
- (f) moving a single card from said second plurality of cards through said outfeed slot into said selected one of said plurality of empty single-card receptacles by first using a frictional drive element to move said single card
- 20 a predetermined portion of a distance into said selected one of said plurality of empty single-card receptacles and thereafter moving an auxiliary card pusher reciprocatingly along the deck-crib to ensure that the single card is moved entirely into the selected single-card receptacle.

Embodiment 38. The method of embodiment 37 including the further steps of:

- 25 (g) recording in said memory component of said controller that the selected one of said plurality of empty single-card receptacles has received a card from the deck-crib and is no longer empty;
- (h) thereafter causing said controller to automatically randomly select another empty one of said plurality of empty single-card receptacle from all of the
- 30 remaining empty ones of said plurality of single-card receptacles; and
- (i) thereafter repeating steps (e) and (f) of embodiment 35 and steps (g) and (h) until each of said second plurality of cards has been moved separately from

- 68 -

said deck-crib to a separate respective randomly selected one of said single-card receptacles.

Embodiment 39. The method of embodiment 37 including the further step of thereafter presenting at least some of said second plurality of cards simultaneously
5 extending from a plurality of adjacent ones of said plurality of single-card receptacles, in a condition of readiness to be dealt.

Embodiment 40. The method of embodiment 37 including the steps of pressing said single card into a flat condition in said deck-crib and keeping said single card flat while performing said step of moving it through said outfeed slot into said selected empty
10 single-card receptacle.

Embodiment 41. The method of embodiment 37 wherein said first plurality of playing cards is greater in number than said second plurality of cards and said second plurality of cards is fewer than a complete deck, and including the step of repeating steps (a) and (d) through (f) with respect to at least one respective additional plurality of cards,
15 thereby shuffling all of said first plurality of playing cards.

Embodiment 42. The method of embodiment 37 wherein said first plurality of playing cards is a complete deck, including the step of repeating steps (a) and (d) through (f) until said controller determines that said complete deck has been moved into said dealing rack, and only thereafter moving said receiving rack to present said shuffled cards
20 to be dealt.

Embodiment 43. The method of embodiment 37 wherein said first plurality of playing cards is a multi-deck group from which cards are being dealt during a game, and including performing a step of placing an additional second plurality of cards selected from said first plurality of playing cards into said deck-crib prior to completion of dealing cards
25 from said first plurality of playing cards, and including the step of thereafter repeating steps (d) through (i) with respect to at least said additional second plurality of cards from said first plurality of playing cards.

Embodiment 44. A method of dealing a plurality of playing cards comprising:
(a) placing a plurality of playing cards into respective single-card receptacles in
30 dealing rack including a plurality of single-card receptacles stacked adjacent one another in a fixed array and arranged so that said playing cards are parallel with each other;

- (b) placing said dealing rack into a first position adjacent a blocking wall alongside a card removal side of said dealing rack;
- (c) in response to a predetermined condition automatically moving one of said dealing rack and said blocking wall relative to the other through a distance determined by a controller, thereby exposing a first selected number of single-card receptacles beyond a margin of said blocking wall and creating an open path along said margin of said blocking wall for removal of a plurality of said playing cards from said exposed single-card receptacles;
- (d) thereafter automatically pushing said plurality of said playing cards in said first selected number of single-card receptacles exposed beyond said margin of said blocking wall so that they extend from said exposed single-card receptacles for a distance beyond said blocking wall;
- (e) removing said plurality of said playing cards from said exposed single-card receptacles as a group of said playing cards;
- (f) thereafter sensing and automatically communicating electrically to said controller that it is appropriate to move the dealing rack to expose additional ones of said single-card receptacles beyond said margin of said blocking wall;
- (g) in response thereto, moving said one of said dealing rack and said blocking wall a further distance relative to the other and thereby exposing another selected number of additional ones of said plurality of single-card receptacles beyond said margin of said blocking wall; and
- (h) thereafter repeating steps (d) through (g) until a desired number of groups of said playing cards have been removed from said dealing rack.

Embodiment 45. The method of embodiment 44, wherein step (f) includes sensing that at least one of said single-card receptacles exposed beyond said margin of said blocking wall has been emptied.

Embodiment 46. The method of embodiment 45 wherein said step of sensing is performed with respect to an exposed single-card receptacle that is closest to said margin of said blocking wall.

Embodiment 47. The method of embodiment 44 including the further steps of sensing that a predetermined time has passed since a group of cards has been removed, and in response thereto causing said dealing rack to move farther and thereby exposing all

- 70 -

remaining ones of said plurality of single-card receptacles beyond said margin of said blocking wall, and thereafter removing all remaining ones of said plurality of playing cards from said dealing rack.

Embodiment 48. The method of embodiment 44 including the further steps of
5 determining that a predetermined number of cards have been removed and in response thereto moving said dealing rack a further distance relative to said blocking wall, thereby exposing all remaining ones of said plurality of single-card receptacles beyond said margin.

Embodiment 49. The method of embodiment 44 including the step of keeping said
10 dealing rack in such a position with respect to said blocking wall that said blocking wall retains said ones of said playing cards in ones of said single-card receptacles not exposed beyond said margin of said blocking wall.

CLAIMS

What is claimed is:

1. A card shuffler comprising:
a deck-crib configured to contain a stack of playing cards with one card of the stack adjacent a deck support member of the deck-crib;
a dealing rack located adjacent to the deck-crib and defining receptacles, each receptacle sized to receive only a single card;
a card mover associated with the deck-crib and operable to move a single playing card from the deck-crib to a receptacle aligned with the deck-crib, the card mover including:
a primary card-contacting drive member in position to engage a surface of a playing card located adjacent to the deck support member of the deck-crib to move the single playing card toward the aligned receptacle;
an auxiliary card pusher including a card-contacting member movable reciprocally in the deck-crib toward and away from the dealing rack to move the single playing card out of the deck-crib and substantially into the aligned receptacle;
a first motor operably connected to cause movement of one of the dealing rack and the deck-crib relative to the other and to place the card mover and a receptacle into mutual alignment; and
a second motor operably connected to cause movement of the auxiliary card pusher.
2. The card shuffler of claim 1, wherein the deck support member of the deck-crib includes a card-facing surface and the card mover includes a frictional drive element protruding into the deck-crib beyond the card-facing surface of the deck support member.
3. The card shuffler of claim 2, wherein the card-contacting member protrudes into the deck-crib relative to the deck support member beyond the frictional drive element, far enough to disengage from the frictional drive element a card adjacent to the single card being moved to the receptacle.

4. The card shuffler of claim 1, further including a card presentation pusher movable between retracted and extended positions, and wherein the dealing rack defines a presentation pusher receptacle on a side of the dealing rack facing the deck-crib sized and configured to receive a portion of the card presentation pusher in the extended position.

5. The card shuffler of claim 4, including a blocking wall located adjacent a side of the dealing rack opposite the deck-crib, the blocking wall having a blocking wall margin, and wherein the dealing rack is movable to a position with respect to the blocking wall, wherein at least one receptacle is exposed beyond the blocking wall margin in a card-presenting position from which every playing card in each exposed receptacle can be slid simultaneously partially out of the dealing rack by the card presentation pusher.

6. The card shuffler of claim 5, in combination with a game table, wherein the shuffler is mounted in a partially recessed position in a top of the game table and the blocking wall margin is located at a predetermined height above the game table top.

7. The shuffler of claim 1, wherein the deck-crib comprises a card block wall and a card transfer slot proximate a bottom of the card block wall having a gap height greater than a thickness of a single playing card and less than twice the thickness of the single playing card.

8. The card shuffler of claim 1, further including a controller operably connected to the first motor, wherein the controller includes a random number generator arranged to randomly select an empty receptacle, and is programmed to cause the first motor to move one of the dealing rack and the deck-crib to align the randomly selected empty receptacle with the card mover and cause the primary card-contacting drive member and the auxiliary card pusher to move the single playing card from the deck-crib substantially into the randomly selected empty receptacle.

9. The card shuffler of claim 1, further including a card shield located alongside the dealing rack and arranged to move automatically to and remain in a first, extended position during a shuffling operation and to move to a second, retracted position thereafter.

10. The card shuffler of claim 1, wherein the dealing rack includes shelves defining the receptacles between adjacent shelves, each of the shelves defining a notch along a margin thereof, the notches jointly defining a presentation pusher receptacle in a side of the dealing rack facing toward the deck-crib.

11. A card shuffler comprising:
a deck-crib configured to contain physical playing cards arranged in a stack;
a receiving rack defining mutually adjacent receptacles, each receptacle sized to receive only a single card, the receiving rack located adjacent to the deck-crib, one of the deck-crib and the receiving rack being movable in a straight line parallel with and along the other one of the deck-crib and the receiving rack;
a card mover associated with the deck-crib and selectively operable to move ones of the playing cards from the deck-crib to selected ones of the receptacles;
a card presentation pusher located in operative proximity to the receiving rack;
a motor operably coupled to move the card presentation pusher reciprocally between retracted and extended positions relative to the receiving rack; and
a controller programmed to activate the motor to move the card presentation pusher to an extended position to contact and move at least one playing card in the receiving rack partially out of the receiving rack to enable the at least one playing card to be removed manually from the receiving rack.

12. The card shuffler of claim 11, wherein the card presentation pusher is movable to make the at least one playing card in the receiving rack enabled to be removed manually at a side of the receiving rack opposite the card mover.

13. The card shuffler of claim 11, wherein the controller is programmed, upon receipt of an input signal, to cause the receiving rack to move a selected distance to place a predetermined number of receptacles of the receiving rack into a card-presenting position in which any cards in the predetermined number of receptacles can be moved by the card presentation pusher to be made available to be manually removed simultaneously from the receiving rack.

14. A method of distributing playing cards comprising:
receiving playing cards in respective receptacles of a dealing rack, each receptacle sized to receive only a single card, the dealing rack including mutually parallel receptacles adjacent one another in a fixed array;
placing the dealing rack into a first position adjacent a blocking wall alongside a card removal side of the dealing rack;
in response to a predetermined condition, moving one of the dealing rack and the blocking wall relative to the other a distance determined by a controller to expose a selected number of receptacles beyond a margin of the blocking wall and create an open path for removal of playing cards from the exposed receptacles;
pushing the playing cards of the exposed single-card receptacles with a card presentation pusher to extend the playing cards of the exposed single-card receptacles from the exposed receptacles partially beyond the blocking wall to enable manual removal of the extended playing cards from the exposed receptacles as a group;
communicating electrically to the controller to expose additional receptacles beyond the margin by moving the one of the dealing rack and the blocking wall a farther distance relative to the other to expose another selected number of additional receptacles beyond the margin;
and
pushing the playing cards of the exposed additional receptacles with the card presentation pusher to extend from the exposed receptacles partially beyond the blocking wall.

15. The method of claim 14, further including sensing that at least one receptacle exposed beyond the margin has been emptied of an extended playing card.

16. The method of claim 15, wherein the sensing is performed with respect to an exposed receptacle closest to the margin.

17. The method of claim 14, further including sensing that a predetermined time has passed since a group of playing cards has been removed from the dealing rack, and in response thereto causing one of the dealing rack and the blocking wall to move relative to the other to expose all remaining receptacles beyond the margin.

18. The method of claim 14, further including determining that a predetermined number of cards have been removed from the dealing rack and in response thereto causing one of the dealing rack and the blocking wall to move relative to the other to expose all remaining receptacles beyond the margin.

19. The method of claim 14, further including keeping the dealing rack and the blocking wall in relative positions to retain playing cards in receptacles not exposed beyond the margin.

20. The method of claim 14, wherein placing playing cards into respective receptacles of a dealing rack comprises randomly placing playing cards into the receptacles.