

FOLDABLE VEHICLE, SYSTEM AND ADJUSTMENT ASSEMBLY THEREOF FOR ADJUSTING WIDTH OF A VEHICLE

FIELD OF THE INVENTION

[0001] The present invention generally relates to foldable/expandable vehicles and methods for folding and unfolding thereof and more particularly to width adjustment methods and systems and mechanisms for adjusting width of a vehicle.

BACKGROUND OF THE INVENTION

[0002] Foldable vehicles such as the HIRIKOTM foldable car (see link: <http://www.youtube.com/watch?v=Qy3OgZYe1ZM>), developed initially by MIT (Massachusetts Institute of Technology), are typically designed to save parking place and for easy maneuvering and parking in urban traffic. In the case of the HIRIKOTM foldable car, the folding mechanism is designed to adjust the length of the car almost by half (i.e. adjust the distance between the rear and front wheels) and optionally to also adjust its height. The length of the HIRIKOTM foldable car is adjusted by bringing the front wheels closer to the rear wheels closer together to fold the car into a folded position and farther from each other to bring the car to an unfolded position. The width of the HIRIKOTM foldable car however remains unchangeable. Since the HIRIKOTM foldable car has a small passenger(s) compartment fitting one driver passenger or more.

SUMMARY OF THE INVENTION

[0003] According to some embodiments of the invention, there is provided an adjustment assembly for changing width of a vehicle that has at least one pair of wheels, where the adjustment assembly is embedded in the vehicle and is connectable to a pair of front, middle or rear wheels thereof. The adjustment assembly includes, inter alia: (i) a foldable unit connectable to the pair of wheels of the vehicle, configured for changing its overall length along a predefined axis "Y" connecting the centers of the pair of wheels, for adjusting a distance between the pair of wheels it connects to; and (ii) a tilting unit operatively associated with the pair of wheels of the vehicle to which the foldable unit connects. The tilting unit is configured for changing angular positioning of the pair of wheels in respect to the "Y" axis, during driving of the vehicle when the vehicle is folding or unfolding.

[0004] According to some embodiments of the invention, there is provided an adjustment assembly for changing vertical size of a vehicle that has at least one pair of wheels, said adjustment assembly is embedded in said vehicle and is connectable to a pair of front, middle or rear wheels of the vehicle. The adjustment assembly comprising: an extendable/foldable unit connectable to the pair of wheels of the vehicle, said foldable unit is configured for changing its overall length along a predefined axis "Y" connecting the centers of the pair of wheels, for adjusting a distance between the pair of wheels it connects to and a tilting unit operatively associated with the pair of wheels of the vehicle to which the foldable unit connects, said tilting unit is configured for changing angular positioning of the pair of wheels in respect to the axis "Y", , said tilting unit is controlled by a controller of the vehicle.

[0005] The folding/unfolding is preformed during driving of the vehicle wherein said tilting unit and/or said foldable unit is controllable via a controller for operating thereof.

[0006] According to some embodiments of the invention the change in the angular position maintain the motion track of the wheel along a pre-defined axis.

[0007] According to some embodiments of the invention the change in the angular position of all wheels is synchronized.

[0008] According to some embodiments of the invention the extendable foldable unit is comprised of: two adjustment assemblies, each connectable to a different pair of front and rear wheels, where the two adjustment assemblies are connect to one another for coordinating and synchronizing their operation via a connecting unit.

[0009] According to some embodiments of the invention the adjustment assembly is comprised of foldable unit, which are configured to move along Y axis inward and toward each other, there by changing the distance between pair of wheels.

[0010] According to some embodiments of the invention the foldable units include adjustable members having serrated portion and sloped portion, where the adjustment assemblies are engaged at the serrated portion by a gear, such that when the wheels are tilted and driven, the gear rotate and transmit torque thereof for causing lateral departing or converging of the adjustment members.

[0011] According to some embodiments of the invention the foldable units are interconnected telescopically.

[0012] According to some embodiments of the invention the foldable units are pentagon collapsing assemblies.

[0013] According to some embodiments of the invention the adjustment assembly is further comprising security folding bottom platforms which are folding and
5 unfolding along with the wheels, wherein the platforms create continues area between each pair of wheels.

[0014] According to some embodiments of the invention the adjustment assembly is further comprising at least motor for actuating the tilting unit operation.

[0015] According to some embodiments of the invention, the adjustment assembly
10 is further comprising at least one motor for supporting the operation of the folding assemblies.

[0016] According to some embodiments of the invention the movable adjustment members movement is restricted from folding or unfolding via safety stoppers, wherein the movement restriction is controlled according to predefined rules.

[0017] According to some embodiments of the invention the tilting unit **120**
15 includes two telescopic members each including a piston, coaxially inserted and movable in cylinders.

[0018] According to some embodiments of the invention the tilting unit is mechanically connected directly to the wheels.

[0019] According to some embodiments of the invention the steering mechanism of
20 the wheels which function at the normal driving mode, is mechanically connected directly to the wheels.

[0020] According to some embodiments of the invention the telescopic members are actuated via an actuator connected to at least one engine of the vehicle for pulling
25 and pushing the pistons inside their respective cylinder.

[0021] According to some embodiments of the invention the tilting units are controlled and operated by or through the controller by electronically simultaneously controlling the movements of their pistons for changing angular positioning of the wheels.

[0022] According to some embodiments of the invention the gear functions as a
30 sensor for sensing and indicating of the positioning and width of the vehicle at each given moment, by having a mechanism associated therewith counting the pitch angle

and reporting the sensed width to the controller for enabling to control the tilting units according to the sensed current width.

[0023] According to some embodiments of the invention both the tilting units and the foldable units are actuated simultaneously via the controller using different or the same actuators for actuating each type of unit.

[0024] According to some embodiments of the invention the controller automatically executes a safety procedure of predefined rules, before starting the folding process including at least one of the following rules: (i) speed limit validation and control, ensures that the vehicle is driven within a predefined range of speeds either (ii) steering angle limit validation and control, ensuring that the steering wheel angle does not exceed a predefined limit.

[0025] According to some embodiments of the invention the adjustment assembly further comprising sensing means for measuring distance between the wheels in each pair in real time during the folding process or unfolding process. the measurements are received and processed at the controller.

[0026] According to some embodiments of the invention the wheels are tilted gradually during the folding process or unfolding process.

[0027] According to some embodiments of the invention the wheels are tilted when the vehicle is not in motion.

[0028] According to some embodiments of the invention the wheels are remain at the same titling angle during the folding process.

[0029] According to some embodiments of the invention the distance between each pair of wheels is sensed only at the starting point of the folding process and at the end of the process.

[0030] Disclosed herein is an adjustment assembly connectable to at least one pair of wheels of a vehicle, said adjustment assembly comprising:

- a) at least one tilting unit configured to change the angular position of the wheels of said pair of wheels with respect to a horizontal axis extending on a horizontal plane and between the centers of said pair of wheels, wherein the at least one tilting unit is configured to change the angular position of the wheels between a convergence tilting positioning of the wheels and a non-convergence tilting positioning of the wheels;

b) a foldable unit having at least two portions coinciding with a folding axis extending on said horizontal plane along said horizontal axis, each of the at least two portions being connected to a corresponding wheel of said pair of wheels, wherein the at least two portions of the foldable unit are configured to move laterally along the folding axis when the wheels are in the convergence tilting positioning thereof, thereby changing the distance between the wheels of said pair of wheels.

[0031] Also disclosed herein is a vehicle comprising one or more adjustment assemblies as described above.

10 BRIEF DESCRIPTION OF THE DRAWINGS

[0032] **Fig. 1** shows a top view of a system for adjusting width of a foldable vehicle, wherein the system includes, inter alia, two adjustment assemblies operatively connected to one another, configured for changing the width of the vehicle, according to some embodiments of the present invention.

15 [0033] **Fig. 2** shows a front view of one of the adjustment assemblies of the system of the vehicle, according to some embodiments of the present invention.

[0034] **Fig. 3** shows an exploded view of one of the adjustment assemblies of the system, according to some embodiments of the present invention.

20 [0035] **Figures 4A-4C** show the system in a converged and folded position, in which the rear and front wheels of the vehicle are in a convergence tilting positioning and the system is in its maximal folded position ready for opening thereof, having its safety stoppers unlocked, according to some embodiments of the invention: **Fig. 4A** shows an isometric view of the system in the converged and folded position; **Fig. 4B** shows a top view of the system in the converged and folded position; and **Fig. 4C** shows a front view of the system in the converged and folded position.

25 [0036] **Figures 5A-5C** show the system in a converged and unfolded position, in which the rear and front wheels of the vehicle are in a convergence tilting positioning and the system is still in an unfolded position ready for folding thereof, having its safety stoppers unlocked, according to some embodiments of the invention: **Fig. 5A** shows an isometric view of the system in the converged and unfolded position; **Fig. 5B** shows a top view of the system in the converged and unfolded position; and **Fig. 5C** shows a front view of the system in the converged and unfolded position.

[0037] **Figures 6A-6C** show the system in a non-converged and unfolded position, in which the rear and front wheels of the vehicle are in a non-convergence titling positioning and the system is in an unfolded position ready for driving or after unfolding thereof, having its safety stoppers locked according to some embodiments of the invention: **Fig. 6A** shows an isometric view of the system in the non-converged and unfolded position; **Fig. 6B** shows a top view of the system in the non-converged and unfolded position; and **Fig. 6C** shows a front view of the system in the non-converged and unfolded position.

[0038] **Figures 7A-7C** show the system in a non-converged and folded/constrict position, of the rear and front vehicle wheels are in a non-convergence titling positioning and the system is in a folded position ready for parking mode or after folding thereof, having its safety stoppers locked, according to some embodiments of the invention: **Fig. 7A** shows an isometric view of the system in the non-converged and folded position; **Fig. 7B** shows a top view of the system in the non-converged and folded position; and **Fig. 7C** shows a front view of the system in the non-converged and folded position.

[0039] **Fig. 8** is a flowchart, schematically illustrating a process of folding/constricting a foldable vehicle, according to some embodiments of the invention.

[0040] **Fig. 9** is a flowchart, schematically illustrating a process of unfolding/extending a foldable vehicle, according to some embodiments of the invention.

[0041] **Figures 10A-10B** show an optional configuration of the system folding/extending mechanism, according to some embodiments of the invention: **Fig. 10A** shows top view of folding/extendable mechanism in folded position; **Fig. 10B** shows a top view of folding/extending mechanism in the unfolded position;

[0042] **Figures 11A-11B** show the alternative configuration of the system folding/extending mechanism (as shown in **Figures 10A-10B**) at different tilting positions, according to some embodiments of the invention: **Fig. 11A** shows top view of folding/extending mechanism in folded (dark wheels) and unfolded (light wheels) positions and the wheels at strait position.;

[0043] **Fig. 11B** shows top view of folding/extending mechanism in folded (the wheels are shown is dark color) and unfolded (the wheels are shown in light color) positions and the wheels at tilted position.

[0044] **Figures 12A-12C** show an alternative configuration of the system folding/extending mechanism, according to some embodiments of the invention: **Fig. 12A** shows top view of folding/collapsing mechanism in folded position; **Fig. 12B** shows a top view of folding/collapsing mechanism in the unfolded position;

5 [0045] **Fig. 12C** shows a top view of folding/collapsing mechanism in different folding position, folded (the wheels are shown in dark color) and unfolded (the wheels are shown in light color) positions

[0046] **Figures 13A-13B** show configuration of the system bottom structure in the different folding position, according to some embodiments of the invention: **Fig. 13A**
10 shows top view of the system bottom structure in folded position; **Fig. 13B** shows a top view of the system bottom structure in the unfolded position;

DETAILED DESCRIPTION OF SOME EMBODIMENTS OF THE INVENTION

[0047] In the following detailed description of various embodiments, reference is made to the accompanying drawings that form a part thereof, and in which are shown
15 by way of illustration specific embodiments in which the invention may be practiced. It is understood that other embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

[0048] The present invention, in some embodiments thereof, provides systems methods and mechanisms such as adjustment assemblies for adjusting width of a
20 vehicle as well as providing a foldable vehicle having a system including one or more of these mechanisms embedded therein as part of the vehicle itself. The foldable vehicle is designed to fold by decreasing width thereof, i.e. distance between each pair of rear and front for taking up fewer parking spaces and/or for easier maneuvering through urban narrow roads.

25 [0049] The system includes one or more adjustment assemblies each is a mechanical mechanism that connects to a pair of front/rear/middle wheels of a foldable vehicle for enabling this vehicle to be folded and unfolded for changing its overall width, where the system is embedded in the foldable vehicle as integral part thereof.

[0050] According to some embodiments, the adjustment assembly connects to a
30 pair of wheels (e.g. front or rear wheels) of the vehicle and includes: (i) a foldable unit connectable to the pair wheels of the vehicle, which is configured for adjusting its overall width, for changing a distance between the pair of wheels it connects to over an

axis "Y" between the centers of the wheels; and (ii) a tilting unit operatively associated with the pair of wheels of the vehicle to which the foldable unit connects, wherein the tilting unit is configured for tilting of a single wheel or a pair of wheels (i.e. changing the angular positioning in respect to the "Y" axis) during driving of the vehicle when folded or unfolded.

[0051] The adjustment assembly is configured such that once the driver orders to fold or unfold the vehicle (depending on its condition at the time) the tilting unit and/or the foldable unit is automatically operated while the vehicle is driven in a limited speed for folding or unfolding thereof in a smooth and comfortable manner, by having the wheels gradually tilted during the slow drive (during the folding process) to one or more desired angular positions in respect to the "Y" axis and the foldable unit fold/unfold in coordination with the tilting of the wheels. Optionally, the tilting operation may be performed when the vehicle is not moving, before starting the folding process.

[0052] Optionally, the wheels are not tilted gradually, but are remain at the same tilting angle during the folding process.

[0053] The tilting unit may include extendible elements that are angularly positioning in respect to the "Y" axis, where each element may connect to a different wheel of the pair. Each extendible element (such as a telescopic member that can be folded and unfolded to change its length) connects to a separate rear/front wheel, such that once these extendible elements are actuated to extend or fold thereof, they cause the front/rear wheels to tilt to a predefined angular positioning while the vehicle (and the wheels thereof) is driven allowing the width to be changed gradually and smoothly during the drive due to the tilt of the wheels.

[0054] The tilting unit may be implemented, partly as an inner unit integrated with in the wheel, optionally using an engine.

[0055] The tilting unit may be implemented, by mechanical mechanism directly controlling the tilting on the wheels. Alternatively the tilting unit may be implemented, by electrical mechanism, using remote controller.

[0056] According to some embodiments, the foldable unit includes one or more foldable members that are laterally connected to the pair of wheels over the "Y" axis thereof, such that when the vehicle is driven and the pair of wheels are tilted by the

tilting unit, these one or more members will automatically extend or shorten and thereby allow stabilized extension or shortening of the vehicle's width.

[0057] Since mechanisms such as these can be connected to the rear and front wheels of a vehicle they can be used to adjust the width of the vehicle rather than its length (i.e. adjusting the distance between the most distal edges of the right and left sides of the vehicle rather than the distance between the most distal edges of the front and back sides of the vehicle).

[0058] According to some embodiments, the system for adjusting the width of a vehicle includes multiple adjustment assemblies: one adjustment assembly for each pair of front and rear wheels (optionally in case of a longer vehicle other middle pairs of wheels are added each may connect to a corresponding adjustment assembly).

[0059] According to some embodiments, the operation of all the adjustment assemblies of the system are controlled by a single centralized controller and can be coordinated and/or synchronized via one or more mechanical and/or electronic means. This means that the pairs of wheels can be brought closer to or farther from one another via their corresponding adjustment assemblies in a synchronized manner in which all are moved simultaneously at the same rate and in a coordinated manner.

[0060] According to some embodiments of the invention, the length of the foldable unit of each adjustment assembly can be mechanically adjusted by for instance including one or more adjustment members such as a telescopic element or by laterally moving several elements from or to each other along the "Y" axis having parts thereof engaging and/or overlapping to enable changing the overall distance between one non-engaging edge of one member to another having these edges directly or indirectly connect to each of the pair of wheels for changing the distance therebetween by their movement. The laterally moving of the adjustment members along the "Y" axis can be controlled and carried out via a mechanical transmission mechanism controlled by the controller of the system. For example, each of two adjustment members includes a serrated portion that can be laterally moved by engaging a central gear (cog wheel), the wheel can be rotated by the controller using the battery of the vehicle as a power source and the vehicle's engine to actuate a drive shaft connecting to the gear for rotating thereof. Each adjustment member connects to the gear in an opposite manner such that a rotation of the same gear will cause opposite lateral movement of the adjustment members along the "Y" axis. In this way the rotation of the gear to one direction (e.g.

counterclockwise) will cause the adjustment members to distance from each other and to the other direction (e.g. clockwise) to approach one another and thereby to increase and decrease their length and the distance between the wheels they connect to, respectively. This mechanical transmission mechanism using a gear for moving the adjustment members, is optional and any other transmission mechanism can be used.

[0061] Additionally or alternatively, the tilting unit includes multiple telescopic members each directly or indirectly connecting to a different wheel at one end thereof such that the axis of each telescopic member can be angularly changed in respect to the "Y" axis. In this way, whenever the distance between the two wheels (e.g. rear or front) is adjusted by the foldable unit (e.g. via rotation of a gear actuating thereof) the span of each of the telescopic members is changed thereby simultaneously changing the tilting angle of the wheels by pulling or pushing them inwardly or outwardly causing them to tilt thereby.

[0062] Reference is now made to **Figures 1, 4A-4B, 5A-5B, 6A-6B and 7A-7B**, schematically illustrating a system **500** for adjusting width of a vehicle in which the system **500** is embedded, according to some embodiments of the invention. This system **500** is adapted to a novel four-wheel vehicle having a pair of front wheels **10a** and **10b** and a pair of rear wheels **20a** and **20b**. The system **500** is configured for being installed as a base unit of the vehicle over which a compartment for one or more passengers (including the driver) can be seated and carried.

[0063] The system **500** includes two adjustment assemblies: a first adjustment assembly **100** and a second adjustment assembly **200** each connectable to a different pair of front and rear wheels **10a-10b** and **20a-20b**, respectively. The two adjustment assemblies **100** and **200** connect to one another for coordinating and synchronizing their operation via a connecting unit **50**, which may be controlled by a controller **300** (see **Figures 4A, 5A, 6A and 7A**). The coordinating of the two adjustment assemblies is optional each unit may be controlled separately

[0064] As illustrated in **Figures 1-7C**, each adjustment assembly **100** and **200** includes a foldable unit **110** and **210** and a tilting unit **120a** and **120b** or **220a** and **220b**, each unit connectable to the wheels **10a-10b** and **20a-20b** of the vehicle, respectively. **Figures 2-3** show the first adjustment assembly **100** in details, although the second adjustment assembly **200** includes identical or similar components associated in the same or similar manner.

[0065] The arrow 5 in all figures indicates the movement of forward direction.

[0066] According to some embodiments, the foldable unit **110** of the first adjustment assembly **100** includes two adjustment members **110a** and **110b** which are movable elements each having a serrated portion **111a** and **111b** and a sloped portion **113a** and **113b**, respectively. The serrated portions **111a** and **111b** engage a cogwheel gear **150** (shortly referred to as gear **150**) ensuring smooth transmission of movement to them by having the opposite lateral movement of the adjustment members **110a** and **110b** along the "Y" axis when the wheels are tilted and driven causing thereby the gear **150** to rotate and transmit torque thereof for causing lateral departing or converging of the adjustment members **110a** and **110b**.

[0067] As illustrated in **Figures 2-3**, the movable adjustment members **110a** and **110b** can be prevented from folding or unfolding via safety stoppers **131a** and **131b**, which in this example are protrusions configured for being inserted to corresponding recesses **141a**, **143a** on one, and corresponding recesses on the other side (not shown) for stopper **131b** where each adjustment member **110a/110b** has two recesses each for locking the adjustment members **110a/110b** in a different folded or unfolded position.

[0068] Once the driver wishes to cause the vehicle to fold for instance for parking thereof or for driving narrow roads or navigate through heavy traffic, he/she may input a signal which will be received at a controller **300** of the system **500** causing the safety locks to be released while verifying that the vehicle is driven in low-speed which may be limited by a predefined speed range. The unlocking of the safety stoppers (e.g. stoppers **131a** and **131b**) while driving the vehicle will automatically and naturally cause the two adjustment members **110a** and **110b** and **210a** and **210b** of the front and rear wheels **10a-10b** and **20a-20b**, respectively, to laterally move along their respective "Y1" and "Y2" axes, while having the tilting units **120** and **220** causing the pairs of wheels **10a** and **10b** and **20a** and **20b** to tilt inwardly as shown in **Figures 5A-5B** for instance for having them converge into a folded distance therebetween for reducing the width of the vehicle. The driving of the vehicle (in a limited low-speed) in a converging angular positioning will automatically cause the released adjustment members **110a** and **110b** to move towards one another having the gear **150** enabling their lateral movement, causing thereby the entire vehicle to fold by reducing/shortening width thereof.

[0069] Once the vehicle is folded, the protrusion stoppers **131a** and **131b** may be inserted into the other recesses of the adjustment members **110a** and **110b** and **210a** and **210b**.

[0070] It is clear to see in **Figures 2-3** that a counterclockwise rotation of the gear **150** will be caused when the adjustment members **110a** and **110b** move away from one another along the "Y" axis, causing thereby increasing of the distance between the wheels **10a** and **10b** connected thereto. A clockwise rotation of the gear **150** is caused when the adjustment members **110a** and **110b** move towards one another along the "Y" axis, causing thereby decreasing of the distance between the wheels **10a** and **10b** connected thereto.

[0071] As illustrated in details in **Figures 2-3**, the tilting unit **120** includes two telescopic members **120a** and **120b** each including a piston **122a** and **122b**, respectively coaxially inserted and movable in cylinders **121a** and **121b**. Each of the telescopic members **120a** and **120b** connects to a different wheel such as to wheels **10a** and **10b**, respectively, at one end thereof and to a connecting element such as a steering joint **190** (if connected to the front wheels **10a** and **10b** for instance) or a standard rear joint or connector **290** (if connected to the rear wheels **20a** and **20b** for instance). The steering joint **190** may be implemented as part of the vehicle steering mechanism or as separate unit for coordinating between the back and the front folding units or tilting units. The coordination between the front and the back unit is optional. The connection between each telescopic member **120a/120b** or **220a/220b** and the respective wheel **10a/10b** or **20a/20b** is via one or more connections such as through a protrusion connector **126a/126b** configured for being inserted through an opening or recess of a corresponding wheel connecting plate **160a/160b**. Each of the connecting plates **160a** and **160b** connects to wheels **10a** and **10b** respectively, via a connector **171a** and **171b**. In other embodiments non-mechanical mechanisms may be used for folding and unfolding the foldable unit and/or for coordinating the folding and unfolding of several adjustment assemblies of the system.

[0072] According to some embodiments of the present invention, the steering mechanism of the wheels which function at the normal driving mode, is mechanically connected directly to the wheels.

[0073] As shown in **Fig. 3**, each connecting plate **160a** and **160b** includes several connecting elements **161a**, **162a**, **161b** and **162b** each having an opening therein

wherein a first connecting element **161a** and **161b** is located off-center to the center of the wheel **10a** and **10b** axis "Y1", where an edge of each telescopic member such as **120a** and **120b** connects to a different first connecting element **161a** and **161b** respectively. This off-center connection allows the angular tilting of the wheels **10a** and **10b** caused by changing the length of the telescopic elements **120a** and **120b** angularly connecting thereto. Second connecting elements **162a** and **162b** are coaxial with "Y1" and connect to the edges of the adjustment members **110a** and **110b** for allowing these members to pull the wheels **10a** and **10b** towards each other along the "Y1" axis for decreasing distance therebetween and push the wheels **10a** and **10b** away from each other along the "Y1" axis for increasing distance therebetween.

[0074] The connection between each telescopic member **120a/120b** or **220a/220b** and the respective wheel **10a/10b** or **20a/20b** is such that the angle between an axis of each telescopic member **120a/120b** such as axes **Z1a**, **Z1b**, **Z2a** and **Z2b** and the wheels central axes **Y1** and **Y2** respectively: α_1 and α_2 is non-zero. In this example $\alpha_1 = \alpha_2$ and $\beta_1 = \beta_2$ and optionally $\alpha_1 = \alpha_2 = \beta_1 = \beta_2$ at each given moment. Optionally the α_1 and α_2 may not be similar. The telescopic members **120a** and **120b** and **220a** and **220b** may be actuated via an actuator connected to the engine or battery of the vehicle for instance for pulling and pushing the pistons inside their respective cylinders.

[0075] The tilting units **120** and **220** of the system **500** are controlled and operated by or through the controller **300** by, for example, electronically controlling the movements of their pistons for changing angular positioning of the wheels **10a-10b** and **20a-20b**.

[0076] According to some embodiments, the tilting units **120** and **220** are actuated via one or more actuators, e.g. via the same motor actuator powered by a separate battery or via the vehicle's battery or any other energy source.

[0077] According to some embodiments, the gear **150** can be used as a sensor for allowing sensing and indicating of the positioning and width of the vehicle at each given moment, by having a mechanism associated therewith counting the pitch angle (i.e. the number of rotations and angular positioning of the gear in respect to a predefined position thereover) and reporting the sensed width to the controller **300** of the system **500** for enabling to control the tilting units **120** and **220** according to the sensed current width.

[0078] According to some embodiments, the system **500** and vehicle it is installed in are configured such that to fold and unfold the system **500** the driver or any other passenger is required to instruct an initiation of a folding/unfolding process via an interface of the controller **300** for instance via an initiation button. Once the controller **300** receives the initiation signal for folding the vehicle (e.g. for parking) it initially executes a safety procedure in which it verifies and/or causes the vehicle to drive within a limited speed range that is non-zero but slow enough to have the wheels tilted easily for adjusting the width. Another function executed in this preliminary safety procedure, is releasing of the safety stoppers. These verifications and operations are carried out and controlled via the controller **300**. Once the safety procedure is verified and done, the controller **300** operates the tilting units **120** and **220** of the system **500** during slow drive of the vehicle forward and optionally backward, depending on the desired driving direction and system **500** definitions. Optionally the tilting can be performed before releasing safety stoppers or at the same time. The tilting optionally done gradually as the vehicle is driven and therefore there is less resistance of the wheels (due to friction between the wheels and the road), as each pair of front and rear wheels **10a-10b** and **20a-20b** is tilted in opposite angular directions to converge for folding the vehicle or to diverge for unfolding thereof. The tilting of the wheels **10a-10b** and **20a-20b** during the slow drive will cause, as mentioned above, the adjustment members **110a** and **110b** to move laterally in opposite directions away from or towards each other for respectively increasing or reducing the distance between each pair of wheels **10a-10b** and **20a-20b**. At the end of the width adjustment the controller **300** will cause the safety stoppers to lock for securing the fully folded/unfolded position.

[0079] According to some embodiments, as illustrated in **Figures 2-3**, the adjustment assembly **100** also includes safety stoppers **132a** and **132b** for locking the telescopic members **120a** and **120b** respectively in the fully unfolded and optionally also in the folded positions by being configured for being inserted into corresponding one or more recesses such as recesses **142a** and **142b** of the telescopic members **120a** and **120b**.

[0080] In alternative embodiment the gear **150** can be optionally rotated by the vehicle's engine or a separate motor to support or cause the operation of the folding or unfolding.

[0081] **Figures 4A-7C** shows the system **500** in several positions. **Figures 4A-4C** show the system **500** in a converged and folded position in respect to a forward driving direction, in which the rear and front wheels **10a-20b** of the vehicle are in a convergence titling positioning and the system **500** is in its maximal folded position, having its safety stoppers unlocked. **Figures 5A-5C** show the system **500** in a converged and unfolded position, in which the rear and front wheels **10a-20b** of the vehicle are in a convergence titling positioning and the system **500** is still in an unfolded position ready for folding thereof, having its safety stoppers unlocked. **Figures 6A-6C** show the system **500** in a non-converged and unfolded position, in which the rear and front wheels **10a-20b** of the vehicle are in a non-convergence titling positioning and the system **500** is still in an unfolded position ready for driving or after unfolding thereof, having its safety stoppers locked. **Figures 7A-7C** show the system **500** in a non-converged and folded position, in which the rear and front wheels **10a-20b** of the vehicle are in a non-convergence titling positioning and the system **500** is still in a folded position ready for parking or after folding thereof, having its safety stoppers locked.

[0082] The maximal width of the vehicle may be set according to standards and regulations of the specific geographical area as well as according to the design of the specific vehicle. In this example, the maximal width of the vehicle in the fully unfolded position is set to 1.60 meters (see **Fig. 6C**) and the minimal width in the folded position is set to 1.00 meter (see **Fig. 7C**). In other embodiments the minimum width may be set to 1.60 meters while the maximum width may be set to 2.20 meters in countries that only allow minimal four-wheel vehicle width of 1.60 meters.

[0083] In these embodiments the system **500** only allows locking onto two optional positions setting two optional vehicle's widths: a maximal one and a minimal one. However, in other embodiments the safety stoppers may fit into other additional recesses, for instance, for allowing one or more middle widths of the vehicle.

[0084] As illustrated in **Figures 1, 4A-4B, 5A-5B 6A-6B and 7A-7B**, the two adjustment assemblies **100** and **200** are connected to one another for coordinating their operations by having a drive shaft **50** connecting the two gears **150** and corresponding gear of the rear wheels (not shown) of the foldable units **110** and **210** of the two adjustment assemblies **100** and **200**. The controller **300** also coordinates its operation of the telescopic members **120a-120b** and **220a-220b** of the tilting units **120**

and **220** to ensure simultaneous and coordinated folding and unfolding of the adjustment assemblies **100** and **200**.

[0085] In other embodiments other mechanism can be applied to coordinate the adjustment assemblies such as hydraulic/pneumatic systems for controlling the pistons or a single electric motor and the like.

[0086] According to some embodiments, as illustrated in **Fig. 1**, since many countries regulations for a four-wheel vehicles require that the sides of the vehicles between the wheels will be walled, walls **11** and **12** (further shown in Figures 13A 13B) may be installed such that they can move along with the wheels **10a-20b** when having the distance therebetween adjusted, for example, by directly or indirectly connecting to the center of the wheels **10a-10b** and **20a-20b**.

[0087] According to some embodiments, the system **500** is configured for being embedded in any vehicle type such as in an electric vehicle or non-electric one having an engine, for enabling width adjustment thereof, wherein the controller **300** may be powered via the battery of the vehicle or any other energy source.

[0088] According to some embodiments, the system **500** requires no chassis to the vehicle, depending of course on the overall weight that can be achieved, which depends mainly on the weight and size of the passengers' compartment and engine/battery weight to be installed thereover.

[0089] According to some embodiments, the system **500** also includes means for limiting the steering angle (i.e. the angle of the steering wheels) during the folding and unfolding drive sessions for preventing the driver from diverting the steering wheel of the vehicle too sharply. The folding process is performed automatically not requiring the driver intervention, the driver may just stop the process in case of emergency.

[0090] According to some embodiments of the invention, the controller **300** includes one or more computerized programmable control boxes that may control other mechanical elements for controlling the pistons of the telescopic elements of the tilting unit and also for controlling the locking and unlocking or releasing of the safety stoppers, for controlling the steering angle and the driving speed during folding and unfolding of the vehicle. The controller **300**, as mentioned above, may be powered via the battery of the vehicle.

[0091] In some embodiments the width adjustment of the adjustment units of the system is done by actuating the tilting units thereof while the length adjustment of the

foldable unit is done automatically during the drive of the vehicle caused by the tilting of the wheels in respect to their "Y" axis connecting their centers. However, in other embodiments the foldable units are the ones actuated (e.g. by having a motor rotating the drive shaft connecting the gears thereof) while the tilting is done automatically due to the off-center connection of the telescopic members to the wheels or by any other means. In yet other embodiments of the invention, both the tilting units and the foldable units are actuated simultaneously via the controller using different or the same actuators for actuating each type of unit. For example, one actuator such as a drive motor may be used for rotating the drive shaft connecting the foldable units' gears, while another actuator motor can be used for tilting the wheels by pulling and pushing the pistons in and out of their corresponding cylinders. In any case, however the vehicle has to be driven in a low non-zero speed during actuation.

[0092] Reference is now made to **Fig. 8**, which is a flowchart schematically illustrating a process for folding a foldable vehicle having several adjustment assemblies as described above or in other configurations, according to some embodiments of the invention. The folding process includes first receiving an input signal at the controller of the system initiated by the driver or another user for initiating a folding drive session **61**, e.g. by having the driver pressing a folding/unfolding real or virtual button at an interface operatively associated with the controller. Once the controller receives this signal **61** it automatically executes a safety and initiation procedure **62** including at least one of the following steps: (i) speed limit validation and control, in which the controller (which may be associated with the power supply system of the vehicle) ensures that the vehicle is driven within a predefined range of speeds either by taking control over the power supply of the vehicle or by instructing the driver via the interface; and optionally (ii) steering angle limit validation and control, in which the controller (which may also be associated with the steering wheel system of the vehicle) ensures that the steering wheel angle does not exceed a predefined limit. Once the safety procedure is done and verified, the safety stoppers or any other locking mechanism that prevents folding of the vehicle are released **63** and the controller begins a coordinated tilting of the vehicles pairs of wheels **64 before or** during the slow driving of the vehicle in a forward or backward direction causing thereby the pairs of wheels to have their front wheels converge when in a forward drive and diverge when in a backward drive, which will cause the foldable unit to fold and

the distance between each pair of wheels to decrease. The distance between the wheels in each pair is optionally sensed **65** in real time via any one or more sensing mechanism such as by sensing the number of rotations done by a drive shaft mechanically connecting the adjustment assemblies of the system and/or by sensors
5 located at the foldable unit's adjustment members and the like. Optionally the wheels are tilted before locking the safety stoppers when the vehicle is not in motion.

[0093] The sensed information is received and processed at the controller or another computerized unit of the system and once a full folded position of the vehicle is identified **66** and the wheels are tilted back to a non-converged angular positioning
10 **67** such as to an angle in which the wheels are parallel to the forward driving direction, and then the safety stoppers are locked **68**. The safety limitations such as the speed and steering angle limitations may be disabled **69** to allow free normal drive of the vehicle. Optionally the wheels are tilted before locking the safety stoppers or at the same time.

[0094] According to some embodiments, the unfolding process illustrated in **Fig. 9**,
15 the unfolding process may include first receiving an input signal at the controller of the system initiated by the driver or another user for initiating an unfolding drive session **71**, e.g. by having the driver pressing a folding/unfolding real or virtual button at an interface operatively associated with the controller. Once the controller receives this signal **71** it automatically executes a similar safety and initiation procedure **72**
20 including at least one of the following steps: (i) speed limit validation and control; and optionally (ii) steering angle limit validation and control. Once the safety procedure is done and verified, the safety stoppers or any other locking mechanism that prevents unfolding of the vehicle are released **73** and the controller begins a coordinated tilting of the vehicles pairs of wheels **74 before** or during the slow driving of the vehicle in a
25 forward or backward direction causing thereby the pairs of wheels to have their front side diverge when in a forward drive and converge when in a backward drive, which will cause the foldable unit to unfold and the distance between each pair of wheels to increase. The distance between the wheels in each pair is optionally sensed **75** in real time in the same manner as it is sensed in the folding process. The sensed information
30 is received and processed at the controller or another computerized unit of the system and once a full unfolded position of the vehicle is identified **76** the wheels are tilted back to a non-converged angular positioning **77** such as to an angle in which the wheels are parallel to the forward driving direction, and then the safety stoppers are

locked **78**. The safety limitations such as the speed and steering angle limitations may be disabled **79** to allow free normal drive of the vehicle.

[0095] **Figures 10A-10B** show an optional configuration of the system folding/extending mechanism, according to some embodiments of the invention: **Fig.**

5 **10A** shows top view of folding/extending mechanism in folded position; **Fig. 10B** shows a top view of folding/extending mechanism in the unfolded position. The folding/extending mechanism according to this embodiment is comprised of two arms 810A, 810B rotatably connected one side to the vehicle front edge and on the other side to the front wheels, 10a, 10b, via hinges 880A,B. The hinges are also connected to
10 bar 870a,b which connects an extendable rods assembly 820a,b. The extendable rods assembly 820a,b is optionally driven by motor 860 through piston 850. The principle operation of the folding/extending mechanism is equivalent to the first solution in Figures 1-7, the wheels are tilted by motor driven tilting mechanism or engine as described in the first solution, (not shown in these figures) causing by friction force, all
15 the extendable/folding parts to move laterally in opposite directions away from or towards each other for respectively increasing or reducing the distance between each pair of wheels **10a-10b**.

[0096] **Figures 11A-11B** show the alternative configuration of the system folding/extending mechanism at different tilting positions, according to some
20 embodiments of the invention: **Fig. 11A** shows top view of folding/extending mechanism in folded position and the wheels at strait position.;

[0097] **Fig. 11A** shows top view of folding/extending mechanism in folded position and the wheels at tilted position.

[0098] **Figures 12A-12C** show another alternative configuration of the system folding/extending mechanism, according to some embodiments of the invention: **Fig.**
25 **12A** shows top view of folding/extending mechanism in folded position; **Fig. 12B** shows a top view of folding/ extending mechanism in the unfolded position

[0099] **Fig. 12C** shows a top view of folding/extending mechanism in different folding position – folded and unfolded positions

30 **[00100]** The folding/extending mechanism according to this embodiment is comprised of two pentagon folding assemblies 1012a,b connected on one end to the edge of the vehicle front 1000 and on the end side to the front wheels, 10a , 10b.,via hinges. The hinges are also connected to bars 1020a, 1020b, which are rotatably

interconnected by bar 1018. Through the folding process, the pentagon folding assemblies are folded as seen in Fig. 12A and the bars 1020a, 1020b move laterally in opposite directions away from or towards each other for respectively increasing or reducing the distance between each pair of wheels **10a-10b**.

5 **[00101]** The principle operation of the folding/extending mechanism is equivalent to the first solution in Figures 1-7, the wheels are tilted by motor driven tilting mechanism or an engine as described in the first solution, (not shown in these figures) causing by friction force all the extendable parts to fold or move laterally in opposite directions away from or towards each other for respectively increasing or reducing the distance
10 between each pair of wheels **10a-10b**.

[00102] **Figures 13A-13B** show configuration of the system bottom structure in the different folding position, according to some embodiments of the invention: **Fig. 13A** shows top view of the system bottom structure in folded position; **Fig. 13B** shows a top view of the system bottom structure in the unfolded position.

15 **[00103]** According to this embodiment, the folding/extending mechanism, is further applied on safety bottom platforms 2010,a,b, which fold and unfold along with the wheels, 10a,b, and 20 a, b Each safety bottom platforms is comprised of two surfaces fixed surfaces 2050 a, b and movable surfaces 2040 a, b which are slidable one above the other, constructing foldable platform. Optionally are integrated wheels covers 2020,
20 which move as one part with the surfaces.

[00104] Many alterations and modifications may be made by those having ordinary skill in the art without departing from the spirit and scope of the invention. Therefore, it must be understood that the illustrated embodiment has been set forth only for the purposes of example and that it should not be taken as limiting the invention as defined
25 by the following invention and its various embodiments and/or by the following claims. For example, notwithstanding the fact that the elements of a claim are set forth below in a certain combination, it must be expressly understood that the invention includes other combinations of fewer, more or different elements, which are disclosed in above even when not initially claimed in such combinations. A teaching that two
30 elements are combined in a claimed combination is further to be understood as also allowing for a claimed combination in which the two elements are not combined with each other, but may be used alone or combined in other combinations. The excision of

any disclosed element of the invention is explicitly contemplated as within the scope of the invention.

[00105] The words used in this specification to describe the invention and its various embodiments are to be understood not only in the sense of their commonly defined meanings, but to include by special definition in this specification structure, material or acts beyond the scope of the commonly defined meanings. Thus if an element can be understood in the context of this specification as including more than one meaning, then its use in a claim must be understood as being generic to all possible meanings supported by the specification and by the word itself.

[00106] The definitions of the words or elements of the following claims are, therefore, defined in this specification to include not only the combination of elements which are literally set forth, but all equivalent structure, material or acts for performing substantially the same function in substantially the same way to obtain substantially the same result. In this sense it is therefore contemplated that an equivalent substitution of two or more elements may be made for any one of the elements in the claims below or that a single element may be substituted for two or more elements in a claim. Although elements may be described above as acting in certain combinations and even initially claimed as such, it is to be expressly understood that one or more elements from a claimed combination can in some cases be excised from the combination and that the claimed combination may be directed to a sub-combination or variation of a sub-combination.

[00107] Insubstantial changes from the claimed subject matter as viewed by a person with ordinary skill in the art, now known or later devised, are expressly contemplated as being equivalently within the scope of the claims. Therefore, obvious substitutions now or later known to one with ordinary skill in the art are defined to be within the scope of the defined elements.

[00108] The claims are thus to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, what can be obviously substituted and also what essentially incorporates the essential idea of the invention.

[00109] Although the invention has been described in detail, nevertheless changes and modifications, which do not depart from the teachings of the present invention, will be evident to those skilled in the art. Such changes and modifications are deemed to come within the purview of the present invention and the appended claims.

[00110] Throughout this specification, unless the context requires otherwise, the word "comprise", and variations such as "comprises" and "comprising", will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

- 5 **[00111]** The reference to any prior art in this specification is not, and should not be taken as, an acknowledgment or any form of suggestion that the prior art forms part of the common general knowledge in Singapore.

CLAIMS

1. An adjustment assembly connectable to at least one pair of wheels of a vehicle, said adjustment assembly comprising:
 - 5 c) at least one tilting unit configured to change the angular position of the wheels of said pair of wheels with respect to a horizontal axis extending on a horizontal plane and between the centers of said pair of wheels, wherein the at least one tilting unit is configured to change the angular position of the wheels between a convergence tilting positioning of the wheels and a non-convergence tilting positioning of the wheels;
 - 10 d) a foldable unit having at least two portions coinciding with a folding axis extending on said horizontal plane along said horizontal axis, each of the at least two portions being connected to a corresponding wheel of said pair of wheels, wherein the at least two portions of the foldable unit are configured to move laterally along the folding axis when the wheels are in the convergence tilting positioning thereof, thereby changing the distance between the wheels of said pair of wheels.
2. The adjustment assembly of claim 1 wherein the change in the angular position of all wheels is synchronized.
- 20 3. The adjustment assembly of claim 2 wherein the change in angular position is equal and opposite in the two wheels of the pair.
4. The adjustment assembly of claim 1, wherein the foldable unit includes adjustment members having serrated portion and sloped portion, wherein the adjustment members are engaged at the serrated portion by a gear, such that when the wheels are in the convergence tilting positioning and the vehicle is driven, the gear rotate and transmit torque thereof for causing lateral departing or converging of the adjustment members; the movement of the adjustable members being optionally restricted via safety stoppers; or the gear optionally comprises a sensor for indicating the width of said assembly.
- 25 5. The adjustment assembly of claim 1, wherein the foldable unit comprises a telescopic element or a pentagon collapsing assembly.
- 30 6. The adjustment assembly of claim 1 further comprising bottom platforms which are folding and unfolding correspondingly to the change in distance between the wheels.

7. The adjustment assembly of claim 1 wherein the tilting unit is associated with a motor configured for changing the angular position of the wheels.
8. The adjustment assembly of claim 1 wherein the foldable unit is associated with a motor configured for changing said distance between the wheels.
- 5 9. The adjustment assembly of claim 1 wherein the tilting unit includes two telescopic members each including a piston, coaxially inserted and movable in cylinders.
10. The adjustment assembly of claim 1, wherein both the tilting unit and the foldable unit are simultaneously actuated.
11. The adjustment assembly of claim 1, further comprising sensing means for
10 measuring distance between the wheels.
12. The adjustment assembly of claim 1, wherein the angular position of the wheels is changed gradually while the distance between the wheels is being changed.
13. A vehicle comprising one or more adjustment assemblies of claim 1.
14. The vehicle of claim 13, comprising a controller configured for controlling at least
15 one of:
- (i) the tilting unit;
 - (ii) the foldable unit;
 - (iii) the execution of a safety procedure of predefined rules, before
activating the adjustment assembly, the rules including at least one
20 of the following: (i) speed limit validation and control, and (ii)
steering angle limit validation and control.
15. The vehicle of claim 14, comprising two adjustment assemblies each connectable to a different pair of wheels, wherein the two foldable units are coupled to and jointly operate with one another.
- 25 16. The vehicle of claim 13, comprising a controller configured to control the tilting unit, to change the angular position of the wheels to tilt the wheels into the convergence tilting positioning thereof when the distance between the wheels is to be changed, and to change the angular position of the wheels to tilt the wheels into the non-convergence tilting positioning thereof when the distance between the wheels is to be kept constant for normal
30 driving of the vehicle.