

FLEXIBLE PRINTED CIRCUIT HARNESS DEVICE AND
FLEXIBLE PRINTED CIRCUIT USED THEREOF

5 The present invention concerns an FPC harness device including a flexible printed circuit board (FPC) which is formed in order to transmit a plurality of signals at high speed, and an FPC used therefor.

BACKGROUND OF THE INVENTION

10 Various types of connecting means are used to connect computer-related devices. For example, harness devices using twisted-pair cables have conventionally been used for the mutual interconnection of devices such as disk arrays and work stations. Twisted-pair cables are flat multi-core conductor cables which have twisted parts in
15 which pairs of lines are twisted in helical form in order to prevent crosstalk, and fused parts in which the lines are fused together at appropriate intervals along the direction of length.

20 In most cases, the connection of twisted-pair cables to connectors is accomplished by pressure-welding connections. In this case, fused parts of the twisted-pair cable are accommodated in the pressure-welding slots of pressure-welding terminals installed on the connector.

25 However, in the case of conventional harness devices using twisted-pair cables, there is a need for improvement in the following respects: first of all, as was described above, the connection of twisted-pair cables is accomplished by means of the fused parts of the cables. However, because of the need for impedance control, the
30 distances between these fused parts cannot be shortened. Accordingly, an arbitrary length of the twisted-pair cable employed cannot be used, so that it is necessary in some cases to use an unnecessarily long length of cable, which is not appropriate for compact mounting.

35 Secondly, since the individual twisted pairs of a twisted-pair cable do not have an integral structure, handling is difficult, e.g., the twisted pairs may become entangled with surrounding objects, etc.

Thirdly, conventional twisted-pair cables are terminated with pressure-welding type connectors. Such pressure-welding connectors are relatively expensive, so that the harness device as a whole also becomes expensive.

5 Accordingly, there is a need for a harness device which can be inexpensively constructed while at the same time allowing easy assembly and connection.

The present invention can be used with computer-related devices, etc. An FPC harness device including an
10 FPC is provided. The FPC (Flexible Printed Circuit) is a two-sided FPC, i.e., an FPC which has two layers of circuit patterns. The intermediate parts of the circuit patterns are substantially parallel, and are shifted in the transverse direction, i.e., in the pitch direction.

15 Accordingly, by using the FPC of the present invention, it is possible to realize compact electrical connections for differential signal transmission between computer-related devices, in which crosstalk is prevented while a high impedance is maintained. Furthermore, the
20 FPC harness device of the present invention also has economic merit in that the manufacture of the connectors and the assembly of the harness device can be accomplished relatively inexpensively. In addition, since the connectors are mechanically connected by an FPC, handling
25 is easy, and since the intermediate parts of the FPC are reinforced by the conductors of the circuit patterns, the FPC is resistant to bending. Moreover, by selecting the FPC and circuit patterns used, different types of connectors can be effectively connected to each other, and
30 the harness device can also be used in applications involving frequent movement of both connectors, so that there is an extremely high degree of freedom.

The object of the present invention is to provide an FPC harness device wherein an FPC is used in the device,
35 which permits compact connections to be made between computer-related devices while preventing crosstalk and maintaining an appropriate impedance.

The present invention provides an FPC harness device comprising an FPC with circuit patterns formed on both surfaces, and a pair of connectors mounted on the FPC at the opposed ends on one surface, wherein at least the
5 intermediate portions of the respective conductors of the upper and lower circuit patterns of the FPC extend substantially in the same direction and are shifted in the transverse direction from a back-to-back position.

Furthermore, the present invention also provides an
10 FPC with upper and lower circuit patterns in two layers each having a plurality of conductors, wherein the FPC has connectors mounting portions formed on the FPC at the opposed ends on one surface thereof, with the connector mounting portions being mutually electrically connected by
15 the conductors; and at least the intermediate portions of the respective conductors of the upper and lower circuit patterns of the two-sided FPC extend substantially in the same direction and are mutually shifted in the transverse direction from a back-to-back position.

The FPC harness device of the present invention has
20 an FPC and connectors which are connected to the FPC. The FPC is a two-sided FPC, and is constructed so that the conductors forming the circuit patterns (which include circuit patterns with a two-layer structure) extend
25 substantially parallel to each other within the respective layers and between the layers. The respective conductors of the first layer extend in the direction of length while maintaining positions that are shifted to one side in the transverse direction with respect to the respective
30 conductors of the second layer.

An embodiment of the invention will now be described by way of example with reference to the accompanying drawings in which:

Figure 1 is plan view of the FPC harness of the
35 present invention.

Figure 2 is a side view of the FPC harness shown in Figure 1.

Figure 3 is a plan view showing one side of the FPC harness illustrating the conductor pattern on side A as identified in Figure 2. For the purposes of illustration, the top surface in this view is assumed to be transparent so that the conductor patterns are visible.

Figure 4 is a plan view showing the opposite side of the FPC harness illustrating the conductor pattern on side B as identified in Figure 2. For the purposes of illustration, the top surface in this view is assumed to be transparent so that the conductor patterns are visible.

Figure 5 is a cross-sectional view taken along line 5-5 of Figure 3 showing the conductors in a first end part of the harness.

Figure 6 is a cross-sectional view taken along line 6-6 of Figure 3 showing the conductors in an intermediate part of the harness.

Figure 7 is a cross-sectional view taken along line 7-7 of Figure 3 showing the conductors in a second end part of the harness.

Figures 1 and 2 show the FPC harness device 10 of the present invention. FPC harness device 10 has a first connector 30, a second connector 40, and an FPC (flexible printed circuit) 50 which electrically connects the first and second connectors 30 and 40. As was described above, the FPC 50 is a flexible printed circuit which has circuit patterns on both its upper and lower faces. For clarity, these circuit patterns are not shown in Figure 1. As is shown in Figure 1, the FPC 50 is formed so that it corresponds to the widths of the first connector 30 and second connector 40, with the portion of the FPC 50 between the connectors being formed in a substantially trapezoidal shape. Furthermore, as is shown in Figure 2, reinforcing plates 61 and 62 are installed at the respective positions of the first connector 30 and second connector 40. These reinforcing plates 61 and 62 are formed from a heat-resistant material such as a glass-added epoxy material, and are bonded to the FPC 50. The reinforcing plates 61 and 62 facilitate the attachment of

the respective connectors and smooth the bending of the FPC 50. Furthermore, the reason that the surfaces of the FPC 50 to which the reinforcing plates 61 and 62 are bonded are on opposite sides of the FPC 50 is that the contacts of the first and second connectors 30 and 40 have different forms (as will be described later).

The contacts of the first connector 30 have post-form tines or through hole solder tails 31. These tines 31 are inserted into through-holes (first connector connecting parts) 51 formed in the FPC 50 (see Figure 3), and are connected thereto by soldering. As a result, the first connector 30 is fastened and connected to the FPC 50. Meanwhile, the contacts of the second connector 40 are soldered to pads (second connector connecting parts) 52 formed on the FPC 50 (see Figure 3). These pads are typically referred to as surface mount solder pads. As a result, the second connector 40 is fastened to the FPC 50.

Figure 3 and 4 show a see-through view from one side (side A in Figure 3) of the circuit patterns formed in two layers on the FPC 50 of the present invention. Of the two layers of circuit patterns, the upper-side circuit pattern, i.e., the circuit pattern on side A in Figure 2, is shown in Figure 3. Each of the conductors (copper foil conductors) 20a forming the circuit pattern has a first end part 21a which extends from the corresponding through-hole 51 in a direction substantially perpendicular to the direction of length of the rows in which the through-holes 51 are arranged, an intermediate part 22a which extends diagonally from the first end part 21a, and a second end part 23a which extends from said intermediate part 22a toward the second connector 40 in substantially the same direction as the first end part 21a. Each second end part 23a is connected to a pad 52a in the front row of pads 52. Furthermore, the pads 52b in the rear row of pads 52 are connected to through-holes 53, and are electrically connected with the circuit pattern on the lower side of the FPC 50, i.e., the circuit pattern on side B in Figure 2 (as will be described hereafter).

Figure 4 shows the lower-side circuit pattern of the two layers of circuit patterns, i.e., the circuit pattern on side B in Figure 2. As in the case of the conductors 20a, each of the conductors 20b forming the circuit pattern has a first end part 21b, intermediate part 22b and second end part 23b. The respective first end parts 21b, intermediate parts 22b and second end parts 23b extend parallel to the respective first end parts 21a, intermediate parts 22a and second end parts 23a of the upper-side circuit pattern. The second end parts 23b are connected to the upper-side circuit pattern via the through-holes 53, and are electrically connected to pads 52b in the rear row of the pads 52.

Figures 5, 6 and 7 are respective part cross-sectional views of the arrangement of the circuit patterns in the first end parts 21a and 21b, intermediate parts 22a and 22b, and second end parts 23a and 23b. The conductors 20a and 20b are installed at an appropriate pitch (interval) on both surfaces of a polyimide base 24, and are covered by respective polyimide covering layers 25a and 25b.

Figures 5 and 7 show respective sectional views of the first end parts 21a and 21b and second end parts 23a and 23b located near the first and second connectors 30 and 40. As is shown in Figures 5 and 7 and in Figures 3 and 4, the conductors 20a and 20b are installed at a greater pitch in the first end parts 21a and 21b than in the second end parts 23a and 23b.

In the second end parts 23a and 23b, the conductors 20a and 20b are arranged substantially back-to-back in order to facilitate connection with the second connector 40. On the other hand, in the first end parts 21a and 21b and intermediate parts 22a and 22b, the conductors 20a and 20b are shifted in the transverse direction by a substantially equal pitch, as shown in Figures 5 and 6. As a result, the capacitance between conductors is uniformly increased, so that the impedance can be set at a uniform and relatively high value.

Next, one example of the operation of the FPC harness device of the present invention will be described. S1 through S3 and G1 through G3 in Figures 5, 6 and 7 indicate that the respective conductors are for signal use (S1 through S3) or ground use (G1 through G3). In this case, differential transmission is performed using the corresponding pairs of conductors S1 and G1, S2 and G2, and S3 and G3 (hereafter indicated as S1 and G1, etc.). In the second end parts 23a and 23b, as is shown in Figure 7, S1 and G1, etc., are disposed back-to-back. As a result, crosstalk is prevented. Meanwhile, in the first end parts 21a and 21b and intermediate parts 22a and 22b, as is shown in Figures 5 and 6, S1 and G1 are shifted in the transverse direction. Accordingly, crosstalk is prevented while a high impedance is maintained.

Returning to Figures 1 and 2, the first connector 30 and second connector 40 are attached with their engagement surfaces facing the same side of the FPC 50. Since the FPC 50 is flexible, the first and second connectors 30 and 40 can be oriented in any desired direction and engaged with mating connectors. In this case, since the FPC is installed in a bent position, the FPC is subjected to a bending load. Since the intermediate parts 22a and 22b are shifted in the transverse direction, i.e., in the pitch direction, as shown in Figure 6, the mechanical strength with respect to such a bending load is improved compared to that obtained in the case of a back-to-back configuration such as that shown in Figure 7.

A preferred embodiment of the present invention has been described above. However, the preferred embodiment does not limit the present invention; various modifications and changes could be made by a person skilled in the art.



- 8 -

CLAIMS:

1 A flexible printed circuit harness device comprising a flexible printed circuit with circuit patterns formed on both surfaces, and connectors mounted
5 on the flexible printed circuit at opposite ends, characterized in that:

at least the intermediate portions of the respective conductors of the upper and lower circuit patterns of said flexible printed circuit extend substantially in the same
10 direction and are shifted in the transverse direction from a back-to-back position.

2. The flexible printed circuit harness device of claim 1 in which the conductors on each surface include first and second end portions joined by said intermediate
15 portions, conductors in one of said first and second end portions being shifted in the transverse direction from a back-to-back position.

3. The flexible printed circuit harness device of claim 1 in which one of said connectors includes contacts
20 having through hole leads and the other of said connectors includes contacts with surface mount leads.

4. The flexible printed circuit harness device of claim 3 wherein the contacts having through hole leads are positioned in four rows in one connector and the contacts
25 with surface mount leads are positioned in two rows in the other connector.

5. The flexible printed circuit harness device of claim 1 including reinforcing plates bonded to the flexible printed circuit adjacent each connector to
30 improve the resistance of the flexible printed circuit to bending so that the harness device can be used in applications involving frequent movement of both connectors.

6. The flexible printed circuit harness device of
35 claim 1 wherein one connector is laterally offset relative to the other connector, the intermediate portions of the respective conductors being angled relative to each connector.



- 9 -

7. The flexible printed circuit harness device of claim 1 wherein the portion of the flexible printed circuit between the connectors is formed in a substantially trapezoidal shape.

5 8. The flexible printed circuit harness device of claim 1 wherein the intermediate portions of the conductors are shifted in the transverse direction from a back-to-back position by a sufficient amount to prevent crosstalk and maintain a high impedance.

10 9. The flexible printed circuit harness device of claim 1 wherein the connectors are mounted on the same side of the flexible printed circuit.

15 10. The flexible printed circuit harness device of claim 1 wherein the conductors forming flexible printed circuit patterns extend substantially parallel to each other on each surface and substantially parallel to conductors on the other surface.