

(19) World Intellectual Property
Organization
International Bureau



WIPO | PCT



(10) International Publication Number

WO 2022/216471 A8

(43) International Publication Date
13 October 2022 (13.10.2022)

(51) International Patent Classification:

A62C 31/28 (2006.01) B05B 15/65 (2018.01)
A62C 35/68 (2006.01)

(74) Agent: CHIONCHIO, John, A. et al.; Ballard Spahr LLP,
1735 Market Street, 51st Floor, Philadelphia, PA 19103
(US).

(21) International Application Number:

PCT/US2022/022154

(22) International Filing Date:

28 March 2022 (28.03.2022)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

63/171,103 06 April 2021 (06.04.2021) US

(71) Applicant: VICTAULIC COMPANY [US/US]; 4901
Kesslersville Road, Easton, PA 18040 (US).

(72) Inventors: BARBOUR, Nicholas; 219 W. Pumping Sta-
tion Road, Quakertown, PA 18951 (US). MADARA, Scott,
D.; 309 Meyer Road, Nazareth, PA 18064 (US). BOW-
MAN, Matthew, A.; 2215 Donald Street, Palmer, PA
18045 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, IT, JM, JO, JP, KE, KG, KH,
KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA,
MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: FITTING AND GASKET




FIG. 1

(57) Abstract: A fitting has a conduit with a bore defined by a surface facing an axis coaxially located with respect to the bore. The surface may have three portions including a conical portion located proximate to the inlet of the conduit, a threaded portion located proximate to the outlet of the conduit and a cylindrical portion located between the conical and threaded portions. A gasket is positioned within the conduit. The gasket has an outer surface and an inner surface facing the axis. The gasket inner surface has angularly oriented lands. One of the lands faces the outlet and is engaged by a threaded component received by the threaded portion. Engagement between the component and the land compresses the gasket radially outwardly and longitudinally within the conduit. An angularly oriented shoulder guides the gasket into a redirection space defined by the conical portion (when present) as it deforms.

[Continued on next page]

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

(48) Date of publication of this corrected version:

03 August 2023 (03.08.2023)

(15) Information about Correction:

see Notice of 03 August 2023 (03.08.2023)