



G00002

1



159159

DESCRIPTION

MAGNETIC CIRCUIT FOR LOUDSPEAKER, AND LOUDSPEAKER USING THE SAME

5

TECHNICAL FIELD

The present invention relates to a magnetic circuit used in various acoustic apparatus, and a loudspeaker using the magnetic circuit.

10

BACKGROUND ART

A prior art of similar technology will be described with reference to Fig. 3 and Fig. 4.

Fig. 3 is a half-sectional view showing a configuration of a conventional loudspeaker, and Fig. 4 is an enlarged sectional view of a configuration of a yoke that is an essential component.

In Fig. 3, magnetic circuit A comprises yoke 1 comprising cylindrical peripheral portion 1a and bottom yoke 1b, magnet 2, and top plate 3. Also, the bottom yoke 1b is provided with recess 1c at a top surface as shown in an enlarged view in Fig. 4. The recess 1c is formed to prevent an adhesive used for bonding the magnet 2 and the bottom yoke 1b from getting into magnetic gap 1d.

Audio signal is input to voice coil 4 inserted into the magnetic gap 1d, to drive diaphragm 6 via the voice coil 4. The diaphragm 6 is held by a peripheral portion fixed on a frame and damper 7.

Generally, the cylindrical peripheral portion 1a of the yoke and the bottom yoke 1b of the yoke are formed of plate members having same thickness and are integrally bonded or welded.

Recently, there is an increasing trend of small-sized and weight reduction even in the field of various acoustic apparatus, and loudspeakers are also required to be smaller in size and higher in efficiency. Accordingly, a neodymium magnet having higher magnetic energy as compared with ferrite magnet is already employed as the magnet 2, but with miniaturization of the

magnetic circuit A, loudspeakers are required to be further enhanced in efficiency, and this becomes an important problem to be solved. For enhancing the loudspeaker efficiency, it is indispensable to improve the efficiency of the magnetic circuit.

5 In a conventional magnetic circuit, as described above, since the yoke is made of materials having the same thickness, magnetic saturation occurs at the bonded portion of the cylindrical peripheral portion 1a and the bottom yoke 1b and at the bent portion shown in Fig. 4. In order to prevent this problem, the materials for the yoke should have a sufficient thickness in accordance with the
10 characteristics of the magnet. As a result, the yoke is increased in weight. In addition, as the recess 1c is formed in the bottom yoke 1b, the sectional area of the yoke decreases at the portion, and therefore, it is necessary to use more thicker plate to compensate the decrease.

 The present invention aims to provide a light-weight, high-efficiency
15 magnetic circuit for loudspeakers, and a loudspeaker using the circuit.

DISCLOSURE OF THE INVENTION

 A magnetic circuit of the present invention uses a yoke of which an average thickness of a bottom yoke is greater than an average thickness of a
20 cylindrical peripheral portion of the yoke. The magnetic circuit of the present invention comprises the yoke, a magnet bonded to the bottom yoke, and a top plate bonded to the magnet, the top plate forms a magnetic gap with the cylindrical peripheral portion in between. According to the configuration of the present invention, magnetic saturation in the bottom yoke can be decreased, and an
25 efficiency of the magnetic circuit can be increased. The increase of the efficiency contributes to improve characteristics and efficiency of the loudspeaker using the magnetic circuit of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

30 Fig. 1 is a side half-sectional view of a loudspeaker in one embodiment of the present invention.

Fig. 2A is an enlarged view of a yoke of the loudspeaker in one embodiment of the present invention.

Fig. 2B is a plan view of the yoke.

Fig. 3 is a side half-sectional view of a conventional loudspeaker.

5 Fig. 4 is an enlarged view showing a configuration of the conventional yoke.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

A magnetic circuit of the present invention uses a yoke of which a
10 thickness of a bottom yoke is greater than a thickness of the cylindrical peripheral portion of the yoke. The magnetic circuit of the present invention comprises the yoke, a magnet bonded to the bottom yoke, and a top plate bonded to the magnet, the top plate forms a magnetic gap with the cylindrical peripheral portion in between. According to the present invention, it is possible to decrease a magnetic
15 saturation in the bottom yoke and to improve the efficiency of the magnetic circuit. Consequently, an usage the magnetic circuit of the present invention contributes to improve the loudspeaker efficiency.

Also, in another preferred embodiment of the present invention, a yoke is formed as an integrated member in which a bottom portion and a cylindrical
20 peripheral portion are formed as separate members and integrated by a caulking. Since the bottom yoke and the cylindrical peripheral portion are formed as separate members, each of them has a simple shape and can be easily manufactured by forging. Accordingly, it is possible to lower the cost of die by simplifying the die structure and to improve productivity.

25 Also, in the present invention, the bottom yoke is thick enough so that magnetic saturation does not occur at a portion close to a recess provided adjacent to an outer peripheral surface of the yoke. Accordingly, it is possible to avoid an generation of magnetic saturation at the peripheral portion of the bottom yoke where magnetic saturation is liable to occur, while preventing the entire bottom
30 yoke from increasing in thickness. As a result, the magnetic efficiency can be improved while suppressing the increase in weight of the magnetic circuit.

Further, in the present invention, a sectional area of the bonded portion of the bottom yoke and the peripheral cylindrical portion is made nearly equal to or larger than a sectional area of the peripheral cylindrical portion to prevent the generation of magnetic saturation in the bottom yoke.

5 Also, in the present invention, a bent portion of a yoke periphery has a curved surface, eliminating an edge portion at which magnetic saturation is liable to occur. Particularly, an outside portion of a back surface of the recess for preventing adhesive from getting into the magnetic gap is formed by bending. Since the portion at the back of the recess where magnetic saturation is liable to
10 occur is increased in thickness by bending, it is possible to reduce the weight of the magnetic circuit without increasing the thickness of the entire bottom yoke, while avoiding the generation of magnetic saturation.

Further, a loudspeaker of the present invention uses the magnetic circuit of the present invention described above. Thus, it is possible to provide a small-
15 sized, light-weight loudspeaker which assures high sound quality and excellent efficiency.

The preferred embodiments of the present invention will be described in the following with reference to Fig. 1 - Fig. 2B. In the description, the same
20 components as those in the prior art are given the same reference numerals, and the description is omitted.

Preferred Embodiment 1

Fig. 1 is a half-sectional view showing a configuration of a loudspeaker in
25 one preferred embodiment of the present invention. Fig. 2A is an enlarged view showing a configuration of a yoke, that is an essential part. Fig. 2B is a plan view of the yoke.

Only the differences from the prior art will be described in the following. In the present preferred embodiment, a thickness of cylindrical peripheral portion
30 10a of yoke 10 forming magnetic circuit B is made greater than a thickness of bottom yoke 10b. That is, in the present preferred embodiment, the sectional area

of a portion of the bottom yoke 10b where magnetic flux flow is equal to or larger than that of the cylindrical peripheral portion 10a.

To describe it in detail, in the present preferred embodiment, as shown in Fig. 2, the bottom yoke 10b at the back surface of recess 10c is formed thicker than the other portions in order to prevent magnetic saturation in the bottom yoke 10b below the recess 10c.

As described earlier, the recess 10c has a ring shape so as to prevent adhesives used to bond the magnet 2 and the bottom yoke 10b from getting into the magnetic gap 10d. It is desirable, considering a production cost, to form the recess 10c simultaneously when the bottom yoke 10b is forged, but magnetic permeability of the bottom yoke 10b, a magnetic material, may be deteriorated due to forging compression. In that case, the deterioration of magnetic permeability cause the generation of magnetic saturation around a portion below the recess 10c. In order to prevent this, the thickness of the bottom yoke 10b is made equal to or greater than the thickness of the cylindrical peripheral portion 10a, assuring a thickness enough to prevent the generation of magnetic saturation at a portion below the recess 10c, and further, it is intended to improve the magnetic efficiency.

Also, in the present preferred embodiment, the bottom yoke 10b and the cylindrical peripheral portion 10a are integrated by caulking, thereby preventing the lowering of magnetic efficiency. Further, an area of the bonded portion of the bottom yoke 10b and the cylindrical peripheral portion 10a is nearly same as the sectional area of the cylindrical peripheral portion 10a, thereby preventing the lowering of magnetic efficiency.

Also, the bottom yoke 10b has side wall 10e to assure a sufficient height so that voice coil 4 is not damaged by a collision with the bottom yoke 10b due to a large amplitude of the voice coil 4 when a high level of input is applied to the loudspeaker. A thickness of a portion of the bottom yoke 10b connecting to the side wall 10e is also made thick enough to make a sectional area equal to or larger than the sectional area of the cylindrical peripheral portion 10a. Thus, the magnetic saturation in the side wall portion is prevented and the magnetic efficiency is improved.

Further, in the present preferred embodiment, it is configured in that bend portion 10f at the periphery of the bottom yoke 10b has a curved surface to improve the magnetic efficiency, and the bend portion 10f is positioned below the recess 10c. According to this configuration, it is not necessary to increase the thickness of the bottom yoke 10b excessively in order to prevent the magnetic saturation in a portion below the recess 10c. As a result, it is possible to provide a magnetic circuit improved in efficiency while suppressing the increase of yoke weight.

To confirm the effects of the present invention, loudspeakers were manufactured according to the conventional technology and the present preferred embodiment and compared. The voice coil of the loudspeaker is 25mm in diameter, and the loudspeaker is 16cm in diameter. The results of measurements of the magnetic flux density and sound pressure level of each of the loudspeakers manufactured are shown in Table 1.

Table 1

	Present invention	conventional technology
Magnetic flux density (Tesla)	0.835	0.797
Sound pressure level (dB)	87.0	86.5

As is apparent from Table 1, as compared with the loudspeaker of conventional structure, with the loudspeaker of the present invention, increase of the magnetic flux density and sound pressure level are observed, and it has been confirmed that it is possible to provide a loudspeaker with a magnetic circuit of higher magnetic efficiency and also improved in sound pressure level.

In the above description, an example where the yoke is separated into a bottom portion and a cylindrical peripheral portion is described. However, it is also possible to integrally form the yoke by casting, forging or cutting in order to prevent the magnetic saturation in the bonded portion of the bottom yoke 10b and the cylindrical peripheral portion 10a and to form a further high-efficiency magnetic circuit.

As described above, in the present preferred embodiment, it is possible to provide a magnetic circuit enhanced in magnetic efficiency, but it is not always necessary to employ all of the various means or configurations mentioned above. It is preferable to improve the magnetic efficiency by properly selecting some of the configurations in accordance with the shape of the intended loudspeaker and the like.

INDUSTRIAL APPLICABILITY

As described above, the magnetic circuit of the present invention and the loudspeaker using the magnetic circuit has the sectional area of magnetic flux flowing portion of the bottom yoke equal to or larger than the sectional area of the cylindrical peripheral portion of the yoke. By using the configuration of the present invention, it is possible to obtain a magnetic circuit of high efficiency by reducing the magnetic saturation due to the differences in sectional areas of each portions of the yoke, and also, to provide a high-output, small-sized, and light-weight loudspeaker by using the magnetic circuit.

CLAIMS

1. A magnetic circuit for a loudspeaker comprising:
a yoke having a bottom portion and a cylindrical peripheral portion;
5 a magnet bonded to said bottom portion of said yoke; and
a top plate bonded to said magnet, said top plate forming a magnetic gap
with said cylindrical peripheral portion in between,
wherein a thickness of said bottom portion is greater than a thickness of
said cylindrical peripheral portion.
- 10 2. The magnetic circuit of claim 1, wherein said bottom portion and said
cylindrical peripheral portion are formed as separate members.
3. The magnetic circuit of claim 2, wherein said bottom portion and said
cylindrical peripheral portion are bonded by caulking.
4. The magnetic circuit of any one of claim 1 through claim 3, wherein a
15 thickness of said bottom portion adjacent to a recess provided in said bottom
portion is thicker than other portions of said bottom portion.
5. The magnetic circuit of any one of claim 1 through claim 3, wherein a
sectional area of a bonded portion of said bottom portion and said cylindrical
peripheral portion is equal to or larger than a sectional area of said cylindrical
20 peripheral portion.
6. The magnetic circuit of any one of claim 1 through claim 3, wherein a
sectional shape of a bent portion of an outer periphery of said bottom portion is
curved.
7. The magnetic circuit of any one of claim 1 through claim 3, wherein a
25 sectional shape of a back surface of said bottom portion where a recess is provided
is curved.
8. A loudspeaker comprising:
(a) a magnetic circuit comprising:
a yoke having a bottom portion and a cylindrical peripheral
30 portion;
a magnet bonded to said bottom portion of said yoke; and

a top plate bonded to said magnet, said top plate forming a magnetic gap with said cylindrical peripheral portion in between;

(b) a voice coil held in said magnetic gap; and

(c) a diaphragm, an inner periphery of said diaphragm being bonded to said voice coil and an outer periphery being bonded to a frame,

wherein a thickness of said bottom portion is greater than a thickness of said cylindrical peripheral portion.

9. The loudspeaker of claim 8, wherein said bottom portion and said cylindrical peripheral portion are formed as separate members.

10. The loudspeaker of claim 8, wherein said bottom portion and said cylindrical peripheral portion are bonded by caulking.

11. The loudspeaker of any one of claim 8 through claim 10, wherein a thickness of said bottom portion adjacent to a recess provided in said bottom portion is thicker than other portions of said bottom portion.

12. The loudspeaker of any one of claim 8 through claim 10, wherein a sectional area of a bonded portion of said bottom portion and said cylindrical peripheral portion is equal to or larger than a sectional area of said cylindrical peripheral portion.

13. The loudspeaker of any one of claim 8 through claim 10, wherein a sectional shape of a bent portion of an outer periphery of said bottom portion is curved.

14. The loudspeaker of any one of claim 8 through claim 10, wherein a sectional shape of a back surface of said bottom portion where a recess is provided is curved.