[Claim 10]

A pouring member attached to a tap configured to pour a foam body of a beverage onto a liquid, and configured to pour the foam body,

the pouring member having a flow path through which the foam body flows,

wherein a front end section of the flow path is oriented in a direction of 0° or more and 45° or less upward and downward with respect to a liquid surface of the liquid.

[Claim 11]

The pouring member according to any one of claims 8 to 10, wherein a liquid guide section in which at least a lower side of an outlet port of the foam body protrudes outward is provided.

[Claim 12]

The pouring member according to any one of claims 8 to 11, wherein the pouring member is attached such that a pouring direction of the foam body is a desired direction.

[Claim 13]

An attachment/detachment tool comprising a pair of clipping sections configured to sandwich a pouring member attached to a tap configured to pour a foam body of a beverage onto a liquid,

wherein the pouring member is detachably attached to the tap while the pouring member is sandwiched between the pair of clipping sections.

[Claim 14]

The tap according to any one of claims 1 to 4, wherein the flow path includes a first flow path and a second flow path, and

a direction of pouring the foam body when the foam body is poured from the first flow path into a beverage container and a direction of pouring the foam body when the foam body is poured from the second flow path into the beverage container become a direction in which the foam body poured from the first flow path and the foam body poured from the second flow path form a spiral shape in the beverage container.