



(51) International Patent Classification:
C09D 163/00 (2006.01)

(21) International Application Number:
PCT/EP2013/050688

(22) International Filing Date:
16 January 2013 (16.01.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12151769.2 19 January 2012 (19.01.2012) EP
61/590,141 24 January 2012 (24.01.2012) US

(71) Applicant: **AKZO NOBEL COATINGS INTERNATIONAL B.V.** [NL/NL]; Velperweg 76, NL-6824 BM Arnhem (NL).

(72) Inventors: **CAMERON, Colin**; 20 Birkdene, Stocksfield Northumberland NE43 7EN (GB). **MALTHOUSE, Michael Leslie**; 20 Ollerton Gardens, Windy Nook, Gateshead Tyne and Wear NE10 9RT (GB). **MARRION, Alastair Robert**; Earsdon Moor House, Earsdon Moor, Morpeth Northumberland NE61 3EQ (GB). **WRIGHT, Anthony Colin**; 25 Castleside Road, Denton Burn, Newcastle-Upon-Tyne Tyne and Wear NE15 7DR (GB). **UNTHANK, Matthew George**; 20 Coquet Avenue, Whitley Bay Tyne and Wear NE26 1EF (GB).

(74) Agent: **AKZO NOBEL IP DEPARTMENT**; Velperweg 76, NL-6824 BM Arnhem (NL).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: CURABLE COATING COMPOSITION

(57) Abstract: The present invention relates to a curable coating composition, comprising: (a) a curable coating resin comprising thiol-reactive groups, (b) a thiolated norbornene curing agent for the curable coating resin, the thiolated norbornene curing agent comprising on average at least 1.0 thiol group per molecule, and (c) an accelerator for accelerating the reaction between the thiol reactive-groups on the curable coating resin and the thiol groups on the thiolated norbornene curing agent. These coating compositions can be cured at ambient temperature and provide a coated surface that can be walked on after only a couple of hours. The coating compositions in general have a VOC below 250 g/L. The coating compositions can be used for the protection of large steel structures, such as ships, buildings, bridges, industrial plants, and oil production installations.

