

9

Description

This invention relates to an apparatus for helically winding elongate strips of material on a rotatively driven beam which comprises means for traversing the strips of material between the opposite ends of said beam, said traversing means including a pivotally supported guide member slidably movable over the layers of strips that have been wound on said beam, and means for switching the direction of winding the strips upon arrival of said guide member at one of the ends of said beam.

An apparatus of this type is disclosed in CH-A-428 367. With this prior art apparatus the switches for reversing the direction of movement of the traversing means are mounted on the frame of the apparatus. As a consequence, the direction of movement of the traversing means is reversed independent of the relative position of the guide member in respect of the beam. Therefore this prior art apparatus cannot be used in connexion with a beam provided with end flanges as basically known from US-A-2 470 549. In this case namely a specific relative position of the switches on the frame ought to be safeguarded relative to the flanges of the beam. Otherwise, the direction of movement of the guide member would be reversed either as early as a distance from, and before, the respective end flange of the beam or — and that would be still more disadvantageous — at a distance from, and behind, the end flange, that which would seriously impair the operation.

Therefore it is an object of the invention to improve the prior art apparatus in such a manner that it can be used in the case of a beam provided with end flanges.

According to the invention there is provided an apparatus of the type mentioned above which is characterized in that said beam includes a perforated cylindrical tube having a central barrel portion, a pair of flanges disposed at opposite ends of said tube and a conical portion disposed between said central barrel portion and each of said flanges, and that said guide member includes an electrically insulative, plastic portion slidably engageable with the layers of strips, a frame portion receiving said strips and a metallic portion engageable with said conical portion of the tube.

Upon contact with either of the conical portions the guide member delivers a signal to a relay circuit, so that a driving shaft reverses its rotation, thereby changing the direction of movement of the guide member.

The apparatus according to the invention is especially suitable for the winding of slide fastener chains.

A preferred embodiment of the invention will now be described in detail with reference to the accompanying drawing.

Figure 1 is a side elevation of a beam winding apparatus embodying the invention;

Figure 2 is a plan view of a part of the apparatus shown in Figure 1;

Figure 3 is a plan view, partly broken away, of a beam provided in accordance with the invention;

Figure 4 is a longitudinal cross-sectional view of a part of the beam of Figure 3, schematically illustrating slide fastener stringers wound on the beam;

Figure 5 is a schematic sectional view of a part of the apparatus of Figure 1, illustrating one form of a fastener chain guide;

Figure 6 is a schematic sectional view illustrating the process of winding slide fastener stringers; and

Figure 7 is a schematic sectional view of a modified form of fastener chain guide.

Referring now to the drawings and Figure 1 in particular, there is shown a beam winding apparatus 10 for helically winding relatively narrow, elongate strips of textile material into a cylindrical form for treatment with dyeing, bleaching or other liquid media. The apparatus 10 includes a perforated cylindrical tube 11 commonly known as a "beam" which is mounted in horizontal disposition rotatably on a drive shaft 12 extending between a pair of collars 13 secured to a base 14.

The beam 11, as better shown in Figure 3, comprises a cylindrical tube 15 provided with a multiplicity of perforations 16 through which a liquid medium such as a dye is allowed to pass radially outward from inside the tube 15 and penetrate the layers of material wound thereon, the material here being shown for illustrative purposes to be slide fastener stringers F carrying rows of coupling elements E.

The tube 15 has a central barrel portion 17 of uniform diameter and an extension 18 thereof at each of its ends engageable peripherally with a disc-like support 19 (Figure 1) secured to the shaft 12. A pair of disc flanges 20, 20' are provided adjacent the respective end extensions 18, 18' and extend a predetermined distance above the barrel portion 17.

The tube 15 further includes a pair of conical portions 21, 21' which flare radially outward from the barrel portion 17 towards and are connected to the respective flanges 20, 20'. The conical portions 21, 21' are also provided with perforations 16' communicating with the interior of the tube 15, but these perforations should be adjusted in their number or in their size so as to reduce the amount of liquid flow per unit area commensurate with the thickness of the layers of material which diminishes progressively toward the flanges 20, 20', so that the material at the conical portions 21, 21' can be dyed or otherwise treated uniformly and substantially to the same extent as the portion of the material that is wound on the barrel 17 of the beam 11.

In the illustrated embodiment, the perforations 16' at each of the conical portions 21, 21' are substantially equal in size to the perforation 16 at the barrel portion 17, but the pore-to-pore spacing

(15)

of the perforations 16' increases proportionately with an increase in the diameter of the conical portion 21, (21').

It has now been found that the angle of inclination α of the generatrix of the conical portion 21 (21') with respect to the axis of the tube 15 is preferably of the order of $25^\circ \pm 5^\circ$ to obtain best results with treatment of ordinary slide fastener stringers having a fabric tape about 5—20 mm wide and a row of coupling elements about 3 to 4 times thicker than the tape. Departures from this angle range would result in off-specification products.

In the case of flat tapes, the above angle may be much greater but should not exceed 70° . If it is below 15° , then the results would be no more different than would be with a flange-less tubular beam.

Turning back to Figure 1, the beam 11 is rotatably mounted on the shaft 12 which is driven by motor 22 via drive belt 23. A chain of slide fastener stringers designated at F is supplied from a source not shown and wound helically on the beam 11 as the latter rotates. Feed of the fastener chain F is traversed or shifted between the opposite ends of the beam 11 by a feed traversing or shifting mechanism generally designated at 24. This mechanism includes a rack 25 attached with a pair of rollers 26, 26' movably mounted on respective rails 27, 27' secured to the base 14. A pair of vertical pillars 28, 28' extend from the rack 25 and are joined at their upper ends by a horizontal bar member 29. This member has an extension 29' provided with a support pin 30. A fastener chain guide 31 comprises, as better shown in Figure 5, a U-shaped guide frame 32 for receiving the wound chain F curing feed thereof, a slide member 33 made of an electrically insulative, plastic material disposed for sliding engagement with the fastener chain F and a metallic box member 34 interposed between guide frame 32 and slide member 33 and having connected thereto an electrical wire 35 for purposes to be hereinafter described, the members 32, 33 and 34 being integrally formed. The chain guide 31 is connected to an arm 36 which is in turn connected pivotally to the support pin 30.

The rack 25 is threadedly engaged with a screw shaft 37 extending parallel with the rails 27, 27' and journaled in oppositely disposed bearings 38, 38'. The screw shaft 37 is provided at one end thereof with a pair of bevel gears 39, 39' which are alternately connected and disconnected to a gear 40 on a drive shaft 41 of a motor 42 by means of respective electromagnetic clutches 43, 43', the arrangement being such that energizing one of the clutches 43, 43' causes the screw shaft 37 to rotate and hence the rack 25 to move in one direction and energizing the other clutch reverses rotation of the screw shaft 37 and hence moves the rack 25 in the opposite direction, whereby the chain guide 31 follows such movement of the rack 25. Selective energization of the clutches 43, 43' is effected by relay circuit (not shown) to which the electrical wire 35 is connected.

The metallic box member 34 of the chain guide 31 has on its opposite sides projections 34a, 34b which extend horizontally in registry with or slightly beyond respective sides of the U-shaped guide frame 32 so that the projections 34a, 34b can come into contact with the conical portions 21, 21' of the beam 11. On contact with either of the conical portions 21, 21', the chain guide 31 via its electrical wire 35 sends a signal to switch the relay circuit so that the screw shaft 37 reverses its rotation thereby changing the direction of helical winding of the chain F towards the other conical portion of the beam. This reciprocal shifting or traversing operation of the mechanism 24 is repeated until the fastener chain F is wound substantially up to the brims of the flanges 20, 20' as indicated by chain-dot lines in Figure 3, in which instance the slide member 33 serves to facilitate smooth movement of the chain guide 31 of the traversing mechanism 24 over the layers of the fastener chain F that have been previously wound on the beam 11. The speed of winding and the speed of traversing are relatively adjusted so that the fastener chain F is helically wound with its adjacent tape portions partially overlapped as shown in Figure 6.

There is shown in Figure 7 a modified form of fastener chain guide 31 wherein a pair of spring-actuated ball members 44, 44' are substituted for the projections 34a, 34b and disposed for resilient contact with the conical surfaces of the beam 11. Each of the ball members 44, 44', when brought in contact with a respective one of the opposite conical surfaces (21, 21') of the beam 11, is pivotally moved to actuate a respective one of the pair of microswitches 47, 47' which controls a relay circuit (not shown) to reverse the rotation of the screw shaft 37 (Figure 2), thereby changing the direction of helical winding of the slide fastener chain F towards the other conical surface (21', 21) of the beam 11.

Designated at 45 is a tension roller disposed for vertical movement in the known manner to maintain smooth feed movement of the fastener chain F passed between a pair of guide rollers 46, 46' located above the tension roller 45.

Claims

1. An apparatus for helically winding elongate strips of material on a rotatively driven beam (11) which comprises means (24) for traversing the strips (F) of material between the opposite ends of said beam (11), said traversing means including a pivotally supported guide member (31) slidably movable over the layers of strips (F) that have been wound on said beam, and means (34a, 34b; 35; 44, 44', 47, 47') for switching the direction of winding the strips upon arrival of said guide member (31) at one of the ends of said beam, characterized in that said beam (11) includes a perforated cylindrical tube (15) having a central barrel portion (17), a pair of flanges (20, 20') disposed at opposite ends of said tube (15) and a conical portion (21, 21') disposed between said

(10)

of the perforations 16' increases proportionately with an increase in the diameter of the conical portion 21, (21').

It has now been found that the angle of inclination α of the generatrix of the conical portion 21 (21') with respect to the axis of the tube 15 is preferably of the order of $25^\circ \pm 5^\circ$ to obtain best results with treatment of ordinary slide fastener stringers having a fabric tape about 5—20 mm wide and a row of coupling elements about 3 to 4 times thicker than the tape. Departures from this angle range would result in off-specification products.

In the case of flat tapes, the above angle may be much greater but should not exceed 70° . If it is below 15° , then the results would be no more different than would be with a flange-less tubular beam.

Turning back to Figure 1, the beam 11 is rotatably mounted on the shaft 12 which is driven by motor 22 via drive belt 23. A chain of slide fastener stringers designated at F is supplied from a source not shown and wound helically on the beam 11 as the latter rotates. Feed of the fastener chain F is traversed or shifted between the opposite ends of the beam 11 by a feed traversing or shifting mechanism generally designated at 24. This mechanism includes a rack 25 attached with a pair of rollers 26, 26' movably mounted on respective rails 27, 27' secured to the base 14. A pair of vertical pillars 28, 28' extend from the rack 25 and are joined at their upper ends by a horizontal bar member 29. This member has an extension 29' provided with a support pin 30. A fastener chain guide 31 comprises, as better shown in Figure 5, a U-shaped guide frame 32 for receiving the wound chain F curing feed thereof, a slide member 33 made of an electrically insulative, plastic material disposed for sliding engagement with the fastener chain F and a metallic box member 34 interposed between guide frame 32 and slide member 33 and having connected thereto an electrical wire 35 for purposes to be hereinafter described, the members 32, 33 and 34 being integrally formed. The chain guide 31 is connected to an arm 36 which is in turn connected pivotally to the support pin 30.

The rack 25 is threadably engaged with a screw shaft 37 extending parallel with the rails 27, 27' and journaled in oppositely disposed bearings 38, 38'. The screw shaft 37 is provided at one end thereof with a pair of bevel gears 39, 39' which are alternately connected and disconnected to a gear 40 on a drive shaft 41 of a motor 42 by means of respective electromagnetic clutches 43, 43', the arrangement being such that energizing one of the clutches 43, 43' causes the screw shaft 37 to rotate and hence the rack 25 to move in one direction and energizing the other clutch reverses rotation of the screw shaft 37 and hence moves the rack 25 in the opposite direction, whereby the chain guide 31 follows such movement of the rack 25. Selective energization of the clutches 43, 43' is effected by relay circuit (not shown) to which the electrical wire 35 is connected.

The metallic box member 34 of the chain guide 31 has on its opposite sides projections 34a, 34b which extend horizontally in registry with or slightly beyond respective sides of the U-shaped guide frame 32 so that the projections 34a, 34b can come into contact with the conical portions 21, 21' of the beam 11. On contact with either of the conical portions 21, 21', the chain guide 31 via its electrical wire 35 sends a signal to switch the relay circuit so that the screw shaft 37 reverses its rotation thereby changing the direction of helical winding of the chain F towards the other conical portion of the beam. This reciprocal shifting or traversing operation of the mechanism 24 is repeated until the fastener chain F is wound substantially up to the brims of the flanges 20, 20' as indicated by chain-dot lines in Figure 3, in which instance the slide member 33 serves to facilitate smooth movement of the chain guide 31 of the traversing mechanism 24 over the layers of the fastener chain F that have been previously wound on the beam 11. The speed of winding and the speed of traversing are relatively adjusted so that the fastener chain F is helically wound with its adjacent tape portions partially overlapped as shown in Figure 6.

There is shown in Figure 7 a modified form of fastener chain guide 31 wherein a pair of spring-actuated ball members 44, 44' are substituted for the projections 34a, 34b and disposed for resilient contact with the conical surfaces of the beam 11. Each of the ball members 44, 44', when brought in contact with a respective one of the opposite conical surfaces (21, 21') of the beam 11, is pivotally moved to actuate a respective one of the pair of microswitches 47, 47' which controls a relay circuit (not shown) to reverse the rotation of the screw shaft 37 (Figure 2), thereby changing the direction of helical winding of the slide fastener chain F towards the other conical surface (21', 21) of the beam 11.

Designated at 45 is a tension roller disposed for vertical movement in the known manner to maintain smooth feed movement of the fastener chain F passed between a pair of guide rollers 46, 46' located above the tension roller 45.

Claims

1. An apparatus for helically winding elongate strips of material on a rotatively driven beam (11) which comprises means (24) for traversing the strips (F) of material between the opposite ends of said beam (11), said traversing means including a pivotally supported guide member (31) slidably movable over the layers of strips (F) that have been wound on said beam, and means (34a, 34b; 35; 44, 44', 47, 47') for switching the direction of winding the strips upon arrival of said guide member (31) at one of the ends of said beam, characterized in that said beam (11) includes a perforated cylindrical tube (15) having a central barrel portion (17), a pair of flanges (20, 20') disposed at opposite ends of said tube (15) and a conical portion (21, 21') disposed between said





central barrel portion (17) and each of said flanges, and that said guide member (31) includes an electrically insulative, plastic portion (33) slidably engageable with the layers of strips (F), a frame portion (32) receiving said strips (F) and a metallic portion (34a, 34b) engageable with said conical portion (21, 21') of the tube (15).

2. An apparatus according to claim 1, wherein said strip (F) of material is a slide fastener stringer chain.

Patentansprüche:

1. Vorrichtung zum schraubenlinienförmigen Aufwickeln länglicher Streifen auf einen rotierend angetriebenen Warenbaum (11) mit einer Quervorschubeinrichtung (24) zum Hin- und Herbewegen der Streifen (F) zwischen den gegenüberliegenden Enden des Warenbaums (11), bestehend aus einem schwenkbar gelagerten Führungsteil (31), das auf den Warenbaum aufgewickelten Lagen der Streifen (F) verschiebbar gelagert ist, und aus einer Einrichtung (34a, 34b, 35; 44, 44', 47, 47') zum Umschalten der Vorschubeinrichtung der Streifen bei der Ankunft des Führungsteils (24) an einem der Enden des Warenbaums, dadurch gekennzeichnet, daß der Warenbaum (11) ein perforiertes, zylindrisches Rohr (15) mit einem zentralen Trommelbereich (17), zwei an gegenüberliegenden Enden des Rohres angeordneten Flanschen (20, 20') und zwei konischen Bereichen (21, 21') aufweist, die jeweils zwischen dem zentralen Trommelbereich (17) und einem der Flansche (20, 20') angeordnet sind, und daß das Führungsteil (31) aus einem elektrisch isolierenden Kunststoffbereich (33), der auf den Lagen der Streifen (F) verschiebbar aufliegt, aus einem die Streifen (F) aufnehmenden Rahmenbereich (32) und aus einem metallischen Bereich (34a, 34b) besteht, der mit den konischen

Bereichen (21, 21') des Rohres (15) in Eingriff gelangen kann.

2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß es sich bei dem Streifen (F) um Reißverschlußbänder handelt.

Revendications

1. Appareil pour enrouler hélicoïdalement des rubans allongés en matière sur un tambour (11) entraîné dans un mouvement de rotation et qui comprend un moyen (24) pour déplacer transversalement les rubans (F) de matière entre les extrémités opposées de ce tambour (11), ce moyen de déplacement transversal comprenant un élément (31) de guidage supporté par un pivot et capable de glisser sur les couches formées par les rubans (F) qui ont été enroulés autour du tambour, et des moyens (34a, 34b; 35; 44, 44'; 47, 47') pour inverser le sens d'enroulement des rubans lorsque l'élément (31) de guidage arrive à l'une des extrémités du tambour, caractérisé en ce que ce tambour (11) comprend un tube cylindrique perforé (15) constitué d'une partie tubulaire centrale (17), deux brides (20, 20') disposées aux extrémités opposées de ce tube (15) et une partie conique (21, 21') placée entre la partie tubulaire centrale (17) et chacune des brides, et en ce que le moyen (31) de guidage comprend une partie (33) en plastique, électriquement isolée et pouvant entrer en contact de glissement avec les couches formées par les rubans (F), une partie (32) en forme de cadre pour recevoir ces rubans (F) et une partie métallique (34a, 34b) pouvant entrer en contact avec la partie conique (21, 21') du tube (15).

2. Appareil suivant la revendication 1, dans lequel ce ruban (F) en matière est une chaîne de fermeture à glissière.



* C L M S *