

METHOD AND SERVER FOR SEARCHING FOR NEARBY USER IN SOCIAL NETWORK

~~This application claims the benefit of priority from Chinese Patent Application, No. 201110363120.4, entitled "Method and Server for Searching for Nearby User in Social Networking Services (SNS)" and filed on November 16, 2011, the entire content of which is hereby incorporated by reference.~~

FIELD OF THE INVENTION

[0001] The present disclosure relates to Internet technologies, and more particularly, to methods and servers for searching for nearby users in SNS.

BACKGROUND

[0002] In SNS, a user may search for nearby users and contact with a user to make friends with the user or seek the user's help, etc.

~~**[0003]** Nearby users may be searched via following methods. According to longitude and latitude information, a server may divide a surface of the earth in to a grid array, in which the area of each grid may be the same. As for any user X, when the user X needs to search for nearby users, the user X may send his/her location information and a user Identification (ID) to a server via a client terminal device used by the user X. The client terminal device may be a mobile terminal device. The location information may be the longitude and latitude information. After the server receives the location information from the user X, the server first may determine a grid, to which the location information belongs. Then, the server may search for other users in this grid, search for user IDs of the other users and distances between the other users and the user X and send the user IDs and the distances to the client terminal device of the user X.~~

~~**[0004]** However, there are some drawbacks in the above method. The user X may be close to a boundary of two adjacent grids. Figure 1 is a schematic diagram illustrating a location of the user X. As shown in figure 1, two adjacent grids may be grid A and grid B. The user X and user Z are located at the grid A~~

and the user Y is located at the grid B. As for the user X, the distance between the user X and the user Y is shorter than that between the user X and the user Z. If the user X seeks for help, the user Y is obviously a better choice than the user Z. According to an example, the user X may search for the user Z but cannot search for the user Y, resulting in inaccurate searching result.

5

SUMMARY

[0005][0003] The present disclosure provides methods and servers for searching for nearby users in SNS, to enhance accuracy of a searching result.

[0006][0004] A method for searching for nearby users in Social Networking Services (SNS) includes:

receiving location information and a user Identification (ID) from a client terminal device of a user X;

determining a grid Y, to which the location information belongs;

storing the user ID and the location information of the user X in a list of the grid Y; wherein the grid Y is one of grids in a grid array obtained by dividing a surface of the earth into the grids and areas of the grids are the same;

searching for users in the grid Y and other grids; wherein the grid Y and the other grids form an N-grid and the grid Y is a center of the N-grid, $N=n*n$, n is an odd larger than or equal to 3;

ranking the users in an ascending order of distances between the users the user X; and

sending the ranked user IDs of the users and distances between the users and the user X to the client terminal device of the user X.

[0007][0005] A method for searching for nearby users in Social Networking Services (SNS) includes:

receiving location information and a user Identification (ID) from a client terminal device of a user X;

determining a grid Y, to which the location information belongs;

saving the user ID, the location information and reporting time of the user X in a list of the grid Y; wherein the grid Y is one of grids in a grid array obtained by dividing a surface of the earth into the grids and areas of the grids are the same;

searching for users in the grid Y and other grids; wherein the grid Y and the other grids form an N-grid and the grid Y is a center of the N-grid, $N=n*n$, n is an odd larger than or equal to 3;

ranking the users according to distances between the users and the user X

and the reporting time of the user X; wherein the closer a distance between a user and the user X, the higher rank of the user is, and the shorter time between the reporting time of the user and a current time is, the higher the rank of the user is; and

5 sending the ranked user IDs of the users and the distances between the users and the user X to the client terminal device of the user X.

[0008][0006] A server includes:

 a first processing module, to divide a surface of the earth into a grid array, in which an area of each grid is the same, and set a list for a grid; and

10 a second processing module, when location information and a user Identification (ID) from a client terminal device of a user X is received, to determine a grid Y, to which the location information belongs, store the user ID and the location information of the user X in a list of the grid Y, search for users in the grid Y and other grids, in which the grid Y and the other grids form an N-grid and the grid Y is a center of the N-grid, $N=n*n$ and n is an odd larger than or
15 equal to 3, rank the users in an ascending order of distances between the users the user X and send the ranked user IDs of the users and distances between the users and the user X to the client terminal device of the user X.

[0009][0007] A server includes:

20 a first processing module, to divide a surface of the earth into a grid array, in which an area of each grid is the same, and set a list for a grid;

 a second processing module, when location information and a user Identification (ID) from a client terminal device of a user X is received, to determine a grid Y, to which the location information belongs, store the user ID,
25 the location information and reporting time of the user X in a list of the grid Y, search for users in the grid Y and other grids, in which the grid Y and the other grids form an N-grid and the grid Y is a center of the N-grid, $N=n*n$ and n is an odd larger than or equal to 3, rank the users according to distances between the users and the user X and the reporting time of the user X and send the ranked
30 user IDs of the users and distances between the users and the user X to the client terminal device of the user X; wherein the closer a distance between a user

and the user X, the higher rank of the user is, and the shorter time between the reporting time of the user and a current time is, the higher the rank of the user is.

[0010][0008] With the technical scheme of the present disclosure, the searching is performed in the grid, at which the user X is located and nearby grids of the grid. The users which are searched out are ranked according to an ascending order of the distances between the users and the user X. Even a user is not located in the above grid, if the distance between the user the user X is short, the user may be searched out and sent to the user X, which may enhance the accuracy of the result of the searching. In addition, in the scheme of the present disclosure, the ranking may be further performed according to the reporting time in addition to the location information and the user ID of the user X. The shorter time between the reporting time of the user and a current time is, the more likely the user X may get in touch with the user and the higher the rank of the user is, which may enhance the accuracy of the searching result.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011][0009] Figure 1 is a schematic diagram illustrating a location of a user X;

[0012][0010] Figure 2 is a flow chart illustrating a first method for searching for nearby users in SNS in accordance with an example of the present disclosure;

[0013][0011] Figure 3 is a schematic diagram illustrating a 9-grid formed by a Y grid and nearby grids;

[0014][0012] Figure 4 is a flow chart illustrating a ~~second~~ another method for searching for nearby users in the SNS in accordance with an example of the present disclosure;

[0015][0013] Figure 5 is a schematic diagram illustrating structure of a server in accordance with an example of the present disclosure.

DETAILED DESCRIPTION

[0016][0014] For simplicity and illustrative purposes, the present disclosure is described by referring mainly to non-limiting examples. In the following

description, numerous specific details are set forth in order to provide a thorough understanding of the present disclosure. It will be readily apparent however, that the present disclosure may be practiced without limitation to these specific details. In other instances, some methods and structures have not been described in detail so as not to unnecessarily obscure the present disclosure. As used throughout the present disclosure, the term “includes” means includes but not limited to, the term “including” means including but not limited to. The term “based on” means based at least in part on. In addition, the terms “a” and “an” are intended to denote at least one of a particular element.

[0015] Nearby users may be searched via following methods. According to longitude and latitude information, a server may divide a surface of the earth in to a grid array, in which the area of each grid is the same. As for any user X, when the user X needs to search for nearby users, the user X may send his/her location information and a user Identification (ID) to a server via a client terminal device used by the user X. The client terminal device may be a mobile terminal device. The location information may be the longitude and latitude information. After the server receives the location information from the user X, the server first may determine a grid, to which the location information belongs. Then, the server may search for other users in this grid, search for user IDs of the other users and distances between the other users and the user X and send the user IDs and the distances to the client terminal device of the user X.

[0016] However, there are some drawbacks in the above method. The user X may be close to a boundary of two adjacent grids. Figure 1 is a schematic diagram illustrating a location of the user X. As shown in figure 1, two adjacent grids may be grid A and grid B. The user X and user Z are located at the grid A and the user Y is located at the grid B. As for the user X, the distance between the user X and the user Y is shorter than that between the user X and the user Z. If the user X seeks for help, the user Y is obviously a better choice than the user Z. According to an example, the user X may search for the user Z but cannot search for the user Y, resulting in inaccurate searching result.

[0017] In order to enhance the accuracy of the searching result, the present

disclosure provides a scheme for searching for nearby users.

[0018] Figure 2 is a flow chart illustrating a first-method for searching for nearby users in SNS in accordance with an example of the present disclosure. As shown in figure 2, the method includes the following blocks.

5 **[0019]** In block 21, a surface of the earth may be divided into a grid array, in which an area of each grid may be the same. A list may be set for a grid. According to an example, a list may be set for each grid.

[0020] According to longitude and latitude information, the surface of the earth may be divided into the grid array, in which the area of each grid may be the
10 same. The area of the grid may be configured as needed, such as one square kilometers.

[0021] The list may be empty at an initial stage.

[0022] In block 22, when location information and a user ID is received from a client terminal device of a user X, a grid Y, to which the location information
15 belongs may be determined. As for the user X, the user ID and location information of the user X may be stored in list of the grid Y.

[0023] The location information may be the longitude and latitude information. Since the grids are divided according to the longitude and latitude information, the grid, to which the received location information belongs, may be determined.

[0032] If the N-grid in this block is the 9-grid shown in figure 3, users in the list of the 9-grid may be the users which are searched out, except for the user X.

[0033] In block 24, users which are searched out may be ranked in an ascending order of distances between the user X and the users and the ranked user IDs of the users and distances between the user X and the user may be sent to the client terminal device of the user X.

[0034] Since the location information of the users which are searched out may be known, the location information of the user X may be known. Therefore, the distances between the user X and the users which are searched out may be computed and the ranking of the user may be performed.

[0035] The searching scope in examples of the present disclosure may be enlarged. Therefore, the number of the users which are searched out is increased. For the user X, users ranked lower are basically not concerned. Therefore, the information of these users needs not to be sent to the user X, which may reduce amount of transmitted data and save bandwidth resources, etc.

[0036] After the ranking is finished, whether the number of users which are searched out is less than or equal to M may be determined. If the number of the users which are searched out is less than or equal to M, the user IDs of the users and the distances between the user X and the users may be sent to the client terminal device of the user X. If the number of the users which are searched out is larger than M, the user IDs of users among top M and the distances between the user X and the users among the top M may be sent to the client terminal device of the user X. M may be a positive integer larger than one. The value of M may be determined according to actual requirements.

[0037] Other information besides the user IDs of the users and the distances between the user X and the users, such as avatars of the users may be sent to the client terminal device of the user X.

~~**[0038]** The method for the user X communicating with the user, information of which is returned, may be conventional method.~~

[0039][0038] Figure 4 is a flow chart illustrating a ~~second~~ another method for searching for nearby users in the SNS in accordance with an example of the present disclosure. As shown in figure 4, the method may include following blocks.

5 [0040][0039] In block 41, a surface of the earth may be divided into a grid array, in which an area of each grid may be the same. A list may be set for a grid.

[0041][0040] In block 42, when location information and a user ID is received from a client terminal device of a user X, a grid Y, to which the location information belongs may be determined. As for the user X, the user ID, location
10 information and reporting time of the user X may be stored in list of the grid Y.

[0042][0041] In block 43, users in the grid Y and other grids may be searched out. The grid Y and the grid may form an N-grid and the grid Y may be the center of the N-grid. Wherein, $N=n*n$ and n may be an odd larger than or equal to 3.

[0043][0042] In block 44, users which are searched out may be ranked
15 according to the distances between the users and the user X and the reporting time and ranked user IDs of the users and distances between the user X and the users may be sent to the client terminal device of the user X. The closer the distance between the user X and a user is, the higher the rank of the user is. The shorter the time between the reporting time of the user and the current time is,
20 the higher the rank of the user is.

[0044][0043] Compared with the example shown in figure 2, when the ranking is performed in this example, the reporting time may be taken into consideration. In block 42, the report time of the user ID and the location information of the user X may be stored in the list of the grid Y.

25 [0045][0044] In block 44, a weight of a user i $A_i = a * D_i + b * T_i$ may be computed, a and b are weighting coefficients and values of a and b may be determined as needed. D_i denotes the distance between the user i and the user X. T_i denotes the time between the current time and the reporting time of the user i. The users are ranked in an ascending order of the weight.

[0046][0045] After the ranking is finished, whether the number of users which are searched out is less than or equal to M may be determined. If the number of the users which are searched out is less than or equal to M, the user IDs of the users and the distances between the user X and the users may be sent to the client terminal device of the user X. If the number of the users which are searched out is larger than M, the user IDs of the users among top M and the distances between the user X and the users among the top M may be sent to the client terminal device of the user X. M may be a positive integer larger than one.

~~[0047] Features of figure 4 which may be the same as those of figure 2 may not be repeated here. Refer to the above description for details of the features.~~

[0048][0046] In the above two examples, the client terminal device of the user X may obtain the location information of the user X with following methods. That is, the client terminal device of the user X may obtain the location information of the user X via method one to method L. After the location information of the user X is obtained, the client terminal device may report the location information. If the location information of the user X is not obtained with a method, the client terminal device of the user X may obtain the location information with a next method. L may be a positive integer larger than one. As for different methods, the smaller the number is, the higher the accuracy of the location information is.

[0049][0047] The value of L may be three. Method one may be obtaining the location information via a Global Positioning System (GPS) function. Method two may be obtaining the location information via a Cell ID of an eNode B. Method three may be obtaining the location information via a Media Access Control (MAC) address of a connected Wireless Fidelity (WiFi) access point.

[0050][0048] The description of the methods in examples of the present disclosure is finished.

[0051][0049] On the basis of the above description, figure 5 is a schematic diagram illustrating structure of a server in accordance with an example of the present disclosure. As shown in figure 5, the server 500 may include:

[0052][0050] a first processing module 501, to divide a surface of the earth into a grid array, in which area of each grid may be the same and set a list for a grid; and

[0053][0051] a second processing module 502, when location information and a user Identification (ID) from a client terminal device of a user X is received, to determine a grid Y, to which the location information belongs, store the user ID and the location information of the user X in a list of the grid Y, search for users in the grid Y and other grids, in which the grid Y and the other grids form an N-grid and the grid Y is a center of the N-grid, $N=n*n$, n is an odd larger than or equal to 3, rank the users in an ascending order of distances between the users the user X and send the ranked user IDs of the users and distances between the users and the user X to the client terminal device of the user X.

[0054][0052] The second processing module 502 may further determine whether number of the users is less than or equal to M after the users are ranked, send the ranked user IDs of the users and distances between the users and the user X to the client terminal device of the user X if the number of the users is less than or equal to M and send ranked user IDs of users among top M and distances between the users among the top M and the user X to the client terminal device of the user X if the number of the users is larger than M; wherein M may be a positive integer larger than one.

[0055][0053] According to another example of the present disclosure, the server 500 may include:

[0056][0054] a first processing module 501, to divide a surface of the earth into a grid array, in which an area of each grid may be the same and set a list for a grid;

[0057][0055] a second processing module 502, when location information and a user Identification (ID) from a client terminal device of a user X is received, to determine a grid Y, to which the location information belongs, store the user ID, the location information and reporting time of the user X in a list of the grid Y, search for users in the grid Y and other grids, in which the grid Y and the other grids form an N-grid and the grid Y is a center of the N-grid, $N=n*n$, n is an odd

larger than or equal to 3, rank the users according to distances between the users and the user X and the reporting time of the user X and send the ranked user IDs of the users and distances between the users and the user X to the client terminal device of the user X; wherein the closer a distance between a user and the user X is, the higher rank of the user is, and the shorter time between the reporting time of the user and a current time is, the higher the rank of the user is.

[0058][0056] The second processing module 502 may further compute a weight $A_i = a * D_i + b * T_i$ of a user i; wherein a and b are weighting coefficients, D_i is a distance between the user i and the user X, T_i is time between the current time and the reporting time of the user i and rank the users in an ascending order of the weight.

[0059][0057] The second processing module 502 may further determine whether number of the users is less than or equal to M after the users are ranked, send the ranked user IDs of the users and distances between the users and the user X to the client terminal device of the user X if the number of the users is less than or equal to M and send ranked user IDs of users among top M and distances between the users among the top M and the user X to the client terminal device of the user X if the number of the users is larger than M; wherein M may be a positive integer larger than one.

[0060][0058] The workflow of the device shown in figure 5 may be referred to the description of the above method, which may not be repeated.

[0061][0059] With the technical scheme of the present disclosure, the searching is performed in the grid, at which the user X is located and nearby grids of the grid. The users which are searched out are ranked according to an ascending order of the distances between the users and the user X. Even a user is not located in the above grid, if the distance between the user the user X is short, the user may be searched out and sent to the user X, which may enhance the accuracy of the result of the searching. In addition, in the scheme of the present disclosure, the ranking may be further performed according to the reporting time in addition to the location information and the user ID of the user X. The shorter time between

the reporting time of the user and a current time is, the more likely the user X may get in touch with the user and the higher the rank of the user is, which may enhance the accuracy of the searching result.

5 | ~~[0062]~~[0060] The foregoing only describes preferred embodiments of the present invention. The protection scope of the present invention, however, is not limited to the above description. Any change or substitution, easily occurring to those skilled in the art, should be covered by the protection scope of the present invention.