

Description

The present invention relates to an excavation tool for use in the excavation of earth and sand, such as the digging of wells or the construction of foundation piling holes and the like.

Conventionally, a type of excavation tool for the excavation of earth and sand was known in which a pilot bit was provided at the lead end of an excavation pipe, by means of this pilot bit the bottom surface of an excavation hole was excavated and the diameter of the excavation hole was widened by means of an eccentric reamer disposed at the upper part of this pilot bit, and using the widened part of the excavation hole, the excavation pipe was advanced. However, in this type of excavation tool, a part of the circumference of the excavation hole was re-excavated by means of the eccentric reamer, and an eccentric hole thus created, so that there was a disadvantage in that the excavation hole bent easily.

Recently, excavation tools such as that disclosed in Japanese Patent Application, first publication, laid open No. sho. 63-11789 (JP-A-63-11789) have been developed in order to solve this problem.

As shown in Figs. 1 through 3, this excavation tool is provided with a device 2 which receives the striking force of a hammer (not depicted in the diagram) and the rotational force of a hammer ring 1; two axle holes 2a and 2b are formed in the bottom surface thereof which are in point symmetry with respect to the center of device 2, and block axes 3a and 3b are inserted into these axle holes 2a and 2b in a freely rotatable and firmly attached manner. At the lead end parts of these block axes 3a and 3b, blocks 5a and 5b, which have roughly the same diameter as that of the above device 2, are roughly semicircular in shape, and have embedded in lead end surfaces thereof a plurality of bits 4..., are provided with the straight edge surfaces 6a and 6b thereof in mutual opposition. When the above device 2 rotates in the direction of excavation, the positions of the above block axes 3a and 3b are such that one end of each of the above blocks 5a and 5b protrudes beyond the outer circumferential surface of device 2 by a predetermined excavation amount, and at this time, the straight edge surfaces 6a and 6b of the blocks are displaced from the center of device 2 so that they are in mutual contact.

When device 2 is rotated in the direction of excavation X by means of hammer ring 1, in the above excavation tool, blocks 5a and 5b rotate about block axes 3a and 3b while receiving excavation resistance, one end of the straight edge surfaces 6a and 6b of blocks 5a and 5b protrudes beyond the outer circumferential surface of device 2 by a prescribed amount, a part of straight edge surfaces 6a and 6b come into mutual contact and stop the rotation of blocks 5a and 5b, and in this state, blocks 5a and 5b

receive the rotational force of device 2, earth is excavated by means of bits 4..., and advancement is made into the earth by means of the striking force of the hammer.

At this time, the earth and sand and the like which is excavated is separated from the lead end of the excavation tool by means of the blowing of compressed air, expelled at the time of the falling of the piston hammer within hammer cylinder 1, from air-holes 8a and 8b provided in the bottom surface of device 2, and after this, the earth and sand and the like is moved to the interior of excavation pipe 9 through exhaust grooves 9a and is finally expelled in an upwards direction.

In the above excavation tool, as shown in Fig. 2, earth is excavated by means of a part of blocks 5a and 5b which protrudes in an outward direction beyond the outer circumferential surface of device 2 (hereinafter termed the outer circumferential blade A); these outer circumferential blades A are only present at two points separated by 180 degrees and beyond the outer circumferential surface of device 2. This excavation tool is superior to the eccentric hole excavating type discussed above; however, it is incapable of balanced excavation, so that for example in the case in which layers of uneven quality are excavated, there is a danger that hole bending will be produced.

Furthermore, as shown in Fig. 3, when an excavation counterforce C which is parallel to straight edge surfaces 6a and 6b is placed on blocks 5a and 5b from the inner circumferential surface of the excavation hole, the friction between straight edge surfaces 6a and 6b is negligibly small, so that almost all the excavation counterforce C acts on block axle 3a(3b) through the medium of the blocks, and a great load is placed on block axle 3a(3b).

Furthermore, an appropriate amount of play is provided between axle holes 2a and 2b and block axes 3a and 3b so that the block axes are able to rotate; however, when the above-described excavation counterforce C is placed on blocks 5a and 5b, rattling is produced in blocks 5a and 5b along straight edge surfaces 6a and 6b in accordance with the extent of the above play, and since it is impossible to firmly fasten the blocks in this manner, the lifespan of the tool is shortened, and excavation efficiency declines.

GB-A- 550 100 discloses a drill for mixed excavation in which the boring tool has a conical frustum leading to a cylindrical part of the tool, and another conical frustum at the bottom carrying a cross drill cutter on its lower face. The cylindrical portion of the tool comprises four pivoted sectors, each having a vertical cutting edge which are brought into the extended or cutting position when the sectors are turned about the vertical pivots.

The present invention was designed to solve the above problems; it has as a purpose thereof to pro-

vide an excavation tool which reduces the incidence of unwanted hole bending, and makes possible a reduction in the amount of force placed on the block axes, a lengthening of tool life, and an increase in excavation efficiency. In order to achieve the above object, in the excavation tool of the present invention according to claim 1, in the bottom surface of a device, which receives the striking force of a hammer and the rotation force of the hammer cylinder, at least three axle holes are provided displaced from the center of the device and at equal angles in the circumferential direction, block axes are engaged in a freely rotatable manner in these axle holes and at the lead end part of each block axle, blocks having roughly a fan shape and in the lead end surfaces of which bits are embedded are provided in such a manner that the side faces thereof contact each other, and moreover, the arc parts of these blocks roughly form a circle. When the device is rotated in the direction of excavation, the blocks rotate by means of the resistance to excavation of the excavation hole bottom, one of the intersection parts of the side faces and arc part of each of the blocks protrudes beyond the outer circumferential surface of the device by a predetermined excavation amount, and at this time, the mutual positioning of the block axes corresponding to the blocks is designed so that the side faces and of the blocks are in contact with the side faces of the neighboring blocks.

In the excavation tool described above, when the hammer cylinder rotates in the direction of excavation, the device also rotates as a unit. Furthermore, by means of the descent of the hammer piston, the device and the blocks which are attached to the lead end thereof advance.

When the device rotates in the direction of excavation, the blocks rotate around the various block axes as a result of excavation resistance, one of the intersection parts of the side faces and the arc part of each of the blocks protrudes beyond the outer circumferential surface of the device by a predetermined excavation amount, this part becomes an outer circumferential blade, and excavates the hole. Furthermore, when the above-described blocks rotate, the side faces of each block are in contact with the side faces of the neighboring blocks and this has a mutual stopper function, so that further rotation of each block is controlled.

Here, three or more blocks are provided, so that three or more outer circumferential blades, each of which corresponds to one block, are created, and moreover, these outer circumferential blades are created with equal spacing in the circumferential direction. As a result, well-balanced excavation can be executed, so that hole bending is unlikely to occur even in ground having uneven qualities.

Furthermore, at the time of excavation, as a result of the combination of the contact of the left and

right side faces of the blocks with the side faces of the neighboring blocks, and the engaging of the block axes which are affixed to the blocks in the axle holes, support is achieved at three points. Accordingly, strong affixing of the blocks can be conducted, rattling is unlikely to occur during excavation, and excellent excavation can be conducted.

Furthermore, as a result of providing a number of outer circumferential blades as stated above, and as a result of the firm support of the blocks, tool life is extended.

In addition, in the case in which an excavation counterforce which acts parallel to the side faces and the lead end surfaces is placed on the blocks, this excavation counterforce is divided among the block axle which supports the block and the other blocks, so that it is possible to reduce the load which is placed on the block axes.

Furthermore, the excavation counterforce which is placed on the blocks finally acts on the block axes which support these blocks; however, as a plurality of these block axes are disposed in a balanced manner in the circumferential direction in the bottom surface of the device, the support strength of the blocks as a whole is increased.

In addition, as three or more blocks are provided, in comparison with the case in which only two blocks are provided, the rotational angle of the blocks at the time of the movement of the blocks from a non excavating state to an excavating state or vice versa is small, so that the movement becomes smooth as a result. Furthermore, it is possible to provide a number of excavated matter exhaust holes formed in the bottom surface of the device in correspondence with the number of blocks, so that the exhaust efficiency of excavated matter increases.

Furthermore, an air exhaust hole extending in the axial direction is formed in the center of the device, and passage holes having openings in the lead end surfaces of the blocks and extending in the axial direction of the block axes are formed, the depth of the axle holes is so set as to be greater than the length of the block axes, and connecting holes which connect the air exhaust holes and axle holes are formed in the device, so that the air which is compressed by means of the descent of the hammer flows into the air exhaust holes, through the connecting holes, and is emitted from the passage holes, so that excavated matter can be efficiently removed. Furthermore, the air exhaust holes and the axle holes are connected by means of connecting holes, so that the axle holes are positively pressurized with respect to the vicinity of the lead end surface of the blocks, that is, with respect to the vicinity of the bits, so that it is possible to prevent the entry of excavated matter into the axle holes.

Furthermore, an air exhaust hole which extends in the axial direction is formed in the center of the de-

vice, and this air exhaust hole is connected through the medium of side holes to airholes which have openings in the bottom surface of the device, and in addition, excavated matter exhaust grooves are formed in the outer circumferential surface of the device, and in the bottom surface of the device, notches are provided which communicate the excavated matter exhaust grooves and the airholes, so that the air which is compressed by means of the descent of the hammer flows from the air exhaust holes and is emitted from the airholes, removing the excavated matter. Notches which are connected to the excavated matter exhaust grooves are formed in the lead end of the airholes, so that a part of the compressed air flows directly, and aids in the expulsion of the excavated matter, so that it is possible to efficiently remove the excavated matter. In addition, at the time of the diameter-reduction operation of the blocks, by means of the blowing of compressed air onto the surfaces of the device and the blocks which are in contact, it is possible to effectively remove the excavated matter from these contact surfaces, and thus to remove the resistance at the time of the reduction of block diameter.

Furthermore, angled surfaces having an angle with respect to the side faces and lead end surfaces of the blocks are provided at one crossing point of the side edge and lead edge surfaces of each block, and a portion of the bits are embedded in these angled surfaces nearly horizontally with respect to these surfaces, so that the combined force of the rotational counterforce at the time of excavation and the counterforce of the striking force, which is perpendicular to this rotational counterforce, act roughly at right angles to the bits embedded in the angled surfaces, so that it is possible to prevent damage or removal of these bits.

In addition, the outer circumference of the blocks is formed by arcs having differing radii, and the radius of the outer circumference of the side of the block which protrudes beyond the outer circumferential surface of the device when the device is rotated in the direction of excavation is greater than the radius of the outer circumference of the side of the block which does not protrude, so that it is possible to embed a plurality of bits in the protruding-side part, and accordingly, even if the amount of work of the part of the block which protrudes, that is, the part which achieves a predetermined hole diameter, is large, it is possible to prevent the complete abrasion of the bits which are embedded in the protruding part before the abrasion of the bits which are embedded in the non-protruding part, so that it is possible to increase the life of the excavation tool.

In addition, the block axes and the blocks are combined so as to be mutually dismemberable, so that it is possible to manufacture the block axes and the blocks separately. Accordingly, the difficulties involved in the unitary formation of the block axes and

blocks are not encountered, so that it is possible to keep the manufacturing costs of the excavation tool low.

Furthermore, the fatigue strength of the block axes is set so as to be greater than that of the blocks, so that even when bending stress which fluctuates primarily over time acts on the block axes at the time of excavation, the breaking of block axes prior to the limit of use of the blocks can be prevented.

Furthermore, between a first sloping surface, which slopes downwardly from the arc-form ridge line of the flat surface of the lead end of the block in the direction of the circumference of the device, and a second sloping surface, which slopes downwardly from the arc-form ridge line of the outer side of the first sloping surface in the direction of the circumference of the device, a step is provided, so that it is possible to maintain the spacing between the bits embedded in these first and second sloping surfaces, so that it becomes possible to embed a number of bits, and thus to increase excavation efficiency.

Figures 1 to 3 show an example of a conventional excavation tool (compare with JP-A-63-11789); Figure 1 is a cross-sectional view of the excavation tool, and Figures 2 and 3 are bottom views of the blocks.

Figures 4 through 7 show a first preferred embodiment of the present invention; Figure 1 is a semi cross-sectional view of the device with the blocks attached thereto, Figure 5 is a bottom view of the blocks when excavation is not being conducted, Figure 6 is a bottom view of blocks during excavation, and Figure 7 is a cross-sectional view of the main parts of the excavation tool at the time of excavation.

Figure 8 is a cross-sectional view of the main parts of an excavation tool in accordance with a second preferred embodiment of the present invention.

Figure 9 is a top view of the same.

Figure 10 is a vertical cross-sectional view of the main part of an excavation tool in accordance with a third preferred embodiment.

Figure 11 is a vertical cross-sectional view of the main parts of an excavation tool in accordance with a fourth preferred embodiment.

Figure 12 is a vertical cross-sectional view of the main parts of an excavation tool in accordance with the fifth preferred embodiment.

Figure 13 is a vertical cross-sectional view of the main parts of an excavation tool in accordance with a sixth preferred embodiment.

Figure 14 is a cross-sectional view of the main parts of an excavation tool in accordance with a seventh preferred embodiment.

Figures 4 through 6 show a first preferred embodiment of an excavation tool in accordance with the present invention. The points of difference between the the excavation tool shown in these diagrams and the excavation tool shown in Figures 1 through 3 are in the structure of the device and the blocks, so that

only these parts will be explained, and depictions of the remaining structure in the diagrams, and explanations thereof, will be omitted here.

In the diagrams, reference numeral 2 indicates a device. Axle holes 2a, 2b, and 2c are formed in the bottom surface of device 2 in such a way that these holes are displaced from the center of device 2 and are placed at equal angles in the circumferential direction (at intervals of 120 degrees).

Block axes 3a, 3b, and 3c are engaged in axle holes 2a, 2b, and 2c in a freely rotatable and firmly attached manner. The firm attachment of block axes 3a, 3b, and 3c is accomplished, for example, by inserting a suspension pin from a side hole (not shown in the diagram) into the device in the state in which block axes 3a, 3b, and 3c are engaged in axle holes 2a, 2b, and 2c, and by connecting the suspension pin to a ring-form groove 10 which is formed on the outer circumference of the block axle.

Furthermore, reference numerals 11a, 11b, and 11c indicate blocks which are provided at the lead ends of block axes 3a, 3b, and 3c and perpendicular with respect to these block axes. It is permissible to form these blocks 11a, 11b, and 11c unitarily with block axes 3a, 3b, and 3c, or to form them separately and connect them by means of bolts or the like. These blocks 11a, 11b, and 11c have identical structures which have the shape of a fan when viewed from the bottom surface thereof, so that the radius of these fan shapes is so set as to be roughly equivalent of radius of device 2. The left and right side faces 12a and 12b of blocks 11a, 11b, and 11c are in mutual opposition, and moreover, the arc parts 12c of the blocks are so disposed as to together form roughly a circular shape. The left and right side faces 12a and 12b of blocks 11a, 11b, and 11c are formed with differing lengths and the angles formed by the side faces 12a and 12b measure 120 degrees.

The front end surfaces (bottom surfaces) of blocks 11a, 11b, and 11c are comprising level surfaces 111a, 111b, and 111c which are positioned on the side of block axes 3a, 3b, and 3c and perpendicular to block axes 3a, 3b, and 3c, first sloping surfaces 13c, which slope downwardly from the arc shaped ridge line of the level surfaces 111a, 111b, and 111c in the direction of the circumference of device 2, and second sloping surfaces 14a, 14b, and 14c, which slope downwardly from the arc-shape ridge line of the outer side of first sloping surfaces 13a, 13b, and 13c in the direction of the outer circumferential surface of device 2; moreover, a step 112 is provided between first sloping surfaces 13a, 13b, and 13c and second sloping surfaces 14a, 14b, and 14c. In this manner, by means of providing step 112, it is possible to maintain the spacing between bits 4 embedded in first sloping surfaces 13a, 13b, and 13c and second sloping surfaces 14a, 14b, and 14c, so that it becomes possible to embed a number of bits 4, and thus to in-

crease the excavation efficiency.

Furthermore, when device 2 is rotated in the direction of excavation, as progress is made in the direction of rotation, sloping surfaces 15a, 15b and 15c, which gradually slope in the direction of the base edge side of the axial direction of device 2, are formed at the end parts of side faces 12a of the blocks which protrude beyond the outer circumferential surface of device 2. A plurality of bits 4... comprising superhardened chips are embedded in the lead end surfaces of the blocks 13a, 13b, and 13c, the surfaces 14a, 14b, and 14c, surfaces 15a, 15b, and 15c, and the sloping surfaces, and are perpendicular with respect to the various surfaces.

The relative positions of block axes 3a, 3b and 3c with respect to blocks 11a, 11b, and 11c are set so that at the time of the rotation of device 2 in the direction of excavation, blocks 11a, 11b, and 11c rotate as a result of the excavation resistance of the bottom part of the excavation hole, the intersecting part of one of the side faces of the block 12a and arc part 12c protrudes beyond the outer circumferential surface of device 2 by a predetermined excavation amount, and at this time, the side faces 12b and 12a of each block are in contact with the side faces 12a and 12b of the neighboring blocks.

Furthermore, the outer circumferences of the blocks 11a, 11b, and 11c are formed with arcs of differing radiuses.

That is, the outer circumferences of blocks 11a, 11b, and 11c are comprising, as shown in Fig. 6, two arcs S1 and S2 and a curve S3 which smoothly connects the arcs S1 and S2. Arcs S1 and S2 have an identical center, and the radius of arc S1 is set to be larger than the radius of arc S2. Furthermore, when the above-described arc S1 is rotated in the direction of excavation of device 2, this arc is positioned on the protruding side of the outer circumferential surface of device 2, while arc S2 is positioned so as to not protrude beyond the outer circumferential surface of device 2.

A plurality of bits 4 are embedded in the lead end surface of blocks 11a, 11b, and 11c; however, the radius of the outer circumference of the part of blocks 11a, 11b, and 11c which protrudes is larger than the radius of the outer circumference of the part which does not protrude, so that it is possible to embed a number of bits on the protruding side part. Accordingly, when device 2 is rotated in the direction of excavation, the amount of work of the protruding part of blocks 11a, 11b, and 11c is large, but a number of bits 4 are embedded in this part, so that it is possible to prevent the abrasion of the bits 4 which are embedded in the protruding part before the abrasion of the bits 4 which are embedded in the non-protruding part, and accordingly, it is possible to improve the lifespan of the excavation tool.

A air exhaust hole 17 which extends in the axial

direction is formed at the center of device 2. This air exhaust hole 17 opens in the base end surface of device 2, and when the hammer piston descends, the air which is thereby compressed is emitted from this opening. Furthermore, in device 2, side holes 19, which extend in the outward radial direction and are connected to the lead end part of air exhaust hole 17, are formed passing between airholes 2a, 2b and 2c at intervals of 120 degrees. At the vicinity of the outer end parts of side holes 19, the sideholes are connected to airholes 20, which extend in the axial direction to the lead end side of device 2, and at the opening parts of airholes 20, which open in the bottom surface of the device, notches 21 are formed which gradually widen in the outward radial direction. The outer ends of notches 21 are connected to excavated matter exhaust grooves 23, which are formed at the outer circumferential surface of device 2 and between the device and the outer side excavation pipe 9. Excavated matter exhaust groove 23 is provided unitarily at the outer circumference of device 2, and is formed with an arc shape between projections 22a which are used for centering, which maintain a state in which the outer circumference of the device 2 has a center identical to that of the excavation pipe 9; excavated matter exhaust groove 23 and projections 22a are disposed alternately in the circumferential direction between device 2 and excavation pipe 9. The width dimension of excavated matter exhaust groove 23 is set within a fixed range so that only excavated matter of less than a predetermined size is able to pass therethrough, so that the excavated matter which passes through the excavated matter exhaust groove 23 and into excavation pipe 9 does not clog excavation pipe 9 so as to render it unusable.

Furthermore, connecting holes 24, which are connected to the bottom surface of axle holes 2a, 2b, and 2c, are formed in the lead end part of air exhaust holes 17 of device 2. Airspaces 25 are formed between the bottom surface of block axes 3a, 3b, and 3c, and axle holes 2a, 2b, and 2c; airspaces 25 are connected to the bottom surface of the blocks through the medium of passage holes 26, which pass through the center part of block axes 3a, 3b, 3c, and passage holes 27, which pass vertically through blocks 11a, 11b, and 11c. Grooves 28, which are formed along the bottom surface of the blocks, extend from the openings of passage holes 27 in the bottom surface of blocks 11a, 11b, and 11c in an outward direction.

Next, the operation of the excavation tool having the above structure will be explained.

When a hammer cylinder 1 receives driving force and rotates in a direction X, device 2, the block axes, and the blocks rotate unitarily in the same direction.

Furthermore, when the hammer piston which is disposed within hammer cylinder 1 is operated and imparts a downward striking force to device 2, blocks

11a, 11b, and 11c are forced into the earth, and bits 4 excavate earth and sand by means of rotational force.

When hammer cylinder 1, device 2, and blocks 11a, 11b, and 11c rotate in the direction of excavation, blocks 11a, 11b, and 11c rotate about block axes 12a, 12b, and 12c as a result of excavation resistance, and one intersection part of side face 12a and arc part 12c of blocks 11a, 11b, and 11c protrudes beyond the outer circumferential surface of device 2, and this part serves as outer circumferential blade A. Furthermore, when blocks 11a, 11b, and 11c rotate, the side faces 12a and 12b of each block come into contact with the side faces 12b and 12a of the neighboring blocks, and this position acts as a stopper, so that further rotation of the blocks is controlled. In this state, blocks 11a, 11b, and 11c receive the rotational force of device 2 and excavate earth by means of the outer circumferential blades A and the like.

Here, three blocks are provided, so that three outer circumferential blades A, each corresponding to one block, are provided, and moreover, these outer circumferential blades A are disposed at equal intervals in the circumferential direction. As a result, it is possible to conduct balanced excavation, so that, for example, even in ground of uneven quality, hole bending is unlikely to occur.

Furthermore, at the time of excavation, the left and right side faces 12a and 12b of blocks 11a, 11b, and 11c are in contact with the side faces 12b and 12a of the neighboring blocks, and the block axes 3a, 3b, and 3c which are fixed to the blocks are engaged with and supported by axle holes 2a, 2b, and 2c, so that blocks 11a, 11b, and 11c are supported at three points. Accordingly, the attachment of the blocks 11a, 11b, and 11c is strong, and excavation can be conducted without the occurrence of rattling therein.

Furthermore, at the time of excavation, as shown in Fig. 6, when a excavation counterforce C which is parallel to a side face 12a is placed upon one block 11a from the inner circumferential surface of the excavation hole, this excavation counterforce C acts upon the block axle 3a, which is unitary in structure with the block, and in addition, acts on another block 11b through the medium of the side faces 12b and 12a, which are in mutual contact. In this manner, even when a parallel force is placed on one side face 12a of a block, this force is distributed to block axle 3a and another block 11b, so that the load placed on one block axle 3a becomes smaller by this amount. Therefore, it is possible to reduce the load which is placed on one block axle 3a (3b, 3c), so that an advantage is gained in that the diameter of the block axes can be made smaller.

In addition, when the piston within hammer cylinder 1 descends, the air which is compressed by this hammer piston flows into supply hole 17, and is blown onto the bottom surface of blocks 11a, 11b, and 11c

through the medium of airspaces 25, which are formed between the axle holes and the block axes, and passage holes 26 and 27, and the excavated matter is thus removed from the blocks. Then, the excavated matter which has been removed from the blocks moves along with the compressed gas from the excavated matter exhaust hole 23 and into excavation pipe 9, and is then expelled in an upward direction. A portion of the compressed air supplied to air supply hole 17 is blown onto the excavated material exhaust hole 23 which is positioned at the outer circumference of device 2, through the medium of side holes 19 and vertical holes 20. Moving along with the flow of compressed air, the excavated matter in the vicinity enters excavated matter exhaust hole 23, so that the expulsion of the excavated matter is conducted smoothly.

Furthermore, at the time of excavation, as shown in Fig. 7, the combined force F of the rotational counterforce and the counterforce of the striking force, which is perpendicular to the rotational counterforce, acts in the most inclined manner, with respect to the vertical axis, on the bits 4 which are embedded in sloping surfaces 15a, 15b and 15c; however, these bits 4 are embedded in sloping surfaces 15a, 15b and 15c, so as to be roughly perpendicular to the surfaces, so that the above-described combined force F acts at right angles to the bits 4, and accordingly, it is possible to prevent damage to or removal of the bits 4.

After excavation has been completed, the hammer cylinder is rotated in a direction which is opposite to that of the direction of excavation; however, at this time, the blocks 11a, 11b and 11c rotate in a direction opposite to that of the time of excavation, and as shown in Figure 2, the arc parts 12c, which are positioned at the extreme circumference of the blocks, have a position which is equivalent to that of the bottom surface of device 2, or is within this position. As it is possible to slide the tool along the interior of excavation pipe 9, by proceeding in this manner, it is possible to withdraw the excavation tool by pulling the hammer cylinder 1 upward.

Furthermore, excavated matter exhaust grooves 23 and projections 22a, which are for centering and are provided in a unitary manner along the outer circumference of device 2, are disposed alternately in the circumferential direction between device 2 and exhaust pipe 9, which is on the outer side thereof, so that it is possible to dispose the requisite number of exhaust passages for the conducting of excavated matter into excavation pipe 9 along the outer circumference of device 2, so that the excavated matter exhaust efficiency can be improved.

In addition, in comparison with the case in which projections 22a for the centering of the device and excavated matter exhaust grooves 23 are disposed in a displaced manner with respect to the length direction

of device 2, for example, in comparison with the case in which the projections for the centering of the device are located at the base end side of the device and a ring-shaped groove for excavated matter exhaust is provided at the lead end of the device, the rattling of the device 2 during excavation is reduced, and the trapping of excavated matter between device 2 and excavation pipe 9 is prevented.

In addition, in comparison with the above-described case in which the projections 22a for the centering of the device 2 and the excavated matter exhaust grooves 23 are disposed in a displaced fashion with respect to the length direction of device 2, the length of device 2 can be reduced, and the overall structure can be made more compact.

In the above-described preferred embodiment, an explanation was given of a case in which three blocks 11A, 11B and 11C were provided; however, this is not necessarily so limited, and the present invention can also be applied to tools having four or more blocks.

Furthermore, in the above-described preferred embodiment, the left- and right-sided surfaces 12a and 12b of blocks 11a, 11b and 11c were formed in a flat manner. However, this is not necessarily so limited, and it is acceptable to form the side faces 12a and 12b in the shape of mutually joining arcs.

Furthermore, in the above-described first preferred embodiment, either a structure in which the blocks and block axes are formed unitarily, or a structure in which the blocks and block axes are formed separately and then joined is permissible.

Next, an example will be given of preferred embodiments of a case in which the blocks and block axes are formed separately and then are joined.

Figures 8 and 9 show a second preferred embodiment. In these diagrams, reference numeral 40 indicates an excavation head. This excavation head 40 is primarily comprising block 42 and block axle 43, which is removably attached to this block 42.

The above-described block 42 has a plate form with a roughly semicircular shape when viewed from the level surface side thereof, and on the upper surface thereof, a plurality of bits 4... comprising super-hardened chips are embedded. Furthermore, a screw hole 44, which passes from the upper surface of block 42 to the lower surface of the block, is formed in block 42.

On the other hand, the above-described block axle 43 has a cylindrical shape, and in the lead-end surface thereof, bits 4... are embedded. Furthermore, on the outer circumference of the lead end of block axle 43, a male screw 45 is formed which screws into the above-described screw hole 44, and on the outer circumference of the basin thereof, a groove 46, which is engaged by a pin in order to prevent the removal of the block axle from device 2, is formed along the circumferential direction of the

block axle.

The above-described excavation head 40 is formed by means of the insertion of block axle 43 into screw hole 44 of block 42, and the screwing-in of the male screw 45 formed on the outer circumference of the upper end.

In accordance with the above-described excavation tool, the excavation head 40 has a block construction comprising block 42 and block axle 43, which is removably screwed into this block 42, so that in the case in which the excavation head 40 is manufactured, it is possible to manufacture the block 42 and block axle 43 separately. Accordingly, the conventional difficulties involved in the process of the unitary formation of the excavation head 40 are solved, so that as a result, the manufacturing costs of the excavation tool can be kept low.

A third preferred embodiment is shown in Figure 10. The third preferred embodiment shown in this diagram is a modification of the structure of the second preferred embodiment; the block axle 54 is joined to block 52 by means of interference fitting.

In accordance with the excavation tool of the present preferred embodiment, there is no need to form screw threads on block axle 54 and block 52 as in the case of the above-described second preferred embodiment, so that an advantage is gained in that the manufacture of block 52 and block axle 54 become simple.

A fourth preferred embodiment is shown in Figure 11. The fourth preferred embodiment shown in the diagram represents a modification of the structure of the third preferred embodiment. In block 62 in Figure 11, a tapered hole 64 is formed which gradually widens in diameter as it approaches the lead end surface. A tapered part 68 which comes into contact with the above-described tapered hole 64 is formed at the upper end of block axle 66.

In accordance with the excavation tool of the present preferred embodiment, in comparison with the case of the third preferred embodiment, an advantage is gained in that the accuracy of attachment and strength of attachment of block axle 66 with respect to block 62 are improved.

Figure 12 shows a fifth preferred embodiment. The fifth preferred embodiment shown in this diagram is a modification of the structure of the third preferred embodiment.

In the lead end surface of block 72, a hole 74 which has a circular shape and a depth which is one third of that of the block 72 is formed, and in the bottom surface of this hole 74, a hole 76 is formed which has an opening in the base end surface of block 72, is coaxial with hole 74, and has a smaller diameter than hole 74.

On the other hand, the block axle 78 which is combined with the above-described block 72 is comprising an axial part 82, which has a cylindrical shape

and in the base end outer circumference of which a groove 80 is formed, and a head part 84, which is formed at the lead end part of this axial part 82 and has a greater diameter than axial part 82.

Block 72 is affixed by means of the insertion of axial part 82 of block axle 78 into hole 74, and the engaging of head part 84 of block axle 78 with hole 76 of block 72.

In accordance with the excavation tool of this preferred embodiment, block 72 is supported between head part 84 of block axle 78 and the bottom surface of the above-described device 2, so that an advantage is gained in that there is no need to form a screw thread between head part 82 of block axle 78 and hole 74 of block 72, as in the second preferred embodiment, or to conduct processes such as interference fitting as in the third preferred embodiment.

Figure 13 shows a sixth preferred embodiment. The excavation tool shown in the diagram is comprising, in the same manner as the above-described fifth preferred embodiment, block 92 and block axle 93.

Block axle 93 has formed, on the outer circumferential surface of the base end thereof, male screw 94, and this block axle comprises axial part 96, which is inserted freely slidably into hole 95 of the above-described block 92, and head part 97, which is formed at the lead end part of the axial part 96, has a larger diameter than axial part 96, and is engaged freely slidably in hole 74 of block 92.

Formation is accomplished by means of the insertion of axial part 96 of block axle 93 into hole 95 of block 92, and by the engaging of head part 97 of block axle 93 and hole 74 of block 92. Furthermore, axial part 96 is attached by means of the screwing of male screw 94 of axial part 96 into screw hole 99 formed in the bottom surface of device 2, and when device 2 rotates in the direction of excavation, block 92 rotates about block axle 93, and protrudes beyond the outer circumference of device 2 by a predetermined amount.

In this preferred embodiment, block axle 93 is affixed by means of being screwed into device 2, so that an advantage is gained in that no rattling is produced in block axle 93 and block 92.

Figure 14 shows a seventh preferred embodiment. In the excavation tool shown in the diagram, a hole 101 is formed in the base end surface of block 100, which does not reach the lead end surface thereof, the lead end part of a cylindrical block axle 103, which has formed on the base end outer circumference thereof a male screw 102, is inserted into this hole 101, a groove 104 is formed in this lead end part in the circumferential direction, a pin 105 is inserted into this groove 104 from a pinhole which is formed in block 100, and the block axle is thereby connected; the removal of block axle 103 from block 100 is prevented by pin 105, and block 100 is thus made rotatable about block axle 103.

In the excavation tool of this preferred embodiment, block axle 103 is not exposed at the lead end surface of block 100, so that an advantage can be gained in that wear resulting from contact with excavated matter is prevented.

In the excavation tools of the second and seventh preferred embodiments above, the blocks and block axles are formed as separate parts. By precisely combining the materials which comprise these parts, it is possible to increase the dependability of the tool.

The following are examples of the qualities required for the blocks.

(1) They should not wear down quickly as a result of contact with rock layers in the earth (resistance to wear).

(2) As it is necessary to form a number of holes for the setting of the bits, they should be machine-manufacturable (machine manufacturability).

In contrast, in comparison with the blocks themselves, the block axles rarely come into contact with rock, and so a low resistance to wear is permissible. Furthermore, the block axles have a simple shape in comparison with the blocks, so that poor machine-manufacturability is also acceptable. However, as the block axles are repeatedly deformed by excavation, a high fatigue strength is necessary. Accordingly, in the blocks, in order to achieve ideal resistance to wear, hardened, tempered materials are generally used, and in the block axles, in order to raise fatigue strength, it is preferable to use surface-hardened materials in which the surface alone has been hardened by means of a carburizing process or the like.

For example, the blocks are formed by steel which contains nickel, chromium, molybdenum, and has a high carbon content and subjecting this to a hardening and tempering process, and the block axles are formed by steel which contains nickel, chromium, molybdenum, and has a low carbon content and subjecting this to carburization.

Claims

1. An excavation tool, in which a device (2) is provided which receives a striking force of a hammer and a rotational force of a hammer cylinder (1), in a bottom surface of which at least three axle holes (2a, 2b, 2c) are provided displaced from a center of said device (2) and at equivalent angular intervals in a circumferential direction, block axles (3a, 3b, 3c) are engaged in said axle holes (2a, 2b, 2c) in a freely rotatable manner, blocks (11a, 11b, 11c) which are roughly fan-shaped and have bits (4) embedded in lead end surfaces thereof are provided at lead end parts of said block axles (3a, 3b, 3c), so that left- and right-

side faces (12a, 12b) of said blocks (11a, 11b, 11c) are in mutual opposition and arc parts of all said blocks (11a, 11b, 11c) together form roughly a circle shape; and

when said device (2) is rotated in a direction of excavation, said blocks (11a, 11b, 11c) rotate as a result of resistance to excavation of a bottom part of an excavation hole, one intersection part of side faces (12a, 12b) and arc parts (12c) of said blocks (11a, 11b, 11c) protrudes beyond an outer circumferential surface of said device (2) by a predetermined excavation amount, and mutual positions of said block axles (3a, 3b, 3c) with respect to said blocks (11a, 11b, 11c) are so determined that both side faces (12a, 12b) of each said block come into contact with side faces (12a, 12b) of neighboring blocks at this time.

2. An excavation tool in accordance with claim 1, characterized in that excavated matter exhaust grooves (23) and projections (22a) used for centering, which are provided unitarily at an outer circumference of device (2), are disposed alternately in a circumferential direction between said device (2) and an excavation pipe (9) on an outer side thereof.

3. An excavation tool in accordance with claim 1, characterized in that an air exhaust hole (17) which extends in an axial direction is formed in a center of said device (2), passage holes (26, 27) having openings in lead end surfaces of said blocks (11a, 11b, 11c) and which extend in an axial direction are formed in said block axles (3a, 3b, 3c), a depth of said axle holes (2a, 2b, 2c) is set so as to be larger than a length of said block axles (3a, 3b, 3c), and connecting holes (24) connecting said air exhaust hole (17) and axle holes (2a, 2b, 2c) are formed in said device (2).

4. An excavation tool in accordance with claim 3, characterized in that grooves (28) are formed in the lead end surface of said blocks (11a, 11b, 11c), leading from edges of openings of said passage holes (26, 27) to said excavated matter exhaust grooves (23).

5. An excavation tool in accordance with claim 1, characterized in that an air exhaust hole (17) which extends in an axial direction is formed in a center of said device (2), said air exhaust hole (17) being connected through the medium of side holes (19) to air holes (20) which reach and have openings in a bottom surface of said device (2), and that excavated matter exhaust grooves (23) are formed in an outer circumferential surface of said device (2) and notches (21) which connect said excavated matter exhaust grooves (23) and

In the excavation tool of this preferred embodiment, block axle 103 is not exposed at the lead end surface of block 100, so that an advantage can be gained in that wear resulting from contact with excavated matter is prevented.

In the excavation tools of the second and seventh preferred embodiments above, the blocks and block axles are formed as separate parts. By precisely combining the materials which comprise these parts, it is possible to increase the dependability of the tool.

The following are examples of the qualities required for the blocks.

(1) They should not wear down quickly as a result of contact with rock layers in the earth (resistance to wear).

(2) As it is necessary to form a number of holes for the setting of the bits, they should be machine-manufacturable (machine manufacturability).

In contrast, in comparison with the blocks themselves, the block axles rarely come into contact with rock, and so a low resistance to wear is permissible. Furthermore, the block axles have a simple shape in comparison with the blocks, so that poor machine-manufacturability is also acceptable. However, as the block axles are repeatedly deformed by excavation, a high fatigue strength is necessary. Accordingly, in the blocks, in order to achieve ideal resistance to wear, hardened, tempered materials are generally used, and in the block axles, in order to raise fatigue strength, it is preferable to use surface-hardened materials in which the surface alone has been hardened by means of a carburizing process or the like.

For example, the blocks are formed by steel which contains nickel, chromium, molybdenum, and has a high carbon content and subjecting this to a hardening and tempering process, and the block axles are formed by steel which contains nickel, chromium, molybdenum, and has a low carbon content and subjecting this to carburization.

Claims

1. An excavation tool, in which a device (2) is provided which receives a striking force of a hammer and a rotational force of a hammer cylinder (1), in a bottom surface of which at least three axle holes (2a, 2b, 2c) are provided displaced from a center of said device (2) and at equivalent angular intervals in a circumferential direction, block axles (3a, 3b, 3c) are engaged in said axle holes (2a, 2b, 2c) in a freely rotatable manner, blocks (11a, 11b, 11c) which are roughly fan-shaped and have bits (4) embedded in lead end surfaces thereof are provided at lead end parts of said block axles (3a, 3b, 3c), so that left- and right-

side faces (12a, 12b) of said blocks (11a, 11b, 11c) are in mutual opposition and arc parts of all said blocks (11a, 11b, 11c) together form roughly a circle shape; and

when said device (2) is rotated in a direction of excavation, said blocks (11a, 11b, 11c) rotate as a result of resistance to excavation of a bottom part of an excavation hole, one intersection part of side faces (12a, 12b) and arc parts (12c) of said blocks (11a, 11b, 11c) protrudes beyond an outer circumferential surface of said device (2) by a predetermined excavation amount, and mutual positions of said block axles (3a, 3b, 3c) with respect to said blocks (11a, 11b, 11c) are so determined that both side faces (12a, 12b) of each said block come into contact with side faces (12a, 12b) of neighboring blocks at this time.

2. An excavation tool in accordance with claim 1, characterized in that excavated matter exhaust grooves (23) and projections (22a) used for centering, which are provided unitarily at an outer circumference of device (2), are disposed alternately in a circumferential direction between said device (2) and an excavation pipe (9) on an outer side thereof.

3. An excavation tool in accordance with claim 1, characterized in that an air exhaust hole (17) which extends in an axial direction is formed in a center of said device (2), passage holes (26, 27) having openings in lead end surfaces of said blocks (11a, 11b, 11c) and which extend in an axial direction are formed in said block axles (3a, 3b, 3c), a depth of said axle holes (2a, 2b, 2c) is set so as to be larger than a length of said block axles (3a, 3b, 3c), and connecting holes (24) connecting said air exhaust hole (17) and axle holes (2a, 2b, 2c) are formed in said device (2).

4. An excavation tool in accordance with claim 3, characterized in that grooves (28) are formed in the lead end surface of said blocks (11a, 11b, 11c), leading from edges of openings of said passage holes (26, 27) to said excavated matter exhaust grooves (23).

5. An excavation tool in accordance with claim 1, characterized in that an air exhaust hole (17) which extends in an axial direction is formed in a center of said device (2), said air exhaust hole (17) being connected through the medium of side holes (19) to air holes (20) which reach and have openings in a bottom surface of said device (2), and that excavated matter exhaust grooves (23) are formed in an outer circumferential surface of said device (2) and notches (21) which connect said excavated matter exhaust grooves (23) and



air holes (20) are provided in a bottom surface of said device.

6. An excavation tool in accordance with claim 1, characterized in that at one intersection point of side faces and lead end surfaces of said blocks (11a, 11b, 11c), sloping surfaces (15a, 15b, 15c) are provided which slope with respect to these surfaces, and a part of said bits (4) are embedded in said sloping surfaces (15a, 15b, 15c) in a vertical manner with respect to said sloping surfaces (15a, 15b, 15c). 5 10
7. An excavation tool in accordance with claim 1, characterized in that the outer circumferences of said blocks (11a, 11b, 11c) are formed by arcs (S1, S2) having differing radii, and when said device (2) rotates in said direction of excavation, a radius of an outer circumference of said blocks (11a, 11b, 11c) on a side which protrudes beyond said outer circumferential surface of said device (2) is set so as to be larger than a radius of an outer circumference of said blocks (11a, 11b, 11c) on side which does not protrude. 15 20 25
8. An excavation tool in accordance with claim 1, characterized in that said blocks axes (3a, 3b, 3c) and said blocks (11a, 11b, 11c) are joined in a mutually detachable manner. 30
9. An excavation tool in accordance with claim 8, characterized in that said block axes (3a, 3b, 3c) and said blocks (11a, 11b, 11c) comprise different materials. 35
10. An excavation tool in accordance with claim 8, characterized in that the fatigue strength of said block axes (3a, 3b, 3c) is set to be greater than the fatigue strength of said blocks (11a, 11b, 11c). 40
11. An excavation tool in accordance with claim 1, characterized in that said lead end surfaces of said blocks (11a, 11b, 11c) are provided with level surfaces (111a, 111b, 111c) which are positioned on a block axle side, and are perpendicular to said block axes (3a, 3b, 3c), first sloping surfaces (13a, 13b, 13c), which slope downwardly from arc-form ridge lines of said level surfaces (111a, 111b, 111c) in a direction of an outer circumference side of said device (2), and second sloping surfaces (14a, 14b, 14c), which slope downwardly from outer side arc-form ridge lines of said first sloping surfaces in the direction of said outer circumference side of said device (2), and that a step (112) is provided between said first and second sloping surfaces. 45 50 55

Patentansprüche

1. Bohrwerkzeug mit einer Einrichtung (2), die eine Schlagkraft eines Hammers und eine Rotationskraft eines Hammerzylinders (1) aufnimmt, in deren Bodenfläche mindestens drei Axialbohrungen (2a, 2b, 2c) vorgesehen sind, die in einem Abstand zum Mittelpunkt der Einrichtung (2) und mit gleichen Winkelabständen in Umfangsrichtung vorgesehen sind, wobei in den Achsbohrungen (2a, 2b, 2c) Blockachsen (3a, 3b, 3c) frei drehbar eingesetzt sind, wobei im wesentlichen fächerartige Blöcke (11a, 11b, 11c) mit an deren vorderen Endflächen eingebetteten Bohrspitzen (4) an den vorderen Endteilen der Blockachsen (3a, 3b, 3c) derart vorgesehen sind, daß linke und rechte Seitenflächen (12a, 12b) der Blöcke (11a, 11b, 11c) sich wechselseitig gegenüberliegen und Bogenteile sämtlicher Blöcke (11a, 11b, 11c) zusammen im wesentlichen ein kreisförmiges Äußeres bilden; und wobei bei einer Drehung der Einrichtung (2) in Bohrrichtung die Blöcke (11a, 11b, 11c) aufgrund des Bohrwiderstandes eines Bodenteils des Bohrloches rotieren, wobei ein Kreuzungsteil der Seitenflächen (12a, 12b) und der Bogenteile (12c) der Blöcke (11a, 11b, 11c) über eine äußere Umfangsfläche der Einrichtung (2) um einen vorbestimmten Bohrabstand vorsteht, und wobei die wechselseitigen Positionen der Blockachsen (3a, 3b, 3c) bezogen auf die Blöcke (11a, 11b, 11c) derart festgelegt sind, daß beide Seitenflächen (12a, 12b) jedes Blocks die Seitenflächen (12a, 12b) der benachbarten Blöcke zu diesem Zeitpunkt berühren.
2. Bohrwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß Auslaßkanäle (23) für Bohrmaterial und zum Zentrieren verwendete Vorsprünge (22a), die einstückig an einem Außenumfang der Einrichtung (2) vorgesehen sind, abwechselnd in Umfangsrichtung zwischen der Einrichtung (2) und einem Bohrröhr (9) an einer Außenseite derselben angeordnet sind.
3. Bohrwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß in der Mitte der Einrichtung (2) eine sich in Axialrichtung erstreckende Luftauslaßöffnung (17) ausgebildet ist, in den Blockachsen (3a, 3b, 3c) sich in Axialrichtung erstreckende Durchlaßöffnungen (26, 27) mit Öffnungen in vorderen Endflächen der Blöcke (11a, 11b, 11c) ausgebildet sind, eine Tiefe der Achsbohrungen (2a, 2b, 2c) derart gewählt ist, daß sie größer ist als eine Länge der Blockachsen (3a, 3b, 3c), und daß Verbindungskanäle (24) in der Einrichtung (2) ausgebil-



det sind, welche den Luftauslaßkanal (17) und die Achsbohrungen (2a, 2b, 2c) verbinden.

4. Bohrwerkzeug nach Anspruch 3, dadurch gekennzeichnet, daß
in der vorderen Endfläche der Blöcke (11a, 11b, 11c) Nuten (28) vorgesehen sind, die von den Rändern der Öffnungen der Durchlaßkanäle (26, 27) zu den Auslaßkanälen (23) für Bohrmaterial führen. 5 10
5. Bohrwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß
in der Mitte der Einrichtung (2) eine in Axialrichtung verlaufende Luftauslaßöffnung (17) ausgebildet ist, die durch Seitenkanäle (19) mit Luftkanälen (20) verbunden ist, die in einer Bodenfläche der Einrichtung (2) Öffnungen haben und erreichen, und daß an einer äußeren Umfangsfläche der Einrichtung (2) Auslaßkanäle (23) für Bohrmaterial und Schlitz (21) ausgebildet sind, welche die Auslaßkanäle (23) für Bohrmaterial verbinden, und daß Luftöffnungen (20) an einer Bodenfläche der Einrichtung vorgesehen sind. 15 20 25
6. Bohrwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß
an einem Kreuzungspunkt der Seitenflächen und der vorderen Endflächen der Blöcke (11a, 11b, 11c) geneigte Flächen (15a, 15b, 15c) vorgesehen sind, die sich bezogen auf diese Flächen neigen, und daß ein Teil der Bohrspitzen (4) in die geneigten Flächen (15a, 15b, 15c) bezogen auf die geneigten Flächen (15a, 15b, 15c) vertikal eingebettet ist. 30 35
7. Bohrwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß der Außenumfang der Blöcke (11a, 11b, 11c) durch Bogen (S1, S2) mit unterschiedlichen Radien gebildet wird, und daß bei Drehung der Einrichtung (2) in Bohrrichtung ein Radius eines Außenumfanges des Blockes (11a, 11b, 11c) an einer Seite, die über die äußere Umfangsfläche der Einrichtung (2) vorsteht, derart gewählt wird, daß er größer ist als der Radius eines Außenumfanges des Blockes (11a, 11b, 11c) an einer Seite, die nicht vorsteht. 40 45
8. Bohrwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß
die Blockachsen (3a, 3b, 3c) und die Blöcke (11a, 11b, 11c) jeweils lösbar befestigt sind. 50
9. Bohrwerkzeug nach Anspruch 8, dadurch gekennzeichnet, daß
die Blockachsen (3a, 3b, 3c) und die Blöcke (11a, 11b, 11c) unterschiedliche Materialien umfassen. 55

10. Bohrwerkzeug nach Anspruch 8, dadurch gekennzeichnet, daß
die Dauerfestigkeit der Blockachsen (3a, 3b, 3c) so gewählt wird, daß sie größer ist als die Dauerfestigkeit der Blöcke (11a, 11b, 11c).

11. Bohrwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß
die vorderen Endflächen der Blöcke (11a, 11b, 11c) mit ebenen Flächen (111a, 111b, 111c) versehen sind, die auf der Seite mit Blockachsen angeordnet sind und die senkrecht zu den Blockachsen (3a, 3b, 3c) verlaufen, sowie mit ersten geneigten Flächen (13a, 13b, 13c), die sich von bogenförmigen Gratlinien der ebenen Flächen (111a, 111b, 111c) in Richtung einer äußeren Umfangsseite der Einrichtung (2) nach unten neigen, und zweite geneigte Flächen (14a, 14b, 14c), die sich von außenseitigen bogenförmigen Gratlinien der ersten geneigten Flächen in Richtung der äußeren Umfangsseite der Einrichtung (2) nach unten neigen, und daß zwischen den ersten und zweiten geneigten Flächen eine Stufe (112) vorgesehen ist.

Revendications

1. Outil de terrassement, dans lequel un dispositif (2) est prévu qui reçoit la force de percussion d'un marteau et une force rotationnelle d'un cylindre (1) du marteau, dans une surface inférieure duquel au moins trois trous (2a, 2b, 2c) pour axes sont ménagés qui sont déplacés par rapport au centre dudit dispositif (2) et se trouvent à des intervalles angulaires identiques dans une direction circonférentielle, des axes (3a, 3b, 3c) de blocs sont engagés dans lesdits trous (2a, 2b, 2c) pour axes d'une manière librement rotative, des blocs (11a, 11b, 11c) qui ont approximativement la forme d'un éventail et comportent des taillants (4) encastrés dans leurs surfaces du côté avant sont prévus aux parties du côté avant desdits axes (3a, 3b, 3c) des blocs, de sorte que les faces des côtés gauche et droit (12a, 12b) desdits blocs (11a, 11b, 11c) sont en opposition mutuelle et les parties en arc de la totalité desdits blocs (11a, 11b, 11c) ont ensemble approximativement la forme d'un cercle; et
lorsque ledit dispositif (2) subit une rotation dans le sens de l'excavation, lesdits blocs (11a, 11b, 11c) tournent par suite de la résistance à l'excavation d'une partie inférieure d'un trou d'excavation, une partie d'intersection des faces de côté (12a, 12b) et des parties en arc (12c) desdits blocs (11a, 11b, 11c) est en saillie au-delà de la surface circonférentielle extérieure du dispositif (2) suivant une quantité d'excavation prédéter-



minée, et les positions mutuelles desdits axes (3a, 3b, 3c) des blocs par rapport auxdits blocs (11a, 11b, 11c) sont déterminées de façon que les deux faces de côté (12a, 12b) de chacun desdits blocs viennent en contact avec les faces de côté (12a, 12b) des blocs voisins à ce moment là.

2. Outil de terrassement selon la revendication 1, caractérisé en ce que des rainures (23) pour l'échappement de la matière excavée et des saillies (22a) servant au centrage, qui sont prévues unitairement à la circonférence extérieure du dispositif (2), sont disposées en alternance dans une direction circonférentielle entre ledit dispositif (2) et une conduite d'excavation (9) sur un côté extérieur de celui-ci. 10 15
3. Outil d'excavation selon la revendication 1, caractérisé en ce qu'un trou d'échappement d'air (17) qui s'étend dans la direction axiale est pratiqué au centre dudit dispositif (2), des trous de passage (26, 27) comportant des ouvertures dans les surfaces du côté avant desdits blocs (11a, 11b, 11c) et qui s'étendent dans la direction axiale sont formés dans lesdits axes (3a, 3b, 3c) des blocs, la profondeur desdits trous (2a, 2b et 2c) des axes est réglée de façon à être supérieure à la longueur desdits axes (3a, 3b, 3c) des blocs, et des trous de liaison (24) reliant ledit trou d'échappement d'air (17) et les trous (2a, 2b, 2c) des axes sont formés dans ledit dispositif (2). 20 25 30
4. Outil de terrassement selon la revendication 3, caractérisé en ce que des rainures (28) sont formées dans la surface, côté avant, desdits blocs (11a, 11b, 11c), allant des bords des ouvertures desdits trous de passage (26, 27) jusqu'auxdites rainures (23) d'échappement de la matière excavée. 35 40
5. Outil de terrassement selon la revendication 1, caractérisé en ce qu'un trou d'échappement d'air (17) qui s'étend dans la direction axiale est ménagé au centre du dit dispositif (2), ledit trou d'échappement d'air (17) étant relié par des trous de côté (19) à des trous d'air (20) qui atteignent et comportent des ouvertures dans la surface inférieure du dispositif (2), et en ce que des rainures (23) d'échappement de la matière excavée sont pratiquées dans la surface circonférentielle extérieure dudit dispositif (2) et des encoches (21) qui relient lesdites rainures (23) d'échappement de la matière excavée et les trous d'air (20) sont pratiquées dans la surface inférieure dudit dispositif. 45 50 55
6. Outil de terrassement selon la revendication 1, caractérisé en ce qu'à un point d'intersection des faces de côté et des surfaces côté avant desdits

blocs (11a, 11b, 11c), des surfaces en pente (15a, 15b, 15c) sont prévues qui sont en pente par rapport à ces surfaces, et une partie desdits taillants (4) est encastrée dans lesdites surfaces en pente (15a, 15b, 15c) d'une façon verticale par rapport auxdites surfaces en pente (15a, 15b, 15c).

7. Outil de terrassement selon la revendication 1, caractérisé en ce que les circonférences extérieures desdits blocs (11a, 11b, 11c) comportent des arcs (S1, S2) ayant des rayons différents, et lorsque ledit dispositif (2) tourne dans ladite direction d'excavation, le rayon de la circonférence extérieure desdits blocs (11a, 11b, 11c) sur un côté qui est en saillie au delà de ladite surface circonférentielle extérieure dudit dispositif (2) est choisi de façon à être supérieur au rayon de la circonférence extérieure desdits blocs (11a, 11b, 11c) sur le côté qui n'est pas en saillie.
8. Outil de terrassement selon la revendication 1, caractérisé en ce que lesdits axes (3a, 3b, 3c) des blocs et lesdits blocs (11a, 11b, 11c) sont réunis d'une manière mutuellement détachable.
9. Outil de terrassement selon la revendication 8, caractérisé en ce que lesdits axes (3a, 3b, 3c) des blocs et lesdits blocs (11a, 11b, 11c) sont constitués de matériaux différents.
10. Outil de terrassement selon la revendication 8, caractérisé en ce que la résistance à la fatigue desdits axes (3a, 3b, 3c) des blocs est choisie de façon à être supérieure à la résistance à la fatigue desdits blocs (11a, 11b, 11c).
11. Outil de terrassement selon la revendication 1, caractérisé en ce que lesdites surfaces du côté avant desdits blocs (11a, 11b, 11c) présentent des surfaces de niveau (111a, 111b, 111c) qui sont positionnées sur un côté des axes des blocs, et sont perpendiculaires auxdits axes (3a, 3b, 3c) des blocs, des premières surfaces en pente (13a, 13b, 13c) qui sont en pente vers le bas à partir des lignes de la bordure en forme d'arc desdites surfaces de niveau (111a, 111b, 111c) dans la direction du côté de la circonférence extérieure du dispositif (2), et des secondes surfaces en pente (14a, 14b, 14c) qui sont en pente vers le bas à partir des lignes de la bordure en forme d'arc du côté extérieur desdites premières surfaces en pente dans le sens dudit côté de la circonférence extérieure dudit dispositif (2), et en ce qu'un gradin (112) est formé entre lesdites premières et secondes surfaces en pente.

