

Description

The present invention relates to an alarm device for informing an operator of the appropriate end-of-cooking timing for food items. The alarm device is generally used in a cooker for cooking foods in cooking liquids such as oil or water.

In cooking apparatus such as fryer apparatus and noodle cookers for cooking food items in a cooking liquid medium, determination of the appropriate heating amount is required for desirable cooking of food items. A generally used alarm device accumulates the heating amount and informs the operator with a buzzer of the appropriate end-of-cooking timing when the accumulated value reaches a predetermined limit. For example, in a fryer apparatus, the operator presses a start pad on the alarm device to initiate the accumulation of heating amount simultaneously when food items are placed into cooking oil whose temperature is maintained in a fixed range. When the heating amount reaches a predetermined value, the buzzer tells the operator the end-of-cooking timing when the food items are to be taken out of a frypot in the fryer apparatus.

Such a conventional alarm device requires the operator to press the start pad simultaneously with placing food items into a cooking liquid. This manual operation is relatively troublesome. Moreover, if the operator forgets to press the start pad, the alarm device does not inform the operator of the appropriate timing for taking food items out of the cooking liquid. This may cause over-cooking of the food items and their taste, flavor and texture may suffer.

In the conventional fryer apparatus, heat input e.g. combustion is controlled ON and OFF to maintain the oil temperature within a predetermined range. When food items are placed into the cooking liquid under the heating or combustion OFF condition, the fryer apparatus cannot resume combustion immediately, but there is a certain time delay before re-start of combustion. This time lag is generally attributed to the temperature sensor which detects the drop in oil temperature below a predetermined value after some delay due to the uneven temperature distribution in the cooking oil and convection in the oil in the frypot. The conventional system resumes heating or combustion after the temperature in the cooking oil around the cold food items falls undesirably, which may cause underdoing or overdoing of food items.

One object of the invention is to provide a novel alarm device for informing the operator of the end-of-cooking timing.

Another object of the invention is to improve usability of the alarm device which works without troublesome manual operation, that is, without

pressing a start pad simultaneously with placing food items into a cooking liquid medium.

Still another object of the invention is to minimize time lag between placing food items into a cooking liquid and the start of heating.

A further object of the invention is to provide an improved alarm device which minimizes abrupt temperature drops in the cooking liquid medium.

The present invention is as claimed in the claims.

In the alarm device of the invention, the accumulation unit determines a heating amount based on the temperature of the cooking medium detected by the temperature detecting unit and heating time. The alarm unit informs the operator of the end-of-cooking timing when the accumulated value reaches a predetermined value. Accumulation of the heating amount starts in the following manner. When food items are placed into the cooking medium, the temperature of the liquid abruptly drops due to the cold food items. When the temperature of the liquid medium falls steeply, or more specifically when the downward slope detected by the slope comparing unit becomes equal to or greater than a predetermined limit, the first control unit controls the accumulation unit to start determining the accumulated heating amount. This system of the invention automatically detects presence of food items in the cooking liquid medium and starts accumulation of the heating amount, thus making the operator free from the troublesome manual operation as pressing a start pad.

The alarm device of the invention may further include a second control unit for controlling the cooker to start forcible heating of the cooking liquid medium irrespective of the temperature control conditions of the cooker, when the accumulation unit starts accumulating the heating amount.

The second control unit controls the cooker to start forcible heating or combustion irrespective of the temperature control conditions of the cooker when accumulation of the heating amount is started or when presence of food items in the cooking liquid medium is detected. The cooker forcibly starts heating or combustion regardless of a delay in detection of the temperature drop by the temperature detecting unit due to the response characteristics of the detecting unit and the uneven temperature distribution of the cooking liquid medium. This feature of the invention prevents an undesirable time lag between substantial drop in temperature and start of heating and efficiently reduces the temperature fall due to cold food items, thus allowing food items to be cooked desirably.

The present invention will now be explained by way of example only in the following detailed description, to be read with reference to the accom-

panying drawings, in which:

Fig. 1 schematically illustrates a fryer apparatus embodying the invention; and

Fig. 2 is a flowchart showing an end-of-cooking timing detection routine.

Fig. 1 is a schematic view illustrating a fryer apparatus including an alarm device for informing the operator of the appropriate end-of-cooking timing, and constituting a preferred embodiment of the invention. Although the alarm device is incorporated in the fryer apparatus in this embodiment, it may be externally attached to the fryer apparatus according to requirements. The fryer apparatus of the embodiment used for cooking or deep fat frying of food items such as french fries or breaded chickens includes: a frypot 10 which is filled with cooking liquid or oil; a pulse combustor 20 for heating the cooking oil in the frypot 10; a combustion controller 40 for controlling combustion of the pulse combustor 20; and an alarm device 50 for accumulating the heating amount and informing the operator of the appropriate end-of-cooking timing.

The pulse combustor 20 in the fryer apparatus has a combustion-exhaust system, an air supply system, and a fuel gas supply system.

The combustion-exhaust system includes: a combustion chamber 21 disposed in the frypot 10 for pulse combustion; a tail pipe 22 winding its way through the frypot 10 and constituting an exhaust conduit for hot combustion byproducts from the combustion chamber 21; and an exhaust muffler 23 placed in the middle of the tail pipe 22. The cooking oil in the frypot 10 is heated by thermal energy transmitted through the outside walls of the combustion chamber 21 and the tail pipe 22. A temperature sensor 11 for detecting the temperature of the cooking oil in the frypot 10 is attached to the side wall of the frypot 10.

The air supply system for supplying air to the combustion chamber 21 includes: a fan 24 for feeding the air for combustion; an intake muffler 25 connected to the fan 24; and an air chamber 26 coupled to the combustion chamber 21 for receiving the air fed through the intake muffler 25.

The fuel gas supply system includes: first and second electromagnetic valves 28 and 29 mounted in a gas conduit 27 for opening and closing a flow path of fuel gas; and a gas chamber 30 disposed in the air chamber 26.

In the air chamber 26, there is a mixing chamber 31 coupled with and connected to the gas chamber 30. The fuel gas is supplied into the mixing chamber 31 via the gas chamber 30 while the air being supplied thereto via the air chamber 26. The separately supplied fuel gas and air are mixed in the mixing chamber 31 and transmitted to the combustion chamber 21 as an air/fuel mixture. The combustion chamber 21 is provided with an

ignition plug 32 for igniting the air/fuel mixture on the commencement of combustion, and a flame rod 33 for detecting the flame.

The pulse combustor 20 thus constructed repeats explosion and combustion at a fixed cycle by taking advantage of its automatic ignition and absorption characteristics at stationary combustion. In the embodiment, a pair of check valves or flapper valves (not shown) are attached to the respective inlets of the fuel gas and the air to the mixing chamber 31 so as to prevent back flow of combustion exhaust into the fuel gas supply system and the air supply system.

The combustion controller 40 for controlling combustion of the pulse combustor 20 is constructed as a microcomputer including: a conventional arithmetic/logic/operation circuit consisting of a CPU or central processing unit, a ROM or read only memory, and a RAM or random access memory, an input interface for inputting signals sent from the temperature sensor 11 and the flame rod 33, and an output interface for outputting control signals to the first and second electromagnetic valves 28 and 29, the fan 24, and an igniter 34.

The combustion controller 40 starts and stops combustion (controls combustion ON and OFF) to maintain the temperature of cooking oil in a predetermined range. In this preferred embodiment, combustion starts when the temperature on the temperature sensor 11 falls below 180°C, and combustion stops when the temperature rises over 182°C. The temperature of the cooking oil is thus efficiently maintained in a range between 180°C and 182°C. Food items held in a food basket (not shown) are placed and deep fried in the cooking oil which is heated and maintained in the above predetermined range.

The alarm device 50 is, like the combustion controller 40, constructed as a micro-computer constituting an arithmetic/logic/operation circuit. The alarm device 50 is connected to the temperature sensor 11 and an audible signaller or buzzer 51 for actually informing the operator of the end-of-cooking timing. The alarm device 50 also outputs a control signal to the combustion controller 40 for initiating forcible combustion.

An end-of-cooking timing detection routine executed by the alarm device 50 is described according to the flowchart of Fig. 2. Along with this end-of-cooking timing detection routine by the alarm device 50, the temperature sensor 11 detects the temperature of cooking oil and the combustion controller 40 executes a combustion control routine.

When the power of the fryer apparatus is on to start this routine, the alarm device 50 waits until the temperature of cooking oil detected by the temperature sensor 11 at a fixed cycle abruptly drops,

more concretely until the downward slope (degree/second) in oil temperature becomes equal to or greater than a predetermined slope K (step S10). When no food items are placed in cooking oil, the oil temperature gradually increases or decreases corresponding to the ON/OFF control of the combustion controller 40. Under such conditions, the answer is consistently NO at step S10. When food items are placed in cooking oil, on the contrary, the oil temperature abruptly drops due to the cold food items, and the downward slope in oil temperature becomes equal to or greater than the predetermined slope K (degree/second). Here the answer at the determination point S10 changes to YES. In this manner, the alarm device 50 automatically detects placing food items in cooking oil.

The program then proceeds to step S11 at which the alarm device 50 outputs a control signal for initiating forcible combustion to the combustion controller 40, and subsequently to step S12 at which the alarm device 50 starts accumulation of the heating amount.

Since the food items are placed into cooking oil at any desired time as long as the oil temperature is maintained in a predetermined range as described above, the pulse combustor 20 may be OFF according to the instruction of the combustion controller 40. In this case, the pulse combustor 20 should resume combustion as soon as possible to prevent an undesirable drop in the oil temperature due to the cold food items. There is, however, a certain time lag between substantial drop in oil temperature and start of heating because of convection of oil and uneven temperature distribution. In other words, the temperature sensor 11 detects the drop of oil temperature below the predetermined range after some delay.

In the embodiment, to overcome this drawback of the conventional system, when detecting existence of food items in cooking oil, the alarm device 50 outputs the control signal to the combustion controller 40 to initiate combustion forcibly irrespective of the combustion conditions of the pulse combustor 20. The pulse combustor 20 is thus forcibly driven to resume or continue combustion regardless of the oil temperature. This improvement reduces the undesirable temperature fall due to the delay of response.

At step S12, the heating amount is accumulated as an integral of oil temperature over time which is obtained through repetitive processing of steps S12 through S15. The heating amount thus accumulated depends upon the oil temperature. The accumulated value for a certain time period is greater for a higher oil temperature than for a relatively lower temperature.

After initiating forcible combustion at step S11, the program proceeds to step S13 at which the

alarm device 50 determines whether the combustion conditions should change to normal ON/OFF control. When the answer is YES at step S13, the program goes to step S14 at which the alarm device 50 outputs a restoration signal for resuming ON/OFF control to the combustion controller 40. This restoration timing may be set as, for example, when a fixed time has elapsed since the start of forcible combustion, or when the temperature at the temperature sensor 11 becomes lower than a predetermined value (for example, 180 °C).

The program then proceeds to step S15 at which the heating amount accumulated at step S12 is compared with a preset heating amount Q. The processing of steps S12 through S15 are repetitively executed until the accumulated heating amount reaches the optimum preset value Q for desirable cooking of the food items. When the heating amount reaches the preset value Q, the program goes to step S16 at which the buzzer 51 informs the operator of the end-of-cooking timing when the food items are to be taken out of the cooking oil. The program initialises all variables including the accumulated value and returns to step S10.

As described above, the fryer apparatus of the embodiment detects presence of food items in cooking oil based on the downward slope of the oil temperature gradient, and informs the operator of the appropriate end-of-cooking timing according to the heating amount accumulated after the detection. The structure of the embodiment makes the operator free from troublesome manual operation as pressing a start pad simultaneously with placing food items into cooking oil, and is thus favorably used by any operators. Whenever detecting presence of food items in cooking oil, the alarm device of the embodiment outputs a control signal to the combustion controller to initiate forcible combustion irrespective of the combustion conditions of the pulse combustor 20. This forcible combustion system prevents an undesirable time lag between a substantial drop in oil temperature and start of heating and efficiently reduces the temperature fall due to cold food items, thus allowing food items to be cooked desirably. The system also changes the heating conditions from forcible combustion to normal ON/OFF control at a predetermined timing, thus effectively preventing over-heating of cooking oil.

Since there may be many modifications, alterations, and changes without departing from the scope of the appended claims, it is clearly to be understood that the above embodiment is only illustrative and not restrictive in any sense. For example, while the alarm device is applied to the fryer apparatus including a pulse combustor as a heat source in the embodiment, it may be applied

to various cooking apparatus and cookers with Bunsen burners or electric heaters, so "combustion" or the like is to be construed to mean, broadly, "heating". The alarm device is incorporated in the fryer apparatus in the embodiment, but a separate alarm device may be attached to the cooker, or the combustion controller may have functions of the alarm device.

Claims

1. A cooker comprising a heat source for heating a pot (10) filled with cooking liquid medium, and including an alarm device, said alarm device comprising:
 - temperature detecting means (11) for detecting temperature of said cooking liquid medium;
 - accumulation means (50; S12) for timing the cooking process by determining an accumulated heating amount based on the temperature detected by said temperature detecting means (11) and heating time;
 - alarm means (51) for informing an operator of an end-of-cooking timing when the accumulated heating amount determined by said accumulation means reaches a predetermined value;
 - slope comparing means (S10) for detecting a slope in the detected temperature of said cooking liquid medium so as to be able to compare it with a predetermined limit; and
 - first control means (S12) which automatically initiates said accumulation means for timing the cooking process when the slope comparing means (S10) detect a downward slope equal to or greater than said predetermined limit.
2. A cooker in accordance with claim 1, further comprising second control means (S11) for controlling said cooker (10) to start forcible heating of said cooking liquid medium irrespective of the temperature control conditions of said cooker when said accumulation means (50; S12) starts accumulating the heating amount.
3. A cooker in accordance with claim 2, further comprising restoration means (S13) for controlling said cooker (10) to stop forcible heating and resume normal heating conditions.
4. A cooker as claimed in any preceding claim comprising a pot (10) filled with said cooking liquid medium, and controlling means (40) for controlling said heat source.

5. A cooker as claimed in claim 4, wherein said pot is a frypot (10) filled with cooking oil as said cooking liquid medium, said heat source is a pulse combustor (21) for heating said cooking oil in said frypot, and said controlling means (40) controls said pulse combustor.

Patentansprüche

1. Speisezubereitungsgerät, das eine Wärmequelle zum Erwärmen eines Gefäßes umfaßt, das mit einem flüssigen Garmedium gefüllt ist, welches eine Alarmeinrichtung einschließt, wobei die Alarmeinrichtung umfaßt:
 - einen Temperaturfühler (11) zum Ermitteln der Temperatur des flüssigen Garmediums;
 - eine Akkumulationseinrichtung (50; S12), die dazu dient, das Verfahren zum Garen zeitlich zu steuern, indem sie eine akkumulierte Wärmemenge ermittelt, die auf der Temperatur, die durch den Temperaturfühler (11) gemessen wird, und der Erwärmungszeit basiert;
 - ein Alarmmittel (51), das dazu dient, eine Bedienungsperson vom Ende der Garzeit in Kenntnis zu setzen, wenn die akkumulierte Wärmemenge, die durch die Akkumulationseinrichtung ermittelt ist, einen vorbestimmten Wert erreicht;
 - ein Steigungsvergleichsmittel (S10), das dazu dient, die Steigung bei der gemessenen Temperatur des flüssigen Garmediums zu ermitteln, um sie mit einem vorbestimmten Grenzwert vergleichen zu können; und
 - ein erstes Steuerungsmittel (S12), welches die Akkumulationseinrichtung automatisch in Gang setzt, um das Verfahren zum Garen zeitlich zu steuern, wenn das Steigungsvergleichsmittel (S10) eine negative Steigung ermittelt, die gleich oder größer als der vorbestimmte Grenzwert ist.
2. Speisezubereitungsgerät nach Anspruch 1, weiter umfassend ein zweites Steuerungsmittel (S11), das dazu dient, das Speisezubereitungsgerät (10) so zu steuern, daß eine starke Erwärmung des flüssigen Garmediums ungeachtet der Temperatur-Steuerungszustände des Speisezubereitungsgerätes in Gang gesetzt wird, wenn die Akkumulationseinrichtung (50; S12) mit der Akkumulation der Wärmemenge beginnt.
3. Speisezubereitungsgerät nach Anspruch 2, weiter umfassend ein Rückstellmittel (S13), das dazu dient, das Speisezubereitungsgerät (10) so zu steuern, daß die starke Erwärmung eingestellt wird und das normale Erwärmen wiederaufgenommen wird.



to various cooking apparatus and cookers with Bunsen burners or electric heaters, so "combustion" or the like is to be construed to mean, broadly, "heating". The alarm device is incorporated in the fryer apparatus in the embodiment, but a separate alarm device may be attached to the cooker, or the combustion controller may have functions of the alarm device.

Claims

1. A cooker comprising a heat source for heating a pot (10) filled with cooking liquid medium, and including an alarm device, said alarm device comprising:
 - temperature detecting means (11) for detecting temperature of said cooking liquid medium;
 - accumulation means (50; S12) for timing the cooking process by determining an accumulated heating amount based on the temperature detected by said temperature detecting means (11) and heating time;
 - alarm means (51) for informing an operator of an end-of-cooking timing when the accumulated heating amount determined by said accumulation means reaches a predetermined value;
 - slope comparing means (S10) for detecting a slope in the detected temperature of said cooking liquid medium so as to be able to compare it with a predetermined limit; and
 - first control means (S12) which automatically initiates said accumulation means for timing the cooking process when the slope comparing means (S10) detect a downward slope equal to or greater than said predetermined limit.
2. A cooker in accordance with claim 1, further comprising second control means (S11) for controlling said cooker (10) to start forcible heating of said cooking liquid medium irrespective of the temperature control conditions of said cooker when said accumulation means (50; S12) starts accumulating the heating amount.
3. A cooker in accordance with claim 2, further comprising restoration means (S13) for controlling said cooker (10) to stop forcible heating and resume normal heating conditions.
4. A cooker as claimed in any preceding claim comprising a pot (10) filled with said cooking liquid medium, and controlling means (40) for controlling said heat source.

5. A cooker as claimed in claim 4, wherein said pot is a frypot (10) filled with cooking oil as said cooking liquid medium, said heat source is a pulse combustor (21) for heating said cooking oil in said frypot, and said controlling means (40) controls said pulse combustor.

Patentansprüche

1. Speisezubereitungsgerät, das eine Wärmequelle zum Erwärmen eines Gefäßes umfaßt, das mit einem flüssigen Garmedium gefüllt ist, welches eine Alarmeinrichtung einschließt, wobei die Alarmeinrichtung umfaßt:
 - einen Temperaturfühler (11) zum Ermitteln der Temperatur des flüssigen Garmediums;
 - eine Akkumulationseinrichtung (50; S12), die dazu dient, das Verfahren zum Garen zeitlich zu steuern, indem sie eine akkumulierte Wärmemenge ermittelt, die auf der Temperatur, die durch den Temperaturfühler (11) gemessen wird, und der Erwärmungszeit basiert;
 - ein Alarmmittel (51), das dazu dient, eine Bedienungsperson vom Ende der Garzeit in Kenntnis zu setzen, wenn die akkumulierte Wärmemenge, die durch die Akkumulationseinrichtung ermittelt ist, einen vorbestimmten Wert erreicht;
 - ein Steigungsvergleichsmittel (S10), das dazu dient, die Steigung bei der gemessenen Temperatur des flüssigen Garmediums zu ermitteln, um sie mit einem vorbestimmten Grenzwert vergleichen zu können; und
 - ein erstes Steuerungsmittel (S12), welches die Akkumulationseinrichtung automatisch in Gang setzt, um das Verfahren zum Garen zeitlich zu steuern, wenn das Steigungsvergleichsmittel (S10) eine negative Steigung ermittelt, die gleich oder größer als der vorbestimmte Grenzwert ist.
2. Speisezubereitungsgerät nach Anspruch 1, weiter umfassend ein zweites Steuerungsmittel (S11), das dazu dient, das Speisezubereitungsgerät (10) so zu steuern, daß eine starke Erwärmung des flüssigen Garmediums ungeachtet der Temperatur-Steuerungszustände des Speisezubereitungsgerätes in Gang gesetzt wird, wenn die Akkumulationseinrichtung (50; S12) mit der Akkumulation der Wärmemenge beginnt.
3. Speisezubereitungsgerät nach Anspruch 2, weiter umfassend ein Rückstellmittel (S13), das dazu dient, das Speisezubereitungsgerät (10) so zu steuern, daß die starke Erwärmung eingestellt wird und das normale Erwärmen wiederaufgenommen wird.



4. Speisezubereitungsgerät nach einem beliebigen vorhergehenden Anspruch, das ein Gefäß (10), das mit dem flüssigen Garmedium gefüllt ist, und ein Steuerungsmittel (40) zum Steuern der Wärmequelle umfaßt.
5. Speisezubereitungsgerät nach Anspruch 4, bei dem das Gefäß ein Fritierbehälter (10) ist, der mit Garöl als flüssiges Garmedium gefüllt ist, und bei dem die Wärmequelle zum Erwärmen des Garöls im Fritierbehälter ein Impuls-Gasbrenner (21) ist und das Steuerungsmittel (40) den Impuls-Gasbrenner steuert.

Revendications

1. Appareil de cuisson comprenant une source de chaleur pour chauffer une marmite remplie d'un milieu liquide de cuisson, et un dispositif d'alarme, ledit dispositif d'alarme comprenant :
 - un moyen (11) de détection de température pour détecter la température dudit milieu liquide de cuisson,
 - un moyen (50 ; S12) d'accumulation pour minuter le processus de cuisson par détermination d'une quantité de chauffage accumulée par rapport à la température détectée par ledit moyen (11) détecteur de température et au temps de chauffage,
 - un moyen d'alarme (51) pour informer un opérateur d'un moment de fin de cuisson lorsque la quantité de chauffage accumulée et déterminée par ledit moyen d'accumulation atteint une valeur prédéterminée,
 - un moyen (S10) de comparaison de pente pour détecter une pente dans la température détectée dudit milieu liquide de cuisson afin de pouvoir la comparer à une valeur limite prédéterminée, et
 - un premier moyen (S12) de commande qui amorce automatiquement ledit moyen d'accumulation pour minuter le processus de cuisson lorsque le moyen (S10) de comparaison de pente détecte une pente descendante égale ou supérieure à ladite valeur limite prédéterminée.
2. Appareil de cuisson selon la revendication 1 comprenant en outre un second moyen (S11) de commande pour commander ledit appareil de cuisson (10) afin de démarrer le chauffage forcé dudit milieu liquide de cuisson sans tenir compte des conditions de régulation de température dudit appareil de cuisson lorsque ledit moyen (50 ; S12) d'accumulation commence

l'accumulation de la quantité de chauffage.

3. Appareil de cuisson selon la revendication 2 comprenant en outre un moyen (S13) de restauration pour commander ledit appareil (10) de cuisson afin d'arrêter le chauffage forcé et reprendre le régime de chauffage normal.
4. Appareil de cuisson selon l'une quelconque des revendications précédentes comprenant une marmite (10) remplie dudit milieu liquide de cuisson et un moyen (40) de commande pour commander ladite source de chaleur.
5. Appareil de cuisson selon la revendication 4 dans lequel ladite marmite est une marmite (10) à frêre remplie d'huile de cuisson en tant que dit milieu liquide de cuisson, ladite source de chaleur est une chambre (21) de combustion à impulsions destinée à chauffer ladite huile de cuisson dans ladite marmite à frêre, et ledit moyen (40) de commande commande ladite chambre de combustion à impulsions.

5

10

15

20

25

30

35

40

45

50

55

6