PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :
G11B 5/02

A2

(11) International Publication Number: WO 95/35563

(43) International Publication Date: 28 December 1995 (28.12.95)

(21) International Application Number: PCT/IB95/00431

(22) International Filing Date: 6 June 1995 (06.06.95)

(30) Priority Data:
94201659.3 10 June 1994 (10.06.94) EP

(34) Countries for which the regional or international application was filed: AT et al.

(71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 5, Kista, S-164 85 Stockholm (SE).

(72) Inventors: VOORMAN, Johannes, Otto; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). POTHAST, Hendrik, Jan; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). WONG-LAM, Ho, Wai; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(74) Agent: HESSELMANN, Gerardus, Johannes, Maria; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).

(81) Designated States: JP, KR, SG, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published
Without international search report and to be republished upon receipt of that report.


9612067-0

RTMP's copy
where's A3?
↳ received
on
6/10/97

(54) Title: ARRANGEMENT COMPRISING A MAGNETIC WRITE HEAD, AND WRITE AMPLIFIER WITH CAPACITIVE CURRENT COMPENSATION

(57) Abstract

A write amplifier (4) comprising four current mirrors (14, 22, 30 and 38) which are turned on two at a time by two switchable floating current sources (46, 48) between the input terminals (16, 40; 24, 32) of the current mirrors in order to produce a write current of alternating polarity through the write head (2). The parasitic capacitances across the write head (2) and/or the parasitic capacitances of the write amplifier (4) at the write terminals (6, 8) are neutralised by means of neutralising capacitors (142, 144, 146, 148). The high impedance at the terminals (6, 8) of the write head (2) enables the common-mode voltage across the write head (2) to be fixed at any desired voltage value by means of a common-mode circuit.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	**GB**	United Kingdom	**MR**	Mauritania
AU	Australia	**GE**	Georgia	**MW**	Malawi
BB	Barbados	**GN**	Guinea	**NE**	Niger
BE	Belgium	**GR**	Greece	**NL**	Netherlands
BF	Burkina Faso	**HU**	Hungary	**NO**	Norway
BG	Bulgaria	**IE**	Ireland	**NZ**	New Zealand
BJ	Benin	**IT**	Italy	**PL**	Poland
BR	Brazil	**JP**	Japan	**PT**	Portugal
BY	Belarus	**KE**	Kenya	**RO**	Romania
CA	Canada	**KG**	Kyrgystan	**RU**	Russian Federation
CF	Central African Republic	**KP**	Democratic People's Republic of Korea	**SD**	Sudan
CG	Congo			**SE**	Sweden
CH	Switzerland	**KR**	Republic of Korea	**SI**	Slovenia
CI	Côte d'Ivoire	**KZ**	Kazakhstan	**SK**	Slovakia
CM	Cameroon	**LI**	Liechtenstein	**SN**	Senegal
CN	China	**LK**	Sri Lanka	**TD**	Chad
CS	Czechoslovakia	**LU**	Luxembourg	**TG**	Togo
CZ	Czech Republic	**LV**	Latvia	**TJ**	Tajikistan
DE	Germany	**MC**	Monaco	**TT**	Trinidad and Tobago
DK	Denmark	**MD**	Republic of Moldova	**UA**	Ukraine
ES	Spain	**MG**	Madagascar	**US**	United States of America
FI	Finland	**ML**	Mali	**UZ**	Uzbekistan
FR	France	**MN**	Mongolia	**VN**	Viet Nam
GA	Gabon				

96 12067-0