

SPECIFICATION

HYDRAULIC MACHINE, OPENING FLANGE OF HYDRAULIC MACHINE AND METHOD OF PRODUCTION THEREOF

TECHNICAL FIELD

5 The present invention relates to a hydraulic machine, in particular, a flange member provided around a fluid inlet opening or a fluid outlet opening of a hydraulic machine for connection of the opening with an outside conduit means.

BACKGROUND OF THE INVENTION

10 In a hydraulic machine such as a pump, it is common for a flange to be provided around a fluid inlet opening and/or a fluid outlet opening so that, when a separate outside conduit means is connected to the opening, a flange provided at an end of the conduit means is aligned with and
15 connected to the flange of the fluid machine and securely fastened by fastener means such as bolts and nuts.

 Fig. 5 shows an example of such a conventional flange provided on a hydraulic machine. In this example, a short tubular member 12 is connected at a rim of an opening of the
20 machine at one end thereof and is provided at the other end with a flange member 18 made of a sheet like member. The flange member 18 is provided on its inside surface with an annular reinforcement member 22, and the reinforcement member is supported by a bracket 24. When a conduit member
25 is connected to the flange member 22, a flange of the conduit member is engaged with the flange 18 with a gasket being interposed therebetween and fastened to the flange 18 by means of bolts and nuts or the like.

In this conventional art, the members 22 and 24 for reinforcing the flange 18 are prepared separately from the flange in order to reduce an amount of nonferrous metal material to be used to form elements that come into contact
5 with a fluid passing through the machine in operation thereby reducing costs.

Fig. 6 shows another conventional art in which a flange 30 is integrally formed with a body of a hydraulic machine and machined to form an O-ring receiving groove in
10 its surface. When connected to a conduit means, the flange is provided with an O-ring in the groove to hermetically seal the connection between the flange and the conduit means.

However, the above-noted conventional arts involve the following problems.

15 In the first conventional art, in order to assure sealing of the connection between the flange member 18 and a conduit means connected thereto, it is necessary for the flange member 18 to have a highly finished surface. However, heat transmitted to the flange member 18 during welding of
20 the reinforcement member 22 to the flange member 18 affects the surface of the flange member 18 and causes a deterioration in the degree of finishing of the surface. Further, since the flange member 18 is generally formed of stainless steel, a friction coefficient of the surface of
25 the flange member 18 is small and thus a gasket interposed between the flange member 18 and a conduit connected thereto tends to slide thereby causing a lowering in sealing therebetween.

The conventional art shown in Fig. 6 involves a problem of high costs in producing the flange 30 as machining of the flange is required to form the O-ring receiving groove 32.

5 In light of the above-noted problems in the conventional arts, the present invention is directed to a flange member which can facilitate formation of a highly reliable seal and can be produced at low cost, a hydraulic machine with such a flange and a method of production
10 thereof.

DISCLOSURE OF THE INVENTION

 The present invention provides an annular flange member adapted to be provided around a fluid passage opening of a housing of a hydraulic machine to connect a fluid
15 conduit means to the fluid passage opening. The annular flange member comprises an inside surface facing the housing, an outside surface opposite the inside surface, and a through hole extending from the inside surface to the outside surface and fluidly communicated with the fluid
20 passage opening. The outside surface is provided with a press formed O-ring receiving groove surrounding the through hole.

 The O-ring receiving groove may be formed by a half die cutting press operation.

25 Specifically, the flange member may include an annular projection formed on the inside surface corresponding to the O-ring receiving groove and a recess formed in the inside surface around a root of the annular projection.

Further, the present invention provides a hydraulic machine including a housing having a fluid passage opening, wherein the hydraulic machine comprises a flange member formed separately from the housing and provided at the fluid passage opening, and the flange member is an annular member having an inside surface facing the housing, an outside surface opposite the inside surface and a through hole extending from the inside surface to the outside surface and fluidly communicated with the fluid passage opening, the outside surface being formed with a press formed O-ring receiving groove therein surrounding the through hole.

Furthermore, the present invention provides a method of producing a flange member provided around a fluid passage opening in a housing of a hydraulic machine. The method comprises the steps of preparing a plate-like member having opposing surfaces including first and second surfaces, forming a through hole in the plate-like member which extends between the first and second surfaces and is adapted to be fluidly communicated with the fluid passage opening, and subjecting the plate-like to a press operation to form an O-ring receiving groove in the first surface in such a manner that the O-ring receiving groove surrounds the through hole.

The present invention also provides a method of producing a hydraulic machine. The method comprises the steps of producing a housing of the machine provided with a fluid passage opening, and producing a flange separately from the housing adapted to be provided around the fluid

passage opening. The step of producing the flange comprises preparing a plate-like member having opposing surfaces including first and second surfaces, forming a through hole in the plate-like member which extends between the first and second surfaces and is adapted to be fluidly communicated with the fluid passage opening, and subjecting the plate-like member to a press operation to form an O-ring receiving groove in the first surface in such a manner that the O-ring receiving groove surrounds the through hole.

According to the present invention, a fluid passage opening flange of a hydraulic machine is prepared separately from a housing of the hydraulic machine, whereby it becomes easy to produce the flange. Further, since an O-ring receiving groove is formed in an outside surface thereof on which an opening flange of an outside conduit means is engaged, it is possible to achieve reliable sealing of a connection between the flange and a conduit means connected thereto by placing an O-ring in the O-ring receiving groove.

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a cross sectional view of a hydraulic machine provided with a flange member according to the present invention;

Fig. 2 is a plan view of the hydraulic machine,

Fig. 3 is a cross sectional view taken along a line A-A in Fig. 2,

Fig. 4 is an enlarge view of a portion enclosed in a dashed line circle in Fig. 3,

Fig. 5 is a cross sectional view of the flange

according to the first conventional art stated above, and

Fig. 6 is a cross sectional view of the flange
according to the second conventional art.

BEST MODE OF THE INVENTION

5 With reference to Figs. 1 - 4, the present invention
will be explained as follows.

A hydraulic machine in accordance with the present
invention or a pump 40 in the embodiment shown in Fig. 1
includes a motor part 46 and a pump part 48 with a partition
10 wall 42 positioned therebetween and includes a rotational
shaft 44 common to the motor and pump parts. A housing 50
of the pump 48 has a fluid inlet opening 52 and a fluid
outlet opening 54 and contains therein first and second
impellers 58 and 60 fixed to the rotational shaft 24, first
15 and second diffusers 62 and 64 corresponding to the first
and second impellers 58 and 60, respectively, and
intermediate housings 66 and 68 provided around the first
impeller and diffuser and the second impeller and diffuser,
respectively, to form first and second pumping chambers 66
20 and 68.

The inlet opening 52 and the outlet opening 54 are
provided with flange members 70 and 70 therearound,
respectively. The inlet opening 52 is defined by an annular
portion projecting outwardly or leftwardly in Fig. 1 from
25 the housing 50 and the flange member 70 is directly welded
to the tip end edge of the annular portion, while the outlet
opening is provided with a tubular member 74 and the flange
70 is welded to an outer end edge of the tubular member 74.

The flange member 70 is an annular member defining an opening or through hole 74 and has an inside surface 76 on a side facing the housing 50 and an outside surface 78 on the opposite side which is formed with an O-ring receiving groove 80 encircling the opening 74.

The flange member 70 is formed of a plate-like member having opposing first and second surfaces. The opening 74 is formed by punching and the O-ring receiving groove 80 is formed by a half die cutting operation.

In the half die cutting operation, an annular projection 84 is formed on the inside surface 76 corresponding to the O-ring receiving groove 80. It is preferable to use a die in the half die cutting operation which forms a recess 88 in the inside surface 76 around or adjacent to the root of the annular projection 84. This is because the recess prevents the edges 8a of the O-ring receiving groove 80 from shifting towards the inside of the groove.

INDUSTRIAL APPLICATION OF THE INVENTION

The present invention as stated above is applicable to various kinds of hydraulic machines having fluid passage openings to be connected to outside conduit means, enabling openings to be formed at a low cost and to have a high sealing capacity.



CLAIMS

1. A hydraulic machine including a housing provided with a fluid passage opening, in which:

said hydraulic machine comprises a flange member formed separately from said housing and provided around said fluid passage opening, and

said flange member is an annular member having an inside surface facing said housing, an outside surface opposite said inside surface and a through hole extending from said inside surface to said outside surface and fluidly communicated with said fluid passage opening, said outside surface being formed with a press formed O-ring receiving groove therein surrounding said through hole.

2. A hydraulic machine according to Claim 1, in which said O-ring receiving groove is formed by a half die cutting press operation.

3. A hydraulic machine according to Claim 2, in which said flange member includes an annular projection formed on said inside surface positionally corresponding to said O-ring receiving groove and a recess formed in said inside surface around a root of said annular projection.

4. An annular flange member adapted to be provided around a fluid passage opening of a housing of a hydraulic machine to connect a fluid conduit means to said fluid passage opening, said annular flange member comprising:

an inside surface facing said housing,

an outside surface opposite said inside surface, and

a through hole extending from said inside surface to



said outside surface and fluidly communicated with said fluid passage opening,

said outside surface being provided with a press formed O-ring receiving groove surrounding said through hole.

5. A flange member according to Claim 4, in which said O-ring receiving groove is formed by a half die cutting press operation.

6. A flange member according to Claim 5, in which said flange member includes an annular projection formed on said inside surface positionally corresponding to said O-ring receiving groove and a recess formed in said inside surface around a root of said annular projection.

7. A method of producing a flange member provided around a fluid passage opening in a housing of a hydraulic machine, preparing a plate-like member having opposing surfaces including first and second surfaces,

forming a through hole in said plate-like member which extends between said first and second surfaces and is adapted to be fluidly communicated with said fluid passage opening, and

subjecting said plate-like to a pressing operation to form an O-ring receiving groove in said first surface in such a manner that the O-ring receiving groove surrounds said through hole.

8. A method according to Claim 7, in which said annular member is subjected to half die cutting to form said O-ring receiving groove.

9. A method according to Claim 8, in which said first



surface is formed with a projection positionally corresponding to said O-ring receiving groove and a recess around a root of said projection.

10. A method of producing a hydraulic machine, comprising:

producing a housing of the machine provided with a fluid passage opening, and

producing a flange separately from said housing adapted to be provided around said fluid passage opening, the step of producing the flange comprising:

preparing a plate-like member having opposing surfaces including first and second surfaces,

forming a through hole in said plate-like member which extends between said first and second surfaces and is adapted to be fluidly communicated with said fluid passage opening, and

subjecting said plate-like to a pressing operation to form an O-ring receiving groove in said first surface in such a manner that the O-ring receiving groove surrounds said through hole.

11. A method according to Claim 10, in which said annular member is subjected to a half die cutting operation to form said O-ring receiving groove.

12. A method according to Claim 11, in which said first surface is formed with a projection corresponding to said O-ring receiving groove and a recess around a root of said projection.

ABSTRACT

An annular flange member is provided which is adapted to be provided around a fluid passage opening of a housing of a hydraulic machine to connect a fluid conduit means to
5 the fluid passage opening. The annular flange member comprises an inside surface facing the housing, an outside surface opposite the inside surface, and a through hole extending from the inside surface to the outside surface and fluidly communicated with the fluid passage opening. The
10 outside surface is provided with an O-ring receiving groove surrounding the through hole which is formed by a half die cutting press operation. A hydraulic machine is provided which includes a flange member as noted above.

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

