

METHOD AND SYSTEM FOR ANALYSING RESPIRATORY TRACT AIR FLOW

FIELD OF THE INVENTION

This invention relates to medical devices and methods and more specifically, to such devices and methods for analyzing respiratory tract function.

BACKGROUND OF THE INVENTION

- 5 Spirometry is a common test of respiratory function that involves measuring the total volume of air inhaled into the lungs over a respiratory cycle. A spirometry test is usually carried out by having a subject inhale air through a tube connected to an air flow meter that measures the flow rate of air inhaled into the respiration system during the inspiration phase of the respiratory cycle. At
10 the termination of the inspiration phase, the subject exhales through the tube and the flow rate of air exhaled during the expiration phase is measured. A curve is then generated showing the air flow as a function of time. The curve is analyzed to obtain one or more respiratory parameters of the subject that are used to assess intrathorax airways obstruction. For example, the so-called "*forced expiratory*
15 *volume in one second*" (FEV_1) is obtained in a test performed during a maximum effort force expiratory vital capacity maneuver started from total lung capacity. FEV_1 is a well characterized test of respiratory function and provides useful information in diseased and normal states. In chronic obstructive pulmonary disease, the level of FEV_1 is used to grade the severity of the obstruction.
- 20 It is known to attach a plurality of microphones to a subject's chest or back in order to record respiratory tract sounds at a plurality of locations on the body surface. U.S. Patent Application No 10/338,742 published on January 9,

- 2 -

2003, and having the Publication Number US 2003-0139679 discloses a method for analyzing respiratory tract sounds detected by a plurality of microphones affixed to a subject's back or chest. The recorded sound signals are processed to determine an average acoustical energy $\tilde{P}(x, t_1, t_2)$ at a plurality of locations x on
5 the body surface over a time interval from t_1 to t_2 .

SUMMARY OF THE INVENTION

The present invention is based on the finding that the average acoustic energy over a region of an individual's back or chest or during a time interval
10 from t_1 to t_2 , can be correlated with the air flow in the portion of the respiratory tract underlying the region during that time interval. Thus, in its first aspect the invention provides a method for calculating an air flow in at least a portion of an individual's respiratory tract. The portion of the respiratory tract may be, for example, the left or right lung, or a single lobe within one of the lungs. In
15 accordance with this aspect of the invention, a plurality of microphones is fixed onto a subject's back or chest over the portion of the respiratory tract, and respiratory tract sounds are recorded from the region over a time interval from t_0 to t_1 . An average acoustical energy during the subinterval is determined at a plurality of locations x in the region. The total average acoustical energy,
20 summed over the locations x is then correlated with the airflow in the portion of the respiratory tract. Correlating the total acoustic energy with the airflow may be done, for example, using previously determined calibration curves. In a presently preferred embodiment, an airflow is calculated that is equal to the logarithm of the total acoustic energy. The process may then be repeated during the
25 expiratory phase of the respiratory cycle.

- 3 -

The airflow during each subinterval obtained by the method of the invention, may be displayed in the form of a graph of the airflow as a function of time over a respiratory cycle. The invention allows regional assessment of the respiratory tract performance.

- 5 The airflow in the lungs as a function of time during the inspiratory phase obtained in accordance with the invention may be integrated from a time t_0 to a time t to produce a total volume of air that has flowed into the airways from time t_0 to t . The airflow at a time t may be plotted as a function of the total volume of air that has flowed into the airways from t_0 to time t , to produce a spirometry
10 curve for inspiration. The process may then be repeated for the expiratory phase of the respiratory cycle.

Thus, in its first aspect, the invention provides a method for determining airflow in a portion of a respiratory tract comprising determining a total acoustic energy in a region of a body surface overlying the portion of the respiratory tract.

- 15 In its second aspect, the invention provides a system for determining airflow in a portion of a respiratory tract comprising a processor configured to determine a total acoustic energy in a region of a body surface overlying the portion of the respiratory tract.

BRIEF DESCRIPTION OF THE DRAWINGS

- 20 In order to understand the invention and to see how it may be carried out in practice, a preferred embodiment will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1 shows a system for analyzing respiratory tract airflow in accordance with one embodiment of the invention;

- 25 **Fig. 2** shows a flow chart diagram for carrying out the method of the invention in accordance with one embodiment of the invention; and

Fig. 3a shows a spirometry curve for both lungs of an individual, and **Fig. 3b** shows a spirometry curve for the right lung.

- 4 -

DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 shows a system generally indicated by **100** for analyzing respiratory tract airflow in a region of a respiratory system in accordance with one embodiment of the invention. A plurality of N sound transducers **105**, of which four are shown, are applied to a planar region of the chest or back skin of individual **110**. The transducers **105** may be applied to the subject by any means known in the art, for example using an adhesive, suction, or fastening straps. Each transducer **105** produces an analog voltage signal **115** indicative of pressure waves arriving to the transducer. The system **100** is used to obtain acoustic signals **115** over a time interval from t_0 to t_m . The analog signals **115** are digitized by a multichannel analog to digital converter **120**. The digital data signals $P(x_i, t)$ **125**, represent the pressure wave at the location x_i of the i th transducer ($i = 1$ to N) at time t . The data signals **125** are input to a memory **130**. Data input to the memory **130** are accessed by a processor **135** configured to process the data signals **125**. The signals **125** may be denoised by filtering components having frequencies outside of the range of respiratory sounds, for example, vibrations due to movement of the individual. Each signal **125** may also be subject to band pass filtering so that only components in the signal within a range of interest are analyzed.

An input device such as a computer keyboard **140** or mouse **145** is used to input relevant information relating to the examination such as personal details of the individual **110**. The input device **140** may also be used to input a subdivision of the time interval t_0 to t_m into subintervals $t_0, t_1, t_2, \dots, t_m$. Alternatively, the times $t_2, \dots, t_{m-1}$ may be determined automatically by the processor **135**. The processor **135** determines an average acoustic energy $\tilde{P}(x, t_i, t_{i+1})$ over each subinterval from t_i to t_{i+1} , $i=0$ to $m-1$ at a plurality of locations x in the region in a calculation involving at least one of the signals $P(x_i, t)$.

The average acoustic energies are stored in the memory **130** and may be displayed on a display device **150** such as a CRT screen for diagnosis by a physician.

- 5 -

The processor is also configured to integrate the functions $\tilde{P}(x, t_i, t_{i+1})$ with respect to x , i.e. to calculate $\sum_x \tilde{P}(x, t_i, t_{i+1})$, in order to obtain a total acoustic energy in the region of the respiratory tract during the interval from t_i to t_{i+1} . A previously obtained calibration curve is then used by the processor to determine

5 from the calculated acoustic energy, an air flow rate into (during inspiratory phase) or out of (during the expiratory phase) the region. A calibration curve is preferably used, previously obtained on a subject having similar characteristics (gender, height, weight and age), as the individual 110. The processor is also configured to integrate the functions $\sum_x \tilde{P}(x, t_i, t_{i+1})$ with respect to time, $\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1})$, in

10 order to obtain the total volume of air that has flowed in the airways from t_0 to t_k , for each k from 1 to m .

The processor is also configured to display on the display device a spirometry curve which is a plot of the flow rate $\sum_x \tilde{P}(x, t_i, t_{i+1})$, during the interval from t_i to t_{i+1} as a function of the volume $\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1})$ during the

15 same time interval.

The processor 135 may also perform an automatic differential diagnosis by comparing the spirometry curve to standard spirometry curves functions stored in the memory and known to be indicative of various disorders in the body region.

Fig. 2 shows a flow chart diagram for carrying out the method of the

20 invention in accordance with one embodiment. In step 200 the signals $P(x_i, t)$ are obtained from N transducers placed at predetermined locations x_i for i from 1 to N in a region R on an individual's chest or back. In step 205 the processor 135 determines an average acoustic energy $\tilde{P}(x, t_i, t_{i+1})$ over each subinterval from t_i to t_{i+1} , $i=0$ to $m-1$ at a plurality of locations x_i in the region R in a calculation

25 involving at least one of the signals $P(x_i, t)$.

- 6 -

In step 210, the processor integrates the functions $\tilde{P}(x, t_i, t_{i+1})$ with respect to x , $\sum_x \tilde{P}(x, t_i, t_{i+1})$ in order to obtain acoustic energy in the airways during the interval from t_i to t_{i+1} . In step 212 the processor obtains a flow rate of air in the region R of the airways from a calibration curve. In step 215, the processor

5 integrates the functions $\sum_x \tilde{P}(x, t_i, t_{i+1})$ or the air flow rates with respect to time,

$\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1})$, in order to obtain the total volume of air that has flowed into or out of the region R from t_0 to t_k , for each k from 1 to m . In step 220, the processor displays on the display device a spirometry curve which is a plot of the air flow rate

$(\sum_x \tilde{P}(x, t_i, t_{i+1}))$ as a function of the air volume $(\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1}))$.

10 It will also be understood that the system according to the invention may be a suitably programmed computer. Likewise, the invention contemplates a computer program being readable by a computer for executing the method of the invention. The invention further contemplates a machine-readable memory tangibly embodying a program of instructions executable by the machine for executing the

15 method of the invention.

Examples

A plurality of 20 sound transducers were applied to an individual's back over each lung. Each transducer produced an analog voltage signal indicative of

20 pressure waves arriving to the transducer over a respiratory cycle. The analog signals were digitized by a multichannel analog to digital converter. The digital data signals $P(x_i, t)$, represent the pressure wave at the location x_i of the i th transducer at time t . The data signals were denoised by filtering components having frequencies outside of the range of respiratory sounds.

25 The respiratory cycle was divided into 0.1 sec subintervals and the subintervals were classified as belonging to either the inspiratory or the expiratory

- 7 -

phase of the respiratory cycle. An average acoustic energy was calculated $\tilde{P}(x, t_i, t_{i+1})$ over each subinterval $[t_i, t_{i+1}]$ at a plurality of locations x over each lung from the signals $P(x_i, t)$.

For each lung, the functions $\tilde{P}(x, t_i, t_{i+1})$ were integrated with respect to x

5 $\sum_x \tilde{P}(x, t_i, t_{i+1})$ in order to obtain a total airflow in the lung during the interval from t_i to t_{i+1} . The integrals $\sum_x \tilde{P}(x, t_i, t_{i+1})$ were then integrated with respect to

(time, $\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1})$, in order to obtain a function that can be correlated with the total volume of air that has flowed into or out of each lung during the inspiratory and the expiratory phase, respectively, from the onset of the phase to a

10 variable time t_k . The logarithm of these integrals were calculated and plotted as a function of time during the respiratory cycle in order to obtain a spirometry curve. The results are shown in Fig. 3. Fig. 3a shows a spirometry curve for both lungs. The portion of the curve corresponding to the expiratory phase of the respiratory cycle is plotted above the horizontal axis. The portion of the curve corresponding to

15 the inspiratory phase of the respiratory cycle is plotted below the horizontal axis. The volume values in the vertical axis may be correlated by using spirometry data of the individual obtained from a mechanical spirometer. Fig. 3b shows a spirometry curve for the right lung. The volume values in the vertical axis may be correlated by using spirometry data of the individual obtained from a mechanical

20 spirometer on both lungs.

CLAIMS:

1. A method for determining airflow in a portion of a respiratory tract comprising determining a total acoustic energy in a region of a body surface overlying the portion of the respiratory tract wherein the total acoustic energy is determined in a process comprising:

(a) obtaining signals $P(x_i, t)$ from N transducers placed at predetermined locations x_i for i from 1 to N in the region of the body surface;

(b) determining an average acoustic energy $\tilde{P}(x, t_i, t_{i+1})$ over one or more time intervals t_i to t_{i+1} , at a plurality of locations x in the region in a calculation involving at least one of the signals $P(x_i, t)$ and

(c) integrating the functions $\tilde{P}(x, t_i, t_{i+1})$ with respect to x , $\sum_x \tilde{P}(x, t_i, t_{i+1})$ in order to obtain an airflow in the region during each of the time intervals.

2. The method according to Claim 1 further comprising integrating the functions $\sum_x \tilde{P}(x, t_i, t_{i+1})$ with respect to time, $\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1})$ in order to obtain a total volume of air that has flowed in the region from t_0 to t_k , for each k from 1 to m .

3. The method according to Claim 2 further comprising displaying on a display device a plot of the flow rate $\sum_x \tilde{P}(x, t_i, t_{i+1})$ as a function of the volume

$$\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1}).$$

4. The method according to Claim 1, wherein the region is a single lung or a lobe of a lung.

5. The method according to Claim 1 further comprising calculating a logarithm of an acoustical energy.

6. A system for determining airflow in a portion of a respiratory tract comprising a processor configured to determine a total acoustic energy in a region of a body surface overlying the portion of the respiratory tract wherein the total acoustic energy is determined in a process comprising:

- (a) obtaining signals $P(x_i, t)$ from N transducers placed at predetermined locations x_i for i from 1 to N in the region of the body surface;
- (b) determining an average acoustic energy $\tilde{P}(x, t_i, t_{i+1})$ over one or more time intervals t_i to t_{i+1} , at a plurality of locations x in the region in a calculation involving at least one of the signals $P(x_i, t)$ and
- (c) integrating the functions $\tilde{P}(x, t_i, t_{i+1})$ with respect to x , $\sum_x \tilde{P}(x, t_i, t_{i+1})$ in order to obtain an airflow in the region during each of the time intervals.

7. The system according to Claim 6 wherein the processor is further configured to integrate the functions $\sum_x \tilde{P}(x, t_i, t_{i+1})$ with respect to time, $\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1})$ in order to obtain a total volume of air that has flowed in the region from t_0 to t_k , for each k from 1 to m .

8. The system according to Claim 7 further comprising display device and wherein the processor is further configured to displaying on the display device a plot of the flow rate $\sum_x \tilde{P}(x, t_i, t_{i+1})$ as a function of the volume $\sum_{t_0}^{t_k} \sum_x \tilde{P}(x, t_i, t_{i+1})$.

9. The system according to Claim 6 wherein the processor is further configured to calculate a logarithm of an acoustical energy.