

LOCK ASSEMBLY FOR HYDRAULIC FRACING VALVE

BACKGROUND

1. Field of Invention

[0001] The invention relates generally to production of oil and gas. More specifically, the invention relates to a locking assembly for use with a valve of a hydraulic fracing system.

2. Description of Prior Art

[0002] Hydrocarbon producing wellbores are sometimes stimulated to increase the production of hydrocarbons. Hydraulic fracturing, or fracing, is one example of stimulation, which involves pressurizing all or a portion of the wellbore to improve communication between the surrounding formation and the wellbore. Generally, a fracing fluid is pressurized at surface by a pump, which then enters a line having an end downhole. As the fluid exits the line it builds pressure in the wellbore that in turn produces, or further propagates, fractures in the formation. Subterranean fractures occur when the pressure exerted by the pumped fluid exceeds the fracture gradient of the formation strata. Typically, the fluid used for fracing includes one or more of water, acids, bauxite, carbon dioxide, nitrogen, and additives.

[0003] The high pressures formed during fracing, along with the impulses that occur when fractures are formed, create vibrations in the piping system that carries the fracing fluid. Vibrations of sufficient magnitude, and/or duration, can cause valves in the piping system to either inadvertently open or close.

SUMMARY OF THE INVENTION

[0004] An example of a hydraulic fracturing system is described herein that includes a pump, a discharge line attached to the pump that can be put in a wellbore. Also included is a valve assembly in the line; the valve assembly includes a body, a passage, a gate, and a bore in the gate that selectively registers with the passage. The system also includes a valve lock assembly that is made up of a cam disk, a balance stem connecting the cam disk and the gate and a retention element that is urged into a path of the cam disk by a resilient member. When a force is applied to the gate to urge the cam disk against the retention element that is less than a designated amount, the retention element is retained in the path of the cam disk by the resilient member. Optionally, when a force is applied to the gate to urge the cam disk against the retention element that exceeds the designated amount, a force is exerted by the cam disk onto the retention element to overcome a force applied by the resilient member and the retention element is moved out of the path of the cam disk. In one example, the cam disk includes a beveled outer edge that contacts the retention element. In an example embodiment, a thrust force is defined by the force applied to the gate to urge the cam disk against the retention element, and wherein upper and lower portions of the outer edge are beveled at angles with respect to an axis of the cam disk so that the thrust force necessary to urge the cam disk past the retention element is greater in one axial direction than in an opposite axial direction. The retention element can be made up of a ball bearing and the resilient member may be made of a spring. In one example, the system includes a plurality of ball bearings and springs and a housing that circumscribes the balance stem having bores radially formed through a sidewall of the housing for retaining the ball bearings and springs. A valve actuator may be coupled to the gate.

[0005] Also disclosed herein is a balancing system for use with a hydraulic fracturing valve. In one example the balancing system includes a generally planar cam member in selective coupling engagement with a valve gate. The cam member is subject to a thrust force from the valve gate in response to a force applied to the valve gate. A latching assembly is included that is made up of a latching element that is maintained in interfering contact with the cam member by a resilient member. The interfering contact takes place when the thrust force produces a resultant force against the latching element that is less than a designated amount. In one example, the latching element is urged out of interfering contact and out of a path of the cam member when the thrust force produces a resultant force against the latching element that exceeds the designated amount. The cam member can have an outer periphery with an upper section profiled at an angle with respect to an upper surface of the cam member and a lower section profiled at an angle with respect to a lower surface of the cam member. In an example embodiment, the upper and lower surfaces are substantially parallel, and wherein the upper and lower sections are profiled at different angles, so that an amount of the thrust force that produces a resultant force against the latching element that exceeds the designated amount is greater when the cam member is axially urged in one direction than when the cam member is axially urged in an opposite direction. The gate may be subjected to forces from vibrations that produce resultant forces that are less than the designated amount.

[0006] A valve assembly is provided herein that can be used in a hydraulic fracturing system. In one example embodiment the valve assembly includes a valve body having a passage, a gate having a bore that is in selective registration with the passage, an actuator coupled with the gate, and a means for retaining the gate in a designated position within the valve body. The gate can be unlocked from the designated position by applying a force that exceeds a force used to lock

the gate. Optionally, the means for retaining the gate are a cam disk coupled to the gate and a latch that retains the cam disk in place when the lock force is applied to the gate and releases the gate when an unlock force is applied to the gate.

BRIEF DESCRIPTION OF DRAWINGS

[0007] Some of the features and benefits of the present invention having been stated, others will become apparent as the description proceeds when taken in conjunction with the accompanying drawings, in which:

[0008] FIG. 1 is a side partial sectional view of an example embodiment of a hydraulic fracturing system in accordance with the present invention.

[0009] FIG. 2 is a side sectional view of a detailed portion of a balance stem of the embodiment of FIG. 1 shown in a locking configuration.

[0010] FIG. 3 is a side sectional view of a detailed portion of a balance stem of the embodiment of FIG. 1 shown in an unlocking configuration.

[0011] While the invention will be described in connection with the preferred embodiments, it will be understood that it is not intended to limit the invention to that embodiment. On the contrary, it is intended to cover all alternatives, modifications, and equivalents, as may be included within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION OF INVENTION

[0012] The method and system of the present disclosure will now be described more fully hereinafter with reference to the accompanying drawings in which embodiments are shown. The method and system of the present disclosure may be in many different forms and should not be construed as limited to the illustrated embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey its scope to those skilled in the art. Like numbers refer to like elements throughout.

[0013] It is to be further understood that the scope of the present disclosure is not limited to the exact details of construction, operation, exact materials, or embodiments shown and described, as modifications and equivalents will be apparent to one skilled in the art. In the drawings and specification, there have been disclosed illustrative embodiments and, although specific terms are employed, they are used in a generic and descriptive sense only and not for the purpose of limitation. Accordingly, the improvements herein described are therefore to be limited only by the scope of the appended claims.

[0014] Figure 1 is a partial side sectional view of an example embodiment of a hydraulic fracturing system 10 used in creating fractures 12 within a subterranean formation 14 by pressurizing a space within the wellbore 16. The system 10 includes a pump 18 that pressurizes a fracturing fluid and a line 20 connected to a discharge of the pump 18. The line 20 is shown fed through an optional wellhead assembly 22 and has an exit disposed in the wellbore 16. Optionally, a packer 24 may be provided in an annular space between the line 20 and inner walls of the wellbore 16 to isolate a zone of the wellbore 16 for the step of fracturing. In the example

of Figure 1, the wellbore 16 is lined with a string of casing 26 that is cemented in place in the formation with cement 28.

[0015] A valve assembly 30 is shown in the line 20 downstream of the pump 18 and upstream of the wellhead assembly 22. The valve assembly 30 of Figure 1 includes a valve body 32 and a passage 34 that laterally extends through the body 32 and is in fluid communication with the line 20. A gate 36 is shown axially inserted within the valve body 32, wherein the gate 36 includes a bore 38 that selectively registers with the passage 34 for regulating the flow of fluid through the valve assembly 30. A valve actuator 40 is shown coupled with the gate 36 via a valve stem 42. Due to the high pressures and flow rates associated with the hydraulic fracturing process, substantial vibrations may be imparted onto the valve gate 36 that may move the gate 36 out of a designated position within the valve body 32. To retain the valve gate 36 in the desired position, a valve lock assembly 44 is shown coupled to an end of the gate 36 by a balance stem 46.

[0016] Referring now to Figure 2, one example embodiment of the valve lock assembly 44 is shown in detail in a side sectional view. In this example, the valve lock assembly 44 is shown further including a generally planar-shaped cam disk 48 that mounts on a lower terminal end of the balance stem 46. In the example of Figure 2, a threaded fastener 50 bolts the cam disk 48 in place on the stem 46. Further illustrated in Figure 2 is a housing 52, that in one example is a substantially annular member having a cylindrical outer circumference. The cam disk 48 is shown having upper and lower surfaces 54, 56 that in the example of Figure 2 are largely parallel with one another and transverse to an axis A_X of the balance stem 46. The cam disk 48 also has an outer periphery 58 profiled to have an upper portion 60; as shown the upper portion 60 is coincident with a plane P_U that intersects the axis A_X above the cam disk 48 at an oblique angle. Similarly, a lower portion 62 is formed on the outer periphery 58 below the upper portion 60 that

lies in a plane P_L that intersects the axis A_X at an oblique angle but below the cam disk 48. In the example of Figure 2, the angle at which plane P_U intersects the axis A_X is different from the angle that P_L intersects the axis A_X .

[0017] Further shown in Figure 2 are retention assemblies 64 that are provided within bores 66 formed through a side wall of the housing 52. The bores 66 are shown having a radially inwardly directed taper 68 proximate to an inner wall of the housing 52. Ball bearings 70 are inserted within the bores 66 and have a diameter less than the diameter of the bore 66 but greater than that of the taper 68 so that a portion of the ball bearing 70 projects through the bore 66 to inside of the housing 52, but prevented from fully entering into the housing 52. A spring 72 is biases the ball bearing 70 against the taper 68 and is held in place against by bolts 74 that threadingly insert into the bores 66 from the outer surface of the housing 52. The inward biasing of the springs 72 positions a portion of the ball bearings 70 into interfering contact with an axial path of the cam disk 48. More specifically, in the example of Figure 2, a force diagram is shown that is based on an angle α of the lower portion 62. In this example, a force F_α in the force diagram depicts an amount of force required to urge the ball bearings 70 radially outward against the springs 72 so that the cam disk 48 may move axially downward past its current location.

[0018] Similarly, in Figure 3, cam disk 48 is illustrated below the ball bearings 70 so that its upper portion 60 is engaging the bearings 70 and a force diagram is provided that illustrates a force necessary to push the ball bearings 70 radially outward and allow the cam disk 40 to move upward within the housing 52. In the example of Figure 3, the angle β of the upper portion 60 as shown relative to the axis A_X of the balance stem 46. As the angle α is greater than the angle β , the thrust force F_β required for upward movement of the cam disk 48 as shown in Figure 3 exceeds the force F_α for downward movement of the cam disk past the ball bearings 70. Thus,

in one example of use, the valve gate 36 may be urged into its desired location and the cam disk 48 and retention assemblies 64 strategically located so that the cam disk 48 is in the configuration of Figure 3, thereby requiring a greater force to “unlock” the valve then would be required for moving the valve into a locking position, *i.e.*, in the configuration of Figure 2 into the configuration of Figure 3.

[0019] The present invention described herein, therefore, is well adapted to carry out the objects and attain the ends and advantages mentioned, as well as others inherent therein. While a presently preferred embodiment of the invention has been given for purposes of disclosure, numerous changes exist in the details of procedures for accomplishing the desired results. These and other similar modifications will readily suggest themselves to those skilled in the art, and are intended to be encompassed within the spirit of the present invention disclosed herein and the scope of the appended claims.

PARTS LIST

10	hydraulic fracturing system
12	fractures
14	formation
15	
16	wellbore
18	pump
20	line
22	wellhead assembly
24	packer
26	casing
28	cement
30	valve assembly
32	valve body
34	passage
36	gate
38	opening
40	actuator
42	valve stem
44	valve lock assembly
46	balance stem
48	cam disk
50	bolt
52	housing
54	upper surface

56	lower surface
58	radial surface
60	upper portion
62	lower portion
64	retention assembly
66	bore
68	taper
70	ball
72	spring
74	bolt

CLAIMS

What is claimed is.

1. A valve assembly 30 for use in a subterranean hydraulic fracturing system 10 comprising:

a body 32 having a passage 34;

a gate 36 disposable in the body 32;

a bore 38 in the gate 36 that selectively registers with the passage 34;

characterized by,

a valve lock assembly 44 comprising:

a valve lock assembly 44;

a balance stem 46 connected between the valve lock assembly 44 and the gate 36;

a retention element 70 urged into a path of the valve lock assembly 44 by a resilient member 72, so that when a force is applied to the gate 36 to urge the valve lock assembly 44 against the retention element 70 that is less than a designated amount, the retention element 70 is retained in the path of the valve lock assembly 44 by the resilient member 72.
2. The valve assembly 30 system of claim 1, characterized in that when a force is applied to the gate 36 to urge the valve lock assembly 44 against the retention element 70 that exceeds the designated amount, a force is exerted by the valve lock assembly 44 onto the retention element

70 to overcome a force applied by the resilient member 72 and the retention element 70 is moved out of the path of the valve lock assembly 44.

3. The valve assembly 30 of claims 1 or 2, characterized in that the valve lock assembly 44 comprises a beveled outer edge that contacts the retention element 70.

4. The valve assembly 30 of claim 3, characterized in that the force applied to the gate 36 to urge the valve lock assembly 44 against the retention element 70 defines a thrust force, and wherein upper and lower portions of the outer edge are beveled at angles with respect to an axis of the valve lock assembly 44 so that the thrust force necessary to urge the valve lock assembly 44 past the retention element 70 is greater in one axial direction than in an opposite axial direction.

5. The valve assembly 30 of any of claims 1 -4, characterized in that the retention element 70 comprises a ball bearing and the resilient member 72 comprises a spring.

6. The valve assembly 30 of claim 5, further characterized by a plurality of ball bearings and springs, a housing 52 that circumscribes the balance stem 46 having bores radially formed through a sidewall of the housing 52 for retaining the ball bearings and springs.

7. The valve assembly 30 of any of claims 1-6, further characterized by a valve actuator 40 coupled to the gate 36.

8. A balancing system 44 for use with a hydraulic fracturing valve 30 comprising:

a generally planar cam member 48 in selective coupling engagement with a valve gate 36 and subject to a thrust force from the valve gate 36 in response to a force applied to the valve gate 36; and

characterized by,

a latching assembly 64 comprising a latching element 70 that is maintained in interfering contact with the cam member 48 by a resilient member 72 when the thrust force produces a resultant force against the latching element 70 that is less than a designated amount.

9. The balancing system of claim 8, characterized in that the latching element 70 is urged out of interfering contact and out of a path of the cam member 48 when the thrust force produces a resultant force against the latching element 70 that exceeds the designated amount.

10. The balancing system of claims 8 or 9, characterized in that the cam member 48 comprises an outer periphery having an upper section 60 profiled at an angle with respect to an upper surface 54 of the cam member 48 and a lower section 62 profiled at an angle with respect to a lower surface 56 of the cam member 48.

11. The balancing system of claim 10, characterized in that the upper and lower surfaces 54, 56 are substantially parallel, and wherein the upper and lower sections 60, 62 are profiled at different angles, so that an amount of the thrust force that produces a resultant force against the latching element 70 that exceeds the designated amount is greater when the cam member 48 is axially urged in one direction than when the cam member 48 is axially urged in an opposite direction.

12. The balancing system of claim 10, characterized in that the gate 36 is subjected to forces from vibrations that produce resultant forces that are less than the designated amount.

13. A valve assembly 30 for use in a hydraulic fracturing system 10 comprising:

a valve body 32 having a passage 34;

a gate 36 having a bore 38 that is in selective registration with the passage 34;

an actuator 40 coupled with the gate 36; and

characterized by,

a means for retaining the gate 36 in a designated position within the valve body 32 that is unlockable from the designated position with a force applied to the gate 36 that is greater than a force applied to lock the gate 36.

14. The valve assembly 30 of claim 13, characterized in that the means for retaining the gate 36 comprises a valve lock assembly 44 coupled to the gate 36 and a latch that retains the valve lock assembly 44 in place when the lock force is applied to the gate 36 and releases the gate 36 when an unlock force is applied to the gate 36.